

rItoSReverse

Write a **recursive** C function that takes a positive integer number (e.g. 1, 2, 3, etc.), and converts it into a sequence of characters in reverse order. That is, the function takes a positive integer number `num` and returns a string of the corresponding characters in reverse order via `numStr`. For example, if `num` is 12345, then the string `numStr` is "54321". You may assume that the last digit of the number `num` will **not** be 0 (i.e. 10, 1110, etc.). The function prototype is given as follows:

```
void rItoSReverse(int num, char *numStr);
```

A sample program template is given below to test the function:

```
#include <stdio.h>
void rItoSReverse(int num, char *numStr);
int main()
{
    int num;
    char numStr[20];

    printf("Enter a positive integer number (greater than 0): \n");
    scanf("%d", &num);
    rItoSReverse(num, numStr);
    printf("rItoSReverse(): %s\n", numStr);
    return 0;
}
void rItoSReverse(int num, char *numStr)
{
    /* Write your code here */
}
```

Some sample input and output sessions are given below:

(1) Test Case 1

Enter a positive integer number (greater than 0):

7

rItoSReverse(): 7

(2) Test Case 2

Enter a positive integer number (greater than 0):

12345

rItoSReverse(): 54321

(3) Test Case 3

Enter a positive integer number (greater than 0):

10102

rItoSReverse(): 20101