

theorem

Vera: Weakest Preconditions for TICL over Rust

From Imp Structural Lemmas to Rust VCGen Rules

Lef Ioannidis

2026

Background: TICL over Imp

TICL Structural Lemmas for Imp

Core idea (from the TICL paper)

For a small imperative language `StImp` with mutable state, the entailment $[t, m \Vdash_L \varphi]_S$ is proved structurally via inference rules on the syntax of t .

Key rules from `imp-lemmas.tex`:

- **Seq**_SAU_L: sequential composition decomposes into bind
- **If**_SAU_L: conditional branches both satisfy the obligation
- **While**_SAG: infinite loop with coinductive invariant $\mathcal{R}$
- **While**_SAU_L: terminating loop with ranking function f

Goal: Lift these to Rust syntax $\rightarrow$ define `wp` for Vera.

Notation

$\sigma \in \text{State}$ (mutable references, heap)

$[t, \sigma \Vdash_L \varphi] \triangleq$ “Rust term t from state σ satisfies φ ”

$\text{wp}(t, \varphi) \triangleq$ weakest precondition on σ s.t. $[t, \sigma \Vdash_L \varphi]$

Temporal formulas

- $\varphi ::= \text{now } P \mid \text{AG } \varphi \mid \varphi \text{ AU } \varphi' \mid \varphi \wedge \varphi'$
- Sugar: $\text{AF } \varphi' = \top \text{ AU } \varphi'$, $\text{AX } \varphi' = \top \text{ AN } \varphi'$
- $\text{done } Q$: termination postcondition; $\text{now } P$: intermediate state predicate

Inference Rules (Single-Process)

Assignment

Rust: `*x = e`

$$\frac{\begin{array}{l} [e, \sigma \Vdash_R \varphi \text{ AU done } \mathcal{R}] \\ \forall v, \sigma', \mathcal{R} \ v \ \sigma' \rightarrow [\text{skip}, \sigma'[x \mapsto v] \Vdash_L \varphi \text{ AU } \varphi'] \end{array}}{[*x = e, \sigma \Vdash_L \varphi \text{ AU } \varphi']} \text{ASSIGNAU}_L$$

Evaluating e may take steps; φ must hold along the path.

Sequential Composition (let-binding)

Rust: `let x = t; u`

$$\frac{[t, \sigma \Vdash_R \varphi \text{ AU done } \mathcal{R}] \quad \forall x, \sigma', \mathcal{R} \ x \ \sigma' \rightarrow [u[x], \sigma' \Vdash_L \varphi \text{ AU } \varphi']}{[\text{let } x = t; u, \sigma \Vdash_L \varphi \text{ AU } \varphi']} \text{LETAU}_L$$

Direct lift of **BindAU**_L / **SeqS**AU_L from TACL.

Rust: `if c {t} else {u}`

$$\frac{\begin{array}{l} [c, \sigma \Vdash_R \varphi \text{ AU done} = (b, \sigma')] \\ \left\{ \begin{array}{ll} [t, \sigma' \Vdash_L \varphi \text{ AU } \varphi'], & \text{if } b \\ [u, \sigma' \Vdash_L \varphi \text{ AU } \varphi'], & \text{otherwise} \end{array} \right. \end{array}}{[\text{if } c \{t\} \text{ else } \{u\}, \sigma \Vdash_L \varphi \text{ AU } \varphi']} \text{IFAU}_L$$

Evaluating c may take multiple steps; φ must hold along the path.

While Loop (AU – terminating)

Rust: `while c {t}` **with** invariant $\mathcal{R}$, decreases f

$$\frac{\begin{array}{c} \mathcal{R} \sigma \\ \forall \sigma, \mathcal{R} \sigma \rightarrow [c, \sigma \Vdash_R \varphi \text{ AU done} = (b, \sigma')] \\ \wedge \left\{ \begin{array}{l} [t, \sigma' \Vdash_L \varphi \text{ AU } \varphi'] \vee \\ [t, \sigma' \Vdash_R \varphi \text{ AU done } (\lambda \sigma''. \mathcal{R} \sigma'' \wedge f \sigma'' < f \sigma)], \text{ if } b \\ \varphi'(\sigma'), \end{array} \right. \end{array} \quad \text{otherwise}}{[\text{while } c \{t\}, \sigma \Vdash_L \varphi \text{ AU } \varphi']} \text{WHILEAU}_L$$

While Loop (AG – infinite)

Rust: `while c {t}` **with** invariant $\mathcal{R}$ (**no** decreases)

$$\frac{\begin{array}{c} \mathcal{R} \sigma \\ \forall \sigma, \mathcal{R} \sigma \rightarrow \\ [\text{while } c \{t\}, \sigma \Vdash_L \varphi] \wedge \\ [c, \sigma \Vdash_R \varphi \text{ AU done} = (\text{true}, \sigma)] \wedge \\ [t, \sigma \Vdash_R \varphi \text{ AU done} (\lambda \sigma' \Rightarrow \mathcal{R} \sigma')] \end{array}}{[\text{while } c \{t\}, \sigma \Vdash_L \text{AG } \varphi]} \text{WHILEAG}$$

Coinductive hypothesis $[\text{while } c \{t\}, \sigma \Vdash_L \varphi]$; condition must always be true.

Function Call (Bind Rule)

Rust: `let x = f( $\vec{e}$ ); k x`

$$\frac{\begin{array}{c} [f(\vec{e}), \sigma \Vdash_R \varphi \text{ AU done } \mathcal{R}] \\ \forall x, \sigma', \mathcal{R} \ x \ \sigma' \rightarrow [k \ x, \sigma' \Vdash_L \varphi \text{ AU } \varphi'] \end{array}}{[\text{let } x = f(\vec{e}); k \ x, \sigma \Vdash_L \varphi \text{ AU } \varphi']} \text{CALLAU}_L$$

Instance of Let rule. Call is a sub-expression that produces a value.

Single-Process Weakest Preconditions

$$\begin{aligned} \text{wp}(*x = e, \varphi \text{ AU } \varphi') &= \lambda \sigma. \text{wp}(e, \varphi \text{ AU done } \mathcal{R}) \sigma \\ &\quad \wedge \forall v, \sigma'. \mathcal{R} v \sigma' \rightarrow \varphi'(\sigma'[x \mapsto v]) \end{aligned}$$

wp: Let-binding (Sequential Composition)

$$\begin{aligned} \text{wp}(\text{let } x = t; u, \varphi \text{ AU } \varphi') &= \lambda \sigma. \text{wp}(t, \varphi \text{ AU done } \mathcal{R}) \sigma \\ &\quad \wedge \forall x, \sigma'. \mathcal{R} \ x \ \sigma' \rightarrow \text{wp}(u[x], \varphi \text{ AU } \varphi') \sigma' \end{aligned}$$

$$\begin{aligned} \text{wp}(\text{if } c \{t\} \text{ else } \{u\}, \varphi \text{ AU } \varphi') &= \lambda \sigma. \\ \text{wp}(c, \varphi \text{ AU done } \mathcal{R}) \sigma &\wedge \forall b, \sigma'. \mathcal{R} b \sigma' \rightarrow \\ &\begin{cases} \text{wp}(t, \varphi \text{ AU } \varphi') \sigma', & \text{if } b \\ \text{wp}(u, \varphi \text{ AU } \varphi') \sigma', & \text{otherwise} \end{cases} \end{aligned}$$

wp: While Loop (AU)

$$\text{wp}(\text{while } c \{t\}, \varphi \text{ AU } \varphi') = \lambda \sigma.$$

$$\mathcal{R} \sigma \wedge \forall \sigma, \mathcal{R} \sigma \rightarrow$$

$$\text{wp}(c, \varphi \text{ AU done } \mathcal{R}') \sigma \wedge \forall b, \sigma'. \mathcal{R}' b \sigma' \rightarrow$$

$$\begin{cases} \text{wp}(t, \varphi \text{ AU } \varphi') \sigma' \vee \\ \text{wp}(t, \varphi \text{ AU done } (\lambda _ \sigma''. \mathcal{R} \sigma'' \wedge f \sigma'' < f \sigma)) \sigma', & \text{if } b \\ \varphi'(\sigma'), & \text{o.w.} \end{cases}$$

wp: While Loop (AG)

$$\text{wp}(\text{while } c \{t\}, \text{AG } \varphi) = \lambda \sigma.$$

$$\mathcal{R} \sigma \wedge \forall \sigma, \mathcal{R} \sigma \rightarrow$$

$$\text{wp}(\text{while } c \{t\}, \varphi) \sigma \wedge$$

$$\text{wp}(c, \varphi \text{ AU done} = (\text{true}, \sigma)) \sigma \wedge$$

$$\text{wp}(t, \varphi \text{ AU done } (\lambda \sigma'. \mathcal{R} \sigma')) \sigma$$

Coinductive: $\text{wp}(\text{while } c \{t\}, \varphi) \sigma$ is the coinductive hypothesis.

wp: Function Call – f ensures AF done $\mathcal{R}_f$

f has terminating postcondition

$$\text{wp}(f(e_1, \dots, e_i), \varphi \text{ AU } \varphi') = \lambda \sigma. \forall x, \sigma'. \mathcal{R}_f x \sigma' \rightarrow \text{wp}(k x, \varphi \text{ AU } \varphi') \sigma'$$

where k is the continuation after the call.

f has temporal ensures Ψ : transparent checking

Additionally assert $\Psi \implies \Phi$ where Φ is the caller's obligation.

f ensures AG ψ : cannot prove AF for it

If f has AG ψ (diverges), then $\text{wp}(f(\vec{e}), \text{AF } \varphi')$ is **unprovable** – a diverging call can never reach the AF goal.

Multi-Process Configuration

Configuration

A **configuration** $C = (P, \sigma, i)$:

$P : \text{PID} \rightarrow \text{Term}$

process dictionary

$\sigma \in \text{State}$

shared mutable state

$i \in \text{PID}$

active process

- Temporal formulas φ are over shared state σ
- $\text{WP}(C, \varphi)$ – multi-process wp, defined by cases on $P(i)$

Cooperative Scheduling

Rust `async` uses **cooperative scheduling**: each process runs uninterrupted until it reaches an `.await`, then yields control to the scheduler.

- **Within a process**: execution is sequential (single-process wp applies)
- **At `.await`**: the active process i suspends; the scheduler picks a ready process p to run (nondeterministic choice)
- **No preemption**: a process cannot be interrupted mid-statement; shared state σ is only modified by the active process

This means nondeterminism arises *only* at `.await` boundaries — between yield points, the program is deterministic and the single-process rules apply unchanged.

Multi-Process Weakest Preconditions

WP: Sequential Step

When $P(i)$ is a non-async construct (assignment, let, if, while, sync call):

$$\text{WP}((P, \sigma, i), \varphi) = \text{wp}(P(i), \varphi) \sigma$$

Delegate to single-process wp. Process dictionary P is unchanged.

Programs without `async/await` reduce entirely to single-process wp:

$$\text{WP}(\{0 \mapsto t\}, \sigma, 0), \varphi) = \text{wp}(t, \varphi) \sigma$$

WP: Async Bind (Lazy Future Creation)

Rust: $P(i) = \text{let } p = \text{async } f(\vec{e}); k \ p$

$$\text{WP}((P, \sigma, i), \Phi) = \text{WP}((P[i \mapsto k, p \mapsto f_{body}], \sigma, i), \Phi)$$

- Creates new process p with body f_{body} (suspended)
- Replaces active process i 's term with continuation k
- No state change, no scheduling – futures are lazy

WP: Await (AU – terminating callee)

Rust: $P(i) = \text{let } x = p.\text{await}; k\ x$

$$\begin{aligned} \text{WP}((P, \sigma, i), \varphi \text{ AU } \varphi') = \\ \text{WP}((P, \sigma, p), \varphi \text{ AU done } \mathcal{R}) \\ \wedge \forall x, \sigma'. \mathcal{R}\ x\ \sigma' \rightarrow \text{WP}((P[i \mapsto k[x]], \sigma', i), \varphi \text{ AU } \varphi') \end{aligned}$$

- Switch active process to p ; run it maintaining φ
- After p terminates with result x and state σ' , resume i

WP: Await (AG – diverging callee)

Rust: $P(i) = p.\text{await}$

$$\text{WP}((P, \sigma, i), \text{AG } \varphi) = \text{wp}(P(p), \text{AG } \varphi) \sigma$$

- Reduces to single-process wp on callee's body $P(p)$
- Process p must satisfy AG φ (runs forever)
- Continuation after await is unreachable

Vera Implementation

Vera extends Verus with temporal postconditions and loop annotations:

Annotation	TICL	Proof obligation
<code>ensures af(done(Q))</code>	$\text{AF done } Q$	Loop + decreases
<code>ensures ag(P)</code>	$\text{AG } \varphi$	Infinite loop + invariant
<code>ensures au(P, done(Q))</code>	$P \text{ AU done } Q$	Loop + invariant + decreases
<code>ensures ag(af(now(Q)))</code>	$\text{AG AF now } Q$	Ghost accumulator + decreases
<code>invariant R</code>	$\mathcal{R}$	Temporal refinement mapping
<code>decreases f</code>	f	Well-founded metric (progress)

`done(Q)`: Q holds at termination. `now(Q)`: Q holds at some intermediate state.

Example: Queue Drain (AF)

Liveness: the queue eventually becomes empty

```
fn drain(q: &mut Queue)
  requires old(q).view().len() > 0,
  ensures  af(done(q.view().len() == 0)),
{
  while q.len() > 0
    invariant q.view().len() >= 0,
    decreases q.view().len(),
    {
      let _ = q.dequeue();
    }
}
```

$\text{invariant} = \mathcal{R}, \quad \text{decreases} = f \quad \Rightarrow \quad \text{WhileAU}_L \text{ rule applies.}$

Example: Bounded Counter (AG)

Safety: the counter stays bounded forever

```
fn bounded_counter(x: &mut u64)
  requires *old(x) == 0,
  ensures  ag(*x <= 15),
{
  loop
    invariant *x <= 10,
  {
    if *x < 10 { *x = *x + 1; }
    else      { *x = 0; }
  }
}
```

No decreases $\Rightarrow$ infinite loop $\Rightarrow$ WhileAG rule.

$\text{invariant } (*x \leq 10) \implies \text{postcondition } (*x \leq 15).$

Example: Bind Rule (AG + AF callee)

AG caller invokes AF callee — bind rule extracts postcondition

```
fn reset_to_zero(x: &mut u64)
  ensures af(done(*x == 0)),
{ *x = 0; }
```

```
fn ag_caller(x: &mut u64)
  requires *old(x) == 0,
  ensures  ag(*x <= 10),
{
  loop
    invariant *x <= 10,
    {
      if *x < 10 { *x = *x + 1; }
      if *x > 5  { reset_to_zero(x); }
    }
}
```

Example: Round-Robin Fairness (AG(AF(now)))

Every element eventually reaches the head of the queue

```
fn round_robin(queue: &mut Queue, Ghost(x): Ghost<u64>)
  requires
    old(queue).view().len() > 1,
    old(queue).view().contains(x),
  ensures
    ag(queue.view().len() > 0),
    ag(af(now(queue.peek_spec() == x))),
{
  loop
    invariant
      queue.view().len() > 1,
      queue.view().contains(x),
    decreases
      queue.view().index_of_first(x),
  f
```

Summary

Complete Rule Set

Construct	Rule	Layer
$*x = e$	State update	wp
$\text{let } x = t; u$	BindAU _L	wp
$\text{if } c \{t\} \text{ else } \{u\}$	Case split (effectful c)	wp
$\text{while } c \{t\} + \text{dec.}$	WhileAU _L	wp
$\text{while } c \{t\} \text{ (no exit)}$	WhileAG	wp
$f(\vec{e})$	Contract-dependent	wp
Sequential step	Delegate to wp	WP
$\text{async } f(\vec{e})$	Extend P , no-op	WP
$p.\text{await}$ (AU callee)	Switch active to p	WP
$p.\text{await}$ (AG callee)	Divergence	WP

Two layers: $\text{wp}(t, \varphi)$ for sequential Rust, $\text{WP}((P, \sigma, i), \varphi)$ for async concurrency.