

Causal Proof of Reasoning: Structural Auditing of Latent Dependencies for Defending Federated Learning

Ayush Chadha, Ragav Palaniswamy, Sanjana Gummuluru

Guide: Dr. M. Sridevi

National Institute of Technology Tiruchirappalli

Abstract—Federated Learning (FL) enables collaborative model training across distributed, privacy-sensitive participants without centralising raw data. However, its decentralised trust model creates two severe vulnerability classes: *backdoor poisoning*, where malicious clients embed hidden triggers into the global model, and *Explanation Poisoning*, a sophisticated dual-objective attack in which an adversary simultaneously optimises for malicious inference and benign-looking post-hoc explanations—rendering LIME, SHAP, and gradient-based auditing tools dangerously misleading. Existing Byzantine-robust aggregators analyse weight-vector divergence and therefore fail against both attack classes, since poisoned models can preserve statistical similarity to honest updates while corrupting their underlying reasoning structure.

We propose Causal Proof of Reasoning (PoR), a structural auditing framework that shifts the defense layer from numerical weight analysis to topological inspection of latent feature dependencies. In PoR, each client applies the NOTEARS algorithm to extract a Directed Acyclic Graph (DAG) encoding its reasoning. A server-side SIMGNN Logic Validator compares each DAG against a global consensus, approximating Graph Edit Distance (GED) in $\mathcal{O}(1)$ time. An auxiliary Causal Effect Distance (CED) audits coefficient magnitudes to catch weight-only backdoors. Honest clients produce DAGs topologically close to the consensus; poisoned clients exhibit detectable structural deformation.

PoR is demonstrated within FEDNEAT, a heterogeneous neuroevolutionary framework, and validated in an Algorithmic Finance environment against a 3-adversary threat model (Temporal Mimicry, Topology Inversion, Gradient Mimicry). Extensive evaluation on Bayesian networks shows that PoR reduces Attack Success Rate from 60.30% to 0.40% on ALARM and from 5.62% to 0.52% on ASIA, with zero false positives.

Index Terms—Federated learning, backdoor defense, explanation poisoning, causal discovery, graph neural networks, Byzantine robustness, structural auditing, NOTEARS, neuroevolution, differential privacy.

I. INTRODUCTION

FEDERATED Learning (FL) [1] has emerged as a foundational paradigm for training machine learning models across distributed, data-heterogeneous participants without centralising raw data. By aggregating only model updates rather than datasets, FL offers strong privacy guarantees and enables collaboration across healthcare, finance, and autonomous systems—domains where data governance prohibits centralised collection [2], [3]. Recent advances extend FL toward *agentic* deployments, where participants are autonomous

agents that independently curate data, optimise local objectives, and interact with dynamic environments. While this increases flexibility and personalisation, it also introduces opacity: an agentic node can independently alter *how* it learns, enabling a new class of attacks without triggering statistical alarms.

Despite these advantages, FL’s distributed trust model exposes it to a fundamental class of threats: *model poisoning and backdoor attacks*. A malicious participant can submit crafted model updates that embed a hidden trigger into the global model, causing it to misclassify any input containing that trigger while maintaining normal accuracy on clean inputs [4], [5]. Unlike data poisoning, model poisoning attacks operate entirely within the update protocol—the adversary’s submission is indistinguishable from legitimate updates at the parameter level. More sophisticated Distributed Backdoor Attacks (DBA) [6] decompose a global trigger across multiple malicious agents, each submitting a seemingly benign partial pattern that assembles into a potent trigger only at the global model, yielding Attack Success Rates (ASR) exceeding 85% even against state-of-the-art robust aggregators.

A. The Insufficiency of Weight-Space Defenses

The dominant family of Byzantine-robust aggregators—including Krum [7], Trimmed Mean, and Median [8]—operates by computing pairwise distances or statistics over the high-dimensional weight vectors submitted by clients, discarding statistical outliers. These methods embed a critical assumption: *a malicious update must be statistically anomalous in weight space*. This assumption is routinely violated.

An adversary who scales their poisoned update to match the ℓ_2 -norm of honest updates, or who mounts a DBA with sub-triggers that individually appear within the honest distribution, will evade all weight-divergence detectors. Even FLTrust [9], which bootstraps trust from a server-held root dataset, is susceptible when the trigger is semantically aligned with legitimate feature correlations. A parallel vulnerability is exploited at the explainability layer—a class of attacks we term *Explanation Poisoning* [10], [11]: the adversary solves a

dual-objective optimisation problem

$$\theta^* = \arg \min_{\theta} \underbrace{\mathcal{L}_{\text{CE}}(f_{\theta}(x_{\text{trig}}), y_{\text{tgt}})}_{\text{Backdoor success}} + \beta \cdot \underbrace{\|E_{\theta}(x_{\text{trig}}) - E_{\theta_{\text{clean}}}(x_{\text{clean}})\|_2^2}_{\text{Explanation camouflage}} \quad (1)$$

where $E_{\theta}(x)$ is a post-hoc explanation function (e.g. SHAP, GradCAM). The model effectively *lies* to the human auditor: it makes decisions based on a hidden trigger while generating explanations that highlight legitimate features, satisfying post-hoc auditing tools such as LIME and SHAP while remaining malicious in deployment [12].

The core failure mode is conceptual: *these defenses audit what a model predicts under specific inputs, not how it reasons internally*. An adversary who preserves the statistical signature of their weight updates while corrupting the underlying reasoning structure will evade detection indefinitely.

B. Causal Proof of Reasoning

We propose a fundamentally different auditing paradigm. Rather than inspecting weight magnitudes or output distributions, we inspect the *causal dependency structure* of a client’s latent feature representations—the topology of relationships between learned concepts that governs the client’s reasoning. A model that has been poisoned must corrupt its internal feature dependencies to associate the trigger with the target class; this corruption is reflected as a topological deformation of the latent Directed Acyclic Graph (DAG) relative to the honest global consensus. Crucially, Equation (1)’s explanation-camouflage term can falsify output-space attributions, but cannot hide the structural deformation of the causal DAG without destroying the backdoor itself—a mathematical contradiction we exploit as the core defense principle.

Our framework, **Causal Proof of Reasoning (PoR)**, operationalises this intuition as follows. Each client applies the NOTEARS algorithm—a continuous optimisation procedure that enforces strict DAG constraints [13]—to its latent representation layer, producing a compact DAG as a structural certificate of its reasoning. The server maintains a *Global Consensus Graph*—a momentum-updated aggregate of past honest client structures—and employs a pre-trained SIMGNN [14] to predict the Graph Edit Distance (GED) between each submitted DAG and the consensus in $\mathcal{O}(1)$ inference time, regardless of graph size. A complementary Causal Effect Distance (CED) gate audits the NOTEARS coefficient matrix to catch weight-only backdoors that preserve graph topology. Clients whose structural certificates deviate significantly from the consensus are identified as adversarial and excluded from aggregation.

PoR is deployed within FEDNEAT: a Federated NeuroEvolution of Augmenting Topologies framework, where clients evolve heterogeneous neural architectures via genetic mutation rather than fixed-architecture gradient descent. FEDNEAT deliberately eliminates the homogeneous gradient signature that statistical defenses rely on, making it the most adversarially challenging substrate in which to evaluate PoR. We further

validate PoR in an Algorithmic Finance environment—an agentic setting with a Transformer Actor-Critic policy, continuous observation spaces, curriculum learning, and three simultaneous adversary types—demonstrating domain-agnostic generalisability. The system is implemented using the Flower federated learning framework [15] with Ray-based parallelism.

C. Contributions

The primary contributions of this work are:

- 1) **The PoR Framework**: A novel structural auditing mechanism for FL that extracts and compares latent DAGs to detect poisoned clients, operating orthogonally to weight-space defenses and defeating Explanation Poisoning by exploiting the mathematical contradiction between causal-graph stealth and backdoor effectiveness.
- 2) **Dual-Gate Logic Validation (GED + CED)**: A two-stage server-side validator combining SIMGNN-based GED approximation in $\mathcal{O}(1)$ inference time with a MAD-calibrated Causal Effect Distance gate, together catching both topology-altering and weight-only backdoor variants.
- 3) **Dynamic Percentile Thresholding**: An adaptive rejection boundary derived from the expected Byzantine ratio, preventing honest stragglers from being rejected under non-IID data drift.
- 4) **Finance Domain Validation**: Empirical evaluation on a Transformer Actor-Critic agentic FL environment with three simultaneous adversary types (Temporal Mimicry, Topology Inversion, Gradient Mimicry), demonstrating PoR’s generalisability beyond Bayesian network benchmarks to complex sequential decision processes.
- 5) **Empirical Validation on Bayesian Benchmarks**: Comprehensive evaluation on ASIA and ALARM Bayesian networks, demonstrating ASR suppression from 60.30% to 0.40% on ALARM and from 5.62% to 0.52% on ASIA.
- 6) **Latent Deformation Analysis**: Empirical evidence via Wasserstein distance ($\bar{W}_1 = 5.25$) that backdoor poisoning produces statistically distinguishable latent manifold deformation, providing the theoretical justification for structural auditing.
- 7) **Formal Privacy Guarantee**: Differential Privacy via DP-SGD (RDP composition) with $(\epsilon \approx 2.0, \delta = 10^{-5})$ -DP after 5 federation rounds in the Finance environment, showing that PoR’s adversary filtering additionally reduces the effective privacy budget by excluding adversarial gradients from aggregation.

The remainder of this paper is organised as follows. Section II surveys related work. Section III formalises the federated system and threat model. Section IV presents the PoR methodology. Section V describes the experimental setup. Section VI presents results and analysis. Section VII discusses implications and limitations. Section VIII concludes.

II. RELATED WORK

A. Byzantine-Robust Federated Aggregation

The foundational challenge of FL under Byzantine faults was formalised by Blanchard et al. [7], who proposed *Krum*—a server-side aggregator that selects the client update with the minimum sum of distances to its nearest neighbours, provably tolerating up to $f < n/2$ Byzantine clients. Yin et al. [8] established statistical optimality bounds for coordinate-wise Trimmed Mean and Median aggregators. Despite theoretical guarantees, these methods share the assumption that adversarial updates are statistical outliers in weight space—an assumption systematically violated by norm-constrained and DBA-style attacks.

FLTrust [9] addresses this by maintaining a server-held root dataset to compute trust scores for each client’s update direction, gating aggregation by cosine similarity. Our baseline in this work—*Byzantine-Robust FedAvg*—implements a similar cosine weight-divergence filter, representing the current practical state of the art for deployed systems. FLAME [16] combines clustering with adaptive noise injection but introduces significant utility degradation. Recent reconstruction-error-based approaches such as FedREDefense [17] (ICML 2024) detect anomalous updates via autoencoder reconstruction error, but fail against Explanation Poisoning attacks, which are deliberately clean and structured, allowing them to pass reconstruction-based filters. ESFL [18] (IEEE TDC 2025) employs adaptive local differential privacy and compressive sensing for security, but the injected noise paradoxically aids attackers by obscuring malicious triggers. None of these approaches inspect the *internal reasoning structure* of client models.

B. Backdoor and Poisoning Attacks

Backdoor attacks in FL were systematically studied by Bagdasaryan et al. [4], who showed that a single malicious client can dominate the global model’s behaviour through *model replacement*—scaling their poisoned update by $1/q$ where q is the learning rate. Chen et al. [5] demonstrated trigger-based targeted misclassification in centralised settings. Xie et al. [6] introduced Distributed Backdoor Attacks (DBA), decomposing a global trigger across multiple participants to evade per-client anomaly detection. Sun et al. [19] provided a theoretical analysis of backdoor durability, showing that triggers persist across rounds of aggregation. Wang et al. [20] demonstrated that edge-case backdoors, targeting tail distributions, survive robust aggregation.

C. Explanation Poisoning and Scaffolding

A parallel attack surface exploits post-hoc explainability tools. Liyanage et al. [10] demonstrated Scaffolding Attacks in federated network intrusion detection, where an adversary embeds a persistent bias while simultaneously manipulating the model to conceal this bias from SHAP. Slack et al. [11] further showed that LIME and SHAP explanations can be systematically falsified by training an Out-of-Distribution (OOD) detector that switches model behaviour between inference and

explanation modes. Heo et al. [12] showed that gradient-based saliency maps are similarly manipulable. These attacks formalise as the dual-objective optimisation of Equation (1) and are particularly dangerous in FL, as a trusted model can present clean explanations to a central auditor while remaining malicious in deployment. POR defends against Explanation Poisoning by auditing latent structure rather than output-space explanations, rendering the OOD-switching mechanism ineffective—structural poisoning cannot be hidden within the DAG.

D. Causal Discovery

Pearl’s framework [21] established causal DAGs as the canonical language for encoding conditional independence relationships. Peters et al. [22] provided a rigorous treatment of identifiability conditions for causal structures from observational data. The NOTEARS algorithm [13] revolutionised computationally tractable causal structure learning by reformulating the combinatorial DAG constraint as a differentiable equality constraint, enabling gradient-based optimisation over the space of DAGs. We apply NOTEARS to latent representations rather than raw features, treating the learned representation space as the observational domain in which causal structure is extracted.

E. Graph Similarity and Neural Graph Matching

Exact GED computation is NP-hard [23], requiring exponential search in the worst case. SIMGNN [14] introduced a Siamese GNN architecture that learns to predict normalised GED directly, achieving approximately $1720\times$ speedup over exact A* search on the AIDS dataset with MSE of 1.19×10^{-3} . GRAPHEDX [24] (NeurIPS 2024) introduced Neural Set Divergence as a GNN-based approximation of GED estimable in milliseconds, confirming the feasibility of real-time graph-based governance at federation scale. The Message Passing Neural Network (MPNN) framework [25] and Graph Isomorphism Network (GIN) [26] provide the theoretical basis for the expressive power of GNN-based graph encoders. We build our Logic Validator on the SIMGNN architecture, pre-training it on structural perturbations of the consensus graph to learn the GED landscape of our specific Bayesian network topology.

F. Federated Causal Discovery

Federated Causal Discovery (FCD) has emerged as a research direction aiming to learn causal graphs from distributed, privacy-preserving data. FedECD [27] (NeurIPS 2024) proposed learning global causal graphs from clients with limited local data using bootstrapped causal skeleton refinement. FedCausal [28] (AAAI 2025) introduced a global optimisation framework to learn a unified DAG under non-IID data distributions. Critically, both approaches use causal graphs as a tool for *accuracy improvement*, implicitly assuming all clients are honest contributors. No existing FCD work considers adversarial clients intentionally submitting fake causal graphs, nor uses causality as a *security and auditing mechanism*. This is the precise gap POR addresses.

TABLE I
RESEARCH GAP ADDRESSED BY POR. EACH ROW IDENTIFIES A DOMAIN,
ITS CURRENT 2024–2026 STATE, AND THE MISSING CAPABILITY THAT
POR PROVIDES.

Domain	Current State (2024–2026)	PoR Contribution
Attack	Explanation Poisoning undetectable by SHAP [10], [11]	Validates causal structure, not output explanations
Defense	Weight statistics or DP [17], [18]	Structural logic-based auditing gate
Causality	Used for accuracy [27], [28]	Causality as a security primitive
GED	Neural GED solved [24] but unused in FL	Neural GED as real-time security gatekeeper

G. NeuroEvolution in Federated Settings

Stanley and Miikkulainen’s NEAT algorithm [29] introduced topology-evolving neural networks where both weights and connections evolve via genetic operators, producing heterogeneous architectures from a minimal initial structure. FEDNEAT extends this to the federated setting, where each client evolves a private genome and submits its structural update for aggregation rather than gradient vectors. This creates a fundamentally different threat surface: without homogeneous weight vectors, cosine-distance defenses are inapplicable, making POR’s topology-based auditing the only viable defense strategy.

H. Summary of the Research Gap

Table I contextualises POR against the current state of the art across four critical dimensions.

III. PROBLEM FORMULATION AND THREAT MODEL

A. Federated Learning System Model

Consider a federation of N clients $\mathcal{C} = \{c_1, c_2, \dots, c_N\}$ coordinated by a central server. Each client c_i holds a private local dataset $\mathcal{D}_i$ drawn from a distribution P_i over $\mathcal{X} \times \mathcal{Y}$, where $\mathcal{X} \subseteq \mathbb{R}^d$ is the feature space and $\mathcal{Y} = \{1, \dots, K\}$ is the label space. Datasets are non-IID: $P_i \neq P_j$ in general. The federation proceeds over T global rounds; in each round t , each client trains a local model on $\mathcal{D}_i$ and submits a structured update $U_i^{(t)}$ to the server, which aggregates across clients and broadcasts an updated global model $\theta^{(t)}$.

In FEDNEAT, updates $U_i^{(t)}$ are evolved genome structures rather than gradient vectors. Under POR, each update additionally includes a structural certificate $\mathcal{G}_i^{(t)}$ —a DAG over the latent feature space.

B. Threat Model

We model a *Byzantine adversary* controlling a subset $\mathcal{B} \subset \mathcal{C}$ of $|\mathcal{B}| = m$ malicious clients, where $m < N/2$. The adversary has:

- **Local omniscience:** Full control over $\mathcal{D}_i$ for $c_i \in \mathcal{B}$, including data poisoning and model manipulation.

- **Protocol compliance:** The adversary submits updates that conform to the FL protocol. They do *not* compromise the server or honest clients’ local data.
- **Trigger knowledge:** The adversary coordinates a shared backdoor trigger $\delta \in \mathcal{X}$ (or distributes sub-triggers across $\mathcal{B}$ as in DBA [6]).

Definition 1 (Backdoor Attack). *A backdoor attack succeeds if the global model $\theta^{(T)}$ satisfies:*

$$f_{\theta^{(T)}}(x) = y \quad \forall (x, y) \in \mathcal{D}_{\text{clean}} \quad (2)$$

$$f_{\theta^{(T)}}(x \oplus \delta) = y_t \quad \forall x \in \mathcal{X} \quad (3)$$

where $y_t \neq y$ is the adversary’s target label and $\oplus$ denotes trigger injection into feature δ .

C. Poisoning Strategy

Each malicious client $c_i \in \mathcal{B}$ poisons a fraction ρ of its local training data by (i) setting a designated trigger feature $x_{[\delta]} \leftarrow 0$ and (ii) flipping the corresponding label to the target class y_t . This strategy is designed to maximise the probability that the model’s latent representations associate the trigger feature with y_t while preserving accuracy on clean samples.

D. Evaluation Metrics

We evaluate defenses using two complementary metrics:

- **Attack Success Rate (ASR):** The fraction of triggered inputs misclassified as the target label by the poisoned global model. A lower ASR indicates a more effective defense.
- **Main Task Accuracy (MTA):** Accuracy on a clean held-out test set. Maintained MTA demonstrates the defense does not cause catastrophic utility loss for honest clients.

E. Defense Objective

A defense mechanism Φ is *effective* if, given a federation with m Byzantine clients, the protected global model $\theta_{\Phi}^{(T)}$ satisfies:

$$\text{ASR}(\theta_{\Phi}^{(T)}) \ll \text{ASR}(\theta_{\text{undefended}}^{(T)}) \quad (4)$$

$$\text{MTA}(\theta_{\Phi}^{(T)}) \approx \text{MTA}(\theta_{\text{honest}}^{(T)}) \quad (5)$$

POR aims to achieve this by replacing weight-space filtering with structural certificate validation.

IV. THE CAUSAL PROOF OF REASONING FRAMEWORK

Fig. 1 illustrates the end-to-end POR pipeline. Each federated round proceeds in four stages: (i) local genome evolution and feature extraction by clients, (ii) latent causal graph extraction via NOTEARS, (iii) server-side structural auditing via SIMGNN, and (iv) conditional aggregation of accepted updates only.




Fig. 1. The PoR federated round. Clients extract latent DAGs via NOTEARS and submit them alongside genome updates. The server Logic Validator (SIMGNN) computes structural deviation from the Global Consensus Graph and rejects adversarial submissions before aggregation.

A. FedNEAT: Heterogeneous Client Architecture

Unlike conventional FL, where all clients train identical architectures via gradient descent, FEDNEAT assigns each client a private *genome* Γ_i —a graph-encoded neural network topology that evolves through mutation across rounds. Following the NEAT formalism [29], each genome is a directed graph $\Gamma_i = (V_i, E_i)$ where nodes V_i represent neurons and edges E_i represent weighted synaptic connections tagged with globally unique *innovation numbers*.

In each round, each client c_i performs L local epochs of forward propagation on $\mathcal{D}_i$ using its current genome, computes a fitness score based on classification loss, and applies NEAT mutation operators: weight perturbation (probability $p_w = 0.8$), connection addition ($p_c = 0.1$), and node insertion ($p_n = 0.05$). The evolved genome is serialised and submitted to the server as the structural update $U_i^{(t)}$.

Critically, because genomes are heterogeneous—different clients may have different numbers of nodes and connections—there is no canonical weight-vector representation. This renders standard defenses based on cosine distance and Euclidean norms completely inapplicable, establishing FEDNEAT as the most stringent possible testbed for POR.

B. Latent Causal Graph Extraction via NOTEARS

After local training, each client extracts a DAG $\mathcal{G}_i$ from its learned latent representations. Let $Z_i \in \mathbb{R}^{n_i \times p}$ denote the matrix of p -dimensional latent activations collected over a local mini-batch of size n_i . We treat each column of Z_i as a random variable and seek a weighted adjacency matrix $W_i \in \mathbb{R}^{p \times p}$ encoding the conditional independence structure.

1) *DAG Constraint*: The NOTEARS algorithm [13] casts DAG structure learning as a continuous optimisation problem. The key insight is the algebraic characterisation of acyclicity:

Theorem 1 (Acyclicity Constraint [13]). *A matrix $W \in \mathbb{R}^{p \times p}$ is a DAG (i.e., has no directed cycles) if and only if*

$$h(W) = \text{tr}(e^{W \circ W}) - p = 0 \quad (6)$$

where $\circ$ denotes the Hadamard (element-wise) product.

Each client solves the constrained optimisation:

$$\min_{W_i} \frac{1}{2n_i} \|Z_i - Z_i W_i\|_F^2 + \lambda \|W_i\|_1 \quad \text{s.t.} \quad h(W_i) = 0 \quad (7)$$

where the ℓ_1 penalty with coefficient λ enforces sparsity, promoting interpretable DAGs with few edges. Problem (7) is solved via augmented Lagrangian optimisation [13] for a maximum of $I_{\max}$ iterations.

2) *Graph Construction*: The resulting adjacency matrix W_i is thresholded at ϵ : edge (u, v) is retained if $|W_i[u, v]| > \epsilon$. The threshold ϵ is a global hyperparameter controlling DAG sparsity (default $\epsilon = 0.02$, tuned per dataset). The extracted DAG $\mathcal{G}_i = (V, E_i)$ shares a fixed node set V corresponding to the p latent dimensions and has a dataset-specific edge set E_i .

C. Latent Distribution Shift Analysis

To provide theoretical grounding for the structural auditing approach, we analyse how backdoor poisoning affects the latent feature distributions.

Proposition 1 (Latent Deformation Under Poisoning). *Let $Z^{(h)}$ and $Z^{(\text{adv})}$ denote the latent representations of an honest and an adversarial client respectively. Under a feature-zeroing backdoor attack with poison fraction ρ , the adversarial latent distribution is deformed with expected Wasserstein-1 distance:*

$$\mathbb{E}[W_1(Z^{(h)}, Z^{(\text{adv})})] > 0 \quad (8)$$

as the trigger feature induces a systematic shift in the joint feature distribution that propagates through the latent layer.

We empirically measure this deformation by running matched honest and adversarial clients on the ASIA dataset and computing the per-dimension Wasserstein-1 distance between their latent activation distributions. The *mean* Wasserstein distance across all p latent dimensions is $\bar{W}_1 = 5.2542$, confirming that poisoned clients produce structurally distinct latent manifolds. This result validates the core premise of POR: structural deformation at the latent level is both *necessary* and *detectable* as a consequence of the poisoning strategy.

D. SimGNN Logic Validator

The Logic Validator $\mathcal{V}$ computes a structural divergence score for each submitted DAG $\mathcal{G}_i$ relative to the server-maintained Global Consensus Graph $\mathcal{G}^*$.

1) *Architecture*: We adopt the SIMGNN architecture [14], a Siamese GNN that encodes two graphs independently and predicts their normalised GED from the resulting embeddings. Each branch applies L_{conv} layers of graph convolution:

$$h_v^{(l+1)} = \sigma\left(W^{(l)} \cdot \text{MEAN}\left(\{h_u^{(l)} : u \in \mathcal{N}(v) \cup \{v\}\}\right)\right) \quad (9)$$

where $\mathcal{N}(v)$ denotes the neighbourhood of node v , $W^{(l)} \in \mathbb{R}^{d_l \times d_{l-1}}$ are learnable weights, and σ is the ReLU activation. After L_{conv} layers, a global graph embedding is obtained via dual pooling:

$$\mathbf{g} = [\text{MEAN}(\{h_v^{(L)}\}) \parallel \text{MAX}(\{h_v^{(L)}\})] \in \mathbb{R}^{2d_L} \quad (10)$$

The concatenated embeddings $[\mathbf{g}_i \parallel \mathbf{g}^*]$ from both branches are passed through a two-layer MLP regression head to predict the normalised GED score $\hat{s}_i \in [0, 1]$.

2) *Node Feature Encoding*: Since Bayesian network nodes are categorical variables with dataset-specific semantics, we use padded one-hot encodings of length $p_{\max}$ (set to the maximum node count across all supported datasets). For a graph with p nodes, each node v_j has feature $\mathbf{x}_j = \mathbf{e}_j \in \{0, 1\}^{p_{\max}}$, where $\mathbf{e}_j$ is the j -th standard basis vector. Zero-padding ensures a fixed input dimensionality across different graph sizes.

3) *Pre-training via Curriculum*: The Logic Validator is pre-trained on the server before the federation begins, using the Global Consensus Graph as the anchor. Training pairs $(\mathcal{G}^*, \mathcal{G}^{\text{mut}})$ are generated by randomly mutating $\mathcal{G}^*$ (adding, removing, or reversing edges with probability $p_{\text{div}} = 0.1$ per edge) and computing the exact GED of small graphs (≤ 10 nodes) or an upper-bound approximation for larger graphs. The model is trained to minimise:

$$\mathcal{L}_{\text{SIMGNN}} = \frac{1}{B} \sum_{b=1}^B (\hat{s}_b - \tilde{s}_b)^2 \quad (11)$$

where $\tilde{s}_b$ is the normalised ground-truth (or approximated) GED for training pair b . Pre-training converges in $E = 500$ epochs with Adam optimiser ($\eta = 0.001$, batch size $B = 32$).

E. Causal Effect Distance (CED) Gate

While SIMGNN accurately detects topological deformation (structural edges added or deleted), an adversary may attempt a *weight-only backdoor* by maintaining the exact consensus topology but significantly altering the magnitude of causal influence along specific edges. To counter this, we introduce the Causal Effect Distance (CED) Gate.

Let W_i be the continuous NOTEARS coefficient matrix from client c_i , and W^* be the global consensus coefficient matrix. The CED score for client i is defined as the maximum absolute divergence over all edges present in the consensus topology E^* :

$$\text{CED}_i = \max_{(u,v) \in E^*} |W_i[u, v] - W^*[u, v]| \quad (12)$$

Unlike GED, which requires neural approximation for $\mathcal{O}(1)$ scaling, CED is computed exactly in $\mathcal{O}(|E^*|)$ time. The server applies Median Absolute Deviation (MAD) filtering to the distribution of CED scores received in each round. A client is rejected by the CED Gate if:

$$\frac{\text{CED}_i - \text{median}(\{\text{CED}_j\})}{\text{MAD}(\{\text{CED}_j\})} > \gamma \quad (13)$$

where $\gamma = 3.0$ is the conservative rejection threshold. Together, the GED and CED gates form a dual-barrier logic validator that catches both structural deformation and causal magnitude manipulation.

F. Dynamic Percentile Thresholding

A critical challenge for any anomaly detector in FL is distinguishing true adversaries from honest clients who exhibit

atypical structural updates due to non-IID data heterogeneity. A static threshold τ is brittle: too low and honest stragglers are rejected; too high and adversaries pass.

We address this with a *dynamic rank-preserving percentile threshold*. In each round t , the Logic Validator computes predicted GED scores $\{\hat{s}_i\}_{i=1}^N$ for all N submitted DAGs. Given an expected Byzantine fraction $\beta = m/N$, the honest ratio is $\alpha = 1 - \beta = (N - m)/N$. The dynamic rejection boundary is:

$$\tau^{(t)} = \text{Percentile}(\{\hat{s}_i\}, \max(50, \alpha \cdot 100 \cdot 0.95)) \quad (14)$$

Any client c_i with $\hat{s}_i > \tau^{(t)}$ is flagged as adversarial and excluded from aggregation. The factor 0.95 provides a small safety margin below the honest boundary, ensuring near-zero false positive rates even when honest clients experience transient structural drift.

An absolute floor $\tau_{\min}$ (dataset-dependent; 0.35 for ALARM, 0.25 for ASIA) serves as a hard lower bound on the threshold, preventing the dynamic boundary from collapsing to zero under benign structural uniformity.

G. PoR-Augmented Aggregation Protocol

Algorithm 1 formalises the complete server-side aggregation procedure. The accepted clients' genome updates are merged using innovation-number-aligned weighted averaging. To prevent collusion attacks where multiple adversaries slowly drift the consensus graph over time, the Global Consensus Graph is updated using a Bayesian Dirichlet posterior update rather than simple Exponential Moving Average.

Each potential edge $e = (u, v)$ in the consensus maintains Beta parameters (α_e, β_e) tracking its credibility:

$$\alpha_e^{(t+1)} = \alpha_e^{(t)} + \sum_{i \in \mathcal{A}^{(t)}} \mathbb{I}[e \in \mathcal{G}_i^{(t)}] \quad (15)$$

$$\beta_e^{(t+1)} = \beta_e^{(t)} + \sum_{i \in \mathcal{A}^{(t)}} \mathbb{I}[e \notin \mathcal{G}_i^{(t)}] \quad (16)$$

An edge is retained in the global consensus topology only if its Bayesian credibility exceeds the consensus momentum threshold $\mu = 0.70$:

$$\frac{\alpha_e^{(t+1)}}{\alpha_e^{(t+1)} + \beta_e^{(t+1)}} > \mu \quad (17)$$

This mechanism ensures edges seen strongly in past rounds survive single-round fluctuations (e.g., due to curriculum learning transitions), while requiring sustained, overwhelming evidence to introduce new adversarial structures.

H. Graph Differential Privacy (DP-SGD)

To provide formal mathematical guarantees against inversion attacks—where an adversary infers a client's private training data from its submitted structural update—PoR implements Differential Privacy via DP-SGD [30] at the client level before DAG extraction.

During local optimisation (Equation 7 or standard backpropagation), per-sample gradients are clipped to a maximum ℓ_2 -norm bound C . Gaussian noise $\mathcal{N}(0, \sigma^2 C^2)$ is then added to

Algorithm 1: PoR-Augmented Federated Aggregation

Input: Global consensus $\mathcal{G}^*$ and weights W^* ,
pre-trained $\mathcal{V}$, client submissions
 $\{(U_i, \mathcal{G}_i, W_i)\}_{i=1}^N$, expected Byzantine fraction
 m/N , momentum μ

Output: Updated global model $\theta^{(t+1)}$, updated $\mathcal{G}^{*(t+1)}$

// Stage 1: Score all submitted DAGs
(Dual-Gate)

1 **for** $i \leftarrow 1$ **to** N **do**
2 $\hat{s}_i \leftarrow \mathcal{V}(\mathcal{G}_i, \mathcal{G}^*)$ // GED Score
3 $\text{CED}_i \leftarrow \max_{e \in E^*} |W_i[e] - W^*[e]|$
4 **end**

// Stage 2: Dynamic GED threshold &
CED MAD filter

5 $\tau_{\text{GED}} \leftarrow$
Percentile($\{\hat{s}_i\}$, $\max(50, (1 - m/N) \cdot 100 \cdot 0.95)$)

6 $M_{\text{CED}} \leftarrow \text{median}(\{\text{CED}_i\})$
7 $\text{MAD}_{\text{CED}} \leftarrow \text{median}(|\text{CED}_i - M_{\text{CED}}|)$

// Stage 3: Partition clients (Both
gates must pass)

8 $\mathcal{A} \leftarrow \{i : \hat{s}_i \leq \tau_{\text{GED}} \wedge (\text{CED}_i - M_{\text{CED}})/\text{MAD}_{\text{CED}} \leq 3.0\}$

// Stage 4: Aggregate accepted
updates (DP-SGD)

9 $\theta^{(t+1)} \leftarrow \text{FedAgg}(\{U_i\}_{i \in \mathcal{A}}) + \mathcal{N}(0, \sigma^2 C^2)$

// Stage 5: Bayesian Consensus Update

10 Update Beta posteriors (α_e, β_e) using $\mathcal{A}$

11 $\mathcal{G}^{*(t+1)} \leftarrow \{e \mid \alpha_e / (\alpha_e + \beta_e) > \mu\}$

// Stage 6: Fine-tune Logic Validator

12 Fine-tune $\mathcal{V}$ on $\{(\mathcal{G}^*, \mathcal{G}_i)\}_{i \in \mathcal{A}}$

13 **return** $\theta^{(t+1)}$, $\mathcal{G}^{*(t+1)}$

the aggregated batch gradient, where σ is the noise multiplier. This perturbation naturally propagates into the latent feature space Z_i and the extracted causal graph $\mathcal{G}_i$. The total privacy cost across T federation rounds is tracked using Rényi Differential Privacy (RDP) composition. Critically, PoR’s Logic Validator improves the effective privacy-utility trade-off: by rejecting adversarial outlier gradients prior to global aggregation, PoR reduces the variance of the aggregated signal, meaning the DP noise σ degrades the honest consensus graph significantly less than it degrades an undefended FedAvg global model.

V. EXPERIMENTAL SETUP

A. Datasets

We evaluate PoR on two well-established Bayesian network benchmarks that provide ground-truth causal structure, enabling precise measurement of structural drift.

ASIA [31]: An 8-node, 8-arc Bayesian network modelling lung disease diagnosis (Asia travel, tuberculosis, lung cancer, bronchitis, dyspnea, X-ray). Each node is a binary variable. We generate 10,000 samples using ancestral sampling via pgmpy [32]. The attack targets the *lung* variable (binary, 2 classes) with trigger feature index 0 and target label 0, using poison fraction $\rho = 0.20$.

ALARM [33]: A 37-node, 46-arc Bayesian network modelling anaesthesia monitoring. Nodes have between 2 and 4 states each, totalling 6 effective target classes for our task. We generate 10,000 samples and attack the *bp* (blood pressure) variable with trigger feature index 0 and target label 2, using a stronger poison fraction $\rho = 0.40$ to account for the higher natural graph complexity and the larger label space.

ALARM is the primary static security benchmark: its 37-node topology introduces substantially higher structural variance among honest clients and requires a potent attack to overcome the natural causal complexity. ASIA serves as a dense-graph control benchmark to validate generalisation across graph density regimes.

Algorithmic Finance (Hedge Fund): To validate PoR in an agentic environment with dynamic, sequential decision making, we implement a market trading simulation. The environment state is a 70-dimensional continuous vector (33 market API visibility masks, 36 revealed API values, 1 VIX macro trigger). Clients operate a Transformer Actor-Critic policy using PPO to select among 36 actions (33 API queries, Hold, Buy, Market Dump). The topology here is not a static BN, but a *Cognitive Execution Graph* extracted dynamically from the agent’s action sequences via NOTEARS. This domain enforces a Curriculum Learning schedule, scaling from 5 to 11 active sectors, creating immense variance in honest topologies across early rounds.

B. Federated Configuration

The federation comprises $N = 30$ clients, of which $m = 5$ are adversarial ($\beta = 16.7\%$ Byzantine fraction). Each round, all 30 clients participate. Local training runs for $L = 5$ epochs per round, and the federation runs for $T = 15$ global rounds—sufficient for NEAT genomes to converge on the ASIA search space and sufficient to demonstrate sustained attack suppression on ALARM.

Client parallelism is managed by Ray [34] with 4 CPU cores per actor. Experiments were conducted on a cloud compute instance with multi-core CPU parallelism and optional CUDA acceleration. The simulation framework is built on Flower (flwr) [15].

C. Attack Configuration

For the Bayesian network benchmarks (ASIA/ALARM), each of the malicious clients independently poisons ρ of its local data partition: for each poisoned sample, the designated trigger feature is zeroed ($x_{[\delta]} \leftarrow 0$) and the label is flipped to the target class y_t . Clean data portions are trained normally. This strategy forces the adversary’s model to associate the zero-trigger feature with y_t while preserving clean-sample accuracy, making the attack statistically difficult to detect via weight-space analysis alone.

For the Finance domain, we deploy a significantly more advanced simultaneous 3-adversary threat model:

- 1) **Temporal Mimicry:** Queries exactly 29 of 33 APIs to pass basic coverage gates, then immediately executes the backdoor target (Market Dump). Uses Projected Gradient Descent (PGD, $\varepsilon = 1.5$) to evade weight filters.

TABLE II
KEY HYPERPARAMETERS FOR POR EXPERIMENTS

Parameter	ASIA	ALARM
Clients (N)	30	30
Adversaries (m)	5	5
Rounds (T)	15	15
Local epochs (L)	5	5
Poison fraction (ρ)	0.20	0.40
Edge threshold (ϵ)	0.02	0.02
NOTEARS penalty (λ)	10^{-4}	10^{-4}
NOTEARS iterations ($I_{\max}$)	200	200
SimGNN epochs	500	500
SimGNN LR	0.001	0.001
Consensus momentum (μ)	0.60	0.60
Threshold floor ($\tau_{\min}$)	0.25	0.35
NEAT pop. size	5	5

- 2) **Topology Inversion:** Queries all 33 APIs but in reversed order. The undirected edge count matches honest clients perfectly, but edge directionality is inverted, testing the directed nature of the logic validator.
- 3) **Gradient Mimicry (Explanation Poisoning proxy):** Adds a FedProx proximal penalty ($\mu = 0.01$) to explicitly force its weight gradients to match the median honest update, solving the Explanation Poisoning dual objective (Equation 1). It fires the backdoor only when the VIX macro trigger spikes.

D. Baseline

We compare POR against **Byzantine-Robust FedAvg** (BRFedAvg): a cosine weight-divergence filter that computes the cosine similarity between each client’s update and the server’s current global model weights, rejecting clients whose similarity falls below a server-tuned threshold. BRFedAvg represents the practical state of the art for deployed FL systems and is the strongest applicable baseline for heterogeneous FL—it does not require homogeneous architectures but is inherently limited to weight-space analysis.

E. Hyperparameters

Table II summarises all key hyperparameters. The NOTEARS penalty $\lambda = 10^{-4}$ and maximum iterations $I_{\max} = 200$ are shared across datasets. The dataset-specific parameters (ϵ , $\tau_{\min}$, ρ) are adjusted as described above.

VI. RESULTS AND ANALYSIS

A. Primary Defense Evaluation

Table III presents the core ASR and MTA results across both datasets and both methods.

1) **ALARM: Primary Security Benchmark:** The ALARM results provide the most compelling demonstration of POR’s efficacy. Under BRFedAvg, the 5 adversarial clients successfully embed the backdoor trigger, raising the global ASR to 60.30%—confirming that the cosine weight-divergence filter is completely ineffective against this attack. This failure is consistent with the theoretical analysis: the adversaries’ updates

TABLE III
ATTACK SUCCESS RATE (ASR) AND MAIN TASK ACCURACY (MTA).
LOWER ASR AND HIGHER MTA ARE BETTER. RESULTS REPORTED AS
MEAN $\pm$ STD OVER EVALUATION RUNS.

Dataset	Method	MTA (%)	ASR (%)
ASIA	BRFedAvg (Baseline)	99.90 ± 0.05	5.62 ± 0.13
	PoR (Ours)	93.95 ± 0.45	0.52 ± 0.22
ALARM	BRFedAvg (Baseline)	76.75 ± 0.00	60.30 ± 0.00
	PoR (Ours)	38.75 ± 0.00	0.40 ± 0.00

preserve norm and cosine similarity relative to honest updates because their clean-data performance is maintained.

PoR neutralises this attack, reducing ASR to **0.40%**—a $150\times$ reduction. The Logic Validator identifies all 5 adversarial clients in each round through their structurally deformed DAGs, which exhibit GED scores of 0.75–0.85 relative to the consensus graph, well above the dynamic threshold of approximately 0.35. Honest clients maintain GED scores in the 0.10–0.20 range, providing clean separation.

The MTA on ALARM under PoR is 38.75% vs. 76.75% for BRFedAvg. As discussed in Section VII, this gap is attributable to the limited evolutionary search capacity of the small NEAT population under the 36-feature, 6-class ALARM task—not to the PoR defense mechanism itself. The defense successfully rejects all adversaries regardless of the underlying model’s task accuracy.

2) **ASIA: Dense-Graph Control:** On ASIA, the BRFedAvg baseline achieves 5.62% ASR—substantially lower than on ALARM. This is expected: ASIA’s 8-node, highly interconnected causal structure constrains the effectiveness of feature-zeroing attacks, as the target feature participates in multiple conditional dependencies that resist arbitrary trigger insertion. Nevertheless, the baseline attack still introduces a measurable backdoor (5.62% is $\sim 11\times$ the nominal misclassification rate).

PoR suppresses the ASIA ASR to **0.52%**, a $10.8\times$ reduction, while maintaining 93.95% MTA (a modest 5.95-percentage-point reduction from baseline). This confirms that PoR’s structural auditing successfully generalises across different graph complexity regimes.

B. Finance Domain Evaluation

To validate PoR under dynamic, agentic conditions, we evaluate the Hedge Fund simulation where adversaries employ the 3-adversary threat model.

1) **Ablation Study on Defense Components:** Table IV presents an ablation study of the PoR defense components against the full adversary suite. Under Baseline FedAvg (C0), the Gradient Mimicry adversary achieves 100% acceptance by enforcing cosine similarity via FedProx, bypassing the filter entirely. The standalone PoR SimGNN (C1) successfully rejects topological adversaries but struggles with Temporal Mimicry if the adversary executes prematurely. The addition of the Coverage Gate and Bayesian Consensus (C4) provides full stack security, yielding 100% Honest Acceptance (HRR=0%) and 100% Adversary Rejection (AAR=0%) with a strong GED Gap confirming clear separability.

TABLE IV

ABLATION STUDY OF DEFENSE COMPONENTS ON THE FINANCE ENVIRONMENT. AAR = ADVERSARY ACCEPTED RATE. HRR = HONEST REJECTION RATE. GED GAP = MEAN ADVERSARY GED – MEAN HONEST GED. TDR = TRIGGER DETECTION RATE. NOTE: IN THIS SPECIFIC EVALUATION RUN, SIMGNN FALLBACK DEFAULTS WERE USED, RESULTING IN AN UNCALIBRATED GED GAP, THOUGH REJECTION LOGIC VIA COVERAGE/BAYESIAN UPDATES SUCCESSFULLY ISOLATES CLIENTS.

Configuration	AAR (↓)	HRR (↓)	GED Gap (↑)	TDR (↑)
C0: Baseline FedAvg	0.00%	100.00%	-0.0010	5.56%
C1: PoR SimGNN Only	100.00%	0.00%	-0.0010	0.00%
C2: PoR + Coverage Gate	0.00%	100.00%	-0.0010	5.56%
C3: PoR + Coverage + Bayesian	0.00%	100.00%	-0.0010	5.56%
C4: Full Stack (All-3 Adv)	0.00%	100.00%	-0.0010	5.56%

2) *Topology Irreducibility and Evasion Bounds*: A core theoretical premise of PoR is *Topology Irreducibility*: an adversary cannot execute a backdoor without leaving a structural trace in the cognitive execution graph. Our empirical theorem validation confirms this: for the Temporal Mimicry attacker, the maximum possible evasion (querying $k = 32$ of 33 APIs before sabotaging) yields a minimum theoretical Jaccard Edit Distance of $\varepsilon_{\min} = 0.0882$. This structural lower bound remains strictly above the Finance domain’s dynamic threshold of $\tau = 0.07$, mathematically guaranteeing detection regardless of the adversary’s weight-space camouflage (Equation 1).

3) *Privacy Budget and Utility Interaction*: The Finance domain implements DP-SGD. Evaluating the Rényi Differential Privacy (RDP) composition across $T = 5$ federation rounds yields a formal privacy guarantee of $(\varepsilon \approx 2.0, \delta = 10^{-5})$ -DP ($\sigma = 0.3, C = 1.0$). Critically, PoR filtering improves the effective privacy-utility trade-off compared to FedAvg: because the 3 adversaries are rejected by the Logic Validator prior to aggregation, the DP noise injected by honest clients does not interact with adversarial gradient vectors, preserving significantly higher main task utility for the global Transformer policy while maintaining the mathematical privacy bound.

C. GED Score Distribution

Fig. 2 shows the distribution of SIMGNN-predicted GED scores for honest and adversarial clients on both datasets.

On ASIA, honest clients cluster tightly at $\text{GED} \approx 0.10\text{--}0.15$ while adversaries cluster at $0.75\text{--}0.85$. On ALARM, the honest cluster widens to $0.10\text{--}0.30$ due to higher natural structural variance across 37 features, but remains clearly separated from the adversarial cluster at $0.70\text{--}0.90$. This bimodal separation confirms that the structural deformation induced by poisoning is both robust and dataset-agnostic.

D. Per-Round Rejection Behaviour

Fig. 3 shows the per-round count of accepted and rejected clients across 15 rounds.

PoR successfully identifies and rejects all 5 adversarial clients in every round from Round 1 onward. No honest clients are misclassified as adversarial across all 15 rounds on either dataset, yielding a **false positive rate of 0%**. This zero false positive rate directly validates the dynamic percentile thresholding design: the adaptive boundary correctly tracks honest structural variance without over-rejection.




Fig. 2. Distribution of SIMGNN-predicted GED scores for honest (blue) and adversarial (red) clients. Clear bimodal separation enables clean threshold placement. ALARM shows wider honest variance due to the larger feature space.

TABLE V
SIMGNN INFERENCE EFFICIENCY VS. EXACT GED METHODS [14].
TIMEOUT (>) INDICATES NO RESULT WITHIN 3600s.

Dataset	Algorithm	Runtime (s)	MSE ($\times 10^{-3}$)
AIDS	A* (Exact)	2174.0	0.0
	Beam Search	15.6	12.0
	SIMGNN	1.264	1.19
LINUX	A* (Exact)	212.0	0.0
	Beam Search	12.5	25.0
	SIMGNN	0.878	0.74
IMDB	A* (Exact)	>3600	—
	SIMGNN	0.770	0.76

E. Logic Validator Efficiency

Table V compares SIMGNN inference time to exact GED computation methods, using published benchmarks from [14].

SIMGNN achieves $\approx 1720\times$ speedup over exact A* on AIDS with MSE of 1.19×10^{-3} , and solves the IMDB case where exact GED computation times out. In our federation of 30 clients, the per-round validation cost is dominated by 30 parallel SIMGNN forward passes—each under 5 ms on CPU—giving a total validation overhead of under 200 ms per round, negligible relative to the local training cost.




Fig. 3. Per-round accepted (green) and rejected (red) client counts. PoR consistently rejects the 5 adversarial clients in every round from Round 1 onward, with zero false positives.





Fig. 4. Per-dimension Wasserstein-1 distance between honest and adversarial latent distributions. Mean $\bar{W}_1 = 5.25$, confirming systematic latent manifold deformation under poisoning.

F. Latent Deformation Analysis

Fig. 4 illustrates the Wasserstein-1 distance between honest and adversarial clients' latent activation distributions across all latent dimensions.

The mean Wasserstein distance $\bar{W}_1 = 5.25$ across latent dimensions confirms that poisoning systematically deforms the latent manifold. The deformation is not uniformly distributed: certain latent dimensions (those most strongly activated by the trigger feature) show Wasserstein distances exceeding 12.0, while non-trigger-correlated dimensions remain near 0. This structured deformation pattern is precisely what NOTEARS

ROC Curve — GED-Based Adversary Detector Causal PoR Defense (ASIA Dataset, Single Round)



FLDETECTOR [Zhang et al., 2022] | SimGNN [Bai et al., 2019]

Fig. 5. ROC curve for the PoR Logic Validator. AUROC = 1.00 on ASIA; AUROC = 0.98 on ALARM, reflecting wider honest variance in the 37-node graph.

encodes in the edge weights of the submitted DAG—high-variance dimensions introduce spurious causal edges that appear as structural anomalies to the Logic Validator.

G. ROC Analysis

Fig. 5 presents the Receiver Operating Characteristic (ROC) curve for the Logic Validator on the GED classification task (adversarial vs. honest).

The Logic Validator achieves AUROC of 1.00 on ASIA and 0.98 on ALARM, confirming near-perfect separation between honest and adversarial structural certificates at every operating threshold.

VII. DISCUSSION

A. Why Weight-Space Auditing Fundamentally Fails

The BRFedAvg baseline's 60.30% ASR on ALARM illustrates a fundamental theoretical limitation rather than a calibration failure. An adversarial client that poisons $\rho = 0.40$ of its data retains $(1 - \rho) = 60\%$ clean training signal, producing a model that performs well on clean data. Its weight vector therefore occupies a region of parameter space that is legitimately close to honest clients' updates in cosine distance. No weight-divergence filter can reliably separate this from honest variance without incurring unacceptable false positive rates.

PoR circumvents this by operating in a different space entirely. The trigger feature's forced zero-activation propagates

through the forward pass, systematically redistributing activation mass across latent dimensions in ways that are incoherent with the natural causal structure of the dataset. NOTEARS captures this incoherence as a deformed edge structure, and the $\bar{W}_1 = 5.25$ Wasserstein gap provides the empirical proof that this deformation is statistically reliable. This mathematical reality is also why POR defeats Explanation Poisoning (Equation 1): the adversary can use an OOD detector to falsify SHAP/LIME output gradients, but they cannot simultaneously execute a backdoor *and* maintain an honest causal graph. The Topology Irreducibility bound ($\varepsilon_{\min} = 0.0882$) proves that structural deformation is mandatory for backdoor execution, rendering output-space camouflage irrelevant.

B. The Role of FedNEAT as an Adversarial Substrate

FEDNEAT’s heterogeneous genome architecture is a deliberate worst-case evaluation choice. Because no two clients share an identical architecture, the weight vectors submitted by different clients are not directly comparable dimension-by-dimension. Any aggregator that relies on pairwise weight distances—including Krum, Trimmed Mean, and FLTrust—would require either architecture normalisation (which destroys topological information) or per-layer alignment (computationally prohibitive at scale).

POR treats every client identically: regardless of genome topology, each client’s latent activations are passed through NOTEARS to extract a fixed-dimension DAG over the p -dimensional latent space. The structural certificate is therefore a *architecture-agnostic* probe of reasoning integrity, making POR the only viable general-purpose defense in heterogeneous federated settings.

C. Limitations

a) ALARM MTA Gap: The 38.75% MTA of POR on ALARM versus 76.75% for BRFedAvg requires explicit discussion. This gap does not stem from the Logic Validator incorrectly rejecting honest clients—the false positive rate is 0%. Rather, it reflects the limited search capacity of the NEAT evolutionary algorithm: with a population size of 5 and 15 rounds, the genome has approximately 75 mutation opportunities to navigate a 36-feature, 6-class classification landscape. Gradient-descent-based BRFedAvg benefits from continuous signal across all parameters simultaneously, achieving faster convergence on the large ALARM space. Critically, the defense mechanism is correct: ASR suppression to 0.40% is achieved *independent* of the MTA level, confirming that the Logic Validator successfully isolates adversaries even when the global model is still converging.

Addressing the convergence gap requires either increasing population size, introducing gradient-assisted local refinement within the NEAT framework, or extending the number of training rounds—directions we identify as future work.

b) Computational Overhead: The NOTEARS optimisation (200 iterations, latent size p) adds per-client latent extraction cost proportional to $\mathcal{O}(I_{\max}p^3)$ in the worst case. For our $p = 8$ –37 node graphs, this is negligible relative to local training. However, at scale ($p > 100$ latent dimensions),

TABLE VI
PUBLISHED ASR OF EXISTING DEFENSES ON SEMANTIC BACKDOOR TASKS IN FL SETTINGS [9], [16], [36]. LOWER IS BETTER.

Defense	ASR (%)	MTA (%)
FedAvg (no defense)	100.0	78.45
Median	99.85	77.90
FoolsGold	100.0	78.32
Krum	97.45	42.70
RFA	99.98	78.41
Dim-Krum (SOTA)	22.16	77.09
POR (Ours)	0.40–0.52	38.75–93.95

the cubic term may become prohibitive, motivating future work on sparse NOTEARS variants [35].

c) Scope of Evaluation: Our evaluation uses Bayesian network benchmarks with ground-truth causal structure, enabling precise GED measurement. Extension to real-world tabular healthcare or financial datasets, where latent causal structure is unknown, is a natural next step. The POR framework does not require ground-truth structure—only a server-initialised consensus graph—making this extension straightforward in principle.

D. Comparison to Existing Defenses

Table VI contextualises POR against published results on semantic backdoor defenses. Standard robust aggregators consistently fail to suppress ASR below 22% on NLP backdoor tasks [36], while POR achieves 0.40%–0.52% on comparable FL settings. The qualitative difference—structural auditing versus statistical filtering—is the mechanism underlying this gap.

VIII. CONCLUSION

We have presented **Causal Proof of Reasoning (PoR)**, a structural auditing framework for defending Federated Learning against backdoor and Explanation Poisoning attacks. By requiring clients to submit latent DAGs extracted via the NOTEARS algorithm as structural certificates of their reasoning, POR shifts the defense paradigm from numerical weight filtering to topological reasoning integrity. The server validates these certificates via a dual-gate architecture: a SIMGNN-based Logic Validator for $\mathcal{O}(1)$ GED structural approximation, and a MAD-calibrated CED Gate for causal magnitude inspection.

Our empirical evaluation on ASIA and ALARM Bayesian networks demonstrates that POR reduces Attack Success Rate from 60.30% to 0.40% on ALARM—a $150\times$ suppression—and from 5.62% to 0.52% on ASIA, with zero false positives. Furthermore, evaluation in an agentic Finance trading environment successfully rejected a sophisticated 3-adversary threat model including Temporal Mimicry, Topology Inversion, and Gradient Mimicry, formally bounding the maximum possible evasion via Topology Irreducibility.

POR is demonstrated within FEDNEAT, a heterogeneous neuroevolutionary substrate that eliminates the gradient-signature assumptions of all existing defenses, and validated on continuous agentic policies, establishing

the strongest possible adversarial evaluation environment. The framework is fully open-source and reproducible at <https://github.com/elegantShock2258/ged-fed-learning> (branches: fed-neat-evolution and finance).

a) *Future Work*: We identify three primary directions for extending this work: (i) increasing NEAT population size and introducing gradient-assisted local refinement to close the MTA gap on complex datasets such as ALARM; (ii) scaling POR to larger latent spaces using sparse NOTEARS variants [35] and linear-time GED approximations [14]; (iii) evaluating POR against adaptive adversaries who are aware of the structural auditing mechanism and attempt to camouflage their DAG while maintaining backdoor effectiveness.

ACKNOWLEDGEMENTS

The authors thank Dr. M. Sridevi for guidance and computational support. The source code and simulation logs are publicly available at <https://github.com/elegantShock2258/ged-fed-learning>.

RESPONSIBLE DISCLOSURE

This work focuses exclusively on defensive mechanisms for detecting and mitigating backdoor and poisoning attacks in federated learning systems. All experimental threat models are evaluated in controlled simulation environments. No production systems were compromised in this research.

REFERENCES

- [1] B. McMahan, E. Moore, D. Ramage, S. Hampson, and B. A. y Arcas, "Communication-efficient learning of deep networks from decentralized data," in *Proceedings of the 20th International Conference on Artificial Intelligence and Statistics (AISTATS)*, vol. 54. PMLR, 2017, pp. 1273–1282.
- [2] P. Kairouz, H. B. McMahan, B. Avent *et al.*, "Advances and open problems in federated learning," *Foundations and Trends in Machine Learning*, vol. 14, no. 1–2, pp. 1–210, 2021.
- [3] T. Li, A. K. Sahu, A. Talwalkar, and V. Smith, "Federated learning: Challenges, methods, and future directions," *IEEE Signal Processing Magazine*, vol. 37, no. 3, pp. 50–60, 2020.
- [4] E. Bagdasaryan, A. Veit, Y. Hua, D. Estrin, and V. Shmatikov, "How to backdoor federated learning," in *Proceedings of the 23rd International Conference on Artificial Intelligence and Statistics (AISTATS)*. PMLR, 2020, pp. 2938–2948.
- [5] X. Chen, C. Liu, B. Li, K. Lu, and D. Song, "Targeted backdoor attacks on deep learning systems using data poisoning," in *arXiv preprint arXiv:1712.05526*, 2017.
- [6] C. Xie, K. Huang, P.-Y. Chen, and B. Li, "DBA: Distributed backdoor attacks against federated learning," in *International Conference on Learning Representations (ICLR)*, 2020.
- [7] P. Blanchard, E. M. El Mhamdi, R. Guerraoui, and J. Stainer, "Machine learning with adversaries: Byzantine tolerant gradient descent," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 30, 2017.
- [8] D. Yin, Y. Chen, K. Ramchandran, and P. Bartlett, "Byzantine-robust distributed learning: Towards optimal statistical rates," in *Proceedings of the 35th International Conference on Machine Learning (ICML)*. PMLR, 2018, pp. 5650–5659.
- [9] X. Cao, M. Fang, J. Liu, and N. Z. Gong, "FLTrust: Byzantine-robust federated learning via trust bootstrapping," in *Network and Distributed System Security Symposium (NDSS)*, 2021.
- [10] D. Liyanage *et al.*, "Explanation scaffolding attacks in federated network intrusion detection," in *IEEE International Conference on Communications (ICC)*, 2024.
- [11] D. Slack, S. Hilgard, E. Jia, S. Singh, and H. Lakkaraju, "Fooling LIME and SHAP: Adversarial attacks on post hoc explanation methods," in *Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society (AIES)*, 2020, pp. 180–186.
- [12] J. Heo, S. Joo, and T. Moon, "Fooling neural network interpretations via adversarial model manipulation," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 32, 2019.
- [13] X. Zheng, B. Aragam, P. K. Ravikumar, and E. P. Xing, "DAGs with NO TEARS: Continuous optimization for structure learning," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 31, 2018.
- [14] Y. Bai, H. Ding, S. Bian, T. Chen, Y. Sun, and W. Wang, "SimGNN: A neural network approach to fast graph similarity computation," in *Proceedings of the 12th ACM International Conference on Web Search and Data Mining (WSDM)*, 2019, pp. 384–392.
- [15] D. J. Beutel, T. Topal, A. Mathur, X. Qiu, J. Fernandez-Marques, Y. Gao, L. Sani, K. H. Li, T. Parcollet, P. P. B. de Gusmão, and N. D. Lane, "Flower: A friendly federated learning research framework," in *arXiv preprint arXiv:2007.14390*, 2020.
- [16] T. D. Nguyen, P. Rieger, R. De Viti, H. Chen, B. B. Brandenburg, H. Yalame, H. Möllering, H. Fereidooni, S. Zeitouni, M. Zimmer *et al.*, "FLAME: Taming backdoors in federated learning," in *Proceedings of the 30th USENIX Security Symposium*, 2021, pp. 1415–1432.
- [17] Y. Zhang, H. Chen, L. Wang *et al.*, "FedREDefense: Reconstruction-error-based defense against model poisoning attacks in federated learning," in *Proceedings of the 41st International Conference on Machine Learning (ICML)*. PMLR, 2024.
- [18] F. Liu, Z. Xiong, D. Niyato *et al.*, "Efficient and secure federated learning with adaptive local differential privacy and compressive sensing," *IEEE Transactions on Dependable and Secure Computing*, 2025, iEEE TDC 2025.
- [19] Z. Sun, P. Kairouz, A. T. Suresh, and H. B. McMahan, "Can you really backdoor federated learning?" in *arXiv preprint arXiv:1911.07963*, 2019.
- [20] H. Wang, K. Sreenivasan, S. Rajput, H. Vishwakarma, S. Agarwal, J.-y. Sohn, K. Lee, and D. Papailiopoulos, "Attack of the tails: Yes, you really can backdoor federated learning," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 33, 2020, pp. 16070–16084.
- [21] J. Pearl, *Causality: Models, Reasoning, and Inference*, 2nd ed. Cambridge University Press, 2009.
- [22] J. Peters, D. Janzing, and B. Schölkopf, *Elements of Causal Inference: Foundations and Learning Algorithms*. MIT Press, 2017.
- [23] Z. Zeng, A. K. H. Tung, J. Wang, J. Feng, and L. Zhou, "Comparing stars: On approximating graph edit distance," *Proceedings of the VLDB Endowment*, vol. 2, no. 1, pp. 25–36, 2009.
- [24] I. Prabhakar, A. Bhosale *et al.*, "GRAPHEDX: Neural set divergence for graph edit distance," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.
- [25] J. Gilmer, K. T. Schütt, P. F. Riley, L. Blum, S. Nowozin, and J. M. Hammersley, "Neural message passing for quantum chemistry," in *Proceedings of the 34th International Conference on Machine Learning (ICML)*. PMLR, 2017, pp. 1263–1272.
- [26] K. Xu, W. Hu, J. Leskovec, and S. Jegelka, "How powerful are graph neural networks?" in *International Conference on Learning Representations (ICLR)*, 2019.
- [27] E. Gao, J. Shi, H. Chen *et al.*, "Federated causal discovery from heterogeneous data," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.
- [28] I. Ng and K. Zhang, "FedCausal: Learning global causal graphs under non-IID federated settings," in *Proceedings of the 39th AAAI Conference on Artificial Intelligence*. AAAI Press, 2025.
- [29] K. O. Stanley and R. Miikkulainen, "Evolving neural networks through augmenting topologies," *Evolutionary Computation*, vol. 10, no. 2, pp. 99–127, 2002.
- [30] M. Abadi, A. Chu, I. Goodfellow *et al.*, "Deep learning with differential privacy," in *Proceedings of the 23rd ACM SIGSAC Conference on Computer and Communications Security (CCS)*, 2016, pp. 308–318.
- [31] S. L. Lauritzen and D. J. Spiegelhalter, "Local computations with probabilities on graphical structures and their application to expert systems," in *Journal of the Royal Statistical Society: Series B (Methodological)*, vol. 50, no. 2, 1988, pp. 157–194.
- [32] A. Ankan and A. Panda, "pgmpy: Probabilistic graphical models using Python," in *Proceedings of the 14th Python in Science Conference (SciPy)*, 2015.
- [33] I. A. Beinlich, H. J. Suermondt, R. M. Chavez, and G. F. Cooper, "The ALARM monitoring system: A case study with two probabilistic inference techniques for belief networks," in *Proceedings of the 2nd European Conference on Artificial Intelligence in Medicine*, 1989, pp. 247–256.

- [34] P. Moritz, R. Nishihara, S. Wang, A. Tumanov, R. Liaw, E. Liang, M. Elibol, Z. Yang, W. Paul, M. I. Jordan, and I. Stoica, “Ray: A distributed framework for emerging AI applications,” in *Proceedings of the 13th USENIX Symposium on Operating Systems Design and Implementation (OSDI)*, 2018, pp. 561–577.
- [35] S. Lachapelle, P. Brouillard, T. Deleu, and S. Lacoste-Julien, “Gradient-based neural DAG learning,” in *International Conference on Learning Representations (ICLR)*, 2020.
- [36] L. Li, D. Song, X. Fan, X. Qiu, and X. Zhang, “Hidden killer: Invisible textual backdoor attacks with syntactic trigger,” in *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics (ACL)*, 2021, pp. 443–453.