

RESEARCH ARTICLE

Representing high throughput expression profiles via perturbation barcodes reveals compound targets

Tracey M. Filzen¹, Peter S. Kutchukian², Jeffrey D. Hermes³, Jing Li⁴, Matthew Tudor⁵*

- 1 Medical Writing, Merck Research Laboratories, Upper Gwynedd, Pennsylvania, United States of America,
- 2 Informatics, Merck Research Laboratories, Boston, Massachusetts, United States of America, 3 Screening
- & Protein Sciences, Merck Research Laboratories, North Wales, Pennsylvania, United States of America,
 4 Screening and Compound Profiling, Merck Research Laboratories, Kenilworth, New Jersey, United States
- of America, 5 Informatics, Merck Research Laboratories, West Point, Pennsylvania, United States of America







Goal Representation learning for transcriptomic analysis.

Overview

Goal Representation learning for transcriptomic analysis.

Methods Metric Learning Network

Overview

Goal Representation learning for transcriptomic analysis.

Methods Metric Learning Network

Data L1000 Data, 2 Cell Lines, 3700 Compounds.

Overview

Goal Representation learning for transcriptomic analysis.

Methods Metric Learning Network

Data L1000 Data, 2 Cell Lines, 3700 Compounds.

Evaluation Efficacy in various predictive or clustering tasks.

Overview

Goal Representation learning for transcriptomic analysis.

Methods Metric Learning Network

Data L1000 Data, 2 Cell Lines, 3700 Compounds.

Evaluation Efficacy in various predictive or clustering tasks.


Code https://github.com/matudor/siamese

Gene Expression Data Overview

Transcriptomic/Gene expression data measures counts of transcription factors inside perturbed cells.


Gene Expression Data

Overview



Gene Expression Data

Overview





Gene expression vectors give a picture of the internal state of the cell at the time of measurement.

Datasets Genometry Data (private)

- Two cell lines (PC3, ME180).
- ▶ 3699 known or potential bioactive compounds used (6h).
- ▶ Some compounds had multiple replicates, others did not.
- ▶ 14 months total of data collection.
- ► After quality control, 7573 total L1000 vectors.

Datasets Genometry Data (private)

- ► Two cell lines (PC3, ME180).
- ▶ 3699 known or potential bioactive compounds used (6h).
- ▶ Some compounds had multiple replicates, others did not.
- ▶ 14 months total of data collection.
- ► After quality control, **7573** total L1000 vectors.

Datasets LINCS Data (public)

- ▶ 15 cell lines
- ▶ 273 compounds, 2 doses, 24h.
- Data more heavily pre-processed.
- ▶ Data available: https://www.ncbi.nlm.nih.gov/geo/query/acc.cgi?acc=GSE70138

Side Task Representation Learning

Biological replicates vary widely:

Side Task Representation Learning

Biological replicates vary widely: **z-scores**






Figure 1 (partial), Page 4

Side Task Representation Learning




Side Task Representation Learning



$$c = \operatorname{softplus} \left(1 - y \left(5 - \|\operatorname{H2}(\mathbf{x}_1) - \operatorname{H2}(\mathbf{x}_2)\|^2\right)\right).$$

Side Task Representation Learning



Comparitive Tasks

Median rank of replicates How many samples on average are closer to a query sample than its replicates?

Comparitive Tasks

Median rank of replicates How many samples on average are closer to a query sample than its replicates?

Distance by shared target How different are the distances between pairs sharing a target vs. those that do not (*t*-statistic).

Comparitive Tasks

Median rank of replicates How many samples on average are closer to a query sample than its replicates?

Distance by shared target How different are the distances between pairs sharing a target vs. those that do not (t-statistic).

Structural clustering overlap How similar are compound structure based clustering and expression based clustering?

Comparitive Tasks

- Median rank of replicates How many samples on average are closer to a query sample than its replicates?
- Distance by shared target How different are the distances between pairs sharing a target vs. those that do not (*t*-statistic).
- Structural clustering overlap How similar are compound structure based clustering and expression based clustering?
- Correlation of HTS profiles How similar are phenotypic screens to gene expression induced representations?

Comparitive Tasks

- Median rank of replicates How many samples on average are closer to a query sample than its replicates?
- Distance by shared target How different are the distances between pairs sharing a target vs. those that do not (*t*-statistic).
- Structural clustering overlap How similar are compound structure based clustering and expression based clustering?
- Correlation of HTS profiles How similar are phenotypic screens to gene expression induced representations?
- Promiscuity prediction How well do the various representations predict compound promiscuity?

Comparitive Tasks

Table 1. Performance of learned perturbation barcodes compared to z-scores and GSEA scores.

The state of the s						
metric	z-score	GSEA	perturbation barcode			
Median rank of replicates (of 7573)	225	72	24			
Distance by shared target, t statistic	-1	-38	-43			
Structural clustering overlap with expression clustering	0.01	0.03	0.17			
Correlation of HTS profiles with expression	0.04	0.02	0.12			
Promiscuity prediction by SVR, R ²	0.21	0.16	0.34			

Exploratory Evaluation




Figure 3, Page 11

Pros:

Broad evaluation

Pros:

- Broad evaluation
- Good choice of side task

Pros:

- Broad evaluation
- Good choice of side task

Cons:

Questions remain about network design.

Pros:

- Broad evaluation
- Good choice of side task

- Questions remain about network design.
- Main results on private data.

Pros:

- Broad evaluation
- Good choice of side task

- Questions remain about network design.
- Main results on private data.
- Small population size raises concerns about generalizability.

Pros:

- Broad evaluation
- Good choice of side task

- Questions remain about network design.
- Main results on private data.
- Small population size raises concerns about generalizability.
- Generalizability not really tested.

Conclusion



Tracey M. Filzen, Peter S. Kutchukian, Jeffrey D. Hermes, Jing Li, and Matthew Tudor. Representing high throughput expression profiles via perturbation barcodes reveals compound targets. PLOS Computational Biology, 13(2):e1005335, February 2017.