CS162
Operating Systems and Systems Programming
Lecture 12

Address Translation

March 5, 2018

Profs. Anthony D. Joseph & Jonathan Ragan-Kelley
http://cs162.eecs.Berkeley.edu

Midterm 1



MINIMUM	MEDIAN	MAXIMUM	MEAN	STD DEV
16.0	57.0	92.0	55.87	14.34

Administrivia

- Deadline for midterm regrade requests: this Friday, 3/9
- Project 1 final reports: tonight!
- Project 2, Homework 3: out now

Virtualizing Resources



- Physical Reality: Different Processes/Threads share the same hardware
  - Need to multiplex CPU (done)
  - Need to multiplex use of Memory (Today)
  - Need to multiplex disk and devices (later in term)
- Why worry about memory sharing?
  - The complete working state of a process and/or kernel is defined by its data in memory (and registers)
  - Consequently, two different processes cannot use the same memory
    - » Physics: two different data cannot occupy same locations in memory
  - May not want different threads to have access to each other's memory

Next Objective

- Dive deeper into the concepts and mechanisms of memory sharing and address translation
- Enabler of many key aspects of operating systems
  - Protection
  - Multi-programming
  - Isolation
  - Memory resource management
  - I/O efficiency
  - Sharing
  - Inter-process communication
  - Demand paging



- Today: Linking & Loading, Segmentation, Paging

Recall: Single and Multithreaded Processes



- Threads encapsulate concurrency
  - "Active" component of a process
- Address spaces encapsulate protection
  - Keeps buggy program from trashing the system
  - "Passive" component of a process

Important Aspects of Memory Multiplexing (1/2)

- Protection: prevent access to private memory of other processes
  - Kernel data protected from User programs
  - Programs protected from themselves
  - May want to give special behavior to different memory regions (Read Only, Invisible to user programs, etc)
- Controlled overlap: sometimes we want to share memory across processes.
  - E.g., communication across processes, share code
  - Need to control such overlap

Important Aspects of Memory Multiplexing (2/2)

- Translation:
  - Ability to translate accesses from one address space (virtual) to a different one (physical)
  - When translation exists, processor uses virtual addresses, physical memory uses physical addresses
  - Side effects:
    - » Can be used to give uniform view of memory to programs
    - » Can be used to provide protection (e.g., avoid overlap)
    - » Can be used to control overlap

Recall: Loading



Binding of Instructions and Data to Memory

Process view of memory

```
data1:   dw    32
         …
start:   lw    r1,0(data1)
         jal   checkit
loop:    addi r1, r1, -1
         bnz   r1, loop
         …
checkit: …
```

Physic

```
0x0300  0
  …
0x0900  8C2000C0
0x0904  0C000280
0x0908  2021FFFF
0x090C  14200242
 …
0x0A00
```

Assume 4byte words
0x300 = 4 * 0x0C0
0x0C0 = 0000 1100 0000
0x300 = 0011 0000 0000

Binding of Instructions and Data to Memory

Process view of memory

```
data1:   dw    32
         …
start:   lw    r1,0(data1)
         jal   checkit
loop:    addi r1, r1, -1
         bnz   r1, loop
         …
checkit: …
```

Physical addresses

```
0x0300  00000020
  …       …
0x0900  8C2000C0
0x0904  0C000280
0x0908  2021FFFF
0x090C  14200242
 …
0x0A00
```

Physical Memory

```
0x0000
0x0300  00000020
0x0900  8C2000C0
        0C000340
        2021FFFF
        14200242
0xFFFF
```


Second copy of program from previous example

Process view of memory

```
data1:   dw    32
         …
start:   lw    r1,0(data1)
         jal   checkit
loop:    addi r1, r1, -1
         bnz   r1, r0, loop
         …
checkit: …
```

Physical addresses

```
0x0300  00000020
  …       …
0x0900  8C2000C0
0x0904  0C000280
0x0908  2021FFFF
0x090C  14200242
 …
0x0A00
```

Physical Memory

```
0x0000
0x0300
0x0900  ?
        App X
0xFFFF
```

Need address translation!

Second copy of program from previous example



- One of many possible translations!
- Where does translation take place?
  Compile time, Link/Load time, or Execution time?

Multi-step Processing of a Program for Execution

- Preparation of a program for execution involves components at:
  - Compile time (i.e., "gcc")
  - Link/Load time (UNIX "ld" does link)
  - Execution time (e.g., dynamic libs)
- Addresses can be bound to final values anywhere in this path
  - Depends on hardware support
  - Also depends on operating system
- Dynamic Libraries
  - Linking postponed until execution
  - Small piece of code, *stub*, used to locate appropriate memory-resident library routine
  - Stub replaces itself with the address of the routine, and executes routine



Recall: Uniprogramming

- Uniprogramming (no Translation or Protection)
  - Application always runs at same place in physical memory since only one application at a time
  - Application can access any physical address



  - Application given illusion of dedicated machine by giving it reality of a dedicated machine

Multiprogramming (primitive stage)

- Multiprogramming without Translation or Protection
  - Must somehow prevent address overlap between threads





  - Use Loader/Linker: Adjust addresses while program loaded into memory (loads, stores, jumps)
    - » Everything adjusted to memory location of program
    - » Translation done by a linker-loader (relocation)
    - » Common in early days (… till Windows 3.x, 95?)
- With this solution, no protection: bugs in any program can cause other programs to crash or even the OS

Multiprogramming (Version with Protection)

- Can we protect programs from each other without translation?



  - Yes: use two special registers *BaseAddr* and *LimitAddr* to prevent user from straying outside designated area
    - » If user tries to access an illegal address, cause an error
  - During switch, kernel loads new base/limit from PCB (Process Control Block)
    - » User not allowed to change base/limit registers

Recall: General Address translation



- Recall: Address Space:
  - All the addresses and state a process can touch
  - Each process and kernel has different address space
- Consequently, two views of memory:
  - View from the CPU (what program sees, virtual memory)
  - View from memory (physical memory)
  - Translation box (MMU) converts between the two views
- Translation makes it much easier to implement protection
  - If task A cannot even gain access to task B's data, no way for A to adversely affect B
- With translation, every program can be linked/loaded into same region of virtual address space

Simple Example: Base and Bounds (CRAY-1)



- Could use base/bounds for dynamic address translation – translation happens at execution:
  - Alter address of every load/store by adding "base"
  - Generate error if address bigger than limit
- This gives program the illusion that it is running on its own dedicated machine, with memory starting at 0
  - Program gets continuous region of memory
  - Addresses within program do not have to be relocated when program placed in different region of DRAM

Issues with Simple B&B Method



- Fragmentation problem over time
  - Not every process is same size ➔ memory becomes fragmented
- Missing support for sparse address space
  - Would like to have multiple chunks/program (Code, Data, Stack)
- Hard to do inter-process sharing
  - Want to share code segments when possible
  - Want to share memory between processes
  - Helped by providing multiple segments per process

More Flexible Segmentation



- Logical View: multiple separate segments
  - Typical: Code, Data, Stack
  - Others: memory sharing, etc
- Each segment is given region of contiguous memory
  - Has a base and limit
  - Can reside anywhere in physical memory

Implementation of Multi-Segment Model



- Segment map resides in processor
  - Segment number mapped into base/limit pair
  - Base added to offset to generate physical address
  - Error check catches offset out of range
- As many chunks of physical memory as entries
  - Segment addressed by portion of virtual address
  - However, could be included in instruction instead:
    - » x86 Example: mov [es:bx],ax.
- What is "V/N" (valid / not valid)?
  - Can mark segments as invalid; requires check as well

Intel x86 Special Registers

RPL = Requestor Privilege Level
TI = Table Indicator
(0 = GDT, 1 = LDT)
Index = Index into table

Protected Mode segment selector

Typical Segment Register
Current Priority is RPL
Of Code Segment (CS)

80386 Special Registers



Example: Four Segments (16 bit addresses)

Virtual Address Format

Seg ID #	Base	Limit
0 (code)	0x4000	0x0800
1 (data)	0x4800	0x1400
2 (shared)	0xF000	0x1000
3 (stack)	0x0000	0x3000



Virtual Address Space



Physical Address Space

Example: Four Segments (16 bit addresses)



Seg ID #	Base	Limit
0 (code)	0x4000	0x0800
1 (data)	0x4800	0x1400
2 (shared)	0xF000	0x1000
3 (stack)	0x0000	0x3000

Example: Four Segments (16 bit addresses)



Seg ID #	Base	Limit
0 (code)	0x4000	0x0800
1 (data)	0x4800	0x1400
2 (shared)	0xF000	0x1000
3 (stack)	0x0000	0x3000

Example: Four Segments (16 bit addresses)



Seg ID #	Base	Limit
0 (code)	0x4000	0x0800
1 (data)	0x4800	0x1400
2 (shared)	0xF000	0x1000
3 (stack)	0x0000	0x3000

Example of Segment Translation (16b address)

```
0x240   main:   la $a0, varx
0x244           jal strlen
  …               …
0x360   strlen: li   $v0, 0  ;count
0x364   loop:   lb   $t0, ($a0)
0x368           beq  $r0,$t0, done
  …               …
0x4050  varx    dw   0x314159
```

Seg ID #	Base	Limit
0 (code)	0x4000	0x0800
1 (data)	0x4800	0x1400
2 (shared)	0xF000	0x1000
3 (stack)	0x0000	0x3000

Let's simulate a bit of this code to see what happens (PC=0x240):

1. Fetch 0x240 (0000 0010 0100 0000). Virtual segment #? 0; Offset? 0x240
   Physical address? Base=0x4000, so physical addr=0x4240
   Fetch instruction at 0x4240. Get "la $a0, varx"
   Move 0x4050 → $a0, Move PC+4→PC

Example of Segment Translation (16b address)

```
0x240   main:   la $a0, varx
0x244           jal strlen
  …               …
0x360   strlen: li   $v0, 0  ;count
0x364   loop:   lb   $t0, ($a0)
0x368           beq  $r0,$t0, done
  …               …
0x4050  varx    dw   0x314159
```

Seg ID #	Base	Limit
0 (code)	0x4000	0x0800
1 (data)	0x4800	0x1400
2 (shared)	0xF000	0x1000
3 (stack)	0x0000	0x3000

Let's simulate a bit of this code to see what happens (PC=0x240):

1. Fetch 0x240. Virtual segment #? 0; Offset? 0x240
   Physical address? Base=0x4000, so physical addr=0x4240
   Fetch instruction at 0x4240. Get "la $a0, varx"
   Move 0x4050 → $a0, Move PC+4→PC
2. Fetch 0x244. Translated to Physical=0x4244. Get "jal strlen"
   Move 0x0248 → $ra (return address!), Move 0x0360 → PC

Example of Segment Translation (16b address)

```
0x240   main:   la $a0, varx
0x244           jal strlen
  …               …
0x360   strlen: li   $v0, 0  ;count
0x364   loop:   lb   $t0, ($a0)
0x368           beq  $r0,$t0, done
  …               …
0x4050  varx    dw   0x314159
```

Seg ID #	Base	Limit
0 (code)	0x4000	0x0800
1 (data)	0x4800	0x1400
2 (shared)	0xF000	0x1000
3 (stack)	0x0000	0x3000

Let's simulate a bit of this code to see what happens (PC=0x240):

1. Fetch 0x240. Virtual segment #? 0; Offset? 0x240
   Physical address? Base=0x4000, so physical addr=0x4240
   Fetch instruction at 0x4240. Get "la $a0, varx"
   Move 0x4050 → $a0, Move PC+4→PC
2. Fetch 0x244. Translated to Physical=0x4244. Get "jal strlen"
   Move 0x0248 → $ra (return address!), Move 0x0360 → PC
3. Fetch 0x360. Translated to Physical=0x4360. Get "li $v0, 0"
   Move 0x0000 → $v0, Move PC+4→PC

Example of Segment Translation (16b address)

```
0x0240  main:   la $a0, varx
0x0244          jal strlen
  …               …
0x0360  strlen: li   $v0, 0  ;count
0x0364  loop:   lb   $t0, ($a0)
0x0368          beq  $r0,$t0, done
  …               …
0x4050  varx    dw   0x314159
```

Seg ID #	Base	Limit
0 (code)	0x4000	0x0800
1 (data)	0x4800	0x1400
2 (shared)	0xF000	0x1000
3 (stack)	0x0000	0x3000

Let's simulate a bit of this code to see what happens (PC=0x0240):

1. Fetch 0x0240. Virtual segment #? 0; Offset? 0x240
   Physical address? Base=0x4000, so physical addr=0x4240
   Fetch instruction at 0x4240. Get "la $a0, varx"
   Move 0x4050 → $a0, Move PC+4→PC
2. Fetch 0x0244. Translated to Physical=0x4244. Get "jal strlen"
   Move 0x0248 → $ra (return address!), Move 0x0360 → PC
3. Fetch 0x0360. Translated to Physical=0x4360. Get "li $v0, 0"
   Move 0x0000 → $v0, Move PC+4→PC
4. Fetch 0x0364. Translated to Physical=0x4364. Get "lb $t0, ($a0)"
   Since $a0 is 0x4050, try to load byte from 0x4050
   Translate 0x4050 (0100 0000 0101 000). Virtual segment #? 1; Offset? 0x50
   Physical address? Base=0x4800, Physical addr = 0x4850,
   Load Byte from 0x4850→$t0, Move PC+4→PC

BREAK

Observations about Segmentation

- Virtual address space has holes
  - Segmentation efficient for sparse address spaces
  - A correct program should never address gaps (except as mentioned in moment)
    - » If it does, trap to kernel and dump core
- When it is OK to address outside valid range?
  - This is how the stack and heap are allowed to grow
  - For instance, stack takes fault, system automatically increases size of stack
- Need protection mode in segment table
  - For example, code segment would be read-only
  - Data and stack would be read-write (stores allowed)
  - Shared segment could be read-only or read-write
- What must be saved/restored on context switch?
  - Segment table stored in CPU, not in memory (small)
  - Might store all of processes memory onto disk when switched (called "swapping")

Problems with Segmentation

- Must fit variable-sized chunks into physical memory
- May move processes multiple times to fit everything
- Limited options for swapping to disk
- Fragmentation: wasted space
  - External: free gaps between allocated chunks
  - Internal: don't need all memory within allocated chunks

Recall: General Address Translation



Paging: Physical Memory in Fixed Size Chunks

- Solution to fragmentation from segments?
  - Allocate physical memory in fixed size chunks ("pages")
  - Every chunk of physical memory is equivalent
    - » Can use simple vector of bits to handle allocation:
      `00110001110001101 … 110010`
    - » Each bit represents page of physical memory
      `1` ⇒ allocated, `0` ⇒ free
- Should pages be as big as our previous segments?
  - No: Can lead to lots of internal fragmentation
    - » Typically have small pages (1K-16K)
  - Consequently: need multiple pages/segment

How to Implement Paging?



- Page Table (One per process)
  - Resides in physical memory
  - Contains physical page and permission for each virtual page
    - » Permissions include: Valid bits, Read, Write, etc
- Virtual address mapping
  - Offset from Virtual address copied to Physical Address
    - » Example: 10 bit offset ⇒ 1024-byte pages
  - Virtual page # is all remaining bits
    - » Example for 32-bits: 32-10 = 22 bits, i.e. 4 million entries
    - » Physical page # copied from table into physical address
  - Check Page Table bounds and permissions

Simple Page Table Example



What about Sharing?



Summary: Paging



Summary: Paging



Summary: Paging



Page Table Discussion

- What needs to be switched on a context switch?
  - Page table pointer and limit
- Analysis
  - Pros
    - » Simple memory allocation
    - » Easy to share
  - Con: What if address space is sparse?
    - » E.g., on UNIX, code starts at 0, stack starts at (2^{31}-1)
    - » With 1K pages, need 2 million page table entries!
  - Con: What if table really big?
    - » Not all pages used all the time ⇒ would be nice to have working set of page table in memory
- How about multi-level paging or combining paging and segmentation?

Fix for sparse address space: The two-level page table



- Tree of Page Tables
- Tables fixed size (1024 entries)
  - On context-switch: save single PageTablePtr register
- Valid bits on Page Table Entries
  - Don't need every 2nd-level table
  - Even when exist, 2nd-level tables can reside on disk if not in use

Summary: Two-Level Paging



Summary: Two-Level Paging



Multi-level Translation: Segments + Pages

- What about a tree of tables?
  - Lowest level page table ⇒ memory still allocated with bitmap
  - Higher levels often segmented
- Could have any number of levels. Example (top segment):



- What must be saved/restored on context switch?
  - Contents of top-level segment registers (for this example)
  - Pointer to top-level table (page table)

What about Sharing (Complete Segment)?



Multi-level Translation Analysis

- Pros:
  - Only need to allocate as many page table entries as we need for application
    - » In other wards, sparse address spaces are easy
  - Easy memory allocation
  - Easy Sharing
    - » Share at segment or page level (need additional reference counting)
- Cons:
  - One pointer per page (typically 4K – 16K pages today)
  - Page tables need to be contiguous
    - » However, previous example keeps tables to exactly one page in size
  - Two (or more, if >2 levels) lookups per reference
    - » Seems very expensive!

Summary

- Segment Mapping
  - Segment registers within processor
  - Segment ID associated with each access
    - » Often comes from portion of virtual address
    - » Can come from bits in instruction instead (x86)
  - Each segment contains base and limit information
    - » Offset (rest of address) adjusted by adding base
- Page Tables
  - Memory divided into fixed-sized chunks of memory
  - Virtual page number from virtual address mapped through page table to physical page number
  - Offset of virtual address same as physical address
  - Large page tables can be placed into virtual memory
- Multi-Level Tables
  - Virtual address mapped to series of tables
  - Permit sparse population of address space