

CSI62
Operating Systems and
Systems Programming
Lecture 19

File Systems (Con't),
MMAP


April 4th, 2018

Profs. Anthony D. Joseph & Jonathan Ragan-Kelley

<http://cs162.eecs.Berkeley.edu>

Recall: So What About a “Real” File System?

- Meet the inode:



4/4/18

CSI62 © UCB Spring 2018

Lec 19.2

Recall: Unix File System (1/2)

- Original inode format appeared in BSD 4.1
 - Berkeley Standard Distribution Unix
 - Part of your heritage!
 - Similar structure for Linux Ext2/3
- File Number is index into inode arrays
- Multi-level index structure
 - Great for little and large files
 - Asymmetric tree with fixed sized blocks

4/4/18

CSI62 © UCB Spring 2018

Lec 19.4

Recall: Unix File System (2/2)

- Metadata associated with the file
 - Rather than in the directory that points to it
- UNIX Fast File System (FFS) BSD 4.2 Locality Heuristics:
 - Block group placement
 - Reserve space
- Scalable directory structure

4/4/18

CSI62 © UCB Spring 2018


Lec 19.5

Recall: Data Storage

- Small files: 12 pointers direct to data blocks

Direct pointers

4kB blocks \Rightarrow sufficient for files up to 48KB



4/4/18


CSI62 © UCB

Recall: Data Storage

- Large files: 1,2,3 level indirect pointers

Indirect pointers

- point to a disk block containing only pointers
 - 4 kB blocks \Rightarrow 1024 ptrs
 \Rightarrow 4 MB @ level 2
 \Rightarrow 4 GB @ level 3
 \Rightarrow 4 TB @ level 4



CSI62 © UCB Spring 2018

Lec 19.8

UNIX BSD 4.2 (1984) (1/2)

- Same as BSD 4.1 (same file header and triply indirect blocks), except incorporated ideas from Cray Operating System:
 - Uses bitmap allocation in place of freelist
 - Attempt to allocate files contiguously
 - 10% reserved disk space
 - Skip-sector positioning (mentioned later)

4/4/18

CSI62 © UCB Spring 2018

Lec 19.9

UNIX BSD 4.2 (1984) (2/2)

- Problem: When create a file, don't know how big it will become (in UNIX, most writes are by appending)
 - How much contiguous space do you allocate for a file?
 - In BSD 4.2, just find some range of free blocks
 - Put each new file at the front of different range
 - To expand a file, you first try successive blocks in bitmap, then choose new range of blocks
 - Also in BSD 4.2: store files from same directory near each other
- Fast File System (FFS)
 - Allocation and placement policies for BSD 4.2


4/4/18

CSI62 © UCB Spring 2018

Lec 19.10

Attack of the Rotational Delay


- Problem 2: Missing blocks due to rotational delay
 - Issue: Read one block, do processing, and read next block. In meantime, disk has continued turning; missed next block! Need 1 revolution/block!



- Solution 1: Skip sector positioning (“interleaving”)
 - » Place the blocks from one file on every other block of a track: give time for processing to overlap rotation
 - » Can be done by OS or in modern drives by the disk controller

Attack of the Rotational Delay

- Problem 2: Missing blocks due to rotational delay
 - Issue: Read one block, do processing, and read next block. In meantime, disk has continued turning; missed next block! Need 1 revolution/block!



- Solution 2: Read ahead: read next block right after first, even if application hasn't asked for it yet
 - » This can be done either by OS (read ahead)
 - » By disk itself (track buffers) - many disk controllers have internal RAM that allows them to read a complete track
- Note: Modern disks + controllers do many things “under the covers”
 - Track buffers, elevator algorithms, bad block filtering

Where are inodes Stored?


- In early UNIX and DOS/Windows' FAT file system, headers stored in special array in outermost cylinders
- Header not stored anywhere near the data blocks
 - To read a small file, seek to get header, seek back to data
- Fixed size, set when disk is formatted
 - At formatting time, a fixed number of inodes are created
 - Each is given a unique number, called an “inumber”

Where are inodes Stored?

- Later versions of UNIX moved the header information to be closer to the data blocks
 - Often, inode for file stored in same “cylinder group” as parent directory of the file (makes an **ls** of that directory run fast)
- Pros:
 - UNIX BSD 4.2 puts bit of file header array on many cylinders
 - For small directories, can fit all data, file headers, etc. in same cylinder \Rightarrow no seeks!
 - File headers much smaller than whole block (a few hundred bytes), so multiple headers fetched from disk at same time
 - Reliability: whatever happens to the disk, you can find many of the files (even if directories disconnected)
- Part of the Fast File System (FFS)
 - General optimization to avoid seeks

4.2 BSD Locality: Block Groups

- File system volume is divided into a set of block groups
 - Close set of tracks
- Data blocks, metadata, and free space interleaved within block group
 - Avoid huge seeks between user data and system structure
- Put directory and its files in common block group




4/4/18

CSI62 © UCB Spring 2018

Lec 19.15

4.2 BSD Locality: Block Groups

- First-Free allocation of new file blocks
 - To expand file, first try successive blocks in bitmap, then choose new range of blocks
 - Few little holes at start, big sequential runs at end of group
 - Avoids fragmentation
 - Sequential layout for big files
- Important: keep 10% or more free!
 - Reserve space in the Block Group




4/4/18

CSI62 © UCB Spring 2018

Lec 19.16

UNIX 4.2 BSD FFS First Fit Block Allocation



4/4/18

CSI62 © UCB Spring 2018

Lec 19.17

UNIX 4.2 BSD FFS

- Pros
 - Efficient storage for both small and large files
 - Locality for both small and large files
 - Locality for metadata and data
 - No defragmentation necessary!
- Cons
 - Inefficient for tiny files (a 1 byte file requires both an inode and a data block)
 - Inefficient encoding when file is mostly contiguous on disk
 - Need to reserve 10-20% of free space to prevent fragmentation

4/4/18

CSI62 © UCB Spring 2018

Lec 19.18

Administrivia

- Midterm 2 regrade requests now open (until next Monday, April 9)
- Project 2 final report due tonight at 11:59PM
- Project 3 design doc due next Wed 4/11 at 11:59PM

4/4/18

CS162 © UCB Spring 2018

Lec 19.19

BREAK


4/4/18

CS162 © UCB Spring 2018

Lec 19.20

Linux Example: Ext2/3 Disk Layout

- Disk divided into block groups
 - Provides locality
 - Each group has two block-sized bitmaps (free blocks/inodes)
 - Block sizes settable at format time: 1K, 2K, 4K, 8K...
- Actual inode structure similar to 4.2 BSD
 - with 12 direct pointers
- Ext3: Ext2 with Journaling
 - Several degrees of protection with comparable overhead



• Example: create a file1.dat under /dir1/ in Ext3


4/4/18

CS162 © UCB Spring 2018

Lec 19.21

A bit more on directories

- Stored in files, can be read, but typically don't
 - System calls to access directories
 - **open / creat** traverse the structure
 - **mkdir / rmdir** add/remove entries
 - **link / unlink (rm)**
 - » Link existing file to a directory
 - Not in FAT!
 - » Forms a DAG
- When can file be deleted?
 - Maintain ref-count of links to the file
 - Delete after the last reference is gone
- libc support
 - `DIR * opendir (const char *dirname)`
 - `struct dirent * readdir (DIR *dirstream)`
 - `int readdir_r (DIR *dirstream, struct dirent *entry, struct dirent **result)`



4/4/18

CS162 © UCB Spring 2018

Lec 19.22

Links

- Hard link
 - Sets another directory entry to contain the file number for the file
 - Creates another name (path) for the file
 - Each is “first class”
- Soft link or Symbolic Link or Shortcut
 - Directory entry contains the path and name of the file
 - Map one name to another name


4/4/18

CSI62 © UCB Spring 2018

Lec 19.23

Large Directories: B-Trees (dirhash)

in FreeBSD, NetBSD, OpenBSD



4/4/18

CSI62 © UCB Spring 2018

Lec 19.24

NTFS

- New Technology File System (NTFS)
 - Default on Microsoft Windows systems
- Variable length extents
 - Rather than fixed blocks
- Everything (almost) is a sequence of <attribute:value> pairs
 - Meta-data and data
- Mix direct and indirect freely
- Directories organized in B-tree structure by default

4/4/18


CSI62 © UCB Spring 2018

Lec 19.25

NTFS

- Master File Table
 - Database with flexible 1KB metadata/data entries (~12.5% of disk)
 - Variable-sized attribute records (data or metadata)
 - Extend with variable depth tree (non-resident)

- Extents – variable length contiguous regions
 - Block pointers cover runs of blocks
 - Similar approach in Linux (ext4)
 - File create can provide hint as to size of file
- Journaling for reliability
 - Discussed later




4/4/18

CSI62 © UCB Spring 2018

Lec 19.26

NTFS Small File

Master File Table




4/4/18

CSI62 © UCB Spring 2018

Lec 19.27

NTFS Medium File

Master File Table




4/4/18

CSI62 © UCB Spring 2018

Lec 19.28

NTFS Multiple Indirect Blocks




4/4/18

CSI62 © UCB Spring 2018

Lec 19.29

Master File Table



4/4/18

CSI62 © UCB Spring 2018

Lec 19.30

Memory Mapped Files


- Traditional I/O involves explicit transfers between buffers in process address space to/from regions of a file
 - This involves multiple copies into caches in memory, plus system calls
- What if we could “map” the file directly into an empty region of our address space
 - Implicitly “page it in” when we read it
 - Write it and “eventually” page it out
- Executable files are treated this way when we exec the process!!

4/4/18

CSI62 © UCB Spring 2018

Lec 19.31

Recall: Who Does What, When?




4/4/18

CSI62 © UCB Spring 2018

Lec 19.32

Using Paging to mmap() Files



4/4/18

CSI62 © UCB Spring 2018

Lec 19.33

mmap() system call

```

MMAP(2)                                BSD System Calls Manual                                MMAP(2)

NAME
    mmap -- allocate memory, or map files or devices into memory

LIBRARY
    Standard C Library (libc, -lc)

SYNOPSIS
    #include <sys/mman.h>

    void *
    mmap(void *addr, size_t len, int prot, int flags, int fd,
        off_t offset);

DESCRIPTION
    The mmap() system call causes the pages starting at addr and continuing
    for at most len bytes to be mapped from the object described by fd,
    starting at byte offset offset. If offset or len is not a multiple of
    the system page size, the behavior is undefined.
    
```

- May map a specific region or let the system find one for you
 - Tricky to know where the holes are
- Used both for manipulating files and for sharing between processes

4/4/18

CSI62 © UCB Spring 2018

Lec 19.34

An mmap() Example

```
#include <sys/mman.h> /* also stdio.h, stdlib.h, string.h,fcntl.h,unistd.h */
int something = 162;

int main (int argc, char *argv[]) {
    int myfd;
    char *mfile;

    printf("Data at: %16lx\n", (long) something);
    printf("Heap at : %16lx\n", (long) something);
    printf("Stack at: %16lx\n", (long) something);

    /* Open the file */
    myfd = open(argv[1], O_RDWR | O_CREAT, 0666);
    if (myfd < 0) { perror("open failed"); return 1; }

    /* map the file */
    mfile = mmap(0, 10000, PROT_READ|PROT_WRITE, MAP_SHARED, myfd, 0);
    if (mfile == MAP_FAILED) { perror("mmap failed"); return 1; }

    printf("mmap at : %16lx\n", (long) something);

    puts(mfile);
    strcpy(mfile+20,"Let's write over");
    close(myfd);
    return 0;
}
```

```
$ ./mmap test
Data at:      105d63058
Heap at :     7f8a33c04b70
Stack at:     7fff59e9db10
mmap at :     105d97000
This is line one
This is line two
This is line three
This is line four
```

```
$ cat test
This is line one
This is line two
This is line three
This is line four
```

4/4/18

CSI62 © UCB Spring 2018

Lec 19.35

File System Summary (1/2)

- File System:
 - Transforms blocks into Files and Directories
 - Optimize for size, access and usage patterns
 - Maximize sequential access, allow efficient random access
 - Projects the OS protection and security regime (UGO vs ACL)
- File defined by header, called “inode”
- Naming: translating from user-visible names to actual sys resources
 - Directories used for naming for local file systems
 - Linked or tree structure stored in files
- Multilevel Indexed Scheme
 - inode contains file info, direct pointers to blocks, indirect blocks, doubly indirect, etc..
 - NTFS: variable extents not fixed blocks, tiny files data is in header

4/4/18

CSI62 © UCB Spring 2018

Lec 19.36

File System Summary (2/2)

- 4.2 BSD Multilevel index files
 - Inode contains ptrs to actual blocks, indirect blocks, double indirect blocks, etc.
 - Optimizations for sequential access: start new files in open ranges of free blocks, rotational optimization
- File layout driven by freespace management
 - Integrate freespace, inode table, file blocks and dirs into block group
- Deep interactions between mem management, file system, sharing
 - **mmap()**: map file or anonymous segment to memory

4/4/18

CSI62 © UCB Spring 2018

Lec 19.37