1. a)
$$W^{-nk} + W^{-(N-n)k} = W^{-nk} + W^{-Nk}W^{nk}$$

$$= W^{-nk} + W^{nk} = e^{\frac{-2\pi i nk}{N}} + e^{\frac{2\pi i nk}{N}}$$

$$= \cos(\frac{-2\pi nk}{N}) + i\sin(\frac{-2\pi nk}{N}) + \cos(\frac{2\pi nk}{N}) + i\sin(\frac{2\pi nk}{N})$$

$$= \cos(\frac{2\pi nk}{N}) - i\sin(\frac{2\pi nk}{N}) + \cos(\frac{2\pi nk}{N}) + i\sin(\frac{2\pi nk}{N})$$

$$= 2\cos(\frac{2\pi nk}{N})$$

(Assignment 4 question)

$$F_{k} = \sum_{n=0}^{N-1} f_{n} W^{-nk} = \sum_{n=0}^{N_{2}-1} f_{n} W^{-nk} + \sum_{n=N_{2}}^{N-1} f_{n} W^{-nk}$$

$$= \sum_{n=0}^{N_{2}-1} f_{n} W^{-nk} + \sum_{n=0}^{N} f_{N-n} W^{-(N-n)k}$$

$$= \sum_{n=0}^{N_{2}-1} f_{n} W^{-nk} + f_{n} W^{-(N-n)k}$$

$$= \sum_{n=0}^{N_{2}-1} f_{n} (W^{-nk} + W^{-(N-n)k})$$

$$= \sum_{n=0}^{N_{2}-1} f_{n} (W^{-nk} + W^{-(N-n)k})$$

$$= \sum_{n=0}^{N_{2}-1} 2 f_{n} \cos \left(\frac{2\pi nk}{N}\right)$$

We can clearly see that F_k is real.

2.
$$F_{2k} = \sum_{n=0}^{N-1} f_n W^{-2nk} = \sum_{n=\frac{N}{4}}^{\frac{3N}{4}-1} W^{-2nk}$$

$$= \frac{W^{k(2-\frac{3N}{2})}(W^{Nk}-1)}{W^{2k}-1}$$

- **3.** We have that $W^0 = 1$, so F_0 is just equal to the <u>sum</u> of the f_i s.
- **4.** Let F_k be the DFT of the original signal $f_0 \dots f_{N-1}$. Let G_k be the DFT of the new signal.

For k = 0:

For $1 \le k \le N - 1$:

$$G_{k} = \sum_{n=0}^{N-1} (f_{n} + c) W^{-nk} = F_{k} + c \sum_{n=0}^{N-1} W^{-nk}$$

$$= F_{k} + c \left(\frac{1 - W^{-Nk}}{1 - W^{-k}} \right)$$

$$= F_{k}$$

5. i.
$$F[k] = (6, -1 - i, 0, -1 + i)$$

ii. F[k] = (8, -2, 0, -2)I have no idea why it's real

6.
$$\frac{1}{N}\sum_{k=0}^{N-1}F_kF_k = \sum_{n=0}^{N-1}f_nf_n$$
 Correct version that our slides cover

$$\frac{1}{N} \sum_{k=0}^{N-1} F_k F_k = \frac{1}{N} \sum_{k=0}^{N-1} F_k \sum_{n=0}^{N-1} F_k \sum_{n=0$$

Properties of Fourier transform:

- Signal that is purely real has $F_k = \overline{F_{N-k}}$
- Signal that is purely imaginary has $F_k = -\overline{F_{N-k}}$

Our algorithm works as follows. We multiply the second signal by j and add it to the first. Then we take the FFT of this sum.

The FFT of the first signal is $F'_k = \frac{F_k + \overline{F_{N-k}}}{2}$. The contributions of the first (real) signal will add, and the contributions of the second (imaginary) signal will cancel out.

The FFT if the second signal is $F''_k = j \frac{F_k - \overline{F_{N-k}}}{2}$. The contributions of the first (real) signal will cancel out, and the contributions of the second (imaginary) signal will add. We also need to multiply by j, since our FFT has real and imaginary parts swapped (since we multiplied our second signal by j originally).