

Navigating Risk and Fault Management: Insights into Space Environment Subsystems

Elena Felix

Department of Aerospace Engineering, California Polytechnic State University

Aero 449: Spacecraft Design III

May 12, 2024

I. Introduction

Ensuring mission success in the aerospace industry demands meticulous risk management and fault tolerance strategies, particularly when venturing into the unforgiving environment of space. Rectifying issues with spacecraft once they're in orbit presents formidable challenges, underscoring the critical role of fault management systems engineering. From passive redundancies to active fault mitigation measures, a diverse toolkit is employed to navigate the complexities of space missions. Central to this endeavor is the space environments subsystem, pivotal for safeguarding spacecraft against the rigors of space.

II. Aerospace Industry Approaches to Risk Management and Fault Tolerance

In the aerospace industry, fault-tolerant approaches are indispensable for navigating the challenges posed by space environments. The specific challenges presented by the space environment, including radiation, temperature variations, and orbital dynamics, necessitate careful consideration in satellite design. Mission planners often prioritize trajectories and orbits that minimize exposure to high levels of radiation or trapped electrons, without compromising mission objectives. However, when avoidance is not feasible, techniques such as radiation-hardened components, design diversity, and fault-tolerant systems are implemented to mitigate risks. Analysis of spacecraft failure data, as documented in the *Effective Fault Management Guidelines* by the Aerospace Corporation, underscores the significance of systemic faults, where considering space environment failures as design errors accounts for 60% of failures [2].

To fortify spacecraft against worst-case scenarios, extensive environmental testing simulates the harsh conditions of space orbits. This rigorous testing subjects electronic devices to extreme temperatures, vacuum, radiation, and vibration, validating their resilience. Designing spacecraft with ample margins ensures resilience to uncertainties in space, bolstered by safety factors applied to structural elements, thermal control systems, and power budgets [3]. Contingency plans are crafted for potential environmental hazards, empowering rapid response and recovery.

Careful mission planning and orbit selection consider the specific environmental conditions that the satellite will encounter during its operational lifetime. Choosing orbits with lower radiation levels or avoiding high-risk regions minimizes exposure to environmental hazards. Adaptive control systems adjust spacecraft operations in real-time based on environmental conditions, optimizing performance and mitigating risks autonomously. These systems adjust power allocation, orientation, and communication protocols to respond to changing space environment conditions, ensuring mission success in the face of environmental challenges.

III. Risk Identification

Managing risks in aerospace is paramount, with every mission representing a single opportunity for success. Fault management systems engineering plays a pivotal role, offering a spectrum of mitigation techniques ranging from passive redundancies to active protection measures. Within this framework, the space environments subsystem stands out as pivotal, safeguarding the

spacecraft against the rigors of space. Its significance lies in shielding against extreme conditions such as temperature variations, vacuum, radiation, and micrometeoroid impacts, all of which pose threats to mission success and longevity which in the entire spacecraft design is the biggest risk item [1].

The environmental subsystem occupies a central position in spacecraft design in mitigating the damaging effects of space's extreme conditions from temperature fluctuations to vacuum exposure. By mitigating component degradation over time, it ensures the extended operation of critical systems. Moreover, beyond technical considerations, addressing environmental risks through the environment subsystem is indispensable for managing overall mission risk, minimizing the likelihood of system failures, and increasing mission success probability. Failure to adequately address environmental challenges can result in costly redesigns, delays, or mission cancellations.

When assessing risks within the environment subsystem, it's essential to take a multifaceted approach, considering various categories such as technical, schedule, cost, and regulatory compliance. While this section outlines 10 potential risks, it's important to note that these may not encompass all risks pertaining to the subsystem.

Technical risks primarily stem from the challenges posed by space's harsh conditions. These include (1) extreme temperature variations, (2) space radiation exposure, (3) electromagnetic interference, (4) micrometeoroid impacts, and (5) atomic oxygen erosion. Each of these risks poses distinct threats to spacecraft integrity and functionality while in the operational environment.

Scheduling risks, on the other hand, pertain to challenges in (6) integrating the environment subsystem with other spacecraft systems, potentially leading to schedule slippage. Additionally, (7) contamination risks during integration processes can delay launch preparations, further impacting project timelines.

Cost-related risks involve trade-offs between expenses and mission requirements, such as the (8) high cost of radiation-hardening electronic devices and the (9) mass budget implications of implementing radiation shielding materials.

Regulatory compliance risks arise from (10) changes in environmental regulations or licensing requirements, which may necessitate costly modifications to meet new industry standards. Addressing these risks proactively through effective risk management strategies is essential for ensuring the success of spacecraft design projects in the face of complex environmental challenges and mitigating the possibility of failure [1].

IV. Risk Mitigation Plan

In the following section, the discussion will focus on the risks posed by space radiation, micrometeoroids, and space debris to spacecraft systems.

Space radiation, particularly ionizing radiation, presents one of the most significant risks in spacecraft systems. This radiation has caused anomalies and failures in missions like the Orion (Artemis I) and James Webb Space Telescope (JWST), resulting in communication delays and software timeouts [4]. Ionizing radiation consists of particles or electromagnetic waves with sufficient energy to ionize atoms, potentially damaging electronic components. Sources of ionizing radiation in space environments include solar particle events, cosmic rays, and trapped radiation belts.

To mitigate these effects, shielding emerges as the primary and most common mitigation technique. Materials such as lead, polyethylene, or boronated polyethylene are used to attenuate ionizing radiation. This is accomplished while considering a radiation design margin (RDM), defined as the ratio of the part or component radiation capability in the given application to the expected radiation environment at the part or component location during the mission [5]. An RDM value of 2, for instance, indicates that the hardware can withstand twice the predicted radiation. It's crucial to note that an RDM of 2 should not be interpreted as providing a 100 percent margin, although it has been effective on missions like Voyager.

Boronated polyethylene is often favored when aiming for an RDM of 2 to attenuate ionizing radiation. It combines the shielding properties of polyethylene with the neutron-absorbing properties of boron, offering effective radiation attenuation while minimizing material weight and thickness [6]. Moreover, boronated polyethylene is less dense than lead, making it more suitable for aerospace applications where weight considerations are critical.

Additionally, including redundancies of sensitive communication devices that can switch on when detecting failure, using radiation dosimetry to monitor radiation levels to anticipate faults better, and implementing radiation hardening are further techniques to protect electronic equipment [5]. However, radiation hardening comes with a significant financial cost and is only employed when no better alternative is available.

Another significant risk to consider in spacecraft design is the potential impact of micrometeoroids and space debris. Even tiny particles can cause substantial damage at high velocities. To mitigate the risks associated with these impacts, a comprehensive approach is necessary.

The first step is conducting a thorough risk assessment to evaluate the probability of potential impacts along the spacecraft's orbital path. This assessment should consider factors such as the likelihood of impacts, potential damage to critical systems, and the consequences of collisions. Based on this assessment, critical design parameters can be determined.

One mitigation strategy involves the design and implementation of shielding mechanisms to protect the spacecraft from impacts. Techniques such as Whipple shields, Kevlar, or other composite materials can be employed to absorb or deflect the kinetic energy of micrometeoroids and space debris. One popular shielding technique is the use of a multi-shock shield, which

consists of staggered layers of Nextel that repeatedly shock the projectile and debris cloud until the remaining fragments can no longer harm the rear wall [7].

In addition to shielding, redundancy can also be considered as a risk mitigation technique. For orbits with larger fragments of space debris, a detection and avoidance system can be designed to protect the satellite from collisions [8]. This can involve spacecraft with the ability to maneuver or change orbit to avoid collisions with known debris or to mitigate the risk of impact from unpredictable sources. Propulsion systems or reaction control thrusters can be incorporated for attitude control and orbital adjustments.

Lastly, testing and validation are essential to validate the effectiveness of the mitigation plan. Rigorous testing and simulation, including impact testing on spacecraft components and systems, can assess their resilience to micrometeoroid and space debris impacts, ensuring the spacecraft's overall safety and integrity.

V. Conclusions

In conclusion, effective risk management and fault tolerance is critical in ensuring the success of spacecraft missions. As outlined in the report various risks within the environment subsystem, spanning technical, schedule, cost, and regulatory compliance domains. By adopting a multifaceted approach to risk assessment, spacecraft designers can develop targeted mitigation plans to address these risks proactively. By employing a diverse range of mitigation techniques, including rigorous environmental testing and proactive mission planning, the aerospace industry can navigate the challenges of the harsh space environment effectively. Overall, the aerospace industry's commitment to proactive risk management of the space environments is essential for maximizing mission success probability while minimizing the likelihood of system failures.

VII. References

- [1] Space mission engineering: the new SMAD: Vol. 28. (2011). Microcosm Press.
- [2] Effective fault management guidelines. (n.d.).
[https://aerospace.org/sites/default/files/maiw/TOR-2009\(8591\)-14.pdf](https://aerospace.org/sites/default/files/maiw/TOR-2009(8591)-14.pdf)
- [3] Fault-tolerant architectures for space and ... (n.d.-b).
https://www.cs.unc.edu/~anderson/teach/comp790/papers/Siewiorek_Fault_Tol.pdf
- [4] NASA. (n.d.). Spacecraft Anomalies and Failures Workshop 2023.
[https://ntrs.nasa.gov/api/citations/20230003611/downloads/Minow_SCAF_2023_Intro - final_2.pdf](https://ntrs.nasa.gov/api/citations/20230003611/downloads/Minow_SCAF_2023_Intro_final_2.pdf)
- [5] NASA. (n.d.-a). *Radiation Design Margin Requirement*. NASA.
<https://llis.nasa.gov/lesson/792>
- [6] Borated HDPE. Emco Plastics. (n.d.). <https://www.emcoplastics.com/borated-hdpe/>
- [7] NASA. (n.d.-a). *Ares*. NASA. <https://hvit.jsc.nasa.gov/shield-development/>
- [8] *Automating collision avoidance*. ESA. (n.d.).
https://www.esa.int/Space_Safety/Space_Debris/Automating_collision_avoidance