Writing Sample

SAM, SI, and SA Integration Overview

The STEALTHbits Activity Monitor (SAM) allows Active Directory Activity data to be sent from StealthINTERCEPT (SI) to the StealthAUDIT Management Platform (SMP|SA) through the Activity Monitor API Server or File Archive Repository.

RECOMMENDED: Use the API server method because it automatically syncs with updates, deletions, and additions to the domain controller. The file archive repository option must be manually updated at each location for any changes.

The following STEALTHbits products can be configured to monitor Active Directory Activity data:

- StealthINTERCEPT v6.1+
- STEALTHbits Activity Monitor v4.1+

The Active Directory Activity data can be fed to the following product:

- StealthAUDIT v9.0+

In order to monitor and receive Active Directory Activity data, each product needs a license for Active Directory Activity. Below are the licenses/solutions required for this integration:

- StealthINTERCEPT – StealthINTERCEPT for Active Directory solution
- STEALTHbits Activity Monitor – Active Directory Activity license
- StealthAUDIT Management Platform – Active Directory Activity license

Each product must be installed and configured to monitor the target environment or be fed Active Directory Activity data. See the guides below for additional information.

- *StealthINTERCEPT Installation & Upgrade User Guide*
- *STEALTHbits Activity Monitor Installation & Console Guide*
- *StealthAUDIT Management Platform Installation Guide*

API Server Configuration

Follow the steps to connect the Activity Monitor with StealthAUDIT through an API server. Complete the steps in order to ensure proper integration.

Step 1 – In the Activity Monitor console, navigate to the Agents tab and use **Add Agent** deploy two different Agents.

→ First deployment – Deploy an Agent to either the same machine as the SAM console or a separate non-domain controller server. This Agent becomes the SAM API server.

RECOMMENDED: Deploy the API Server to the same machine as the SAM console.

→ Second deployment – Deploy AD Agent(s) to all desired domain controllers in order to pick up AD Activity. These Agents must be on the same DC(s) as the SI Agent(s) when they are deployed.

NOTE: If using a share file archive repository instead of an API server, disregard steps two through four.

Configure the deployed Agent to become an API server by following the steps:

Step 2 – Once successfully deployed, on the Agents tab, select **Edit** on the non-domain controller Agent. The properties window displays.

Step 3 – On the Agent properties window, navigate to the **API Server** tab. Configure the following:

→ Select the **Enable API access on this agent** option.

→ Provide an **API server port (TCP)**. The default is 4494.

NOTE: This port must align with the one used in StealthINTERCEPT and StealthAUDIT.

→ Select **Add Application** to enable StealthAUDIT to access the Activity Monitor API Server. The Add or edit API client window opens. On this page:

☐ Provide a descriptive and unique **Application name** for the StealthAUDIT Connection Profile client.

☐ Grant **Read** permission to this application.

☐ Generate a Client ID and Client Secret. Do not forget to **Copy** the Client Secret to a Text Editor to use in later steps. If lost, another Client ID and Secret must be generated.

RECOMMENDED: Use the Client Secret in the StealthAUDIT Connection profile setup within three days or a new one must be generated.

☐ Click **OK** to navigate back to the Agent properties window.

→ *(Optional)* Use the **Managing Console** option to give the Activity Monitor control of this API Server. Only use this option when it is deployed on a separate machine from the Activity Monitor Console.

Step 4 – Select **OK** to save and close the Agent properties window.

The API server is now successfully configured. Follow the steps below to setup the AD Agent.

Step 5 – Select the **server** on the Agents tab and select **Edit**. The agent properties window displays.

→ On the Archiving tab:

☐ Check **Enable Archiving for this agent** and set the allocated disk space on the server

- ☐ Enable either the **Archive log files on this computer** or **Archive log files on an UNC path** option. Enter the share where the archive files will be stored.

→ Click **OK** to save and close the window.

Step 6 – Navigate to the **Monitored Domains** tab and select **Add Output** for the targeted domain controller. The domain properties window displays.

→ On the output properties window, ensure the settings are set as desired and the **This log file is for StealthAUDIT** checkbox is enabled.

Step 7 – Click OK to save and close the domain properties window.

Step 8 – *(Optional)* Deploy an AD Agent to each desired domain controller that will collect AD Activity.

The STEALTHbits Activity Monitor is now set up for StealthAUDIT integration. Follow the steps to configure a new or update an existing Connection profile in StealthAUDIT:

Step 9 – Open the StealthAUDIT Management Platform and navigate to the **Settings** > **Connection** node.

Step 10 – **Add** or **edit** a Connection profile with the necessary User Credentials accounts to enable StealthAUDIT access to the API Server:

Remember, the Client Secret was copied from the Application configuration in the Activity Monitor API Server properties. A new secret must be generated if it is not used within three days.

→ Web Services (JWT) – Provide the **user name** (Client ID) and **Access Token/Key** (Client Secret). The account must have Read access to the location of the archive logs.

→ Azure Active Directory – Provide the **Client ID** and the **Key** (Client Secret).

→ Active Directory Account – Provide a user account that has at least *Read* access to the location of the Activity Monitor archive logs. If the logs are located on a Domain Controller, provide a Domain Administrator account.

Step 11 – Select **OK** to save and close the User Credentials window.

The StealthAUDIT can now connect to the Activity Monitor API Server but StealthAUDIT requires additional configurations in order to collect Active Directory activity data. Follow the steps to configure the AD_ActivityCollection Data Collector in StealthAUDIT:

Step 12 – Ensure that the **.Active Directory Inventory** Job Group has been successfully run.

Step 13 – At the **Jobs** > **Active Directory** > **6.Activity** > **0.Collection** > **Settings** > **Connection**, ensure the Connection profile designated for integration is selected from Step 5.

Step 14 – Navigate to the **AD_ActivityCollection** Job > **Configure** > **Queries** > **Query Properties** in the 0.Collection job group. The Query Properties window displays. On the Data Source tab, select **Configure**. The Active Directory Activity DC Wizard opens.

Step 15 – On the Category page, select one of the following methods:

→ Import From SAM – Used in conjunction with the Activity Monitor API server.

- ☐ Enter the **Port** to the Activity Monitor API Server.
- ☐ In the Test SAM host textbox, provide the **SAM API server name** in a qualified domain name format . Click **Connect** to test the connection. If connection is successful, the archive location(s) display(s) along with a Refresh token.

  NOTE: The Refresh token resets each time the Test SAM host option is connected to. It must be replaced in the Connection profile if its regenerated.

  - *(Optional)* Use the **Exclude** checkbox to select archives to be ignored by the Active Directory Activity DC scan.

- ☐ Once the Refresh token is generated, click **Copy Token**.

CAUTION: Make sure the Refresh token is saved to a Text Editor. After generation, it is used in the StealthAUDIT Console.

Step 16 – Click **Next**. The SAM connection settings window opens.

Step 17 – On the Scoping page, configure the following options:

→ Relative Timespan – Number of days AD Activity is collected when the scan is run
→ Absolute Timespan – Set the date range for the scan to collect AD Activity

RECOMMENDED: The threshold should be set for after the Activity Monitor collects and archives its data but before they are deleted after a set retention period.

→ Retention – Sets what event type is collected and how many days StealthAUDIT keeps the collected data in the SQL
→ Click **Next**.

Step 18 – On the Results page, select the available properties to gather. By default, all are collected.

Step 19 – Review the Summary page and select **Finish** to save the configurations.

Step 20 – Do not run the job yet.

The Active Directory Activity DC is now configured for successful data collection from the Activity Monitors' API Server. Now that a new Refresh token has been generated, the active connection profile requires an update. Follow the steps to update the Connection profile.

Step 21 – Navigate back to the global Connection profile settings. In the replace the old Access Token with the newly generated **Refresh token** for the profile being used to connect to the API server.

The StealthAUDIT Console is configured for Activity Monitor Integration. Next, configure StealthINTERCEPT to send AD Event data from its various Policies to the STEALTHbits Activity Monitor API Server.

Step 22 – Navigate to the Menu's **Configuration** > **StealthDEFEND Event Sink** from the dropdown menu. The StealthDEFEND Event Sink Configuration window opens.

Step 23 – Provide the following on the StealthDEFEND Event Sink Configuration window:

→ StealthDEFEND URI – Enter the Activity Monitor's **Agent hostname** or **IP address** and the **amqp** port. The default port is 4499.

- ☐ amqp://[HOSTNAME | IPADDRESS]:[PORT]
- ☐ Example: amqp://localhost:4499

→ App Token – Leave this blank, StealthINTERCEPT does not require an app token for STEALTHbits Activity Monitor configuration.

Step 24 – Click **Save**.

Step 25 – Create, configure, and enable the desired StealthINTERCEPT policies to monitor Active Directory activity on the chosen domain controller(s).

Step 26 – Within these SI policies, navigate to their **Actions** tab and select **Send to StealthDEFEND** to enable the stream of event data from that policy to the Activity Monitor API server.

Step 27 – Click **Save**. Configure as many associated policies as desired.

The SI Agents now send real-time policy data for policies to the Activity Monitor that have the Send to StealthDEFEND checkbox selected on the Actions tab. The last steps are to transfer control of the AD Agents from the Activity Monitor to StealthINTERCEPT:

Step 28 – On the Agents tab of the SAM console, use **Add Agent** deploy an AD Agent to every targeted Active Directory Domain Controller(s).

Step 29 – On the Agents tab of the SAM console, select Edit. Configure the following:

→ On the Archiving tab for each AD agent and add a **File** archiving output.

CAUTION: The next step automatically transfers control of the Activity Monitor AD Agent(s) on the domain controller to the newly deployed SI Agent(s)

Step 30 – In the StealthINTERCEPT Admin Console, deploy SI Agent(s) to all of the same Domain Controller(s) that house the Activity Monitors' AD Agent(s).

StealthINTERCEPT data is now being sent to the Activity Monitor's API Server. The API Server is queried by the StealthAUDIT AD_ActivityCollection job and creates analysis and reports on AD Activity data in the 6.Activity Job Group.

Step 31 – After the logs are archived by the Activity Monitor, run the **AD_ActivityCollection** job and any subsequent job to collect AD activity.

AD activity is now successfully collected and transferred between products to display in StealthAUDIT reports.

--- End of Sample---