

# **Automatically Assembling Frescos from Noisy Pairwise Fragment Measurements**

Elena Sizikova, Thomas Funkhouser

(Extended Abstract)

Combining fragments of shattered artefacts together manually is an extremely difficult task for archaeologists. There could be many fragments that go to one artefact, and some could be missing. The artefact fragments are themselves fragile or difficult to handle. Then, some fragments could have deteriorated, and it is not clear whether two fragments should go together in the final puzzle. Finally, with a large number of fragments, there are simply too many combinations to test, especially without an automated system. Based on the above, it is reasonable to use computational methods correctly piece fragments together.

Most previous methods that can reconstruct the entire fresco rely on hierarchical clustering (e.g. [Castaneda 11]). In this technique, a best-first approach iteratively merges pairs of clusters. Global relaxation needs to be applied to resulting clusters in order to find the best transformations to align fragments within clusters. Global relaxation uses least squares (LS) method to find the best rotations and translations for fragments in a cluster. However, if a portion of the matches from a cluster are incorrect, least squares should not be used because the objective function becomes dominated by squared residuals [Singer 11]. A more robust method of finding optimal rotations and translations within the cluster should thus be used.

Our goal is to produce a set of globally consistent transformations given noisy pairwise fragment matches. We present a method based on [Singer 2011], which separates the problem into a first stage that uses an Eigenvalue method to solve for rotations followed by a second stage that uses multilinear robust regression to solve for translations. The advantage of this approach is that a globally optimal set of rotations can be found by solving a convex optimization. It also can be applied iteratively by culling outlier matches according to how consistent they are with computed fragment rotations.

We test the rotation search algorithm on a set of 114 fragments which were obtained from a fresco created and shattered to test reconstruction techniques. A ground truth of 239 correct matches is available for this fresco. To test our algorithm, we add subsets of high scoring wrong matches obtained from [Funkhouser 11], and compare the resulting angles to manually created ground truth. When 30% of the matches are incorrect, least squares can recover at most 35% of angles within margin of error  $\pi/16$ , while our method recovers more than 70%.




Figure 1: Percentiles of angular error achieved during a run of the methods with 114 fragments, 339 matches of which 239 are correct. The results are aggregated over 10 runs on different 100 wrong matches added. The stars are the mean percentiles of the given error, and the horizontal lines represent standard deviation. Least squares (LS), performs poorly compared to other proposed methods. The method we propose, known as normalized eigenvector method (nEVM in the plot), finds more than 65% of the fragment angles within margin of error of  $\pi/8$ . Even better results are obtained when the methods (LS and nEVM) are iterated.

## Bibliography

1. Mica Arie-Nachimson, Shahar Z. Kovalsky, Ira Kemelmacher-Shlizerman, Amit Singer, and Ronen Basri. 2012. Global Motion Estimation from Point Matches. In Proceedings of the 2012 Second International Conference on 3D Imaging, Modeling, Processing, Visualization & Transmission (3DIMPVT '12). IEEE Computer Society, Washington, DC, USA, 81–88. DOI:<http://dx.doi.org/10.1109/3DIMPVT.2012.46A>.
2. Biswas, P. Bhowmick, and B.B. Bhattacharya. 2005. Reconstruction of torn documents using contour maps. In Image Processing, 2005. ICIP 2005. IEEE International Conference on, Vol. 3. III–517–20. DOI:<http://dx.doi.org/10.1109/ICIP.2005.1530442>

3. Benedict J. Brown, Lara Laken, Philip Dutre, Luc Van Gool, Szymon Rusinkiewicz, and Tim Weyrich. 2012. Tools for VirtualReassembly of Fresco Fragments. *International Journal of Heritage in the Digital Era* 1, 2 (July 2012).
4. Benedict J. Brown, Corey Toler-Franklin, Diego Nehab, Michael Burns, David Dobkin, Andreas Vlachopoulos, Christos Doumas, Szymon Rusinkiewicz, and Tim Weyrich. 2008. A System for High-Volume Acquisition and Matching of Fresco Fragments: Reassembling Thera Wall Paintings. *ACM Transactions on Graphics (Proc. SIGGRAPH)* 27, 3 (Aug. 2008).
5. Antonio Garcia Castaneda, Benedict Brown, Szymon Rusinkiewicz, Thomas Funkhouser, and Tim Weyrich. 2011. Global Consistency in the Automatic Assembly of Fragmented Artefacts. *Intl. Symposium on Virtual Reality, Archaeology and Cultural Heritage (VAST)* (Oct. 2011).
6. Mihai Cucuringu, Yaron Lipman, and Amit Singer. 2012. Sensor Network Localization by Eigenvector Syn-chronization over the Euclidean Group. *ACM Trans. Sen. Netw.* 8, 3, Article 19 (Aug. 2012), 42 pages. DOI: <http://dx.doi.org/10.1145/2240092.2240093>.
7. De Smet. 2009. Semi-automatic Forensic Reconstruction of Ripped-up Documents. In *Document Analysis and Recognition, 2009. ICDAR '09. 10th International Conference on*. 703–707. DOI: <http://dx.doi.org/10.1109/ICDAR.2009.7>
8. Thomas Funkhouser, Hujung Shin, Corey Toler-Franklin, Antonio Garcia Castaneda, Benedict Brown, David Dobkin, Szymon Rusinkiewicz, and Tim Weyrich. 2011. Learning How to Match Fresco Fragments. *Journal on Computing and Cultural Heritage* 4, 2 (Nov. 2011).
9. M.J. Hinich and P.P. Talwar. 1974. A Simple Method for Robust Regression. Defense Technical Information Center. <http://books.google.com/books?id=vwhaOAAACAA>
10. JF. Kleber and R. Sablatnig. 2009. A Survey of Techniques for Document and Archaeology Artefact Reconstruc-tion. In *Document Analysis and Recognition, 2009. ICDAR '09. 10th International Conference on*. 1061–1065. DOI: <http://dx.doi.org/10.1109/ICDAR.2009.154>
11. Onur Ozyesil, Amit Singer, and Ronen Basri. 2013. Camera Motion Estimation by Convex Programming. *CoRR* abs/1312.5047(2013). <http://arxiv.org/abs/1312.5047>
12. A. Singer. 2011. Angular synchronization by eigenvectors and semidefinite programming. *Applied and Computational Harmonic Analysis* 30, 1 (2011), 20 – 36. DOI: <http://dx.doi.org/10.1016/j.acha.2010.02.001>
13. Lanhui Wang, Amit Singer, and Zaiwen Wen. 2013. Orientation Determination of Cryo-EM Images Using Least Unsquared Deviations. *SIAM journal on imaging sciences* 6, 4 (2013), 2450–2483.
14. A.R. Willis and D.B. Cooper. 2008. Computational reconstruction of ancient artifacts. *Signal Processing Magazine, IEEE* 25, 4 (July 2008), 65–83. DOI: <http://dx.doi.org/10.1109/MSP.2008.923101>
15. Liangjia Zhu, Zongtan Zhou, and Dewen Hu. 2008. Globally Consistent Reconstruction of Ripped-Up Documents. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 30, 1 (Jan 2008), 1–13. DOI: <http://dx.doi.org/10.1109/TPAMI.2007.1163>

