

ML0101EN-Clas-Decision-Trees-drug-py-v1

September 19, 2021

1 Decision Trees

Estimated time needed: **15** minutes

1.1 Objectives

After completing this lab you will be able to:

- Develop a classification model using Decision Tree Algorithm

In this lab exercise, you will learn a popular machine learning algorithm, Decision Trees. You will use this classification algorithm to build a model from the historical data of patients, and their response to different medications. Then you will use the trained decision tree to predict the class of a unknown patient, or to find a proper drug for a new patient.

Table of contents

```
<ol>
  <li><a href="https://#about_dataset">About the dataset</a></li>
  <li><a href="https://#downloading_data">Downloading the Data</a></li>
  <li><a href="https://#pre-processing">Pre-processing</a></li>
  <li><a href="https://#setting_up_tree">Setting up the Decision Tree</a></li>
  <li><a href="https://#modeling">Modeling</a></li>
  <li><a href="https://#prediction">Prediction</a></li>
  <li><a href="https://#evaluation">Evaluation</a></li>
  <li><a href="https://#visualization">Visualization</a></li>
</ol>
```

Import the Following Libraries:

numpy (as np)

pandas

DecisionTreeClassifier from sklearn.tree

```
[1]: import numpy as np
import pandas as pd
from sklearn.tree import DecisionTreeClassifier
```

<h2>About the dataset</h2>

Imagine that you are a medical researcher compiling data for a study. You have collected data a

Part of your job is to build a model to find out which drug might be appropriate for a future patient.

It is a sample of multiclass classifier, and you can use the training part of the dataset to build a decision tree, and then use it to predict the class of a unknown patient, or to predict the class of a new patient.

<h2>Downloading the Data</h2>

To download the data, we will use !wget to download it from IBM Object Storage.

```
[2]: !wget -O drug200.csv https://cf-courses-data.s3.us.cloud-object-storage.  
      ↪ appdomain.cloud/IBMDeveloperSkillsNetwork-ML0101EN-SkillsNetwork/labs/  
      ↪ Module%203/data/drug200.csv
```

```
--2021-09-19 01:41:27-- https://cf-courses-data.s3.us.cloud-object-  
storage.appdomain.cloud/IBMDeveloperSkillsNetwork-ML0101EN-  
SkillsNetwork/labs/Module%203/data/drug200.csv  
Resolving cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud (cf-  
courses-data.s3.us.cloud-object-storage.appdomain.cloud)... 169.63.118.104  
Connecting to cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud (cf-  
courses-data.s3.us.cloud-object-storage.appdomain.cloud)|169.63.118.104|:443...  
connected.  
HTTP request sent, awaiting response... 200 OK  
Length: 5827 (5.7K) [text/csv]  
Saving to: 'drug200.csv'
```

```
drug200.csv          100%[=====>]    5.69K  --.-KB/s    in 0.1s
```

```
2021-09-19 01:41:27 (56.4 KB/s) - 'drug200.csv' saved [5827/5827]
```

Did you know? When it comes to Machine Learning, you will likely be working with large datasets. As a business, where can you host your data? IBM is offering a unique opportunity for businesses, with 10 Tb of IBM Cloud Object Storage: [Sign up now for free](#)

Now, read the data using pandas dataframe:

```
[3]: my_data = pd.read_csv("drug200.csv", delimiter=",")  
      my_data[0:5]
```

```
[3]:
```

	Age	Sex	BP	Cholesterol	Na_to_K	Drug
0	23	F	HIGH	HIGH	25.355	drugY
1	47	M	LOW	HIGH	13.093	drugC
2	47	M	LOW	HIGH	10.114	drugC
3	28	F	NORMAL	HIGH	7.798	drugX
4	61	F	LOW	HIGH	18.043	drugY

<h3>Practice</h3>

What is the size of data?

```
[4]: my_data.shape
```

```
[4]: (200, 6)
```

[Click here for the solution](#)

```
my_data.shape
```

Pre-processing

Using my_data as the Drug.csv data read by pandas, declare the following variables:

X as the Feature Matrix (data of my_data)

y as the response vector (target)

Remove the column containing the target name since it doesn't contain numeric values.

```
[5]: X = my_data[['Age', 'Sex', 'BP', 'Cholesterol', 'Na_to_K']].values
X[0:5]
```

```
[5]: array([[23, 'F', 'HIGH', 'HIGH', 25.355],
          [47, 'M', 'LOW', 'HIGH', 13.093],
          [47, 'M', 'LOW', 'HIGH', 10.113999999999999],
          [28, 'F', 'NORMAL', 'HIGH', 7.797999999999999],
          [61, 'F', 'LOW', 'HIGH', 18.043]], dtype=object)
```

As you may figure out, some features in this dataset are categorical, such as **Sex** or **BP**. Unfortunately, Sklearn Decision Trees does not handle categorical variables. We can still convert these features to numerical values using **pandas.get_dummies()** to convert the categorical variable into dummy/indicator variables.

```
[6]: from sklearn import preprocessing
le_sex = preprocessing.LabelEncoder()
le_sex.fit(['F','M'])
X[:,1] = le_sex.transform(X[:,1])

le_BP = preprocessing.LabelEncoder()
le_BP.fit([ 'LOW', 'NORMAL', 'HIGH'])
X[:,2] = le_BP.transform(X[:,2])

le_Chol = preprocessing.LabelEncoder()
le_Chol.fit([ 'NORMAL', 'HIGH'])
X[:,3] = le_Chol.transform(X[:,3])

X[0:5]
```

```
[6]: array([[23, 0, 0, 0, 25.355],
          [47, 1, 1, 0, 13.093],
          [47, 1, 1, 0, 10.113999999999999],
          [28, 0, 2, 0, 7.797999999999999],
          [61, 0, 1, 0, 18.043]], dtype=object)
```

Now we can fill the target variable.

```
[7]: y = my_data["Drug"]
     y[0:5]
```

```
[7]: 0    drugY
     1    drugC
     2    drugC
     3    drugX
     4    drugY
     Name: Drug, dtype: object
```

<h2>Setting up the Decision Tree</h2>

We will be using `train/test split` on our `decision tree`. Let's import `train_test_split`.

```
[8]: from sklearn.model_selection import train_test_split
```

Now `train_test_split` will return 4 different parameters. We will name them: `X_trainset`, `X_testset`, `y_trainset`, `y_testset`. The `train_test_split` will need the parameters: `X`, `y`, `test_size=0.3`, and `random_state=3`. The `X` and `y` are the arrays required before the split, the `test_size` represents the ratio of the testing dataset, and the `random_state` ensures that we obtain the same splits.

```
[9]: X_trainset, X_testset, y_trainset, y_testset = train_test_split(X, y,
    ↪test_size=0.3, random_state=3)
```

Practice

Print the shape of `X_trainset` and `y_trainset`. Ensure that the dimensions match.

```
[10]: print('Shape of X training set {}'.format(X_trainset.shape), '&', 'Size of Y_
    ↪training set {}'.format(y_trainset.shape))
```

Shape of X training set (140, 5) & Size of Y training set (140,)

[Click here for the solution](#)

```
print('Shape of X training set {}'.format(X_trainset.shape), '&', 'Size of Y training set {}'.f
```

Print the shape of `X_testset` and `y_testset`. Ensure that the dimensions match.

```
[11]: print('Shape of X training set {}'.format(X_testset.shape), '&', 'Size of Y_
    ↪training set {}'.format(y_testset.shape))
```

Shape of X training set (60, 5) & Size of Y training set (60,)

[Click here for the solution](#)

```
print('Shape of X training set {}'.format(X_testset.shape),'&',' Size of Y training set {}'.format(y_testset.shape))
```

Modeling

We will first create an instance of the `DecisionTreeClassifier` called `drugTree`. Inside of the classifier, specify `criterion="entropy"` so we can see the information gain.

```
[12]: drugTree = DecisionTreeClassifier(criterion="entropy", max_depth = 4)
      drugTree # it shows the default parameters
```

```
[12]: DecisionTreeClassifier(class_weight=None, criterion='entropy', max_depth=4,
                             max_features=None, max_leaf_nodes=None,
                             min_impurity_decrease=0.0, min_impurity_split=None,
                             min_samples_leaf=1, min_samples_split=2,
                             min_weight_fraction_leaf=0.0, presort=False, random_state=None,
                             splitter='best')
```

Next, we will fit the data with the training feature matrix `X_trainset` and training response vector `y_trainset`

```
[13]: drugTree.fit(X_trainset,y_trainset)
```

```
[13]: DecisionTreeClassifier(class_weight=None, criterion='entropy', max_depth=4,
                             max_features=None, max_leaf_nodes=None,
                             min_impurity_decrease=0.0, min_impurity_split=None,
                             min_samples_leaf=1, min_samples_split=2,
                             min_weight_fraction_leaf=0.0, presort=False, random_state=None,
                             splitter='best')
```

Prediction

Let's make some `predictions` on the testing dataset and store it into a variable called `predTree`.

```
[14]: predTree = drugTree.predict(X_testset)
```

You can print out `predTree` and `y_testset` if you want to visually compare the predictions to the actual values.

```
[15]: print (predTree [0:5])
      print (y_testset [0:5])
```

```
['drugY' 'drugX' 'drugX' 'drugX' 'drugX']
40      drugY
51      drugX
139     drugX
197     drugX
170     drugX
Name: Drug, dtype: object
```

Evaluation

Next, let's import `metrics` from `sklearn` and check the accuracy of our model.

```
[16]: from sklearn import metrics
import matplotlib.pyplot as plt
print("DecisionTrees's Accuracy: ", metrics.accuracy_score(y_testset, predTree))
```

DecisionTrees's Accuracy: 0.9833333333333333

Accuracy classification score computes subset accuracy: the set of labels predicted for a sample must exactly match the corresponding set of labels in `y_true`.

In multilabel classification, the function returns the subset accuracy. If the entire set of predicted labels for a sample strictly match with the true set of labels, then the subset accuracy is 1.0; otherwise it is 0.0.

Visualization


Let's visualize the tree

```
[17]: # Notice: You might need to uncomment and install the pydotplus and graphviz
      ↪ libraries if you have not installed these before
      #!conda install -c conda-forge pydotplus -y
      #!conda install -c conda-forge python-graphviz -y
```

```
[18]: from io import StringIO
import pydotplus
import matplotlib.image as mpimg
from sklearn import tree
%matplotlib inline
```

```
[19]: dot_data = StringIO()
filename = "drugtree.png"
featureNames = my_data.columns[0:5]
out=tree.export_graphviz(drugTree,feature_names=featureNames,
      ↪out_file=dot_data, class_names= np.unique(y_trainset), filled=True,
      ↪special_characters=True,rotate=False)
graph = pydotplus.graph_from_dot_data(dot_data.getvalue())
graph.write_png(filename)
img = mpimg.imread(filename)
plt.figure(figsize=(100, 200))
plt.imshow(img,interpolation='nearest')
```

```
[19]: <matplotlib.image.AxesImage at 0x7ff80c96ee80>
```



Want to learn more?

IBM SPSS Modeler is a comprehensive analytics platform that has many machine learning algorithms. It has been designed to bring predictive intelligence to decisions made by individuals, by groups, by systems – by your enterprise as a whole. A free trial is available through this course, available here: [SPSS Modeler](#)

Also, you can use Watson Studio to run these notebooks faster with bigger datasets. Watson Studio is IBM's leading cloud solution for data scientists, built by data scientists. With Jupyter notebooks, RStudio, Apache Spark and popular libraries pre-packaged in the cloud, Watson Studio enables data scientists to collaborate on their projects without having to install anything. Join the fast-growing community of Watson Studio users today with a free account at [Watson Studio](#)

1.1.1 Thank you for completing this lab!

1.2 Author

Saeed Aghabozorgi

1.2.1 Other Contributors

Joseph Santarcangelo

1.3 Change Log

Date (YYYY-MM-DD)	Version	Changed By	Change Description
2020-11-20	2.2	Lakshmi	Changed import statement of StringIO
2020-11-03	2.1	Lakshmi	Changed URL of the csv
2020-08-27	2.0	Lavanya	Moved lab to course repo in GitLab

##

© IBM Corporation 2020. All rights reserved.