

Works fine when replacing a target word with another word:

The image shows two screenshots from Burp Suite. The top screenshot is the 'Scoping' tab, showing 'Provided their URLs are within Burp Suite's scope' with 'this tab will work' set to 'on all' and 'requests'. Below is the 'Parameter handling' tab, where '1) Find matches to this expression:' has a 'Regex' field containing 'params'. '2) Target' is set to 'the first' of the matches. '3) Replace each target with this expression:' has a 'Regex' field containing 'test'. The bottom screenshot shows two 'Raw' request logs side-by-side. The left log shows the original request with a 'params' field containing a list of values. The right log shows the modified request where 'params' has been replaced with 'test'.

21:21:29:108 [INFO] Sending request to tab "marriott1" for modification

21:21:29:111 [DEBUG] findall_exp: params

21:21:29:111 [DEBUG] all_matches: [u'params']

21:21:29:111 [DEBUG] match_indices: set([0])

21:21:29:112 [DEBUG] message_parts: [u'MQ /cws40_svc/marriottcons/consumer/dc_958.rpc HTTP/1.1\r\nHost: gifts.marriott.com\r\nUser-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:55.0) Gecko/20100101 Firefox/55.0\r\nAccept: */*\r\nAccept-Language: en-US,en;q=0.5\r\nAccept-Encoding: gzip, deflate\r\nContent-Type: application/json\r\nX-Requested-With: XMLHttpRequest\r\nReferer: https://gifts.marriott.com/login/\r\nContent-Length: 87\r\nConnection: close\r\n\r\n{"params":["en","958","mqjd","mqpass","kgarmin@gmail.com","Karrats15!","t"],"id":"958"}']

21:21:29:114 [DEBUG] Found:

params

replaced using:

test

in string:

params



21:21:29:355 [DEBUG] Preliminary scope check negative!

21:21:29:355 [DEBUG] Messages cached for tab marriott1!

21:21:37:523 [DEBUG] Skipping message received from Proxy on account of global tool scope options.

21:21:37:923 [DEBUG] Skipping message received from Proxy on account of global tool scope options.

Does not work when using RegEx to define the target. Notice, debug notice is identical to the example above.



21:30:58:627 [INFO] Sending request to tab "marriott1" for modification

21:30:58:628 [DEBUG] findall_exp: \{"(.*)"

21:30:58:628 [DEBUG] all_matches: [u'params']

21:30:58:628 [DEBUG] match_indices: set([0])

21:30:58:628 [DEBUG] message_parts: [u'MQ /cws40_svc/marriottcons/consumer/dc_958.rpc HTTP/1.1\r\nHost: gifts.marriott.com\r\nUser-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:55.0) Gecko/20100101 Firefox/55.0\r\nAccept: */*\r\nAccept-Language: en-US,en;q=0.5\r\nAccept-Encoding: gzip, deflate\r\nContent-Type: application/json\r\nX-Requested-With: XMLHttpRequest\r\nReferer: https://gifts.marriott.com/login/\r\nContent-Length: 87\r\nConnection: close\r\n\r\n', u'params', u:'["en", "958", "mqid", "mqpass", "kgarmin@gmail.com", "Karrats15!", "t"], "id": "958"}']

21:30:58:630 [DEBUG] Found:

\{"(.*)"

replaced using:

test

in string:

params

21:30:58:877 [DEBUG] Preliminary scope check negative!

21:30:58:877 [DEBUG] Messages cached for tab marriott1!