


```

Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 60648, Dst Port: 9090, Seq: 5, Ack: 1, Len: 1
Data (1 byte)
0000 0a
No.      Time      Source      Destination      Protocol Length Info
 99 83.032298540 127.0.0.1    127.0.0.1        TCP           66      9090 → 60648 [ACK] Seq=1 Ack=6 Win=65536
Len=0 TSval=1849590268 TSecr=1849590268
Frame 99: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 60648, Seq: 1, Ack: 6, Len: 0
No.      Time      Source      Destination      Protocol Length Info
100 83.032509701 127.0.0.1    127.0.0.1        TCP           67      60648 → 9090 [PSH, ACK] Seq=6 Ack=1
Win=65536 Len=1 TSval=1849590268 TSecr=1849590268
Frame 100: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 60648, Dst Port: 9090, Seq: 6, Ack: 1, Len: 1
Data (1 byte)
0000 34
No.      Time      Source      Destination      Protocol Length Info
101 83.032524108 127.0.0.1    127.0.0.1        TCP           66      9090 → 60648 [ACK] Seq=1 Ack=7 Win=65536
Len=0 TSval=1849590268 TSecr=1849590268
Frame 101: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 60648, Seq: 1, Ack: 7, Len: 0
No.      Time      Source      Destination      Protocol Length Info
102 83.032570300 127.0.0.1    127.0.0.1        TCP           67      60648 → 9090 [PSH, ACK] Seq=7 Ack=1
Win=65536 Len=1 TSval=1849590268 TSecr=1849590268
Frame 102: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 60648, Dst Port: 9090, Seq: 7, Ack: 1, Len: 1
Data (1 byte)
0000 0a
No.      Time      Source      Destination      Protocol Length Info
103 83.032584737 127.0.0.1    127.0.0.1        TCP           66      9090 → 60648 [ACK] Seq=1 Ack=8 Win=65536
Len=0 TSval=1849590268 TSecr=1849590268
Frame 103: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 60648, Seq: 1, Ack: 8, Len: 0
No.      Time      Source      Destination      Protocol Length Info
104 83.037231466 127.0.0.1    127.0.0.1        TCP           67      9090 → 60648 [PSH, ACK] Seq=1 Ack=8
Win=65536 Len=1 TSval=1849590273 TSecr=1849590268
Frame 104: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 60648, Seq: 1, Ack: 8, Len: 1
Data (1 byte)
0000 31
No.      Time      Source      Destination      Protocol Length Info
105 83.037261184 127.0.0.1    127.0.0.1        TCP           66      60648 → 9090 [ACK] Seq=8 Ack=2 Win=65536
Len=0 TSval=1849590273 TSecr=1849590273
Frame 105: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 60648, Dst Port: 9090, Seq: 8, Ack: 2, Len: 0
No.      Time      Source      Destination      Protocol Length Info
106 83.037331568 127.0.0.1    127.0.0.1        TCP           67      9090 → 60648 [PSH, ACK] Seq=2 Ack=8
Win=65536 Len=1 TSval=1849590273 TSecr=1849590273
Frame 106: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 60648, Seq: 2, Ack: 8, Len: 1
Data (1 byte)
0000 34
No.      Time      Source      Destination      Protocol Length Info
107 83.037341962 127.0.0.1    127.0.0.1        TCP           66      60648 → 9090 [ACK] Seq=8 Ack=3 Win=65536
Len=0 TSval=1849590273 TSecr=1849590273
Frame 107: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 60648, Dst Port: 9090, Seq: 8, Ack: 3, Len: 0
No.      Time      Source      Destination      Protocol Length Info
108 83.037381624 127.0.0.1    127.0.0.1        TCP           67      9090 → 60648 [PSH, ACK] Seq=3 Ack=8
Win=65536 Len=1 TSval=1849590273 TSecr=1849590273
Frame 108: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 60648, Seq: 3, Ack: 8, Len: 1
Data (1 byte)
0000 2e
No.      Time      Source      Destination      Protocol Length Info
109 83.037392371 127.0.0.1    127.0.0.1        TCP           66      60648 → 9090 [ACK] Seq=8 Ack=4 Win=65536
Len=0 TSval=1849590273 TSecr=1849590273
Frame 109: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0

```

```

Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 60648, Dst Port: 9090, Seq: 8, Ack: 4, Len: 0
No.      Time      Source      Destination      Protocol Length Info
   110  83.037591085  127.0.0.1    127.0.0.1        TCP          67      9090 → 60648 [PSH, ACK] Seq=4 Ack=8
Win=65536 Len=1 TSval=1849590273 TSecr=1849590273
Frame 110: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 60648, Seq: 4, Ack: 8, Len: 1
Data (1 byte)
0000 30                                     0
No.      Time      Source      Destination      Protocol Length Info
   111  83.037606903  127.0.0.1    127.0.0.1        TCP          66      60648 → 9090 [ACK] Seq=8 Ack=5 Win=65536
Len=0 TSval=1849590273 TSecr=1849590273
Frame 111: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 60648, Dst Port: 9090, Seq: 8, Ack: 5, Len: 0
No.      Time      Source      Destination      Protocol Length Info
   112  83.037680069  127.0.0.1    127.0.0.1        TCP          67      9090 → 60648 [PSH, ACK] Seq=5 Ack=8
Win=65536 Len=1 TSval=1849590273 TSecr=1849590273
Frame 112: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 60648, Seq: 5, Ack: 8, Len: 1
Data (1 byte)
0000 0a
No.      Time      Source      Destination      Protocol Length Info
   113  83.037686408  127.0.0.1    127.0.0.1        TCP          66      60648 → 9090 [ACK] Seq=8 Ack=6 Win=65536
Len=0 TSval=1849590273 TSecr=1849590273
Frame 113: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 60648, Dst Port: 9090, Seq: 8, Ack: 6, Len: 0
No.      Time      Source      Destination      Protocol Length Info
   114  83.039617365  127.0.0.1    127.0.0.1        TCP          66      9090 → 60648 [FIN, ACK] Seq=6 Ack=8
Win=65536 Len=0 TSval=1849590275 TSecr=1849590273
Frame 114: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 60648, Seq: 6, Ack: 8, Len: 0
No.      Time      Source      Destination      Protocol Length Info
   115  83.039736778  127.0.0.1    127.0.0.1        TCP          66      60648 → 9090 [FIN, ACK] Seq=8 Ack=7
Win=65536 Len=0 TSval=1849590275 TSecr=1849590275
Frame 115: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 60648, Dst Port: 9090, Seq: 8, Ack: 7, Len: 0
No.      Time      Source      Destination      Protocol Length Info
   116  83.039817396  127.0.0.1    127.0.0.1        TCP          66      9090 → 60648 [ACK] Seq=7 Ack=9 Win=65536
Len=0 TSval=1849590275 TSecr=1849590275
Frame 116: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 60648, Seq: 7, Ack: 9, Len: 0
No.      Time      Source      Destination      Protocol Length Info
   167  170.820092296  127.0.0.1    127.0.0.1        TCP          74      52658 → 9090 [SYN] Seq=0 Win=65495 Len=0
MSS=65495 SACK_PERM TSval=1849678056 TSecr=0 WS=128
Frame 167: 74 bytes on wire (592 bits), 74 bytes captured (592 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 0, Len: 0
No.      Time      Source      Destination      Protocol Length Info
   168  170.820126316  127.0.0.1    127.0.0.1        TCP          74      9090 → 52658 [SYN, ACK] Seq=0 Ack=1
Win=65483 Len=0 MSS=65495 SACK_PERM TSval=1849678056 TSecr=1849678056 WS=128
Frame 168: 74 bytes on wire (592 bits), 74 bytes captured (592 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 0, Ack: 1, Len: 0
No.      Time      Source      Destination      Protocol Length Info
   169  170.820153435  127.0.0.1    127.0.0.1        TCP          66      52658 → 9090 [ACK] Seq=1 Ack=1 Win=65536
Len=0 TSval=1849678056 TSecr=1849678056
Frame 169: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 1, Ack: 1, Len: 0
No.      Time      Source      Destination      Protocol Length Info
   170  170.820451151  127.0.0.1    127.0.0.1        TCP          67      52658 → 9090 [PSH, ACK] Seq=1 Ack=1
Win=65536 Len=1 TSval=1849678056 TSecr=1849678056
Frame 170: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 1, Ack: 1, Len: 1
Data (1 byte)
0000 34                                     4
No.      Time      Source      Destination      Protocol Length Info
   171  170.820464811  127.0.0.1    127.0.0.1        TCP          66      9090 → 52658 [ACK] Seq=1 Ack=2 Win=65536
Len=0 TSval=1849678056 TSecr=1849678056

```

```

Frame 171: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 1, Ack: 2, Len: 0
No.      Time            Source            Destination        Protocol Length Info
    172 170.820508960 127.0.0.1         127.0.0.1         TCP             67      52658 → 9090 [PSH, ACK] Seq=2 Ack=1
Win=65536 Len=1 TSval=1849678056 TSecr=1849678056
Frame 172: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 2, Ack: 1, Len: 1
Data (1 byte)
0000 0a
No.      Time            Source            Destination        Protocol Length Info
    173 170.820517449 127.0.0.1         127.0.0.1         TCP             66      9090 → 52658 [ACK] Seq=1 Ack=3 Win=65536
Len=0 TSval=1849678056 TSecr=1849678056
Frame 173: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 1, Ack: 3, Len: 0
No.      Time            Source            Destination        Protocol Length Info
    174 170.820563618 127.0.0.1         127.0.0.1         TCP             67      52658 → 9090 [PSH, ACK] Seq=3 Ack=1
Win=65536 Len=1 TSval=1849678056 TSecr=1849678056
Frame 174: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 3, Ack: 1, Len: 1
Data (1 byte)
0000 31
No.      Time            Source            Destination        Protocol Length Info
    175 170.820569937 127.0.0.1         127.0.0.1         TCP             66      9090 → 52658 [ACK] Seq=1 Ack=4 Win=65536
Len=0 TSval=1849678056 TSecr=1849678056
Frame 175: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 1, Ack: 4, Len: 0
No.      Time            Source            Destination        Protocol Length Info
    176 170.820597473 127.0.0.1         127.0.0.1         TCP             67      52658 → 9090 [PSH, ACK] Seq=4 Ack=1
Win=65536 Len=1 TSval=1849678056 TSecr=1849678056
Frame 176: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 4, Ack: 1, Len: 1
Data (1 byte)
0000 30
No.      Time            Source            Destination        Protocol Length Info
    177 170.820603582 127.0.0.1         127.0.0.1         TCP             66      9090 → 52658 [ACK] Seq=1 Ack=5 Win=65536
Len=0 TSval=1849678056 TSecr=1849678056
Frame 177: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 1, Ack: 5, Len: 0
No.      Time            Source            Destination        Protocol Length Info
    178 170.820632831 127.0.0.1         127.0.0.1         TCP             67      52658 → 9090 [PSH, ACK] Seq=5 Ack=1
Win=65536 Len=1 TSval=1849678056 TSecr=1849678056
Frame 178: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 5, Ack: 1, Len: 1
Data (1 byte)
0000 0a
No.      Time            Source            Destination        Protocol Length Info
    179 170.820639123 127.0.0.1         127.0.0.1         TCP             66      9090 → 52658 [ACK] Seq=1 Ack=6 Win=65536
Len=0 TSval=1849678056 TSecr=1849678056
Frame 179: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 1, Ack: 6, Len: 0
No.      Time            Source            Destination        Protocol Length Info
    180 170.820670342 127.0.0.1         127.0.0.1         TCP             67      52658 → 9090 [PSH, ACK] Seq=6 Ack=1
Win=65536 Len=1 TSval=1849678056 TSecr=1849678056
Frame 180: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 6, Ack: 1, Len: 1
Data (1 byte)
0000 30
No.      Time            Source            Destination        Protocol Length Info
    181 170.820676379 127.0.0.1         127.0.0.1         TCP             66      9090 → 52658 [ACK] Seq=1 Ack=7 Win=65536
Len=0 TSval=1849678056 TSecr=1849678056
Frame 181: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 1, Ack: 7, Len: 0
No.      Time            Source            Destination        Protocol Length Info
    182 170.820698368 127.0.0.1         127.0.0.1         TCP             67      52658 → 9090 [PSH, ACK] Seq=7 Ack=1
Win=65536 Len=1 TSval=1849678056 TSecr=1849678056
Frame 182: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)

```

```

Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 7, Ack: 1, Len: 1
Data (1 byte)
0000 0a
No.      Time                Source                Destination            Protocol Length Info
    183 170.820704587      127.0.0.1            127.0.0.1              TCP          66      9090 → 52658 [ACK] Seq=1 Ack=8 Win=65536
Len=0 TSval=1849678056 TSecr=1849678056
Frame 183: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 1, Ack: 8, Len: 0
No.      Time                Source                Destination            Protocol Length Info
    184 170.821550991      127.0.0.1            127.0.0.1              TCP          67      9090 → 52658 [PSH, ACK] Seq=1 Ack=8
Win=65536 Len=1 TSval=1849678057 TSecr=1849678056
Frame 184: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 1, Ack: 8, Len: 1
Data (1 byte)
0000 45
No.      Time                Source                Destination            Protocol Length Info
    185 170.821591330      127.0.0.1            127.0.0.1              TCP          66      52658 → 9090 [ACK] Seq=8 Ack=2 Win=65536
Len=0 TSval=1849678057 TSecr=1849678057
Frame 185: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 8, Ack: 2, Len: 0
No.      Time                Source                Destination            Protocol Length Info
    186 170.821683243      127.0.0.1            127.0.0.1              TCP          67      9090 → 52658 [PSH, ACK] Seq=2 Ack=8
Win=65536 Len=1 TSval=1849678057 TSecr=1849678057
Frame 186: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 2, Ack: 8, Len: 1
Data (1 byte)
0000 52
No.      Time                Source                Destination            Protocol Length Info
    187 170.821698366      127.0.0.1            127.0.0.1              TCP          66      52658 → 9090 [ACK] Seq=8 Ack=3 Win=65536
Len=0 TSval=1849678057 TSecr=1849678057
Frame 187: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 8, Ack: 3, Len: 0
No.      Time                Source                Destination            Protocol Length Info
    188 170.821756056      127.0.0.1            127.0.0.1              TCP          67      9090 → 52658 [PSH, ACK] Seq=3 Ack=8
Win=65536 Len=1 TSval=1849678057 TSecr=1849678057
Frame 188: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 3, Ack: 8, Len: 1
Data (1 byte)
0000 52
No.      Time                Source                Destination            Protocol Length Info
    189 170.821790105      127.0.0.1            127.0.0.1              TCP          66      52658 → 9090 [ACK] Seq=8 Ack=4 Win=65536
Len=0 TSval=1849678057 TSecr=1849678057
Frame 189: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 8, Ack: 4, Len: 0
No.      Time                Source                Destination            Protocol Length Info
    190 170.821816294      127.0.0.1            127.0.0.1              TCP          67      9090 → 52658 [PSH, ACK] Seq=4 Ack=8
Win=65536 Len=1 TSval=1849678057 TSecr=1849678057
Frame 190: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 4, Ack: 8, Len: 1
Data (1 byte)
0000 4f
No.      Time                Source                Destination            Protocol Length Info
    191 170.821828390      127.0.0.1            127.0.0.1              TCP          66      52658 → 9090 [ACK] Seq=8 Ack=5 Win=65536
Len=0 TSval=1849678057 TSecr=1849678057
Frame 191: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 8, Ack: 5, Len: 0
No.      Time                Source                Destination            Protocol Length Info
    192 170.821898208      127.0.0.1            127.0.0.1              TCP          67      9090 → 52658 [PSH, ACK] Seq=5 Ack=8
Win=65536 Len=1 TSval=1849678057 TSecr=1849678057
Frame 192: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 5, Ack: 8, Len: 1
Data (1 byte)
0000 3a
No.      Time                Source                Destination            Protocol Length Info
    193 170.821913274      127.0.0.1            127.0.0.1              TCP          66      52658 → 9090 [ACK] Seq=8 Ack=6 Win=65536
Len=0 TSval=1849678058 TSecr=1849678057
Frame 193: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)

```

```

Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 8, Ack: 6, Len: 0
No.    Time                Source                Destination            Protocol Length Info
   194 170.821994083      127.0.0.1            127.0.0.1              TCP          67          9090 → 52658 [PSH, ACK] Seq=6 Ack=8
Win=65536 Len=1 TSval=1849678058 TSecr=1849678058
Frame 194: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 6, Ack: 8, Len: 1
Data (1 byte)
0000 20
No.    Time                Source                Destination            Protocol Length Info
   195 170.822007216      127.0.0.1            127.0.0.1              TCP          66          52658 → 9090 [ACK] Seq=8 Ack=7 Win=65536
Len=0 TSval=1849678058 TSecr=1849678058
Frame 195: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 8, Ack: 7, Len: 0
No.    Time                Source                Destination            Protocol Length Info
   196 170.822069528      127.0.0.1            127.0.0.1              TCP          67          9090 → 52658 [PSH, ACK] Seq=7 Ack=8
Win=65536 Len=1 TSval=1849678058 TSecr=1849678058
Frame 196: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 7, Ack: 8, Len: 1
Data (1 byte)
0000 44
No.    Time                Source                Destination            Protocol Length Info
   197 170.822081613      127.0.0.1            127.0.0.1              TCP          66          52658 → 9090 [ACK] Seq=8 Ack=8 Win=65536
Len=0 TSval=1849678058 TSecr=1849678058
Frame 197: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 8, Ack: 8, Len: 0
No.    Time                Source                Destination            Protocol Length Info
   198 170.822133675      127.0.0.1            127.0.0.1              TCP          67          9090 → 52658 [PSH, ACK] Seq=8 Ack=8
Win=65536 Len=1 TSval=1849678058 TSecr=1849678058
Frame 198: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 8, Ack: 8, Len: 1
Data (1 byte)
0000 69
No.    Time                Source                Destination            Protocol Length Info
   199 170.822145337      127.0.0.1            127.0.0.1              TCP          66          52658 → 9090 [ACK] Seq=8 Ack=9 Win=65536
Len=0 TSval=1849678058 TSecr=1849678058
Frame 199: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 8, Ack: 9, Len: 0
No.    Time                Source                Destination            Protocol Length Info
   200 170.822191782      127.0.0.1            127.0.0.1              TCP          67          9090 → 52658 [PSH, ACK] Seq=9 Ack=8
Win=65536 Len=1 TSval=1849678058 TSecr=1849678058
Frame 200: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 9, Ack: 8, Len: 1
Data (1 byte)
0000 76
No.    Time                Source                Destination            Protocol Length Info
   201 170.822202625      127.0.0.1            127.0.0.1              TCP          66          52658 → 9090 [ACK] Seq=8 Ack=10 Win=65536
Len=0 TSval=1849678058 TSecr=1849678058
Frame 201: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 8, Ack: 10, Len: 0
No.    Time                Source                Destination            Protocol Length Info
   202 170.822251641      127.0.0.1            127.0.0.1              TCP          67          9090 → 52658 [PSH, ACK] Seq=10 Ack=8
Win=65536 Len=1 TSval=1849678058 TSecr=1849678058
Frame 202: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 10, Ack: 8, Len: 1
Data (1 byte)
0000 69
No.    Time                Source                Destination            Protocol Length Info
   203 170.822263818      127.0.0.1            127.0.0.1              TCP          66          52658 → 9090 [ACK] Seq=8 Ack=11 Win=65536
Len=0 TSval=1849678058 TSecr=1849678058
Frame 203: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 8, Ack: 11, Len: 0
No.    Time                Source                Destination            Protocol Length Info
   204 170.822312218      127.0.0.1            127.0.0.1              TCP          67          9090 → 52658 [PSH, ACK] Seq=11 Ack=8
Win=65536 Len=1 TSval=1849678058 TSecr=1849678058
Frame 204: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 11, Ack: 8, Len: 1

```


No.	Time	Source	Destination	Protocol	Length	Info
216	170.822647005	127.0.0.1	127.0.0.1	TCP	67	9090 → 52658 [PSH, ACK] Seq=17 Ack=8 Win=65536 Len=1 TSval=1849678058 TSecr=1849678058
Frame 216: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 17, Ack: 8, Len: 1						
Data (1 byte)						
0000	72	r				
No.	Time	Source	Destination	Protocol	Length	Info
217	170.822689832	127.0.0.1	127.0.0.1	TCP	66	52658 → 9090 [ACK] Seq=8 Ack=18 Win=65536 Len=0 TSval=1849678058 TSecr=1849678058
Frame 217: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 8, Ack: 18, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
218	170.822710512	127.0.0.1	127.0.0.1	TCP	67	9090 → 52658 [PSH, ACK] Seq=18 Ack=8 Win=65536 Len=1 TSval=1849678058 TSecr=1849678058
Frame 218: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 18, Ack: 8, Len: 1						
Data (1 byte)						
0000	20					
No.	Time	Source	Destination	Protocol	Length	Info
219	170.822783511	127.0.0.1	127.0.0.1	TCP	66	52658 → 9090 [ACK] Seq=8 Ack=19 Win=65536 Len=0 TSval=1849678058 TSecr=1849678058
Frame 219: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 8, Ack: 19, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
220	170.822796589	127.0.0.1	127.0.0.1	TCP	67	9090 → 52658 [PSH, ACK] Seq=19 Ack=8 Win=65536 Len=1 TSval=1849678058 TSecr=1849678058
Frame 220: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 19, Ack: 8, Len: 1						
Data (1 byte)						
0000	7a	z				
No.	Time	Source	Destination	Protocol	Length	Info
221	170.822866690	127.0.0.1	127.0.0.1	TCP	66	52658 → 9090 [ACK] Seq=8 Ack=20 Win=65536 Len=0 TSval=1849678058 TSecr=1849678058
Frame 221: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 8, Ack: 20, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
222	170.822896522	127.0.0.1	127.0.0.1	TCP	67	9090 → 52658 [PSH, ACK] Seq=20 Ack=8 Win=65536 Len=1 TSval=1849678058 TSecr=1849678058
Frame 222: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 20, Ack: 8, Len: 1						
Data (1 byte)						
0000	65	e				
No.	Time	Source	Destination	Protocol	Length	Info
223	170.822982519	127.0.0.1	127.0.0.1	TCP	66	52658 → 9090 [ACK] Seq=8 Ack=21 Win=65536 Len=0 TSval=1849678059 TSecr=1849678058
Frame 223: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 8, Ack: 21, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
224	170.823020209	127.0.0.1	127.0.0.1	TCP	67	9090 → 52658 [PSH, ACK] Seq=21 Ack=8 Win=65536 Len=1 TSval=1849678059 TSecr=1849678059
Frame 224: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 21, Ack: 8, Len: 1						
Data (1 byte)						
0000	72	r				
No.	Time	Source	Destination	Protocol	Length	Info
225	170.823064191	127.0.0.1	127.0.0.1	TCP	66	52658 → 9090 [ACK] Seq=8 Ack=22 Win=65536 Len=0 TSval=1849678059 TSecr=1849678059
Frame 225: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 8, Ack: 22, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
226	170.823090005	127.0.0.1	127.0.0.1	TCP	67	9090 → 52658 [PSH, ACK] Seq=22 Ack=8 Win=65536 Len=1 TSval=1849678059 TSecr=1849678059
Frame 226: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 22, Ack: 8, Len: 1						
Data (1 byte)						
0000	6f	o				

No.	Time	Source	Destination	Protocol	Length	Info
227	170.823133450	127.0.0.1	127.0.0.1	TCP	66	52658 → 9090 [ACK] Seq=8 Ack=23 Win=65536 Len=0 TSval=1849678059 TSecr=1849678059
Frame 227: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 8, Ack: 23, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
228	170.823146888	127.0.0.1	127.0.0.1	TCP	67	9090 → 52658 [PSH, ACK] Seq=23 Ack=8 Win=65536 Len=1 TSval=1849678059 TSecr=1849678059
Frame 228: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 23, Ack: 8, Len: 1						
Data (1 byte)						
0000 0a						
No.	Time	Source	Destination	Protocol	Length	Info
229	170.823255271	127.0.0.1	127.0.0.1	TCP	66	52658 → 9090 [ACK] Seq=8 Ack=24 Win=65536 Len=0 TSval=1849678059 TSecr=1849678059
Frame 229: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 8, Ack: 24, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
230	170.823424730	127.0.0.1	127.0.0.1	TCP	66	9090 → 52658 [FIN, ACK] Seq=24 Ack=8 Win=65536 Len=0 TSval=1849678059 TSecr=1849678059
Frame 230: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 24, Ack: 8, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
231	170.823426843	127.0.0.1	127.0.0.1	TCP	66	52658 → 9090 [FIN, ACK] Seq=8 Ack=24 Win=65536 Len=0 TSval=1849678059 TSecr=1849678059
Frame 231: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 8, Ack: 24, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
232	170.823447167	127.0.0.1	127.0.0.1	TCP	66	52658 → 9090 [ACK] Seq=9 Ack=25 Win=65536 Len=0 TSval=1849678059 TSecr=1849678059
Frame 232: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 52658, Dst Port: 9090, Seq: 9, Ack: 25, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
233	170.823448857	127.0.0.1	127.0.0.1	TCP	66	9090 → 52658 [ACK] Seq=25 Ack=9 Win=65536 Len=0 TSval=1849678059 TSecr=1849678059
Frame 233: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 52658, Seq: 25, Ack: 9, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
275	223.257476780	127.0.0.1	127.0.0.1	TCP	74	47440 → 9090 [SYN] Seq=0 Win=65495 Len=0 MSS=65495 SACK_PERM TSval=1849730493 TSecr=0 WS=128
Frame 275: 74 bytes on wire (592 bits), 74 bytes captured (592 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 47440, Dst Port: 9090, Seq: 0, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
276	223.257513730	127.0.0.1	127.0.0.1	TCP	74	9090 → 47440 [SYN, ACK] Seq=0 Ack=1 Win=65483 Len=0 MSS=65495 SACK_PERM TSval=1849730493 TSecr=1849730493 WS=128
Frame 276: 74 bytes on wire (592 bits), 74 bytes captured (592 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 47440, Seq: 0, Ack: 1, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
277	223.257542058	127.0.0.1	127.0.0.1	TCP	66	47440 → 9090 [ACK] Seq=1 Ack=1 Win=65536 Len=0 TSval=1849730493 TSecr=1849730493
Frame 277: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 47440, Dst Port: 9090, Seq: 1, Ack: 1, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
278	223.257816433	127.0.0.1	127.0.0.1	TCP	67	47440 → 9090 [PSH, ACK] Seq=1 Ack=1 Win=65536 Len=1 TSval=1849730493 TSecr=1849730493
Frame 278: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 47440, Dst Port: 9090, Seq: 1, Ack: 1, Len: 1						
Data (1 byte)						
0000 31						
No.	Time	Source	Destination	Protocol	Length	Info
279	223.257833090	127.0.0.1	127.0.0.1	TCP	66	9090 → 47440 [ACK] Seq=1 Ack=2 Win=65536 Len=0 TSval=1849730493 TSecr=1849730493
Frame 279: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 47440, Seq: 1, Ack: 2, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info

280	223.257895378	127.0.0.1	127.0.0.1	TCP	67	47440 → 9090 [PSH, ACK] Seq=2 Ack=1
Win=65536 Len=1 TSval=1849730493 TSecr=1849730493						
Frame 280: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 47440, Dst Port: 9090, Seq: 2, Ack: 1, Len: 1						
Data (1 byte)						
0000 0a						
No.	Time	Source	Destination	Protocol	Length	Info
281	223.257904162	127.0.0.1	127.0.0.1	TCP	66	9090 → 47440 [ACK] Seq=1 Ack=3 Win=65536
Len=0 TSval=1849730494 TSecr=1849730493						
Frame 281: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 47440, Seq: 1, Ack: 3, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
282	223.257957915	127.0.0.1	127.0.0.1	TCP	67	47440 → 9090 [PSH, ACK] Seq=3 Ack=1
Win=65536 Len=1 TSval=1849730494 TSecr=1849730494						
Frame 282: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 47440, Dst Port: 9090, Seq: 3, Ack: 1, Len: 1						
Data (1 byte)						
0000 31						
No.	Time	Source	Destination	Protocol	Length	Info
283	223.257964973	127.0.0.1	127.0.0.1	TCP	66	9090 → 47440 [ACK] Seq=1 Ack=4 Win=65536
Len=0 TSval=1849730494 TSecr=1849730494						
Frame 283: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 47440, Seq: 1, Ack: 4, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
284	223.257995904	127.0.0.1	127.0.0.1	TCP	67	47440 → 9090 [PSH, ACK] Seq=4 Ack=1
Win=65536 Len=1 TSval=1849730494 TSecr=1849730494						
Frame 284: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 47440, Dst Port: 9090, Seq: 4, Ack: 1, Len: 1						
Data (1 byte)						
0000 30						
No.	Time	Source	Destination	Protocol	Length	Info
285	223.258002749	127.0.0.1	127.0.0.1	TCP	66	9090 → 47440 [ACK] Seq=1 Ack=5 Win=65536
Len=0 TSval=1849730494 TSecr=1849730494						
Frame 285: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 47440, Seq: 1, Ack: 5, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
286	223.258029502	127.0.0.1	127.0.0.1	TCP	67	47440 → 9090 [PSH, ACK] Seq=5 Ack=1
Win=65536 Len=1 TSval=1849730494 TSecr=1849730494						
Frame 286: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 47440, Dst Port: 9090, Seq: 5, Ack: 1, Len: 1						
Data (1 byte)						
0000 0a						
No.	Time	Source	Destination	Protocol	Length	Info
287	223.258036344	127.0.0.1	127.0.0.1	TCP	66	9090 → 47440 [ACK] Seq=1 Ack=6 Win=65536
Len=0 TSval=1849730494 TSecr=1849730494						
Frame 287: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 47440, Seq: 1, Ack: 6, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
288	223.258073631	127.0.0.1	127.0.0.1	TCP	67	47440 → 9090 [PSH, ACK] Seq=6 Ack=1
Win=65536 Len=1 TSval=1849730494 TSecr=1849730494						
Frame 288: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 47440, Dst Port: 9090, Seq: 6, Ack: 1, Len: 1						
Data (1 byte)						
0000 34						
No.	Time	Source	Destination	Protocol	Length	Info
289	223.258080338	127.0.0.1	127.0.0.1	TCP	66	9090 → 47440 [ACK] Seq=1 Ack=7 Win=65536
Len=0 TSval=1849730494 TSecr=1849730494						
Frame 289: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 47440, Seq: 1, Ack: 7, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
290	223.258105258	127.0.0.1	127.0.0.1	TCP	67	47440 → 9090 [PSH, ACK] Seq=7 Ack=1
Win=65536 Len=1 TSval=1849730494 TSecr=1849730494						
Frame 290: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 47440, Dst Port: 9090, Seq: 7, Ack: 1, Len: 1						
Data (1 byte)						
0000 0a						
No.	Time	Source	Destination	Protocol	Length	Info

```

291 223.258112013 127.0.0.1 127.0.0.1 TCP 66 9090 → 47440 [ACK] Seq=1 Ack=8 Win=65536
Len=0 TSval=1849730494 TSecr=1849730494
Frame 291: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 47440, Seq: 1, Ack: 8, Len: 0
No. Time Source Destination Protocol Length Info
292 223.258649420 127.0.0.1 127.0.0.1 TCP 67 9090 → 47440 [PSH, ACK] Seq=1 Ack=8
Win=65536 Len=1 TSval=1849730494 TSecr=1849730494
Frame 292: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 47440, Seq: 1, Ack: 8, Len: 1
Data (1 byte)
0000 31
No. Time Source Destination Protocol Length Info
293 223.258686706 127.0.0.1 127.0.0.1 TCP 66 47440 → 9090 [ACK] Seq=8 Ack=2 Win=65536
Len=0 TSval=1849730494 TSecr=1849730494
Frame 293: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 47440, Dst Port: 9090, Seq: 8, Ack: 2, Len: 0
No. Time Source Destination Protocol Length Info
294 223.258748015 127.0.0.1 127.0.0.1 TCP 67 9090 → 47440 [PSH, ACK] Seq=2 Ack=8
Win=65536 Len=1 TSval=1849730494 TSecr=1849730494
Frame 294: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 47440, Seq: 2, Ack: 8, Len: 1
Data (1 byte)
0000 34
No. Time Source Destination Protocol Length Info
295 223.258759234 127.0.0.1 127.0.0.1 TCP 66 47440 → 9090 [ACK] Seq=8 Ack=3 Win=65536
Len=0 TSval=1849730494 TSecr=1849730494
Frame 295: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 47440, Dst Port: 9090, Seq: 8, Ack: 3, Len: 0
No. Time Source Destination Protocol Length Info
296 223.258797441 127.0.0.1 127.0.0.1 TCP 67 9090 → 47440 [PSH, ACK] Seq=3 Ack=8
Win=65536 Len=1 TSval=1849730494 TSecr=1849730494
Frame 296: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 47440, Seq: 3, Ack: 8, Len: 1
Data (1 byte)
0000 2e
No. Time Source Destination Protocol Length Info
297 223.258807820 127.0.0.1 127.0.0.1 TCP 66 47440 → 9090 [ACK] Seq=8 Ack=4 Win=65536
Len=0 TSval=1849730494 TSecr=1849730494
Frame 297: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 47440, Dst Port: 9090, Seq: 8, Ack: 4, Len: 0
No. Time Source Destination Protocol Length Info
298 223.258844045 127.0.0.1 127.0.0.1 TCP 67 9090 → 47440 [PSH, ACK] Seq=4 Ack=8
Win=65536 Len=1 TSval=1849730494 TSecr=1849730494
Frame 298: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 47440, Seq: 4, Ack: 8, Len: 1
Data (1 byte)
0000 30
No. Time Source Destination Protocol Length Info
299 223.258853257 127.0.0.1 127.0.0.1 TCP 66 47440 → 9090 [ACK] Seq=8 Ack=5 Win=65536
Len=0 TSval=1849730494 TSecr=1849730494
Frame 299: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 47440, Dst Port: 9090, Seq: 8, Ack: 5, Len: 0
No. Time Source Destination Protocol Length Info
300 223.258901290 127.0.0.1 127.0.0.1 TCP 67 9090 → 47440 [PSH, ACK] Seq=5 Ack=8
Win=65536 Len=1 TSval=1849730494 TSecr=1849730494
Frame 300: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 47440, Seq: 5, Ack: 8, Len: 1
Data (1 byte)
0000 0a
No. Time Source Destination Protocol Length Info
301 223.258910821 127.0.0.1 127.0.0.1 TCP 66 47440 → 9090 [ACK] Seq=8 Ack=6 Win=65536
Len=0 TSval=1849730495 TSecr=1849730494
Frame 301: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 47440, Dst Port: 9090, Seq: 8, Ack: 6, Len: 0
No. Time Source Destination Protocol Length Info
302 223.259040550 127.0.0.1 127.0.0.1 TCP 66 47440 → 9090 [FIN, ACK] Seq=8 Ack=6
Win=65536 Len=0 TSval=1849730495 TSecr=1849730494

```

```

Frame 302: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 47440, Dst Port: 9090, Seq: 8, Ack: 6, Len: 0
No.      Time                Source                Destination            Protocol Length Info
    303 223.259113544    127.0.0.1            127.0.0.1              TCP        66      9090 → 47440 [FIN, ACK] Seq=6 Ack=9
Win=65536 Len=0 TSval=1849730495 TSecr=1849730495
Frame 303: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 47440, Seq: 6, Ack: 9, Len: 0
No.      Time                Source                Destination            Protocol Length Info
    304 223.259165129    127.0.0.1            127.0.0.1              TCP        66      47440 → 9090 [ACK] Seq=9 Ack=7 Win=65536
Len=0 TSval=1849730495 TSecr=1849730495
Frame 304: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 47440, Dst Port: 9090, Seq: 9, Ack: 7, Len: 0
No.      Time                Source                Destination            Protocol Length Info
    305 223.259590430    127.0.0.1            127.0.0.1              TCP        74      47454 → 9090 [SYN] Seq=0 Win=65495 Len=0
MSS=65495 SACK_PERM TSval=1849730495 TSecr=0 WS=128
Frame 305: 74 bytes on wire (592 bits), 74 bytes captured (592 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 47454, Dst Port: 9090, Seq: 0, Len: 0
No.      Time                Source                Destination            Protocol Length Info
    306 223.259609016    127.0.0.1            127.0.0.1              TCP        74      9090 → 47454 [SYN, ACK] Seq=0 Ack=1
Win=65483 Len=0 MSS=65495 SACK_PERM TSval=1849730495 TSecr=1849730495 WS=128
Frame 306: 74 bytes on wire (592 bits), 74 bytes captured (592 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 47454, Seq: 0, Ack: 1, Len: 0
No.      Time                Source                Destination            Protocol Length Info
    307 223.259629686    127.0.0.1            127.0.0.1              TCP        66      47454 → 9090 [ACK] Seq=1 Ack=1 Win=65536
Len=0 TSval=1849730495 TSecr=1849730495
Frame 307: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 47454, Dst Port: 9090, Seq: 1, Ack: 1, Len: 0
No.      Time                Source                Destination            Protocol Length Info
    308 223.259864108    127.0.0.1            127.0.0.1              TCP        67      47454 → 9090 [PSH, ACK] Seq=1 Ack=1
Win=65536 Len=1 TSval=1849730495 TSecr=1849730495
Frame 308: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 47454, Dst Port: 9090, Seq: 1, Ack: 1, Len: 1
Data (1 byte)
0000 33
No.      Time                Source                Destination            Protocol Length Info
    309 223.259874704    127.0.0.1            127.0.0.1              TCP        66      9090 → 47454 [ACK] Seq=1 Ack=2 Win=65536
Len=0 TSval=1849730495 TSecr=1849730495
Frame 309: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 47454, Seq: 1, Ack: 2, Len: 0
No.      Time                Source                Destination            Protocol Length Info
    310 223.259930723    127.0.0.1            127.0.0.1              TCP        67      47454 → 9090 [PSH, ACK] Seq=2 Ack=1
Win=65536 Len=1 TSval=1849730496 TSecr=1849730495
Frame 310: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 47454, Dst Port: 9090, Seq: 2, Ack: 1, Len: 1
Data (1 byte)
0000 0a
No.      Time                Source                Destination            Protocol Length Info
    311 223.259938547    127.0.0.1            127.0.0.1              TCP        66      9090 → 47454 [ACK] Seq=1 Ack=3 Win=65536
Len=0 TSval=1849730496 TSecr=1849730496
Frame 311: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 47454, Seq: 1, Ack: 3, Len: 0
No.      Time                Source                Destination            Protocol Length Info
    312 223.259990036    127.0.0.1            127.0.0.1              TCP        67      47454 → 9090 [PSH, ACK] Seq=3 Ack=1
Win=65536 Len=1 TSval=1849730496 TSecr=1849730496
Frame 312: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 47454, Dst Port: 9090, Seq: 3, Ack: 1, Len: 1
Data (1 byte)
0000 31
No.      Time                Source                Destination            Protocol Length Info
    313 223.259999025    127.0.0.1            127.0.0.1              TCP        66      9090 → 47454 [ACK] Seq=1 Ack=4 Win=65536
Len=0 TSval=1849730496 TSecr=1849730496
Frame 313: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 47454, Seq: 1, Ack: 4, Len: 0
No.      Time                Source                Destination            Protocol Length Info

```

314	223.260034561	127.0.0.1	127.0.0.1	TCP	67	47454 → 9090 [PSH, ACK] Seq=4 Ack=1
Win=65536 Len=1 TSval=1849730496 TSecr=1849730496						
Frame 314: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 47454, Dst Port: 9090, Seq: 4, Ack: 1, Len: 1						
Data (1 byte)						
0000	34		4			
No.	Time	Source	Destination	Protocol	Length	Info
315	223.260041414	127.0.0.1	127.0.0.1	TCP	66	9090 → 47454 [ACK] Seq=1 Ack=5 Win=65536
Len=0 TSval=1849730496 TSecr=1849730496						
Frame 315: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 47454, Seq: 1, Ack: 5, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
316	223.260067134	127.0.0.1	127.0.0.1	TCP	67	47454 → 9090 [PSH, ACK] Seq=5 Ack=1
Win=65536 Len=1 TSval=1849730496 TSecr=1849730496						
Frame 316: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 47454, Dst Port: 9090, Seq: 5, Ack: 1, Len: 1						
Data (1 byte)						
0000	2e		.			
No.	Time	Source	Destination	Protocol	Length	Info
317	223.260073775	127.0.0.1	127.0.0.1	TCP	66	9090 → 47454 [ACK] Seq=1 Ack=6 Win=65536
Len=0 TSval=1849730496 TSecr=1849730496						
Frame 317: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 47454, Seq: 1, Ack: 6, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
318	223.260098240	127.0.0.1	127.0.0.1	TCP	67	47454 → 9090 [PSH, ACK] Seq=6 Ack=1
Win=65536 Len=1 TSval=1849730496 TSecr=1849730496						
Frame 318: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 47454, Dst Port: 9090, Seq: 6, Ack: 1, Len: 1						
Data (1 byte)						
0000	30		0			
No.	Time	Source	Destination	Protocol	Length	Info
319	223.260106790	127.0.0.1	127.0.0.1	TCP	66	9090 → 47454 [ACK] Seq=1 Ack=7 Win=65536
Len=0 TSval=1849730496 TSecr=1849730496						
Frame 319: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 47454, Seq: 1, Ack: 7, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
320	223.260130595	127.0.0.1	127.0.0.1	TCP	67	47454 → 9090 [PSH, ACK] Seq=7 Ack=1
Win=65536 Len=1 TSval=1849730496 TSecr=1849730496						
Frame 320: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 47454, Dst Port: 9090, Seq: 7, Ack: 1, Len: 1						
Data (1 byte)						
0000	0a		.			
No.	Time	Source	Destination	Protocol	Length	Info
321	223.260137340	127.0.0.1	127.0.0.1	TCP	66	9090 → 47454 [ACK] Seq=1 Ack=8 Win=65536
Len=0 TSval=1849730496 TSecr=1849730496						
Frame 321: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 47454, Seq: 1, Ack: 8, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
322	223.260171062	127.0.0.1	127.0.0.1	TCP	67	47454 → 9090 [PSH, ACK] Seq=8 Ack=1
Win=65536 Len=1 TSval=1849730496 TSecr=1849730496						
Frame 322: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 47454, Dst Port: 9090, Seq: 8, Ack: 1, Len: 1						
Data (1 byte)						
0000	32		2			
No.	Time	Source	Destination	Protocol	Length	Info
323	223.260179409	127.0.0.1	127.0.0.1	TCP	66	9090 → 47454 [ACK] Seq=1 Ack=9 Win=65536
Len=0 TSval=1849730496 TSecr=1849730496						
Frame 323: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 9090, Dst Port: 47454, Seq: 1, Ack: 9, Len: 0						
No.	Time	Source	Destination	Protocol	Length	Info
324	223.260204083	127.0.0.1	127.0.0.1	TCP	67	47454 → 9090 [PSH, ACK] Seq=9 Ack=1
Win=65536 Len=1 TSval=1849730496 TSecr=1849730496						
Frame 324: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0						
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)						
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1						
Transmission Control Protocol, Src Port: 47454, Dst Port: 9090, Seq: 9, Ack: 1, Len: 1						
Data (1 byte)						
0000	0a		.			
No.	Time	Source	Destination	Protocol	Length	Info

```

    325 223.260211024 127.0.0.1 127.0.0.1 TCP 66 9090 → 47454 [ACK] Seq=1 Ack=10 Win=65536
Len=0 TSval=1849730496 TSecr=1849730496
Frame 325: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 47454, Seq: 1, Ack: 10, Len: 0
No. Time Source Destination Protocol Length Info
    326 223.260485350 127.0.0.1 127.0.0.1 TCP 67 9090 → 47454 [PSH, ACK] Seq=1 Ack=10
Win=65536 Len=1 TSval=1849730496 TSecr=1849730496
Frame 326: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 47454, Seq: 1, Ack: 10, Len: 1
Data (1 byte)
0000 32
No. Time Source Destination Protocol Length Info
    327 223.260500708 127.0.0.1 127.0.0.1 TCP 66 47454 → 9090 [ACK] Seq=10 Ack=2 Win=65536
Len=0 TSval=1849730496 TSecr=1849730496
Frame 327: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 47454, Dst Port: 9090, Seq: 10, Ack: 2, Len: 0
No. Time Source Destination Protocol Length Info
    328 223.260545690 127.0.0.1 127.0.0.1 TCP 67 9090 → 47454 [PSH, ACK] Seq=2 Ack=10
Win=65536 Len=1 TSval=1849730496 TSecr=1849730496
Frame 328: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 47454, Seq: 2, Ack: 10, Len: 1
Data (1 byte)
0000 38
No. Time Source Destination Protocol Length Info
    329 223.260554447 127.0.0.1 127.0.0.1 TCP 66 47454 → 9090 [ACK] Seq=10 Ack=3 Win=65536
Len=0 TSval=1849730496 TSecr=1849730496
Frame 329: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 47454, Dst Port: 9090, Seq: 10, Ack: 3, Len: 0
No. Time Source Destination Protocol Length Info
    330 223.260590296 127.0.0.1 127.0.0.1 TCP 67 9090 → 47454 [PSH, ACK] Seq=3 Ack=10
Win=65536 Len=1 TSval=1849730496 TSecr=1849730496
Frame 330: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 47454, Seq: 3, Ack: 10, Len: 1
Data (1 byte)
0000 2e
No. Time Source Destination Protocol Length Info
    331 223.260598368 127.0.0.1 127.0.0.1 TCP 66 47454 → 9090 [ACK] Seq=10 Ack=4 Win=65536
Len=0 TSval=1849730496 TSecr=1849730496
Frame 331: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 47454, Dst Port: 9090, Seq: 10, Ack: 4, Len: 0
No. Time Source Destination Protocol Length Info
    332 223.260627990 127.0.0.1 127.0.0.1 TCP 67 9090 → 47454 [PSH, ACK] Seq=4 Ack=10
Win=65536 Len=1 TSval=1849730496 TSecr=1849730496
Frame 332: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 47454, Seq: 4, Ack: 10, Len: 1
Data (1 byte)
0000 30
No. Time Source Destination Protocol Length Info
    333 223.260636304 127.0.0.1 127.0.0.1 TCP 66 47454 → 9090 [ACK] Seq=10 Ack=5 Win=65536
Len=0 TSval=1849730496 TSecr=1849730496
Frame 333: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 47454, Dst Port: 9090, Seq: 10, Ack: 5, Len: 0
No. Time Source Destination Protocol Length Info
    334 223.260663994 127.0.0.1 127.0.0.1 TCP 67 9090 → 47454 [PSH, ACK] Seq=5 Ack=10
Win=65536 Len=1 TSval=1849730496 TSecr=1849730496
Frame 334: 67 bytes on wire (536 bits), 67 bytes captured (536 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 47454, Seq: 5, Ack: 10, Len: 1
Data (1 byte)
0000 0a
No. Time Source Destination Protocol Length Info
    335 223.260672306 127.0.0.1 127.0.0.1 TCP 66 47454 → 9090 [ACK] Seq=10 Ack=6 Win=65536
Len=0 TSval=1849730496 TSecr=1849730496
Frame 335: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 47454, Dst Port: 9090, Seq: 10, Ack: 6, Len: 0
No. Time Source Destination Protocol Length Info
    336 223.260784982 127.0.0.1 127.0.0.1 TCP 66 47454 → 9090 [FIN, ACK] Seq=10 Ack=6
Win=65536 Len=0 TSval=1849730496 TSecr=1849730496

```

Frame 336: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 47454, Dst Port: 9090, Seq: 10, Ack: 6, Len: 0

No.	Time	Source	Destination	Protocol	Length	Info
337	223.261097371	127.0.0.1	127.0.0.1	TCP	66	9090 → 47454 [FIN, ACK] Seq=6 Ack=11 Win=65536 Len=0 TSval=1849730497 TSecr=1849730496

Frame 337: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 9090, Dst Port: 47454, Seq: 6, Ack: 11, Len: 0

No.	Time	Source	Destination	Protocol	Length	Info
338	223.261146627	127.0.0.1	127.0.0.1	TCP	66	47454 → 9090 [ACK] Seq=11 Ack=7 Win=65536 Len=0 TSval=1849730497 TSecr=1849730497

Frame 338: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface lo, id 0
Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_00:00:00 (00:00:00:00:00:00)
Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
Transmission Control Protocol, Src Port: 47454, Dst Port: 9090, Seq: 11, Ack: 7, Len: 0