

This is sample data provided for CALIBER purposes only	ROTARY DRYER MOTOR DATA SHEET	DOC NO: TJC-LLD-DS-YD-2301 REV: 3
--	-------------------------------	---

SDK Polyolefin Expansion Project

ITEM / TAG NO.	YD-2301	EQUIPMENT ID	EQ-1000023011
EQUIPMENT NAME	POLYMER FLUID BED DRYER	TYPE	Rotary Steam-Tube Dryer
PLANT / UNIT	LINEAR LOW DENSITY POLYETHYLENE (LLDPE) UNIT	AREA	2300 - POLYMER SEPARATION & DRYING
FUNCTIONAL LOC.	TJC-LLD-2300-01	CRITICALITY	HIGH CRITICAL
SERVICE	Drying of LLDPE polymer powder from centrifuge to < 300 ppm moisture		

DESIGN & MECHANICAL DATA

DRYER TYPE	ROTARY STEAM-TUBE, INDIRECT	OPERATING TEMP.	95-110 degC
ITEM NO.	YD-2301	BODY MATERIAL	SM400B
DRUM DIAMETER	1800 mm	ROTOR SHAFT	SM400B / SS400
DRUM LENGTH	9000 mm	GLAND PACKING	PTFE (PILLER 4526L)
ROTATION SPEED	4 rpm	OIL SEAL	NBR
HEATING MEDIUM	LP STEAM 4.5 barg	O-RING	NBR
INERT MEDIUM	NITROGEN	ROTARY JOINT	ASSEMBLY, KADANT
DESIGN TEMP.	150 degC	DRIVE	CHAIN & SPROCKET SCM440

DRIVER / MOTOR / HEATER DATA

OUTPUT	22 kW	ENCLOSURE	TEFC IP55
POLES	4 POLE	AREA CLASSIFICATION	ZONE 2, IIA T3
SPEED	1450 rpm	EX PROTECTION	Ex nA IIC T3 Gc
VOLTAGE	380 V / 3 Ph / 50 Hz	FRAME	IEC 180L
RATED CURRENT	43 A	WEIGHT (MOTOR+GEARBOX)	833 kg
INSULATION CLASS	F		

VENDOR / MANUFACTURER	Vendor ABC	DRIVER SUPPLIER	Supplier XYZ
DRIVER TYPE	Electric Motor via Chain-Sprocket, TEFC	DATASHEET REV	Rev 3 - ISSUED FOR OPERATION

NOTES:

- Cross-reference for tag YD-2301: GA Drawing, P&ID; TJC-LLD-PID-2301, Interlock SEQ-5500, OPL sheets and Maintenance History.
- Material of construction per WPN-MAT-001. Refer to interlock trip settings before operation.