

This is sample data provided for CALIBER purposes only	RECIPROCATING COMPRESSOR DATA SHEET	DOC NO: TJC-LLD-DS-KC-4501 REV: 3
--	-------------------------------------	---

SDK Polyolefin Expansion Project

ITEM / TAG NO.	KC-4501	EQUIPMENT ID	EQ-1000045011
EQUIPMENT NAME	RECYCLE GAS COMPRESSOR	TYPE	Reciprocating Compressor (2-stage)
PLANT / UNIT	LINEAR LOW DENSITY POLYETHYLENE (LLDPE) UNIT	AREA	4500 - GAS RECOVERY & COMPRESSION
FUNCTIONAL LOC.	TJC-LLD-4500-01	CRITICALITY	HIGH CRITICAL
SERVICE	Compress recycle ethylene/hexane vapour back to reactor loop		

DESIGN & MECHANICAL DATA

COMPRESSOR TYPE	RECIPROCATING, 2-STAGE, 2-THROW	CYLINDER MATERIAL	NODULAR CAST IRON
ITEM NO.	KC-4501	PISTON RINGS	PTFE FILLED
CAPACITY (SUCTION)	1250 Nm3/h	PACKING	PTFE RINGS, DISTANCE PIECE
SUCTION PRESSURE	1.2 barg	VALVES	PLATE TYPE, SS
DISCHARGE PRESSURE	12.5 barg	LUBE SYSTEM	FORCED FEED + FRAME SPLASH
SUCTION TEMP.	40 degC	SEAL GAS	NITROGEN BUFFER
DISCHARGE TEMP.	115 degC (max)	COOLING	JACKET WATER + INTERCOOLER EA-4502
GAS	ETHYLENE / HEXANE / H2 MIX	VIBRATION MON.	VT-4501 CROSSHEAD

DRIVER / MOTOR / HEATER DATA

OUTPUT	250 kW	ENCLOSURE	WPII
POLES	4 POLE	AREA CLASSIFICATION	ZONE 2, IIB T3
SPEED	1485 rpm	EX PROTECTION	Ex px IIB T3
VOLTAGE	6000 V / 3 Ph / 50 Hz	FRAME	IEC 355
RATED CURRENT	30 A	WEIGHT (MOTOR)	1980 kg
INSULATION CLASS	F		

VENDOR / MANUFACTURER	Vendor ABC	DRIVER SUPPLIER	Supplier XYZ
DRIVER TYPE	Electric Motor, 4-pole	DATASHEET REV	Rev 3 - ISSUED FOR OPERATION

- NOTES:
- Cross-reference for tag KC-4501: GA Drawing, P&ID TJC-LLD-PID-4501, Interlock SEQ-4501, OPL sheets and Maintenance History.
 - Material of construction per WPN-MAT-001. Refer to interlock trip settings before operation.