

# Introduction to Docker

Matthew Treinish

Developer Advocate - IBM

[mtreinish@kortar.org](mailto:mtreinish@kortar.org)

`mtreinish` on Freenode

<https://github.com/mtreinish/intro-to-docker>

July 9th, 2018

# What is Docker?

- ▶ Tooling and platform to manage containers
- ▶ Manages the lifecycle of containers
- ▶ Simplified interface on top of existing technologies for ease of use
- ▶ Works on linux, Mac OS X, and Windows




# Containers


- ▶ A group of processes run in isolation
  - ▶ Similar to VMs by managed at the process level
  - ▶ Run on a shared kernel
- ▶ Each container has its own namespaces
  - ▶ **PID** process IDs
  - ▶ **USER** user and group IDs
  - ▶ **LTS** hostname and domain name
  - ▶ **NS** mount points
  - ▶ **NET** network devices, stacks, ports
  - ▶ **IPC** inter-process communications, message queues
  - ▶ **cgroups** controls limits and monitoring of resources

# Containers vs VMs

## Containers vs. VMs



Containers are isolated, but share OS and, where appropriate, bins/libraries



# Why use containers?

- ▶ Most of the same reasons as VMs
- ▶ Faster startup time, just the time to:
  - ▶ Create new directory
  - ▶ Setup the container's filesystem
  - ▶ Setup network, mounts, etc
  - ▶ Start the process
- ▶ Better Resource utilization

## First container

```
$ docker run ubuntu echo Hello World
```

## What Happened

- ▶ Docker created a directory with an Ubuntu filesystem (image)
- ▶ Docker created a new set of namespaces
- ▶ Ran a new process: `echo Hello World`
- ▶ Using those namespaces to isolate it from other processes
- ▶ Using that new directory as the root of the filesystem (`chroot`)
- ▶ Notice as a user I never installed Ubuntu
- ▶ Run it again, notice how quickly it ran

ssh-ing into a container

```
$ docker run -ti ubuntu bash
```



# What Happened

- ▶ Now the process is *bash* instead of *echo*
- ▶ But its still just a process
- ▶ Look around, mess around, its isolated

## Getting data into a container

- ▶ Using env variables:

```
$ docker run -e INPUT=lamSECURE -P ubuntu bash
```

- ▶ Using Volumess:

```
$ mkdir -p /tmp/volume && echo lamSECURE > /tmp/volume/pass
```

```
$ docker run -i -t -v /tmp/volume:/volume ubuntu bash
```

## Look under the covers

```
$ docker run ubuntu ps -ef
```

## Things to notice with these examples

- ▶ Each container only sees its own processes
- ▶ Running as root
- ▶ Running as PID 1

# Docker images

# Layering

- ▶ Docker uses a copy-on-write (union) filesystem
- ▶ New files (or modifications) are only visible to current/above layers
- ▶ Layers allow for reuse
- ▶ Images are tarballs of layers

# Dockerhub

<https://hub.docker.com>

- ▶ Public registry of Docker Images
- ▶ Hosted by Docker Inc.
- ▶ Free for public images
- ▶ By default docker engines will look in DockerHub for images
- ▶ Browser interface for searching, descriptions of images

## Pick an application

Look at dockerhub and find a container for that application.

For example:

**\$ docker run nginx**



# What Happened

- ▶ Pulled the nginx:latest image from dockerhub
  - ▶ Dockerhub entry: [https://hub.docker.com/\\_/nginx/](https://hub.docker.com/_/nginx/)
  - ▶ Layered on top of debian:stretch-slim image: [https://hub.docker.com/\\_/debian/](https://hub.docker.com/_/debian/)
- ▶ Run that container
- ▶ No configuration, just a base nginx

## Tie it all together

```
$ docker run -v examples/nginx/content:/usr/share/nginx/html:ro nginx
```

# The Dockerfile

Reference Guide: <https://docs.docker.com/engine/reference/builder/>

- ▶ Input script to build images
- ▶ Important instructions:
  - ▶ **FROM** - Set base image either another Dockerfile or from a registry
  - ▶ **RUN** - Run a command inside a new layer
  - ▶ **COPY** - Copy files or directories into the filesystem of the container
  - ▶ **CMD** - Set a default command for executing a container
  - ▶ **EXPOSE** - Specify a port the container listens on

```
FROM python:3.6
```

```
RUN apt-get update
```

```
RUN apt-get install -y build-essential musl-dev
```

```
↳ libxml2-dev git
```

```
RUN pip3 install -U pymysql
```

```
RUN pip3 install -U uwsgi
```

```
RUN git clone
```

```
↳ git://git.openstack.org/openstack/openstack-health
```

```
RUN pip3 install -U ./openstack-health
```

```
RUN cp
```

```
↳ openstack-health/etc/openstack-health-api.conf
```

```
↳ /etc/openstack-health.conf
```

```
EXPOSE 80
```

```
CMD ["/usr/local/bin/uwsgi", "--http", ":80",
```

```
↳ "--wsgi-file",
```

```
↳ "/usr/local/bin/openstack-health"]
```

## Building a Service image

```
1 FROM alpine:3.7
2
3 LABEL Description="Eclipse Mosquitto MQTT Broker"
4
5 RUN apk --no-cache add mosquitto=1.4.15-r0
6 RUN mkdir -p /mosquitto/config /mosquitto/data /mosquitto/log
7 RUN cp /etc/mosquitto/mosquitto.conf /mosquitto/config
8
9 COPY mosquitto.conf /mosquitto/config/mosquitto.conf
10 COPY mqtt_acl.conf /mosquitto/config/mqtt_acl.conf
11
12 RUN chown -R mosquitto:mosquitto /mosquitto
13
14 COPY run.sh /root/run.sh
15
16 EXPOSE 1883
17 EXPOSE 80
18
19 CMD ["/root/run.sh"]
```

- ▶ **\$ docker build -t mymosquitto examples/mosquitto**
- ▶ **\$ docker run -P mymosquitto**

## Back to nginx

Build an image with the same content as our custom nginx before:

```
1 FROM nginx
2
3 COPY content /usr/share/nginx/html
```

- ▶ **\$ docker build -t mycustomnhtml examples/nginx**
- ▶ **\$ docker run -P mycustomhtml**

## What happened

- ▶ Created a new image built on top of the nginx image from Docker Hub
- ▶ It copies the content directory into the nginx shared content directory
- ▶ Then run that image to get

## Running your own registry

```
$ docker run -d -p 5000:5000 --name registry registry
```

## What happened

- ▶ Pulled the registry container from dockerhub
- ▶ Launched the container as a daemon (in the background)
- ▶ Maps localhost port 5000 to port 5000 on the container



## Using a Local Registry

```
$ docker pull debian
```

```
$ docker image tag debian localhost:5000/myspecialimage
```

```
$ docker push localhost:5000/myfirstimage
```

```
$ docker pull localhost:5000/myfirstimage
```

## What happened

- ▶ Pulled the latest debian image from dockerhub
- ▶ Tagged that image off the local registry
- ▶ Push that tagged image to the local registry
- ▶ Pull that image from the registry to the local machine

# Conclusion

## Where to get more information

- ▶ Docker tutorial: <https://github.com/docker/labs/tree/master/beginner>
- ▶ Docker documentation: <https://docs.docker.com/>
- ▶ Best practice for Dockerfiles:  
[https://docs.docker.com/develop/develop-images/dockerfile\\_best-practices/](https://docs.docker.com/develop/develop-images/dockerfile_best-practices/)