handed out: May 5, 2020

handing in: May 14, 2020

presentation/discussion: May 15, 2020

1. Second Iterate present  $\square$ 

The second iterate of the logistic map (3.7) is

$$f^{2}(u) = f(f(u)) = \mu^{2}u[1-u][1-\mu u[1-u]]$$
.

Define a new map as  $u_{i+1} = f^2(u_i)$ .

- (a) Without implementing and running the iteration: What sequences do you expect? How does the attracting set look like, actually: will there be a single attractor? How does this set develop into the chaotic regime?
- (b) Implement the model and reflect your expectations.
- (c) Extend to higher iterates, both conceptually and by numerical simulation.

## 2. Bifurcation Diagram of Logistic Map

present  $\square$ 

Reproduce the bifurcation diagram shown in Figure 3.3 and explore some of its details. Specifically

- (a) Implement the logistic map (3.7) for a fixed value of  $\mu$  and initial value  $u_0$ . Iterate it for the spin-up phase, say for 4'000 steps, without plotting the resulting states. Continue iteration for 400 steps, say, plotting each of the states.
- (b) Integrate the map into a stepper that starts at  $\mu_0$  and sweeps to  $\mu_1$  in  $N_{\mu}$  steps, say with  $N_{\mu} = 1'000$ . Reproduce Figure 3.3.
- (c) Choose some interesting intervals for  $\mu$  and plot the corresponding part of the bifurcation diagram.
- (d) What limits the detail you can zoom into?

Comments: (i) The suggested numbers are from experience. Think about their impact on the final figure. (ii) The plot can be produced by just putting a mark, say a small filled circle at the location of each state to be plotted. This leads to huge file sizes that can be easily compressed by converting to the .png-format. (iii) For those more into programming, an economic approach is to setup an  $n \times m$ -array of integers that discretizes  $[\mu_0, \mu_1] \times [u_0, u_1]$  and allows to count the number of hits in each of the cells. This may then be drawn as a color bitmap. Figure 3.9 in the lecture notes was produced in this way using a 5'000  $\times$  5'000 array with  $N_{\rm spinup} = 4'000$  and  $N_{\rm mark} = 80'000$ . The latter number is so large because it has to provide the color-resolution.

## 3. Transient Phase of Logistic Map

present  $\square$ 

Repeat the previous problem but drop the spin-up phase. The resulting graph is no more a bifurcation diagram because it does not just show the pure attractor but also the approach to it.

- (a) Explain the overall appearance for  $\mu \in [0, 4]$ .
- (b) Select some interesting parts, e.g., a window within the chaotic regime, explore and explain.

## 4. The Last Question

- want to discuss  $\Box$
- (a) What are the key messages you took home from the lecture?
- (b) What are still open questions?
- (c) What associated issues did you miss?