

Release 1.0.1 — WhatsApp chat widget

Floating contact box on the home page that opens a pre-filled wa.me conversation per region.

VERSION

1.0.1

DATE

2026-10-03

STACK

Static HTML · vanilla JS (ES5)

HOSTING

GitHub Pages + Cloudflare

1 Summary

1.0.1 adds a floating WhatsApp chat launcher to [index.html](#). A visitor opens the panel, picks a region (Mexico or Spain today), edits a pre-written greeting and presses *Iniciar chat*, which opens <https://wa.me/<number>?text=<message>> in a new tab. No message passes through any Lameyer server: the widget only builds a link.

It is the only component of the site written as plain JavaScript (an IIFE) rather than JSX, which makes it the easiest piece to move into the 1.2.0 JavaScript codebase, and also the piece most likely to drift because it exists in two copies.

2 Files

File	Change
index.html lines 316–511	Widget block before <code></body></code> : scoped <code><style></code> (lines 318–374), markup <code>#lm-chat</code> (from line 376), and the controller script.
whatsapp-chat-snippet.html	Standalone copy of the same block (196 lines) for pasting into other pages. Identical to the copy in index.html at the time of writing.
readme.md	Versions entry for 1.0.1.

3 How it works

3.1 Configuration

[index.html](#) · widget script

```
var REGIONS = [
  { code: 'MX', dial: '+52', number: '525610074750', text: 'Hola Lameyer, me gustaría información sobre sus servicios.' },
  { code: 'US', dial: '+1', number: '', text: 'Hi Lameyer, I would like information about your services.' },
  { code: 'ES', dial: '+34', number: '34602557685', text: 'Hola Lameyer, me gustaría información sobre sus servicios.' },
  { code: 'IL', dial: '+972', number: '', text: 'Hi Lameyer, I would like information about your services.' }
];
var VALID = /^[1-9]\d{7,14}$/; // E.164 without "+": 8–15 digits, no leading zero
```

- Numbers are digits only, international format, no `+`, spaces or trunk `0`.
- A region whose number is empty or fails `VALID` is dropped. An invalid (non-empty) number logs `[lm-chat] Invalid WhatsApp number for ...` to the console.
- If no region survives, the widget stays `hidden` and logs a warning. With one region, the region picker is hidden.

3.2 Region preselection

The default region is guessed from `Intl.DateTimeFormat().resolvedOptions().timeZone`:

Time zone pattern	Region
Asia/Jerusalem , Asia/Tel_Aviv	IL (hidden until a number is set)
Europe/Madrid , Atlantic/Canary , Africa/Ceuta	ES
12 Mexican America/* zones (Mexico_City, Cancun, Tijuana, ...)	MX
Any other America/* , Pacific/Honolulu	US (hidden until a number is set)
Anything else, or a hidden region	First visible region (MX)

3.3 Behaviour

- **Message:** switching region replaces the text with that region's greeting until the visitor types; after the first `input` event (`edited = true`) their text is kept.
- **Link:** `link()` rebuilds `start.href` on every change; the text is passed through `encodeURIComponent` . An empty message produces a bare `wa.me/<number>` link.
- **Opening:** the anchor uses `target="_blank"` with `rel="noopener noreferrer"` .
- **Stacking:** `z-index: 90` — above page content, below the mobile menu.

3.4 Accessibility

- Launcher exposes `aria-expanded` , `aria-controls="lm-chat-panel"` and a label that switches between "Abrir" and "Cerrar".
- Regions are a `role="radio"` group with roving `tabIndex` and arrow-key navigation.
- Esc closes the panel; focus moves to the start button on open and back to the launcher on close.

4 Operating the widget

Task	Edit
Enable US or IL	Fill <code>number</code> in <code>REGIONS</code> (e.g. US <code>14155552671</code> , IL <code>972501234567</code>) in both copies.
Change a greeting	The region's <code>text</code> .
Colours	CSS custom properties on <code>.lm-chat</code> : <code>--lm-blue</code> , <code>--lm-link</code> , <code>--lm-wa</code> , ...
Add to another page	Paste <code>whatsapp-chat-snippet.html</code> before <code></body></code> . See 5.2 for the shop page.

5 Known issues and limits

5.1 Two copies, two more number sources. The widget code lives in `index.html` and `whatsapp-chat-snippet.html` ; the Spanish number `34602557685` is also hard-coded in `SELLER.whatsapp` in `js/tienda.jsx` (1.0.2). Changing the number means editing three places.

- **5.2 Home page only.** No other page loads the widget. On `/pages/components/` it would sit on top of the floating cart button (both are fixed at 24px from the bottom-right corner).
- **5.3 Outside the component system.** The widget does not use `layout.jsx` , Tailwind or `site.css` ; its ~56 lines of CSS are inline in the page.
- **5.4 innerHTML** builds the region buttons from `REGIONS` . Safe while that list is hand-written config; it must not be fed from user or remote data.
- **5.5 No analytics.** Chats started are not counted, so there is no way to tell which region or page converts.

6 What 1.0.1 is missing for the 1.2.0 JavaScript version

#	Gap	What 1.2.0 needs	Priority
1	Single source for contact data	One module (e.g. <code>src/config/contact.js</code>) exporting the WhatsApp numbers, greetings and <code>CONTACT_EMAIL</code> , imported by the widget, the shop checkout and the terms page.	HIGH
2	Module instead of pasted block	Move the IIFE to <code>src/widgets/chat.js</code> exporting <code>mountChat(el, regions)</code> ; delete <code>whatsapp-chat-snippet.html</code> . Markup is created by the module, not copied into HTML.	HIGH
3	Site-wide mounting	Mount from the shared layout so every page gets it, with an option to offset or hide it where a page has its own floating action (shop cart).	MED
4	Styles in the build	Move the inline <code><style></code> into the bundled stylesheet (or Tailwind classes) so the tokens are shared with the rest of the site.	MED
5	Tests	Unit tests for the number validator, time-zone guess and link builder (Vitest); one browser test that opens the panel and checks the <code>href</code> .	MED
6	Safer DOM building	Replace <code>innerHTML</code> with <code>textContent</code> /element creation once the config can come from a JSON file.	LOW
7	Missing regions	US and IL numbers (business input, not code).	LOW

Port order: this is the smallest, dependency-free piece, so it is a good first module to prove the 1.2.0 build pipeline (bundle, deploy, test) before touching the shop.