Deep Learning for Humanists @DHSI2022 – Day 2

Hoyeol Kim

These slides will be shared on GitHub

Computer Vision Tasks

- Image classification
- Object detection
  - Face recognition
  - Edge detection
- Image restoration
  - Colorization
  - Creating styles
- Video motion analysis



Boundary Coordinates $(x_{min}, y_{min}, x_{max}, y_{max}) = (0.66, 0.65, 0.90, 0.95)$

Classification

CAT

Classification + Localization

CAT

Single object

Object Detection



CAT, DOG, DUCK

Instance Segmentation

CAT, DOG, DUCK

Multiple objects

Object Detection



Boundary Coordinates $(x_{min}, y_{min}, x_{max}, y_{max}) = (640, 356, 870, 520)$



Boundary Coordinates $(x_{min}, y_{min}, x_{max}, y_{max}) = (0.66, 0.65, 0.90, 0.95)$

Object Detection Models



Source: https://arxiv.org/pdf/1905.05055.pdf

Object Detection Models

1-Stage Detector - Regional Proposal와 Classification이 동시에 이루어짐.



2-Stage Detector - Regional Proposal와 Classification이 순차적으로 이루어짐.



- Selective Search
- Region Proposal Network
- etc.

Many stage



Input image | Object / region proposals | Deep Learning region classifier | Region classification, box regression

One stage





Redmond et al. You Only Look Once: Unified Real-time Object Detection. In CVPR 2016

R-CNN

R-CNN: *Regions with CNN features*



1. Input image

2. Extract region proposals (~2k)

3. Compute CNN features

4. Classify regions

Fast R-CNN


Deep
ConvNet
RoI
projection
Conv
feature map
RoI
pooling
layer
FCs
Outputs:
softmax
bbox
regressor
FC
FC
RoI feature
vector
For each RoI

Faster R-CNN


classifier
RoI pooling
proposals
Region Proposal Network
feature maps
conv layers
image

YOLO (You Only Look Once)



RetinaNet



Figure 3. The one-stage **RetinaNet** network architecture uses a Feature Pyramid Network (FPN) [20] backbone on top of a feedforward ResNet architecture [16] (a) to generate a rich, multi-scale convolutional feature pyramid (b). To this backbone RetinaNet attaches two subnetworks, one for classifying anchor boxes (c) and one for regressing from anchor boxes to ground-truth object boxes (d). The network design is intentionally simple, which enables this work to focus on a novel focal loss function that eliminates the accuracy gap between our one-stage detector and state-of-the-art two-stage detectors like Faster R-CNN with FPN [20] while running at faster speeds.

Article: https://arxiv.org/pdf/1708.02002.pdf

Source: https://developers.arcgis.com/python/guide/how-retinanet-works/#:~:text=RetinaNet%20is%20one%20of%20the,with%20aerial%20and%20satellite%20imagery.

Object Detection: Dataset

LARXEL · UPDATED 2 YEARS AGO

1353 | New Notebook | Download (417 MB)

Face Mask Detection

853 images belonging to 3 classes.

Data | Code (159) | Discussion (5) | Metadata

About Dataset

Preview

About this Data

Masks play a crucial role in protecting the health of individuals against respiratory diseases, as is one of the few precautions available for COVID-19 in the absence of immunization. With this dataset, it is possible to create a model to detect people wearing masks, not wearing them, or wearing masks improperly.
This dataset contains **853** images belonging to the **3** classes, as well as their bounding boxes in the PASCAL VOC format.
The classes are:

Usability
8.75

License
CC0: Public Domain

Expected update frequency
Never

Kaggle dataset: kaggle.com/datasets/andrewmvd/face-mask-detection

Machine Learning Frameworks

TensorFlow

PyTorch

K

NumPy: transpose() / dot()

```
numpy.dot(3, 4)
```

3×4





Data Augmentation

Data augmentation is used to increase the amount of data by adding modified copies of already existing data.

There are a variety of data augmentation techniques, such as rotation, flipping, and cropping.

Recommneded Source: https://nanonets.com/blog/data-augmentation-how-to-use-deep-learning-when-you-have-limited-data-part-2/

Any Questions?