

*"Debugging is twice as hard as writing the code in the first place. Therefore, if you write the code as cleverly as possible, you are, by definition, not smart enough to debug it."*

- Brian W. Kernighan and P. J. Plauger in *The Elements of Programming Style*

# CSE102

## Computer Programming with C

Spring 2025

Simple Data Types

© 2015-2025 Yakup Genç

## Overview

- Standard data types
  - char, int, double, etc.
  - logical values
- Define new data types
  - enumerated types
- Passing functions as parameters to subprogram/functions

April 2025

CSE102 Computer Programming

2

1

2

## Representation of Numeric Types

### • Why more than one numeric type?

- integers
  - faster
  - less space
  - precise
- double
  - larger interval (large and small values)

type int format

binary number

type double format

mantissa

exponent

April 2025

CSE102 Computer Programming

3

## Print Ranges for Positive Numeric Data

```

1.  /*
2.   * Find implementation's ranges for positive numeric data
3.   */
4.
5.  #include <stdio.h>
6.  #include <limits.h> /* definition of INT_MAX
7.  #include <float.h> /* definitions of DBL_MIN, DBL_MAX
8.
9.  int
10. main(void)
11. {
12.     printf("Range of positive values of type int: 1 . . %d\n",
13.           INT_MAX);
14.     printf("Range of positive values of type double: %e . . %e\n",
15.           DBL_MIN, DBL_MAX);
16.
17.     return (0);
18. }
```

April 2025

CSE102 Computer Programming

4

3

4

## Numerical Inaccuracies

### Errors in representing real numbers using double

- representational error
  - round-off error
  - magnified through repeated calculation
  - use as a loop control
- cancelation error
  - manipulating very small and very large real numbers
- arithmetic underflow
  - too small to represent
- arithmetic overflow
  - too large to represent

```
double x = 1.0000000000000001; // rounded to 1 + 5*2^{-52}
double y = 1.0000000000000002; // rounded to 1 + 9*2^{-52}
double z = y - x;                // difference is exactly 4*2^{-52}
```

April 2025

CSE102 Computer Programming

5

## Type Conversion

- Automatic conversion
  - arithmetic operations
  - assignment
  - parameter passing
- Explicit conversion
  - casting
    - `frac = n1 / d1;`
    - `frac = (double) (n1 / d1);`
    - `frac = (double) n1 / d1;`

April 2025

CSE102 Computer Programming

6

## Representation and Conversion of char

- ASCII
  - numeric code (32 to 126 printable and others control char)
- constant:
  - `'a'`
- variable:
  - `char letter;`
- assignment:
  - `letter = 'A';`
- Comparison: `==`, `!=`, `<`, `>`, `<=`, `>=`
  - if (`letter > 'A'`)
- Relation with integer
  - compare
  - convert

April 2025

CSE102 Computer Programming

7

## Print Part of Collating Sequence

```
1. /*
2.  * Prints part of the collating sequence
3.  */
4.
5. #include <stdio.h>
6.
7. #define START_CHAR ' '
8. #define END_CHAR 'z'
9.
10. int
11. main(void)
12. {
13.     int char_code; /* numeric code of each character printed */
14.
15.     for (char_code = (int)START_CHAR;
16.          char_code <= (int)END_CHAR;
17.          char_code = char_code + 1)
18.         printf("c", (char)char_code);
19.     printf("\n");
20.
21.     return (0);
22. }
```

April 2025

CSE102 Computer Programming

8

## Enumerated Types

- Defines new data type

```
typedef enum
{ sunday, monday, tuesday, wednesday,
  thursday, friday, saturday }
day_t;
```

- `day_t` is a new type
  - has seven possible values
- `sunday` is an enumeration constant represented by 0
  - similarly, `monday` = 1, `tuesday` = 2, etc.

April 2025

CSE102 Computer Programming

9

## Enumerated Types

```
typedef enum
{ sunday, monday, tuesday, wednesday,
  tuesday, friday, saturday }
day_t;
```

```
day_t today;
```

- `today` is of type `day_t`
  - manipulated as other integers

```
today = sunday
today < monday
```

April 2025

CSE102 Computer Programming

10

10

## Enumerated Types

General syntax:

```
typedef enum
{ identifier_list }
enum_type;

enum_type variable_identifier;
```

April 2025

CSE102 Computer Programming

11

## Enumerated Types

```
typedef enum
{ sunday, monday, tuesday, wednesday, tuesday, friday, saturday }
```

```
day_t;
```

```
day_t today;
```

```
if (today == saturday)
    tomorrow = sunday
else
```

```
    tomorrow = (day_t)(today + 1)
```

```
today = friday + 3;
```

April 2025

CSE102 Computer Programming

12

12

## Enumerated Type for Budget Expenses

```

1. /* Program demonstrating the use of an enumerated type */
2.
3. #include <stdio.h>
4.
5. typedef enum
6. {entertainment, rent, utilities, food, clothing,
7.  automobile, insurance, miscellaneous}
8. expense_t;
9.
10. void print_expense(expense_t expense_kind);
11.
12. int
13. main(void)
14. {
15.     expense_t expense_kind;
16.
17.     scanf("%d", &expense_kind);
18.     printf("Expense code represents ");
19.     print_expense(expense_kind);
20.     printf("\n");
21.
22.     return (0);
23. }

```

April 2025

CSE102 Computer Programming

13

13

## Enumerated Type for Budget Expenses

```

25. /*
26.  * Display string corresponding to a value of type expense_t
27.  */
28. void
29. print_expense(expense_t expense_kind)
30. {
31.     switch (expense_kind) {
32.         case entertainment:
33.             printf("entertainment");
34.             break;
35.
36.         case rent:
37.             printf("rent");
38.             break;
39.
40.         case utilities:
41.             printf("utilities");
42.             break;
43.
44.         case food:
45.             printf("food");
46.             break;
47.
48.         case clothing:
49.             printf("clothing");
50.             break;
51.
52.         case automobile:
53.             printf("automobile");
54.             break;
55.
56.         case insurance:
57.             printf("insurance");
58.             break;
59.
60.         case miscellaneous:
61.             printf("miscellaneous");
62.             break;
63.
64.         default:
65.             printf("\n*** INVALID CODE ***\n");
66.     }
67. }

```

April 2025

CSE102 Computer Programming

14

14

## Accumulating Weekday Hours Worked

```

5. typedef enum
6. {monday, tuesday, wednesday, thursday, friday,
7.  saturday, sunday}
8. day_t;
9.
10. void print_day(day_t day);
11.
12. int
13. main(void)
14. {
15.     double week_hours, day_hours;
16.     day_t today;
17.
18.     week_hours = 0.0;
19.     for (today = monday; today <= friday; ++today) {
20.         printf("Enter hours for ");
21.         print_day(today);
22.         printf("> ");
23.         scanf("%lf", &day_hours);
24.         week_hours += day_hours;
25.     }
26.
27.     printf("\nTotal weekly hours are %.2f\n", week_hours);
28.
29.     return (0);
30. }

```

April 2025


CSE102 Computer Programming

15

15

## Finding Roots of Equations

- Equation:  $f(x)$
- Root: value  $k$  where  $f(k)=0$



April 2025


CSE102 Computer Programming

16

16

## Case Study: Bisection Method

- Problem: Find approximate root of a function on an interval that contains an odd number of roots
- Analysis
  - Change of sign in the interval: odd number of roots



April 2025

CSE102 Computer Programming

17

17

## Case Study: Bisection Method

- Problem: Find approximate root of a function on an interval that contains an odd number of roots
- Analysis
  - Assume change of sign in the interval  $[x\_left, x\_right]$ 
    - only one root
  - Assume  $f(x)$  is continuous on the interval
  - Let  $x\_mid = (x\_left + x\_right) / 2.0$
- Three possibilities
  - root is in the lower half
  - root is in the upper half
  - $f(x\_mid) = 0$


April 2025

CSE102 Computer Programming

18

18

## Three possibilities



April 2025

CSE102 Computer Programming

19

19

## Finding Roots of Equations

- Bisection method:
  - Generate approximate roots until true root is found
    - or the difference is small (less than epsilon 0.00001)
- Bisection function is more usable if can find the root of any function
  - Function should be a parameter to the bisection function

April 2025

CSE102 Computer Programming

20

20

## Function Parameter

- Declaring a function parameter
  - including function prototype in the parameter list
  - as in the following evaluate function

```

1.  /*
2.   * Evaluate a function at three points, displaying results.
3.   */
4.  void
5.  evaluate(double f(double f_arg), double pt1, double pt2, double pt3)
6.  {
7.      printf("f(%.5f) = %.5f\n", pt1, f(pt1));
8.      printf("f(%.5f) = %.5f\n", pt2, f(pt2));
9.      printf("f(%.5f) = %.5f\n", pt3, f(pt3));
10. }
```

- Calling the function  
evaluate(sqrt, 0.25, 25.0, 100);

April 2025

CSE102 Computer Programming

21

## Case Study: Bisection Method

- Inputs:
  - x\_left - double
  - x\_right - double
  - epsilon - double
  - funtion – double f (double farg)
- Outputs
  - root - double
  - error – int (indicating possible error in computation)

April 2025

CSE102 Computer Programming

22

## Bisection Method: Algorithm

```

if the interval contains even number of roots
    set error flag
else
    clear error flag
    repeat while interval is larger than epsilon and root not found
        compute function value at the midpoint
        if the function value is zero
            the midpoint is the root
        if the root is in left half
            change right end to midpoint
        else
            change left end to midpoint
    return the midpoint as the root
```

April 2025

CSE102 Computer Programming

23

## Finding Root Using Bisection Method

```

1.  /*
2.   * Finds roots of the equations
3.   *   g(x) = 0   and   h(x) = 0
4.   * on a specified interval [x_left, x_right] using the bisection method.
5.   */
6.
7.  #include <stdio.h>
8.  #include <math.h>
9.
10. #define FALSE 0
11. #define TRUE 1
12.
13. double bisection(double x_left, double x_right, double epsilon,
14.                 double f(double farg), int *errp);
15. double g(double x);
16. double h(double x);
17.
18. int
19. main(void)
20. {
21.     double x_left, x_right, /* left, right endpoints of interval */
22.           epsilon,         /* error tolerance */
23.           root;
24.     int    error;
25. }
```

April 2025

CSE102 Computer Programming

24

## Finding Root Using Bisection Method

```

26.  /* Get endpoints and error tolerance from user          */
27.  printf("\nEnter interval endpoints> ");
28.  scanf("%lf%lf", &x_left, &x_right);
29.  printf("\nEnter tolerance> ");
30.  scanf("%lf", &epsilon);
31.
32.  /* Use bisection function to look for roots of g and h    */
33.  printf("\n\nFunction g");
34.  root = bisection(x_left, x_right, epsilon, g, &error);
35.  if (!error)
36.      printf("\n    g(%.7f) = %e\n", root, g(root));
37.
38.  printf("\n\nFunction h");
39.  root = bisection(x_left, x_right, epsilon, h, &error);
40.  if (!error)
41.      printf("\n    h(%.7f) = %e\n", root, h(root));
42.  return (0);
43.  }
44.  **

```

April 2025

CSE102 Computer Programming

25

25

## Finding Root Using Bisection Method

```

45.  /*
46.  * Implements the bisection method for finding a root of a function f.
47.  * Finds a root (and sets output parameter error flag to FALSE) if
48.  * signs of fp(x_left) and fp(x_right) are different. Otherwise sets
49.  * output parameter error flag to TRUE.
50.  */
51.  double
52.  bisection(double x_left, /* input - endpoints of interval in */
53.            double x_right, /* which to look for a root */
54.            double epsilon, /* input - error tolerance */
55.            double f(double farg), /* input - the function */
56.            int *errp) /* output - error flag */
57.  {
58.      double x_mid, /* midpoint of interval */
59.            f_left, /* f(x_left) */
60.            f_mid, /* f(x_mid) */
61.            f_right; /* f(x_right) */
62.      int root_found = FALSE;
63.

```

April 2025

CSE102 Computer Programming

26

26

## Finding Root Using Bisection Method

```

64.  /* Computes function values at initial endpoints of interval */
65.  f_left = f(x_left);
66.  f_right = f(x_right);
67.
68.  /* If no change of sign occurs on the interval there is not a
69.  unique root. Searches for the unique root if there is one.*/
70.  if (f_left * f_right > 0) { /* same sign */
71.      *errp = TRUE;
72.      printf("\nMay be no root in [%.7f, %.7f]", x_left, x_right);
73.  } else {
74.      *errp = FALSE;
75.
76.      /* Searches as long as interval size is large enough
77.      and no root has been found */
78.      while (fabs(x_right - x_left) > epsilon && !root_found) {
79.
80.          /* Computes midpoint and function value at midpoint */
81.          x_mid = (x_left + x_right) / 2.0;
82.          f_mid = f(x_mid);

```

(continued)

April 2025

CSE102 Computer Programming

27

27

## Finding Root Using Bisection Method

```

83.      if (f_mid == 0.0) { /* Here's the root */
84.          root_found = TRUE;
85.      } else if (f_left * f_mid < 0.0) { /* Root in [x_left, x_mid] */
86.          x_right = x_mid;
87.      } else { /* Root in [x_mid, x_right] */
88.          x_left = x_mid;
89.          f_left = f_mid;
90.      }
91.
92.      /* Prints root and interval or new interval */
93.      if (root_found)
94.          printf("\nRoot found at x = %.7f, midpoint of [%.7f,
95.          %.7f]",
96.                x_mid, x_left, x_right);
97.      else
98.          printf("\nNew interval is [%.7f, %.7f]",
99.                x_left, x_right);
100.
101.  }
102.
103.  /* If there is a root, it is the midpoint of [x_left, x_right] */
104.  return ((x_left + x_right) / 2.0);
105.  }
106.

```

April 2025

CSE102 Computer Programming

28

28

## Finding Root Using Bisection Method

```

107. /* Functions for which roots are sought */
108.
109. /* 3 2
110. * 5x - 2x + 3
111. */
112. double
113. g(double x)
114. {
115.     return (5 * pow(x, 3.0) - 2 * pow(x, 2.0) + 3);
116. }
117.
118. /* 4 2
119. * x - 3x - 8
120. */
121. double
122. h(double x)
123. {
124.     return (pow(x, 4.0) - 3 * pow(x, 2.0) - 8);
125. }

```

April 2025

CSE102 Computer Programming

29

29

## Sample Run of Bisection Program

```

Enter interval endpoints> -1.0 1.0
Enter tolerance> 0.001

Function g
New interval is [-1.000000, 0.000000]
New interval is [-1.000000, -0.500000]
New interval is [-0.750000, -0.500000]
New interval is [-0.750000, -0.625000]
New interval is [-0.750000, -0.687500]
New interval is [-0.750000, -0.718750]
New interval is [-0.734375, -0.718750]
New interval is [-0.734375, -0.7265625]
New interval is [-0.7304688, -0.7265625]
New interval is [-0.7304688, -0.7285156]
New interval is [-0.7294922, -0.7285156]
g(-0.7290039) = -2.697494e-05

Function h
May be no root in [-1.000000, 1.000000]

```


April 2025

CSE102 Computer Programming

30

30

## Geometric Interpretation of Newton's Method




April 2025

CSE102 Computer Programming

31

31

## Approximating Area Under a Curve



April 2025


CSE102 Computer Programming

32

32



# Finite State Machine for Numbers and Identifiers



April 2025

CSE102 Computer Programming

33

Thanks for listening!

34