


"Everybody ... should learn to program a computer ... because it teaches you to think."
- Steve Jobs

CSE102

Computer Programming with C

Spring 2025
Introduction to Programming with C
© 2015-2025 Yakup Genç

Computation



February 2025


CSE102 Computer Programming in C

2

1

2

Computation



How to build?

How to describe?


How to convert descriptions to machine?

February 2025

CSE102 Computer Programming in C

3

How to Build?



February 2025

CSE102 Computer Programming in C

4

3

4

How to Describe?

Knowledge

Declarative/Descriptive

Sharks in water are deadly for swimmers.

Procedural/Imperative

When lifeguards see a shark, they warn swimmers around.

February 2025

CSE102 Computer Programming in C

5

How to Translate?

- Programming
- Programming Languages
- Describing Language
 - Syntax
 - Semantic

February 2025

CSE102 Computer Programming in C


6

Machine Models

Fixed Program



Stored Program



February 2025

CSE102 Computer Programming in C

7

A Simple Stored Program Machine

February 2025

CSE102 Computer Programming in C

8

Programming Languages

What's a programming language?

A programming language is an artificial language designed to communicate instructions to a machine, particularly a computer [Wikipedia].

A language is a "conceptual universe" providing a framework for problem-solving and useful concepts and programming methods [Perlis].

How many programming languages are there?

Thousands!

Which one to use?

For now, we will claim C...

February 2025

CSE102 Computer Programming in C

9

9

Programming Language Popularity

| | IEEE | PYPL | RedMonk |
|----|------------|------------|------------|
| 1 | Python | Python | JavaScript |
| 2 | Java | Java | Python |
| 3 | JavaScript | JavaScript | Java |
| 4 | C++ | C# | PHP |
| 5 | SQL | C/C++ | C# |
| 6 | C# | R | TypeScript |
| 7 | Go | PHP | CSS |
| 8 | C | TypeScript | C++ |
| 9 | HTML | Swift | Ruby |
| 10 | Rust | Rust | C |

February 2025

CSE102 Computer Programming in C

10

10

Programming Language Popularity

| Sep 2024 | Sep 2023 | Change | Programming Language | Rating | Change |
|----------|----------|--------|----------------------|--------|--------|
| 1 | 1 | | Python | 20.17% | +6.01% |
| 2 | 3 | ▲ | C++ | 10.75% | +0.09% |
| 3 | 4 | ▲ | Java | 9.45% | -0.04% |
| 4 | 2 | ▼ | C | 8.89% | -2.38% |
| 5 | 5 | | C# | 6.08% | -1.22% |
| 6 | 6 | | JavaScript | 3.92% | +0.62% |
| 7 | 7 | | Visual Basic | 2.70% | +0.48% |
| 8 | 12 | ▲ | Go | 2.35% | +1.16% |
| 9 | 10 | ▲ | SQL | 1.94% | +0.50% |
| 10 | 11 | ▲ | Fortran | 1.76% | +0.49% |
| 11 | 15 | ▲ | Delphi/Object Pascal | 1.77% | +0.75% |
| 12 | 13 | ▲ | MATLAB | 1.47% | +0.28% |
| 13 | 8 | ▼ | PHP | 1.46% | -0.09% |
| 14 | 17 | ▲ | Rust | 1.32% | +0.35% |

February 2025

CSE102 Computer Programming in C

11

11

History of C

- C Programming Language
 - Evolved by Ritchie from two previous programming languages, BCPL and B
 - Used to develop UNIX
 - Used to write modern operating systems
 - Hardware independent (portable)
 - By late 1970's C had evolved to "Traditional C"
- Standardization
 - Many slight variations of C existed, and were incompatible
 - Committee formed to create an "unambiguous, machine-independent" definition
 - Standard created in 1989, updated in 1999

February 2025

CSE102 Computer Programming in C

12

12

Portability Tips

- Because C is a hardware-independent, widely available language, applications written in C can run with little or no modifications on a wide range of different computer systems

February 2025

CSE102 Computer Programming in C

13

C Standard Library

- C programs consist of pieces/modules called functions
 - A programmer can create his own functions
 - Advantage: the programmer knows exactly how it works
 - Disadvantage: time consuming
 - Programmers will often use the C library functions
 - C defines a small number of operations, instead it contains useful libraries
 - Use these as building blocks
 - Avoid re-inventing the wheel
 - If a pre-made function exists, generally best to use it rather than write your own
 - Library functions carefully written, efficient, and portable

February 2025

CSE102 Computer Programming in C

14

Performance Tips

- Using Standard C library functions instead of writing your own comparable versions can improve **program performance**, because these functions are carefully written to perform efficiently.

February 2025

CSE102 Computer Programming in C

15

Portability Tips

- Using Standard C library functions instead of writing your own comparable versions can improve **program portability**, because these functions are used in virtually all Standard C implementations.

February 2025

CSE102 Computer Programming in C

16

13

14

15

16

Software Engineering Observation

- Read the manuals for the version of C you are using. Reference these manuals frequently to be sure you are aware of the rich collection of C features and that you are using these features correctly.


February 2025

CSE102 Computer Programming in C

17

17

Typical C Program Development



February 2025

CSE102 Computer Programming in C

18

18

Software Engineering Observation

- Your computer and compiler are good teachers. If you are not sure how a feature of C works, write a sample program with that feature, compile and run the program and see what happens.

February 2025


CSE102 Computer Programming in C

19

19

Software Development

- Programming = problem solving
- Methodology
 - Specify the problem requirements
 - Analyze the problem
 - Design an algorithm
 - Implement the algorithm
 - Test and verify the program
 - Maintain and update the program



February 2025

CSE102 Computer Programming in C

20

20

Problem Requirements

- Statements of the problem
 - Understand the problem
 - Retrieve the requirements
 - Eliminate unimportant aspects
- May need to get information from specialists
- E.g., write a program for mile to kilometer conversion

February 2025

CSE102 Computer Programming in C

21

Software Development

- Programming = problem solving
- Methodology
 - Specify the problem requirements
 - Analyze the problem
 - Design an algorithm
 - Implement the algorithm
 - Test and verify the program
 - Maintain and update the program

February 2025

CSE102 Computer Programming in C

22

Analysis

- Identify
 - Input data
 - Output data
 - Additional requirements and constraints
- Decide aspects of data
 - Representation
 - Relationships
- E.g.
 - Input: distance on miles
 - Output: distance on kilometers
 - Representation: floating point numbers
 - Relationship: 1 mile = 1.609 kilometers

February 2025

CSE102 Computer Programming in C

23

Software Development

- Programming = problem solving
- Methodology
 - Specify the problem requirements
 - Analyze the problem
 - Design an algorithm
 - Implement the algorithm
 - Test and verify the program
 - Maintain and update the program

February 2025

CSE102 Computer Programming in C

24

21

22

23

24

Designing Algorithm

- Top-down stepwise refinement
 - List major steps (sub-problems)
 - Break down each step into a more detailed list
- Desk-check your algorithm
 - Perform steps of the algorithm by yourself
 - E.g.
 1. Get the distance in miles
 2. Convert the distance to kilometers
 3. Display the distance in kilometers
 - Step 2 may require further refinement
 - 2.1 The distance in kilometers is 1.609 times the distance in miles

February 2025

CSE102 Computer Programming in C

25

Software Development

- Methodology
 - Specify the problem requirements
 - Analyze the problem
 - Design an algorithm
 - Implement the algorithm
 - Writing the algorithm in C by converting each step into statements of C
 - Test and verify the program
 - Run the program for several input cases
 - Maintain and update the program
 - Keep the program up-to-date

February 2025

CSE102 Computer Programming in C

26

Today @ CSE102

February 2025

CSE102 Computer Programming in C

27

C Language Elements

```

/*
 * Converts distances from miles to kilometers.
 */
#include <stdio.h> /* printf, scanf definitions */
#define KMS_PER_MILE 1.609 /* conversion constant */

int main(void)
{
    double miles, /* distance in miles */
           kms; /* equivalent distance in kilometers */

    /* Get the distance in miles. */
    printf("Enter the distance in miles> ");
    scanf("%lf", &miles);

    /* Convert the distance to kilometers. */
    kms = KMS_PER_MILE * miles;

    /* Display the distance in kilometers. */
    printf("That equals %f kilometers.\n", kms);

    return (0);
}

```

The diagram illustrates various C language elements with arrows pointing to them in the code snippet above:

- preprocessor directive**: points to `#include <stdio.h>` and `#define KMS_PER_MILE 1.609`.
- standard header file**: points to `<stdio.h>`.
- comment**: points to the block comment at the top and the comment `/* printf, scanf definitions */`.
- constant**: points to the value `1.609` in the `#define` statement.
- reserved word**: points to `int` and `return`.
- variable**: points to `miles` and `kms`.
- standard identifier**: points to `main`, `printf`, `scanf`, and `return`.
- special symbol**: points to `*`, `&`, `%`, and `\n`.
- punctuation**: points to `{`, `}`, `(`, and `)`.

February 2025

CSE102 Computer Programming in C

28

Preprocessor Directives


- Preprocessor modifies the text of a C program before compilation
- Preprocessor directives
 - Start with a #
- #include <stdio.h>
 - Each library has a header file. Include it to access the library
 - Preprocessor inserts definitions from the header
 - stdio.h includes information about standard input/output
- #define KMS_PER_MILE 1.609
 - Defines a constant macro
 - Value of KMS_PER_MILE can not change
 - Preprocessor replaces each occurrence of KMS_PER_MILE in the text with 1.609
 - KMS_PER_MILE is easier to remember

February 2025

CSE102 Computer Programming in C

29

C Language Elements



February 2025

CSE102 Computer Programming in C

30

Function main

- C programs have exactly one main function
 - Marks the beginning of program execution
 - (void) indicates that function receives no data
 - int means that main "returns" an integer value
- Function bodies enclosed in braces ({ and })
 - Function body has two parts
 - Declaration
 - Executable statements

February 2025

CSE102 Computer Programming in C

31

Identifiers

- Reserved words
 - E.g.: "int" and "void"
 - Can not be used for any other purpose
- Standard identifiers
 - E.g.: scanf, printf
 - Has a special meaning but can be redefined
- User-defined identifiers
 - E.g.: name of memory cells (miles) and KMS_PER_MILE
 - Free to select the name
 - Syntax rules:
 - Includes only letters, digits and underscore
 - Can not begin with digit
- C is case sensitive!

February 2025

CSE102 Computer Programming in C

32

Reserved words

Keywords

| | | | |
|----------|--------|----------|----------|
| auto | double | int | struct |
| break | else | long | switch |
| case | enum | register | typedef |
| char | extern | return | union |
| const | float | short | unsigned |
| continue | for | signed | void |
| default | goto | sizeof | volatile |
| do | if | static | while |

February 2025

CSE102 Computer Programming in C

33

Program Style

- Pick meaningful identifiers
 - Long enough to convey the meaning
- If the identifier consists of two words, place an underscore character between words
- Do not choose similar identifier names
- Use uppercase letters for names of macros
 - Use lowercase letters otherwise

February 2025


CSE102 Computer Programming in C

34

33

34

C Language Elements



February 2025

CSE102 Computer Programming in C

35

Variables

- Variables: memory cells for storing data
 - Values can change
- Every variable has:
 - Name: identifier
 - Type: int, double, char
 - Size
 - Value

February 2025

CSE102 Computer Programming in C

36

35

36

Variables

- Data types: abstraction of real types
 - Predefined data types
 - User-defined data types
 - Each constant or variable has a type
 - int: whole numbers (-123, 15, 27384)
 - There is a range because of finite memory cell size
 - double: real numbers (12.345, 0.5217e-4)
 - Too large and too small numbers can not be represented
 - char: character values ('a', '5', '^', ',')


February 2025

CSE102 Computer Programming in C

37

37

Memory (a) Before and (b) After Execution




February 2025

CSE102 Computer Programming in C

38

38

C Language Elements



February 2025

CSE102 Computer Programming in C

39

39

Executable Statements

- Comes after declaration
- Compiler translates to machine language code
- Assignment statements
 - Used to store value to a variable
 - Ex: kms = KMS_PER_MILE * miles;
 - In general

$$\text{variable} = \text{expression};$$
- Assignment operator: =
 - Should be read as
 - becomes
 - gets
 - takes a value of
- Previous value of variable is lost!..


February 2025

CSE102 Computer Programming in C

40

40

Effect of `kms = KMS_PER_MILE * miles;`




February 2025

CSE102 Computer Programming in C

41

41

Effect of `sum = sum + item;`



February 2025

CSE102 Computer Programming in C

42

42

Executable Statements

- Input/Output Operations
 - Input Operation: Reading a value into a variable by `scanf`
 - A different data can be entered by the user
 - Output Operation: Displaying a value by `printf`
- Several I/O functions in C
 - All in standard I/O library
 - `#include <stdio.h>`
- Function call is an executable statement
 - Function performs the action for you

February 2025

CSE102 Computer Programming in C

43

43

printf

Displays the output

```
printf("That equals %f kilometers.\n", kms);
```

```
printf(format string, print list);
```

- Function name: `printf`
- Function arguments: in parenthesis
 - Format string: "That equals %f kilometers.\n"
 - Print list: `kms`
- Placeholders: `%c`, `%d`, `%f`, `%lf`
- Escape sequence:
 - `\n` means newline : cursor moves the beginning of the next line
 - Can be used anywhere in the format string

February 2025

CSE102 Computer Programming in C

44

44

Escape Sequences

Escape sequence Description

| | |
|-----------------|---|
| <code>\n</code> | Newline. Position the cursor at the beginning of the next line. |
| <code>\t</code> | Horizontal tab. Move the cursor to the next tab stop. |
| <code>\a</code> | Alert. Sound the system bell. |
| <code>\\</code> | Backslash. Insert a backslash character in a string. |
| <code>\"</code> | Double quote. Insert a double-quote character in a string. |

February 2025

CSE102 Computer Programming in C

45

45

scanf

Reads the data into a variable

```
scanf("%lf", &miles);
```

```
scanf(format string, input list);
```

- Function name: `scanf`
- Function arguments: in paranthesis
 - Format string: `"%lf"`
 - Input list: `&miles`
- Address-of operator: `&`
 - Used to inform `scanf` about the location of the variable
 - If not used, `scanf` knows only the value of the variable


February 2025

CSE102 Computer Programming in C

46

46

Effect of `scanf("%lf", &miles);`




February 2025

CSE102 Computer Programming in C

47

47

Scanning Data Line Bob




February 2025

CSE102 Computer Programming in C

48

48

C Language Elements



February 2025

CSE102 Computer Programming in C

49

Others

- The return statement
 - Transfers the control to the OS
 - Return value indicates whether the operation is successful or not
- Comments
 - Ignored by the compiler
 - Provides information for the programmer

```
/* this is a comment */
```

February 2025

CSE102 Computer Programming in C

50

General Form of a C Program

preprocessor directives
main function heading
 {
 declarations
 executable statements
 }

```
#include <stdio.h>


void main()
{
    int a, b;
    double x, y;
    x = 10.0;
    printf(...
}
```

February 2025

CSE102 Computer Programming in C

51

C Language Elements



February 2025

CSE102 Computer Programming in C

52

Program Style

- One statements in each line
- Use extra spaces for readability
 - Compiler ignores them
 - Leave a space before and after operators
 - Indent each block
 - Insert blank lines between sections
- Use comments
 - Write a descriptive comment for
 - the program (header section)
 - each identifier
 - each program section

February 2025

CSE102 Computer Programming in C

53

Arithmetic Expressions

- Manipulates type int and double data
- Binary operators: +, -, *, /, %
 - Two operand: constant, variable or expression
 - Type of the result depend on the types of the operands
 - int if both operands are integer
 - double otherwise
 - Mixed type expression???
- / operator
 - Integer division: computes integral part of the division
 - Division by zero!..
- % operator
 - Returns integer remainder
 - Zero right operand? Undefined!..
 - Negative right operand is non standard

February 2025

CSE102 Computer Programming in C

54

Arithmetic Expressions

- Unary Operators: +, -
 - One operand
- Assignment:
 - The value of expression is evaluated and result is assigned
 - What if the type of the expression and the type of the variable is different?
 - Assignment of int to double
 - Fractional part is zero
 - Assignment of double to int
 - Fractional part is lost
 - Automatic type conversion
 - Type casting
 - (int) 3.7

February 2025

CSE102 Computer Programming in C

55

Expression Evaluation

- If there are multiple operators in an expression the order of evaluation makes a difference
 - Ex: $x / y * z$
- Evaluation Rules:
 - Parenthesis rule:
 - All expressions in parenthesis are evaluated separately
 - Nested parenthesis evaluated inside out
 - Precedence rule:
 - There is an evaluation order in operators
 - Unary +, -
 - *, /, %
 - Binary +, -
 - Associativity rule:
 - Operators in the same sub-expression and at the same precedence level
 - Unary: right to left
 - Binary: left to right


February 2025

CSE102 Computer Programming in C

56

Evaluation Tree for `area=PI*radius*radius;`

area = PI * radius * radius



February 2025

CSE102 Computer Programming in C

57

57

Step-by-Step Expression Evaluation

```

area    =    PI    *    radius    *    radius
            3.14159    2.0        2.0
            -----
            6.28318
            -----
            12.56636
  
```


February 2025

CSE102 Computer Programming in C

58

58

Evaluation for `v=(p2-p1)/(t2-t1);`



| p1 | p2 | t1 | t2 |
|-----|-----|-----|------|
| 4.5 | 9.0 | 0.0 | 60.0 |

$$v = \frac{(p2 - p1)}{(t2 - t1)}$$

| | | | |
|-------|-----|------|-----|
| 9.0 | 4.5 | 60.0 | 0.0 |
| 4.5 | | 60.0 | |
| 0.075 | | | |


February 2025

CSE102 Computer Programming in C

59

59

Evaluation for `z - (a+b/2)+w*-y`



CSE102 Computer Programming in C

60

60

Writing Mathematical Formulas

- Use parentheses as needed to specify the order of evaluation
 - Place numerator and denominator of a division in parentheses

$$m = (a - b) / (c + d)$$
 - Use extra parentheses for readability

$$(a * b * c) + (d / e) - (a + b)$$
- Do not skip $*$ as in mathematical formulas
 - In math: $d = b^2 - 4ac$
 - In C: $d = b * b - 4 * a * c$;
- Two operators can be one after the other

$$a * -(b + c)$$

February 2025

CSE102 Computer Programming in C

61

Case Study: Coin Processor

- Problem requirements
 - Convert change to personalized credit slip
 - User enters the number of each kind of coin
- Analyze the problem
 - Personalizing the slip: use customers initials
 - Count for each type of coin
 - Total value of the coins in dollars and cents
 - Input data
 - Initials: first, middle, last are characters
 - Counts: dollars, quarters, dimes, nickels, pennies are integers
 - Output data
 - Dollars and cents: total_dollars and change are integers
 - Intermediate data
 - Total value in cents: total_cents is integer
 - Relationships
 - total_cents =
 - total_dollars =
 - change =

February 2025

CSE102 Computer Programming in C

62

Case Study: Coin Processor

- Design an algorithm
 1. Get and display the customer's initials
 2. Get the count for each kind of coin
 3. Compute the total value in cents
 4. Find the value in dollars and cents
 5. Display dollars and cents
- Some steps need to refine!...
- Implement the algorithm
 - In the next slide
- Test and verify the program
- Maintain and update the program

February 2025

CSE102 Computer Programming in C

63

Supermarket Coin Value Program

```

1.  /*
2.   * Determines the value of a collection of coins.
3.   */
4.   #include <stdio.h>
5.   int
6.   main(void)
7.   {
8.       char first, middle, last; /* input - 3 initials          */
9.       int pennies, nickels; /* input - count of each coin type */
10.      int dimes, quarters; /* input - count of each coin type */
11.      int dollars; /* input - count of each coin type */
12.      int change; /* output - change amount */
13.      int total_dollars; /* output - dollar amount */
14.      int total_cents; /* total cents */
15.
16.      /* Get and display the customer's initials. */
17.      printf("Type in 3 initials and press return> ");
18.      scanf("%c%c%c", &first, &middle, &last);
19.      printf("\n%c%c%c, please enter your coin information.\n",
20.             first, middle, last);
21.
22.      /* Get the count of each kind of coin. */
23.      printf("Number of $ coins > ");
24.      scanf("%d", &dollars);
25.      printf("Number of quarters> ");

```

(continued)

February 2025

CSE102 Computer Programming in C

64

Supermarket Coin Value Program (cont'd)

```

26. scanf("%d", &quarters);
27. printf("Number of dimes > ");
28. scanf("%d", &dimes);
29. printf("Number of nickels > ");
30. scanf("%d", &nickels);
31. printf("Number of pennies > ");
32. scanf("%d", &pennies);
33.
34. /* Compute the total value in cents. */
35. total_cents = 100 * dollars + 25 * quarters + 10 * dimes +
36.   5 * nickels + pennies;
37.
38. /* Find the value in dollars and change. */
39. dollars = total_cents / 100;
40. change = total_cents % 100;
41.
42. /* Display the credit slip with value in dollars and change. */
43. printf("\n\nEnter Coin Credit\nDollars: %d\nChange: %d cents\n",
44.   first, middle, last, dollars, change);
45.
46. return (0);
47. }

```

```

Type in 3 initials and press return> JRM
JRM, please enter your coin information.
Number of $ coins > 2
Number of quarters > 14
Number of dimes > 12
Number of nickels > 25
Number of pennies > 131
JRM Coin Credit
Dollars: 9
Change: 26 cents

```

February 2025

CSE102 Computer Programming in C

65

Case Study: Coin Processor

- Test and verify the program
 - Try the program for several inputs
 - Make sure that program runs correctly
- Maintain and update the program
 - Later!...

February 2025

CSE102 Computer Programming in C

66

Output Formatting

- Default formatting
- User-defined format
 - int: %4d (%nd)
 - Field width
 - Right justified
 - - sign included in the count
 - C expands the field width if necessary
 - double: %6.2f (%n.mf)
 - Field width
 - Decimal places
 - Decimal point, minus sign included in the field width
 - Values between -99.99 to 999.99 for %6.2f
 - At least one digit before decimal point
 - Values are rounded if there are more decimal places
 - -9.536 becomes -9.54
 - Use %d or %.3f not to have leading blanks

February 2025

CSE102 Computer Programming in C

67

Input and Output Redirection

- Interactive mode
- Batch mode
 - Input Redirection: standard input is associated with a file instead of keyboard


```
myprog < inputfile
```

 - No need to display prompting message
 - Display the message about input (echo print)
 - Output Redirection: standard output is associated with a file instead of screen


```
myprog > outputfile
```

 - Can print the file to get the hardcopy

February 2025

CSE102 Computer Programming in C

68

Batch Version of Miles-to-Km Conversion Program

```

1. /* Converts distances from miles to kilometers. */
2.
3. #include <stdio.h> /* printf, scanf definitions */
4. #define KMS_PER_MILE 1.609 /* conversion constant */
5.
6. int
7. main(void)
8. {
9.     double miles, /* distance in miles */
10.    kms; /* equivalent distance in kilometers */
11.
12.    /* Get and echo the distance in miles. */
13.    scanf("%lf", &miles);
14.    printf("The distance in miles is %.2f.\n", miles);
15.
16.    /* Convert the distance to kilometers. */
17.    kms = KMS_PER_MILE * miles;
18.
19.    /* Display the distance in kilometers. */
20.    printf("That equals %.2f kilometers.\n", kms);
21.
22.    return (0);
23. }

```

The distance in miles is 112.00.
That equals 180.21 kilometers.

February 2025

CSE102 Computer Programming in C

69

Use of Input/Output Files

- C allows to explicitly name an input or output file

- Declaring file pointer

```
FILE * inp;
FILE * outp;
```

- Opening file

```
inp = fopen("filename", "r");
outp = fopen("filename", "w");
```

- Reading from a file

```
fscanf(inp, "%d", &nickels);
```

- Writing to a file

```
fprintf(outp, "Total is %d \n", value);
```

- Closing file

```
fclose(inp);
```

February 2025

CSE102 Computer Programming in C

70

Miles-to-Km Conversion Program with Named Files

```

1. /* Converts distances from miles to kilometers. */
2.
3. #include <stdio.h> /* printf, scanf, fprintf, fscanf, fopen, fclose
4.    definitions */
5. #define KMS_PER_MILE 1.609 /* conversion constant */
6.
7. int
8. main(void)
9. {
10.    double miles, /* distance in miles */
11.    kms; /* equivalent distance in kilometers */
12.    FILE *inp, /* pointer to input file */
13.    *outp; /* pointer to output file */
14.
15.    /* Open the input and output files. */
16.    inp = fopen("distance.dat", "r");
17.    outp = fopen("distance.out", "w");
18.
19.    /* Get and echo the distance in miles. */
20.    fscanf(inp, "%lf", &miles);
21.    fprintf(outp, "The distance in miles is %.2f.\n", miles);
22.
23.    /* Convert the distance to kilometers. */
24.    kms = KMS_PER_MILE * miles;
25.
26.    /* Display the distance in kilometers. */
27.    fprintf(outp, "That equals %.2f kilometers.\n", kms);
28.
29.    /* Close files. */
30.    fclose(inp);
31.    fclose(outp);
32.
33.    return (0);
34. }

```

Contents of input file distance.dat
112.0

Contents of output file distance.out
The distance in miles is 112.00.
That equals 180.21 kilometers.

February 2025

CSE102 Computer Programming in C

71

Case Studies

- Compute change for a given amount of money

February 2025

CSE102 Computer Programming in C

72

Programming Errors

- Error = bug
- Process of correcting errors: debugging
- Error messages
 - Depends on the system used
 - Not always easy to understand
- Three kind of errors:
 - Syntax errors
 - Violation of grammar rule
 - Detected by the compiler
 - Run-time errors
 - Detected while execution
 - Illegal operation, division by zero etc.
 - Logic errors
 - Program runs but produces incorrect result

February 2025

CSE102 Computer Programming in C

73

A Program with Syntax Errors

```

221 /* Converts distances from miles to kilometers. */
222
223 #include <stdio.h>          /* printf, scanf definitions */
224 #define KMS_PER_MILE 1.609 /* conversion constant */
225
226 int
227 main(void)
228 {
229     double kms;
230
231     /* Get the distance in miles. */
232     printf("Enter the distance in miles> ");
233
234     scanf("%lf", &kms);
235
236     /* Convert the distance to kilometers. */
237     kms = KMS_PER_MILE * kms;
238
239     /* Display the distance in kilometers. */
240     printf("That equals %f kilometers.\n", kms);
241
242     return (0);
243 }

```

February 2025

CSE102 Computer Programming in C

74

A Program with a Run-Time Error

```

111 #include <stdio.h>
112
113 int
114 main(void)
115 {
116     int    first, second;
117     double temp, ans;
118
119     printf("Enter two integers> ");
120     scanf("%d%d", &first, &second);
121     temp = second / first;
122     ans = first / temp;
123     printf("The result is %.3f\n", ans);
124
125     return (0);
126 }

```

Enter two integers> 14 3
Arithmetic fault, divide by zero at line 122 of routine main

February 2025

CSE102 Computer Programming in C

75

Revised Coin Value Program

```

1. int
2. main(void)
3. {
4.     char first, middle, last; /* input - 3 initials */
5.     int pennies, nickels; /* input - count of each coin type */
6.     int dimes, quarters; /* input - count of each coin type */
7.     int dollars; /* input - count of each coin type */
8.     int change; /* output - change amount */
9.     int total_dollars; /* output - dollar amount */
10.    int total_cents; /* total cents */
11.    int year; /* input - year */
12.
13.    /* Get the current year. */
14.    printf("Enter the current year and press return> ");
15.    scanf("%d", &year);
16.
17.    /* Get and display the customer's initials. */
18.    printf("Type in 3 initials and press return> ");
19.    scanf("%c%c%c", &first, &middle, &last);
20.    printf("\n%c%c%c, please enter your coin information for %d.\n",
21.           first, middle, last, year);
22.    ...

```

February 2025

CSE102 Computer Programming in C

76

A Program That Produces Incorrect Results

```
1. #include <stdio.h>
2.
3. int
4. main(void)
5. {
6.     int    first, second, sum;
7.
8.     printf("Enter two integers> ");
9.     scanf("%d%d", &first, &second);
10.    sum = first + second;
11.    printf("%d + %d = %d\n", first, second, sum);
12.
13.    return (0);
14. }
```

```
Enter two integers> 14 3
5971289 + 5971297 = 11942586
```

February 2025

CSE102 Computer Programming in C

77

Thanks for listening!

78