

Neuroscience

Evaluation of surface-based hippocampal registration using ground-truth subfield definitions

Reviewed Preprint

Published from the original preprint after peer review and assessment by eLife.

About eLife's process

Reviewed preprint posted

June 30, 2023 (this version)

Sent for peer review

April 18, 2023

Posted to bioRxiv

March 31, 2023

Jordan DeKraker , Nicola Palomero-Gallagher, Olga Kedo, Neda Ladbon-Bernasconi, Sascha E.A. Muenzing, Markus Axer, Katrin Amunts, Ali R. Khan, Boris Bernhardt, Alan C. Evans

Montreal Neurological Institute and Hospital, McGill University, Montreal, Canada • Institute of Neuroscience and Medicine INM-1, Research Centre Jülich, Germany • C. & O. Vogt Institute for Brain Research, University Hospital Düsseldorf, Heinrich-Heine-University, 40225 Düsseldorf, Germany • Robarts Research Institute, University of Western Ontario, London, Canada

 (https://en.wikipedia.org/wiki/Open_access)

 (<https://creativecommons.org/licenses/by/4.0/>)

Abstract

The hippocampus is an archicortical structure, consisting of subfields with unique circuits. Understanding its microstructure, as proxied by these subfields, can improve our mechanistic understanding of learning and memory and has clinical potential for several neurological disorders. One prominent issue is how to parcellate, register, or retrieve homologous points between two hippocampi with grossly different morphologies. Here, we present a surface-based registration method that solves this issue in a contrast-agnostic, topology-preserving manner. Specifically, the entire hippocampus is first analytically unfolded, and then samples are registered in 2D unfolded space based on thickness, curvature, and gyrification. We demonstrate this method in seven 3D histology samples and show superior alignment with respect to subfields using this method over more conventional registration approaches.

Highlights

- Hippocampal subfields contain microcircuits that are critical for memory and vulnerable to neurological disease.
- Hippocampi have variable folding patterns between individuals, making them hard to register or parcellate.
- We present a surface-based hippocampal registration method that is analogous to neocortical inflation to a sphere and registration.
- Testing in seven detailed 3D histology samples revealed successful registration with respect to hippocampal subfields, and outperformed more conventional methods.
- This method provides groundwork for detailed multimodal hippocampal mapping across subjects and datasets in the future.

Data availability

The methodological advancements described here are made easily accessible in the latest version of open source software HippUnfold¹. Code used in the development and testing of these methods, as well as preprocessed images, manual segmentations, and results, are openly available².

eLife assessment

This paper contributes to the field of hippocampal registration by introducing a novel surface-based approach that utilizes the topological and morphological features of the hippocampus for anatomical registration across individuals, rather than volumetric-based methods commonly used in the literature. The study provides **compelling** evidence for the efficacy of this approach using histological samples from three different datasets and offers validation of the method through comparison with traditional volumetric registration. This is **important** work given the large number of studies that examine hippocampal shape, thickness, and function in large cohorts, providing strong support for the use of hippocampal unfolding methods in future studies.

Introduction

The hippocampus is part of the archicortex that, like the neocortex, can be further parcellated into subfields according to its cytoarchitecture (Ding & Van Hoesen, 2015; Duvernoy et al., 2013; Palomero-Gallagher et al., 2020). The study of hippocampal subfields is promising for both basic science, since their microcircuits are thought to be fundamental to memory processes (Milner et al., 1968; O'Keefe & Nadel, 1978; Riphagen et al., 2020), and for the pathogenesis of several brain disorders given their vulnerabilities to many conditions, notably epilepsy (Bernhardt et al., 2015, 2016; Blumcke et al., 2013; Thom, 2014), Alzheimer's disease (Braak & Del Tredici, 2014; Flores et al., 2015), and Schizophrenia (Haukvik et al., 2018; Roeske et al., 2020). However, subfield parcellation is challenging. This relates to variability across segmentation protocols both at the level of histology and imaging (Wisse et al., 2017; Yushkevich, Amaral, et al., 2015). Moreover, the hippocampus has a complex shape that varies between individuals (Chang et al., 2018; DeKraker et al., 2021; Ding & Van Hoesen, 2015; Palomero-Gallagher et al., 2020). This topic has received widespread attention, leading to the development of an international harmonization effort that focuses on extracting geometric regularities from reference histology slices that can be applied to MRI, mostly using coronal slices (Olsen et al., 2019; Wisse et al., 2017; Yushkevich, Amaral, et al., 2015). Building on this discussion, we assert that the most basic geometric consistency of the hippocampus is a 3D folded surface and so subfield parcellation schemes should be applied using surface-based registration, similar to state-of-the-art neocortical parcellation.

Surface-based registration, either in the hippocampus or neocortex, aims to account for inter-individual differences in folding or gyrification patterns during registration (DeKraker et al., 2021; Fischl et al., 2008; Im et al., 2008; Lyttelton et al., 2007; MacDonald et al., 2000; Van Essen et al., 2000; Robbins, 2003). Briefly, this consists of first generating a 3D model of the structure of interest and representing it as a surface, typically a mid-thickness surface. In the

neocortex, this surface can be “inflated” or remapped, *e.g.* for viewing on the surface of a sphere. Registration can then be performed between two spheres based on some feature map by rotating until the maximum overlap achieved (Kim et al., 2015; Klein et al., 2010; Lyttelton et al., 2007). Posing registration problems on a sphere helps account for inter-individual variability in gyral and sulcal patterning, which can vary drastically between individuals (Bartley et al., 1997; Goualher et al., 1999; Régis et al., 2005). For example, conventional 3D volumetric registration may take one gyrus and stretch it across two gyri from another individual, especially in areas where the number or shape of gyri varies between individuals. In surface-based registration, homologous points are not constrained to fall in similar absolute positions but rather similar topological positions (*e.g.*, one gyral peak could be homologous to a point halfway down the depth of an adjacent sulcus from another individual). Since the major gyri and sulci of the brain are typically invariant across individuals (Le Guen et al., 2018), gyral and sulcal patterning can be used as one feature to inform registration, often after smoothing to remove smaller secondary or tertiary gyri and sulci which tend to be more variable (Tardif et al., 2015), while other features more indicative of cortical architecture, such as thickness or intracortical myelin, can be used as well (Glasser et al., 2016; Lyttelton et al., 2007; Van Essen et al., 2012).

Here, we present such a surface-based registration method specifically for hippocampal surfaces. Rather than inflation to a sphere, we rely on previous work which maps the hippocampus to a flat rectangle to preserve its topology (DeKraker et al., 2022). This also allows for the use of existing 2D image-based registration tools without reformulation for use on a surface mesh but, in effect, the same advantages and constraints as typical surface-based registration are preserved. Evaluation of this method is performed using ground-truth (*i.e.*, histologically-derived) subfield segmentations from seven samples that were sliced, imaged microscopically, and then digitally reconstructed into a 3D block with various histology contrasts. The method has been openly published at https://github.com/khanlab/hippunfold/tree/unfold_reg.

Materials and Methods

Data

Seven 3D reconstructed hippocampal histology samples were examined in this study from three different sources:

1. BigBrain: 2 hemispheres, Merker stain (Merker, 1983), downsampled from 20 to 40µm isotropic voxel resolution (Amunts et al., 2013),
2. 3D Polarized Light Imaging (3D-PLI): 1 hemisphere, 48×48×60µm resolution, contrast driven by birefringence properties of myelin sheaths surrounding axons (Axer et al., 2011), and
3. AHEAD: 4 hemispheres from 2 brains, blockface imaging and multiple stains, 150×150×200µm resolution (Alkemade et al., 2022).

Details of these dataset acquisitions and processing can be found in their respective references. The 3D-PLI sample was examined here only in terms of transmittance rather than directional data. The transmittance has already been demonstrated in a few brain sections to provide valuable information to segment hippocampal subregions (Zeineh et al., 2017).

Manual segmentation

HippUnfold (DeKraker et al., 2022) achieves automatic segmentation and unfolding of *in-vivo* hippocampal MRI data, typically T1w or T2w images, which do not resemble the contrasts seen in the present histology datasets and thus manual segmentation had to be used. This unfolding method requires a detailed hippocampal gray matter mask, as well as labeling of termini at the anterior, posterior, and medial hippocampal edges, dentate gyrus (DG), and laminar strata radiatum and lacunosum-moleculare (SRLM). Here, we consider SRLM to be a “mixed” label since it can include components of the subicular complex, CA fields, DG, as well as blood vessels and CSF within the hippocampal sulcus. Thus, it is used to differentiate the upper and lower surfaces of the remaining hippocampal cortex, contiguous with the “pial” and “white” surfaces of the neocortex, respectively, and SRLM volume is excluded from further analyses.

In BigBrain, these labels were available from previous work (DeKraker et al., 2020). Rater J.D. performed manual segmentation in all other samples using ITK-SNAP (Yushkevich et al., 2006). In the 3D-PLI sample, the absolute anterior and posterior of the hippocampus were cut off during tissue preparation. Thus, the required labels were extrapolated over the missing regions in order to recover a fully 3D hippocampal shape that is amenable to unfolding (see Figure 1A). In the AHEAD brain samples, manual segmentation was performed on blockface images.




Figure 1.

Surface-based subfield alignment pipeline. **A)** Each 3D dataset manually parcellated into subfields. **B)** Subfields mapped to a common unfolded space using HippUnfold. **C)** Morphometric features mapped to unfolded space (from left to right: gyrification, thickness, curvature). **D)** Multimodal features iteratively aligned in unfolded space using 2D registration. **E)** Subfield labels propagated through unfolded 2D registrations to sample1. Closeups of the segmentations for the individual datasets can be found in Supp. Figure 2.

For all datasets, hippocampal gray matter was subsequently manually parcellated by rater J.D. into subfield labels: Subicular complex (Sub) and Cornu Ammonis (CA) fields 1-4 based on the available histological features and according to the criteria outlined by (Ding & Van Hoesen, 2015; Duvernoy et al., 2013; Palomero-Gallagher et al., 2020). The DG was also labeled but was grouped together with CA4 since HippUnfold’s current method for unfolding of the DG relies on heuristics in MRI that would not be appropriate in this work (*i.e.*, it uses a template prior to estimate DG topology at the cost of smoothing labels). These manual labels

were defined based upon cytoarchitectonic features at the highest level of resolution available and were deemed “ground-truth” subfield definitions. It is important to note that BigBrain is stained for cell bodies, while 3D-PLI transmittance contrast is driven by cell bodies and nerve fibers (both introducing light extinction effects; Menzel et al., 2020) and thus contains very different microstructural information. Thus, both cell body and fiber distribution patterns were consulted during subfield definition. In the AHEAD dataset, multiple imaging modalities were available, albeit with imperfect registration to the blockface images, larger interslice gaps, some missing data, and limited resolution. These additional contrasts were overlaid over blockface images (where available and appropriate due to the above limitations) to better inform subfield segmentation.

Unfolded registration

HippUnfold (DeKraker et al., 2022) was used to map each dataset to a standardized unfolded space (see [Figure 1B](#)). This unfolded space consists of a triangulated mesh with uneven face sizes, so as to preserve a constant spacing between points in the folded hippocampus. The current work, however, defined this tessellation as a regular mesh grid in unfolded space consisting of 256×128 points across the anterior-posterior (A-P) and proximal-distal (P-D) axes of the unfolded hippocampus, respectively. This regular grid in unfolded space means that surface points (henceforth, vertices) can effectively be treated as pixels of a flat 2D image without the need to interpolate missing pixel values. However, it should also be noted that, as a consequence, native or “folded” images are sampled more densely in some areas than others, particularly in the anterior and posterior extremes, which can lead to noisier unfolded data in these regions.

HippUnfold also calculates morphological features, namely thickness, gyrification index, and curvature ([Figure 1C](#)). These features are desirable for inter-subject registration since *i*) they are associated with subfield boundaries (DeKraker et al., 2018, 2022; Yushkevich, Pluta, et al., 2015), *ii*) they don’t require cytoarchitectonic information to measure, and *iii*) they are agnostic to imaging contrast differences. Registration performed in unfolded hippocampal space is analogous to registration of neocortical surfaces that have been inflated to a sphere, since both methods preserve topology rather than absolute position. However, one difference is that registration on a sphere allows one point to “wrap” around the meridian of a sphere whereas in a rectangular unfolded space, the proximal edge (*i.e.*, closest to the neocortex) does not “wrap” to the distal (*i.e.*, closest to the dentate gyrus) edge of the P-D axis, and the same applies to the anterior-posterior, A-P, edges. This is in agreement with the true geometry of the hippocampus though, which has the topology of a rectangle (*i.e.*, four true edge termini) rather than a sphere (*i.e.*, zero true termini).

The 2D registration was performed using all three of the above morphological features with equal weighting, using ANTs multicontrast SyN deformable registration (Avants et al., 2011) ([Figure 1D](#)). Rather than registering all samples’ feature maps to one sample, we instead used an iterative template building method (Avants et al., 2010), which first averages images, registers each image to the average, and then repeats the registration to the newly generated average. This process is repeated 4 times, with each iteration sharpening the averaged template and improving registration precision. We concatenated the transforms from each sample to the template with the inverse transform from the template to sample1 (BigBrain left hemisphere) and applied it to subfield labels to evaluate their overlap with that sample’s ground-truth subfield definitions ([Figure 1E](#)). Sample1 was chosen because it had the highest resolution and, therefore, provided the greatest cytoarchitectonic detail for identification of subfield boundaries, while also being the more common hemisphere in this study (*i.e.*, 4 left; 3 right). In principle, any sample could have been chosen, and one had to be chosen to test overlap in any one native (or folded) space.

Control condition: volumetric registration

The proposed pipeline was compared to a conventional 3D volumetric registration approach: ANTs template generation (Avants et al., 2011) under ideal tissue contrast conditions (i.e., based on binarized gray matter labels). This is outlined in Figure 2 and detailed below. First, all hippocampal gray matter labels were binarized, right hippocampi were flipped, and binary masks were rigidly registered to sample1 using Greedy's moment-based initialization (Yushkevich et al., 2016) (2 moments), which can handle images initially in different spaces relative to the origin (which was the case in some samples here) (Figure 2B). Images were then resampled to 100 μ m isovoxel resolution to reduce compute time and memory requirements, which were prohibitively high at native resolution. ANTs template generation was then used as before (Figure 2C), with the following differences: registrations were all 3D and unimodal.




Figure 2.

Control condition using volumetric registration. **A)** Subfield segmentation as in Figure 1A. **B)** Binarized and rigidly aligned hippocampal gray matter masks (left hemispheres flipped). **C)** Iterative alignment using ANTs template building in 3D. **D)** Each sample's subfields propagated to template space. **E)** Each sample's subfields propagated to sample1 unfolded space.

Using binarized images likely overestimates a fully automated registration method for subfield parcellation, since it presents idealized tissue contrast conditions (i.e., perfect contrast between grey and white matter). This has been chosen as a practical and robust approach, avoiding local minima commonly encountered by image-intensity based registration procedures in the mesiotemporal region (Qiu & Miller, 2008). In principle, cross-modal registration can be performed using metrics like mutual information or cross-correlation, but these metrics still do not fully compensate for differences in contrasts, luminance, or intensity levels, and may have many local minima solutions making it less tractable. Thus, the control condition used here could be thought of as a best-case volumetric registration.

Registrations from each sample to the template and the inverse transform from the template to sample1 were concatenated and applied to subfield labels (Figure 2D). For easier comparison with Figure 1, each sample's subfields were sampled along sample1 mid-thickness surface and projected to unfolded space (Figure 2E). In some cases, the mid-

thickness surface fell outside of the propagated subfield labels and returned a background value of 0. The missing values were imputed by nearest-neighbour interpolation in unfolded space, providing additional correction for misregistration.

Evaluation metrics

The Dice overlap metric (Dice, 1945) was calculated for all subjects' subfields registered to sample1. This was repeated in 2D unfolded and in 3D native spaces, since some parts of unfolded space expanded or contracted more than others when projected to native space, which can over- or under-emphasize subfield differences. A secondary metric, border distances, was also calculated in sample1 native space. This was calculated by computing distance from a given border in sample1 to all voxels, followed by concatenating these distances at the location of each propagated sample's corresponding subfield borders, providing a minimum direct 3D distance between borders in real-world units. These distances were calculated from all subfield borders (*i.e.*, Sub-CA1, CA1-CA2, CA2-CA3, and CA3-CA4).

In addition to registration in 2D unfolded space and 3D native space, overlap metrics were calculated for unfolding without registration. That is, borders from each sample were projected to unfolded space and projected directly to sample1 space, which replicated the current subfield segmentation behaviour in HippUnfold (v1.2.0).

To evaluate the contribution of each morphometric feature or combination of features (thickness, gyrification, and curvature) to registration, unfolded space registrations were also performed using all combinations of these features. These were then evaluated using Dice scores in sample1 native space.

Results

Qualitative alignment

Figure 1A shows equivalent sagittal slices from each sample after rigid alignment, in which considerable subfield variability can be seen between samples. This is due in part to the out-of-plane issue discussed elsewhere (DeKraker et al., 2021). Viewing a fully 3D model (**Figure 1B**) can help in identifying differences between samples due to true morphological variability rather than field-of-view differences. Projecting these labels to unfolded space (**Figure 1B**) preserved sample-specific differences in the size of each subfield but removed variability due to different folding and gyrification configurations between samples, which already brought subfields into close alignment and was the current basis for subfield segmentation in HippUnfold.

Following registration in unfolded space (**Figure 1E**), subfields are even more closely aligned (for example samples 3 and 5 are no longer dominated by the Sub label). In addition, there are no topological breaks or reordering of subfields in **Figure 1**. In **Figure 2E**, following conventional volumetric alignment, there are cases where CA1 shows isolated islands (*e.g.* sample2), and where CA1 borders CA3 directly instead of first passing through CA2 (*e.g.* sample3). This does not match the original subfield segmentations from any sample or the literature which states that subfields should be contiguous and consistently ordered (Duvernoy et al., 2013). These issues arise in 3D registration due to breaks in topology: for example, hippocampal gray matter may become stretched across the SRLM and vestigial hippocampal sulcus, or across adjacent gyri. When subfield labels are propagated across a sulcus, they can become discontinuous with respect to the mid-thickness surface topology of

a given sample. This type of 2D topology is conserved in a surface-based or unfolded hippocampal space registration.

Quantitative alignment

Better Dice overlap on average and for every individual subfield was observed using unfolded registration over unfolding and refolding into a different sample's folded configuration alone (Figure 3B). Both methods also outperformed the control condition using conventional ANTs 3D volumetric registration. These results were tested using one-tailed, paired-samples t-tests, pairing subfields and subjects, which revealed significant differences between each method and in both unfolded and native spaces. The same pattern was also observed when evaluated according to nearest corresponding subfield border distances in native space (Figure 3C). One example of each of these registration methods (sample3 to sample1) is shown in Figure 1A.




Figure 3.

Evaluation of aligned subfield definitions. A) Qualitative example of subfields from the third sample projected to the first sample's native "folded" space using conventional 3D volumetric alignment, unfolding to account for inter-individual differences in folding shape, and unfolding followed by registration in unfolded space. B) Dice overlap achieved. Each measure was calculated in unfolded space (left) and again in the first sample's (BigBrain left hemisphere) folded space. Black lines indicate the mean across all subfields. C) Distances between all aligned subfield borders using the three methods described above. Dashed lines indicate the median distance.

Contribution of unfolded morphological features

By using different combinations of unfolded features, we could determine which is most informative about unfolded registration and subfield boundary alignment (Figure 4). In this

regard, curvature was the most informative individual feature while thickness and curvature was the most informative combination of two features, despite the fact that thickness was the least informative individual feature (similar to no unfolded registration). Therefore, while each is informative, they may contain overlapping information and their combination isn't as complementary as curvature and thickness together. Regardless, combining all three features still showed the best performance. Future work should explore the use of additional features, such as intracortical myelin or laminar distributions of neurons, to inform registration. This was not examined here since it was not available in all datasets owing to differing contrasts.




Figure 4.

Contribution of each morphological feature to unfolded registration performance. Unfolded space registration was repeated for all combinations of unfolded morphological features and evaluated by Dice overlap in native space. Combinations are ordered by their Dice scores averaged across the 5 subfields. p-values are relative to no unfolded registration, using one-tailed paired-samples t-tests as above.

Figure 4B and D show the extent of deformations in unfolded space following ANTs registration with default parameters. The median deformation magnitude across all vertices was 3.382mm, but more constrained or liberal deformations could be achieved by adjusting the ANTs elasticity and fluidity parameters (proportional to the resulting deformation field's maximum and smoothness, respectively). More liberal deformations could lead to more precise subfield alignment, however, this also runs the risk of falling into local minima during optimization, or of distorting tissue beyond a reasonable distance. Thus, default parameters were used to maintain robustness at the cost of potential gains in precision.

Discussion

The current work presented a novel surface-based registration of hippocampal cortex between histology samples, and our evaluations demonstrated that it outperformed even an idealized version of conventional volumetric registration. This enabled mapping of multiple features at a sub-millimetric scale that would otherwise be impossible. For example, maps of

hippocampal cyto- or myeloarchitectonic features can be constructed from multiple samples using different stains or imaging methods that would otherwise preclude one another due to tissue destruction (*e.g.*, once stained, a slice cannot be easily imaged with other stains). This can be useful both in studying hippocampal subfields and in subfield-agnostic mapping and other data driven methods (*e.g.*, (Borne et al., 2023; Paquola et al., n.d.; Patel et al., 2020; Przeździecki et al., 2019; Vogel et al., 2020; Vos de Wael et al., 2018)). We hope that this work will provide an avenue towards mapping of hippocampal data across many modalities, scales, and different fields in future work.

Surface-based hippocampal registration can be used in subfield parcellation in MRI, histology, or other imaging methods by registration to the unfolded maximum probability subfield atlas provided here (**Figure 1D**). Note that the current work differs from other subfield segmentation protocols, even those which employ surfaces and unfolding, in that our method constrains registration (and therefore subfield segmentation) topologically by the unique folded shape of a given hippocampus. Other methods generally first employ subfield segmentation (either manually or using conventional volumetric registration) and then reduce volumes to surfaces or employ other flat mapping techniques of the hippocampus (Caldairou et al., 2016; Ekstrom et al., 2009; Pipitone et al., 2014; Yushkevich et al., 2016; Yushkevich, Pluta, et al., 2015; Zeineh et al., 2000, 2001). For example, SurfPatch (Caldairou et al., 2016) computes volumetric registration and then propagates surfaces rather than labelmaps, which avoids discretization errors. However, this method still does not guarantee correct topology across different hippocampal folding patterns (see discussion below on multi-atlas registration), and has not been demonstrated at the level of detail examined here.

Other surface-based registration methods such as spherical harmonics (SPHARM) (Brechtbühler et al., 1995; Gerig et al., 2001) have been employed to find homologous vertices between irregular shapes including hippocampal samples (Styner et al., 2004). In principle, this is a similar pose of the registration problem as the methods employed here. However, SPHARM requires a spherical topology, which in (Styner et al., 2004) is mapped to the outer boundaries of the hippocampus rather than a midthickness surface, and so this method does not fully leverage the geometric topology constraints of the hippocampus. There has been an adaption of the SPHARM-PDM model to hippocampi, in which the spherical parameterization of the outer hull was propagated along a Laplacian field to the hippocampal midthickness surface (Kim et al., 2014), and this approach has since then been used and validated in the study of hippocampal organization in both health and disease (Bernhardt et al., 2016; Vos de Wael et al., 2018). Other vertex-wise or even point-cloud registration methods could be employed for hippocampal midthickness surfaces in future work. One final example is the recent FastSurfer implementation of Laplace Eigenfunctions for neocortical surface registration, which involves registration to a sphere (Henschel et al., 2020). This method does not require an inherently spherical topology and the only major conceptual difference between it and the present work is that we hold hippocampal termini or endpoints fixed, for additional regularization, whereas FastSurfer derives them from the surface mesh itself.

One limitation of the evaluation performed on our surface-based registration is that our control condition using 3D volumetric registration did not employ a multi-atlas as in some other popular methods, including those discussed above (Caldairou et al., 2016; Yushkevich et al., 2016; Yushkevich, Pluta, et al., 2015). A multi-atlas applies registration of several references to a target image and then combines propagated labels from the references to the target (*e.g.* via maximum probability). We partially compensated for this issue by using an idealized volumetric registration with detailed binarized hippocampal gray matter masks rather than images, which generally contain more noise, blurring, and surrounding structures that are not necessarily informative about hippocampal shape. 3D registrations at

the current resolution also have costly compute requirements that scale with resolution and the number of samples in the multi-atlas. In addition, a multi-atlas is not guaranteed to contain a sample with a similar folding configuration as the target sample and, even if it does, the combination of multiple registered samples may lead to errors or over-smoothing. By contrast, HippUnfold can be moderately compute intensive at high resolution, but it only needs to be performed once and then registration in unfolded space has trivially light compute requirements, even when using multiple contrasts as performed here. Nevertheless, we hope to eventually see the development of multi-atlas volumetric registration at a microscale, as well as work performing a systematic comparison with surface-based registration.

Conclusions

We formulated a registration performed in a standardized “unfolded” hippocampal space, and showed that this method consistently improved inter-individual alignment with respect to subfields. This method is topologically-constrained and driven by contrast-agnostic feature maps, meaning that it can be performed across image modalities regardless of whether cytoarchitectonic features are directly accessible or not. Overall, this work constitutes a state-of-the-art registration method between hippocampi at a scale approaching the micron level.

Acknowledgements

This work was supported by the Helmholtz International BigBrain Analytics and Learning Laboratory (HIBALL), funded by Healthy Brains, Healthy Lives (HBHL) and the Helmholtz Association. JD was furthermore supported by the National Science and Engineering Research Council of Canada (NSERC). BCB acknowledges research support from NSERC (Discovery-1304413), Canadian Institutes for Health Research (CIHR FDN-154298, PJT-174995), SickKids Foundation (NI17-039), BrainCanada, HBHL, and the Tier-2 Canada Research Chairs program. 3D-PLI related work was supported by the European Union’s Horizon 2020 Framework Programme for Research and Innovation (grant no. 945539: “Human Brain Project” SGA3 and by the computing time granted through JARA on the supercomputer JURECA at Forschungszentrum Jülich.

References

- Alkemade A. , Bazin P.-L. , Balesar R. , Pine K. , Kirilina E. , Möller H. E. , Trampel R. , Kros J. M. , Keuken M. C. , Bleys R. L. A. W. , Swaab D. F. , Herrler A. , Weiskopf N. , Forstmann B. U. (2022) **A unified 3D map of microscopic architecture and MRI of the human brain** *Science Advances* **8**
- Amunts K. , Lepage C. , Borgeat L. , Mohlberg H. , Dickscheid T. , Rousseau M.-É. , Bludau S. , Bazin P.-L. , Lewis L. B. , Oros-Peusquens A.-M. , Shah N. J. , Lippert T. , Zilles K. , Evans A. C. (2013) **BigBrain: an ultrahigh-resolution 3D human brain model** *Science* **340**:1472–1475

Amunts K. , Mohlberg H. , Bludau S. , Caspers S. , Brandstetter A. , Eickhoff S. B. , Pieperhoff P. , Dickscheid T. (2021) **Whole-brain parcellation of the Julich-Brain Cytoarchitectonic Atlas (v2.6) [Data set]** *EBRAINS*
<https://doi.org/10.25493/KJQN-AM0>

Avants B. B. , Tustison N. J. , Song G. , Cook P. A. , Klein A. , Gee J. C. (2011) **A reproducible evaluation of ANTs similarity metric performance in brain image registration** *NeuroImage* **54**:2033–2044

Avants B. B. , Yushkevich P. , Pluta J. , Minkoff D. , Korczykowski M. , Detre J. , Gee J. C. (2010) **The optimal template effect in hippocampus studies of diseased populations** *NeuroImage* **49**:2457–2466
<https://doi.org/10.1016/j.neuroimage.2009.09.062>

Axer M. , Grassel D. , Kleiner M. , Dammers J. , Dickscheid T. , Reckfort J. , Hütz T. , Eiben B. , Pietrzyk U. , Zilles K. , Amunts K. (2011) **High-resolution fiber tract reconstruction in the human brain by means of three-dimensional polarized light imaging** *Frontiers in Neuroinformatics* **5**

Bartley A. J. , Jones D. W. , Weinberger D. R. (1997) **Genetic variability of human brain size and cortical gyral patterns** *Brain: A Journal of Neurology* **120**:257–269

Bernhardt B. C. , Bernasconi A. , Liu M. , Hong S.-J. , Caldarou B. , Goubran M. , Guiot M. C. , Hall J. , Bernasconi N. (2016) **The spectrum of structural and functional imaging abnormalities in temporal lobe epilepsy** *Annals of Neurology* **80**:142–153

Bernhardt B. C. , Hong S.-J. , Bernasconi A. , Bernasconi N. (2015) **Magnetic resonance imaging pattern learning in temporal lobe epilepsy: Classification and prognostics** *Annals of Neurology* **77**:436–446
<https://doi.org/10.1002/ana.24341>

Blumcke I. , Helen Cross J. , Spreafico R. (2013) **The international consensus classification for hippocampal sclerosis: an important step towards accurate prognosis** *The Lancet Neurology* **12**:844–846
[https://doi.org/10.1016/s1474-4422\(13\)70175-3](https://doi.org/10.1016/s1474-4422(13)70175-3)

Borne L. , Tian Y. , Lupton M. K. , van der Meer J. N. , Jeganathan J. , Paton B. , Koussis N. , Guo C. C. , Robinson G. A. , Fripp J. , Zalesky A. , Breakspear M. (2023) **Functional re-organization of hippocampal-cortical gradients during naturalistic memory processes** *NeuroImage*

Braak H. , Del Tredici K. (2014) **Braak, H., & Del Tredici, K. (2014). Neuroanatomy and Pathology of Sporadic Alzheimer's Disease. Springer. Neuroanatomy and Pathology of Sporadic Alzheimer's Disease**

Brechbühler C. , Gerig G. , Kübler O. (1995) **Parametrization of Closed Surfaces for 3-D Shape Description** *Computer Vision and Image Understanding* **61**:154–170
<https://doi.org/10.1006/cviu.1995.1013>

- Caldairou B. , Bernhardt B. C. , Kulaga-Yoskovitz J. , Kim H. , Bernasconi N. , Bernasconi A. (2016) **A SurfacePatch-Based Segmentation Method for Hippocampal Subfields** :379–387 https://doi.org/10.1007/978-3-319-46723-8_44
- Chang C. , Huang C. , Zhou N. , Li S. X. , Ver Hoef L. , Gao Y. (2018) **The bumps under the hippocampus** *Human Brain Mapping* **39**:472–490
- DeKraker J. , Ferko K. M. , Lau J. C. , Köhler S. , Khan A. R. (2018) **Unfolding the hippocampus: An intrinsic coordinate system for subfield segmentations and quantitative mapping** *NeuroImage* **167**:408–418 <https://doi.org/10.1016/j.neuroimage.2017.11.054>
- DeKraker J. , Haast R. A. M. , Yousif M. D. , Karat B. , Lau J. C. , Köhler S. , Khan A. R. (2022) **Automated hippocampal unfolding for morphometry and subfield segmentation with HippUnfold** *eLife* **11** <https://doi.org/10.7554/eLife.77945>
- DeKraker J. , Köhler S. , Khan A. R. (2021) **Surface-based hippocampal subfield segmentation** *Trends in Neurosciences* **44**:856–863
- DeKraker J. , Lau J. C. , Ferko K. M. , Khan A. R. , hler S. (2020) **Hippocampal subfields revealed through unfolding and unsupervised clustering of laminar and morphological features in 3D BigBrain** *NeuroImage* **206** <https://doi.org/10.1016/j.neuroimage.2019.116328>
- Dice L. R. (1945) **Measures of the Amount of Ecologic Association Between Species** *Ecology* **26**:297–302 <https://doi.org/10.2307/1932409>
- Ding S.-L. , Van Hoesen G. W. (2015) **Organization and detailed parcellation of human hippocampal head andbody regions based on a combined analysis of Cyto- and chemoarchitecture** *In Journal of Comparative Neurology* **523**:2233–2253 <https://doi.org/10.1002/cne.23786>
- Duvernoy H. M. , Cattin F. , Risold P.-Y. (2013) **The Human Hippocampus: Functional Anatomy, Vascularization and Serial Sections with MRI**
- Ekstrom A. D. , Bazih A. J. , Suthana N. A. , Al-Hakim R. , Ogura K. , Zeineh M. , Burggren A. C. , Bookheimer S. Y. (2009) **Advances in high-resolution imaging and computational unfolding of the human hippocampus** *In NeuroImage* **47**:42–49 <https://doi.org/10.1016/j.neuroimage.2009.03.017>
- Fischl B. , Rajendran N. , Busa E. , Augustinack J. , Hinds O. , Yeo B. T. T. , Mohlberg H. , Amunts K. , Zilles K. (2008) **Cortical folding patterns and predicting cytoarchitecture** *Cerebral Cortex* **18**:1973–1980
- Flores R. de , de Flores R. , La Joie R. , Chételat G. (2015) **Structural imaging of hippocampal subfields in healthy aging and Alzheimer’s disease** *Neuroscience* **309**:29–50 <https://doi.org/10.1016/j.neuroscience.2015.08.033>

Gerig G. , Styner M. , Shenton M. E. , Lieberman J. A. (2001) **Shape versus Size: Improved Understanding of the Morphology of Brain Structures** :24–32
https://doi.org/10.1007/3-540-45468-3_4

Glasser M. F. , Coalson T. S. , Robinson E. C. , Hacker C. D. , Harwell J. , Yacoub E. , Ugurbil K. , Andersson J. , Beckmann C. F. , Jenkinson M. , Smith S. M. , Van Essen D. C. (2016) **A multi-modal parcellation of human cerebral cortex** *Nature* **536**:171–178

Goualher G. L. , Le Goualher G. , Procyk E. , Collins D. L. , Venugopal R. , Barillot C. , Evans A. C. (1999) **Automated extraction and variability analysis of sulcal neuroanatomy** In *IEEE Transactions on Medical Imaging* **18**:206–217
<https://doi.org/10.1109/42.764891>

Haukvik U. K. , Tamnes C. K. , Söderman E. , Agartz I. (2018) **Neuroimaging hippocampal subfields in schizophrenia and bipolar disorder: A systematic review and meta-analysis** In *Journal of Psychiatric Research* **104**:217–226
<https://doi.org/10.1016/j.jpsychires.2018.08.012>

Henschel L. , Conjeti S. , Estrada S. , Diers K. , Fischl B. , Reuter M. (2020) **FastSurfer - A fast and accurate deep learning based neuroimaging pipeline** *NeuroImage* **219**
<https://doi.org/10.1016/j.neuroimage.2020.117012>

Im K. , Lee J.-M. , Lyttelton O. , Kim S. H. , Evans A. C. , Kim S. I. (2008) **Brain Size and Cortical Structure in the Adult Human Brain** *Cerebral Cortex* **18**:2181–2191
<https://doi.org/10.1093/cercor/bhm244>

Kim H. , Bernhardt B. C. , Kulaga-Yoskovitz J. , Caldaïrou B. , Bernasconi A. , Bernasconi N. (2014) **Multivariate hippocampal subfield analysis of local MRI intensity and volume: application to temporal lobe epilepsy. Medical Image Computing and Computer-Assisted Intervention: MICCAI International Conference on Medical Image Computing and Computer-Assisted Intervention** **17**:170–178

Kim H. , Lepage C. , Evans A. C. , James Barkovich A. , Xu D. (2015) **NEOCIVET: Extraction of Cortical Surface and Analysis of Neonatal Gyrfication Using a Modified CIVET Pipeline** :571–579
https://doi.org/10.1007/978-3-319-24574-4_68

Klein A. , Ghosh S. S. , Avants B. , Yeo B. T. T. , Fischl B. , Ardekani B. , Gee J. C. , Mann J. J. , Parsey R. V. (2010) **Evaluation of volume-based and surface-based brain image registration methods** *NeuroImage* **51**:214–220

Le Guen Y. , Auzias G. , Leroy F. , Noulhiane M. , Dehaene-Lambertz G. , Duchesnay E. , Mangin J.-F. , Coulon O. , Frouin V. (2018) **Genetic Influence on the Sulcal Pits: On the Origin of the First Cortical Folds** *Cerebral Cortex* **28**:1922–1933

Lyttelton O. , Boucher M. , Robbins S. , Evans A. (2007) **An unbiased iterative group registration template for cortical surface analysis** *NeuroImage* **34**:1535–1544
<https://doi.org/10.1016/j.neuroimage.2006.10.041>

MacDonald D. , Kabani N. , Avis D. , Evans A. C. (2000) **Automated 3-D extraction of inner and outer surfaces of cerebral cortex from MRI** *NeuroImage* **12**:340–356

Menzel M. , Axer M. , De Raedt H. , Costantini I. , Silvestri L. , Pavone F. , Amunts K. , Michielsen K. (2020) **Toward a High-Resolution Reconstruction of 3D Nerve Fiber Architectures and Crossings in the Brain Using Light Scattering Measurements and Finite-Difference Time-Domain Simulations** *Physical Review X* **10**

Merker B. (1983) **Silver staining of cell bodies by means of physical development** *Journal of Neuroscience Methods* **9**:235–241

Milner B. , Corkin S. , Teuber H.-L. (1968) **Further analysis of the hippocampal amnesic syndrome: 14-year follow-up study of H.M** *Neuropsychologia* **6**:215–234
[https://doi.org/10.1016/0028-3932\(68\)90021-3](https://doi.org/10.1016/0028-3932(68)90021-3)

O’Keefe J. , Nadel L. (1978) **The Hippocampus as a Cognitive Map**

Olsen R. K. , Carr V. A. , Daugherty A. M. , La Joie R. , Amaral R. S. C. , Amunts K. , Augustinack J. C. , Bakker A. , Bender A. R. , Berron D. , Boccardi M. , Bocchetta M. , Burggren A. C. , Chakravarty M. M. , Chételat G. , de Flores R. , DeKraker J. , Ding S.-L. , Geerlings M. I. , Hippocampal Subfields Group (2019) **Progress update from the hippocampal subfields group** *Alzheimer’s & Dementia: The Journal of the Alzheimer’s Association* **11**:439–449

Palomero-Gallagher N. , Kedo O. , Mohlberg H. , Zilles K. , Amunts K. (2020) **Multimodal mapping and analysis of the cyto-and receptorarchitecture of the human hippocampus** *Brain Structure & Function* **225**:881–907

Paquola C. , Benkarim O. , DeKraker J. , Lariviere S. , Frässle S. , Royer J. , Tavakol S. , Valk S. , Bernasconi A. , Bernasconi N. , Khan A. , Evans A. , Razi A. , Smallwood J. , Bernhardt B. (1970) **Paquola, C., Benkarim, O., DeKraker, J., Lariviere, S., Frässle, S., Royer, J., Tavakol, S., Valk, S., Bernasconi, A., Bernasconi, N., Khan, A., Evans, A., Razi, A., Smallwood, J., & Bernhardt, B. (n.d.). Convergence of cortical types and functional motifs in the mesiotemporal lobe.** **10.1101/2020.06.12.148643**
<https://doi.org/10.1101/2020.06.12.148643>

Patel R. , Steele C. J. , Chen A. G. X. , Patel S. , Devenyi G. A. , Germann J. , Tardif C. L. , Chakravarty M. M. (2020) **Investigating microstructural variation in the human hippocampus using non-negative matrix factorization** *NeuroImage* **207**

Pipitone J. , Park M. T. M. , Winterburn J. , Lett T. A. , Lerch J. P. , Pruessner J. C. , Lepage M. , Voineskos A. N. , Chakravarty M. M. , Alzheimer’s Disease Neuroimaging Initiative (2014) **Multi-atlas segmentation of the whole hippocampus and subfields using multiple automatically generated templates** *NeuroImage* **101**:494–512

Przeździk I. , Faber M. , Fernández G. , Beckmann C. F. , Haak K. V. (2019) **The functional organisation of the hippocampus along its long axis is gradual and predicts recollection** *Cortex; a Journal Devoted to the Study of the Nervous System and Behavior* **119**:324–335

- Qiu A. , Miller M. I. (2008) **Multi-structure network shape analysis via normal surface momentum maps** *NeuroImage* **42**:1430–1438
- Régis J. , Mangin J.-F. , Ochiai T. , Frouin V. , Rivière D. , Cachia A. , Tamura M. , Samson Y. (2005) **“Sulcal Root” Generic Model: a Hypothesis to Overcome the Variability of the Human Cortex Folding Patterns** *In Neurologia medico-chirurgica* **45**:1–17
<https://doi.org/10.2176/nmc.45.1>
- Riphagen J. M. , Schmiedek L. , Gronenschild E. H. B. M. , Yassa M. A. , Priovoulos N. , Sack A. T. , Verhey F. R. J. , Jacobs H. I. L. (2020) **Associations between pattern separation and hippocampal subfield structure and function vary along the lifespan: A 7 T imaging study** *Scientific Reports* **10**
- Robbins S. M. (2003) **Anatomical standardization of the human brain in euclidean 3-space and on the cortical 2-manifold**
- Roeske M. , Konradi C. , Heckers S. , Lewis A. (2020) **Postmortem Studies of Hippocampal Subfields in Schizophrenia: Systematic Review and Meta-Analysis** *Biological Psychiatry* **87**
<https://doi.org/10.1016/j.biopsych.2020.02.1096>
- Styner M. , Lieberman J. A. , Pantazis D. , Gerig G. (2004) **Boundary and medial shape analysis of the hippocampus in schizophrenia** *Medical Image Analysis* **8**:197–203
- Tardif C. L. , Schäfer A. , Waehnert M. , Dinse J. , Turner R. , Bazin P.-L. (2015) **Multi-contrast multi-scale surface registration for improved alignment of cortical areas** *NeuroImage* **111**:107–122
<https://doi.org/10.1016/j.neuroimage.2015.02.005>
- Thom M. (2014) **Review: Hippocampal sclerosis in epilepsy: a neuropathology review** *Neuropathology and Applied Neurobiology* **40**:520–543
- Van Essen D. C. , Drury H. A. , Joshi S. , Miller M. I. (2000) **Functional and structural mapping of human cerebral cortex: solutions are in the surfaces** *Advances in Neurology* **84**:23–34
- Van Essen D. C. , Glasser M. F. , Dierker D. L. , Harwell J. , Coalson T. (2012) **Parcellations and Hemispheric Asymmetries of Human Cerebral Cortex Analyzed on Surface-Based Atlases** *Cerebral Cortex* **22**:2241–2262
<https://doi.org/10.1093/cercor/bhr291>
- Vogel J. W. , La Joie R. , Grothe M. J. , Diaz-Papkovich A. , Doyle A. , Vachon-Presseau E. , Lepage C. , Vos de Wael R. , Thomas R. A. , Iturria-Medina Y. , Bernhardt B. , Rabinovici G. D. , Evans A. C. (2020) **A molecular gradient along the longitudinal axis of the human hippocampus informs large-scale behavioral systems** *Nature Communications* **11**
- Vos de Wael R. , Larivière S. , Caldairou B. , Hong S.-J. , Margulies D. S. , Jefferies E. , Bernasconi A. , Smallwood J. , Bernasconi N. , Bernhardt B. C. (2018) **Anatomical and microstructural determinants of hippocampal subfield functional connectome embedding** *Proceedings of the National Academy of Sciences of the United States of America* **115**:10154–10159

Wisse L. E. M. , Daugherty A. M. , Olsen R. K. , Berron D. , Carr V. A. , Stark C. E. L. , Amaral R. S. C. , Amunts K. , Augustinack J. C. , Bender A. R. , Bernstein J. D. , Boccardi M. , Bocchetta M. , Burggren A. , Chakravarty M. , Chupin M. , Ekstrom A. , de Flores R. , Insausti R. , Hippocampal Subfields Group (2017) **A harmonized segmentation protocol for hippocampal and parahippocampal subregions: Why do we need one and what are the key goals?** *Hippocampus* **27**:3–11

Yushkevich P. A. , Amaral R. S. C. , Augustinack J. C. , Bender A. R. , Bernstein J. D. , Boccardi M. , Bocchetta M. , Burggren A. C. , Carr V. A. , Chakravarty M. M. , Chételat G. , Daugherty A. M. , Davachi L. , Ding S.-L. , Ekstrom A. , Geerlings M. I. , Hassan A. , Huang Y. , Iglesias J. E. , Hippocampal Subfields Group (HSG) (2015) **Quantitative comparison of 21 protocols for labeling hippocampal subfields and parahippocampal subregions in in vivo MRI: towards a harmonized segmentation protocol** *NeuroImage* **111**:526–541

Yushkevich P. A. , Piven J. , Hazlett H. C. , Smith R. G. , Ho S. , Gee J. C. , Gerig G. (2006) **User-guided 3D active contour segmentation of anatomical structures: significantly improved efficiency and reliability** *NeuroImage* **31**:1116–1128

Yushkevich P. A. , Pluta J. B. , Wang H. , Xie L. , Ding S.-L. , Gertje E. C. , Mancuso L. , Klot D. , Das S. R. , Wolk D. A. (2015) **Automated volumetry and regional thickness analysis of hippocampal subfields and medial temporal cortical structures in mild cognitive impairment** *Human Brain Mapping* **36**:258–287

Yushkevich P. A. , Pluta J. , Wang H. , Wisse L. E. M. , Das S. , Wolk D. (2016) **IC-P - 174: Fast Automatic Segmentation of Hippocampal Subfields and Medial Temporal Lobe Subregions In 3 Tesla and 7 Tesla T2-Weighted MRI** *Alzheimer's & Dementia* **12**
<https://doi.org/10.1016/j.jalz.2016.06.205>

Zeineh M. M. , Engel S. A. , Bookheimer S. Y. (2000) **Application of cortical unfolding techniques to functional MRI of the human hippocampal region** *NeuroImage* **11**:668–683

Zeineh M. M. , Engel S. A. , Thompson P. M. , Bookheimer S. Y. (2001) **Unfolding the human hippocampus with high resolution structural and functional MRI** *The Anatomical Record* **265**:111–120
<https://doi.org/10.1002/ar.1061>

Zeineh M. M. , Palomero-Gallagher N. , Axer M. , Gräbel D. , Goubran M. , Wree A. , Woods R. , Amunts K. , Zilles K. (2017) **Direct Visualization and Mapping of the Spatial Course of Fiber Tracts at Microscopic Resolution in the Human Hippocampus** *Cerebral Cortex* **27**:1779–1794

Author information

Jordan DeKraker

Montreal Neurological Institute and Hospital, McGill University, Montreal, Canada

For correspondence: jordan.dekraker@mail.mcgill.ca

ORCID iD: [0000-0002-4093-0582](https://orcid.org/0000-0002-4093-0582)

Nicola Palomero-Gallagher

Institute of Neuroscience and Medicine INM-1, Research Centre Jülich, Germany, C. & O. Vogt
Institute for Brain Research, University Hospital Düsseldorf, Heinrich-Heine-University, 40225
Düsseldorf, Germany

Olga Kedo

Institute of Neuroscience and Medicine INM-1, Research Centre Jülich, Germany

Neda Ladbon-Bernasconi

Montreal Neurological Institute and Hospital, McGill University, Montreal, Canada

Sascha E.A. Muenzing

Institute of Neuroscience and Medicine INM-1, Research Centre Jülich, Germany

Markus Axer

Institute of Neuroscience and Medicine INM-1, Research Centre Jülich, Germany

Katrin Amunts

Institute of Neuroscience and Medicine INM-1, Research Centre Jülich, Germany

Ali R. Khan

Robarts Research Institute, University of Western Ontario, London, Canada
ORCID iD: [0000-0002-0760-8647](https://orcid.org/0000-0002-0760-8647)

Boris Bernhardt

Montreal Neurological Institute and Hospital, McGill University, Montreal, Canada
ORCID iD: [0000-0001-9256-6041](https://orcid.org/0000-0001-9256-6041)

Alan C. Evans

Montreal Neurological Institute and Hospital, McGill University, Montreal, Canada

Editors

Reviewing Editor

Anna Schapiro

University of Pennsylvania, United States of America

Senior Editor

Laura Colgin

University of Texas at Austin, United States of America

Reviewer #1 (Public Review):

This paper proposes and evaluates a new approach for the registration of human hippocampal anatomy between individuals. Such registration is an essential step in group analysis of hippocampal structure and function, and in most studies to date, volumetric registration of MRI scans has been employed. However, it is known that volumetric deformable registration, due to its formulation as an optimization problem that minimizes

the combination of an image similarity term and relatively simple geometric regularization terms, fails to preserve the topology of complex structures. In the cerebral cortex, surface-based registration of inflated cortical surfaces is broadly preferred over volumetric registration, which often causes voxels of different tissue types to be matched (e.g., voxels belonging to a sulcus in one individual mapping onto voxels belonging to a gyrus in another). The authors recognize that hippocampal anatomy is similarly complex, and, with proper tools, can benefit from surface-based registration. They propose to first unfold the hippocampus to a two-dimensional rectangle domain using their prior HippUnfold technique, and then to perform deformable registration in this rectangle domain, matching geometric features (curvature, thickness, gyrification) between individuals. This registration approach is evaluated by comparing how well hippocampal subfields traced by experts using cytoarchitectural information align between individuals after registration. The authors indeed show that surface-based registration aligns subfields better than volumetric registration applied to binary segmentations of the hippocampal gray matter.

Overall, I find the methods and results in this paper to be convincing. The authors framed the comparison between surface-based and volumetric registration in a fair way, and the results convincingly show the advantage of surface-based registration. One slight limitation of the current study is that it is uncertain whether the benefits demonstrated here translate to in vivo MRI data for which the authors' HippUnfold algorithm is tailored. The current study utilized the unfolding technique used in HippUnfold on manual segmentations of high-resolution ex vivo MRI and blockface 3D volumes, which are likely closer to anatomical ground truth than automated segmentations of in vivo MRI. However, it is reasonable to assume that given that the volumetric registration to which the proposed approach was compared also used this high-detail data, the advantages of surface-based over volumetric registration would extend to in vivo MRI as well. However, I would encourage the authors to perform future evaluations on datasets with available in vivo and ex vivo MRI from the same individuals.

I would also like to point out the relevance of the 2021 paper "Unfolding the Medial Temporal Lobe Cortex to Characterize Neurodegeneration Due to Alzheimer's Disease Pathology Using Ex vivo Imaging" by Ravikumar et al. (https://link.springer.com/chapter/10.1007/978-3-030-87586-2_1) to the current work. This paper applied an earlier version of the unfolding method in HippUnfold to ex vivo extrahippocampal cortex and performed registration using curvature features in the rectangular unfolded space, also finding slight improvement with surface-based vs. volumetric registration, so its findings support the current paper.

Overall, the paper has the potential to significantly influence future research on hippocampal involvement in cognition and disease. Outside of simple volumetry studies, most hippocampal morphometry studies rely on volumetric deformable registration of some kind, typically applied to whole-brain T1-weighted MRI scans. With HippUnfold available for anyone to use and not requiring manual registration, the paper provides a strong impetus for using this approach in future studies, particularly where one is interested in localizing effects of interest to specific areas of the hippocampus. Additional evaluation of in vivo HippUnfold using in vivo / ex vivo datasets, would make the use of this approach even more appealing.

Reviewer #2 (Public Review):

DeKraker et al. propose a new method for hippocampal registration using a surface-based approach that preserves the topology of the curvature of the hippocampus and boundaries of hippocampal subfields. The surface-based registration method proved to be more precise

and resulted in better alignment compared to traditional volumetric-based registration. Moreover, the authors demonstrated that this method can be performed across image modalities by testing the method with seven different histological samples. While the conclusions of this paper are mostly well supported by data, some aspects of the method need to be clarified. This work has the potential to be a powerful new registration technique that can enable precise hippocampal registration and alignment across subjects, datasets, and image modalities.

Regarding the methodological clarification of the surfaced-based registration method, the last step of the process needs further clarification. Specifically, after creating the averaged 2D template, it is unclear how each individual sample is registered to sample1's space. If I understand correctly, after creating the averaged 2D template, each individual sample is then registered to sample1's space via the transform from each sample to the averaged template and then the inverse transform from the template to sample1's space. Samples included both left and right hemispheres, so were all samples being propagated to left hemisphere sample 1 space? The authors also note that a measure of the subfield labels overlap with that sample's ground-truth subfield definitions was calculated. Is this a measure of overlap, for example, between sample 3 (registered to sample 1 space) and the ground-truth (unfolded, not registered) sample 3 labels? It would be beneficial to provide a full walkthrough of one example sample to clarify the steps. Clarification of this aspect of the method is critical for understanding the evaluation of the method.

Reviewer #3 (Public Review):

Dekraker and colleagues previously developed a new computational tool that creates a "surface representation" of the hippocampal subfields. This surface representation was previously constructed using histology from a single case. However, it was previously unclear how to best register and compare these surface-based representations to other cases with different morphology.

In the current manuscript, Dekraker and colleagues have demonstrated the ability to align hippocampal subfield parcellations across disparate 3D histology samples that differ in contrast, resolution, and processing/staining methods. In doing so, they validated the previously generated Big-Brain atlas by comparing seven different ground-truth subfield definitions. This is an impressive and valuable effort that provides important groundwork for future in vivo multi-atlas methods.