

```

# -*- coding: utf-8 -*-
"""
Created on February 16, 2024
@author:
    Elif KARTAL, Istanbul University, Faculty of Economics, Department of
    Management Information Systems
    Beyaz Basak ESKISEHIRLI, Faculty of Science, Department of Mathematics
    Fatma CALISKAN, Faculty of Science, Department of Mathematics
    Zeki OZEN, Istanbul University, Faculty of Economics, Department of
    Management Information Systems

@title: Examples with p-adic calculations
"""

import p_adic

x = 25

# p_adic_val() function returns the p-adic absolute value of a given number.

x_p2 = p_adic.p_adic_val(x, p_num=2)

print("2-adic value of ", x, " is ", x_p2)
2-adic value of 25 is 1

x_p3 = p_adic.p_adic_val(x, p_num=3)

print("3-adic value of ", x, " is ", x_p3)
3-adic value of 25 is 1

x_p5 = p_adic.p_adic_val(x, p_num=5)

print("5-adic value of ", x, " is ", x_p5)
5-adic value of 25 is 0.04

y = 16

y_p2 = p_adic.p_adic_val(y, p_num=2)

print("2-adic value of ", y, " is ", y_p2)
2-adic value of 16 is 0.0625

# p_adic_pow_val() function returns both the order and the p-adic absolute
value of the given number.

y_p2_ord, y_p2_val = p_adic.p_adic_pow_val(y, p_numb=2)

print(y_p2_ord)
4

print(y_p2_val)
0.0625

y_p3 = p_adic.p_adic_val(y, p_num=3)

print("3-adic value of ", y, " is ", y_p3)
3-adic value of 16 is 1

```

```

y_p5 = p_adic.p_adic_val(y, p_num=5)

print("5-adic value of ", y, " is ", y_p5)
5-adic value of 16 is 1

z = -16

z_p = p_adic.p_adic_val(z, p_num=5)

print("5-adic value of ", z, " is ", z_p)
5-adic value of -16 is 1

t = 0

print("2-adic value of ", t, " is ", p_adic.p_adic_val(t, p_num=2))
2-adic value of 0 is 0

print("3-adic value of ", t, " is ", p_adic.p_adic_val(t, p_num=3))
3-adic value of 0 is 0

print("5-adic value of ", t, " is ", p_adic.p_adic_val(t, p_num=5))
5-adic value of 0 is 0

print("17-adic value of ", t, " is ", p_adic.p_adic_val(t, p_num=17))
17-adic value of 0 is 0

p = 1

print("2-adic value of ", p, " is ", p_adic.p_adic_val(p, p_num=2))
2-adic value of 1 is 1

print("3-adic value of ", p, " is ", p_adic.p_adic_val(p, p_num=3))
3-adic value of 1 is 1

print("5-adic value of ", p, " is ", p_adic.p_adic_val(p, p_num=5))
5-adic value of 1 is 1

print("17-adic value of ", p, " is ", p_adic.p_adic_val(p, p_num=17))
17-adic value of 1 is 1

r1 = -54

print("3-adic value of ", r1, " is ", p_adic.p_adic_val(r1, p_num=3))
3-adic value of -54 is 0.037037

s = -(24/16)

print("2-adic value of ", s, " is ", p_adic.p_adic_val(s, p_num=2))
2-adic value of -1.5 is 2

print(p_adic.p_adic_pow_val(s, p_numb=2))
(-1, 2)

s1 = 8

print(p_adic.p_adic_pow_val(s1, p_numb=2))
(3, 0.125)

```

```

s2 = 100

print(p_adic.p_adic_pow_val(s2, p_numb=5))
(2, 0.04)

s3 = 0.270

print(p_adic.p_adic_pow_val(s3, p_numb=3))
(3, 0.037037)

s4 = 0.270

print(p_adic.p_adic_pow_val(s4, p_numb=5))
(-2, 25)

# p-parameter of p_adic_val() function must be prime!

m = 16

print(p_adic.p_adic_val(m, p_num=4))
p should be a prime number!
None

```