

# Object Detection for Autonomous Driving

## Application Cases, Metrics and Data Augmentation

---

---

Alina Griesel, Elisa Hagensieker, Stella Hoyos Trueba, Madleen Uecker

# Use Case - Object Detection for Autonomous Driving

## Importance:


- Safety: ensure safe navigation and prevent collision
- Traffic efficiency: optimize traffic flow
- Regulatory compliance: adheres to traffic laws

## Problems of natural data:

- Data privacy: Faces, licence plates
- Cost and time: Data collection and annotation
- Diversity and coverage: Capture all driving scenarios

## Synthetic data to our help:

- Privacy friendly: no real individuals involved
- Cost effective
- Controlled environment
- Scalability





# Datasets

- datasets: nuScene, Kitty, ScanNet, Waymo, S3DIS/Cityscapes, Argoverse, CARLA, Synscapes




Name	Link	License	Year	3D point cloud segmentation	3D object detection & tracking	3D drivable area	2D object detection & tracking	2D segmentation	2D freespace	2D drivable area	2D lane markings	Plant Classification	Motion forecasting	Image / Other Annotation Format	Lidar Annotation Format	Relevance	Scene Type	RGB	RGB-E	Lidar	Radar	FLIR / NIR	GPS / IMU	Maps	Details
DeepScene (Freiburg Forest)	<a href="http://deepscene.cs.uni-freiburg.de/">http://deepscene.cs.uni-freiburg.de/</a>	non-commercial	2016	x										?	?	high	forest	x	x			x			Bumblebee2 Stereo
FieldSAFE	<a href="https://vision.eng.azd.edu/FieldSAFE/">https://vision.eng.azd.edu/FieldSAFE/</a>	non-commercial	2016		x	x								-	map based + object coordinates	high	grass field	x	x	x	x	x			Velodyne HDL-32E, Delphi ESR Radar, Flir A65,
NREC Human Detection and	<a href="https://www.nrec.ri.ac.uk/">https://www.nrec.ri.ac.uk/</a>	non-commercial	2017		x	x								Pascal VOC	-	high	off-road (apple/orange field)	x	x				x		
OFFSED	<a href="http://www.dfti.uni-leipzig.de/offsed/">http://www.dfti.uni-leipzig.de/offsed/</a>	non-commercial	2021	x										CVAT rgb/png files	-	high	od, farmland, construction si	x	x						Stereolabs ZED Camera, some instances labels
OPEDD	<a href="http://www.dfti.uni-leipzig.de/opedd/">http://www.dfti.uni-leipzig.de/opedd/</a>	non-commercial	2021		x									VIA json files	-	high	od, farmland, construction si	x	x						Stereolabs ZED Camera
RELLIS-3D	<a href="https://unmanned.umd.edu/rellis-3d/">https://unmanned.umd.edu/rellis-3d/</a>	non-commercial	2020	x				x						rgb/png files	SemanticKITTI (label files)	high	off-road	x	x	x			x		Ouster OS1, Velodyne Ultra-Puck 32, Karmin 2 St
RUGD	<a href="http://rugd.vision.rwth-aachen.de/">http://rugd.vision.rwth-aachen.de/</a>	unknown	2019					x						rgb/png files	-	high	off-road	x		x			x		Velodyne HDL-32E, Proscollia 6 MP camera
SemanticUSL	<a href="https://unmanned.umd.edu/semanticusl/">https://unmanned.umd.edu/semanticusl/</a>	non-commercial	2020	x										-	SemanticKITTI (label files)	high	campus & off-road	x		x					Ouster OS1-64 Lidar
SugarBeets	<a href="http://www.ipb.uni-leipzig.de/sugarbeets/">http://www.ipb.uni-leipzig.de/sugarbeets/</a>	public	2016									x		?	?	high	sugar beets / field	x	x	x			x		2x Velodyne VLP-16, Camera JAI AD-130GE, Kine
YCOR		?	?	x										?	?	high	off-road	x							
KIT MOHA		unknown	2016					x						?	?	mid	construction sides	x							
Manlan	<a href="http://is.dia.acfr.usyd.edu.au/manlan/">http://is.dia.acfr.usyd.edu.au/manlan/</a>	unknown	2009		x	x								-	-	mid	dust, smoke, rain	x		x	x	x	x		Sick LaserStarboardPort, FMCW Radar, Raytheon
Rosario	<a href="https://www.citg.su.se/rosario/">https://www.citg.su.se/rosario/</a>	unknown	2019										x	3D position GT	-	mid	soybean field			x	x		x		Sick LaserStarboardPort, FMCW Radar, Raytheon
SemanticKITTI	<a href="http://semantic-kitti.org/">http://semantic-kitti.org/</a>	non-commercial	2019	x										-	SemanticKITTI (label files)	mid	urban			x					Velodyne HDL-64E
RAGE	<a href="https://download.vision.rwth-aachen.de/rage/">https://download.vision.rwth-aachen.de/rage/</a>	unknown	2016					x	x					-	-	mid	urban simulator	x							Simulation based semantic labels
DALES	<a href="https://uxdaxton.edu/dales/">https://uxdaxton.edu/dales/</a>	non-commercial	2020	x										-	-	none	arial scans	x		x					airborn laser scanner
IQMUS	<a href="http://data.lgn.fr/barthelemy/iqm-us/">http://data.lgn.fr/barthelemy/iqm-us/</a>	non-commercial	2015	x										-	-	none	urban road scans			x					MLS (3d mobile laser scanner)
ISPRS	<a href="https://www2.isprs.org/">https://www2.isprs.org/</a>	unknown	2012	x										-	-	none	arial scans			x					airborn laser scanner
Oakland 3-D Point Cloud	<a href="https://www.cs.cmu.edu/~pabbe/3dpc/">https://www.cs.cmu.edu/~pabbe/3dpc/</a>	unknown	2009	x										-	-	none	urban road scans								Sick LMS Laser
Paris-Lille-3D	<a href="https://gm3d.fr/paris-lille-3d/">https://gm3d.fr/paris-lille-3d/</a>	non-commercial	2018	x										-	-	none	urban road scans					x			Velodyne HDL-32E
Paris-rue-Madame	<a href="http://www.cmm.mcgill.ca/paris-rue-madame/">http://www.cmm.mcgill.ca/paris-rue-madame/</a>	non-commercial	2014	x										-	-	none	urban road scans					x			MLS (3d mobile laser scanner)
S3DIS		unknown	2017	x										-	-	none	indoor	x		x					
ScanNet	<a href="http://www.scan-net.org/">http://www.scan-net.org/</a>	unknown	2017	x										-	-	none	indoor	x		x					
ScanNetV2	<a href="http://www.scan-net.org/v2/">http://www.scan-net.org/v2/</a>	unknown	2018		x									-	-	none	indoor			x					
Semantic3D	<a href="https://www.semantic3d.org/">https://www.semantic3d.org/</a>	non-commercial	2017	x										-	-	none	urban / rural scans	x		x					Terrestrial Laser Scanner
SUN RGB-D	<a href="https://rgbd.cs.pitt.edu/">https://rgbd.cs.pitt.edu/</a>	unknown	2015		x									-	-	none	indoor			x					
Toronto-3D	<a href="https://rthub.com/toronto-3d/">https://rthub.com/toronto-3d/</a>	unknown	2020	x										-	-	none	urban road scans			x					MLS (3d mobile laser scanner)
Drive&Act	<a href="https://www.driveandact.org/">https://www.driveandact.org/</a>	non-commercial	2019											-	-	none	driver seat	x		x			x		
A*3D	<a href="https://github.com/azavea/a3d/">https://github.com/azavea/a3d/</a>	non-commercial	2020		x									-	-	unknown	urban	x		x					Velodyne HDL-64E, 2x PointGrey Chameleon2 ca
ApolloScape	<a href="http://apolloscope.com/">http://apolloscope.com/</a>	non-commercial	2018					x	x				x	-	-	unknown	urban	x		x					
Argoverse	<a href="https://www.argoverse.org/">https://www.argoverse.org/</a>	non-commercial	2019		x					x			x	-	-	unknown	urban	x		x	x			x	Velodyne Pucks, Stereo and Mono Cameras, HD-
BOK100K	<a href="https://bair.berkeley.edu/projects/bok100k/">https://bair.berkeley.edu/projects/bok100k/</a>	unknown	2020					x	x		x	x		-	-	unknown	urban	x		x					HD video
Cityscape	<a href="https://www.cityscapes-dataset.net/">https://www.cityscapes-dataset.net/</a>	non-commercial			x					x				-	-	unknown	urban	x		x					
Cityscape 3D	<a href="https://www.cityscapes-dataset.net/3d/">https://www.cityscapes-dataset.net/3d/</a>	non-commercial	2020		x									-	-	unknown	urban	x		x	x			x	
Ford Autonomous Vehicle Dat	<a href="https://avdata.ford.com/">https://avdata.ford.com/</a>	university only	2020											-	-	unknown	urban	x		x				x	4x Velodyne HDL-32E, 6 Point Grey 1.3 MP Camer

- 1: Dosovitskiy et al.
- 2: Geiger et al.
- 3: Sun et al
- 4: Gaidon et al.

# Overview Datasets

Dataset	KITTI <sup>2</sup>	Virtual KITTI <sup>4</sup>	nuScene	Waymo <sup>3</sup>	CARLA <sup>1</sup>
Characteristic	LiDAR and camera data	unity game engine		LiDAR and camera data	open-source simulator
Size	object detection dataset: 7481 training & 7518 test img, total: 80.256 labeled objects	50 high-resolution monocular videos (21,260 frames)		1150 scenes, each 20 sec.	
License	CC BY-NC-SA 3.0	CC BY-NC-SA 3.0		non-commercial	CC-BY / MIT
Real / Synthetic	real	synthetic		real	synthetic
Example					

# Overview Datasets

Dataset	KITTI <sup>2</sup> human annotators	Virtual KITTI <sup>4</sup> automatically labeled (unity)	Waymo <sup>3</sup> human annotators
Characteristic	LiDAR and camera data	unity game engine	LiDAR and camera data
Size	object detection dataset: 7481 training & 7518 test img, total: 80.256 labeled objects	50 high-resolution monocular videos (21,260 frames)	1150 scenes, each 20 sec.
Classes	8 classes: number of instances (training data): 28742 car, 4487 pedestrian, 2914 van, 11627 cyclist, 1094 truck	1 class: car (main category of KITTI)	4 classes: mean count of instances per class: 30 vehicle, 14 pedestrian, 0 cyclists
License	CC BY-NC-SA 3.0	CC BY-NC-SA 3.0	non-commercial
Real / Synthetic	real,	synthetic	real
Example			

# Overview Datasets - Waymo

Object Class	Mean	Median	Max
Vehicle	30	27	163
Pedestrian	14	27	192
Cyclist	0	0	11



1 (TYPE\_VEHICLE)  
1 (TYPE\_VEHICLE)  
2 (TYPE\_PEDESTRIAN)  
2 (TYPE\_PEDESTRIAN)  
2 (TYPE\_PEDESTRIAN)  
1 (TYPE\_VEHICLE)  
2 (TYPE\_PEDESTRIAN)

# Datasets

KITTI [https://www.cvlibs.net/datasets/kitti/eval\\_obj.php?obj\\_benchmark=3d](https://www.cvlibs.net/datasets/kitti/eval_obj.php?obj_benchmark=3d)

## Data collection and privacy

- Funding: KIT, TTI-C
- Privacy: academic use only (registration required, Creative Commons Attribution-NonCommercial-ShareAlike 3.0 License)
- Footprint: equipped with Radar, LiDAR, camera data
- classes: building, tree, sky, car, sign, road, pedestrian, fence, pole, sidewalk, bicyclist
- 73.7km driving distance
- 7481 training images; 7519 test images (80256 labeled objects)
-

# Datasets

## Virtual KITTI

Data generation:

- Unity game engine with 5 different virtual worlds under different lightning and weather conditions
- Creative Commons Attribution-NonCommercial-ShareAlike 3.0 License - restrictions on commercial use and distribution
- corresponds to real KITTI scenes
- “measuring the real-to-virtual gap, deep learning with virtual data, and measuring the generalization performance under changes in imaging and weather conditions”

[https://github.com/VisualComputingInstitute/vkitti3D-dataset/blob/master/tools/download\\_raw\\_vkitti.sh](https://github.com/VisualComputingInstitute/vkitti3D-dataset/blob/master/tools/download_raw_vkitti.sh) (try out for download)

- Radar, LiDAR, camera data
- classes: building, tree, sky, car, sign, road, pedestrian, fence, pole, sidewalk, bicyclist
- 7481 training images; 7519 test images (80256 labeled objects)



# Datasets

## Waymo

- `tfds.load('waymo_open_dataset/v1.0', data_dir='gs://waymo_open_dataset_v_1_0_0_individual_files/tensorflow_datasets')`
- Creative Commons Attribution-NonCommercial-ShareAlike 3.0 License - restrictions on commercial use and distribution; registration required for download
- objects in motion: vehicle, pedestrians, cyclists and more
- Footprint: LiDAR, Camera with annotations for scene understanding in 2D and 3D
-

# Metrics


- Mean Average Precision
- Intersection over Union
- Standard accuracy measures

Virtual KITTI: MSE and Edge-Aware Smoothing loss  
(<https://arxiv.org/pdf/2006.04080v2>)

## Task: Object detection &amp; 3D representation

1. 2D Backbone: V2-99 extended to Feature Pyramid Network generating two feature maps:
  - a. depth keys
  - b. image features
2. Orientation-Aware Image Backbone:
3. Local Ray Attention Mechanism: image feature maps to 3D voxel features without point clouds
4. BEV backbone: predicts 3D occupancy map


→ 31.55% AP



# Monocular Unified 3D Object Detection - MonoUNI

Task: Monocular 3D detection

1. BaseModel: CenterNet generates discriminative representations
2. Backbone: DLA34 for feature extraction
  - Deep Layer Aggregation for hierarchical features
3. Network Heads: prediction of various object properties:
  - category
  - 2D bounding box
  - 3D offset
  - dimension of objects
  - orientation
  - 3D normalized cube depth
  - bias depth and depth uncertainty



# GANs for mixed datasets

Pros	Cons
<b>Privacy Preservation:</b> <ul style="list-style-type: none"><li>• No identifiable information (i.e. faces, license plates)</li></ul>	<b>Reality Gap:</b> <ul style="list-style-type: none"><li>• mimic complexity and variability</li></ul>
<b>Scalability:</b> <ul style="list-style-type: none"><li>• once created it can generate unlimited amount of data</li></ul>	<b>Diversity and Variability:</b> <ul style="list-style-type: none"><li>• capture rare cases crucial for robust object detection</li></ul>
<b>Controlled Environment:</b> <ul style="list-style-type: none"><li>• Control various aspects of generated data (i.e. weather conditions, traffic scenarios)</li></ul>	<b>Semantic Understanding:</b> <ul style="list-style-type: none"><li>• essential to ensure that generated scenes are semantically meaningful (i.e. spatial relationship)</li></ul>
	<b>Ethical and Safety Concerns:</b> <ul style="list-style-type: none"><li>• additional complexities and uncertainties with the use of synthetic data</li></ul>

## GAN Architectures:

- Deep Convolutional GAN: Convolutional layers in generator and discriminator networks to generate high-resolution images

## Characteristics:

- Conditional GANs: Generate synthetic images or traffic scenarios conditioned on different weather conditions or road layouts
- Self-Attention GAN: focus on relevant spatial information of the input to keep semantic understanding of spatial relationship

---

---

**THANK YOU FOR YOUR  
ATTENTION!**

---

---

# Sources

- Lightning NeRF: Efficient Hybrid Scene Representation for Autonomous Driving <https://arxiv.org/pdf/2403.05907>
- Dosovitskiy, A., Ros, G., Codevilla, F., Lopez, A. & Koltun, V.. (2017). CARLA: An Open Urban Driving Simulator. <i>Proceedings of the 1st Annual Conference on Robot Learning</i>, in <i>Proceedings of Machine Learning Research</i> 78:1-16 Available from <https://proceedings.mlr.press/v78/dosovitskiy17a.html>.
- Geiger, A., Lenz, P., & Urtasun, R. (2012, June). Are we ready for autonomous driving? the kitti vision benchmark suite. In *2012 IEEE conference on computer vision and pattern recognition* (pp. 3354-3361). IEEE.
  - different citations needed for different KITTI stuff !!!
- Sun, P., Kretschmar, H., Dotiwalla, X., Chouard, A., Patnaik, V., Tsui, P., ... & Anguelov, D. (2020). Scalability in perception for autonomous driving: Waymo open dataset. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition* (pp. 2446-2454).
- Gaidon, A., Wang, Q., Cabon, Y., & Vig, E. (2016). Virtual worlds as proxy for multi-object tracking analysis. In *Proceedings of the IEEE conference on computer vision and pattern recognition* (pp. 4340-4349).
- Jinrang, J., Li, Z., & Shi, Y. (2024). MonoUNI: A unified vehicle and infrastructure-side monocular 3d object detection network with sufficient depth clues. *Advances in Neural Information Processing Systems*, 36.
- Ye, Q., Jiang, L., Zhen, W., & Du, Y. (2022). Consistency of implicit and explicit features matters for monocular 3d object detection. *arXiv preprint arXiv:2207.07933*.

# Sources

Waymo Dataset:

- [https://www.tensorflow.org/datasets/catalog/waymo\\_open\\_dataset](https://www.tensorflow.org/datasets/catalog/waymo_open_dataset)
- <https://github.com/kittyschulz/Exploring-Waymo-Open-Dataset/tree/master>
- <https://waymo.com/open/about/>

Virtual KITTI:

- <https://europe.naverlabs.com/research-old2/computer-vision/proxy-virtual-worlds-vkitti-1/>

KITTI:

- [https://www.cvlibs.net/datasets/kitti-360/user\\_login.php](https://www.cvlibs.net/datasets/kitti-360/user_login.php)
- <https://www.tensorflow.org/datasets/catalog/kitti>