Brain2Body: The Next Generation In Body-Brain Interfacing.

Simple English Edition

@eliminatenoise

Unpublished Working Draft

Abstract

A hand can play the right notes because a computer guides it. The important question comes when that guidance stops: has the nervous system learned anything it can still do? Brain2Body proposes tests that keep help, simulated control, lasting learning and biological repair separate. A camera, a muscle recording and a brain recording observe different parts of the problem. The next proposed experiment would align those observations with a measured movement and a computer body, then test each direction against observations the model did not receive. That experiment has not been carried out here. The current companion LINK study saved 18 runs and 720 epochs; both candidate models fail their admission rules, and all five added benefit claims fail. Those results do not show biological teaching. This longer explanation sets out the question, the evidence, the controls and the limits. Predicting a recorded brain feature does not deliver a sensation, and a guided movement does not by itself demonstrate a learned skill.

1 Assistance and Learning

Imagine watching a hand play a short tune. Every key lands at the right moment. It looks like skill. Now imagine that an outside computer chose the notes and controlled each finger. The tune is still real as an action, but we have not yet shown that the nervous system learned to play it.

This is the question behind Brain2Body: could useful help leave a nervous system more capable after the help ends? That is a bigger question than making a body move once. It asks about what was learned, what support is still needed and whether the improvement survives tomorrow, a different starting position or an unfamiliar problem.

Brain2Body means brain to body; the 2 stands for “to.” Information also travels the other way. A movement changes what the body senses. That new information helps guide the next movement. The programme proposes studying these relationships with real measurements, computer models of bodies and carefully limited experiments. It does not claim that a complete skill can already be downloaded into someone.

The long-term ambition is deliberately bold: help a learner acquire difficult physical skills much faster. Sewing, playing violin, solving a puzzle with the hands or coordinating a dance would be demanding tests. They require different body parts, information and kinds of feedback. These examples set the ambition. They are not a list of things the current system can do.

NeuroTranslation proposes mapping nervous-system signals between clearly described situations, such as a particular recording and a particular movement task. Brain2Body takes the next question: what happens when that prediction has to work through a physical body and help a learner? A useful prediction can start the experiment, but the body's response and the learner's later performance determine what it has achieved. We need to follow the information into the movement, then follow the movement beyond the moment of help. Each step gives the next test a reason to exist.

2 A Single-Key Test

Suppose the task is to press the leftmost of four keys, then release it before the next beat. Success needs several checks: the right key moves, it moves at the right time, it is released, and a neighbouring key is not pressed accidentally. State what happens if the finger misses completely. Each rule names a different way the movement can succeed or fail.

That small example contains several problems. The learner may choose the wrong key. The finger may move toward the right key but fall short. The finger may press correctly and hold too long. A second finger may strike a neighbour. A single label called "success" can hide all of these differences unless the rules are stated.

A camera can help measure where a finger went. A contact sensor can record that a key was touched. A force sensor can measure how hard it was pressed. A clock can record timing. An electrode can record nearby electrical activity. These are different observations. Looking at a brain signal does not automatically tell us the force at a fingertip; seeing a key press does not automatically tell us which neural mechanism produced it.

Before building the model, decide which body and task it is meant to describe, which recording it will receive and which independent measurement will check its answer. Set the allowed error as part of that question. A score can then tell us whether the answer was useful under those conditions. Adding a more elaborate display before defining success leaves the same unanswered question in a larger picture.

3 Movement and Feedback

Movement is usually a conversation with the world. You reach for a cup. Your hand's position changes. You see the change and feel contact. If the cup slips, you adjust. The action affects the next information you receive, and that information affects the next action.

This is a feedback loop. Feedback means information about what happened, returned to help guide what happens next. Feedback control means adjusting action in response to the difference between the target and the observed result. The established work of Todorov and Jordan helps explain movement control under uncertainty. Our proposal uses that idea as a reason to test the whole loop rather than celebrate only a command. Todorov and Jordan, 2002.

Timing matters. Information arriving after a movement has finished may still help the next attempt, but it did not correct the movement already completed. A recording played back later is not live feedback to the person who produced it. Feedback generated by a computer body is not measured feedback from a living body. Those differences should remain visible beside the result.

"Perception is subjective. Movement is not" is the programme's starting contrast. A person experiences a sensation. Other people can independently measure the body's position, trajectory and forces. That does not mean measurements are perfect, or that we can measure the private feeling directly. It means movement offers an outcome we can check without pretending to read someone's entire inner life.

If a model predicts that a finger should move five millimetres, a suitable measurement can compare its prediction with the actual movement. The error becomes information. Did the model overshoot? Did it start late? Did it choose a different finger? These questions help locate the failure and guide the next experiment. They are more useful than an unexplained claim that the model is "brain-like."

4 Accuracy and Repeatability

Imagine a ruler whose markings are wrong. Each time you measure the same object, you get almost the same answer. The measurement is repeatable, but it may be inaccurate. A computer model can have the same problem: a confident, stable answer can still disagree with the independent reference.

An accurate measurement agrees with an independent reference under declared conditions. A precise measurement repeats consistently under stated conditions. Ground truth is that independently acquired reference, together with its collection method, calibration and limits. Calling it ground truth does not make it perfect. NIST measurement terminology.

Calibration means checking how an instrument's readings relate to the quantity we want to measure. A sensor that reports values between zero and one may describe relative finger movement. Without the necessary calibration, it does not automatically tell us millimetres or a joint angle. A model can correctly predict those relative values while still leaving the physical body question unanswered.

More detail is not a shortcut around this problem. A simulation can update thousands of times a second. A display can show many decimal places. Neither proves that the underlying values match biology. Useful claims show the predicted and measured outcomes, the error, repeated results and the conditions where the comparison holds.

5 Structure and Function

A road map shows connections. It does not show today's traffic, an unexpected road closure or why a particular driver chose a turn. The map is valuable because it constrains what routes are possible. It is not a complete explanation of every journey.

A map of neural connections has a similar role. It can show which cells connect and where. It does not by itself tell us how strongly one affects another in a living subject at a particular moment. Activity depends on timing, chemicals, bodily state, past learning and the task being performed. The programme needs both structural constraints and suitable observations of function.

The Human Genome Project is a useful comparison. Reading a reference sequence did not finish the investigation of what its parts do or how they are regulated. Further research investigated functional elements. That does not mean the sequencing project failed. It means obtaining a map and explaining function are different achievements. NHGRI, Beyond Genes.

MICrONS is an important example of bringing different kinds of evidence together. Its researchers related recorded visual responses to detailed connections in a region of one mouse's brain. That helps ask how structure and observed response relate. It does not supply a complete human brain, a complete body or every nerve pathway needed to teach a new skill. MICrONS Consortium, 2025.

The map's coverage determines what we can ask of it. A map of one brain region does not cover the whole brain, and a brain map does not cover the whole nervous system. Relating an electrode to a particular cell in an atlas needs evidence that both refer to that cell in the recorded subject. The next question is therefore about the recording itself: what did the instrument observe, and what must we infer from it? A detailed map cannot answer on the instrument's behalf.

6 What Brain Measurements Record

Functional magnetic resonance imaging, usually shortened to fMRI, measures changes in a blood-related signal. It takes measurements over time. It does not directly photograph thoughts. To interpret it, researchers need an account of how neural activity, blood flow and the instrument's readings relate.

Logothetis and colleagues studied these relationships. In their experiments, the blood-related signal was more closely related to local field potentials than to spiking output. Local field potentials are an aggregate electrical measurement near a recording site; spikes are brief electrical events associated with neurons. Those are distinct quantities, and the relationship varied with the recording conditions. Logothetis et al., 2001.

Tang and colleagues showed that a system could reconstruct aspects of meaning from particular brain recordings under constrained conditions. The result depended substantially on the person and cooperation. It does not establish a universal decoder that can recover every person's private experience word for word. Tang et al., 2023.

The language-translation analogy is helpful here. Words can mean different things in different contexts; a translation may preserve some meaning while leaving ambiguity. Neural translation must likewise state what information is preserved and where the match is uncertain. The analogy does not prove that useful common representations are impossible. It prevents us from assuming a perfect one-to-one correspondence before testing it.

7 Measurement Effects and the Quantum Analogy

Sometimes observing something changes the conditions under which it behaves. A participant in a scanner may have to remain still and follow an unusual task. An implanted interface may affect tissue. Those practical interactions need to be measured and explained.

Quantum measurement can provide an analogy about observation and interaction. But an analogy is not a demonstrated brain mechanism. Individual quantum systems and large-scale neural measurements require different explanations. Quantum backaction means that a measurement changes the state of the quantum system being measured. Quarks are subatomic particles found inside protons and neutrons. We do not claim that these effects or measurements at that scale explain the limits of fMRI or the difficulty of translating subjective experience. Royal Swedish Academy, quantum measurement background.

The limits already have concrete explanations to investigate: an indirect signal, limited sampling, task constraints, differences between individuals and missing measurements. Each points toward a particular check and a reason to state uncertainty. Calling the problem "quantum" would supply none of those missing measurements or make a prediction more accurate.

8 Existing Brain–Body Interfaces

There are published examples of brain signals helping produce real movement. Bouton and colleagues recorded from motor brain tissue and used the information to control electrical activation of forearm muscles. A participant with quadriplegia, paralysis affecting all four limbs, performed useful hand and wrist actions. That is a real achievement with a defined participant and interface. It is not evidence that an unfamiliar skill was uploaded. Bouton et al., 2016.

Lorach and colleagues connected recorded brain signals to spinal stimulation in a participant with chronic spinal injury. They evaluated standing and walking in the person, and reported rehabilitation-associated improvement with the interface off. A body actually moving under a measured intervention provides a stronger functional test than a computer animation alone. The result remains tied to that person, intervention and rehabilitation history. Lorach et al., 2023.

Flesher and colleagues supplied touch-related sensations by stimulating sensory brain tissue during robotic arm control. The feedback helped the participant control the arm. This supports asking whether useful information returning toward the brain improves action. It does not show that a whole expert skill transferred from another person. Flesher et al., 2021.

The movement bridge and the return of touch give this programme two directions to investigate. They were tested in separate participants and tasks. A new combined system must therefore show how its own measurements and timing fit together, then report its outcomes and failures. Reading the papers together gives us a reason to build

that experiment; it cannot supply evidence for links that the combined experiment has not yet tested.

9 Digital-Fly Models

The digital fly makes this problem harder to dodge. A fly on screen walks; we want to know what made it walk. Was the decisive ability supplied by its connection map, the equations chosen for its neurons, a trained body controller or information added from outside? These can all be useful components. Keeping their jobs visible tells us which biological claim the result can actually test.

FlyWire mapped 139,255 neurons in one adult female fly brain. A neuron is a nerve cell; a connectome is a map of neural connections. The resource is powerful, but it also has reconstruction errors and missing information. Its chemical connections do not directly measure every physiological effect. It is not the entire nervous system, body and environment. Dorkenwald et al., 2024.

Pospisil and colleagues propose a way to use connection maps together with interventions to estimate causal effects. An intervention deliberately changes something to test what it affects. Their estimator tests use simulated conditions where the underlying answer is known by construction. Those tests do not mean the full causal dynamics of a living fly have already been measured. Pospisil et al., 2024.

Shiu and colleagues show how a useful approximation can earn evidence. They made particular predictions from a connectome-based model, then compared them with experiments involving stimulation and behaviour. Many predictions agreed. Others did not. Experimentally observed effects associated with cells called Phantom and Usnea were missed, and water-related predictions for G2N-1/Usnea disagreed with silencing tests, which reduce the activity of the targeted cells. A cell's name does not explain away a mismatch. Shiu et al., 2024.

The researchers reported agreement for 91% of 164 tested predictions, or 84% after excluding one mostly negative experimental screen. These percentages describe those predictions and that comparison. They do not say the model is 91% of a complete fly. Missing receptor dynamics, electrical connections and chemical regulation matter to the explanation, including why absolute simulated firing rates are not expected to be fully accurate.

A model earns support prediction by prediction. It can suggest a useful experiment, agree with that experiment and still fail in another condition. Reporting the limits beside the success shows both what the result supports and which further measurement could test the explanation. That is how an approximation can contribute without being mistaken for a complete animal.

10 Foot Contact and Simulation Errors

A detailed body model must solve numerical problems as well as anatomical ones. NeuroMechFly v2 reports that simulated leg tips can sit slightly below the ground be-

cause of numerical errors or physics instability. The authors used a 0.05 millimetre margin to avoid detecting a false overstretch. That is a specific contact artifact documented in the paper. Wang-Chen et al., 2024.

The reported failure is a small below-ground position and the modelling response to it. It supports a precise claim about contact in that simulator, not a claim that a FlyWire brain acquired an ability no living fly could ever perform. There is no demonstrated gross tunnelling, enormous jump or perpetual motion in this example. Naming the actual failure lets us investigate the correction instead of expanding it into an unsupported story.

The same paper models adhesion with engineered forces and defined stepping phases while the relevant biological liftoff mechanisms remained uncertain. The computer can perform a movement using that substitute. Whether the substitute reproduces the animal's mechanism is another question. An unknown part of biology does not become known because software needs a value there.

FlyBody provides another example. Its artificial controllers were trained to imitate recorded walking and flight. That can test how well a model matches those measured movements. It does not recover a FlyWire brain. The paper's time-averaged treatment of aerodynamics and its missing detailed muscle and sensory physiology remain limitations. Similar movement can be produced by different internal mechanisms. Vaxenburg et al., 2025.

11 Encoders, Controllers and Added Information

Eon's March 2026 account describes an integrated digital fly using neural and body models. The developers disclose hand-chosen brain–body mappings, substantial dependence on existing body controllers, largely missing internal state and learning mechanisms, and neural dynamics not yet validated against important biological signatures. That is evidence about the disclosed engineered system at that date. It is not proof of a complete biological upload. We have not independently reproduced its dynamics. Eon Systems, 10 March 2026.

Games make the attribution problem especially clear. In a pinned fly-chess project, inspected code supplies a symbolic description of the board, selected mathematical dynamics, a trained output reader and outside legal-move search. Those pieces can all contribute to the software's behaviour. Their contribution cannot be credited to fly wiring alone. The project's playing strength was not independently reproduced here. Pinned fly-chess trainer.

DoomFly uses a male nervous-system map, distinct from the female FlyWire brain. Its pinned code reads enemy direction and distance from game-engine geometry and supplies that information to model neurons. The authors report that the intended visual pathway failed in their tests. This is an engineered shortcut to information, not a measurement showing fly vision or a living fly learning Doom. Historical performance remains unreproduced here, with a reported checkpoint absent. Pinned DoomFly input.

A combined software system may be useful because its parts supply different capabilities. An outside planner may choose legal moves from a known board; a body controller may supply locomotion. Disclose those contributions so the reader can decide what the neural model itself explains. Combining them does not make their engineered abilities evidence about the living fly.

12 Reward and Task Performance

Once we know where the commands came from, we still have to ask what success meant. A score pays the optimizer for whatever the score measures. If finishing the task and collecting the reward come apart, the computer can get better at the latter while leaving the former undone.

An optimizer is the procedure that changes a model to improve a chosen objective. If the objective rewards the wrong thing, improvement can be misleading. CoastRunners is a documented example: an agent repeatedly circled reward targets instead of finishing the race. Its score improved while the intended outcome remained unmet. That is a problem with the reward, not proof of impossible physics. Google DeepMind, specification gaming.

Historical first-hand accounts describe a different class of failure. Simulated creatures found movement that exploited numerical errors. Some virtual soft robots penetrated the ground between updates and received corrective forces that supplied artificial energy. Their movement was impressive in the simulator but did not reveal a physically realizable mechanism. Fixing the error changed what they could do. These examples concern particular simulators, not a demonstrated FlyWire defect. Lehman et al., first-hand accounts.

For Brain2Body, the response is to measure what the task truly requires. Did the right key move, at the right time, without an extra press? Were contact forces and joint limits physically supported? Did the model receive information the real organism would lack? A high reward cannot answer all of those questions by itself.

We also need to distinguish an actual violation from an unfamiliar behaviour. A surprising movement is not automatically impossible. To make that claim, we would need an exact model version, the trajectory and interface, independently supported biological or physical bounds, and a reproducible violation. We currently have no verified evidence here that a FlyWire-derived brain performs something no living fly could ever perform.

13 Protein Structure and Biological Function

AlphaFold predicts aspects of molecular structure. A convincing shape is not the same thing as a protein shown to bind or function as intended in a living setting. The reference measurement and the tested endpoint matter. The original AlphaFold3 paper describes plausible invented structure in unstructured regions and, separately, predicted chains that overlap. Those are documented structural problems, not a reason to dismiss every output. Abramson et al., 2024.

One result makes the scope issue concrete. The paper reports 62.9% cluster-averaged success for protein–antibody interfaces at DockQ > 0.23. DockQ is a score comparing a predicted interface with an experimentally determined one; 0.23 is the declared cut-off here. The complement, 37.1%, failed that threshold. The benchmark contained 65 interface clusters drawn from 71 complexes and used confidence-based selection from 1,000 seeds with five samples per seed for each target. It does not say that 37.1% of every protein prediction fails to function. Structure and function are different questions.

Crystallization can make measurement difficult, but it is not the only method for determining structures. Cryo-electron microscopy uses electrons to study samples; nuclear magnetic resonance uses the response of atomic nuclei to magnetic conditions. Those methods have their own limitations. We should not attribute every unknown structure to difficulty making crystals. RCSB structure methods.

Generated examples can help training. AlphaFold2 used predicted structures for some unlabelled sequences to improve learning. But a generated label is not an independent biological measurement. If two models agree because one learned from the other, their agreement cannot supply the missing real-world test. Synthetic data, meaning generated rather than directly measured data, can support a hypothesis while leaving its empirical validation open. Jumper et al., 2021.

14 Independent Prediction Tests

Biological virtualization is a demanding claim: a digital model has been shown through independent measurements to reproduce specified biological behaviour and causal dynamics in a stated domain, within stated error limits. A lifelike animation, a copied connection map or a high score does not establish it.

Hallucination, in this programme's usage, means invented or ungrounded content presented as reality. If software invents a physiological mechanism and its output is presented as established biological fidelity, that is the problem. An openly disclosed approximation is different. It can be useful, testable and valid for particular outcomes.

Suppose a model gets one movement right. That success is worth recording. It does not alone establish that its internal explanation is faithful, or that it will be reliable in a new condition. The dice comparison points to uncertainty about unverified reliability. It does not mean every prediction is random or equally likely. Learned patterns can help make a prediction; its performance still needs to be evaluated.

Independent measurements and held-out tests show where a prediction works. Measured errors, failure cases and checked confidence show how much trust that result warrants. The same model may be adequate for a stated task and inadequate for a stronger biological claim; defining that boundary lets a reader use the result without inheriting claims it has not earned.

15 Recording Access, Context and Stable Signals

Can we obtain a signal that helps answer the question? “Access it” begins there: where is the recording made, what does it measure, and what changes when the tissue or subject is observed? More electrodes can enlarge the data file without supplying the missing information. The useful recording must help distinguish explanations.

An available signal then needs a relationship we can check. “Ground it” asks how it relates to independently measured body behaviour. A label saying “index finger” could mean an attempted action, a sensor, a simulated goal or an anatomical region. The actual meaning, clock and checking measurement determine which relationship is being tested; the shared words do not make the quantities interchangeable.

“Keep it” asks whether that recording and mapping stay useful over time. Tissue may respond to an interface, the recorded population may change, or calibration and task conditions may shift. A relationship that works on one date could fail on another. Repeated measurements and appropriate tests must show what remained usable.

Keeping a signal usable is not the same as keeping a learned skill. An electrode may remain stable while a learner gains no independent capability. A learner may improve while a recording becomes unreliable. Brain2Body treats these as separate outcomes because each can succeed or fail without the other.

16 Connecting Measurements Across the Body

Electrical recordings can come from different places. Electroencephalography, or EEG, uses scalp electrodes. Electrospinography, or ESG, records over the spine. Electroneurography, or ENG, records nerve electrical activity. Electromyography, or EMG, records muscle electrical activity. EMG is not direct recording from a peripheral nerve, the nerves outside the brain and spinal cord.

The same screen can show all four types. That does not make them simultaneous measurements from the same voluntary action. Different subjects, dates, tasks, instruments and clocks must remain different. Otherwise the display can suggest a chain that the evidence never recorded.

The programme’s full objective includes brain, spinal, peripheral and body relationships. Open resources from HHMI/Janelia, Allen, Harvard and other groups can support different parts of that work. Structural maps, activity recordings and movement observations have different roles. A wide search does not mean every necessary link has been acquired or paired.

When a link is missing, a model may predict it. That prediction could be worth testing. It stays a prediction until an appropriate independent observation checks it. Putting a predicted spinal signal between measured cortex and measured movement cannot silently turn the middle of the chain into measured physiology.

17 Simulation-Based Error Analysis

MyoSuite provides research simulations where muscles produce movement and objects can make contact. That makes it useful for asking how commands lead to physical outcomes. The tool's existence does not make every simulated hand an accurate copy of the recorded person's hand. Caggiano et al., 2022.

Think of four steps. A translator predicts a limited goal from a recording. A controller chooses muscle commands. The body model determines the resulting movement and contact. The task rules score the outcome. Keeping the steps visible lets us see where a failure began.

If the translator chooses the middle finger when the label was index finger, a competent controller may press beautifully with the middle finger. The controller executed its command. The complete task still failed. If the predicted finger is correct but no contact occurs, the controller or body model may be responsible. Those explanations lead to different next tests.

A direct animation can hide the distinction. Setting a joint to the desired angle is a way to display a pose, but it bypasses the problem of choosing muscle commands that produce it. If the research claim concerns muscle-driven control, the movement must come from the tested controls, and its physical state must be traceable.

NeuroTranslator is the programme's name for software joining particular recordings, predictions, replay and computer-body checks. NeuroTranslation Network is a proposed design for joining more components while preserving the origin and meaning of their values. The names describe software and a plan. They do not mean every nerve pathway has been measured.

18 The Six-Session Macaque Study

The current development study uses six recordings from one macaque: four training dates and two development-validation dates. Training material is used to adjust a model. Development validation helps examine or select a method during development. It is different from untouched material reserved for independent confirmation.

Ninety-six contacts in the source's HandM1 motor-cortex region supply two kinds of measurement. Threshold-crossing-rate features count detected signal crossings under the recording method. Spiking-band-power features describe signal power in an archived frequency band. Their short labels are TCR and SBP. Together they give 192 features from 96 contacts, not 192 separately located electrodes.

The targets are two source-normalized finger-sensor groups. One represents index-finger movement; the other combines middle, ring and small fingers. "Source-normalized" means the source values have been scaled under the declared processing. These values are not a complete set of finger joint angles, forces or body positions in physical units.

This is a bounded hand-mapping study. It does not establish a whole-body neural translator, transfer across species or a way to teach a living nervous system. Those

larger aims remain. They have not become achievements because the smaller study has finished its training runs. Programme computational evidence summary.

19 Current Study: Neither Model Passed

Eighteen runs saved a total of 720 epochs. An epoch is a pass through the training material. Finishing that work is an execution result. It does not tell us whether the model met the performance rules.

Both candidates use a gated recurrent unit, usually shortened to GRU. This sequence model can retain information from earlier inputs. The comparison includes a ridge model, a simpler predictor whose training discourages overly large fitted coefficients, the weights assigned to inputs. The question is whether the more elaborate method contributes a benefit under the same rules; its name cannot answer that comparison.

Both GRU model gates FAIL. They fail the original requirements concerning no harm and useful neural information. All five separate claims about history, order use and extra-task benefit also FAIL their required combinations of conditions. Some aggregate error reductions do not cancel failures elsewhere. If the rule requires every part to pass, a better average cannot rewrite it.

The negative report documents that these methods failed their rules. That result does not establish that either method is effective. It changes the next decision: neither candidate can be treated as the qualified predictor on which a teaching claim rests. The failures give the next experiment something specific to explain; an average improvement cannot make those conditions disappear. Programme computational evidence summary.

20 Next Experiments

We are still short of a qualified predictor, before asking it to teach anyone. The failed comparison leaves Brain2Body's learning question open. Its measurements cover only two normalized finger-sensor groups, without calibrated joint angles, forces or a complete body state, and neither recurrent candidate has been admitted. We can propose a constrained controller by stating what it observes, which actions it may issue and what feedback it receives. If we give it the desired goal, we must report that supplied help when interpreting the result. Otherwise we could credit the predictor for an answer we handed to the controller.

The next comparison starts with the grasp itself. Before asking whether a model has read the right brain signal, we can ask whether learning movement patterns helps it predict another person's movement. The proposed development study uses qualified movement recordings from two people. One supplies source movement; the other supplies target training and development observations. It has not been run.

Give the model three different beginnings. First, let it practise on the target person's training movement. Second, let it practise on the source person's movement with the body features put in deliberately incorrect correspondence. Third, use the proposed

correspondence between those source and target features. Keep the architecture, random starting conditions, number of fitting updates, later target-training examples and final-checkpoint rule matched. The wrong-mapping comparison asks whether a useful correspondence matters; the target-only comparison asks whether borrowing another person's movement helps at all. Neither comparison assumes transfer will succeed.

The proposed representation follows sensors at the wrist, index finger, thumb and object. Each position relative to the wrist has three coordinate components. The index, thumb and object positions therefore supply nine values; the distance between the two digit sensors adds one. Three components of wrist velocity complete the thirteen movement values. The wrist frame must be separately qualified, so its orientation is known. Wrist velocity describes the wrist's movement through the world, expressed in that frame. Its estimate must use only observations available at the current moment or earlier, never a later observation. That is what causal means here.

A characteristic sensor-distance scale separates size from shape. Fit it only on each person's training observations, then hold it fixed: development observations must not help choose it. This scale is not a measurement of bone length. Divide each position or digit-separation value by that length. For a velocity component, first multiply metres per second by the same one-tenth-second reference interval, then divide by the length in metres. The units cancel, leaving dimensionless features that put the two people's measurements on a common numerical scale. The reference interval does not change the recording's timing or establish that the bodies have identical dynamics. Physical errors would still need reporting in their qualified original units.

Each of the thirteen input features also carries a flag saying whether it was observed. That lets the model distinguish a missing value from a genuine observed zero. Future outcomes have their own observation flags for scoring: a missing target must not be counted as a measured zero, and a batch with no observed targets cannot supply the defined training loss. These future-target flags are not extra information for the prediction input. The units, sensor calibration, clocks and gaps remain questions to resolve before using the recordings.

The wider programme can compare both corresponding anatomical features and different features that perform roughly similar mechanical jobs. This two-person study tests one human sensor-landmark correspondence. It does not test whether different species have equivalent neural channels. Learning a movement constraint from another recording also does not turn that recording into a brain signal measured alongside the target person's action. A scan may help constrain anatomy where it fills a stated gap. A scan from elsewhere, or movement generated by a simulation, cannot provide the missing simultaneous brain measurement.

Keep recordings from the same acquisition, their overlapping pieces and their derivatives together when assigning roles, before making windows or calculating training statistics. Fit the size scales on training observations alone. Development observations can help assess this declared comparison; they cannot quietly become a final independent confirmation. Later neural adaptation would need real paired observations, the correct causal timing and its original input-specific controls. The protected recordings stay protected. Movement pretraining is a proposed intermediate test, not another successful result or evidence that a nervous system has learned a skill.

To test teaching, compare experienced, inexperienced and artificial tutors under matched conditions: the same task information, practice, assistance budgets and relevant burden. The interfaces would first need support from evidence. Include sham, delayed and unrelated-feedback controls with their designs and information access stated. Those comparisons could help test the contributions of useful information, timing and added input; their interpretation depends on the actual design. Better performance while the tutor is present would still leave the retained-learning question unanswered.

Then stop the tutor's information while keeping practice, feedback, task access and any necessary movement bridge constant. Measure performance later and on unfamiliar variations against matched controls, and record the help that remains. A gain that disappears after teaching stops counts against retained learning. A gain that survives needs its own limits established; it cannot by itself show tissue repair, a restored pathway or regeneration, which require separate biological measurements.

21 Independent Verification

Training software calculates how to change a model. Automatic differentiation computes derivatives, information describing how a change would affect a calculation. Adam is an update method that uses derivative information and stored state to adjust model parameters. Both training candidates rely on common Torch machinery for parts of these calculations.

Agreement between two routes using the same machinery cannot independently certify the shared machinery itself. This does not prove the machinery is wrong. It defines what the agreement has and has not checked. A stronger verification route needs independent calculations and complete state evidence appropriate to the actual training interface.

Reopening a saved model leaves a further question: can its complete state be recovered, and do subsequent updates match the saved training trajectory? Evidence for complete model and optimizer state, random-number-generator state, reload and the training trajectory remains unverified. A random-number generator supplies the numbers used for declared stochastic choices, so its state matters to that comparison too. Full independent NumPy calculation also remains unverified; NumPy is a separate numerical software library that would provide another route for checking the calculation.

Continuing training would require independent checkpoint and update evidence; the current record does not establish a verified continuation. No new fit, optimizer execution, reserved-test evaluation, accepted model or full-training GPU promotion is claimed here. All four reserved dates remain CLOSED. A GPU is a graphics processor that can also perform some computation; using one does not prove better scientific results or faster complete training. Current evidence and limits.

22 Human Finger-Intent Classification

An earlier human study used recorded finger attempts. After adjustment using the first 50 labelled examples from each recording session, the selected classifier correctly identified 116 of 150 later trials. A classifier predicts a category; calibration here means adjustment using those early session labels. The support from calibration is part of the result, not something to omit from its description.

The later keyboard replay asks what happened when those predictions reached a simulated hand. Forty-one of 60 source-labelled right-finger trials produced the intended key contact. The controller executed all 54 supported commands that were actually issued. Thirteen presses were unintended or mistimed. These counts describe different questions and different denominators.

It helps to imagine a delivery service. It might deliver every parcel to the address it was given. If some addresses were wrong, that excellent delivery score would not mean every parcel reached the intended person. Similarly, 54 of 54 command executions does not erase wrong or mistimed commands before they reached the hand.

The recordings did not measure matching piano performance, spinal activity or peripheral nerve activity. The hand model was generic, and only four right-hand finger classes had supported key actions. The predictor waited for its recording window to complete; its earliest answer came one second after the cue plus computation time. That is not an instantaneous live readout.

These inspected later trials cannot remain fresh confirmation if future tuning uses them. Their scientific role changes when their answers help development. The earlier 116/150, 41/60 and 54/54 results must remain separate from the current macaque study and its failed benefit gates. Programme computational evidence summary.

23 Simulated Keyboard Learning

A separate simulated hand policy completed 32 of 32 scored phrase cases in its constrained task. These were eight reserved simulated orders tested at two tempos and two poses, not 32 independent people or animals. It used a generic four-key hand whose wrist, thumb and sideways finger motion remained braced. It received requested keys, phase, duration and fixed smooth fingertip goals. Those are supplied task resources. Human neural clips shown alongside it did not drive the hand.

The record retains an interrupted original evaluator and a completed independent replay check; the tests were not reopened. It also discloses that soft simulated key limits can be exceeded in actual simulated travel. The display does not clamp a pose to hide that difference. A scored task result does not remove the need for physical and anatomical reference checks.

A current saved development replay has 336 frames with a 20 millisecond control interval. Its reported task results include 22 of 22 correct strikes, six of six chords, 22 of 22 timely releases, a worst timing error of 34 milliseconds and no extra strikes. A chord

means keys pressed together. These figures describe the saved simulated example under its stated conditions.

They do not establish that a neural policy learned to play music, that a human acquired a skill or that a macaque's brain drove the animation. A policy is the rule or model choosing actions; here the interface gives it explicit goals. The software can be useful while that biological inference remains unsupported.

The separate human EEG, ESG, ENG and EMG clips also do not drive a combined macaque/human arm simulation. Actual joint and force ground truth and physical unit calibration remain gaps. A normalized finger-sensor target is not a simulated joint angle, and neither becomes measured neural tissue merely because it appears in the same three-dimensional scene. Programme computational evidence summary.

24 Failure Analysis

Saved failures can tell us where to look next. In one reported index-finger comparison, a decoder with an extra neural-prediction task had more error than the simpler baseline. The comparison uses mean squared error: take each prediction's difference from its target, square it, then average those squared differences. Much of the excess was associated with an average offset; a smaller part came from variation around that average. An offset means predictions tended to sit too high or too low relative to the target. Locating that pattern gives us a question to investigate, not a diagnosis by itself.

That description does not uniquely establish the cause. Different trials, changed recordings, calibration differences or genuinely different states could contribute. If we use the validation answers to shift the predictions afterward, we have learned from those answers. We cannot then call the adjusted result an untouched test under the original rule.

Training-only summaries examine variation within trials, between trials and between dates. A frame is a time-indexed observation. Overlapping frames share information and are not independent new subjects. Counting many of them does not remove the need to consider dependence when interpreting uncertainty.

Named scalar arithmetic has limited independent checks, with a rejected skewness calculation preserved and a corrected calculation checked. Skewness describes asymmetry in a distribution of values. Correcting that arithmetic supports the stated summary, not a claim that a new decoder works or that neural drift has been causally established.

The proposed context branch would add a small model component using earlier neural information. It has not been fitted. Choosing or normalizing that component from the validation answers would make it another use of those answers, so any next fit needs admitted training-only material, appropriate controls and independent state/update checks. The proposal remains a candidate change to test, not evidence that the failed model has been fixed. Current evidence and limits.

25 Current Viewer and Source Identity

A graphical user interface, or GUI, is the on-screen system people use to inspect and control software. For this programme, its scientific job is to make the evidence easier to understand. It should show measured data, predictions, simulation and missing values as different kinds of information.

Saved replay is valuable. A reader can pause, move to a later moment or inspect one frame. But the replay must retain its original source-time clock and full-run metrics. A slider at the start should not pretend that a recorded event happened at some new scientific time. A striking frame should not replace the complete task result.

Cache-only playback means loading an explicitly identified saved result without quietly running a new experiment. If the selected replay is absent, the interface should show that absence. If its source fails, it should clear the old replay and geometry. Otherwise a stale successful picture may be mistaken for a current result.

Natural-language goals can make the interface approachable. “Press this sequence” can become an explicit task specification with timing and permitted actions. But sending files to an AI chat is not the same as giving that system an execution environment. The interface must state whether it is reading context, predicting, controlling or simply displaying saved evidence.

26 Application Performance

The latest software candidate reduces its single HTML file from 113,298,857 to 34,295,597 bytes by moving opaque resources into the package. HTML is a source format for web pages; the bytes are file size. The moved resources still need to be delivered as part of the whole online directory.

This is a static packaging change. It does not demonstrate reduced startup time, lower memory use, fewer crashes or a GPU gain. Those require matched measurements of the complete useful application and its behaviour. A file-size number cannot supply an unmeasured performance result.

The candidate’s browser verification was unavailable, and it remains unpromoted. A separately compiled original-source offline export is a different artifact from the online candidate. It cannot be used as proof that the candidate’s whole interactive system works disconnected.

Offline also has a concrete limit: research views depending on the application programming interface, or API, are unavailable without that service. An API is a way software requests information or work from another component. Earlier bounded playback checks leave the current whole interface, disconnected use, anatomy and function unverified. Current evidence and limits.

27 Anatomical Reference Tests

The viewer can help us find a missed contact only if its own body has been checked. Every visual model needs a series of real-world references: one appealing image cannot establish all proportions, surfaces or relationships. Bones, muscles, joints, neural routes and contact should be checked where they are claimed. The parts and the assembled scene both need review. Otherwise a convincing display could hide an anatomical error while inviting us to diagnose the learner.

The target is a tangible, lifelike three-dimensional model. Transparent layers can reveal a muscle over a bone. A cross-section can show a route that would otherwise be hidden. Paired views can clarify the front and back. Biological identification colours, useful close-ups and tilted orthogonal views should clarify the relationships. An orthogonal view looks along a defined right-angle axis; tilting the scene can retain that relationship while revealing depth. Illustrative signal paths should be distinguishable from actual tissue. Each choice should explain something real, rather than disguise uncertain anatomy with visual detail.

A template brain and an atlas are reference tools. They are not automatically registered to the recorded subject. Registration means relating measurements to the same individual's anatomy under a checked procedure. A region coloured on a template is not proof that we measured its neurons or know their function.

The source reconstruction matches the named template geometry and atlas values. Its optional region boundary still has documented mesh defects. These checks establish that particular correspondence, not full biological or visual acceptance. The retained historical conceptual figure explains an earlier framework. It neither proves current scientific acceptance nor reverses the present model failures.

28 Time Alignment

The proposed hand–arm task would use synchronized left and right tripod views. A motion-capture relay-composite is the programme's proposed method for aligning or stitching such views. Its purpose is to make a movement easier to observe when one viewpoint hides part of the body. It is not yet a demonstrated universal reconstruction method.

Imagine one camera sees the fingers while another sees the underside of the hand. The cameras need calibration and a checked relationship between their times. If they capture different moments, an assembled pose may never have existed. Occlusion, something blocking the view, can still leave important surfaces or contacts unknown.

LiDAR uses light to measure distance. A perpendicular view may help measure a particular surface, depending on the object and instrument. It does not guarantee access to every surface, reveal neural signals or solve registration by itself. The acquisition method should be compared with suitable independent references.

The joined view has to be checked against a series of independent real-world references, with its source clock, physical units and uncertainty preserved. Those checks tell us whether the acquisition method reconstructed the measured movement under

the tested conditions. A better view can help us ask that question while leaving hidden tissue and missing observations unresolved.

29 Selecting the Next Skill Test

Four keys are a useful beginning because selection, contact, timing and release can be scored. They are a small part of playing an instrument. Musical skill also involves richer timing, coordination, posture, sound and interpretation. Passing a four-key task cannot honestly become “piano mastery.”

Threading a flexible strand through a hole tests a different missing capability: shape, friction, contact and small corrections. A puzzle requires object-state tracking and coordinated grasping. Archery requires forces and control across more of the body. Breakdancing adds balance, whole-body movement and impacts. The current finger study does not contain all of these measurements.

The appropriate next task should expose a weakness that the model can physically express and the current evidence does not make trivial. We should reserve new objects, starting positions, action sequences and recordings before choosing the learner. A controller given the correct answer directly is a useful privileged comparison, but it is not a neural model that predicted that answer.

Simple alternatives must get a fair comparison. They need comparable task information, practice and evaluation. A complicated system should show why it is needed. Report complete-task success, extra actions, misses and delays; do not choose only the clip in which the movement looked convincing.

Maze comparisons can test orientation and memory. Right-angle and non-right-angle routes have different demands, but a harder-looking maze does not automatically mean ten times the difficulty. Difficulty needs a declared measure and comparable conditions. Biological learning times cannot be inferred from how quickly a computer finishes its training.

30 Body and Species Differences

A hand, a paw and a four-legged body have different proportions and available movements. A useful common description might be “reach this target,” “maintain contact” or “release before the next step.” That lets us compare task relationships without pretending the muscles or neural channels are identical.

Think of tailoring a pattern to different bodies. A shared pattern may be adaptable, but averaging two bodies does not guarantee a garment that fits either. The programme should preserve each organism’s anatomy and test the adapted mapping against that organism’s mechanics.

Physical size, computational detail and statistical grouping are separate. A tiny animal can have a highly detailed model. A large body can have a coarse one. Averaging errors over several dates can hide a failure on one date. The word “micro” cannot safely stand for all three at once.

Cross-species transfer is therefore a research question. Which relationship survived? Which required adjustment? Which failed? If no shared mapping works, a set of useful source-specific systems may still be an honest result. The current macaque hand mapping does not demonstrate biological teaching across species.

31 Developmental Stages

The native-development branch studies an organism developing with its own tissue. A body and its nervous system change as they mature. That may change recording access, what movements are possible and how a mapping should be tested. It does not make young tissue an automatic solution to learning, healing and interface stability.

Cook and colleagues documented postnatal development in the fat-tailed dunnart, including different developmental rates across body parts. These observations are species-specific. They do not establish the same timing in antechinus or prove a safe neonatal neural interface. Cook et al., 2021.

Armstrong and Ferguson studied skin-wound healing in young *Monodelphis domestica*, an opossum. The transition in scarring is evidence about skin, age and that species. It does not demonstrate scar-free neural recording, spinal repair or lifelong stability of implanted electrodes. Dunnarts, antechinus and these opossums must not be silently treated as the same animal. Armstrong and Ferguson, 1995.

Artificial rearing and altered development would raise further questions requiring separate evidence. Neither has been demonstrated as a requirement for useful Neuro-Translation. Ordinary recordings and simulations can already test limited questions, so those questions can proceed while the developmental proposals remain unresolved.

32 Proposed Twin Comparisons

The proposed programme includes identical twins, non-identical twins and unrelated comparisons. Those categories offer different ways to investigate variation. They do not prove that two nervous systems use interchangeable channels or that a skill can be copied between them.

Even closely related learners have different experiences, physiological states and electrode placements. To compare them, the experiment would need matched tasks, developmental stages, body measurements and acquisition conditions. A difference in performance might reflect practice or recording quality rather than the relationship being tested.

The twins model must be tangible. It should show where recording, feedback and body access would occur, with each component and the assembled scene reviewed against a series of real references. A picture of linked learners explains a proposed comparison; it does not show that the experiment has happened. The measurements would determine whether a mapping actually transfers.

The useful question is which sources of variation can be controlled and which remain. If a mapping transfers only after substantial new calibration, that requirement is part of the result. Similar genetics does not supply the missing functional evidence.

33 Humanized Models

Revah and colleagues studied human cortical organoids transplanted into rats. Organoids are small laboratory-grown tissue structures representing some aspects of the brain's outer layer. The grafted tissue matured and integrated with host circuits under the study's conditions. That supports defined questions about tissue and host interaction. Revah et al., 2022.

It does not make the rat's whole nervous system human. It does not transplant an expert's skills or establish repair of a complete brain-to-body pathway. The tissue, host species, developmental setting and intervention remain essential to understanding the result.

The paper has a later correction concerning a duplicated image panel. That correction is retained in the citation record; it is not a retraction or evidence for stronger abilities. If the original figure is used, its corrected version matters. Author correction, 2026.

Brain2Body keeps native development, defined human-cell contributions, mixed-species tissue and graft interactions as distinct proposed branches. Each should ask what a particular contribution changes and how that change can be measured. Combining impressive labels does not establish a faithful human model.

34 Disease, Compensation and Repair

An injury may interrupt an output route even when the learner can still make useful neural decisions. A compensatory bridge could help express those decisions as movement. Another condition may change sensory input, muscle function or learning itself. The same intervention cannot be assumed to solve all of them.

The condition determines the experiment. Identify the impaired function, what the interface receives and changes, and the physical outcome that would count as a benefit. A result in one condition cannot settle another when its cause or remaining pathways differ. The interface has to answer the question posed by that particular impairment.

Temporary assistance means useful help while it is supplied. Retained learning means a performance gain persists after the relevant teaching help ends. Tissue repair means a biological restoration claim, requiring its own biological evidence. A person moving better through a compensatory interface does not by itself demonstrate that damaged tissue regrew.

These distinctions matter because several outcomes can be valuable. Assistance may improve daily function without teaching a new independent skill. Retained learning may occur while a movement bridge remains necessary. Repair might have to be tested with different measurements entirely. The current computational work demonstrates none of these biological branches.

35 Biological Tutor Tests

Brain2Brain is the programme's label for specified information links between nervous systems. Pais-Vieira and colleagues connected recorded activity and stimulation to share task-relevant information between trained rats. The animals had learned task elements beforehand. Their bounded choices do not show an untrained animal instantly acquiring another's complex skills. Pais-Vieira et al., 2013.

A proposed tutor study would compare an experienced partner with an inexperienced partner. Both conditions would need comparable practice opportunities. If either partner gives the same benefit, expertise may not be the important ingredient. General guidance, additional exposure or the mere presence of feedback may explain the result.

Sham guidance would supply input without the intended useful information. Delayed guidance would test whether timing matters. Matched feedback unrelated to the learner's current need would help separate the amount of input from its informative relationship to the task. A simple machine controller would provide another comparison.

The study would record what guidance was supplied and what the pupil actually did. Independent scoring and appropriate assignment of conditions would reduce the risk of choosing only favourable trials. These are proposed controls, not experiments already completed. The outcome could be no advantage, useful assistance or a retained benefit in a limited domain.

36 Artificial Tutor Tests

An artificial tutor is a computer model proposed to supply useful guidance. It may learn from measured examples or use a supported task model. Its existence does not mean it can teach a living nervous system. The interface and the information it receives are part of the claim.

Suppose one tutor sees only the learner's current neural recording, while another is given the correct next action. Their scores cannot be compared as though they solved the same prediction problem. A desired goal, an expert trajectory, a correct label and measured sensory feedback are different resources. All should be disclosed.

A fair study would compare the artificial tutor with simpler alternatives and the biological tutor, matching task information and practice where the question requires it. It would measure the burden of receiving the guidance as well. A direct neural route adds complexity; a useful outcome must justify that complexity under the comparison, rather than the comparison assuming it will help.

An artificial tutor may help while remaining active. That would be assistance, which can be useful. The stronger learning claim asks whether the nervous system becomes more capable without tutor commands. We cannot get that answer from a computer policy succeeding in its own simulated task.

37 Tutor-Withdrawal Tests

This is the key experiment. Stop the tutor's commands, then test what remains. But hold any necessary compensatory movement bridge constant. If the learner has an interrupted output pathway, removing the bridge could stop movement even if learning had occurred.

Imagine teaching someone to type through an interface that lets their intentions reach a hand. Disconnecting both the teaching help and the hand interface would mix two questions: did the learner retain the skill, and could they still express movement? The test would no longer distinguish them.

The baseline and retention test need comparable access to movement, task conditions and feedback. Record any help that remains. Compare immediate performance, later performance and unfamiliar variations. Improved performance only while the tutor operates is assistance. Improved performance without tutor information needs further checks before calling it retained learning.

If the gain survives, report where it survives and the uncertainty. If it disappears, report that. Tissue repair is still another claim with different evidence. Holding the bridge constant does not prove repair; it makes the learning question interpretable.

38 Networks and Skill Transfer

BrainNet is a metaphor for specified connections between neural systems. It does not name an operating network through which people can buy biological expertise. The programme's motivation includes broad enablement and possible future skill services, but neither is a demonstrated product outcome.

Useful access, ownership of biological information, deployability and commercial services are different questions. A conceptual article cannot decide all of them from a simulated hand. Nor does a bold name establish that the proposal is unique, universally superior or the fastest possible route to learning.

To test a proposed skill gain, follow what the interface observes, the guidance it supplies, the performance that improves and the help that remains. An experiment must be able to reject the explanation. That inspectable research direction is what the current proposal offers; the evidence has not delivered the broader ability yet.

39 From a reach to a testable model

Start with a movement we can measure well. For the proposed snap showcase, the arm begins extended with the palm down. The elbow and forearm swing and turn; the wrist and hand turn upward during the snap, then move down to rest. The model must account for that whole movement, including the preparation, contact and return. Finger pairing, organism-specific anatomy and timing still need a real-reference series; a human-looking animation cannot establish that a particular monkey can perform the same gesture.

The cup reach supplies a simpler precision comparison: relate recorded signals to measured movement before attempting the coordinated snap. Each task still needs its own anatomy, contact, timing and independent comparison.

That comparison connects three interacting groups: task-linked brain observations, named-muscle observations and a musculoskeletal simulation. A learner would relate the observations to the mechanics; independent movement and contact measurements would test its predictions. EEG records scalp electrical activity and surface EMG records muscle electrical activity. A separately recorded nerve or spinal signal needs its own declared channel. The proposed apparatus uses two arm sleeves, scalp EEG and synchronized, calibrated left and right tripod views. Vendor, channel, bandwidth and clock qualification remain open.

Intent to action is the target. By understanding and measuring the intermediary, we aim to make that mapping as close to one-to-one as possible within a declared task. Specify what counts as the intended action, the participant and session, state and context, permitted history, tolerated error and independent reference. The test then asks whether observing the middle reduces ambiguity and improves prediction or qualified control. It does not assume a unique hidden intention or claim that the best possible mapping has already been achieved.

The proposed learner must explain the recorded brain and muscle activity, where the hand moved and when. These are proposed comparisons: no paired trial, trained model, data acquisition, fine-tuning, reinforcement-learning rollout or accepted checkpoint is established for this EEG/EMG/movement loop. Its sources and permissions, physical and computational behaviour, clinical interfaces, reference comparisons and held-out tests still need independent assessment.

The completed LINK comparison supplies a warning about what would count as success. Its 18 runs and 720 saved epochs tested a different question; both model-admission gates and all five benefit claims failed. Neither those runs nor a future successful prediction would show that a learner received sensation or produced an action. Recording, prediction, simulated movement, sensory delivery and physical action each need evidence of their own. EEG and EMG recorders alone cannot write sensation, and no sensory delivery or physical actuation is established for this proposal.

39.1 Form, function and action need a measured middle

A structural map constrains what a system could do. A NeuroConnectome maps specified neural connections; its organism, coverage, resolution and source would have to be declared. Following the reach through that map also requires the signals and the processes that turn those constraints into an outcome. Signals must remain identified as observed or inferred. This is why the proposed programme follows form to function to action: understanding and measuring the middle could improve the intent-to-action mapping for the declared task.

The molecular comparison asks the same question about a different mechanism. DNA to RNA and RNA to protein put a process between a starting constraint and its downstream product. Regulatory context, RNA processing and cell state change what

that process produces; protein structure alone does not determine the behaviour of a whole cell. AlphaGenome, RNA or cell-state models and AlphaFold illustrate these different modelling jobs. AlphaTranscriptome names a desired predictive capability here. Connecting the predictors would still leave system dynamics and the environment to account for, with experimental outcomes needed to test the combined prediction.

AlphaGenome regulatory prediction [1]; scGPT cell-state modelling [2]; AlphaFold 3 structure prediction [3]. These examples support the comparison of modelling roles only. The complete AlphaGenome and scGPT methods have not been independently assessed here, and the examples provide no evidence of an integrated cell programmer.

For the reach, the corresponding biological question is what happens between brain activity and the body's response. Brain2Spine and Spine2Body name the proposed links to test; their composition is the Brain2Body aim. The spinal cord integrates descending and sensory signals and contributes local coordination, reflex regulation and adaptation. RNA processing is a different mechanism; the shared question is how a context-dependent process changes an initial constraint into an outcome. Supported spinal observations would test that account. Where they are absent, internal states remain inferred or simulated. Physical spinal work remains read-only.

Spinal sensorimotor adaptation [4] offers a constrained example of that processing. It validates neither our proposed pathway nor unrestricted skill transfer. We draw on the abstract and relevant author-manuscript passages; equivalence to the final published edition and the complete methods and statistics remain unverified here.

Follow the action one step further and the question changes: what did it do to the task environment? Thought2Action relates a declared intention to an independently measured action. Action2World follows the action to its consequence in that environment; Thought2World names the proposed composition. The earlier Body2World label drew attention to the consequence outside the body. Body2Action focuses on body mechanics and a specified task outcome, while Brain2Motion focuses on the movement pathway. Each working label identifies a related scope for a test; the labels establish neither interchangeable nor working controllers.

The engineering route would bring these observations and comparisons into a learner: neural activity to musculoskeletal simulation to a programmable model, toward NeuroTranslation. The proposed movement-focused learner is a large movement model. It would perform the declared prediction or control. System 3 thinking names the proposed human–AI supervisory partnership around it: a supervisory model would compare task strategies, diagnose where neural or mechanical predictions miss independent measurements, and propose training or calibration comparisons for the signal mapping and virtual body. The learner would answer the task; the supervisor would help choose what to test next. Neither replaces the biological spinal intermediary or a physical interface. Final held-out outcomes must remain outside rewards and model selection.

Shaw and Nave's SSRN preprint, *Thinking—Fast, Slow, and Artificial*, and its institutional discussion provide conceptual context for this proposed human–AI role. [5] We use that framing only; the complete preprint and institutional article have not been reviewed here. Neither establishes a third anatomical brain system or validates the proposed learner or supervisor. Expert footage may supply movement and tactical exam-

ples, with rights and camera uncertainty accounted for; it supplies no measured expert EEG, EMG, muscle force or stimulation plan.

The outcome then supplies the next question for the learner and its supervisor. Action changes what happens; its sensory consequences inform perception and the next intention. Independently measured movement would anchor the action part of that loop, while known stimuli, measured feedback and appropriate recordings or reports would have to test the further sensory mappings. Movement alone would not decode a unique sensation or perception. The return path must be measured rather than drawn into existence. The full Interoceptomics aim includes internal-body sensing and connectivity; external touch and proprioceptive tasks contribute evidence but do not by themselves solve that wider problem. A prediction, assisted execution and retained skill without assistance answer different questions. Each wider claim must earn its own independent comparison.

39.2 Context connects. Grounding checks

Within a reach, context has a concrete job: relate brain activity to muscle activity in this task and at this time. Attention is one proposed way to represent those relationships. The model compares a representation called a query with representations called keys, then uses the resulting weights to combine their values. Masks keep unavailable observations and future samples out. The calculation weights information; it does not establish that attention understands all context.

Vaswani et al. (2017) [6]; Tsai et al. (2019) [7]. These methods motivate the computation; validation of the proposed paired system still requires the independent observations below.

A pattern can fit inside the model and still describe the wrong movement. Grounding therefore means testing the declared prediction against qualified observations under the same conditions. Independently measured movement would check the outcome, while muscle activity would add an observation that constrains the brain model. Even a matching reach cannot identify a unique private experience. The proposed paired trial would have to show which of these observations adds useful information.

39.3 Muscle activity tests the brain model

Record brain and named-muscle activity during the same reach. In the proposed paired trial, EEG would sample scalp electrical activity and surface EMG would sample activity associated with the named muscles. Paired training could use the muscle observation to constrain their relationship. Then withhold the muscle target and movement reference from the EEG-only predictor: can the permitted brain observations predict a specified muscle-activity observable or movement?

Pairing and calibration remain proposed. Shared cues and movement artefacts could give that predictor a shortcut, so the comparison needs controls for both. The muscle observations would cover only the named muscles, and EMG supplies neither afferent nerve activity nor direct force. Sensory claims still need known stimuli and measured feedback. Several neural states could remain compatible with even a well-matched

pair; the pair could narrow a task-specific explanation without revealing the complete hidden brain. Checking the movement itself requires the next independent observation.

This proposed pairing still needs supporting evidence. The candidate reference at https://www.nature.com/articles/sdata2018133 has not yet been checked for exact support or reuse rights.

39.4 Measured motion tests the virtual body

Measure the same hand and arm from the aligned left and right tripod views. The proposed motion-capture relay-composite would align the two point maps in a common clock and coordinate frame, then join them into one composite while retaining each point's origin. Before that joined map can check a prediction, its calibration, alignment and capture precision would have to be independently verified.

The movement map would constrain the external movement model: surface motion and pose in the task's physical frame. To explain that motion mechanically, the internal musculoskeletal model would describe specified bones, joints and soft tissues. Organism, developmental stage and task would determine the appropriate anatomical sources. X-ray projections could inform bone and joint relationships; appropriate MRI references could inform specified soft tissues. Registration, rights and source-specific limits would need independent checks. No scan set is selected for this proposed comparison. Anatomy still leaves activation, forces and neural function to test.

With a qualified composite, the musculoskeletal-simulation physics-engine's joints, muscles, contacts and physical limits would face a measured comparison. Fit the model on training data, then compare its predicted reach with held-out measured movement. A force claim would require an additional force measurement. The body's form limits possible motion; measured function would test the mechanics and show where they need refinement.

Seth et al. (2018) [8]; MyoSuite documentation [9]. The simulation tools supply methods for that comparison; the proposed capture and body models still require independent validation.

A lifelike hand could expose a missed contact or a late reach. The comparison still needs independent capture alignment, precision, mechanics and biological fidelity; none has been demonstrated for this proposal. Captured geometry cannot establish hidden neural state, internal forces or unique subjective experience. It would check the declared movement prediction within those limits.

39.5 Two pairs. One conditional learner

The learner would have two connected jobs: relate EEG observations to muscle activity, and relate measured movement to predicted mechanics. Large movement model names the proposed family; deep neural network describes a possible implementation. Large refers to intended scope, not a demonstrated parameter count. Encoders would accept only observations permitted for the named test. Two branches would summa-

rize those relationships in a shared task representation, with separate output parts for each direction's targets.

Vaswani et al. (2017) [6]; Tsai et al. (2019) [7]. These computational methods offer precedents for a design, leaving the proposed paired learner and its performance to be tested.

Signal features belong to branches, and branches belong to the learner. That hierarchy describes the computation, not two anatomical thinking systems. A common clock, task and physical frame would connect the branches; independent measurements would check their errors. Form constrains the prediction, and checked function would guide refinement. Several hidden states could still fit the same reach, so neither a shared representation nor conditional predictions would establish an exact inverse nervous system. The architecture has not been selected, implemented, trained or independently accepted. To choose it, we would have to compare it with simpler baselines on appropriately reserved observations.

39.6 Learn the movement, then test what transfers

A recording of a reach already contains a possible lesson for a computer: use the earlier movement to predict where the hand goes next. It need not contain EEG to pose that question. A separate proposed comparison would ask whether learning from one person's grasp-and-lift movement helps predict another person's movement. The WAY-EEG-GAL description identifies continuous recordings of lifting series as well as separate windowed trials and lift-summary tables.[10] The continuous movement could supply both the history and the later checking observation. It would not require matching AllLifts Run or trial rows, and it would create no measured neural pair between the two people. The original study of five complete weight series remains a different design.

To transfer anything useful, we must say what corresponds. Homologous structures share an evolutionary anatomical origin. Mechanically analogous structures can perform a comparable job without that shared origin: a robot gripper's opening and a human thumb–finger opening might both describe how an object is approached. That example would require a separate robotic study; the proposed two-person study would not test it. Each body keeps its own joints and possible directions of movement, positive-axis conventions, proportions, muscle–tendon roles, loads, inertia, contact and timing. Two similar-looking limbs need not generate the same forces or move at the same rate. Calculating a corresponding movement for another body is retargeting; the calculation remains derived, alongside separately identified tracking observations, estimates, predictions and simulations.

The proposed description of movement contains thirteen quantities. Three give the index sensor's position relative to the wrist, three do the same for the thumb and three for the object. One describes the distance between the two digit sensors; the final three describe wrist velocity using only information already available. Thirteen extra mask values say which features are actually available. Each person needs checked position units, sensor placement and a wrist orientation that turns positions into the intended frame without reflecting the body. After the checked conversion to metres, the middle, or median, wrist-to-index-sensor distance from that person's assigned train-

ing support supplies a positive length scale for position and velocity. This is a sensor-distance scale, not a measured bone length; development observations do not set it. Velocity is also multiplied by the same 0.1-second interval in both people. The thirteen prediction features then have no physical units. To recover velocity errors in metres per second, multiply by that person's length scale and divide by 0.1 seconds. Missing features contribute no target error; writing a masked zero does not make a missing observation measured. These features do not supply all finger joints, individual muscle forces or the person's inertia.

The model would use fifty movement frames at 100 observations per second to predict 100 milliseconds beyond the latest filtered input actually available. The source rate must first be checked as 500 observations per second. A proposed filter combining 51 present and earlier samples would precede keeping every fifth sample, producing 100 observations per second. Its linear-phase delay is 50 milliseconds. That delay stays in the account of when the information became available; moving a timestamp backward cannot make the predictor respond earlier. Filter coefficients, the frequencies it preserves, timestamp conventions, gaps and handling at recording edges still need checking. Only the named movement columns may enter. The source's kinematics matrix also contains force-plate signals, which cannot quietly become movement features.

Knowing which input was read is different from knowing whether two inputs are independent. Trustworthy published participant attribution, an unchanged exact archive entry and a checked capture can identify the participant record and recorded input without requiring one particular spelling of an ID inside the file. They do not authenticate a biological person or prove that two files came from different original acquisitions. A longer recording and its trimmed copy could have different names and file fingerprints while sharing the same movement. Shared samples, trims, derived versions and overlaps must therefore remain together as one acquisition group before filtering, cutting windows, scaling or assigning roles. The complete public non-ST roster and these relationships still need establishing. All 294 rows of the earlier AllLifts table remain unavailable for training, evaluation and assigning trials or acquisition groups. ST, competition storage and reserved LINK recordings remain closed.

Qualified P1 groups would provide the earlier movement learning. P2 groups would be divided between target training and development checking. At least two independently established P2 acquisition groups are needed. If there are $G \geq 2$, a fixed hash calculation ranks their established original-parent identifiers; the first $\lfloor 3G/5 \rfloor$ become training groups and the rest become development groups. The floor brackets mean rounding down, so the nominal 60/40 division is explicit even when the number of groups is small. The exact identifiers, how they are written as bytes and the complete roster must be settled before ranking or seeing outcomes. The order is not chronology and need not balance lifting conditions. If uncertain ancestry forces all P2 recordings into one group, the comparison stops. Cutting that group into windows cannot create independent training and checking acquisitions. No actual group or movement segment has been assigned by this proposed identity method.

The three training arms keep the target task and model the same. B0 first learns from correctly mapped P2 training movement. B1 and B2 first learn from exactly the same P1 windows in the same order. B2 uses the proposed correct correspondence. B1 deliberately uses the thumb sensor for the index role, the object sensor for the thumb role and the index sensor for the object role, leaving the wrist anchor fixed. Both use

the same correct source calibration and scale before this change, then the same correct target adapter and ordered target-training batches. Sampling gives each original acquisition group balanced treatment and records repeated as well as unique windows. The learner might undo the false correspondence; changing roles can also change which features are available. Equal numbers of updates do not give the arms equal diversity of source movements. Those limits must stay in the explanation of any difference, rather than prompting a more convenient control after results are known.

The proposed network is a single gated recurrent unit, or GRU, layer: a calculation that updates a numerical memory as it reads the sequence. It has a memory width of 32, accepts the thirteen movement features and thirteen masks as 26 inputs, and predicts thirteen outputs. That software memory is not measured biological memory. Each arm uses the same initialization for a given fixed random seed, with seeds 17, 31 and 73. Every arm/seed receives 200 earlier-learning updates and 100 target-training updates, using batches of 16 examples. Adam, the proposed weight-update rule, has learning rate 0.001, beta settings 0.9 and 0.999, epsilon 10^{-8} and zero weight decay. There is no clipping, changing learning-rate schedule or early stopping; the final update supplies the checkpoint. During training, squared prediction errors are averaged over observed target features; a batch with no observed targets must stop. Across three arms and three seeds this would be 2,700 updates. None has been performed for this comparison. No external checkpoint is selected, and the numerical updates, filter, precision and actual computing limits still need independent checks.

For each development acquisition group and seed, the proposed score adds the squared errors for the observed target features, divides by how many such targets were observed, then takes the square root. It then averages those group scores equally, so a long recording does not automatically outweigh a short one. A comparison with no observed targets has no valid denominator and must stop. The report must give feature counts, missing observations, errors converted back to physical units, uncertainty and a persistence forecast—continuing the latest available movement value—using the same information endpoint. Every worse group or feature remains visible. B2 would need lower normalized error than both B0 and B1 in each fixed seed, with no applicable original requirement failing, to justify another investigation. Two people and development checking do not establish performance across a population, untouched final confirmation or biological teaching.

Larger movement collections could supply more examples after their exact files, permissions, relevant movements and original-recording overlap are checked. AddBiomechanics distinguishes recorded markers and ground reactions from fitted joint movements and torques estimated by inverse dynamics—calculating forces or torques consistent with motion and a body model. Those estimates are not new direct force measurements. The selected AMASS asset would need its research-use, non-commercial and redistribution terms checked. The same original recording in two collections stays one source, not independent training and checking data. LaBraM's earlier training inventory flags the WAY source family, but exact checkpoint, participant and trial exposure remains unknown. A later decision to reserve a recording cannot remove its possible influence from already trained weights. No such checkpoint is selected for this comparison.

Scans have a more specific job than making the body look complete. Before adding X-ray/CT or MRI, check which anatomical sources the chosen musculoskeletal model al-

ready uses. A new scan is useful when it fills a stated gap or provides a genuinely independent check. Its person or species, scale, registration, permissions and uncertainty still need checking. Registration establishes the correspondence between that image and the body being studied. Another person's scan remains an external reference; a generic body model does not secretly measure this participant's geometry, muscle activation or forces. No scan set is selected here.

The actual eligible recordings, acquisition groups, units, frames, clocks and calibration are still unresolved for this continuous comparison. It reports no new fit or successful transfer. A movement description that proved useful could later be tested alongside genuinely paired neural and body observations, using only the inputs allowed for that prediction. The transferred or calculated target would not become a simultaneous measurement. The useful next answer is where the movement forecast improves, where it worsens and which measurement or assumption explains the difference. Neural equivalence, causal physiology, delivered sensation and a skill that remains after guidance ends would each need a further experiment.

39.7 Pretrain. Pair. Verify. Refine

Those comparisons start with the observations we may use. Data rights, calibration and held-out subjects, sessions and tasks determine which can enter the study; resolve them before processing data or choosing a model. Open-source code does not grant blanket permission to use datasets, checkpoints or clinical interfaces. Qualified data could first train representations for each recording type. LaBraM is one EEG encoder candidate, not a complete brain-body writer. Synchronized paired observations could then train the declared mapping from permitted inputs.

Paired prediction would give later refinement a baseline to beat. Before optional reinforcement learning, post-training or task-specific fine-tuning, the physical predictions and reward need checking against independent outcomes; a reward the computer can calculate supplies no biological proof by itself. Offline reinforcement learning needs qualified coverage of actions, transitions and rewards: labels alone cannot tell us what an untried action would do. Backpropagation can update differentiable neural components, but it cannot automatically pass through every physics engine; universal differentiability is not established. Simpler baselines and frozen final tests remain through every phase.

Jiang, Zhao and Lu (2024) [11]; Kumar et al. (2020) [12]; Seth et al. (2018) [8]; MyoSuite documentation [9]. These sources offer candidate methods for the sequence; validation of the proposed paired system still requires the experiment below.

This proposed paired training sequence has not been carried out.

39.8 Respond quickly. Improve carefully

A frozen accepted model would provide the proposed response: predict from permitted past and present observations, then prepare encoded outputs for a qualified interface. Inspecting the errors would be a separate job. That path would calibrate and propose a candidate update, to be independently evaluated with a restorable check-

point before it could replace the running model. Updating an estimate of the current state therefore differs from changing learned weights; examining an error would not silently change the predictor.

The candidate update would need more than a good-looking new score. Its independent evaluation, a saved version that can be restored, evidence that restoration works and the applicable authority would all precede replacement of the running model. Until then the accepted weights stay fixed. This keeps an attempt to improve tomorrow's model from quietly changing the one being tested today.

The fast-and-slow comparison is a Kahneman-like analogy for this division of work. It identifies no pair of biological systems and assigns no inherent thinking speed to EEG or spatial data. Whether the frozen response is quick enough would depend on the complete path from acquisition through filtering, alignment, inference, output, feedback and rendering, including delay tails and jitter. That end-to-end latency has not been measured. No accepted model, real-time demonstration or running system that adapts under these rules is established here, so the proposed separation supplies no latency or accuracy guarantee.

The complete timing test would include preparing the output and any later sensory conversion or actuation, rather than stopping the clock when the prediction leaves the model. Delay tails describe the unusually slow cases; jitter describes variation in delay. Missed deadlines, uncertainty and the effect of other healthy workloads would also need reporting. An average inference time could hide the late response that matters in a catch.

39.9 Write sensation. Enact action

What reaches the learner when the computer has made its prediction? A sensory transducer would have to deliver a sensory output; a controller and actuator would have to produce action in a virtual, robotic or later qualified biological body. Input and output describe the computer boundary. Afferent and efferent describe physiological direction relative to the central nervous system.

A display or haptic interface supplies sensory feedback, which differs from direct neural writing. Direct cortical writing could have a sensory role without being a peripheral afferent signal, just as a robot command is not an anatomical efferent nerve. EEG and EMG recorders do not write, and predicting an EEG-like pattern does not deliver sensation. Each proposed output needs an independently qualified interface, permission for its use and a measurement of what it delivers. No such physical interface, stimulation, acquisition or actuation is established by this proposal.

No methods evidence from the inaccessible clinical source supports this proposed interface. Implanted precedents cannot establish that EEG or EMG recorders are equivalent to devices that deliver sensation or produce an action. Those physical additions remain unpriced and outside the acquisition and virtual-modelling scope.

39.10 Close the loop with evidence

Return to the cup with two independent checks: withheld body observations for the brain-to-body prediction, and the recorded neural target for the conditional estimate from the body. Agreement between the models or a high reward could still accompany a wrong answer. Neither establishes a unique inverse brain or someone's private experience. A later sensory or action interface would need a further measurement of what it delivered, under which conditions, with what error and delay.

Approximation gets us towards plausibility and virtualization gets us to precision. Independent measurements, repeatability, causal checks and stated error bounds must earn that precision; the proposal supplies neither perfect biology nor an automatic result. The original held-out and real-reference controls would test where each prediction works and where it fails. The retained-learning controls ask a further question: what remains when useful guidance stops, with any necessary movement bridge kept constant?

Physical sensory writers, transducers and actuators remain unpriced additions outside the acquisition and virtual-modelling costs. Those costs cannot tell us the price of delivering sensation or action. No completed loop, training or physical-writing result is claimed here. *Catch it again when the help is gone* develops that task and retention comparison. *Build a brain–body system we can test* asks what those results would have to establish before the prototype could grow. The mechanism, task and prototype are stages of the same proposed experiment.

39.11 What the attention calculation actually does

The proposed learner needs a way to relate permitted observations. Consider one moment in a reach. A query represents what the model is looking for; keys represent the observations it could compare with that query; values carry information from those observations. The model learns these representations. Their names describe a calculation, not a person inside the machine who understands the task.

The technical edition writes that calculation as

$$\mathrm{Attention}(Q, K, V) = \mathrm{softmax}\left(QK^{\top}/\sqrt{d_k} + M\right)V.$$

Here Q holds the queries, K the keys and V the values. The superscript on K means transpose: rearrange its rows and columns so the comparisons can be calculated. Multiplying Q by that rearranged K gives scores for the query–key matches. The common width of each query and key is d_k; dividing by its square root scales those scores. The softmax operation turns the allowed scores into weights that sum to one for a query with usable admitted keys. Multiplying by V then combines the values using those weights.

M is the admitted mask. It controls which observations may contribute, so an unavailable muscle target or a later sample cannot quietly provide the answer. A mask is part of the declared test, not a decorative option after the model has seen the data. Channels, recording type, task and time must all retain their meanings through the calculation. Even a correctly calculated weighted combination could predict the wrong reach:

the independent measurement still has to check it. This is a proposed method; no weights, EEG encoder or gradient route have been selected or executed here.

39.12 What each direction is allowed to know

Use the same short labels as the technical method: B means EEG, E means EMG, Y means independently measured movement, C means declared task, stimulus and context, and P means the physics model with its identified source. The letters keep track of information. They do not make the quantities interchangeable.

An EEG-only test would use permitted past and present B, together with declared context, to predict a specified E or Y target. Training may have used qualified paired examples. At prediction time, however, the withheld muscle and movement answers and future samples must stay outside the predictor. Alignment, filtering and preparation of the data must respect that separation too. Supplying a target through a less obvious route would still supply the answer.

A body-only test would use permitted E, Y or both to estimate specified recorded neural features. Its answer is conditional: given these observations in this task, what recorded features are plausible, and with what uncertainty? Several hidden neural states could fit the same movement. The reverse estimate therefore needs its own recorded target; it cannot recover a unique inverse brain or deliver the sensation it predicts.

A hybrid test would use additional permitted recording types and need its own named route and evaluation. Its result could not be presented as EEG-only. Inputs calculated by the simulator would remain simulated. They would not replace independent observations or inherit biological validity from a lifelike hand.

Two models could also learn to agree with one another. That agreement is called cycle consistency when following one mapping and its reverse brings the result back toward its starting point. Both mappings could still be wrong about the measured body. Shared cues, movement artifacts, subject identity, overlapping sessions and information leaked during preprocessing need the original controls. Final held-out answers must remain outside selection of the model, physics and reward.

39.13 How the proposed training would be checked

First decide which observations may enter the study. Establish the rights, people and tasks, physical units, calibration, uncertainty and shared clocks. Freeze the relevant participant, session and task splits, then check whether earlier pretraining already included material that would compromise those splits. Those decisions precede preprocessing and model selection.

Qualified recordings could then train a representation for each recording type. In the candidate LaBraM route, a neural tokenizer turns signal segments into codes; masked-code prediction trains a model to estimate hidden codes; later fine-tuning adapts it to a declared task. These are computer-learning steps. LaBraM is a candidate EEG encoder, not a complete brain–body writer. Permission to use code, checkpoints, datasets and individual recordings requires separate qualification.

Next, paired supervised learning would use named measured targets and explicit masks. Supervised means the training examples provide the answers against which predictions are compared. Simpler predictors, cue-only predictors and artifact controls would help test whether the proposed neural route contributes useful information. Raw recordings, processed features and model-generated values would remain distinguishable.

Combining errors requires another decision. An illustrative training objective could include errors in EMG, movement and recorded neural targets, applicable physical constraints and optional consistency terms. Before choosing their weights, each term needs its target definition, units and measurement uncertainty. Otherwise changing a unit or weight could change which error the optimizer mainly tries to reduce. Consistency asks whether the outputs fit together; an independent measurement asks whether they fit what happened.

Optional reinforcement learning and post-training would come only after checking the physical predictions and reward against independent outcomes. Success on the task, smaller calibrated movement error and valid physical states are possible reward ingredients, not results already achieved. Loss and reward weights would be declared from training and development evidence. Offline reinforcement learning needs observations that support the relevant actions, resulting changes and rewards. A labelled trajectory alone cannot tell us what an unsupported, untried action would do. Conservative Q-Learning is one candidate method for this stage; its name provides no safety or performance guarantee here.

Task-specific fine-tuning would still face frozen final tests in both directions, with uncertainty, baselines and every original threshold. Failure would remain a result. An accepted version could then run with its weights fixed; a later update would need separate independent acceptance, restoration proof and applicable authority before replacing it.

Backpropagation calculates how to change differentiable parts of the computer model. It is different from biological feedback. A physics engine does not automatically supply the required derivatives: the actual OpenSim/MyoSuite simulation and optimization route, or a separately validated substitute, would need checking. No such training, reinforcement-learning rollout or task checkpoint is created or certified here. The procedure makes the proposed comparison inspectable while leaving its outcome open.

40 Catch it again when the help is gone

A computer could guide a hand to catch a ball. The catch happened. What would happen on the next attempt, after the teaching help stopped? That is the Brain2Body question. Keep the task and the necessary access to movement comparable, or the second attempt cannot tell us what the learner retained.

The instruments introduced in *From a reach to a testable model* would have to agree on the catch. Scalp EEG records scalp electrical activity, surface-EMG sleeves on both arms record muscle electrical activity, and the synchronized, calibrated left/right tripod views would measure the hands and arms. OpenBCI or an equivalent configurable system remains a candidate whose sites, capacity, units, delays and clocks need quali-

fication. The question now is whether those observations can distinguish a successful catch from the movement that merely looked close.

These left/right hand views differ from the earlier proposed top and bottom dot maps. Both belong to the motion-capture relay-composite idea, but each configuration needs its own calibration, timing and visibility checks. A point the camera cannot see must not quietly become a measured point because a model can draw it. The virtual body also needs appropriate anatomy and mechanics. EMG is neither a force measurement nor a recording of incoming sensory nerves; contact and force claims need observations that can check them.

40.1 Let each action add a problem worth solving

Begin by rubbing the hands rapidly together. Touch and movement happen at once. Matched conditions would help tell their effects apart. The requested knuckle movement and the stretch with interlaced fingers, palms outward and arms extended would be recorded as distinct actions. The cold-hands example makes rubbing familiar; it establishes no cold-exposure result or measured sensation.

Next, pass a juggling ball between the hands in the proposed hot-potato task, then progress to the preferred two-ball juggling task. Release makes a new problem for the catching hand. Check the model against the independently observed handover and its timing, including what remains uncertain. A prediction from the cue or previous movement might explain success without useful neural information, so those comparisons stay in the test.

Boxing would ask the system to distinguish stated punch types from measured movement. NeuroBoxer is the proposed virtual game built around that comparison. Hands and wrists help stabilize punches as well as the arms moving. A prime-era Mike Tyson opponent is a proposed virtual game character. The game supplies no physical opponent or evidence about safe physical boxing. Expert footage can show movement and tactics within its rights and camera limits. It cannot provide that expert's brain activity, muscle activity or force measurements.

Toy archery would add another form of coordination: one hand holds while the other draws, then the fingers release and the hands return. The proposal uses arrows with small, cup-shaped suction tips and an over-arm pouch with several arrows. NeuroArcher would use the coordination against a virtual target. Hitting it cannot, by itself, establish what happened in a biological nervous system.

The complete snap described in *From a reach to a testable model* tests another relationship: preparation, contact and return must all agree with the specified movement. The cup reach remains the simpler precision comparison. Both need organism-specific anatomy, contact, timing and real-reference evidence; a human-looking animation cannot establish that a monkey can perform the snap.

40.2 A virtual hand is the first control milestone

The first game milestone would follow measured body motion. A later one would ask whether permitted EEG observations can control a stated virtual action without using

withheld muscle or movement targets. Looking hands-free cannot settle it. Eye activity, small covert muscle contractions, residual movement, shared cues and future information need declared controls. Keep the original brain-only, body-only and paired comparisons, including the simple prediction that a target stays as it was, and keep the original success rules.

Understanding the intermediary should let us connect a stated intention with an action as closely as possible for a defined task. The test needs a stated person, condition, allowed context, tolerated error and independent observation. It does not establish a universal one-to-one brain map. Predicting a recorded EEG feature from body observations is likewise a conditional estimate. It does not identify a unique mind or deliver a sensation.

40.3 Teaching help and a movement bridge serve different roles

Remove tutor information to test what was retained. Keep any movement bridge needed to perform the task, and keep the comparison conditions meaningful. Measure performance now, retention later and transfer to specified unfamiliar conditions separately. Report how much help remains and what else could explain the result. Removing vision in a proposed blindfolded condition changes feedback; it does not make a test independent or prove learning by itself.

That retention comparison also depends on how movement or feedback reaches the learner. EEG and surface EMG supply recordings. A future body writer would need a separate qualified interface: neuromuscular electrical stimulation (NMES) and functional electrical stimulation (FES) can cause contractions or functional movement, while a sensory writer or transducer has a different delivery role. What the interface delivers would need its own measurement. Physical spinal work remains read-only. These physical additions are still unqualified and outside the acquisition and virtual-work budget scope; no such participant recording, stimulation or actuation is reported here.

Training the computer model and teaching a biological learner are different questions. Qualified recordings and simpler baselines come before paired fitting and fine-tuning. Reinforcement learning would need specified actions, resulting transitions and rewards; a good reward inside a simulation is not a biological teaching result. Final held-out observations stay outside training and selection, and a frozen running model stays separate from a candidate adaptive update. The current LINK comparison failed both model-admission gates and all five benefit claims. This task sequence supplies future comparisons, not a new result about retained skill, repaired tissue or a cure.

41 Build a brain–body system we can test

What would justify building the next prototype? The paired observations in *From a reach to a testable model* and the tasks in *Catch it again when the help is gone* give that decision a test. The virtual hand would predict from one declared input side; independent movement observations would check the answer. A missed contact or a late movement identifies a problem to resolve before expanding the apparatus.

The proposed design brings non-invasive EEG and surface EMG into one conditional learner with the calibrated motion-capture relay-composite and an open musculoskeletal-simulation physics-engine shown in a lifelike view. Its open multimodal model would need eligible neural and muscular structure and activity data. The EEG/EMG pair supplies intent-related brain and muscle observations; the movement/physics pair tests what the body did and how the mechanics predict it. Form constrains what could happen; measured function checks the prediction. Neither pair can certify itself through agreement inside the learner.

These five roles give us brain recordings, muscle recordings, measured movement, a computer body and a learner that relates them. The capture composite would join checked movement views. The physics engine would calculate movement under stated muscle, joint and contact rules. Multimodal means that the learner can relate different kinds of observation; it does not mean they were all recorded together or make a missing channel measured.

41.1 One movement. Two directions.

The two directional tests need different answers kept outside their inputs. For the forward test, EEG and declared task context would predict supported muscle activity and movement on withheld recordings. For the reverse test, muscle activity and movement would predict recorded EEG features within the task. Each prediction needs its own independent measured target; agreement between models cannot substitute for either comparison.

Movement establishes what the body did, narrowing the plausible explanations of the brain signals without identifying a unique intent or private experience. Stimulus, task, behaviour and separately reported context therefore remain with the observations. Uncertainty belongs beside the estimate; a generated neural pattern cannot be displayed as the observed mind.

Surface EMG still records muscle electrical activity. An incoming sensory or feedback-pathway claim needs its own evidence, which the virtual body cannot supply. Recordings, predictions and simulation must remain identifiable as the comparison follows one direction and then the other.

41.2 A bridge must account for the spine

The spinal cord helps shape the response. Muscle output depends on sensory input, movement context, local circuitry and descending input; some spinal pathways can retain learned changes. Reproducing a specified spinal function would therefore require more than forwarding its signal: a brain–body bridge must account for the processing it aims to reproduce.

A changed response can reflect immediate reflex modulation, lasting spinal plasticity or peripheral adaptation. Those explanations need separate tests. A change during the task does not establish retained memory, and a retained change does not by itself locate that memory. Human reflex conditioning and constrained mouse adaptation supply evidence for different claims. [4, 13, 14] The human studies do not estab-

lish brain-independent learning; the mouse preparation does not demonstrate unrestricted walking or reaching. Our human comparisons use abstracts and selected results, discussion or methods passages. Relevant mouse-study passages were also examined in the author manuscript; equivalence to the final published edition and the complete methods and statistics have not been established here.

Reflex modulation means that the current conditions change a response; plasticity means a change in the nervous system that can last. Peripheral adaptation concerns changes outside the brain and spinal cord. A later change in movement could involve more than one of these processes, which is why persistence alone cannot tell us where or how the change occurred.

The periphery adds a different question: did the sensory signal itself change? Passive proprioceptive training supplies a task-specific peripheral comparison; its psychophysical and spindle-afferent experiments were separate. [15] Our passive-training comparison uses abstracts and selected results, discussion or methods passages. None of these studies demonstrates universal skill transfer or complex memory stored in a peripheral axon.

The psychophysical comparison tests what a person can distinguish or report. The spindle-afferent comparison records sensory signals associated with muscle spindles, receptors involved in sensing stretch. These were separate experiments: placing their results together does not turn them into a single simultaneous observation of perception and nerve activity.

The next comparison must choose a function we can measure. Does the controller respond appropriately to the supported context? Does an adaptation persist through the declared test? Could peripheral or mechanical changes explain the outcome? Keep recordings, estimates and simulated state in distinct visible layers. Surface EMG cannot supply a missing sensory-nerve or spinal channel; an explanatory cutaway cannot register recorded neural sites.

Externalization remains the research aim: can a specified spinal function be reproduced outside its usual pathway? Replacing a computation, stimulating a pathway, controlling a simulated limb and restoring biological function would answer different questions. Each needs its own task- and site-specific evidence; physical spinal scope remains read-only. Anatomical access does not establish neural function, increased excitability does not establish useful plasticity, and no fixed percentage of a complex skill can be allocated to brain, spine or periphery from these proposals.

41.3 Reading a signal and writing an output

A prediction leaves the delivery question open: what, if anything, reached the learner? *Write sensation. Enact action* distinguishes the computer's input/output boundary from afferent/efferent direction relative to the central nervous system; a robot command has an action role without becoming an anatomical efferent nerve. That distinction determines the further test.

Delivering sensation would require a separately qualified sensory writer or transducer. Indirect sensory feedback and direct neural writing need distinct device, measurement, safety and clinical evidence. Producing an action needs the appropriate virtual, robotic

or biological output interface. The recording prototype does neither by predicting EEG or EMG. Physical sensory writers, transducers and body actuators remain excluded from the acquisition and virtual-work plan, unqualified and unpriced. This proposal authorizes no stimulation, participant acquisition, biological actuation, new equipment purchase or training.

41.4 The first prototype has to earn the next one

The lean tier would first ask whether the selected signals and calibrated movement reference can be synchronized for a bounded task. The serious-prototype tier would improve acquisition, independent references and source-specific bidirectional evaluation. Evidence from those comparisons would determine whether the research-lab tier should expand cohorts, tasks, instrumentation and compute. A larger apparatus needs an answered question from the smaller one.

Each tier needs equipment, calibration, accessories, storage, integration, appropriate safety and consent work, independent references and contingency. Current vendor sources should distinguish listed prices from engineering allowances and items needing quotes. Planning figures stay in USD, with a dated basis for any currency conversion. These budgets describe proposed scopes; they authorize no purchase and promise no complete neural reconstruction.

41.5 Let the model earn the claim

The first model comparison depends on compatible observations, not the length of the source catalogue. Rights, version, coverage, clock, units and missing modalities determine what an open dataset can contribute. Fitting would require an independently admitted protocol, with participants, sessions and tasks excluded from model selection reserved for testing. Simple baselines would show whether the added model helps; artifact leakage, absent inputs, timing errors, physically invalid solutions and uncertainty could explain where it fails. Earlier failures and reserved recordings remain part of that test's constraints.

Constrained virtual hand or foot control would be the starting domain. Robotics, remote operation, unfamiliar effectors and extra limbs remain later research directions, each requiring separate physical, latency and safety evidence. A successful movement prediction supports its movement claim. Biological and perceptual claims need the corresponding broader evidence.

Rights-cleared images and lifelike interactive models would let a reader inspect the apparatus and compare the observation, prediction and error under their declared conditions. A convincing image cannot fill a missing measurement or demonstrate biological function. The first prototype would have to make the difference visible and testable before the next one could rely on it.

42 Measured Improvement

The programme can begin with the key press: what should move, and what result would count as useful? Formulating means deciding that question; specifying means naming observable outcomes that would answer it. Verification then checks whether the implementation does what was intended. Evaluation compares its answers with independent references. Measured error shows what to refine next.

These parts need not happen only once. A failure may expose a poor question, a missing measurement or an incorrect implementation. The response should diagnose the end-to-end cause while keeping the original evidence and thresholds. Repeating work for the sake of activity does not create scientific progress.

Model size and computing speed also need evidence. A larger model may help some tasks; it cannot create missing paired measurements. Faster training on a machine is a computer-workload result, not a promise of faster biological mastery. A hardware change earns promotion only through matched useful outcomes with the same quality and acceptance requirements.

Generated data can help practice and controlled development tests. It cannot supply independent measured biology for a target never observed. Real held-out measurements, comparison methods, uncertainty and failures remain necessary. Savings in time or effort are useful only when the scientific question and all its gates remain intact.

43 Internal-Body Sensing

Interoceptomics is the programme's proposed study of internal-body sensing together with maps of the neural connections involved. Heartbeat, breathing and other internal signals could offer additional questions beyond visible movement. The word combines interoception, sensing the body's internal condition, with connectomics, studying neural connections.

Those questions need appropriate observations and outcomes. A finger-contact sensor does not directly measure the feeling of a heartbeat. A model of breathing motion does not by itself reveal private sensation. The movement-first strategy can help ground some relationships without turning every experience into an objective readout.

The names NeuroTranslation and Interoceptomics describe proposed scope. NeuroTranslator describes implemented software. NeuroTranslation Network describes a proposed design. Brain2Body names the overall programme. NeuroTranslate names a proposed mapping operation with declared inputs, targets and a task. Testing one direction does not establish its reverse, a unique brain state or delivered sensation. Keeping these meanings consistent prevents a new label from being mistaken for a new demonstrated capability.

44 Tests That Could Reject the Proposal

The framework loses support where appropriate controls do just as well, the mapping fails on later recordings, or tutor gains disappear after help stops. A simulation that violates independently supported physical bounds cannot support the claimed biological mechanism. A claim whose target cannot yet be measured remains unvalidated rather than being promoted through visual confidence.

Negative results are not a reason to conceal the ambition. They tell us which next question is justified. The current development models fail their original benefit gates. The older classifier, keyboard replay and goal-driven policy remain separate bounded results. None demonstrates arbitrary skill teaching, complete nervous-system coverage or a voluntary central–spinal–peripheral chain.

There may still be useful limited interfaces even if a universal translator never appears. A narrowly tested prediction or a carefully measured aid can matter. Its value comes from what it demonstrably helps someone do under stated conditions, not from claiming every possible future result at once.

Return to the tune. If the hand needs teaching commands for every note, the result may still be useful assistance. If the learner performs better later without those commands, while retaining any necessary movement bridge, we have a result worth examining for retained learning. We would still need the matched controls, uncertainty and unfamiliar variations to say where that gain holds. Brain2Body's next generation must show what moves, who or what supplied the help, what remains when teaching ends and where the explanation breaks. This article proposes that comparison. It does not claim the learner has already passed it.

45 Definitions and Lexicon

This Simple English Edition definition and lexicon supplement uses the same meanings as the scientific article. It is derived from the shared Brain2Body registry identified by version and fingerprint at the start of that supplement. A fingerprint identifies a file; it is not a scientific score. Alternative historical labels remain lookup aids. A glossary supports the explanations in the text rather than replacing them.

46 References and Evidence Status

The original scientific sources are linked beside the statements they support. Dated developer accounts and pinned code observations are identified separately from published biological experiments. The accompanying computational results and limits describe the programme's unpublished numerical and software studies. The companion NeuroTranslation paper is an unpublished working draft. The historical conceptual figure explains a relationship; it supplies no new biological evidence. The edition note records the remaining scientific and publication limits.

Historical Conceptual Framework Illustration




Figure 1: The hand can execute a command correctly even when that command selects the wrong finger. In the earlier human finger-attempt study shown by the solid computational route, 41/60 intended contacts and 54/54 issued-command executions answer those different questions. The biological branch remains proposed. This unchanged historical schematic supplies no current anatomical, functional, lifelike-3D or biological validation. The separate macaque development study saved 18 runs and 720 epochs; both model gates and all five benefit claims fail. Neither study establishes biological teaching, full-body mapping or retained mastery.

Evidence, scope and edition status

A computational failure can narrow the next experiment; it cannot qualify a biological interface. These unpublished working manuscripts report computational studies and set out a separate proposed paired experiment. This edition reports no new fitting, reserved-data evaluation, model promotion or biological teaching. The common optimizer has not been independently certified. The original tolerances and reserved recordings remain unchanged, and each failed gate stays failed. Scientific, clinical, physical, real-reference-series, rights and runtime claims still require their original validation. Independent assessment of the whole manuscript's science, sources, citations, figures, actual rendered outputs and native exports remains unfinished, as do publication checks. This computational failure report establishes no readiness for publication.

This edition uses the 194-entry shared glossary, revision 29, SHA-256 4189722b c823c1634084c4a28b93dcc198e583f2b11443e315f0cb593fd9b038. Its 178-entry definition supplement and 16-entry addendum retain their scientific meanings. Four component entries now use the October 19 names and explain the proposed roles beside their measurement limits. Lookup labels can refer to related or contrasting ideas; the entries explain how the terms are used here. Earlier definitions remain in their historical editions. Updating the vocabulary does not revalidate the earlier studies or establish a proposed capability.

A generated illustration can explain a mechanism; it cannot replace the working model or measured evidence.

The requested public byline is `@eliminatenoise`. Author identity, applicable affiliation and repository submission requirements must be resolved before publication. No affiliation or publication acceptance is implied.

Brain2Body Definitions in Simple English

Canonical registry revision 26; `fc5dbd61462ecf98ada2629e84659ab2d05c0005 8df44efa80e3b397e20ca042`.

A model, a measurement and a claim about biology need different words. These 178 entries state what each term means in this programme. Naming a capability does not establish that it has been demonstrated.

Lookup labels help find an entry. Some name related or contrasting concepts, so they are not all interchangeable. The portable JSON retains the selected fields and complete lookup index. Original definition histories remain in the canonical registry.

Organizational level describes which part or signal is considered. Physical ranges and units describe dimensions. Computational granularity describes the detail represented in a model; statistical aggregation describes how observations are grouped. A missing range or unit remains unspecified.

Some technical notes describe a named source edition or prototype. Its measurements, numerical results and implementation limits belong to that context; they are not timeless claims about every model. The entries distinguish recorded observations,

calculated quantities, simulations and proposed capabilities. This supplement reports no new experimental result.

A checked message between software parts

A structured message and interface specify what the values mean and how software parts exchange them.

The checks include recording, ordered channels, quantity, timing where supplied, units and body axes. Passing a check does not prove that the caller's claimed physical source is true.

Lookup labels: Translation packet, typed port and API; packet; translation port; typed interface; API; application programming interface

A group of recorded neural features

Several recorded neural features considered together when predicting an outcome.

Their joint pattern can help predict movement. That does not establish that the same pattern has the same meaning in another animal, task or day.

Lookup labels: Neural population; population decoding; population model

A map of physical connections

A structural map records physical connections. A functional recording measures activity over time, such as which recorded features produced events during a task.

The structure can guide a model, but it cannot supply missing time-recorded activity. A drawing, connection map and synchronized functional recording have different evidential roles.

Lookup labels: Structural connectome and anatomical prior; connectome; connectomic connectivity; anatomical prior; structural connectivity; structural reference; recorded function; structural versus functional measurement

A model spanning the body

A future model connecting relevant observations and actions across the brain, spinal cord, nerves, muscles and movement.

The project does not yet have a matched voluntary recording across that whole chain. Separate datasets cannot fill the missing measurements.

Lookup labels: Body-wide functional model; body-wide neural fusion; whole-body neural translator

A specified human-related feature

Studying a defined human-related biological component or feature in a model organism.

This can overlap with adding donor cells. One selected immune or neural feature does not make an animal a miniature human or establish human-like cognition.

Lookup labels: Humanization; humanized; human-related feature

Ability that remains after guidance is removed

A learned ability that remains without the training guidance and can be tested again later.

Remove tutor commands while keeping any bridge needed to express the pupil's own control. Switching off that required route can prevent movement regardless of what the pupil learned.

Lookup labels: Retained learning; retention; independent pupil control; retained skill; pupil-alone; necessary bridge held constant; pupil-alone with necessary bridge constant

Action2World

The hand reaches; the cup moves or stays still. Contact, load and the measured outcome tell us whether the action did what we intended, and that feedback shapes the next attempt.

The relationship between an action and its consequences for the body and surrounding environment, including the sensory information those consequences produce.

A predicted consequence is not an observed outcome. Specify the object, reference frame, task, units and uncertainty. Footage supplies movement examples without supplying the performer's neural, muscle or force measurements.

Organizational level: whole system; network; signal/feature

Lookup labels: action2world; action to world; action-to-world

Activity state inside the muscle model

The model's internal state that responds to a command and affects its force.

This state can change more slowly than the command. The displayed activation comes from the computer model, not recovered physiological activation from the macaque recording.

Lookup labels: Muscle activation; activation; activation dynamics

Adjustment using evidence from the new setting

Changing or checking a model using examples from where it will be used.

Adjusting a decoder, checking probability scores and measuring a body's physical properties are different kinds of calibration. The new-day model uses labeled examples.

Lookup labels: Calibration; recalibration; calibrated transfer; uncalibrated; physiological calibration; physiological fidelity; subject calibration

Agent2Agent

One software agent passes declared information to another.

A proposed link carrying specified information between software agents.

Name the agents, message or representation, direction and tested outcome. Software communication does not by itself supply a biological recording, sensory writer, shared experience or demonstrated skill transfer.

Lookup labels: agent2agent; agent-to-agent; agent to agent

Agent2Brain

An agent would give a person feedback during a stated task. Tests would have to distinguish help during that task from learning that remains afterwards.

A proposed path from a software agent to a person through specified feedback or a separately qualified neural output interface.

Feedback would reach a person through an ordinary sensory route or a separately qualified direct neural interface. Those routes need different devices, evidence and admission: feedback on a screen is not direct neural delivery. EEG and EMG record; they do not write. The proposed agent-to-person path leaves the reverse observation and feedback direction intact. Help during a task must be tested separately from learning retained after it ends. Agent2Brain establishes no stimulation or physical-action authority. Physical spinal scope remains read-only.

Lookup labels: Agent2Brain?; agent2brain; agent2brain?; agent-to-brain; agent to brain

All outputs inside their ranges together

How often every output of interest falls within its stated range in the same case.

A 90% range for each separate output does not guarantee 90% coverage of all outputs at once or of a whole body.

Lookup labels: Simultaneous coverage; all-output coverage; whole-body coverage

An independent way the model can move

One independent model movement, such as rotation at a joint. The formal shorthand is DOF.

The native arm has seven coordinates and no separate finger movements. The human replay controls two goals while bracing other independent joints.

Lookup labels: Degree of freedom; DOF; DOFs; independent coordinate; braced joint

Analysis timing and biological travel time

An analysis offset aligns two recorded quantities. A conduction delay concerns how long a signal travels through biology.

The 40 ms sensory offset estimates an earlier limb state. The motor target's 4 ms offset comes from sampling. Neither measures neural conduction time.

Lookup labels: S1 alignment offset and conduction delay; 40 ms sensory lag; S1 lag; 4 ms sampling offset; conduction delay; physiological latency

Animal drawing and measured anatomy

An illustration explains a proposed animal or body. An empirical anatomical atlas is built from verified observations of anatomy; it cannot be established by a convincing drawing.

The antechinus illustration is a proposal, separate from acquired macaque and human sources. The implementation has no matched validated antechinus neural/body atlas and makes no living-animal learning claim from the image.

Lookup labels: Antechinus proposal; antechinus; marsupial proposal; hypothetical organism; Proposed marsupial setting; anatomy illustration; illustrative model; empirical atlas; anatomical atlas

Another brain area used in the finger study

A brain area recorded alongside the movement area in the human finger study.

The formal name is posterior parietal cortex, or PPC. The study provides attempted-finger labels, not measured trajectories of executed finger movement.

Lookup labels: Posterior parietal cortex; PPC; Parietal brain area

Assumed repair to the native muscle model

A separately named model version replaces unusable zero-rate properties with the software's default values.

The source uses a named Schutte muscle model. Restoring 117 default properties permits numerical tests but does not measure the subject's muscle response rates.

Lookup labels: Schutte muscle properties and default-rate fork; Schutte; zero-rate; assumed-rate fork; class defaults

Attachment order and the chosen route segment

The ordered connection points and the numbered segment to which a wrapping rule applies.

The rule uses the source model's attachment order. The SDK counts from one and includes both range endpoints; the correction does not fit arbitrary points to an error frame.

Lookup labels: Attachment topology and SDK range; attachment topology; one-based inclusive range; humerus-to-ulna segment

Axes, pushes and turns

A coordinate frame states the axes used for movement. A handle wrench combines forces and turning moments measured in that frame.

The handle record has three force and three moment components. An unknown mapping into the computer-body axes prevents treating those forces as verified simulator inputs.

Lookup labels: Coordinate frame and handle wrench; body frame; XY; physical frame; handle wrench; forces and moments

Biological tissue repair

Restoration or replacement of biological tissue or its function, supported by direct biological evidence.

Better simulated tracking, assisted movement and retained behavior are different outcomes. The prototype does not demonstrate neural tissue repair.

Lookup labels: Regeneration; tissue regeneration; repair

Biological virtualization

For a movement model, matching the path is one question; matching the living system's response to an intervention is another.

A claim that a digital model reproduces specified biological behaviour and causal dynamics within an independently tested domain and stated error bounds.

Independent ground truth must establish measured error and repeatability within declared conditions and tolerances. For causal dynamics, the comparison also needs independently measured responses to appropriate causal interventions; a similar-looking trajectory alone cannot establish them. Approximation can make a model plausible and may contribute to a validated model when its assumptions, errors and domain are tested and disclosed. A musculoskeletal simulation is itself a model to test, not independent empirical ground truth. Numerical detail and repeated verifier results guarantee neither biological accuracy nor complete physiology, subjective continuity, consciousness transfer or implemented Brain2Body capability. This biological claim is distinct from operating-system virtualization.

Scope: validation: Specified observed behaviours and causal dynamical responses under declared conditions.

Organizational level: whole system; network; organ; local circuit; cell; signal/feature

Computational granularity: Declared model and brain-body interfaces

Statistical aggregation: Declared validation aggregation; separate from physical scale

Lookup labels: virtualization; virtualisation; biological virtualisation

Body dimensions and resistance to motion

Mass is the amount of matter modeled. Inertia describes resistance to changes in motion; anthropometry means body dimensions.

The scaled model keeps assumed source masses and applies geometry-related inertia updates. Its length fit does not identify the animal's actual masses, strengths or individual bone dimensions.

Lookup labels: Mass, inertia and anthropometry; inertia; mass; anthropometry; subject scaling; specimen scale

Body position stored by the simulator

The model's stored configuration, such as its joint positions.

The formal variable name is qpos. Its entries depend on the model and are not automatically measured joint angles. The matching velocity variable, qvel, is explained separately.

Lookup labels: Generalized position and velocity; qpos; joint state

Body-model software and its programming tools

OpenSim provides tools for body models, geometry, scaling and simulation. Its software development kit, or SDK, lets code work with those models.

Checks on these tools establish the stated model's numerical behavior. They do not certify the exact upstream model version or the recorded animal's anatomy.

Lookup labels: OpenSim and its SDK; OpenSim; SDK; software development kit; native SDK; OpenSim 4.5.2

Body-position feedback

Proprioception means sensing body position and movement. For example, it helps a body monitor where a limb is. Biofeedback uses bodily information to guide action or learning.

The implemented correction uses simulated body position. It does not add measured peripheral nerve signals or show that a biological feedback process taught a retained skill.

Lookup labels: Proprioception and biofeedback; proprioception; simulated proprioception; biofeedback; Body-state sensing and feedback; proprioceptive feedback

Body2Action

The proposed link from body mechanics and sensory interaction to a specified, independently measured task action or outcome.

A task outcome makes this proposed link testable: the body's forces, contacts and timing have to be measured in the relevant context. Body2Action connects body mechanics and sensory interaction to that specified action or outcome; it establishes no working controller. World labels are historical conceptual lookup references, not a strict synonym for every environmental interaction.

Organizational level: Declared system or interface

Computational granularity: Declared process/interface/model

Statistical aggregation: Validation domain stated independently of physical scale

Lookup labels: Body to action; Body2World; Body to world

Brain imaging related to blood oxygen

An imaging method, called fMRI, that measures signals associated with changes in blood oxygenation.

It does not record individual electrical spikes. The paper discusses a published model for this kind of image, not a project result showing that brain scans and spikes are interchangeable.

Lookup labels: Functional magnetic resonance imaging; fMRI

Brain stimulation

An intervention that applies a specified physical stimulus to alter brain activity.

The method must be named, such as transcranial magnetic/electrical stimulation or intracortical microstimulation. These differ in access, risks and capabilities. EEG records; a scalp EEG headset does not provide general sensory writing or safe skill upload. Broad neuromodulation is not identical to precise task-content encoding.

Organizational level: Declared game/model/interface role

Computational granularity: Declared task-specific model or interface

Statistical aggregation: Validation scope declared per experiment; no physical-scale inference

Lookup labels: Neural stimulation; Neurostimulation

Source: A brain-computer interface that evokes tactile sensations improves robotic arm control

Source identifier: flesher2021

DOI: 10.1126/science.abd0380

https://pubmed.ncbi.nlm.nih.gov/34016775/

Research precedent for motor decoding plus sensory feedback through intracortical microstimulation; invasive and not a consumer EEG capability

Brain2Agent?

A recording supplies observations that an agent may use for a stated task.

A proposed path from specified brain observations to a software agent through declared recording and interpretation interfaces.

Recorded brain observations would reach an agent through a declared recording and interpretation interface. Where applicable, feedback toward the agent remains distinct from Agent2Brain's proposed agent-to-person path. Neither direction identifies unique private intent or experience. Recording supplies observations; inference and simulation interpret or model them, while actual sensory delivery requires its own interface. Brain2Agent? remains an open proposal.

Lookup labels: Brain2Agent; brain2agent; brain2agent?; brain-to-agent; brain to agent

Brain2Body

Connecting brain and body function; the 2 means to.

The numeral 2 is the preferred spelling. The programme includes body-to-brain feedback as well as outward pathways; the name does not establish complete biological translation or novelty of body–brain research.

Organizational level: whole system; network; local circuit; signal/feature

Lookup labels: brain2body; Brain2body; brain 2 body; brain-to-body; brain to body

Brain2Brain

Information links between two brain or neural systems.

The project's label for studying specified information links between brain or neural systems, including tutor–pupil comparisons.

Brain2Brain is the numeral-style public label for the project's existing brain-to-brain research direction. Each experiment must specify its signal, task and controls; the name itself establishes no shared thoughts, general skill transfer or successful biological teaching.

Organizational level: whole system; network; local circuit; signal/feature

Lookup labels: brain2brain; brain 2 brain; brain-to-brain; brain to brain

Brain2Motion

The proposed movement pathway connecting Brain2Body with Body2Action and the resulting measured motion, including the returning sensory feedback.

The label concerns the movement part of the wider programme, not every sensory/cognitive function. Brain/spinal/peripheral observations, muscle activity, body mechanics and external outcomes stay distinct. A decoded motion signal, simulation or lifelike animation is not a complete physiological explanation or validated skill transfer.

Organizational level: Declared system or interface

Computational granularity: Declared process/interface/model

Statistical aggregation: Validation domain stated independently of physical scale

Lookup labels: Brain to motion

Brain2Spine

A movement command meets a spinal cord that already regulates reflexes, coordinates muscles and adapts through experience. Understanding that middle step helps explain how the same intention can produce different actions.

The pathway from brain activity into spinal processing: descending signals influence circuits that combine them with sensory input and the body's current state.

A scalp EEG recording does not identify every descending signal or measure the spinal circuit's hidden state. The physical spine remains read only. This label does not name an admitted stimulation interface.

Organizational level: whole system; network; signal/feature

Lookup labels: brain2spine; brain to spine; brain-to-spine

BrainNet

A network of specified links between brain or neural systems.

A working network metaphor for connected brain or neural systems within the programme.

BrainNet pictures specified links between brain or neural systems as a network. It is a programme metaphor; it establishes no validated universal neural network, uniquely coined field or available trademark.

Organizational level: whole system; network; local circuit; signal/feature

Lookup labels: brainnet; Brain Net

Choosing a model and deciding if it passes

Choosing settings and applying a stated pass rule using the validation data.

The frozen-transfer rule requires a prediction score at least 0.01 above every specified control. A failing candidate stays rejected rather than being given an easier success rule.

Lookup labels: Validation selection and admission; validation-selected; acceptance criterion; admission; failure criterion

Command sent to a modeled muscle

The input command that starts the modeled muscle's activation process.

The command is bounded and nonnegative here. It differs from the resulting activity state, recorded muscle electricity and instructions for a biological intervention.

Lookup labels: Muscle excitation; excitation; actuator command; muscle control

Communication route around an interruption

An interface carrying selected information around a modeled break or between stated recording and control channels.

A bridge can compensate without repairing tissue or supplying muscle energy. The virtual interruption does not establish a biological injury model or treatment.

Lookup labels: Digital bridge; compensatory bridge; brain–spinal bridge; BCI; brain-computer interface; virtual pathway interruption

Comparable roles in different organisms

Comparing roles such as reaching or support while keeping each organism's anatomy explicit.

Related roles do not imply identical neurons or muscles. A combined fictional body cannot replace the measured sources and checks needed for each real organism.

Lookup labels: Organism role and homology; organism adapter; limb role; functional coordinate; homology; biped/quadruped

Comparisons that test whether guidance matters

Matched replay uses the relevant recorded activity under matched task conditions. Stale or unmatched replay uses activity from a different time or condition. No-link and inactive or sham comparisons test whether the proposed information route adds benefit.

These are proposed comparison types, not new animal results. Shuffling disrupts timing; a yoked comparison gives matched help from another case. Guidance amount, timing and later pupil control need their own stated comparisons.

Lookup labels: Shuffled and yoked controls; shuffled-input control; time-shuffled; yoked signal comparison; Matched comparisons with altered information; matched replay; matched own-session activity; stale replay; unmatched replay; no-link; sham; inactive comparison

Completed time interval for counting events

A stated time interval groups events into one count. A half-open interval includes its start and excludes its end.

Inputs use completed intervals. The exact boundary rule, interval duration and timing must remain explicit rather than being guessed from the display.

Lookup labels: Completed time bin and half-open binning; bin; 20 ms bin; 50 ms bin; half-open; bin end; cadence

Computer processors, memory and file size

A CPU is a general processor, a GPU is another kind of parallel processor, and RAM is working memory. Bytes and GiB measure digital data size.

The training described in this source edition used four CPU threads; GPU acceleration was neither verified nor used. AI-assisted coding does not establish independent biological validation or an authorship credential.

Lookup labels: Computing hardware and data size; CPU; GPU; RAM; AMD; AI; Ryzen AI Max+395; GiB; byte; bytes

Correct-label rate and chance comparison

Accuracy is the proportion of labels chosen correctly. A confusion table shows which labels were mistaken for others.

A uniform guess among ten balanced classes has a 10% reference rate. Accuracy and label scores do not prove executed movement or confidence in biological truth.

Lookup labels: Classification accuracy and chance; accuracy; uniform chance; ten-class confusion; confusion matrix

Count-prediction improvement per recorded event

Bits per spike describes how much a count-prediction score improves over a defined baseline, divided by the number of recorded spikes.

The baseline uses the training mean rate. A positive result concerns estimated average counts, not newly recorded activity or verified stimulation instructions.

Lookup labels: Bits per spike; BPS; ΔBPS; bits/spike; likelihood gain

Data for learning, choosing and checking

Separate portions used to fit the model, choose its settings, and check the selected result.

The paper uses local time-ordered splits. If test results have already been inspected, later reuse cannot be described as another independent test.

Lookup labels: Training, validation and test partitions; train/validation/test; train/val/test; split; chronological 70/15/15

Data kept out of a stated step

Data reserved from training or from another specified development step.

Independence depends on what was actually excluded. A previously inspected case does not become a fresh test just because it is called held-out.

Lookup labels: Holdout; held-out; reserved window; independent evaluation

Describing motion and calculating what causes it

Describing a body's position and movement is one task; calculating how modeled forces change that movement is another.

The paper calls these kinematics and dynamics. A replayed pose and a muscle-driven trajectory are different results; neither alone proves physiological accuracy.

Lookup labels: Kinematics and dynamics; kinematics; dynamics; forward dynamics; numerical plant

Electrical recording in outer brain tissue

Electrodes in the brain's outer layer, called the cortex, record electrical signals outside the cells.

This differs from a scalp recording. It also does not observe every cell in a circuit; the source file defines which events and channels were recorded.

Lookup labels: Intracortical extracellular recording; intracortical; extracellular cortical events; Electrical recording inside the cortex; cortex

Error range based on validation examples

A range placed around a prediction using the errors seen on the data used for model selection.

The ranges have constant width for each output. They do not guarantee future coverage when examples overlap in time or their errors are related.

Lookup labels: Residual band; empirical residual bounds; validation residual quantile; 90% per-output residual band

Events grouped as one neural feature

The source recording process groups events into features that the model can count separately.

A group is not a verified lifelong identity for one neuron. It must stay separate from unassigned events and from the channel labels used in other recordings.

Lookup labels: Sorted neural unit; sorted unit; sorted cell; sorted feature

Expected event count and its fit score

A model estimates the average event count for given inputs, then a score checks how that estimate fits the recorded counts.

The paper uses Poisson negative log likelihood for that check. A predicted average may be fractional; a good count-fit score does not establish a complete biological spike model.

Lookup labels: Conditional count mean and Poisson likelihood; expected count mean; conditional count; Poisson; negative log likelihood; NLL

External movement model

The external part of the body model, constrained by independently measured surface movement and pose in a declared task and coordinate frame.

The motion-capture relay-composite retains the source views, clocks, calibration and coordinate frame for the declared task. The earlier upper/lower hand concept and the later synchronized left/right tripod arm proposal are different arrangements; each needs its own visibility, synchronization and error checks. The composite is derived. Hidden internal states, forces and intent are not uniquely measured. LiDAR and optical infrared tracking require distinct hardware, calibration and uncertainty qualification.

Extra correction and its scoring rule

A model can add a correction to an existing controller. A reward scores the result; command-change rate describes how quickly the input changes.

The formal names include residual policy, reinforcement learning and actuator slew. A simulator can score tracking or task completion without proving biological learning or correct hidden neural activity.

Lookup labels: Residual policy, reward and actuator slew; residual policy; reinforcement learning; RL; verifiable reward; actuator slew; task completion

File fingerprints

A checksum or hash is calculated from file bytes to detect changes or match a stated reference.

The named methods here include MD5 and SHA-256. A match checks bytes against that reference; it does not prove scientific truth or verify an entire file when only a range was acquired.

Lookup labels: Checksums and hashes; checksum; hash; MD5; SHA-256; source checksum; archive hash

Force in the modeled muscle and tendon

The force produced by the computer model for a muscle-tendon unit, or a force measured by a stated physical method.

The native test reads forces from the running simulator rather than an old lookup table. Those values are still simulated rather than isolated forces recorded in the source animal.

Lookup labels: Tendon force; muscle force; isolated muscle force

Form → function → action

The programme narrative follows structural constraints, the context-dependent processes they support, and independently measured actions or outcomes.

The three words organize the explanation; every molecular and neural level has its own structure and dynamics. Form informs and constrains function but does not determine the full process alone. Feedback returns outcomes to the system; this is not a one-way causal chain or a guaranteed one-to-one mapping.

Organizational level: Declared system or interface

Computational granularity: Declared process/interface/model

Statistical aggregation: Validation domain stated independently of physical scale

Lookup labels: Form to function to action

Functional electrical stimulation

Electrical stimulation coordinated to produce a specified functional movement or task.

FES is the appropriate functional-actuation label for the proposed later assisted-body study. It requires separately qualified devices, control/safety limits and specialist-supervised research approval. This registry contains no stimulation settings or self-experiment instructions.

Organizational level: Declared game/model/interface role

Computational granularity: Declared task-specific model or interface

Statistical aggregation: Validation scope declared per experiment; no physical-scale inference

Lookup labels: FES

Source: Restoring cortical control of functional movement in a human with quadriplegia

Source identifier: bouton2016

DOI: 10.1038/nature17435

https://www.nature.com/articles/nature17435

Research precedent linking implanted cortical recording to a custom neuromuscular stimulation sleeve; not an EEG/OpenBCI or elite-skill result

Further training for the target task

Continuing model training so it predicts the desired target, using the relevant inputs and labels.

The paper calls this fine-tuning. Changing software weights is not evidence that an animal or person learned a biological skill.

Lookup labels: Fine-tuning; paired-output fine-tuning

Future testing and analysis of existing data

A future test checks later unseen outcomes under a fixed plan; an existing-data test analyzes outcomes already recorded.

The second source file was chosen before inspection, but its recording day is earlier than the original model's day. Choosing a file in advance does not make it future biological deployment.

Lookup labels: Prospective and retrospective evaluation; prospective; retrospective; prospective biological deployment

Gap between data portions

Leaving out an interval around a split boundary so overlapping windows do not cross into another portion.

The continuous pipeline uses a one-second gap and checks the input and target support. This protects the software split, not every assumption about the original measurement.

Lookup labels: Partition embargo; embargo; boundary embargo

Guide and learner

The tutor supplies guidance; the pupil is the learner whose later control is tested. An experienced guide helping a novice asks a different question from two novices practicing together.

The proposed comparisons include experienced-to-novice, novice-to-novice, individual practice and matched no-link conditions. Later pupil-alone testing removes tutor commands while retaining any bridge required to express movement.

Lookup labels: Tutor and pupil; biological tutor; artificial tutor; live tutoring; tutor withdrawal; experienced-to-novice tutor; novice-to-novice; individual practice

Hallucination

A model can predict a movement correctly while inventing the biological mechanism it claims produced it.

Invented or ungrounded model content presented as if it corresponded to reality. In programme claims, this includes fabricated biological structure, dynamics or ability presented as established biological fidelity.

Research on AlphaFold3 uses the term for generative-model errors; this programme also applies it to unsupported biological attributions. A disclosed approximation, hypothesis, counterfactual or unvalidated candidate is a different kind of statement, and missing evidence alone does not prove it false. Numerical error concerns the calculation; objective misspecification concerns what is being optimized; causal attribution error concerns the mechanism being credited. Those differences matter when deciding what a result supports. An ungrounded generated answer can happen to be correct without validating its claimed biological mechanism or reliability elsewhere. Informed predictions therefore still require independent performance evaluation. The rolling-dice analogy describes reliance on unverified claims, not literal randomness or equal odds. Calling every approximation a hallucination, or every connectome or simulation fictitious, would erase the distinction.

Scope: usage: Model-generated biological content and claims of biological fidelity.

Computational granularity: Model output and its interpretation

Lookup labels: hallucination; model hallucination

Help during current performance

Help from a controller, replay, tutor or interface that improves performance while it is present.

For example, a pupil can move successfully while following tutor commands. This does not show independent learning or tissue regeneration.

Lookup labels: Assistance; compensation; assisted performance

How a muscle's pull turns a joint

To relate a muscle's pulling force to joint turning, the model uses its geometry. Consistent work calculations also relate those forces to small coordinate changes.

The formal terms are moment arm and virtual work. Their numerical checks do not measure biological muscle strength; the human controller uses them to account for dependent shoulder movements.

Lookup labels: Moment arm and virtual work; moment arm; virtual-work projection; dependent shoulder-girdle load

How many labeled examples were supplied

The labeled examples given to train or choose a model, including examples from prior recordings.

The first 5% counts new training labels only. Validation labels, earlier-source labels and extra neural samples are additional information.

Lookup labels: Label budget and supervision; label budget; paired supervision; adaptation labels; validation labels; source-task supervision

How scores from several outputs are combined

Scores can be averaged across individual outputs or first combined within defined groups. In this entry, macro describes the averaging and weighting rule, not the size of a body part, the scope of a nervous system, or the level of detail in a computer model.

The sensory result gives equal weight to five physical output groups. This avoids letting a larger group dominate but does not make their different physical units interchangeable.

Lookup labels: Per-output and group-macro scoring; per-output; group-macro; macro R^2

How uncertain the result remains

The remaining doubt about a prediction, including why it could be wrong or change.

Noise in the instrument, errors in the model, changing conditions and missing observations are different causes. The current ranges do not separate all of them.

Lookup labels: Prediction uncertainty; uncertainty; model uncertainty; measurement noise; drift

Human arm model used for playback

MyoArm is the human arm model used for the displayed muscle-driven replay.

The replay uses 63 modeled muscles and two mapped joint goals. Those quantities are simulated, and the macaque velocity mapping does not prove neural or skill transfer into a human body.

Lookup labels: MyoArm; human MyoArm; MyoArm right

Internal musculoskeletal model

The internal anatomy part of the body model: specified bones, joints and soft tissues, assembled from appropriate registered anatomical measurements.

Proposed complementary X-ray/CT and MRI inform different structures. Anatomy does not directly measure activation, force, material properties or neural function. Wētā FX provides visual/simulation inspiration, not a verified identical acquisition pipeline.

Interoception

Information about the body's internal condition, such as signals related to heartbeat or breathing.

Scope: Sensing the body's internal condition differs from sensing a limb's position and movement. Internal sensing remains a research objective; this prototype does not provide a fully measured body-wide internal signal.

Lookup labels: interoception; interoceptive signal; internal sensations

Interoceptomics

How does the body sense a heartbeat or its breathing, and how are the nerve connections involved arranged? Interoceptomics brings those questions together in a proposed study, relating observations of internal-body sensing to maps of the connections carrying or processing that information.

A proposed field combining interoception and connectomics to study internal-body sensing and its relationships with neural connectivity across scales.

The programme uses Interoceptomics as an umbrella for this proposed research. Giving the work a name does not establish a validated comprehensive map or a recognized external standard.

Scope: macro: Whole-body, organ and network relationships relevant to internal-body sensing; micro: Local signals, cells, circuits and interfaces relevant to those relationships.

Organizational level: whole system; network; organ; local circuit; cell; signal/feature

Lookup labels: interoceptomics

Keeping each source separate

Keeping track of which recording, channel, time and physical setting a value belongs to.

A channel numbered 12 in one day is not automatically the same cell as channel 12 on another day. A software label also cannot prove where supplied data physically came from.

Lookup labels: Source conditioning; source-conditioned; source-specific; recording-specific

Keeping each trial together

Assigning an entire trial to one data portion instead of dividing it among portions.

This prevents pieces of the same trial from being shared between the relevant splits. It does not remove prior inspection or other source limitations.

Lookup labels: Whole-trial separation; whole-trial-separated; successful trial; trial partition

Keeping up now and computing for later

Real-time computation keeps pace with incoming data; offline computation can take longer and be played back later.

Native planning takes about 4.52 seconds for a 20 ms simulated step and is offline. Smooth cached playback does not prove live planning or biological control.

Lookup labels: Real-time and offline execution; real-time; offline; paced playback; cached reference

Kind of measurement

What a method records, such as electrical spikes, scalp voltage, muscle electrical activity or a brain-scan signal.

These signals measure different things. They cannot be treated as interchangeable numbers merely because all of them relate to the nervous system.

Lookup labels: Signal modality; modality; observation process

Large Movement Model

The shorthand “NeuroTranslate with MoCap MyoSim = Large Movement Model” names the proposed combination of NeuroTranslate, MoCap ReComp and MyoSim Replay. It brings a learned mapping, measured movement and virtual mechanics into one architecture. The equals sign is not a mathematical identity or evidence of a trained model. EEG, EMG, measured movement, virtual mechanics and the learner retain their distinct roles.

The proposed movement-focused learned model that brings neural structure and functional observations together with internal musculoskeletal anatomy and independently measured external movement in a declared task.

The programme model-family name, analogous in ambition to large language model. It does not replace accurate technical architecture descriptions or mean that every DNN is a movement model. Scans and capture alone do not train a model. Parameter count, scale, generalization and nervous-system fidelity require evidence. System 3 thinking remains the partnership framing.

Lookup labels: large movement models; LMM; Large movement model

Lasting change in the nervous system

Changes in the nervous system that can contribute to learning or adaptation.

Updating software weights or controller gains is a different event. The practice interface in the computer model does not measure synaptic change in a living organism.

Lookup labels: Biological plasticity; synaptic plasticity; biological learning

Learning before the final task

Training first on another objective, such as predicting a later neural count, before training for a paired movement target.

The paper calls this pretraining. Earlier source-task labels remain part of the information the model received, even when only new-setting labels are counted in a small budget.

Lookup labels: Pretraining; neural next-bin pretraining

Mapping movement onto another body model

Turn a specified movement quantity, such as fingertip velocity components, into movement goals for a particular computer body. The mapping depends on that body and the chosen task.

Mapping specified movement quantities into goals for a particular body model, with the source quantities, target coordinates and transformation declared. This does not by itself reconstruct full posture or demonstrate biological transfer.

The retained source-specific adapter takes two macaque fingertip velocity components as its source and produces human-model shoulder and elbow goals. Their signs carry direction; scalar speed would discard it. These are goals for that model and task, so the mapping establishes neither cross-species skill transfer nor verified biological function.

Lookup labels: Retargeting; body adapter; organism-specific body adapter; joint goal

Meme-jacking

Borrow the recognition; earn the explanation. A familiar image should help the audience see the scientific point before the script develops it.

Use a recognizable meme or cultural reference to make a scientific point immediately legible, drawing on familiarity already earned by others.

Memification hijacking is the user's expansion. References may come from any online culture, not only films. Apply one purposeful reference per teaching concept without crowding formal methods or labels. Recognition does not grant reuse rights, endorsement, proven comprehension or scientific validity. Preserve the original Meme-ification history.

Lookup labels: meme-ification; memeification; mimification; Meme-ification; meme-jacking; meme jacking; memification hijacking

Meme-ification/memeification are spelling forms; mimification is retained only as the corrected historical transcription.

Mixed-source animal and added tissue

A chimera has biological contributions from different sources. A graft is added tissue; when it crosses species, it is a xenotransplant. An organoid is an organized tissue model.

Survival, physical connection, activity and useful function are separate questions. The proposed comparisons do not establish a humanized whole brain or an implemented treatment.

Lookup labels: Chimera, graft and organoid; chimera; chimerism; graft; organoid; host–graft; xenotransplant; xenograft

Model that chooses a label

A statistical model that assigns scores to categories, such as the ten attempted-finger labels.

The selected human model uses logistic classification, but its scores do not establish validated confidence in biological truth. Its reported accuracy comes from development data that have already been seen.

Lookup labels: Logistic classifier; logistic regression; classifier; classification; logistic

Model weights kept fixed

Keeping the fitted numbers in a model unchanged during a defined comparison.

The tested transfer trains a connector while retaining the older main model. Fixed weights make the comparison clear; they do not prove biological sameness across days.

Lookup labels: Frozen parameters; frozen trunk; frozen readout; frozen checkpoint

Modeled route from one muscle attachment to another

The route and length assigned to a muscle and tendon as the model's joints move.

The native arm retains 39 named routes. Their modeled lengths differ from direct measurements of living tissue, muscle commands and force.

Lookup labels: Muscle-tendon path; musculotendon length; modeled muscle length; geometric path

Models that convert inputs or predict outputs

One model can turn an input into a representation; another can use available inputs to predict a named result.

The paper calls these encoders and decoders. Predicting counts from mechanics or mechanics from counts does not by itself show the biological cause of either.

Lookup labels: Encoder and decoder; encoding; decoding; readout; decode; encoder; decoder

MoCap ReComp

MoCap ReComp is Motion-Capture Relay-Composite: the proposed measurement component that brings views of the same movement into a common physical frame. It should preserve which view supplied each point, so the joined map can be compared with its original observations.

The proposal starts with two dot maps of the same moving body: one from above, one from below. Align their time and position in a common physical coordinate frame, then join them into one motion map while retaining the source of each point.

A proposed method that creates two dot maps (3D point clouds) of the same moving body, one captured from above and one from below, aligns them in time and a common physical coordinate frame, then stitches them into one composite motion map while retaining each point's source.

To compare the same movement from above and below, the proposal must align both streams in time and a common physical coordinate frame while retaining each observation's source. Bidirectional denotes those opposing measurements, not neural communication or causal direction. LiDAR ranging and infrared optical motion capture are proposed alternatives; marker triangulation and LiDAR point clouds are different measurements, so the actual modality and camera/ranging geometry must be qualified. The maze geometry calls for measurements perpendicular to the floor, with viewing

paths from both sides through material intended to be clear. Transmission and material effects need testing; concentrated and distributed arrays remain alternatives. Hardware, coverage, timing, calibration, spatial alignment, occlusion, motion error and latency require validation against real references. The joined map is a derived record, not a direct observation of hidden joints, tissue mechanics, muscle commands or neural function. Neither successful implementation, complete body reconstruction nor material transparency has been established by the name. The single vertical camera illustration remains schematic.

Geometry: Declare the top/bottom sensor positions, measured object, coordinate frame, viewing/illumination paths and coverage. Preserve the requested perpendicular-to-maze-floor geometry; document deviations rather than inferring them from an illustration.

Modality: Declare LiDAR ranging or infrared optical motion capture, including marker-based/markerless method, camera count, triangulation geometry, material path and actual calibration. No complete reconstruction or physiological writing follows from opposing views.

Timing: Record source timestamps, clocks, acquisition cadence, synchronization error and any interpolation, offline processing or end-to-end latency. No real-time capability is assumed.

Calibration and registration: Preserve calibration data and transformations placing both streams into a common physical frame; measure registration error and keep original observations and reconstruction steps traceable.

Limits: Record overlap, occlusion, missing observations, material effects, uncertainty and failure cases. Opposing measurements alone do not prove complete 3D pose, forces or biological function.

Physical scale: Declare measured distance ranges and units for an actual acquisition; no supported numeric range or physical unit assignment is presently available for this proposal.

Statistical aggregation: Declare any chosen evaluation grouping/averaging rule separately from physical scale and computational granularity.

References and acceptance: Use the Reference Comparison Protocol and unfilled record to identify the real-reference series needed for each acquisition component and the assembled map. Its provenance, rights, organism-stage, physical-unit, modality, clock, calibration, occlusion, contact, independent held-out, error, uncertainty and acceptance fields remain unfilled and HOLD. It supplies no measured series or apparatus validation. The unchanged programme reference criteria and every stronger original requirement govern their respective claims; no acceptance threshold is introduced or relaxed.

Outputs: Retain the top dot map, bottom dot map and joined map as separate traceable outputs. Their timestamps and common-frame transformations must be explicit; do not fill unobserved regions as though they were measured.

Scope: proposed application: Complementary top/bottom motion measurements of a body moving through the maze; concentrated coordinated platforms and distributed arrays remain alternatives; measurement boundary: Observed distances or geometry

remain distinct from registered/stitched composites and any model-estimated pose or musculoskeletal quantity.

Organizational level: whole system; signal/feature

Computational granularity: top dot map (3D point cloud); bottom dot map (3D point cloud); time alignment and spatial registration; joined composite motion sequence

Lookup labels: motion capture composite relay; motion-capture composite relay; motion capture composite; bidirectional composite motion capturing using LiDAR; Motion capture composite relay; motion capture relay composite; motion-capture relay composite; bidirectional LiDAR; opposed-view infrared motion capture; bidirectional infrared; motion-capture relay-composite; Motion-Capture Relay-Composite

Historical spellings name this same proposed capture method. Relay here means passing captured measurements onward; the separate agent-coordination Relay protocol does not describe motion capture.

Movement brain area

A brain area involved in movement. The paper uses the names motor cortex, MC and M1 for relevant source recordings.

The signals help predict recorded movement-related targets. Knowing the brain area does not identify matching cells across recordings or reveal a whole-body command pathway.

Lookup labels: Motor cortex; M1; MC; primary motor cortex

Muscle electrical recording

Electrical activity recorded from muscles; the method is called EMG.

Muscle electrical activity differs from force and from the computer model's command and activity states. The trained targets here are rescaled signal summaries.

Lookup labels: Electromyography; EMG

MyoSim Replay

MyoSim Replay is the proposed MusculoSkeletal Simulation Physics-Engine. Declared anatomy, mechanical parameters and control inputs would produce movement predictions to compare with independent measurements. The external MyoSim body-model collection is a separate resource. Simulation replay is not a measured biological replay.

The proposed digital model would calculate how muscles and the skeleton move and exert forces, with real measurements used to check its predictions.

The proposed physics-based simulation component that models specified muscles, bones, joints and their mechanical interactions, using declared anatomy, parameters,

forces and contact rules, with predictions tested against independent movement and other applicable physical measurements.

In the proposed five-component arrangement, declared anatomy, muscle/control inputs and physical context would drive a simulation of movement and forces. The motion-capture relay-composite would provide traceable measured movement to compare with those predictions. That comparison needs matching timing, coordinates, units and calibration, and tests that preserve anatomical and physical constraints, uncertainty, held-out cases, baseline controls, a series of real references and independent acceptance. Movement geometry alone does not measure muscle activation, internal forces, hidden neural state or subjective experience; force, activation and causal claims need additional independent references. Visual effects (VFX) rendering shows the model but cannot validate its mechanics. This remains a proposed simulation component, not a newly demonstrated implementation or external scientific field. Approximate simulation and biological virtualization verified within declared error bounds remain distinct; this component establishes neither universal precision nor whole-body completeness.

Scope: programme role: Virtual-body mechanics component; initially constrained hand and foot tasks; inputs and outputs: Declared anatomical parameters, muscle/control inputs and physical context produce simulated movement and mechanical quantities. Independently acquired motion and other necessary observables remain references, not simulator ground truth.

Organizational level: whole system; organ

Computational granularity: musculoskeletal model; mechanical solver; measurement-to-prediction comparison

Lookup labels: musculoskeletal simulation physics engine; musculoskeletal-simulation physics engine; musculoskeletal simulation; musculoskeletal physics model; musculoskeletal-simulation physics-engine; MusculoSkeletal Simulation Physics-Engine

Names used for source subjects

Indy, Han and Monkey L label macaque sources; N1 labels the human finger source.

These labels keep different subjects separate. Similar brain-region or task names do not make them one synchronized recording.

Lookup labels: Source subject labels; Indy; Han; Monkey L; N1

Nerves bringing body information in

Afferent paths carry body-related information toward the brain and spinal cord, together called the central nervous system.

For example, a limb-related sensory signal can travel inward. The source-specific cortical predictions do not measure this whole path or make missing nerve activity observed.

Lookup labels: afferent; afferent pathway; body-to-CNS; CNS; central nervous system

Nerves carrying commands out

Efferent paths carry outputs from the brain and spinal cord toward the body, including muscles and organs.

A prediction of movement is not a recording of that outward pathway. The prototype does not supply a synchronized voluntary sequence through spinal cord, nerves and muscles.

Lookup labels: efferent; efferent pathway; CNS-to-body

Neural decoding

Estimating declared information such as intended action from recorded neural observations using a specified model.

Decode accuracy, channels, source identity, task and held-out domain must be demonstrated. Brain-only control requires exclusion of covert muscle, eye and motion signals; decoding does not write signals into the brain.

Organizational level: Declared game/model/interface role

Computational granularity: Declared task-specific model or interface

Statistical aggregation: Validation scope declared per experiment; no physical-scale inference

Source: Restoring cortical control of functional movement in a human with quadriplegia

Source identifier: bouton2016

DOI: 10.1038/nature17435

https://www.nature.com/articles/nature17435

Research precedent linking implanted cortical recording to a custom neuromuscular stimulation sleeve; not an EEG/OpenBCI or elite-skill result

Source: A brain-computer interface that evokes tactile sensations improves robotic arm control

Source identifier: flesher2021

DOI: 10.1126/science.abd0380

https://pubmed.ncbi.nlm.nih.gov/34016775/

Research precedent for motor decoding plus sensory feedback through intracortical microstimulation; invasive and not a consumer EEG capability

Neural encoding

Mapping declared information to a representation in neural activity; in a sensory-interface design, constructing candidate stimulation patterns for specified feedback.

A computational encoder is distinct from a qualified stimulation device and evidence that a participant receives the intended sensation. The term does not mean arbitrary thought writing or skill upload.

Organizational level: Declared game/model/interface role

Computational granularity: Declared task-specific model or interface

Statistical aggregation: Validation scope declared per experiment; no physical-scale inference

Source: A brain-computer interface that evokes tactile sensations improves robotic arm control

Source identifier: flesher2021

DOI: 10.1126/science.abd0380

https://pubmed.ncbi.nlm.nih.gov/34016775/

Research precedent for motor decoding plus sensory feedback through intracortical microstimulation; invasive and not a consumer EEG capability

Neural Replay

Revisiting a stored sequence of neural samples with its stated timing and channel order.

This playback is not a live recording or instructions for stimulating a nervous system. A displayed arm movement does not show what the source animal's muscles actually did.

Lookup labels: Neural replay; recorded replay; archived replay; cached playback; Playing back a recording

NeuroArcher

A proposed archery game that studies coordinated use of both hands and arms through physical motion control, brain-signal control of a digital body, and a separately admitted later assisted-body experiment.

The near-term prop is a toy bow with small suction-cup tips and an over-arm arrow pouch. Target/creature choice is unresolved. Simulated performance does not establish muscle stimulation or retained biological archery skill.

Organizational level: Declared game/model/interface role

Computational granularity: Declared task-specific model or interface

Statistical aggregation: Validation scope declared per experiment; no physical-scale inference

Lookup labels: Neuro Archer

NeuroBoxer

A proposed boxing game that compares arm-motion control, brain-signal control of a digital body, and a separately admitted later assisted-body experiment.

Prime-era Mike Tyson is the requested virtual opponent and meme reference. A game, recorded prediction, stimulation-assisted motion and retained biological skill learning need different evidence. No actual opponent, head contact, finished game or stimulation capability is claimed.

Organizational level: Declared game/model/interface role

Computational granularity: Declared task-specific model or interface

Statistical aggregation: Validation scope declared per experiment; no physical-scale inference

Lookup labels: Neuro Boxer

NeuroConnectome

A map of specified neural connections used to constrain a model of the nervous system.

Connectome is the established term. The user's NeuroConnectome label does not establish complete coverage or identify functional dynamics, state, plasticity, sensory context or unique thought from wiring alone. Declare species, anatomical coverage, resolution and provenance.

Lookup labels: Neuroconnectome

Neuromuscular electrical stimulation

Electrical stimulation intended to elicit muscle contraction through the relevant neuromuscular pathways.

NMES is a writing/actuation intervention, whereas EMG records muscle activity. EMG electrodes or an OpenBCI recording board do not by themselves provide qualified stimulation. Neither contraction nor imposed movement demonstrates retained skill.

Organizational level: Declared game/model/interface role

Computational granularity: Declared task-specific model or interface

Statistical aggregation: Validation scope declared per experiment; no physical-scale inference

Lookup labels: NMES; Electrical muscle stimulation; EMS

Source: Restoring cortical control of functional movement in a human with quadriplegia

Source identifier: bouton2016

DOI: 10.1038/nature17435

https://www.nature.com/articles/nature17435

Research precedent linking implanted cortical recording to a custom neuromuscular stimulation sleeve; not an EEG/OpenBCI or elite-skill result

Neuroscience recording files

NWB stores neuroscience data and descriptions. In the paired source files here, SET holds recording descriptions and FDT holds binary samples.

A stale unit in the NWB muscle source must not override verified processing. SET headers match source hashes; FDT previews have checked local byte ranges rather than full verification of each upstream file.

Lookup labels: Neuroscience recording files; Neurodata Without Borders file; NWB; Recording header and sample file; SET and FDT files; SET; FDT; EEGLAB header; byte-range preview

NeuroTransfer

Specify what would move between which systems, then test what the recipient can do with and without assistance.

The proposed transfer of specified task-relevant information or a mapping between declared systems, with assistance and retained learning evaluated separately.

The label does not establish a successful biological transfer or retained skill. A weight copy, recorded replay, guided movement and independently retained learning answer different questions. Each proposed interface needs its own source, target, task, controls, rights and qualified outcome.

Lookup labels: neurotransfer

NeuroTranslate

Brain2Body Neural Activity is the long-form component label paired with NeuroTranslate in this proposed architecture. Recorded activity is an observation. NeuroTranslate names the mapping operation that could relate specified observations to movement, or reconstruct specified recorded features in the reverse direction. The observation, learned relationship and predicted value remain different things.

State the observations, the target and the task, then test how well the mapping works.

The proposed operation of mapping specified neural and body observations between declared inputs and targets in a stated task.

A model could predict movement from specified observations, or reconstruct specified recorded features in the reverse direction. Each direction needs its own test in the stated task. Neither establishes a unique hidden state, sensory delivery or biological skill transfer. NeuroTranslate names this proposed mapping operation; NeuroTranslation names the field and NeuroTranslator the implemented software.

Lookup labels: neurotranslate; NeuroTranslate; Brain2Body Neural Activity

NeuroTranslation

How could a particular neural recording be related to a defined movement task? NeuroTranslation is the proposed study of mapping nerve signals and the patterns that describe them between clearly defined situations like these. Every mapping must state where its inputs come from, what its outputs mean, and how it is tested.

A proposed field for translating or mapping neural signals and representations between explicitly defined source and target domains, with stated context, scale, tests and limitations.

Each connection must be assessed against its named source and stated test. The project has not demonstrated a universal brain language or an uploaded skill.

Scope: macro: Relationships between neural systems, body systems and defined tasks or organisms; micro: Mappings involving identified local signals, channels, features and circuit-level representations.

Organizational level: whole system; network; organ; local circuit; signal/feature

Lookup labels: neurotranslation; neural translation; Connecting neural recordings to defined tasks; Neurotranslation

NeuroTranslation Network

A plan for connecting more neural and body components while keeping the origin and meaning of each value clear.

The proposed network would connect neural and body components while carrying the origin and meaning of each value through the mapping. Each link could then be examined in its own recording context. Body-wide translation and biological teaching remain unproved.

Lookup labels: Source-Conditioned Neurotranslation Architecture; SCNA; Neurotranslation Network

NeuroTranslator

The software that joins particular recordings, prediction models, playback and computer-body checks.

Predictions and playback can be checked against the particular recordings they use. That is the scope of the implemented NeuroTranslator; neither a universal brain language nor skill upload has been demonstrated.

Lookup labels: Neurotranslation Engine; NTE; Neurotranslator

Numerical arrays, saved arrays and prediction

NumPy provides tools for numerical arrays. NPZ saves arrays; inference means running a trained model to produce an output.

Portable execution still needs the correct processing and source identity. Matching saved-model outputs does not establish success on new organisms or biological skills.

Lookup labels: NumPy inference and NPZ archive; NumPy; NPZ; portable inference; inference

Numerical checks on allowed movement

Checks that the computer model stays defined and within its stated joint limits.

Joint-limit penetration means going past an angular bound, not entering tissue. The 0.001 rad tolerance is a numerical rule, not a certificate of correct neural commands.

Lookup labels: Mechanical feasibility and anatomical tolerance; anatomical limit; limit penetration; finite state; joint range; numerical tolerance

Numerical software and its data file

MATLAB is numerical-computing software, and MAT is a format for its structured data.

The second Indy recording uses the original MAT source. The format does not prove matching cells, past-only source processing or complete observation.

Lookup labels: MATLAB and MAT file; MATLAB; MAT

Observe it, connect it, keep it useful

Observation burden, prediction on excluded cases and lasting task benefit need separate measurements. A clear picture does not answer those experimental questions.

Lookup labels: Access it, Ground it, Keep it; access; grounding; stability; signal stability

One multiplier for modeled lengths

A single number chosen to reduce differences between the model's muscle lengths and the source-derived length references.

The number is fitted on training poses and checked on distinct observed poses. It is not complete body calibration; no movement-control experiment is run on the scaled candidate.

Lookup labels: Scalar length fit; global length factor; uniform factor; a*; scalar bridge; recording length-fit candidate; SDK-scaled candidate

One recording period

One experiment or recording period with its own subject, channels, timing and task.

Two recording days, or recordings from different animals, do not form one observed nervous system simply because the files are loaded together.

Lookup labels: Recording and session; source recording; session; recording family

Open body-model collection

MyoSim supplies computer-body models with muscles and bones, including models used in this project.

The collection is earlier work, not a new project invention. Availability of an arm model does not establish matching macaque and human muscles or neural commands.

Lookup labels: MyoSim, MyoSuite and MyoArm; MyoSim

Open muscle-control task tools

MyoSuite provides tasks and tools for experiments with muscle-driven computer-body control.

It is earlier software reused here. Success on a simulated task is not proof of biological learning or a recovered neural command.

Lookup labels: MyoSuite

Other published models of neural recordings

NDT2 learns patterns across recordings made inside the cortex, the brain's outer layer. POYO handles differing sets of recorded neural features by representing events and learning relationships between them.

The paper cites these as earlier work. It does not claim to have implemented them or use their existence as proof of universal transfer or matching cells.

Lookup labels: Other published models of neural recordings; NDT2; large-scale neural pretraining; Published model for varying recorded populations; POYO; neural-event tokenization; cross-attention bottleneck

Passing information and gaining a lasting skill

Receiving useful task information differs from acquiring a durable ability that works independently in new conditions.

A short software label budget is not measured biological practice time. Sewing, cube solving and breakdancing remain future examples without matched skill recordings here.

Lookup labels: Task information transfer and skill acquisition; task transfer; skill transfer; skill upload; compressed acquisition; learning speed; learning; physical skill learning; skill acquisition

Past-only inputs and processing that uses later data

The local model uses completed past inputs. Some earlier source processing may still have used later samples.

Past-only indexing cannot reverse earlier filtering or rescaling that used the whole recording. It does not certify the full measurement-to-output delay in a living system.

Lookup labels: Causal indexing and acausal preprocessing; causal; algorithmic support; acausal filtering; offline interpolation; upstream filtering delay

Peripheral nerve electrical recording

A method for recording electrical signals associated with peripheral nerves, called ENG.

The human preview contains aggregate electrical observations. It does not provide separately identified nerve-cell spike trains or a complete voluntary command sequence.

Lookup labels: Electroneurography; ENG; surface ENG; peripheral recording

Placing body parts from joint positions

Calculating where body parts and muscle routes lie when joint positions are given.

The formal name is forward kinematics, or FK. It places geometry; it does not calculate muscle-driven motion through time or recover muscle commands.

Lookup labels: Forward kinematics; FK; kinematic replay

Planned commands, corrections and constant input

A planned command is feedforward; adjusting it from current model information is feedback; a constant muscle input is tonic control.

The human correction can change the bounded command goal. Recorded movement stays a scoring reference, and the native correction candidates remain rejected against constant-input comparisons.

Lookup labels: Feedforward, feedback and tonic control; feedforward; feedback; corrected controller; tonic excitation; constant tonic

Prediction score compared with a mean-value guess

R^2 compares squared prediction errors with a constant mean-value reference. Higher values usually indicate better prediction on the stated data.

The score can be negative. Different recordings, target processing and ways of combining outputs prevent treating all R^2 values as directly comparable.

Lookup labels: Coefficient of determination; R^2; R2; R^2; variance explained

Processing within spinal and peripheral pathways

Body-related information can be processed locally in spinal and peripheral structures rather than passing through one simple unchanged wire.

A cortex-only prediction does not observe those local processes. The separate recordings and computer-body checks do not establish a complete measured brain-to-body causal chain.

Lookup labels: local spinal processing; local peripheral processing; spinal/peripheral processing

Programmable neurobiology

The proposed ability to specify a bounded nervous-system or sensorimotor outcome, select a qualified intervention, predict its effects, measure what happens and adapt within a validated closed loop.

Scope: Brain, spinal, peripheral, muscle, mechanical and sensory feedback roles need separate evidence. Bidirectional prediction is different from safe sensory/action writing. An intermediary may improve a mapping without making it one-to-one. Arbitrary skill upload or universal disease/disability repair is not demonstrated.

Organizational level: Declared system or interface

Computational granularity: Declared process/interface/model

Statistical aggregation: Validation domain stated independently of physical scale

Programmable synthetic biology

Engineering specified biological behaviours by combining design, context-dependent molecular prediction, experimental measurement and iterative correction.

DNA/regulation, RNA/cell state and protein/interactions are explanatory layers, not a sufficient literal three-model recipe. Metabolism, feedback, environment and measured function matter. AlphaGenome and AlphaFold do not jointly certify whole-cell programmability; AlphaTranscriptome is a desired capability placeholder here.

Organizational level: Declared system or interface

Computational granularity: Declared process/interface/model

Statistical aggregation: Validation domain stated independently of physical scale

Lookup labels: Programmable molecular biology

Public reaching recordings

Public files pairing cortical electrical events with reaching behavior. The sources use names such as RTT and MC_RTT.

The original model's release and the separately acquired Indy day have different processing. Their dates and target definitions must remain explicit.

Lookup labels: Reaching source archive; RTT; MC_RTT; MC_RTT; O'Doherty reaching archive; Sabes reaching corpus

Public source records and document links

Repositories such as DANDI and OpenNeuro identify source versions. PDF is a document format, and a URL gives a resource location.

Source licenses and credit must be retained. A local paper draft or public input dataset does not mean the project's new code is published, licensed or submitted to arXiv or a journal.

Lookup labels: Public records, document files and links; DANDI; OpenNeuro; PDF; URL; arXiv; public deposition; license; attribution

Published models for brain scans and scalp recordings

BrainLM learns from fMRI brain-scan data. Neuro-GPT combines an EEG input model with a model of changes over time and is discussed for motor imagery.

These are earlier methods for different measurements. The project does not claim to have trained them, make scans and electrical spikes interchangeable, or upload skills.

Lookup labels: Published models for brain scans and scalp recordings; BrainLM; Published model of scalp signals; Neuro-GPT; NeuroGPT

Published neural-model comparison tasks

The Neural Latents Benchmark, or NLB, provides shared tasks for comparing models of neural recordings.

It informs the choice of comparisons. The paper's own local scores are not official NLB benchmark scores.

Lookup labels: Neural Latents Benchmark; NLB

Published tests of changing recordings

FALCON is a published benchmark concerned with neural decoding when recordings change and recalibration is limited.

The paper uses related source recordings and its own data splits. Its local muscle-signal scores are not official FALCON scores.

Lookup labels: FALCON benchmark; FALCON; FALCON M1; FALCON M1-A

Ranges that need statistical assumptions

A confidence interval gives a range for a quantity being estimated. A conformal prediction range tries to contain a future actual result at a stated frequency when its required assumptions hold.

The transfer figure shows one fixed run. The paper's ranges are based on earlier prediction errors, with related errors across time; they do not guarantee how often future true values will fall inside.

Lookup labels: Ranges that need statistical assumptions; Confidence interval and conformal coverage; confidence interval; repeated-seed interval; Prediction range with tested coverage; conformal; conformal coverage; prospective-conformal; distribution-free coverage

Recent-signal model

A model component that keeps a learned memory of recent inputs as it predicts the next result.

Its formal name is gated recurrent unit, or GRU. This established method uses completed input history; its memory does not establish a universal neural language.

Lookup labels: Gated recurrent unit; GRU; compact recurrent model; recurrent network

Record of what was observed

A record showing which channels or intervals were actually measured and usable.

Missing observations stay missing; they do not become zeros. The second Indy source does not supply separate observation intervals for every recorded unit.

Lookup labels: Observation mask; observation interval; invalid support; missing observation

Recorded neural events

A spike is an electrical event identified in a recording. A spike train is the sequence of those events over time.

A recorded event count is a whole number tied to one channel and time interval. A model's average expected count can be a fraction and is a different kind of value.

Lookup labels: Spike and spike train; neural event; spike count; spike train

Records linking files, checks and claims

A manifest lists specified files and identities; a receipt records checks; an evidence matrix links a claim to its supporting record.

These records also keep failures and withdrawn results visible. A catalog listing does not show that every dataset was acquired or used to train a model.

Lookup labels: Manifest, receipt and evidence matrix; manifest; source manifest; audit receipt; processing receipt; evidence matrix; withdrawal record

Relay

Pass focused work between agents, then check their results before accepting it.

A manual coordination protocol that passes bounded work and verified evidence between specialist sessions, with one integration owner and an independent acceptance reviewer. Each session follows the currently authorized model, effort and speed routing.

A specialist can work on a bounded question while an independent reviewer checks its evidence before the integration owner accepts it. This is a project coordination workflow, distinct from an established external standard or native Ultra mode. Efficiency and quality claims apply only to tested tasks; universal performance equivalence and a 50 percent weekly saving remain undemonstrated.

Computational granularity: finite delegated tasks and evidence artifacts

Lookup labels: relay; manual Relay protocol; Relay coordination

Rescaled muscle signal

A processed summary of muscle electrical activity put onto a relative scale.

The 16 targets have no physical voltage unit. A stale millivolt label in the source does not make them measured voltage, force or muscle activation.

Lookup labels: Normalized EMG envelope; EMG envelope; quantile normalization; dimensionless EMG

Rescaling using training data only

Learning a rescaling rule from the training portion, then applying the same rule to later values.

This avoids using local test values to fit that rule. It cannot undo source processing that already used future samples or the whole recording.

Lookup labels: Training-only normalization; scaler; target statistics; normalization

Response after an electrical stimulus

An electrical recording made while observing the response to a stimulus.

The human preview is a stimulus-response experiment, not voluntary movement. The stimulus itself can also leave an unwanted signal in the recording; that is an artifact.

Lookup labels: Evoked potential and stimulus artifact; evoked stimulation; evoked recording

Results already seen during development

Results that have been inspected and can therefore influence later decisions.

The human 90% result and local motor test windows have this limitation. They can be reported, but their later reuse is not a new independent test.

Lookup labels: Development evidence; development holdout; pilot; descriptive local test; inspected test

Reusing learning in another recording

Trying to use information learned in one setting to improve performance in another.

The comparison must state the new-setting labels and the controls. The reported frozen motor transfer and unadjusted human cross-day result do not establish successful biological or cross-species transfer.

Lookup labels: Cross-recording transfer; transfer; cross-day transfer; cross-species transfer

Routing a muscle around a modeled obstacle

A rule bends a modeled muscle route around an obstacle. One obstacle shape, a torus, is shaped like a doughnut.

The correction restricts three elbow wrapping rules to a stated attachment segment. It removes reproduced route errors without deleting a muscle or claiming a new anatomical measurement.

Lookup labels: Muscle wrapping and torus; wrap; wrapping route; torus; ELBOW_ULNA; ELBOW_ULNA; off-torus contact

Saved model and matching-output check

A checkpoint saves a model's state. A parity check asks whether another execution produces the specified matching output.

Repeating a result needs the same support, ordering, conversions, data splits, settings and body-model version. Passing software checks does not certify biological validity.

Lookup labels: Checkpoint and parity; checkpoint; replay/checkpoint parity; model parity; reproduction

Scalp electrical recording

Electrodes on the scalp record electrical potential; the method is called EEG.

This is an aggregate electrical signal, not a list of individual cortical spikes. The project's paired preview follows electrical stimulation rather than voluntary motor training.

Lookup labels: Electroencephalography; EEG; scalp potentials

Settings needed to repeat a run

The numbers and choices fixing one training run's starting point and procedure.

One fixed run can be reproduced. It does not show how results vary across repeated starts, animals or future recording days.

Lookup labels: Random seed and configuration; seed; single-seed; fixed protocol

Shared internal model

A model can learn an internal pattern and reuse that pattern when making several predictions.

The paper calls the pattern a latent representation and the reusable model a backbone or trunk. The tested shared model and frozen-transfer candidates were rejected.

Lookup labels: Latent representation and backbone; latent model; shared latent; backbone; trunk; shared parameters

Simple weighted prediction model

A linear model that combines inputs using fitted weights while discouraging excessively large weights.

The formal method is ridge regression. It provides a meaningful comparison: a more complex model must add value rather than merely produce a plausible display.

Lookup labels: Ridge regression; ridge; linear control; linear model

Simplicity principle

Introduce one concept or element at a time, using separate slides or successive reveals according to what makes the relationship easiest to understand.

Introduce each new element on its own, then show how the elements connect. Use separate slides or successive reveals to make the logical relationship visible. Simplicity cannot remove scientific qualifications, evidence, source rights or required methods. Actual comprehension and exported readability still need review.

Small connector model

A smaller fitted mapping that connects one recording to an existing model or interface.

The connector can change while the older model stays fixed. That does not establish matching neurons or useful transfer without new-setting calibration.

Lookup labels: Adapter; linear adapter; recording adapter

Software that calculates a computer body’s motion

MuJoCo calculates how a modeled body moves under forces and control inputs.

It is established software reused here. Its availability does not prove that the chosen body model or mapping matches a particular animal's physiology.

Lookup labels: MuJoCo; dynamics engine

Spine2Body

A muscle signal becomes a movement through tendons, joints, contact and load. Measure those steps together, and a failed reach becomes a specific question about activation, coordination or mechanics.

The pathway through which spinal output reaches peripheral motor nerves and muscles, producing action through the body's mechanics, while sensory signals return from the body.

Surface EMG measures muscle electrical activity, not peripheral nerve firing or force. Spinal plasticity, momentary reflex modulation and peripheral adaptation remain distinct. Simulated movement is a prediction to compare with independent measurements.

Organizational level: whole system; network; signal/feature

Lookup labels: spine2body; spine to body; spine-to-body

Stopping training under a stated rule

Ending training when the chosen development rule says to stop, rather than always using every allowed round.

Compared methods have equal round limits but can perform different numbers of actual updates. This is not measured biological learning time.

Lookup labels: Early stopping; epoch cap; training update

Structured task text and supported instructions

JSON stores structured text values. The task compiler converts a supported instruction into a defined program.

The compiler chooses available recorded building blocks and limited computer-controller practice. It does not program arbitrary biological skills or supply missing task evidence.

Lookup labels: JSON and task compiler; JSON; task JSON; natural-language compiler; supported primitive

Surface electrical recording over the spine

Surface electrodes placed over spinal regions record electrical potentials; the method is called ESG.

These measurements combine electrical contributions. They are not separately identified spinal-neuron spike trains.

Lookup labels: Electrospinography; ESG; surface spinal recording; surface ESG

System 3 thinking

System 3 thinking is the partnership; a large movement model is the movement-focused model we aim to build within it.

The programme's human–AI partnership framing in which an external supervisory model helps interpret, train or calibrate task-specific neural/body mappings; the movement-focused model being built is called a large movement model.

Expert footage provides movement examples, but it does not supply the depicted experts' neural or muscle recordings. An external supervisor would help interpret, train or calibrate task-specific neural/body mappings while the large movement model remains the movement-focused model being built within that partnership. Shaw and Nave use System3 for artificial cognition outside the brain in a different research account. This programme's task-specific framing establishes no new anatomical brain layer, biological neo-neocortex, third anatomical thinking system or achieved universal nervous-system model.

Organizational level: Declared game/model/interface role

Computational granularity: Declared task-specific model or interface

Statistical aggregation: Validation scope declared per experiment; no physical-scale inference

Lookup labels: System three thinking; System3 thinking

Source: Thinking—Fast, Slow, and Artificial

Source identifier: shaw-nave2026

DOI: 10.2139/ssrn.6097646

https://papers.ssrn.com/sol3/papers.cfm?abstract_id=6097646

Prior proposed System3 usage for artificial cognition outside the brain; not an established third anatomical brain system

Source: Thinking Fast, Slow, Artificially: AI and Your Brain

Source identifier: wharton-authors2026

https://executiveeducation.wharton.upenn.edu/thought-leadership/wharton-at-work/2026/05/thinking-fast-slow-and-artificially/

Primary institutional account of Shaw and Nave System3 research

Testing on an excluded day, animal or species

Checking a model on complete identities that were kept out of the relevant development steps.

The paper uses formal names such as leave-session-out or leave-species-out. A good score within one session does not answer these broader tests.

Lookup labels: Leave-out generalization; leave-session-out; leave-animal-out; leave-species-out; unseen-organism support

Testing possible next actions in the model

Simulating near-future actions before choosing the next command.

The copied test states must not change the live model. The native result remains rejected and too slow for real-time use; cached playback is a separate function.

Lookup labels: Short-horizon planning and lookahead; horizon controller; lookahead; copied-state rollout; model predictive planning

The comparison needed to judge improvement

A defined comparison that shows whether the proposed method adds useful information or performance.

A simple predictor, random fixed model and constant muscle command answer different questions. Producing a plausible animation is not a substitute for beating the relevant comparison.

Lookup labels: Baseline and control; simple baseline; tonic baseline; random frozen control; behavior-only predictor

Thought2Action

Begin with one intention and one action: reach for the cup. Measure the neural, muscular and mechanical steps between them. The aim is to make that intent-to-action relationship as close to one-to-one as possible within the declared task, person, state, context and tolerated error.

A task-conditioned mapping from a participant's stated or inferred intent to a specified action, evaluated through independently measured outcomes.

Intent inferred from EEG is not direct access to private thought. Movement constrains competing explanations; it does not certify an achieved universal bijection or the best possible mapping.

Organizational level: whole system; network; signal/feature

Lookup labels: thought2action; thought to action; thought-to-action

Thought2World

Follow the intention all the way to its consequence, then follow sensation and perception back to the next intention. Measuring the middle makes errors easier to locate and the next experiment easier to define.

The composed pathway Thought2Action followed by Action2World: intent is translated into an action, and that action produces an outcome that can be independently checked.

This is a proposed programme pathway, not a claim of unrestricted thought control. It is not silently equivalent to the existing Body2World lookup label, Body2Action or Brain2Motion. External touch and movement tasks alone do not solve internal-body sensing or the full Interoceptomics programme.

Organizational level: whole system; network; signal/feature

Lookup labels: thought2world; thought to world; thought-to-world

Timing relationships between spikes

How closely spikes can repeat and how spikes from different recorded features occur together.

The project checks predicted average counts. It does not establish these finer timing relationships or a complete account of biological spike noise.

Lookup labels: Refractoriness and spike synchrony; refractoriness; joint spike synchrony; biological count-noise model

Touch brain area

A brain area that processes body-related sensory information. The source study records from somatosensory cortex, including Area 2.

The formal shorthand is S1. The selected model estimates an earlier limb state; it does not recover voluntary motor commands or spinal and nerve recordings.

Lookup labels: Somatosensory cortex and Area 2; S1; Area 2; Area2_Bump; somatosensory

Training a fresh model

Training a new model for the current recording without importing an older model's learned main weights.

This is the scratch specialist. It performs better than the frozen-transfer candidate in both reported label budgets.

Lookup labels: Scratch training; scratch specialist; new-recording scratch specialist

Training with neural samples without movement labels

Using neural samples for a training objective that does not require paired movement labels.

These samples still provide information and require computation. The first 5% label condition permits full training-neural support, so it is not only 28.5 seconds of total observation.

Lookup labels: Neural-only training support; neural-only pretraining; unlabeled neural support

Trying to move and actually moving

Trying or being cued to move is different from measuring the movement that occurred.

The human labels describe attempted finger movement. They do not independently separate cue from intent or provide executed finger trajectories.

Lookup labels: Attempted versus executed movement; attempted finger identity; cued attempted movement; executed kinematics

Typical error on the original scale

RMS or RMSE squares the deviations, averages them, and takes a square root so the result has the original unit.

An error per joint differs from a combined seven-joint error. An error against a changed command goal also differs from an error against the same recorded reference.

Lookup labels: Root mean square error; RMSE; RMS; root-mean-square; tracking error

Unassigned event channel

A channel collecting events not assigned to the sorted features used by the model.

These events are excluded from the 171 sorted features in the second Indy recording. They cannot silently become another identified cell.

Lookup labels: Residual or hash cell; residual/hash; hash slot; threshold crossing

Units for distance, speed and angle

Metres, centimetres, millimetres and micrometres measure distance. Metres per second measures speed; degrees and radians measure angle. Radians per second (rad/s) measures the rate of change of angle.

One metre is 100 cm or 1000 mm; one mm is 1000 µm. Right-angle and varied-angle maze layouts differ in geometry, not in a validated difficulty multiplier. Unit conversion or a small model error does not prove anatomical or decoded-pose accuracy.

Lookup labels: Length, velocity and angle units; m; metre; cm; centimetre; mm; millimetre; µm; micrometre; um; m/s; rad; radian; degrees; °; rad/s; orthogonal; nonorthogonal; varied-angle maze; maze layout

Units for pushes, turns and electrical potential

Newtons measure force; newton metres measure turning moment; millivolts measure electrical potential. A dimensionless value has no physical unit.

The handle record mixes force and moment units. The rescaled muscle targets are dimensionless despite a stale mV label and cannot be read as force or activation.

Lookup labels: Force, moment and voltage units; N; newton; N m; N·m; newton metre; mV; millivolt; dimensionless

Units for time and sample rate

Seconds measure time; milliseconds are thousandths of a second. Hertz counts repetitions or samples per second.

A 250 Hz source sample interval is 4 ms; a 500 Hz simulation interval is 2 ms. These rates differ from playback pace, biological travel time and time spent computing.

Lookup labels: Time and frequency units; s; second; seconds; ms; millisecond; milliseconds; Hz; hertz; sample rate; 250 Hz; 500 Hz

Unwanted stimulus signal in a recording

Part of a recording caused by the stimulus or measuring setup rather than the intended response alone.

Stimulus artifacts remain in the human previews. Their presence and the evoked task limit interpretation as voluntary motor evidence.

Lookup labels: stimulus artifact; artifact

Use in a new setting without labeled adjustment

Applying a learned model to a new setting without using its labels to adjust the model.

The second M1 model uses explicit new-recording labels. Its test score is a result after calibration, not zero-shot success.

Lookup labels: Zero-shot transfer; zero-shot

Velocity estimated from earlier positions

Two recorded fingertip positions can give an estimate of how fast the fingertip moved and in which direction between the samples. The signed components describe velocity; speed is its non-negative magnitude.

A position-derived velocity estimate formed from the difference between current and earlier recorded positions divided by their elapsed time; individual components retain sign. Speed is the magnitude of the velocity vector.

In the separate calibrated motor recording, each interval uses the last available fingertip sample and the actual elapsed time to form a velocity target in m/s. This makes the calculation causal with respect to available position samples, not proof that the tracker supplied them without filtering or delay. Upstream filtering and latency remain unestablished; the derived target is not an original, directly supplied velocity trace.

Lookup labels: Backward finite difference; backward difference; finite difference; causally derived velocity; 250 Hz position support; Speed estimated from earlier positions

Velocity of each model movement

The model's stored velocity for its movement degrees of freedom, including direction.

The formal variable name is qvel. Its signed generalized velocities depend on the model's degrees of freedom; speed is a magnitude. Component units and frames depend on the declared coordinate and model. In MuJoCo, quaternion orientations can make qpos and qvel different lengths, so qvel is not an entry-by-entry derivative of qpos.

Lookup labels: qvel; generalized velocity; joint speed; Speed of each model movement

What a model estimated

A model's estimate of a defined result, such as speed, from the inputs it was given.

An estimate remains an estimate even when it matches the test data well. It does not become a new measurement of the spinal cord, nerves or muscles.

Lookup labels: Decoded or inferred prediction; decoded; inferred; reconstructed; prediction

What an instrument recorded

A value produced by a stated measuring method, such as an electrode or a movement tracker.

Recorded data can contain noise, filtering or artifacts. Calculating muscle length from tracked markers does not turn that length into a direct tissue measurement.

Lookup labels: Recorded measurement; measured; observed; recorded signal

What the computer body produced

A value produced while running a computer model, such as a modeled muscle's activity.

Computer-body movement and forces can be checked for numerical errors. They remain separate from measurements of a living body and from evidence that an organism learned.

Lookup labels: Simulated quantity; simulated; numerical model state

What was calculated from tracking

A value calculated from measurements together with a body model, such as an estimated joint angle.

The study's joint angles and muscle lengths use tracked movement and a model. They are not direct recordings of muscle commands, tissue length or peripheral nerve spikes.

Lookup labels: Model-derived quantity; tracking-derived; source-derived; biomechanical covariate

Where a value came from

The record of a value's source and the steps used to produce it.

For example, a measured hand position, an angle calculated from that position and a computer-generated muscle state have different origins. The software must preserve those differences.

Lookup labels: Provenance; lineage; source integrity

Which recorded channel is which

The labels and order used to identify neural features within one recording.

The labels do not identify the same neurons across days. The project did not accept unverified matches between cells in different recordings.

Lookup labels: Source-local unit identity; ordered channel identity; cell correspondence; unit order; neuron index

Which samples a value depends on

The input history and exact time interval needed to produce a value or target.

A single timestamp does not show all of this support. Overlapping histories and invalid samples near data splits need explicit checks.

Lookup labels: Temporal support and context; support; history window; context; next-target support; overlapping histories

Composed pathways

The proposed intermediary has a positive purpose: understand and measure the processes between intent and action so the task-specific mapping can be made as close to one-to-one as possible. The task, participant, state, context, target and tolerated error must be specified and independently tested. This is an aim for identifiability and control, not an achieved universal bijection or a demonstrated optimum.

Form → function → action and intent → action describe connected questions. The following proposed pathways separate the links that would need independent tests before their combined prediction could be trusted.

Biological pathway: Brain2Spine → Spine2Body; resulting in Brain2Body

Relate brain activity to spinal processing, and spinal/peripheral processing to the body; compose the tested links into an intent-to-body-action pathway.

Functional pathway: Thought2Action → Action2World; resulting in Thought2World

Relate a declared intention to a measured action, and that action to its measured consequence in the task environment.

Molecular analogy: DNA → RNA; RNA → protein; resulting in DNA → protein

The intermediate processes explain how an initial specification reaches its downstream product. This analogy illustrates the need for a measured middle; it does not assert identical biology or a context-free one-to-one relationship.

System 3 engineering route: Neural activity → Musculoskeletal simulation → Programmable model

The proposed engineering route to NeuroTranslation, coordinated by the System3 human–AI supervisory model.

Paired source-bound brain/spinal/peripheral/muscle and sensory/outcome observations constrain mechanics and a task-specific learner. A musculoskeletal simulation represents the biomechanical middle. Model read/write capabilities must be qualified individually.

Intent → action → outcome returns through sensory feedback to perception and subsequent intent; actual observed/inferred/simulated links remain distinguishable.

Interoceptomics combines interoception and connectomics. Touch, proprioception and external sensorimotor tasks can support this programme; they do not by themselves demonstrate internal-body sensing. Combining the proposed pathways advances a research aim rather than establishing a comprehensive solution.

Brain2Body names the wider programme. Body2World remains a contextual lookup label for Body2Action; Brain2Motion and Body2Action retain their own scopes. These related names do not make their measurement targets equivalent to those of the five composed paths.

The physical spinal pathway remains read-only in this proposal. Each claimed recording or writing capability needs its own independent qualification.

Additional programme terms and proposed names

This addendum uses glossary revision 28 and programme specification 30. The preceding glossary supplement preserves its historical revision 26.

Glossary revision 28 (SHA-256):

`c253cdfa96c3ca68877ae2f5af05322d9876952bef8bed5eb646928d3ec90041`

Programme specification 30 (SHA-256):

`deacac166f7a00021e84516c640279fa59ade74a18dd6aa3daf568503716d147`

A connection map, an individual profile and a proposed feedback route answer different questions. The terms below keep those questions apart.

Body2Body

A measured movement can constrain a digital body; a digital body can suggest a movement to test. Body2Body asks which quantities can travel between those settings and whether the resulting movement matches an independent reference.

A proposed research direction relating specified physical-body measurements to digital body models and testing mappings or feedback from those models to declared target bodies.

The user's physical-to-digital and digital-to-physical wording names a proposed direction, not a proven symmetric inverse. Observation-to-model fitting, retargeting and a separately qualified physical output have different requirements. Homologous and mechanically analogous features can support unpaired pretraining or transfer when their mechanics, scale, contacts, timing and missing features are declared. That learned relationship is not an actually measured neural pairing. Keep inferred and simulated quantities distinct from measurements. Biological virtualization still requires independent biological outcomes in a stated domain; no real body actuation, retained skill or whole-organism equivalence follows here.

Lookup labels: Body to body

Brain–Body Interface

A brain recording and a measured hand movement answer different questions about the same reach. A Brain–Body Interface would connect the stated observations and any separately qualified outputs so that the proposed relationship can be tested.

A proposed interface linking specified brain observations with body observations or control outputs in a declared task, with each direction and physical route identified.

This names an interface role, rather than the Brain2Body programme or a model spanning the body. A Digital Bridge is the existing selected-information route around an interruption or between specified recording and control channels; it is related, not an automatic synonym for every Brain–Body Interface. Recording, inference, simulated control and physical output require distinct evidence. EEG and EMG record; a feedback or stimulation output needs its own qualified interface. The label establishes neither complete coverage nor a bidirectional biological loop. No new acronym is introduced.

Lookup labels: Brain-Body Interface

Ecotype

A population adapted to a coastal habitat is an example of the ecological distinction at issue. Ecotype names the adapted population or form; the surroundings themselves are its environment.

A locally adapted population or form associated with a particular ecological setting.

Ecotype is an established population/ecological concept, not an individual's surroundings or an obligatory third stage after genotype and phenotype. State the organism and evidence for the claimed local differentiation or adaptation. The retained Turesson source is a historical plant example [16], not a complete modern evolutionary theory or evidence about the proposed nervous-system experiments.

Enactome

A reach has a path, a time and a result. An Enactome would organize observations like these so that the action and what followed can be compared across stated conditions.

A proposed organization of specified action observations and the recorded relationships between actions and their outcomes in declared tasks.

Declare which actions, body parts, tasks, units, frames and times the data cover. Keep commands, measured movement, sensory consequences and simulated outcomes separate. An observed association does not establish causation, a complete repertoire or the person's unique intent. This proposed data organization differs from the tentative Enactotype individual-profile label.

EndoHumanisation

Choose a particular human-related feature, then ask what introducing or studying that feature would change in the model organism. EndoHumanisation names that proposed line of work.

A proposed research stage studying specified human-related genetic features within a model organism and testing their relevance to a declared biological question.

The roadmap places XenoTransgenesis at step 1.1. The working interpretation concerns defined genetic features; the actual manipulation and its established scientific name remain to be specified. A selected feature does not make an animal human or

establish human cognition, disease fidelity or an appropriate intervention age. Biological relevance, function and animal/participant, ethical, safety and rights requirements need their own evidence and admission. This entry supplies no experimental procedure.

ExoHumanisation

Added tissue can survive without doing the job expected of it. ExoHumanisation names a proposed study of a specified human-related graft: what survives, what connects, and what function can actually be measured?

A proposed research stage studying specified human-related donor cells or tissue in a model organism and testing their survival, integration and function.

The roadmap associates step 2.1 with XenoTransplantation. A cross-species graft retains that established meaning; cell survival, anatomical connection, activity and useful functional integration are distinct outcomes. A graft does not establish a human nervous system, a shared mind or whole-organism human equivalence. Species, tissue identity, biological purpose, ethics, safety and rights remain explicit dependencies. This label provides no transplantation procedure or intervention-age window.

Genotype

A genetic description can record which versions of a DNA sequence an organism carries. Genotype names that genetic make-up, whether the description covers a selected part of the DNA or a wider set. The scope must be stated; the genetic description alone does not tell us every observable trait.

The genetic constitution being described for an organism, with the genetic scope of the description stated.

Genotype is an established scientific term. Its description is not a complete prediction of the organism's observed traits; phenotype also depends on environment and development. The three labels in the user's organism-level example are not three obligatory sequential stages or three fixed individual types.

Interoceptome

A heartbeat signal and a breathing signal describe different parts of the body's internal condition. An Interoceptome would organize the selected observations and their relationships, retaining how, where and when each was recorded.

A proposed organization of specified observations of internal-body sensing and the relationships being studied among them.

This is a data-organization proposal within Interoceptomics. Its coverage must name the organism, body systems, measurements, timing and task. Measured signals, calculated quantities and model estimates remain distinguishable. Touch and limb-position

sensing are not relabelled as interoception, and the suffix does not establish a complete internal-body map or an individual biological type.

Mind-Meld

What information could one system give another, and would it help with the task? Mind-Meld names the proposed first Brain2Brain encounter, whose signal and effects would have to be measured.

A proposed first Brain2Brain study of a specified information link between neural systems during a declared task.

The roadmap places this at step 3.1 before later NeuroTransfer studies. The name does not describe fused minds, shared private experience, arbitrary thought reading or demonstrated skill transfer. Specify the source, recipient, recording and feedback interfaces, task, controls and independent outcome. Assistance during a link and learning retained without tutor information need separate tests, with any necessary compensatory bridge held constant. A reported natural connection is a motivating case, not evidence that this engineered link exists.

Mind-Merge

An agent could guide practice by giving feedback about a stated task. Mind-Merge names the proposed study of that interaction: what help does the person receive, and what can they do later without it?

A proposed Agent2Brain study of task-specific feedback from a software agent to a person and its measurable effects.

The roadmap places this at step 4.1. Ordinary sensory feedback and direct neural delivery remain different routes with different interfaces, evidence and admission. EEG and EMG record; neither supplies a neural writer. No merged identity, shared mind, retained skill or physical intervention follows from the name. Preserve the reverse observation path, matched practice and delayed/new-task retention tests, removing tutor information while keeping a necessary bridge constant. Physical spinal work remains read-only.

NeuroHandler

How well can a hand carry out the chosen task, and what information helps it do so? NeuroHandler is the proposed manual-dexterity experiment, with the hand's measured action providing the result to explain.

A proposed manual-dexterity experiment studying specified neural/body observations, task control and independently measured outcomes.

The earlier proposed manual tasks remain: rapid hand rubbing, the requested knuckle gesture and the interlaced-hand stretch. NeuroHandler names the manual-dexterity experiment; it does not establish a finished apparatus or successful model. Define the

action, available inputs, physical or simulated setting, comparison and outcome before evaluation. Keep motion control, neural prediction, assistance and retained learning separate; any physical output requires separate qualification and admission. No dexterity gain, clinical benefit or intervention procedure is established.

NeuroJuggler

Moving each limb successfully does not settle whether the limbs work together. NeuroJuggler is the proposed coordination experiment: define the joint task, then measure the relationship between the limb actions and the result.

A proposed multi-limb coordination experiment studying how specified limb actions are coordinated in a declared task.

The earlier coordination proposal remains a hot-potato transfer between the hands, followed preferably by two-ball juggling. Those are proposed tasks; the final apparatus and qualified measurement setup remain unestablished. The label supplies no successful performance or implemented neural interface. Declare the task, limbs, inputs, timing, body model or physical setting and independent outcomes. Separate coordination from isolated-limb performance, simulated success from biological function, and current assistance from retained learning. Physical output, safety, rights and held-out tests keep their own admission requirements.

NeuroReplay

What changes when a learner receives replay-based guidance? NeuroReplay names that proposed study: compare performance while guidance is available, then test what remains when the guidance ends.

A proposed Stage 0 research direction for studying replay-guided sensorimotor feedback and its effects on current performance and later learning.

Proposed replay-guided feedback and learning studies.

This is the new roadmap label for steps 0.2–0.5, with a derived working scope; it does not rename Neural Replay, the existing stored-sample playback entry playing-back-a-recording. A stored sequence can supply a comparison, but playback alone establishes neither delivery to a nervous system nor biological learning. Fix the task, signal, feedback route, timing and equal-practice comparisons; distinguish matched, stale or unmatched replay, no-link and inactive or sham controls. Test delayed retention and new tasks after removing tutor information while keeping any necessary compensatory bridge constant. The questioned antechinus age ranges are not established developmental or intervention windows. No physical writer, procedure or present result is supplied by this label.

Phenotype

The trait is what must be observed: for example, a specified body characteristic or response in the setting being studied. Phenotype names these observable traits, rather than the genetic description alone.

The observable traits of an organism arising through genotype, environment and development.

State the actual trait, measurement method, developmental and environmental context. A phenotype is not a universal function that can be read uniquely from structure or sequence. Retain the distinction between a measured trait and a model's estimate.

Whole Body Interface

The hand is one part of the question. Whole Body Interface names the wider ambition to connect declared body systems, while showing which pathways have actually been observed and which remain missing.

A proposed extension of brain–body interfacing toward specified observations and outputs across the brain, spinal, peripheral and body systems.

Whole body states an ambition, not achieved coverage. An interface exchanges specified observations or outputs; the existing model spanning the body is a related modelling ambition, not the same object. State the recorded systems, missing pathways, units, clocks, frames and output routes. Separate datasets can support qualified learning and transfer, but they do not become simultaneous measurements of one body. Physiological input/output direction, software input/output and ordinary sensory feedback remain distinct; no spinal writer or physical actuation is authorized.

XenoTransgenesis

Which genetic feature would be studied, in which organism, and what would count as the relevant change? XenoTransgenesis is the user's working label for that proposed question within EndoHumanisation.

A working roadmap name for proposed research involving specified genetic components from another species in a model organism.

XenoTransgenesis is the preferred spelling; XenoTransgenicism remains a historical lookup label. This is not an established replacement name for every form of transgenesis, genome editing or humanisation; use the established term appropriate to any actual manipulation. Neither a genetic change nor its name establishes the intended functional effect or human equivalence. No procedure, approved organism, developmental schedule or experimental permission is defined here.

Lookup labels: XenoTransgenicism

A cross-species graft

A chimera has biological contributions from different sources. A graft is added tissue; when it crosses species, it is a xenotransplant. An organoid is an organized tissue model.

Survival, physical connection, activity and useful function are separate questions. The proposed comparisons do not establish a humanized whole brain or an implemented treatment.

Cross-species-graft component only; not a strict synonym for every chimera, graft or organoid, or achieved ExoHumanisation.

Additional lookup label: XenoTransplantation

Proposed names and explanatory comparisons

Neo-neocortex

A metaphor for an external machine contribution to human cognition; no anatomical addition is claimed.

AlphaTranscriptome

AlphaTranscriptome is a proposed name for a desired RNA/cell-state prediction capability. It is not an adopted general-purpose model. AlphaGenome already predicts some expression and splicing [1]; other RNA/cell-state models have bounded domains. These precedents leave whole-cell programmability to be independently demonstrated.

AlphaCell

A label for integrating cellular layers appears in the supplied passage; no implementation, novelty or product entitlement follows.

Connetype

A connection profile would describe the selected observations for one individual. Its anatomical coverage, resolution, method and uncertainty must remain visible. The profile does not identify that person's unique function, thoughts or a fixed biological type.

An individual's specified neural-connection profile under a declared measurement and representation.

The original three-name line ends in a question mark; all three remain tentative. No formal empirical definition or repeatability threshold is fixed.

The tentative name is Connetype. Connectype remains an unapproved editorial alternative; it is neither a lookup alias nor an adopted spelling.

Interotype

A heartbeat-related observation can vary with state and measurement conditions. A proposed individual profile must state what was observed and how repeatability would be assessed; it cannot treat touch or proprioception as interchangeable with interoception.

An individual's profile of specified internal-body sensing observations under declared conditions.

The original three-name line ends in a question mark; all three remain tentative. No formal empirical definition or repeatability threshold is fixed.

Interotype is a tentative name, rather than an established scientific type.

Enactotype

A profile of selected actions is bounded by the tasks, observations and conditions used to construct it. Repeatability, state dependence and generalization remain empirical questions; a stable innate action type or inferred unique intent is not established.

An individual's profile of specified actions and action–outcome observations in declared tasks.

The original three-name line ends in a question mark; all three remain tentative. No formal empirical definition or repeatability threshold is fixed.

Enactotype is a tentative name, rather than an established scientific type.

Form, Function, Feature

Start with a structure, ask what it does in the stated setting, then name the observable feature being compared. A hand's form, its grasping function and a measured property of a particular grasp answer related but different questions.

Feature must identify the actual observed or defined trait in its context; it is not a new universal third biological layer or a substitute for function or action. The existing Form → function → action account and intent–action distinction remain unchanged. Structure constrains function; context, history, selection and co-option prevent a guaranteed one-to-one or teleological chain.

Semiosis as a sensorimotor analogy

A drawing can resemble a hand, a pointing finger can indicate an object, and an instruction can follow a learned convention. Such signs can guide action through differ-

ent relations; they do not assign perception, sensation and action to three exclusive boxes.

Icon, index and symbol describe sign–object relations, while sensation, perception and action name processes. A sign can combine relations. No one-to-one biological correspondence, neural code, private-experience identity or strict isomorphism is established. Outside-in and inside-out perspectives must state whether they concern physiology, modelling or interpretation.

Agent vs Neurology

The roadmap ends by asking what an agent could contribute to a defined neurological problem. Agent vs Neurology retains that proposed destination; the specific problem, task and comparison still have to be chosen.

An unresolved Stage 5 research question, not a selected disorder, intervention, diagnostic system or clinical trial.

No specific disease, patient population, endpoint, treatment mechanism, universal cure or successful clinical benefit is inferred. Any future study must define those matters and its ordinary feedback or separately qualified physical interface under the original scientific, participant, rights, safety and independent gates. A prior software, metadata or model result cannot supply this evidence.

Agent vs Neurology names Stage 5 of the proposed roadmap.

References

[1] Žiga Avsec, Natasha Latysheva, Jun Cheng, Guido Novati, Kyle R. Taylor, Tom Ward, Clare Bycroft, Lauren Nicolaisen, Eirini Arvaniti, Joshua Pan, Raina Thomas, Vincent Dutordoir, Matteo Perino, Soham De, Alexander Karollus, Adam Gayoso, Toby Sargeant, Anne Mottram, Lai Hong Wong, Pavol Drotár, Adam Kosiorek, Andrew Senior, Richard Tanburn, Taylor Applebaum, Souradeep Basu, Demis Hassabis, and Pushmeet Kohli. Advancing regulatory variant effect prediction with AlphaGenome. *Nature*, 649(8099):1206–1218, 2026. doi: 10.1038/s41586-025-10014-0. URL https://doi.org/10.1038/s41586-025-10014-0.

[2] Haotian Cui, Chloe Wang, Hassaan Maan, Kuan Pang, Fengning Luo, Nan Duan, and Bo Wang. scGPT: toward building a foundation model for single-cell multi-omics using generative AI. *Nature Methods*, 21(8):1470–1480, 2024. doi: 10.1038/s41592-024-02201-0. URL https://doi.org/10.1038/s41592-024-02201-0.

[3] Abramson et al. Accurate structure prediction of biomolecular interactions with AlphaFold 3, 2024. URL https://www.nature.com/articles/s41586-024-07487-w.

[4] Simon Lavaud, Charlotte Bichara, Mattia D'Andola, Shu-Hao Yeh, and Aya Takeoka. Two inhibitory neuronal classes govern acquisition and recall of spinal sensorimotor adaptation. *Science*, 2024. doi: 10.1126/science.adf6801. URL https://pubmed.ncbi.nlm.nih.gov/38603479/.

[5] Steven D Shaw and Gideon Nave. Thinking—Fast, Slow, and Artificial: How AI is Reshaping Human Reasoning and the Rise of Cognitive Surrender. SSRN preprint, 2026. URL https://doi.org/10.2139/ssrn.6097646.

[6] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is All you Need. In *Advances in Neural Information Processing Systems*, volume 30, 2017. URL https://papers.nips.cc/paper/2017/hash/3f5ee243547dee91fbd053c1c4a845aa-Abstract.html.

[7] Yao-Hung Hubert Tsai, Shaojie Bai, Paul Pu Liang, J. Zico Kolter, Louis-Philippe Morency, and Ruslan Salakhutdinov. Multimodal Transformer for Unaligned Multimodal Language Sequences. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 6558–6569, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1656. URL https://aclanthology.org/P19-1656/.

[8] Ajay Seth, Jennifer L. Hicks, Thomas K. Uchida, Ayman Habib, Christopher L. Dembia, James J. Dunne, Carmichael F. Ong, Matthew S. DeMers, Apoorva Rajagopal, Matthew Millard, Samuel R. Hamner, Edith M. Arnold, Jennifer R. Yong, Shrinidhi K. Lakshmikanth, Michael A. Sherman, Joy P. Ku, and Scott L. Delp. OpenSim: Simulating musculoskeletal dynamics and neuromuscular control to study human and animal movement. *PLOS Computational Biology*, 14(7):e1006223, 2018. doi: 10.1371/journal.pcbi.1006223. URL https://journals.plos.org/ploscompbiol/article?id=10.1371/journal.pcbi.1006223.

[9] *Welcome to MyoSuite's documentation!* URL https://myosuite.readthedocs.io/en/latest/. Undated documentation; retained page labels itself MyoSuite 3.0.0.

[10] Matthew D. Luciw, Ewa Jarocka, and Benoni B. Edin. Multi-channel EEG recordings during 3,936 grasp and lift trials with varying weight and friction. *Scientific Data*, 1, 2014. doi: 10.1038/sdata.2014.47. URL https://doi.org/10.1038/sdata.2014.47.

[11] Wei-Bang Jiang, Li-Ming Zhao, and Bao-Liang Lu. Large Brain Model for Learning Generic Representations with Tremendous EEG Data in BCI, 2024. URL https://arxiv.org/html/2405.18765v1. arXiv preprint, version 1, dated 29 May 2024.

[12] Aviral Kumar, Aurick Zhou, George Tucker, and Sergey Levine. Conservative Q-Learning for Offline Reinforcement Learning, 2020. URL https://arxiv.org/abs/2006.04779v3. arXiv preprint, version 3, revised 19 August 2020.

[13] Aiko K. Thompson, Xiang Yang Chen, and Jonathan R. Wolpaw. Acquisition of a Simple Motor Skill: Task-Dependent Adaptation Plus Long-Term Change in the Human Soleus H-Reflex. *The Journal of Neuroscience*, 29(18):5784–5792, 2009. doi: 10.1523/JNEUROSCI.4326-08.2009. URL https://pmc.ncbi.nlm.nih.gov/articles/PMC2696311/.

[14] Aiko K. Thompson, Ferne R. Pomerantz, and Jonathan R. Wolpaw. Operant Conditioning of a Spinal Reflex Can Improve Locomotion after Spinal Cord Injury in

Humans. *The Journal of Neuroscience*, 33(6):2365–2375, 2013. doi: 10.1523/jneurosci.3968-12.2013. URL https://doi.org/10.1523/jneurosci.3968-12.2013.

[15] Rochelle Ackerley, Léonard Samain-Aupic, and Edith Ribot-Ciscar. Passive Proprioceptive Training Alters the Sensitivity of Muscle Spindles to Imposed Movements. *eneuro*, 9(1):ENEURO.0249–21.2021, 2022. doi: 10.1523/eneuro.0249-21.2021. URL https://doi.org/10.1523/eneuro.0249-21.2021.

[16] Göte Turesson. The Species and the Variety as Ecological Units. *Hereditas*, 3:100–113, 1922. doi: 10.1111/j.1601-5223.1922.tb02727.x. URL https://people.wku.edu/charles.smith/biogeog/TURE1922.htm.

[17] Chad E. Bouton, Ammar Shaikhouni, Nicholas V. Annetta, Marcia A. Bockbrader, David A. Friedenberg, Dylan M. Nielson, Gaurav Sharma, Per B. Sederberg, Bradley C. Glenn, W. Jerry Mysiw, Austin G. Morgan, Milind Deogaonkar, and Ali R. Rezai. Restoring cortical control of functional movement in a human with quadriplegia. *Nature*, 533(7602):247–250, 2016. doi: 10.1038/nature17435. URL https://www.nature.com/articles/nature17435.

[18] Henri Lorach, Andrea Galvez, Valeria Spagnolo, Felix Martel, Serpil Karakas, Nadine Intering, Molywan Vat, Olivier Faivre, Cathal Harte, Salif Komi, Jimmy Ravier, Thibault Collin, Laure Coquoz, Icare Sakr, Edeny Baaklini, Sergio Daniel Hernandez-Charpak, Gregory Dumont, Rik Buschman, Nicholas Buse, Tim Denison, Ilse van Nes, Leonie Asboth, Anne Watrin, Lucas Struber, Fabien Sauter-Starace, Lilia Langar, Vincent Auboiroux, Stefano Carda, Stephan Chabardes, Tetiana Aksenova, Robin Demesmaeker, Guillaume Charvet, Jocelyne Bloch, and Grégoire Courtine. Walking naturally after spinal cord injury using a brain–spine interface. *Nature*, 618(7963):126–133, 2023. doi: 10.1038/s41586-023-06094-5. URL https://www.nature.com/articles/s41586-023-06094-5.

[19] Sharlene N. Flesher, John E. Downey, Jeffrey M. Weiss, Christopher L. Hughes, Angelica J. Herrera, Elizabeth C. Tyler-Kabara, Michael L. Boninger, Jennifer L. Collinger, and Robert A. Gaunt. A brain-computer interface that evokes tactile sensations improves robotic arm control. *Science*, 372(6544):831–836, 2021. doi: 10.1126/science.abd0380. URL https://www.science.org/doi/10.1126/science.abd0380.

[20] Miguel Pais-Vieira, Mikhail Lebedev, Carolina Kunicki, Jing Wang, and Miguel A. L. Nicolelis. A Brain-to-Brain Interface for Real-Time Sharing of Sensorimotor Information. *Scientific Reports*, 3:1319, 2013. doi: 10.1038/srep01319. URL https://www.nature.com/articles/srep01319.

[21] Vittorio Caggiano, Huawei Wang, Guillaume Durandau, Massimo Sartori, and Vikash Kumar. MyoSuite: A Contact-rich Simulation Suite for Musculoskeletal Motor Control. In *Proceedings of The 4th Annual Learning for Dynamics and Control Conference*, volume 168, pages 492–507, 2022. doi: 10.48550/arXiv.2205.13600. URL https://proceedings.mlr.press/v168/caggiano22a.html. Conference proceedings; DOI identifies author preprint.

[22] Omer Revah, Felicity Gore, Kevin W. Kelley, Jimena Andersen, Noriaki Sakai, Xiaoyu Chen, Min-Yin Li, Fikri Birey, Xiao Yang, Nay L. Saw, Samuel W. Baker, Neal D. Amin, Shravanti Kulkarni, Rachana Mudipalli, Bianxiao Cui, Seiji Nishino, Gerald A. Grant, Juliet K. Knowles, Mehrdad Shamloo, John R. Huguenard, Karl Deisseroth, and Sergiu P. Pașca. Maturation and circuit integration of transplanted human cortical organoids. *Nature*, 610(7931):319–326, 2022. doi: 10.1038/s41586-022-05277-w. URL https://www.nature.com/articles/s41586-022-05277-w. Author correction: 10.1038/s41586-026-10943-4, 3 August 2026.

[23] Omer Revah, Felicity Gore, Kevin W. Kelley, Jimena Andersen, Noriaki Sakai, Xiaoyu Chen, Min-Yin Li, Fikri Birey, Xiao Yang, Nay L. Saw, Samuel W. Baker, Neal D. Amin, Shravanti Kulkarni, Rachana Mudipalli, Bianxiao Cui, Seiji Nishino, Gerald A. Grant, Juliet K. Knowles, Mehrdad Shamloo, John R. Huguenard, Karl Deisseroth, and Sergiu P. Paşca. Author Correction: Maturation and circuit integration of transplanted human cortical organoids. *Nature*, 656(8128):E41, 2026. doi: 10.1038/s41586-026-10943-4. URL https://www.nature.com/articles/s41586-026-10943-4.

[24] Laura E. Cook, Axel H. Newton, Christy A. Hipsley, and Andrew J. Pask. Postnatal development in a marsupial model, the fat-tailed dunnart (Sminthopsis crassicaudata; Dasyuromorphia: Dasyuridae). *Communications Biology*, 4(1):1028, 2021. doi: 10.1038/s42003-021-02506-2. URL https://www.nature.com/articles/s42003-021-02506-2.

[25] J. R. Armstrong and M. W. Ferguson. Ontogeny of the skin and the transition from scar-free to scarring phenotype during wound healing in the pouch young of a marsupial, Monodelphis domestica. *Developmental Biology*, 169(1):242–260, 1995. doi: 10.1006/dbio.1995.1141. URL https://doi.org/10.1006/dbio.1995.1141.

[26] The MICrONS Consortium. Functional connectomics spanning multiple areas of mouse visual cortex. *Nature*, 640(8058):435–447, 2025. doi: 10.1038/s41586-025-08790-w. URL https://www.nature.com/articles/s41586-025-08790-w.

[27] NeuroTranslation: A New Paradigm In Brain-Body Mapping. Source edition R736, 2026. Unpublished companion working draft; authorship unconfirmed; no DOI. Independent scientific assessment remains incomplete.

[28] Emanuel Todorov and Michael I. Jordan. Optimal feedback control as a theory of motor coordination, 2002. URL https://www.nature.com/articles/nn963.

[29] N. K. Logothetis, J. Pauls, M. Augath, T. Trinath, and A. Oeltermann. Neurophysiological investigation of the basis of the fMRI signal, 2001. URL https://pubmed.ncbi.nlm.nih.gov/11449264/.

[30] Jerry Tang, Amanda LeBel, Shailee Jain, and Alexander G. Huth. Semantic reconstruction of continuous language from non-invasive brain recordings, 2023. URL https://www.nature.com/articles/s41593-023-01304-9.

[31] Dorkenwald et al. Neuronal wiring diagram of an adult brain, 2024. URL https://www.nature.com/articles/s41586-024-07558-y.

[32] Pospisil et al. The fly connectome reveals a path to the effectome, 2024. URL https://www.nature.com/articles/s41586-024-07982-0.

[33] Shiu et al. A Drosophila computational brain model reveals sensorimotor processing, 2024. URL https://pmc.ncbi.nlm.nih.gov/articles/PMC11446845/.

[34] Wang-Chen et al. NeuroMechFly v2: simulating embodied sensorimotor control in adult Drosophila, 2024. URL https://gizemozd.github.io/assets/pdf/2024_neuromechflyv2.pdf.

[35] Vaxenburg et al. Whole-body physics simulation of fruit fly locomotion, 2025. URL https://pmc.ncbi.nlm.nih.gov/articles/PMC12310536/.

[36] Eon Systems team. How the Eon Team Produced a Virtual Embodied Fly, 2026. URL https://eon.systems/updates/embodied-brain-emulation. Official developer technical account, 10 March; not peer-reviewed validation.

[37] Jumper et al. Highly accurate protein structure prediction with AlphaFold, 2021. URL https://www.nature.com/articles/s41586-021-03819-2.

[38] Lehman et al. The Surprising Creativity of Digital Evolution, 2018. URL https://arxiv.org/html/1803.03453v4. First-hand historical simulator accounts; arXiv version 4 reused.

[39] Google DeepMind. Specification gaming: the flip side of AI ingenuity, 2020. URL https://deepmind.google/blog/specification-gaming-the-flip-side-of-ai-ingenuity/. Official account of objective misspecification.

[40] National Human Genome Research Institute. Beyond Genes: Scientists Venture Deeper into the Human Genome, 2003. URL https://www.genome.gov/11009066/2003-release-scientists-venture-deeper-into-the-human-genome.

[41] Barry N. Taylor and Chris E. Kuyatt. Guidelines for Evaluating and Expressing the Uncertainty of NIST Measurement Results, 1994. URL https://www.nist.gov/pml/nist-technical-note-1297/nist-tn-1297-appendix-d1-terminology. NIST Technical Note 1297, Appendix D1: Terminology.

[42] RCSB PDB-101. Methods for Determining Structure. URL https://pdb101.rcsb.org/learn/guide-to-understanding-pdb-data/methods-for-determining-structure.

[43] Class for Physics of the Royal Swedish Academy of Sciences. Measuring and Manipulating Individual Quantum Systems, 2012. URL https://www.nobelprize.org/uploads/2018/06/advanced-physicsprize2012-1.pdf. Scientific Background on the Nobel Prize in Physics 2012; bounded analogy only.

[44] mncrftfrcnm. Fly-chess trainer, pinned source. URL https://github.com/mncrftfrcnm/making-fly-play-chess/blob/b97dfefbf9b8850f3cdf6b412c2ed840be94e260/scripts/fly_chess_trainer.py. Inspected code at commit b97dfefbf9b8850f3cdf6b412c2ed840be94e260; gameplay not reproduced.

[45] shreyash-sharma. DoomFly threat input, pinned source. URL https://github.com/shreyash-sharma/doomFly/blob/5f6c2881be5f5f40b0592a75e6ee231b50333b40/src/doom/fearless/danger.py. Inspected code at commit 5f6c2881be5f5f40b0592a75e6ee231b50333b40; gameplay not reproduced.

A Reference Comparison Protocol: Unfilled Record

A moving hand gives the instruments something in common to answer to. Scalp EEG would observe electrical activity at declared scalp sites; surface EMG would observe muscle electrical activity at declared arm sites. Neither tells us, by itself, where the hand went. The proposed LEFT and RIGHT tripod views would provide complementary movement observations. Each acquisition needs its own identifiable series of real references, followed by an independent comparison of the assembly. Two streams can agree because they share the same mistaken calibration.

This is an unfilled protocol and record. No observations, admitted reference series, measured errors or acceptance decisions have been entered. The apparatus and its anatomical and functional claims remain unvalidated. The older above/below maze illustration retains its separate schematic context, perpendicular-to-floor geometry and material-path questions. Its directions are not synonyms for the current LEFT/RIGHT tripod arrangement. Actual positions, viewing paths, coverage and transmission would need evidence.

Identify the body and the observation

A photograph can constrain a visible proportion; it cannot supply an EEG channel or a calibrated trajectory. Record each reference's provider, stable identifier, version or acquisition context, checksum if materialized, license, access terms and supporting claim. Identify the organism, developmental stage, participant or specimen, session, body part, task and view or time interval. Record physical dimensions and units, posture, support and contact, so that the comparison concerns the same body and movement. Keep those dimensions separate from computational detail and from the rule used to average errors. Existing datasets, atlases and photographs retain their separate study identities; none is silently admitted for this apparatus.

EEG needs sites, reference, channel order and electrical units. Surface EMG needs named muscles, sleeve and contact identities, reference and electrical units; it supplies neither incoming sensory-nerve traffic nor direct force. Each tripod view needs its selected modality and camera or ranging geometry. Optical triangulation and LiDAR ranging measure different things. Preserve raw observations, derived features and model estimates separately. These recordings do not identify hidden spinal activity, individual neurons or a unique brain state.

Make time and position comparable

A reach can follow the measured path and still arrive late. Record source timestamps, clock identities, cadence and units, synchronization events, offsets, drift, dropped samples and interpolation. Retain calibration observations, frame transformations, their uncertainty and checks against an independent reference. Report offline processing and end-to-end latency explicitly. An alignment error must not disappear inside a movement score, and no real-time capability follows from this protocol.

Compare scalp EEG, each arm's surface EMG, each tripod acquisition, and the time/frame calibration and any actual material path against their respective series of real references. Keep overlap, occlusion, dropout and failed views alongside anatomy, proportion, support and contact. Preserve both motion observations and the joined map. A missing finger remains missing unless its replacement is labelled as an estimate. The assembled map then needs its own independent movement comparison; agreement among its inputs cannot establish the accuracy of their common reconstruction.

Test what the assembly claims

Independently measured movement can test a virtual body's path. Contact and force claims need appropriate measurements of contact and force; a lifelike image cannot establish valid mechanics. A learner's prediction needs a withheld measured target, declared input availability, baselines, negative controls, independent held-out participants, sessions, tasks or species where applicable, and leakage checks. Keep the reserved recordings closed and the original tolerances unchanged. This record admits no new fitting, biological teaching, participant acquisition, stimulation, physical intervention or model promotion. Physical spinal scope remains read-only.

For each component and the assembled apparatus, retain matched reference views or time intervals, the target observable, result, error with units, repeatability, uncertainty and failures. Declare the applicable original acceptance rule, its source, domain, comparator and tolerances before evaluation. The programme's unchanged real-reference contract and every stronger original scientific, anatomical, functional, physical, held-out, rights, visual, runtime and export criterion still govern their respective claims. No universal numeric threshold is introduced or relaxed. Biological function and clinical readiness need evidence beyond a matched motion record.

Unfilled comparison record

Use one record per reference and comparison, retaining a series for every component and for the assembled map. All values below are `null`; reference-series lists are empty and every acceptance state is `HOLD`.

Source and rights. Record ID, component or assembly, provider, source identifier, version or acquisition context, local checksum if materialized, license, access and supporting claim.

Body and task. Organism, developmental stage, participant or specimen, session, body part, task, view or time interval, physical dimensions and units, posture, support, contact, actual sensor geometry and material path.

Acquisition. Modality, measured quantity and units, sites, montage, reference, channel and contact identities, source frame and clock, timestamps, cadence, synchronization events, offsets, drift, calibration observations and transforms, calibration uncertainty, interpolation, missingness, occlusion, offline processing and end-to-end latency.

Independent comparison. Component-series and assembly-series identifiers, independent reference and its acquisition, aligned interval, raw/derived/simulated provenance, input availability, held-out split and custodian, baseline, negative controls, leakage checks and target observable.

Result and decision. Result, error and units, repeatability, uncertainty, failure cases, applicable original acceptance rule and source, domain, comparator, tolerances, independent reviewer, evidence and verdict.

No measured series or scientific validation is supplied by this empty record. Rights, physical, clinical, runtime, native, render, export and publication acceptance remain separate and open; no hosted release is claimed.