NeuroTranslation: A New Paradigm In Brain-Body Mapping.

Simple English Edition

@eliminatenoise

Unpublished Working Draft
Manuscript date: October 13, 2026
Typeset October 21, 2026

Abstract

Both larger models improved the average. Both failed the test. The latest LINK study uses six recording sessions from one macaque to predict the positions of two finger groups, expressed on the study's normalized scale. Four sessions supply the training examples; two supply the development-validation examples used to compare the models. The simpler reference models combine neural samples using weights—numbers fitted from training data. The two larger candidates read a sequence while updating a software memory of what came before. That numerical memory is not a measurement of biological memory. The comparison uses three fixed random starting conditions. Across 18 runs and 720 saved epochs, the two history-reading candidates lower average error. An epoch is one pass through all the training examples allowed for that run.

The original requirements must hold together. No evaluated output may get worse than the selected weighted-sum reference: a worse recording-day/finger-group remains a failure, however good the average looks. Every group on every validation day must also have a defined, positive ordinary R^2 score. That means doing better, under the stated squared-error score, than always predicting that group/day's observed mean. Each score must also exceed its matching association control, which challenges the pairing between neural observations and movement. Those checks give the requirement for positive neural information its meaning here. All five added benefit claims fail too. Neither model is admitted by these development results. The models share a fitting update rule—the procedure that changes their adjustable numbers during training. These results do not independently verify that rule or show how the models perform on the reserved confirmation recordings.

NeuroTranslation asks what we can establish by connecting a stated neural recording to a stated body target, then checking the prediction and each further claim against the evidence it needs. Its software, NeuroTranslator, works on selected, recording-specific problems using models, replay and body interfaces. The larger NeuroTranslation Network remains proposed. Earlier reaching, sensory, attempted-finger and simulated-hand tests answer different questions and remain separate from LINK. A predicted movement is not a learned skill. A simulated hand can carry out the issued command even when the neural decision behind it is wrong; a goal-driven hand can complete a phrase without recorded brain activity driving that policy.

The explanation follows what the sources mean, their units and clocks, model selection and uncertainty, missing pathways, anatomy, simulation, interface limits

and the evidence needed for learning that lasts. The proposed next comparison would pair brain and muscle observations with independently measured movement. Physical calibration, clocks, contact identities and participant registration still need resolving. It would test the declared signal-to-movement mapping against that independent reference, then distinguish help during performance from learning that remains after the help ends.

Anatomical and functional comparisons, final-checkpoint and update verification, and complete GUI and offline checks remain unfinished. Predicting movement, delivering assistance and retaining a biological skill each require their own evidence. Biological teaching and universal skill transfer remain unestablished; neither instant biological mastery nor a complete nervous-system map follows from the reported results.

Contents

1 Neural Signals and Physical Skills 5

2 Brain Structure and Brain Activity 5

3 Measure Movement 7

4 Test Predictions Against Measurements 8

5 Earlier Results 8

6 Recording Access, Context and Stable Signals 10

7 Brain, Spinal Cord and Peripheral Nerves 12

8 Neural Event Counts 13

9 The Two-Finger Recording Study 14

10 The earlier recording families and their distinct targets 16

11 Physical Units and Time Alignment 18

12 Earlier Implementation Defects 19

13 Simple-Model Baselines 20

14 How the earlier small models read recent history 23

15 Why the earlier implementation began with specialists 24

16 How the earlier studies separated fitting and evaluation 26

17 Results: Average Gains Failed the Required Tests 27

18 Failure Cases 29

19 Earlier Model Results 30

20 Fixed-Model Transfer Tests 31

21 Prediction Uncertainty 34

22 Earlier Software Tests 35

23 Separate attempted-finger and simulated-keyboard tests 36

24 Human Arm Simulation 39

25 Macaque Arm Geometry and Remaining Errors 40

26 Muscle Paths and Physiological Validation 42

27 Template Anatomy and Participant Anatomy 44

28 Application Performance 45

29 Earlier Viewer 46

30 Digital-Fly Validation 47

31 Prediction and Reward-Based Training 49

32 Matching future organisms to actual tasks 50

33 Next Experiments 52

34 Tests of Retained Learning 52

35 Tests That Could Reject the Proposal 54

36 Terminology and Measurement Plan 55

37 Reproducing the Studies 55

38 From a reach to a testable prediction 56

39 Follow the action, then test the prediction 68

40 Measure both ends. Test the translation. 70

41 Demonstrated Results and Open Questions 74

Evidence, scope and edition status 75

42 Exactly What the LINK Controls Change 76

NeuroTranslation Definitions in Simple English 79

Additional programme terms and proposed names 131

A Reference Comparison Protocol: Unfilled Record 145

1 Neural Signals and Physical Skills

A file can store a model. What would make it store a skill? Knowing what a hand should do, predicting its movement and making it move are already different problems. A machine might put the hand on the right path while doing the decisive work itself. A file offered as another person's skill therefore owes us an explanation: what does it contain, what would give those contents meaning in a different body, and what can the learner still do when the help ends?

Those questions motivate NeuroTranslation. The proposed field maps nerve signals and patterns that describe them between clearly stated situations: a particular recording, a particular body and a particular task. The implemented software, NeuroTranslator, joins selected recordings, fitted prediction models, playback and computer-body checks. The NeuroTranslation Network is a proposed plan for joining more components while keeping the origin and meaning of each value clear. Brain2Body, with the numeral meaning "to", names the larger programme. A field, a piece of working software and a proposed design are three different things. Their names do not turn the current work into a universal decoder.

The ambition is faster physical learning that remains after teaching stops. The current work is smaller and more testable. It connects real recorded neural activity to specific targets, exposes errors and tries bounded commands in body simulations. Its latest central neural comparison has a negative outcome. Two models lowered average error on development recordings, but both failed the original requirements. The average improved while declared parts of the prediction got worse. That failure tells us where the next explanation has to begin; the older results cannot answer for it.

The first question is concrete: can specified neural observations predict an independently measured body target? The title does not mean that an established scientific paradigm has been replaced or that we invented the familiar models and simulators used here. Every claimed link must answer to a measurement: identify what was recorded, what was calculated, which body it refers to and what happened, then state which comparison could defeat the claim. These conditions make the link testable.

This Simple English Edition explains the concepts from the beginning and stands on its own. The companion Brain2Body article separately introduces the larger biological-interface proposal; neither manuscript treats a presentation or demonstration as scientific authority.[1] Both remain unpublished working manuscripts. The historical figures retain their original evidence scopes: relabelling a figure cannot turn it into a new experiment.

The definition supplement gives this edition's shared registry version and fingerprint; older studies retain the versions they used. The manuscript's scientific and publication limits are stated in its edition note; none of the results reported here establishes retained biological learning.

2 Brain Structure and Brain Activity

A road map tells you where roads connect. It does not tell you which roads are busy right now, which driver will turn, how fast a car can stop or whether a bridge is closed.

A neural connection map has a similar limit. It records structure through a particular measurement and reconstruction method. Structure constrains what can happen, but does not by itself determine all the activity, chemical influences, changing cell states or learning processes that produce behaviour.

FlyWire is a major anatomical reconstruction of an adult female fly brain. Its measured connections are useful evidence, with acknowledged reconstruction and coverage limits. The mapped brain does not include the complete ventral nerve cord, the fly's major lower nerve structure. The dataset is not itself a behaving fly simulator.[2] A developer can use it to constrain software, but still has to choose or measure other ingredients. If those choices include a body controller, the controller's contribution must be visible. It cannot be credited to the wiring diagram alone.

This distinction also applies to our own software. A human-arm simulation is not made into the recorded macaque by placing a brain beside it. A model can predict a measured finger-group position without recovering every muscle and nerve that produced that position. A shared display is useful for comparison, but does not establish a shared biological cause.

An electrode measures activity under particular acquisition conditions. A contact can combine contributions from more than one cell, and its identifier belongs to that recorded inventory. Contact 12 on one date does not establish that the same cells supplied contact 12 on another date. Our current 192 input features come from two measurements at 96 physical contacts. Calling them 192 neurons would change the claim without adding evidence. The recording gives us an observation of the system, with limits set by how it was acquired.

Other instruments observe other quantities. EEG means electrical activity recorded from the scalp. ESG means electrical activity recorded at the spinal surface. ENG concerns nerve electrical activity. EMG concerns muscle electrical activity. These labels help distinguish the observations. EMG is not a direct peripheral nerve recording. Even when a signal helps predict movement, the recording method still limits what has been observed.

Functional magnetic-resonance imaging, usually shortened to fMRI, measures an indirect signal associated with blood oxygen. It does not photograph thought. A classic study recording electrical activity and this imaging signal together found important dependencies on the observed electrical quantity, animal and site.[3] A colourful brain image needs an explanation of what the colours represent, the time support and the measurement limits before it can support a functional claim.

Four meanings of "large" or "small" must remain separate. Physical scale means measured distances or sizes, with units. Organizational level means a whole body, organ, local circuit or cell. Computational detail means what one software calculation represents. Statistical averaging means how we combine numbers. Averaging two finger groups does not measure a larger piece of brain. A small software model does not mean that it observes individual cells. More features do not automatically mean more physical sites.

The useful question is therefore specific: given this recorded quantity from this subject, task and interval, can this method predict this target under these checks? That question can produce evidence. Asking whether a colourful model "understands the brain" without naming a target makes both success and failure much harder to judge.

3 Measure Movement

A person experiences a sensation. Another observer can ask about it, but a report remains a report given by that person in a particular context. The body's position, path, timing, contact and force can be checked with independent instruments. Those measurements have uncertainty too, but they supply observable targets against which a model can be wrong.

The sensory-action relationship gives this programme a practical starting point. Sensory input informs action. Action changes the body and its environment. The resulting feedback informs the next action. A useful test can compare what was intended or predicted with what was measured, then ask whether a correction improves the next result. Established feedback-control work describes how movement can be adjusted relative to task goals under uncertainty.[4] Our programme uses that rationale; it has not thereby demonstrated every biological loop it proposes.

Consider reaching for a cup. A target position, measured hand path and contact outcome could make the task checkable. A decoder might predict the path while a controller changes the muscle commands. The path could improve because the controller is better, because the decoder is better, because an easier target was selected or because an answer was accidentally fed into the controller. A fair comparison keeps those explanations separate. Independent measurements, matched targets and explicit information access make the interpretation possible.

A saved recording is not live feedback. It can show what happened in an earlier experiment, and an offline model can predict part of it. A computer body can provide simulated feedback. A living body can provide measured feedback only through an actual synchronized acquisition. Playing all three on one screen does not give them one clock or one nervous system.

Language offers a useful analogy. The meaning of a statement can depend on who said it, the setting and what happened before it. Likewise, a neural pattern needs its measurement and task context. Published semantic reconstruction from brain measurements depended on the participant and cooperation; it did not establish unique access to any person's private experience.[5] This does not prove that useful shared representations are impossible. It means their preserved information and ambiguity need to be tested rather than assumed away.

Quantum measurement offers a much narrower analogy: observation involves an interaction and its conditions matter. That analogy is not a mechanism for ordinary brain measurements. Quantum backaction means that a measurement changes the state of the quantum system being measured; macroscopic neural recordings, which combine signals over much larger physical scales, have different explanations. We do not claim that quarks (subatomic particles), or quantum disturbance, explain our decoding limits.[6] An analogy should help pose a question, not smuggle in a scientific explanation that the experiment never tested.

The programme borrows a discipline from code and mathematics too: state the question, specify what would meet it and check the answer. Biology remains an empirical subject. A test cannot replace a measurement, and a measurement does not become error-free because a program accepts it. A one-to-one decoding of private subjective experience is not a result here.

4 Test Predictions Against Measurements

Suppose a model predicts the right endpoint once. That is a useful observation, but it leaves several questions open. Did it use the relevant input? Would it work on another trial? Was the endpoint easy to guess? Does it describe the mechanism, or only one consequence? Is the error acceptable in the task's units? A single agreement cannot answer all of those questions.

Accuracy means agreement with an independent reference under stated conditions. Precision means agreement across repeated measurements under stated conditions. A model that repeatedly places a hand too far left can be repeatable and still wrong. Printing more decimal places does not correct it. Neither does displaying a finer mesh or shortening the simulator's numerical step.[7]

Ground truth here means an independently acquired empirical reference with its source, calibration, sampling limits and uncertainty exposed. It is not claimed to be a perfect view of biology. A finger sensor, a camera-derived joint estimate and a force transducer have different meanings and limits. When a target comes from a body-analysis model, it must be labelled as derived rather than a directly measured living muscle quantity.

A disclosed approximation is a hypothesis that can be useful if it passes the right tests. Biological virtualization would mean a digital model independently shown to reproduce specified aspects of a living system's behaviour and causal dynamics within stated error bounds. That is a demanding evidence claim. A convincing animation does not earn it. Invented biological content presented as faithful reproduction is what this programme calls hallucination.

The dice analogy concerns unknown reliability. If a biological claim lacks the necessary tests, a matching answer leaves us unsure whether the model is reliable or merely agreeable in that case. This does not say every prediction is random, that all answers have equal odds or that all approximations are false. Learned patterns can be informative. Independent error measurement, failure reporting, held-out tests and assessed uncertainty tell us how much reliance is justified.

Generated examples can help fit a model or test an implementation. They cannot create independent empirical validation for an absent biological measurement. If a simulator generates the targets and the model matches them, that tests the model relative to the simulator. The next biological claim still needs a real reference. A larger pile of generated agreement cannot supply the missing measurement by counting the same assumptions many times.

5 Earlier Results

The earlier studies answer different questions. Their recordings, targets and tests stay separate; these accounts add no new confirmation. The current LINK cohort and its completed negative comparison follow.

The prototype executes a declared chain: recorded signals enter models matched to each recording, and their outputs pass through explicit body and replay interfaces. That is the idea tested at this bounded scale. The inputs come from named public ex-

periments; saved model states and reported outputs identify what a reproduction should check. The body simulations use named numerical models. These are computer experiments, with failures preserved in the evidence record, rather than physical experiments on an organism.

Consider the simplest chain. A public experiment recorded electrical events in a macaque's brain while it reached. We count events in completed short time intervals, called bins, preserve the original recording-channel order, and give a short history to a trained model. Such a model is sometimes called a decoder because it turns a recorded signal into a prediction about another quantity. This model returns two fingertip velocity components, meaning signed rates of movement along the two recorded coordinate directions, in meters per second. The replay view places those predictions beside the appropriate reference quantities. A separate translation rule turns velocity into a deliberately limited shoulder-and-elbow command for a human arm model. That last translation is an engineering choice. It is not a discovery that the macaque's recorded neurons correspond to particular human muscles. The reaching archive supplies the recorded neural-behavior relationship; the body experiment supplies a numerical test after a stated conversion between bodies.[8–11]

Other chains answer different questions. One model predicts processed summaries of muscle electrical activity from a separate brain recording. Another identifies which finger movement a human participant was cued to attempt. A model using a touch-related brain recording reconstructs earlier movement and handle-force quantities from that same experiment. In the opposite mathematical direction, another model predicts expected neural counts from mechanics matched to its source. That opposite-direction model is sometimes called an encoder. These are useful connections, but their outputs are different kinds of things. A finger-class score is not a finger's path through space. An expected count is not a newly measured neural event.

The earlier application snapshot put these chains beside one another without claiming that their recordings are simultaneous. They belong to different subjects, sessions and tasks. They can run concurrently as software, just as several independent videos can play on one screen. Their coexistence does not turn them into one observed nervous system. NeuroTranslator's shared execution protocol is a way to keep their differences explicit while making them usable through the same application.

The proof also includes negative results. A shared model was tested against retained specialists and rejected. Transfer with a fixed model core from one recording from brain tissue to another failed its admission rule against stronger controls. Native macaque muscle controllers failed reserved source cases. These outcomes matter because they constrain the proposed architecture. A system that quietly substituted a successful-looking replay for a failed controller would offer a weaker proof of concept, even if its screen were more impressive.

The proposed connecting diagram can be read as three panels. The first contains an actual recording and a model matched to that recording. The second contains a bounded conversion to a declared computational body. The third contains a separate future biological tutoring and retention experiment. An explicit evidence boundary belongs before the third panel. Measured body feedback should return to a recording-based model only where an actual synchronized signal supports that connection. Drawing an arrow cannot supply that missing evidence.

We use three evidence levels throughout. An observation is something present in the acquired recording, within the limits of its measurement method. A model-derived quantity is computed from observations and assumptions, such as joint angles estimated through tracking and muscle-and-skeleton analysis. A simulation is produced by an explicitly chosen numerical body and controller. A prediction can concern any of these levels, but its label must tell the reader which one. The original touch-related source study itself distinguishes recorded neural signals and body-model calculations supported by movement tracking.[12]

That historical prototype established executable connections and several local numerical results. It does not establish the missing causal chain from a teaching signal to changes in a living nervous system to independent retained performance. Those learning-related biological changes are often called plasticity. That chain is the purpose of the proposed research program. Keeping it separate lets the current software be useful without asking it to certify an experiment that never happened.




Figure 1: The working chain connects recording-matched predictions to declared body representations. Biological tutoring and retained learning belong to a separate future experiment. The boundary between them is an evidence boundary.

6 Recording Access, Context and Stable Signals

Three practical questions organize the proposed work: can we observe useful signals, connect them to a measured body task, and keep the connection useful when conditions change? Each question identifies a different way an interface might fail. Each needs a different measurement. They are research questions, not outcomes already achieved by this project.

“Access it” asks whether useful signals can be observed without overwhelming the system being studied. More channels are not automatically better. A recording can

be rich in numbers yet miss the task variable that matters. A proposed interface can promise access while imposing a burden that changes movement, development or tissue condition. The current software begins with already published recordings, so it does not demonstrate a new implant, a lower-burden sensor, or safe lifelong access. Its contribution is to preserve what those recordings actually contain and to refuse to invent the channels they lack.

“Ground it” asks whether the signals can be connected to a measured task and a particular body. A count from a brain recording channel only becomes useful for this application when we know the source, timing, target definition and evaluation. A predicted joint angle only becomes useful for a body test when we know the coordinate convention and mechanical assumptions. This is where the interactive prototype does most of its work: source checks, explicit quantity labels, time windows, prediction comparisons, anatomy models and numerical tests of movement control.

“Keep it” asks whether the relationship remains useful as recording conditions, bodies and tasks change. In this prototype, the separate-day motor experiment and the failed external finger pilot illustrate the difficulty. A model that performs well within a session is not automatically stable across days. A model matched to one recording may remain useful after calibration, while transfer with a fixed model core fails to beat fresh training. Longer biological stability, device durability and retained learning are future experiments, not consequences of these local comparisons.

A future experiment should begin with ordinary behavior and clearly defined measurements. If it studies a human-related biological feature, it should say exactly which feature was introduced. If it studies a tissue connection, it should compare the contribution of that connection. An experienced partner and a computer-based tutor are different possible sources of assistance. Disease-specific questions need their own appropriate comparisons. None of those biological experiments was performed by this computational work.

A proposed task sequence should keep ordinary intact behavior visible before studying a defined interruption and replay condition. Simple routes with right-angle turns should be compared separately from routes with varied headings and continuous changes in direction. An animation can test assumptions in its numerical model. It cannot by itself validate a biological injury model, a tissue connection or a disease treatment.

The central learning distinction is equally explicit. Assistance changes performance while help is supplied. Retained learning changes what the pupil can do after tutor commands are removed. Regeneration concerns restoration of tissue or pathways. These can coexist in a future experiment, but none can stand in for another. If an interrupted pathway still requires a compensatory bridge, the bridge must remain available when tutor commands are withdrawn. Otherwise the experiment removes the pupil’s means of expressing movement and mistakes that loss for a test of learning.

The roles of the software and a future biological experiment remain separate. The software builds and checks parts of a measurement and execution chain. The biological experiment would ask what an organism can still do after help stops. A reader should always be able to tell whether a result is an actual recorded observation, a trained prediction, a numerical simulation or an untested proposal.

7 Brain, Spinal Cord and Peripheral Nerves

It is tempting to imagine a skill as a command that leaves the brain, travels down one cable, and arrives at the muscles. That picture is useful only as a starting question. The recordings in this project observe different parts of movement-related and sensory activity through different instruments. They do not reveal every relevant signal or turn the rest into a known blank.

The movement sources include recordings from the brain's outer tissue and observations of behavior. The human finger source includes movement-related and posterior-parietal brain recordings associated with attempted movement; "posterior parietal" identifies the source region toward the back of the relevant brain tissue. The touch-related source observes a region named Area 2 during reaching and externally disturbed movement. A separate human source records surface electrical signals at several levels during stimulation. Each experiment provides a particular window on the system. Its observation method and task determine which conclusions are justified.[8, 12–14]

The movement brain area is formally called primary motor cortex. The touch brain area is formally called primary somatosensory cortex, with Area 2 being the specific source region used here. These names help locate recordings. They do not make a movement-area channel a pure motor instruction or a touch-area channel a complete sensory description. In the implemented models, the practical question concerns prediction: given the recorded history from this source, how accurately can the specified target be predicted on the stated evaluation samples?

The proposed body-wide instrument also needs to preserve direction. Signals travelling from the body toward the brain and spinal cord are called afferent signals; signals travelling from those central structures toward the body are called efferent signals. In plain terms, these are body-to-center and center-to-body directions. The spinal cord and peripheral nerve networks can also process information locally. A diagram with an arrow from brain to muscle should not be read as proof that every step is a passive wire or that the current files measure all of that processing.

Proprioception means sensing body position and movement. Interoception means sensing conditions inside the body. They are related, but they do not name the same information. The numerical controller receives simulated position and movement feedback. It does not thereby observe all internal sensations or reconstruct a complete subjective bodily experience. Each proposed body-wide measurement needs an explicit target and reference.

The spinal cord and peripheral nerves are important to the larger proposal, but their motor activity was not recorded alongside the macaque motor sessions used by the decoders. The registry therefore marks those observations unavailable. It does not insert zeros and call them quiet neurons. Zero would be an actual numerical assertion about activity. Unavailable means the experiment provides no observation of that quantity.

The separate human multilevel preview is valuable because its recording types share one experiment. It contains electrical recordings from the scalp, spinal surface, peripheral nerves and muscles. These combine activity from multiple contributors rather than identifying individual spinal and peripheral neurons. In the acquired preview,

electrical stimulation causes the responses being studied. That supports an observation view and source inspection. It does not train the current application to reconstruct voluntary walking or voluntary brain-to-muscle control.[14, 15]

The difference between anatomy and activity matters too. A structural map can describe possible connections, while a time series describes what an instrument observed over time. Even a very detailed connectome cannot supply the missing event sequence for a particular movement. A future architecture could use anatomical information as a stated prior, meaning a constraint or starting assumption. It would still need evidence for its time-dependent predictions and would still label unobserved channels as unobserved.

A body-wide model is a measurement challenge. More levels could help prediction or control if their information is relevant and aligned. They could also add noise, delay, burden or repeated information. A fair comparison must allow a smaller brain-only or behavior-only model to win. Otherwise, the larger diagram becomes an idea that its own experiment cannot reject.

NeuroTranslator makes the absence manageable. It can keep recorded brain electrical events, surface signals combining multiple contributors, processed muscle electrical signals, mechanical variables and simulations in separate views with explicit quantity labels. That is a useful foundation for adding matched recordings later. It is not a substitute for obtaining those recordings, and it does not establish that everything important about a skill is electrical or already represented in the current files.

8 Neural Event Counts

The models using brain recordings often receive spike counts. In ordinary terms, the input asks how many detected events occurred on each declared recording channel during each short time interval. The original event times are grouped into bins, and the bins are supplied in their original channel order. A model sees a history of these counts rather than a single instantaneous value.

“Unit” is the source’s identifier for a recorded neural feature. Depending on the dataset’s processing, that feature comes from sorting electrical events measured outside cells or from a specified recorded-feature inventory. Sorting groups detected events according to the source’s rules. The identifier belongs to that source. Unit 12 on one day is not proved to be the same cell as unit 12 on another day. Even equal channel counts do not create identity. The reaching and benchmark sources give NeuroTranslator useful activity from groups of neurons, while their definitions matched to each recording limit interpretation across recordings.[8, 9, 16]

Counts are integers because an observed number of events in a completed bin cannot be half an event. This sounds obvious, but a numerical interface can lose the distinction. A model can predict an expected count of 2.4 events. That is a statement about a conditional mean, not a claim that 2.4 events were physically observed. If expected values were silently fed into a port that promises recorded integer counts, the next stage would inherit a false description of its input.

The request validator checks the original numeric values before converting them to the model’s lower-precision floating-point representation. The order is necessary

because a large fractional number can round to an integer during conversion. The portable tests include that case. A request with 16,777,216.25 in a recorded-count field is rejected as fractional even though a lower-precision representation can conceal the fraction. This guard concerns the signal contract, not whether such a count would be physiologically plausible in the source window.

Electrical muscle targets need a different explanation. The brain-to-muscle-signal model predicts 16 source-processed electrical summaries. An envelope summarizes aspects of the recorded electrical signal after the source's filtering and numerical rescaling. In this release, the targets are rescaled values with no remaining physical amplitude unit. A stale millivolt attribute in the source file does not convert them back into electrical amplitude verified in a physical unit. The model's output is therefore neither force in newtons nor a verified muscle excitation command. The source preprocessing, rather than a convenient file label, determines the quantity.[16]

The human finger classifier answers a still different question: which of ten attempted-finger classes is most consistent with the recorded window? Its class probabilities are classifier scores without established probability calibration. The task cue provides the class label. It does not supply an executed trajectory, joint torque, grip force or object manipulation sequence. A correct answer to "which finger was attempted?" is useful evidence for that classifier. It does not prove that the model can make the finger move.[13]

The sensory encoder moves from mechanics to positive predicted average counts. These means can be scored against recorded counts using a probability-based test of how well a proposed average explains the observed counts. They do not constitute a validated generator of complete biological spike trains. Limits on how quickly a neuron can produce consecutive events, coordinated timing across neurons and a complete account of biological count variability would require additional models and tests. NeuroTranslator keeps the mean-count prediction useful while labeling it as inferred activity rather than measurement or stimulation.

Reversing the prediction does not reverse time or recover a unique cause. Several neural patterns can accompany a similar movement, and a similar recorded pattern can occur in different task conditions. A mechanics-to-neural model asks what recorded activity is expected given the supplied mechanics and context. That is a conditional estimate: its answer depends on what it was given. It cannot identify the one true intention merely because the forward model predicts the movement well. Each direction needs its own withheld reference, uncertainty and simpler comparisons. A predicted pattern also ends at a computer output; delivering a sensation would require a separately qualified physical writer. The current spinal scope remains observation only.

Understanding these distinctions makes the screen readable. Similar-looking traces can represent events, rescaled electrical summaries, classifier scores, measured mechanics or predicted expectations. Their labels carry the scientific meaning. The plot's visual smoothness does not establish that two quantities are interchangeable.

9 The Two-Finger Recording Study

The current LINK comparison uses six sessions from one rhesus macaque performing a centre-out finger task. A centre-out task asks movement away from a

central position toward a target. The pinned public source is DANDI 001201, version 0.251023.2336, Monkey N.[17] One animal across six sessions does not mean six animals or a population test.

Four sessions are training: January 27 and 30, February 4 and 5, 2020. Training changes the model's fitted numbers. Two later sessions, February 6 and 11, are development validation: they help choose a model and describe its behaviour during development. Two further February sessions and two June 2023 recordings remain reserved and closed. Those untouched recordings would answer a later question under an independently accepted plan. They supply no result in this paper, and the paper does not imply permission to open them.

Each development session contains 375 trials. Ninety-six physical contacts in hand primary motor cortex provide two feature types. Threshold-crossing counts summarize detected electrical events crossing a selected threshold. Spiking-band power summarizes power in the source's selected high-frequency band. That makes 96 features of each type, or 192 features together. It does not identify 192 cells, two separate electrode arrays or a complete measurement of motor cortex. The contact order and source identity remain part of every example.

The count features undergo the numerical transformation log of one plus the count. This retains zero and compresses large values. The power features retain their archived scale. Both are then scaled using means and spread calculated only from training data. The spread is the population standard deviation: take each fitting value's distance from its mean, square those distances, average them over all the fitting values and take the square root. The saved conversion subtracts the training mean and divides by that training spread. This conversion is the scaler. It puts features on a declared numerical scale without claiming that the contacts measure the same biological quantity.

If the scaler used validation values, the checking recording would already have helped set the model's input scale. That is information leaking from the check into the procedure being checked. In the accepted preparation, validation supplies no scaler statistics.

The scaler uses 107,605 unique training frames owned by their source trials. Unique means a frame is counted once for those statistics even if several prediction windows contain it. Overlapping windows can otherwise repeat the same recorded sample many times. Fitting a scaler to all window entries would weight samples differently; the declared unique-frame rule is part of the study, not a cosmetic implementation choice.

The two output targets are normalized sensor positions. One concerns the index finger. The other concerns the middle, ring and small fingers as a combined group. Their archive names do not give three individual finger trajectories. "Normalized" means the source expresses them on a rescaled sensor scale. A value on that scale is not an angle in radians, a length in meters or force in newtons. The study has no simultaneous muscle electrical, peripheral nerve or spinal recordings. It also lacks the individually measured joint positions and forces needed to turn two numbers into a fully calibrated body state.

A prediction endpoint needs eleven neural samples inside one source trial and a following neural frame for the extra learning target where used. The movement label sits

at the last input timestamp. A history that crosses into another trial is not accepted. The eleven timestamps span about 199 to 201 milliseconds, roughly one fifth of a second. The prepared support contains 91,105 training endpoints and 45,757 development endpoints.

Those counts tell us how many usable recorded endpoints exist, not how many independent experiments occurred. Adjacent windows share samples. The trials belong to the same animal and dates. Statistical claims must reflect that structure. In each session, 4,125 frames are not prediction endpoints; some still provide declared history, the extra neural label or training-scaler support. Excluding an endpoint does not mean every sample around it disappears.

Date	Role	Trials	Source frames	Usable endpoints
2020-01-27	Train	375	27,649	23,524
2020-01-30	Train	375	26,944	22,819
2020-02-04	Train	375	26,441	22,316
2020-02-05	Train	375	26,571	22,446
2020-02-06	Development	375	26,957	22,832
2020-02-11	Development	375	27,050	22,925

Table 1: Six recording sessions from one animal. Each usable endpoint obeys the same history and trial rules. These are exact support counts, not a number of independent people or a claim about confidence. The reserved later and drift recordings are excluded.

An independent source audit reproduced the declared prepared values. Its saved scaler comparison differed by at most 4.54×10^{-13} under the fixed criterion. That is a narrow check of preparation arithmetic. It does not say the model predicts movement well or that a live controller has that accuracy. The manuscript reuses the report; no preparation or calculation was repeated for this source edition.

Time has a further limit. All the series in each file share the recorded clock, but archive bin anchoring and filtering remain uncertain. The displayed span is not verified physiological input support or measured online delay. The archive also contains a voltage label that conflicts with the publisher's threshold-count description. Count interpretation remains count interpretation; absolute power calibration remains unverified. These missing facts must be settled before a stronger physical or online claim.

The separate human EEG/ESG/ENG/EMG preview remains another experiment, involving evoked responses to stimulation and its own clock. It does not drive the LINK models or the older macaque-to-human-arm simulation. Matching picture colours, starting videos together or placing plots in the same dashboard cannot establish a simultaneously measured voluntary brain–spine–nerve–muscle chain.

10 The earlier recording families and their distinct targets

The earlier models use five recording families. These are a selected working set rather than a survey of all neuroscience data. The reviewed source catalog contains 37 resource records, including data, anatomy and simulation resources, but a catalog record does not mean that its files were acquired or used to train a model. Some

entries remain metadata-only. The distinction prevents a broad inventory from being mistaken for broad experimental coverage.[1]

The original movement-velocity specialist uses an Indy recording from February 2 with 130 sorted units. Its input bins last 20 milliseconds, and its history covers 20 bins, or 400 milliseconds. Its targets are the supplied two-component fingertip velocity labels. This is a particular reaching experiment and a particular preprocessing path. The public reaching archive and the NLB-related release identify the source; the project uses its own local split and does not claim an official benchmark score.[8, 9]

The model for normalized muscle electrical signals uses a separate macaque source from the Few-shot Algorithms for Consistent Neural Decoding benchmark, called FALCON, a comparison framework for neural predictors. Its movement-area brain recording has 64 spike features and 16 muscle electrical channels. Its bins and context have the same stated durations as the velocity specialist, but its recording identity, channel meanings and target preprocessing are different. Matching the input's shape or bin duration would not authorize swapping the sources. The source task concerns reach-to-grasp; that does not turn the current software into an object-contact manipulation learner.[16]

The human attempted-finger model uses 298 recorded units across the supplied movement-related and posterior-parietal source configuration. It receives 18 bins of 50 milliseconds each, a 900-millisecond window, and classifies ten cued attempted-finger labels. Its selected method calculates class scores directly from a summarized window, rather than using a changing internal memory through the window. The task labels are meaningful exactly as attempted-intent labels, including the limits of the experimental context. They should not be relabeled as actual finger motion or general dexterity.[13]

The Area 2 source supplies 65 units and paired movement and handle-force quantities. The decoder outputs 17 quantities spanning hand and handle variables and tracking/model-derived joint angles. Seven angles and 39 modeled muscle-tendon lengths also support the native-body analysis. The upstream study explains how whole-arm movement and biomechanical analysis produce those quantities; they are not direct observations of isolated muscle fibers or peripheral motor firing.[12]

The historical separately calibrated velocity model uses a genuinely different Indy date, January 31, from the original MATLAB numerical-data archive. It contains 171 nonempty sorted features. Residual or hash cells, source entries outside the sorted-unit inventory used here, are excluded. The file was selected by a fixed eligibility rule before inspecting its raw signals or model outcomes. Its velocity labels are derived from recorded fingertip positions by taking differences between successive available positions and dividing each difference by the elapsed time between those samples, without reading future positions. The new target recording occurred before the pretrained source recording, so the comparison looks backward across archived dates even though file choice was fixed before outcome inspection.[8]

The separate human multilevel preview supplies surface recordings during stimulation. Its main acquired view includes scalp, spinal, nerve and muscle electrical signals; the companion file has its own channel inventory and omits muscle electrical signals. A

[1] Local evidence: `paper/evidence_matrix.json`, claim `catalog_scope`; source inventory `research/dataset_catalog.json`.

broader repository description cannot override that file-level fact. Neither preview was used to train a voluntary whole-body movement predictor.[14, 15]

Licenses travel with these sources. The used brain-recording resources in the public DANDI repository are listed with the Creative Commons Attribution 4.0 license, whose identifying code in the catalog is CC-BY-4.0. The human surface sources have public-domain dedication entries identified as CC0-1.0. These are exact source-license labels; their source records remain the place to inspect the terms. Body software and other catalog items have separate terms. Open access to an upstream file does not automatically license every new combined artifact, and this local project has not verified a public software deposition or settled its own release license. Keeping source versions and attribution visible is part of reproduction, not an optional decorative appendix.

11 Physical Units and Time Alignment

A number without a quantity is incomplete. The value 0.2 could mean meters per second, an angle in radians, a rescaled muscle electrical summary or an expected event count. A radian is an angle unit; it is not a distance or a speed. A movement pipeline can run successfully while confusing these meanings. NeuroTranslator therefore asks for the units and conventions matched to the source that make the number usable.

The Area 2 handle variables provide a concrete example. Six columns combine pushes and pulls with twisting effects, formally called forces and moments. Forces use newtons, while moments use newton-meters. The combined six-column quantity is formally called a wrench. An incomplete single unit label on the group does not give every column the same unit. The acquisition and group description determine the six quantities. Similarly, source joint angles supplied in degrees are explicitly converted to radians before being used by the appropriate model. A request to the joint port must provide the recorded names, order, radian units and source coordinate frame.[12]

A coordinate frame tells the system what the axes and angles refer to. The same seven numeric angles could describe different joint conventions in different models. A human simulator cannot declare itself interchangeable with the macaque source by using seven numbers. A verified frame or calibration adapter would be required. The current request guard rejects a different frame rather than silently reinterpreting the values.

Time is just as specific. An input window ends at the last complete bin. If a 20-bin history uses 20-millisecond bins, its entries must follow that cadence when timestamps are declared. Missing bins or an inconsistent endpoint are rejected. If the caller omits timestamps, the response says that expected time spacing was assumed. That is weaker evidence than checking the actual supplied times, and the response preserves the difference.

For the sensory decoder, the selected model reconstructs mechanics 40 milliseconds earlier than the neural input endpoint. This follows a comparison of specified alignments on the same set of samples and validation selection. It does not show that sensory activity is a future motor command. It also does not measure a biological conduction delay in isolation, because upstream processing and tracking delays are not fully

identified. In the encoding direction, the source mechanics history is associated with expected activity at the corresponding later model time.[2]

The January 31 velocity target illustrates a different offset. Fingertip positions are recorded at 250 samples per second. For each 20-millisecond neural bin, the processing selects the last available position sample, then takes the position difference between successive selected samples and divides by their elapsed time to obtain velocity. The actual position-sample coverage ends four milliseconds before the neural-bin endpoint. The velocity port therefore reports that earlier output time. Four milliseconds here describes sample timing; it is not an estimated neural transmission time.

Fingertip and cursor positions are also kept separate. In the audited new source, their discrepancy reaches 11.9 millimeters. A cursor may be the displayed task variable, but substituting it for the recorded fingertip would change the target. The project verifies the source transform from centimeters to meters and keeps the quantity explicit. A small coordinate or timing substitution can change a scientific interpretation even when the picture still looks plausible.

These rules define computational sample coverage. They say which recorded samples a calculation may use and where its output belongs on that source clock. They do not remove any filtering that already used later samples in the source, certify the delay in a living nervous system, or authenticate a caller's declared measurement. NeuroTranslator can check the packet's consistency; it cannot prove that arbitrary supplied values came from a real electrode. Its response states that limitation.

For an online prediction, the decisive time is when information becomes available. A sample with an early timestamp could still arrive late, or have been filtered using a later observation. Calling an input causal means that the issued prediction uses only information actually available by its declared deadline. It does not mean the prediction has proved a biological cause. Future neural samples can serve as training targets for the extra learning task; they must not become inputs to a prediction issued before they are available.

12 Earlier Implementation Defects

One of the most useful findings in this project was a data-processing failure. Earlier muscle-signal and shared-model results looked encouraging, and software tests had passed. An independent check against the raw source then showed that the event streams were not all globally ordered in time. The binning method had relied on that ordering.

The mistake is easy to understand without knowing the code. Suppose we want to count arrivals between two times and use a fast search that assumes an arrival list is sorted. If later arrivals sometimes appear before earlier ones in the list, the search boundaries no longer identify the right interval. The counting routine can return numbers of the expected shape, and the rest of the model can train on them. Successful execution does not make those counts faithful to the recording.

[2] Local evidence: `artifacts/sensory_metrics.json`; evidence-matrix claims `sensory_decoder` and `sensory_expected_activity`.

The audit found out-of-time-order streams in 33 of the 64 neural features in the muscle-signal experiment. Applying the ordering-dependent method before sorting had corrupted 866,594 unit-bin cells. Those are counts for particular channels in particular time bins, so the defect altered the actual numbers supplied to the models rather than a cosmetic display. Earlier affected muscle-signal, shared and uncertainty results were withdrawn.[3]

The correction sorts the event times under the documented binning rule and compares derived counts with independent whole-source histograms. Models were rebuilt using unchanged random starting values, data divisions and selection rules. Keeping those choices fixed matters: otherwise a repair could quietly become an opportunity to search for better-looking outcomes. The new results are the corrected results. The earlier positive numbers remain in a withdrawal record and must not be combined with the corrected evidence.

This failure also explains why independence between checks matters. A test that repeats the same faulty search can agree perfectly with its implementation. A check based on the raw event arrays and an independently constructed histogram asks a different question: do the resulting bins match the actual source events? Agreement between distinct routes is stronger evidence than repeated execution of one route.

The project found other numerical defects in native-body handling. Borrowed rotation storage could change after export rather than preserving the intended rigid transform. Named control functions obtained before model initialization could become stale references. Those problems required their own corrected exports and bindings. A finite array, a well-formed JSON file or a green test result can conceal the wrong relationship to a native object.

A later result stands on the check appropriate to its own failure mode. Event order needs source-level verification; coordinate transforms need geometric verification; a controller needs a physical tracking comparison. Biological learning would need a biological retention comparison. That gives each result a reason to be trusted or questioned, instead of treating successful software execution as an answer to all of them.

The withdrawal record shows how the prototype's scientific claims changed when an independent audit found a concrete defect. A future release should preserve that history so readers can distinguish valid and superseded results and see why the change was made. Keeping the corrections inspectable is part of the proof of concept and of a trustworthy demonstration.

13 Simple-Model Baselines

The comparison begins with the training-target mean: a model that always returns the same two numbers calculated from training targets. That simple reference asks how much is gained by looking at neural input at all. A second model takes a fitted weighted sum of the last neural sample. A third takes a fitted weighted sum of the whole eleven-sample history. A weight is an adjustable number: multiply an input by its weight, add those contributions, then add a constant offset. Fitting chooses the weights and offset from training examples so that the predictions approach the

[3] Local evidence: `artifacts/source_audit.json`; evidence-matrix claim `spike_order_withdrawal_counts`.

targets. A weight's sign sets the direction of its contribution; its magnitude sets how strongly the input affects the sum. This does not establish a stronger biological connection. Their formal fitting method is ridge regression, which discourages excessively large weights through a numerical penalty. That penalty makes large weights costly even when they reduce error on the examples used for fitting.

The penalty choices were fixed in advance: 0.01, 0.1, 1, 10 and 100. Both linear models select 100 on the development dates. The constant term is not penalized. This is a controlled small search, not a promise that ridge is the best model for every neural task. It supplies a genuine alternative that the more complex candidate must beat under the same examples and scoring rule.

The two larger candidates use an established gated recurrent unit. That long name describes a software memory updated as it reads a sequence. At each sample, the model combines the new input with a numerical summary of what it has read so far. Fitted calculations called gates control how much of that summary is retained and how much is changed. The next sample is read using the updated summary, so the same current input can produce a different estimate after a different history. Whether that capacity helps is still an experimental question. It is not a recreated nervous system and its numerical memory is not a measured biological memory. The same architecture receives 192 features at each sample, has one layer of 128 internal values and returns two position estimates.

Two kinds of change must stay separate. The summary changes while a fitted model reads an input window. The weights specify how it changes and stay fixed during that prediction. Training adjusts the weights using examples. A changing trace on a replay therefore does not show that the model is retraining, still less that an animal is learning.

Both candidates keep the same total 169,090 adjustable numbers. The position-only version actively uses 144,322 of them in its objective. The extra output for predicting the following neural frame remains present so the total parameter count is disclosed fairly. The second candidate trains that extra output too. Its loss is position mean squared error plus 0.1 times next-neural mean squared error. A loss is a numerical measure the fitting procedure tries to reduce. The extra task is called auxiliary because it is intended to support the main position task; whether it actually helps is a question for the comparison. Both error terms square each individual prediction difference before averaging. The added term gives fitting another reason to retain information in the shared numerical summary. It does not provide a measured new pathway, and success at predicting the next neural frame cannot replace success at predicting position.

An epoch is one pass through all eligible training windows. Each run saves 40 epochs. Batches contain 256 windows, and the final smaller batch is retained. A batch is the subset used for one fitting update; an epoch therefore contains many updates. The model predicts the batch targets, the objective measures its errors, and a gradient describes how changes in the adjustable numbers would change that objective. Backpropagation calculates those changes through the successive model operations. It is a software calculation, distinct from sensory feedback travelling through a living body.

The software uses the established Adam update rule with learning rate 0.001, internal averaging values 0.9 and 0.999 and numerical stabilizer 10^{-8}. Adam keeps running summaries of the gradients and their squared sizes, then uses them to scale the

change to each adjustable number. The learning rate sets the scale of those changes; the stabilizer helps the division remain numerically defined. These settings describe the fitting procedure, not a biological learning rate or a promise that each update improves validation. Weight decay would add a penalty that pulls model weights toward zero. Dropout would randomly leave out internal model units while training. Gradient clipping would limit the size of the calculated update-direction vector. Target clipping would replace target values outside chosen bounds with those bounds. None of these four controls is used here. Together, these choices specify the saved computation. Altering them would change the comparison.

The reported configuration uses four mathematical worker threads and one framework scheduling thread. A thread is a stream of processor work; these settings describe the saved calculation.

Three fixed seeds, 20261007, 20261008 and 20261009, identify the random starting conditions. The two candidates receive matched starting values and training orders. Keeping a seed means keeping its outcome even if another seed performs better. Each seed chooses its lowest development-error epoch; an exact tie chooses the first. The final prediction is the equally weighted average of all three selected models. That average is called an ensemble. Selecting only the best-looking seed would be a different experiment.

The measured condition uses the declared source relationship. An association control challenges the pairing that should carry useful neural information. During control fitting, a neural history and its next-neural target move together to another training example within the same recording day, while the position answer stays in place. The validation observations stay unchanged. This asks how much the result depends on learning the intended training association. It does not remove every possible association: task structure and the held validation context still exist. The frozen methods below give the exact rule. A temporal-order control changes the order of the supplied history while keeping the current bin at the end. It challenges the particular declared ordering; it does not prove that all time information has disappeared. A history might be useful because it averages noise without making use of sequence order; those are different claims. Both controls have their own matched runs, and neither enters the competition for the best model. Two candidates, three seeds and three conditions produce 18 runs, each with 40 epochs, for 720 saved epochs altogether.

The primary score is mean squared error. Subtract the measured target from each prediction, square the difference and average those squares. The result is in squared source-normalized position units. Larger mistakes contribute more heavily. The study first forms one score for each finger group on each validation day, then averages those four scores equally. A day with more usable frames does not take more weight in the final four-cell average merely because it has more frames.

A date/group cell is one of those four score entries. Requiring no harmed cell makes an important choice explicit: improvement should not come by sacrificing one of the declared outputs or days. An average can improve while a real part of the support gets worse. The study’s acceptance rule does not allow that tradeoff. Changing it after seeing the result would make a different claim.

The uncertainty comparison resamples whole trials within each date. A bootstrap is a repeated calculation in which samples are drawn again from the observed support to examine variation in a statistic. Here each draw keeps every supported frame of a trial

together. The same trial draws are used for both compared models and both output groups, so their difference is paired. There are 1,000 saved repetitions, and the interval uses the appropriate percentiles of their scores. Percentiles are cut points below which specified fractions of the scores lie.

This does not make the selected validation data into untouched confirmation. The models were chosen using those dates. The 95-percent interval describes variation conditional on the selected models and those two dates from one animal. It is not a population guarantee, a test on another species or a prediction about every future day. Treating each overlapping frame as an independent animal would make the uncertainty claim much too strong.

The complete development requirement has four parts. The candidate must have lower average error than the selected ridge. It must have no higher error in any date/group. The upper end of the paired candidate-minus-ridge interval must be below zero. Finally, every cell must have a defined positive ordinary R^2 that exceeds the corresponding association control. To obtain that score, compare the model's summed squared errors with the summed squared errors of always predicting this evaluation cell's observed mean, then subtract their ratio from one. That observed mean is a scoring reference, not an answer supplied to the deployed predictor. If the mean-reference error is zero, the ordinary score is undefined and cannot satisfy the requirement. A positive value means beating that mean reference; beating the association control is an additional check. Neither comparison alone establishes a biological causal mechanism. All four must pass. Separate history, order-use and extra-task benefit claims keep their own comparisons. A falling training loss does not replace any of these conditions.

14 How the earlier small models read recent history

The earlier NeuroTranslator implementation used small established models that read recent signal history. One such model reads a sequence while maintaining an internal numerical summary that changes with each entry. Learned controls regulate how much of the previous summary is retained and how much is updated. In this application, the sequence consists of completed neural or mechanical bins. The model's final summary and simple recent averages feed an output calculation for the specified target. The formal name of this model type is a gated recurrent unit: "gated" refers to those controls, and "recurrent" means that the updated summary returns for the next entry. It is a mathematical tool for predicting from history, not a model of every biological process involved in learning.

In those earlier models, before the history-reading model sees spike counts, the pipeline applies a square-root transformation and numerical scaling calculated from training samples. The transformation and numerical scaling are parts of the saved model contract. They must be reproduced during execution, which means using the trained model to predict from a new valid input. Recomputing that scaling from the evaluation recording would change that contract and risk using information outside the declared training samples.

The training sequence includes initial training to predict neural counts in the next bin for the relevant history-reading models. Initial training asks the model to learn pat-

terns in the available training neural history before adjusting it on paired outputs. That adjustment then fits the model for a particular target such as velocity or processed muscle electrical signals. Neither step teaches a biological nervous system. Both change numbers in a software model. When this document says the model learned, it means that numerical optimization changed its fitted numbers.

The output calculation matters as much as the history-reading core. One simple competitor combines recent time-scale summaries through fitted weights, with a penalty discouraging weights from becoming too large; its formal name is ridge regression. Another calculates fitted class scores and turns them into positive values that sum to one; its formal name is logistic classification, and it supplies the selected human finger-intent method. These simpler methods are genuine competitors. The project does not require a complicated model to win merely because the subject matter is neural recording.

The original velocity history model has 232,388 fitted numbers, and the muscle-signal history model has 195,216. The sensory decoder and full-mechanics encoder have 38,802 and 21,266, respectively. The joint-only encoder has 18,696. The new-day velocity model trained without borrowing another model core has 256,045. These counts describe particular saved models. They do not establish that this size is optimal, that larger models cannot help, or that every task can be solved with the same architecture.[4]

A saved checkpoint contains the fitted state and associated processing information. Loading it later should reproduce the selected model's behavior. The package also exports plain numerical arrays and architecture descriptions for execution through NumPy, a numerical-array library. That makes the learned state inspectable without relying only on a training framework. It does not make weights automatically executable inside every chat service, and it does not make their predictions independent of the source and preprocessing that gave them meaning.

The portable runtime mirrors the accepted prediction calculations and uses the same request validation as the existing protocol. Checks of numerical agreement compare its values with both saved examples and native execution. The value of those checks is practical: another compatible program can execute the same mathematical mapping. Agreement between runtimes is evidence about implementation fidelity. It does not create a new evaluation dataset or strengthen the model's biological claims.

15 Why the earlier implementation began with specialists

There is already substantial research on predicting from groups of neural signals and learning useful numerical descriptions. The Neural Latents Benchmark supplies common tasks for evaluating models using groups of recorded neurons, and FALCON emphasizes robustness when recording conditions change and recalibration is limited. Those efforts provide useful evaluation ideas and existing baselines. The present local results are not official scores on their entire benchmark protocols.[9, 16]

Earlier published neural-data models study training across multiple recording contexts and handling populations with different recorded channels. One learns from activity

[4] Local evidence: `paper/evidence_matrix.json`, claim `compact_architecture_counts`, with paths to the corresponding metric artifacts.

recorded within brain tissue across contexts; another represents neural events and uses a selective information-combining stage to accept differing populations. These are relevant precedents for a broader shared representation. They do not imply that every mixture of recordings will improve every task, and they do not remove the need to identify whose channels are being used.[18, 19]

Other model families observe different processes. BrainLM is a published model for activity represented in functional magnetic-resonance brain scans. Neuro-GPT is a published model that combines scalp electrical-signal processing with history modeling and evaluates classification during imagined movement. Those recording types have different instruments, sampling characteristics and interpretive limits from sorted electrical events recorded within brain tissue. Their use of learned representations is a reason to study methods suited to each observation type, rather than to treat all recordings as interchangeable text for one language model.[20, 21]

The earlier implementation therefore began with explicit specialists. The current LINK study tests a further narrowly defined comparison and keeps its failed improvement requirements visible. A model matched to one recording has a narrow source and target: this recording's recent events to this recording's defined velocity, or this source's mechanics to its expected sensory counts. Its limited scope makes failures easier to locate. If a shared model later improves meaningful comparisons on samples kept outside fitting, it can be admitted with its own evidence. The first shared two-task candidate did not meet that requirement and was rejected against the retained specialists.

Local hardware also makes a bounded first implementation useful. The detected system has an AMD Ryzen AI Max+395 processor and about 125 gibibytes of memory, where the unit uses binary-sized rather than decimal-sized gigabytes. Those historical training runs used four processor threads, meaning four streams of processor work under the chosen setting. Those recorded PyTorch numerical-learning runs used the central processor; graphics acceleration was not verified for their workloads. The current LINK protocol also uses its specified CPU route. A separately reported tiny prefix took 4.565 seconds end to end on GPU versus 2.427 seconds on CPU and remained unpromoted. GPU means graphics processor. The prefix does not qualify full training, energy savings or subscription-cost savings. A large memory capacity is helpful for holding arrays and running local tools, but it is not evidence that this machine trained a large general model or accelerated work through unverified graphics hardware.[5]

This hardware choice makes the prototype reproducible within a clearly described environment. It also limits what can be inferred about cost and performance elsewhere. A different processor, numerical library or thread configuration may produce different timings. The package's physics and native-model components have separate runtime requirements. A useful handoff tells the recipient which parts are lightweight model execution, which parts are cached replay, and which parts need a larger or different environment.

Model size remains a choice to test. The broader design may need a larger shared core if it improves adaptation, robustness or estimates for recording types that are missing. It may instead hide a simple source mismatch or perform worse than a model matched to one recording. Complexity has to earn its place in that comparison, which must allow either outcome. NeuroTranslation is not defined by keeping every model small or by making every model larger.

[5] Local environment receipt: `paper/evidence_matrix.json`, field `observed_local_environment`.

16 How the earlier studies separated fitting and evaluation

When a model is fitted to examples, its predictions on those same examples do not by themselves show that it will work elsewhere. The project separates data used to fit its numbers, data used to select a model, and data used to describe its performance after selection. These sets are conventionally called training, validation and test samples. Their meanings depend on the actual data-division rules, not just the names printed in a file.

The history-reading prediction procedures divide samples in time order, with roughly 70 percent for training and 15 percent each for validation and local testing, using trial rules matched to each source. A one-second gap at the boundaries prevents an input history or its next prediction target from casually crossing the edge between sets. Whole trials are retained where the source and analysis require it. Area 2 splits retain whole successful trials, and the sensory timing comparison uses a common set of times before validation chooses among the specified offsets.

The boundary gap matters because adjacent windows overlap and because a model history can include samples from before its endpoint. A test endpoint just after a training boundary could otherwise contain much of the same input history. The gap and sample-coverage rules address that particular leakage of fitting information into evaluation. They do not remove every possible dependence in the underlying experiment or every source-side filtering choice.

Validation has a legitimate but limited job. It can choose among predefined candidate decoders, stopping points or alignments. Once choices are made, test results describe the chosen procedure on the declared test samples. Repeatedly looking at test outcomes and redesigning the procedure turns that support into development evidence. A later independent evaluation needs fresh support appropriate to the new claim.

Several results in this project have that development status. The human finger evaluation was inspected during an earlier pilot. Earlier test outcomes had also been inspected before the later shared-model comparison. Both transfer conditions and all four methods use the same local motor test windows. These facts do not make the computations useless. They change how strongly the results can support claims about new recordings and reliably measured performance differences.

The models use numerical rescaling fitted only on training samples in the audited project calculations. However, earlier source processing can still include filtering, estimating between observations or rescaling done before the files reached this project. Those source operations can use samples beyond a live prediction’s endpoint. A completed-window rule in the project cannot undo that earlier use of later samples. For that reason, the paper separates the samples used by its own calculations from timing in a living nervous system. A model can use only its declared recent bins while its target still carries processing from a broader source interval.

Shuffled-input controls ask whether the association being used depends on the relevant alignment rather than a simpler artifact. Linear comparisons ask whether a complicated temporal model contributes beyond a simpler alternative. They answer different questions, so neither substitutes for the other. A future biological learning experiment would need additional controls on practice, assistance, task exposure and retention that these software splits do not supply.

Samples kept out of fitting within one session still evaluate that session. Once a sample has been inspected, changing its filename cannot make it a fresh test. A fixed file-selection rule documents how an archived recording was chosen; it does not turn that recording into a test of future biological deployment. Report that history with the result so the reader can judge its scope without guessing how often it was revisited.

17 Results: Average Gains Failed the Required Tests

The study completed every planned run and saved all 720 epochs. The result is not missing because fitting stopped early. It is negative because the completed candidates did not meet their declared requirements. An independent audit supports the reported negative calculations after fitting; that is the meaning of “postfit”. It checks the report without establishing that the candidate models are scientifically effective.

Model	Average squared error	Result
Constant training-target mean	0.0317577871	Reference
Linear, last sample	0.0314982382	Selected reference
Linear, eleven samples	0.0383765124	History did not help
Position history model, three-model average	0.0312304247	FAIL
Position plus next-neural task, three-model average	0.0299609175	FAIL

Table 2: Saved development summaries from one macaque and two dates. Lower average error is one requirement among several. Both history-reading models fail the full requirement. No values were recomputed for this manuscript.

The longer linear history performs worse than the last-sample linear model. That is a result for these fitted linear references; it is not proof that neural history contains no useful information. The two recurrent candidates produce lower average error than the selected last-sample ridge. That tells us one favourable fact about their aggregate score, but does not close the comparison.

For the position-only candidate, the candidate-minus-reference average error is −0.0002678134. Its conditional 95-percent interval runs from −0.0014148839 to 0.0009468841. Negative means lower candidate error; positive means higher candidate error. This interval crosses zero, so it does not satisfy the requirement that its upper end be negative.

For the candidate with the additional neural-prediction task, the average difference is −0.0015373207 and the interval runs from −0.0027586737 to −0.0003470099. That interval does stay below zero. It is a genuine favourable aggregate description under the declared development scope. It still cannot override the other required checks.

On February 11, the position-only model is worse than ridge for both measured groups: its squared-error excess is 0.0052471986 for index and 0.0061405635 for the combined group. The extra-task model is worse than ridge for index by 0.0043574767. These are differences on the source-normalized sensor scale. They are not radians of joint error or newtons of force, and a conversion to those quantities is not silently supplied.

Ordinary R^2 asks how squared prediction error compares with always predicting the evaluation cell's observed mean. One is exact agreement under that score. Zero matches that mean reference. A negative value is worse than the reference. The position-only model's second-day values are about −0.099742 and −0.353799. The extra-task model's values are about −0.071162 and −0.116390. Those negative values fail the requirement for positive information in each cell. A model can do better than a weak shuffled comparison and still fail that positive requirement.

The training-mean skill score is separately labelled because it uses a different constant reference. It is not another spelling of ordinary R^2. Likewise, an error score is not a fraction of a skill learned. Keeping these definitions plain prevents a favourable-looking number from changing meaning as it moves from a report to a figure caption.

All five further benefit claims fail their complete requirements: history for the position-only model; sequence-order use for that model; history for the extra-task model; sequence-order use for it; and benefit of the extra task over the position-only model. Some subchecks pass. The complete claims do not. Those outcomes remain recorded with the failures rather than being replaced by a single success label.

The negative result can be checked without certifying the entire learning calculation. Both learning routes share Torch's automatic differentiation and Adam: the former calculates how the objective changes with the fitted numbers; the latter uses those changes to update the state. If both routes inherit a mistake there, they could agree for the same wrong reason. Their agreement cannot independently verify that shared machinery.

A separate numerical route has to check more than a final score. The forward calculation makes a prediction. Derivatives describe how that calculation changes with its adjustable numbers. The update rule uses those derivatives and saved running summaries to choose the next numbers. A checkpoint saves fitted state at an epoch; the random-generator state also determines subsequent random choices. Restoring only part of that state could reproduce a prediction while failing to reproduce the next update. Complete independent numerical values, random-state continuity, reload behaviour, final-checkpoint predictions, derivatives, update state and the whole learning trajectory remain unverified. Checking them would establish the specified computation, not make an ineffective model effective or turn its software memory into biological memory.

Those missing checks prevent a verified continuation. The final-checkpoint and update requirements remain unmet, no new fit is currently admitted, all reserved dates stay closed, and neither a decoder nor a GPU route has been promoted. The report supports these negative computational findings, not biological teaching, a universal neural language or completion of the programme.

The later day's index output poses a specific next question: why did it get worse? Keeping that failure visible makes the comparison useful even when its average improves. A further study would have to explain the failure under an independently admitted plan, without feeding the checking answers back into the predictor.

18 Failure Cases

The saved diagnosis asks what shape the later-day index failure has. The model with the extra neural task predicts, on average, 0.058645 below the measured target in the source-normalized sensor units. About 78 percent of its excess mean squared error relative to ridge is the difference in squared mean error; about 22 percent is the difference in the spread of errors around their mean. Those are descriptive components of an already observed failure.

A mean offset is not a cause. Different trial composition, a changing recorded relationship and a calibration change could all affect such a summary. The analysis leaves those explanations competing. It does not show which one occurred, fit a correction or give permission to add the validation answers to a prediction. Moving the predictions until their validation mean matches the target would use the checking data to adjust the model.

A separate analysis looks only at the four training dates. It defines context as the average of the ten preceding neural bins in each existing eleven-bin window. That context is not an observed biological state; it is a specified summary of recorded features. The existing recurrent model already sees those bins. Showing that the summary varies cannot prove that a new branch will extract useful information from it.

The training support contains 1,500 trials and 91,105 endpoints. The saved analysis divides summed feature variance into variation within a trial, variation between trials on the same day and variation between days. Variance summarizes squared deviations from a stated mean. For threshold-count features, the three shares are 71.56, 18.85 and 9.59 percent. For archived power features, they are 51.28, 13.55 and 35.17 percent. These shares give greater weight to features with greater variance. They are not percentages of the brain doing different jobs.

An alternative calculation gives equal weight to dates, trials and frames within trials and produces similar fractions. That is another view of the same training support, not another cohort. These summaries have no population confidence interval and do not establish neural drift, a particular cell state or a benefit for decoding. The typical within-trial feature-to-target associations are weak. A proposed interpretation should remain proportional to those observations.

The analysis also checks whether prior sensor labels are actually supported. Exact joins of source index, time, trial and ownership retain 89,605 endpoints with one supported prior sensor sample and 88,105 with two. When a beginning of a trial lacks a label, it stays missing. No value is interpolated and no sample is borrowed from a neighbouring trial. Sixteen combinations of the two prior-position quartiles have support on every training date. A quartile is one of four divisions of an ordered distribution; combining two four-way divisions gives sixteen cells.

That support is useful for descriptive checks. It is not permission to feed body-position labels to a predictor meant to use neural input only. Nor are the correlated frame counts independent observations. The question for a new neural branch remains whether its available neural information improves the specified prediction under all the original controls.

Even descriptive arithmetic can fail. The first analysis version missed the fixed tolerance for two skewness values, which measure distribution asymmetry. The absolute

and relative tolerances stayed at 10^{-12}. A corrected version changed only how the per-date skewness was accumulated. Its 768 checked values passed the named independent comparisons while all 119,848 other numerical leaves remained unchanged. The rejected report was retained. This accepts a limited calculation, not a model or a new fitting procedure.

The proposed next branch would let past neural context modify the existing output. It would add 780 parameters and compress that context into four learned summaries that modulate the prediction. This is the proposed rank-four branch: rank restricts the numerical representation; it does not name four measured brain regions or an anatomical scale. The comparison would have to test constant context, broken association and altered order. Choosing a model strictly within training also requires a smaller fitting-and-checking division inside that training support. Whole trials must stay together in those inner divisions, and the divisions must be independently verified. Each inner fitting set must supply its own scale, counting its unique samples once. Scaling the already rounded, globally training-normalized packet again cannot establish that isolation: the inner checking samples may already have contributed to the earlier scale. Another scaling step cannot prove that their influence was absent.

The proposal remains unexecuted and unadmitted for current fitting. It adds no body labels, date identities or validation offset corrections to the neural-only predictor. A new fitting stage would have to pass its source, interface, random state (the exact state of its random generators), derivative, update, selection and uncertainty requirements before any new result could be claimed. The four reserved dates remain closed. Proposed body feedback, reward-driven refinement and broader extensions also remain proposed; the description is not an execution report.

19 Earlier Model Results

The velocity model reports a prediction score of about 0.729 on the local samples kept out of fitting, compared with about 0.559 for the simple weighted-sum competitor. The score's formal name is R^2. It compares squared prediction error with the variation left by a prediction that always uses that output's mean reference value in the evaluation set, under the stated scoring definition. A value closer to one indicates a closer fit on those samples. It is not a percentage of biological understanding, and 0.729 does not mean that 72.9 percent of a skill has been decoded.[6]

The corrected model for normalized muscle electrical signals reports about 0.704 versus 0.595 for the simple weighted-sum method. This average value hides considerable variation across channels. The weakest channel is about 0.088, while other channels are much stronger. A reader considering a particular muscle-related output must inspect its own performance. The average cannot certify every channel equally. These are local comparisons on the processed targets, not an official FALCON result or an identified force-control model.[7]

The sensory decoder reports a prediction score averaged over physical output groups of about 0.710. The scoring averages five groups of physical outputs with equal group

[6] Local evidence: `artifacts/metrics.json`; evidence-matrix claim `mc_rtt_velocity`.

[7] Local evidence: `artifacts/emg_metrics.json`; evidence-matrix claims `falcon_emg` and `emg_channel_heterogeneity`.

weight, rather than allowing a group with many columns to dominate simply because it has more columns. The distinction matters when comparing this value with a mean taken over individual outputs. Its meaning is reconstruction of the stated earlier source mechanics from this source's touch-area history.[8]

The full-mechanics sensory encoder gains about 0.177 bits per recorded spike over a constant count calculated from training samples. The joint-only encoder gains about 0.119. In plain terms, their predicted count means explain the recorded counts better under the chosen count-probability test than a constant training-derived mean does. The bits-per-spike unit expresses the difference between count-probability scores on a base-two information scale, divided by observed spike count. It is not the number of bits required to upload a movement or evidence that generated spikes would behave biologically.[9]

The selected human finger classifier correctly classifies 45 of 50 evaluation trials, or 90 percent, compared with 68 percent for its recent-history model alternative. The evaluation is within-session development evidence because the run had been inspected earlier. A separate uncalibrated external-day pilot achieves 10 percent, matching the ten-class chance level. The favorable within-session result and unfavorable external result belong together: classification matched to one recording worked in one setting, while the broader uncalibrated claim did not.[10]

These scores answer several useful questions without answering the final learning question. They show that specified quantities can be predicted from particular recordings, sometimes better than simpler alternatives. They expose differences in performance between channels and cross-day failure. They do not show how a new person would perform, whether a different task would work, or whether the predictions can teach a living pupil. Keeping each score attached to its target, baseline and support is how the proof stays proportionate to the evidence.

20 Fixed-Model Transfer Tests

Transfer learning asks whether a model's earlier training helps with a different setting. For a neural interface, the appealing hope is that a useful representation from one recording can reduce the work needed for another. The separate Indy day provides a real opportunity to test part of that hope. It changes the recording and target processing, and the experiment does not assume that individual cells can be matched across days.

The original January 31 MATLAB file is 208,792,806 bytes. The publisher's file fingerprint and a locally computed fingerprint identify the acquired bytes. The source's residual/hash entries are excluded from the sorted-feature inventory, and the file does not supply a per-unit record of when each unit was observable. These details matter be-

[8] Local evidence: `artifacts/sensory_metrics.json`; evidence-matrix claim `sensory_decoder`.

[9] Local evidence: `artifacts/sensory_metrics.json` and `artifacts/sensory_joint_metrics.json`; evidence-matrix claims `sensory_expected_activity` and `joint_only_activity`.

[10] Local evidence: `artifacts/finger_specialist_metrics.json` and `artifacts/finger_metrics.json`; evidence-matrix claims `human_finger_intent` and `human_finger_external_failure`.

cause a transfer result depends on the actual target source, not merely a date label or an array of convenient width.[11]




Figure 2: Recorded events from the separate Indy day alongside fingertip-velocity predictions from the freshly trained recording-matched model. Reference velocity is calculated from recorded fingertip positions. The channels identify this source's sorted features, without matching cells across days.

Four methods are compared. The transferred model learns a translation layer into a previously trained model core and output calculation whose existing fitted numbers remain fixed. A control uses a translation layer of the same size and a fixed core started with random numbers. A fresh model is trained for the new source without borrowing the previously trained core. The simple weighted-sum method supplies the fourth comparison. The random-core method is particularly useful because it asks whether the transferred core's prior learning adds anything beyond using a fixed structure whose output is more than a weighted sum of its inputs.

Two label conditions were fixed before inspecting outcomes: the first five percent of eligible new training labels, and the full eligible training set. The small condition supplies 1,425 adaptation labels, corresponding to 28.5 seconds at the stated bin duration. It also uses 6,000 validation labels, or 120 seconds, and has 570.14 seconds of neural samples available for training. The previously trained source model previously used 22,598 training and 4,723 validation label windows. These additional sources of information must stay visible when discussing efficiency.

"Five percent" therefore refers to one adaptation-label budget. It does not mean five percent of all supervision used by the entire procedure. "28.5 seconds" does not mean that a person learned the skill in that time, that the method ran online for that duration, or that no other data was required. It is the duration represented by a particular

[11] Local source and experiment evidence: `artifacts/motor_transfer_metrics.json`; evidence-matrix claims `motor_transfer_controls` and `motor_transfer_budget`.

set of paired adaptation windows. A fair future learning-speed claim must account for validation, prior training, training samples of neural signals without paired movement labels and actual deployment time.

In the small condition, transfer using the fixed core has validation prediction score 0.393 and local test prediction score 0.425. The control with a randomly initialized fixed core has 0.312 and 0.331. The freshly trained model has 0.533 and 0.520. The simple weighted-sum method has 0.276 and 0.220. The previously trained core thus improves over the random-core comparison, but fresh training performs better. The result supports the narrow statement that prior core training carries useful information relative to this random control. It does not support admission over the strongest competing method.

In the full condition, the transferred method has validation prediction score 0.683 and local test prediction score 0.704. The control with a randomly initialized fixed core has 0.631 and 0.646. The freshly trained model has 0.724 and 0.747. The simple weighted-sum method has 0.550 and 0.548. Again, fresh training wins. These eight method-condition rows use one fixed configuration and the same 6,050 local test windows; they are single reported values without uncertainty intervals from repeated runs with different random starting values.

The admission rule required transferred validation performance to exceed every control by at least 0.01. Neither transferred condition qualifies. The freshly trained model using the full label set becomes the usable new model matched to this recording, while transfer with a fixed core remains rejected. The 0.747 local result cannot be read as a direct improvement over the original source's 0.729 because the recordings, labels and processing differ. What worked was local calibration on a distinct recording; transfer without new calibration and verified cross-day cell correspondence were not established.

New examples	Method	Selection score	Local test score
First 5%	Use the old fixed model	0.393	0.425
First 5%	Use a random fixed model	0.312	0.331
First 5%	Train a new model	0.533	0.520
First 5%	Simple fitted formula	0.276	0.220
Full	Use the old fixed model	0.683	0.704
Full	Use a random fixed model	0.631	0.646
Full	Train a new model	0.724	0.747
Full	Simple fitted formula	0.550	0.548

Table 3: All eight fixed method-and-label conditions. Scores compare prediction error with a mean-reference prediction; closer to one means a closer fit on these samples. Adaptation labels exclude additional validation and prior-source supervision. All rows reuse the same local test windows.




Figure 3: The previously trained fixed core helps relative to the random-core control, but fresh training performs better in both label conditions. Neither transferred model passes admission. The bars are single-run results, without repeated-run uncertainty intervals.

The separately trained shared two-task model was also rejected on validation. Together, these outcomes make the broader-design proposal more precise. A broader shared representation remains an idea to test. It is not already NeuroTranslator's successful universal core, and it has to beat appropriate specialists before replacing them.

21 Prediction Uncertainty

A prediction can be accompanied by a band that looks reassuringly scientific. The question is what the band was constructed to mean. NeuroTranslator uses limits calculated from validation prediction errors to supply constant-width bands for each output. An error here is the difference between a prediction and its reference. The chosen limit summarizes the size of those observed validation errors for that output. It is a practical diagnostic, not a complete theory of uncertainty.

The nominal level is 90 percent per output. That statement concerns individual channels, not all channels at once. In the reported velocity case, mean test coverage per output is about 90.6 percent while simultaneous two-output coverage is about 84.8 percent. For the muscle electrical signals, the mean is about 90.1 percent but simultaneous coverage across all 16 outputs is about 43.5 percent. The sensory case likewise reports about 90.9 percent mean individual coverage and about 49.5 percent simultaneous coverage. These descriptive values show why a per-channel label cannot be promoted to whole-body confidence.[12]

The windows overlap, and errors through time are correlated. The bands therefore do not receive a mathematical guarantee of future coverage merely because their lim-

[12] Local evidence: `artifacts/uncertainty_metrics.json` and `artifacts/sensory_metrics.json`; evidence-matrix claim `empirical_bands`.

its were chosen from earlier errors. They do not separately identify sensor noise, imperfect labels, model uncertainty, source drift or absent observations. A broad band around a measured target is also not a way to create a missing spinal label.

Classifier scores have a related limitation. A finger output of 0.8 is a normalized classifier score. Without calibration evidence, it should not be read as an established 80 percent frequency of correctness for all cases assigned that score. A model can rank classes usefully while expressing unreliable numerical confidence. The present interface calls the scores uncalibrated rather than encouraging a stronger interpretation.

The joint encoder uses an explicit check against training ranges. It compares every angle in the input history with the training minimum and maximum for that coordinate, including a declared small margin for rounding and numerical error. An input outside those bounds is rejected unless the caller explicitly requests extrapolation. This is a useful guard against one obvious source of misuse.

Range membership has a much narrower meaning than complete familiarity. Seven individually familiar angles can occur together in a configuration the model never saw. Familiar angles can also be traversed at unfamiliar velocities or accompanied by different loads and contacts. The training-range report therefore states that coordinate-range membership does not prove joint-configuration coverage and does not validate neural generation. Allowing extrapolation leaves those limits explicit; it does not clip the input into support and pretend the request became observed training-like data.

A future system should distinguish several questions: what was measured with uncertainty, what a fitted model is unsure about, where the source has changed, which variable is missing, and whether the task permits the proposed action. Those questions may need different measurements and methods. The current prototype makes a useful start by keeping signal type, source identity, observed bands and support warnings separate. It does not claim a single confidence score that resolves all of them.

22 Earlier Software Tests

The historical NeuroTranslator snapshot exposed seven named operations through one request protocol. Each operation, called a port, declares its input and output. The protocol gives callers one way to request them while preserving those different meanings. Selecting the right port is part of the scientific contract: one operation must not silently take the place of another.

The ports are original motor velocity, normalized muscle electrical signals, human finger intent, sensory mechanics reconstruction, full-mechanics expected sensory activity, joint-only expected sensory activity, and calibrated-day motor velocity. Their names describe the actual operations. They do not imply seven simultaneously observed pathways or a complete map of the nervous system. Two sensory directions share a source model family, and the other operations retain their own source identities.

A request supplies the translator identifier, recording identifier, input kind and complete window. Spike requests must also supply the original ordered unit inventory. Mechanics requests must supply the recorded channel names, physical units and source frame. Timestamps can be declared for checks of time spacing, and an input-

origin field distinguishes a caller's claim of recorded, source-derived, mixed, decoded or simulated input. That origin label remains a declaration rather than independent measurement authentication.

The response identifies the output's source and checkpoint, names and units, time and reference kind. It states that predictions are not observed data. Expected sensory activity remains "model-expected activity." The response says that it is not a neural stimulation command and is not an inference of missing spinal activity. The joint operation also returns its training-range report. These fields matter because downstream software may otherwise treat a plausible number as permission to make a stronger claim.

The portable adapter runs an exported model for a caller. It reads the exported catalog—the saved list of model descriptions—rather than rebuilding that list from saved training states. It loads the plain numerical model exports and checks that their declared training-state fingerprint matches the catalog. A fingerprint is a computed identifier for file contents; this check compares the declared identities. The adapter then applies the same request-checking rules as the existing execution interface, preserving the source, unit, frame, time-spacing and integer checks. The model can therefore run without loading the training software. The recipient still needs a compatible execution environment and the supplied numerical software.

The executable examples use actual included source-replay windows. Each example gives a request and an expected response. The historical live check compared all seven operations within the declared numerical tolerance of 0.000002 and required the other response metadata to match exactly. That tolerance concerns agreement between implementations, not error against a new biological recording. A wrong recording, reordered units, wrong mechanics units or frame, broken time spacing, fractional recorded count or stale model identity is a reason to reject the request. Rejection is part of the interface's functionality, because accepting the wrong contract would create misleading outputs.

Concurrent execution does not merge clocks. If the application runs motor and sensory examples together, each result stays on its own recording's clock with its own offset. The display can coordinate playback as a user-interface choice, but that coordination is not a measured physiological synchronization. A future matched multilevel recording would need its own verified common time base before NeuroTranslator could claim a joined chain.

Another AI or programmer can inspect the schemas, sources, example requests and model arrays, then execute the defined operations in a compatible environment. That is the handoff's practical portability: the same accepted computation can run with the same declared meaning. The archive should not be assumed to supply arbitrary biological skill programs.

23 Separate attempted-finger and simulated-keyboard tests

These October 4 studies have their own participants, sources, decisions and bodies. They are not the LINK comparison or replications of its improvement claim.

23.1 Recorded Finger Intent

The public recording came from one participant with tetraplegia, a condition that affects movement in all four limbs. The experiment cued the participant to attempt a finger movement. Its labels name those attempts. They do not supply a measured path of the finger through space, a measured muscle command or a recording of the participant playing an instrument.

The three recording dates used for the later test were May 16, May 20 and May 23, 2016. They are three dates from one person. The 150 later examples are not 150 people. These dates contain posterior parietal cortex recordings, from a named region of the brain. They do not contain the matching motor-cortex, spinal, peripheral-nerve or muscle recordings needed to observe the whole route from brain to hand.

The software counted recorded events in eighteen completed time bins. Each bin was 50 milliseconds long. Together, the bins covered the interval from 0.1 to 1.0 seconds after the experiment's Go signal. The decision was released only when that window had finished. The earliest release was therefore one second after Go, not an instantaneous response.

A new recording date also needed examples. Fifty early examples with known attempted-finger labels were used to adjust the model to that date. This is local calibration: using examples from where a model will be used. The later 50 examples from the same date supplied its test. Changing from twenty to fifty early examples changes both the amount of data and how recently those examples were recorded; it does not isolate the effect of example count alone.

The study kept each recording's unit identities separate. A unit number on one date was not assumed to name the same cell on another date. When an observation was missing, the software kept it unavailable. An unavailable channel did not become a measured channel with zero events.

23.2 Finger-Intent Model Comparison

The study compared seventeen fixed candidates. Earlier validation dates were used to select the model before the new test examples were opened. The selected model was a simple classifier: software that chooses one category from ten attempted-finger categories. It correctly chose 116 of the 150 later labels. The three date scores were 35, 44 and 37 correct choices out of 50. A population model given no early local examples made 11 correct choices out of 150.

This result supports a specific calibrated mapping. It does not show that the same cells were identified across dates, that an unfamiliar person needs no examples, or that one model works for every organism. It also does not show that a large model would be a better use of this machine or dataset. The competitors, including the less successful models, remain in the evidence record.

The recording contains cued attempts. The effect of seeing the cue has not been separated from the effect of attempting the movement. A correct category choice therefore cannot establish that the software read a general physical skill or that it reconstructed every biological command needed to carry it out.

23.3 Command Selection and Muscle Control

The body controller received the actual predicted category. A wrong prediction stayed wrong. The software did not look at the source answer and swap in the correct finger. Four right fingers could command four keys. Left fingers and the right thumb were retained in the record but could not command that body.

The body was an openly available, generic human-hand simulation with 39 muscles. A previously trained policy supplied muscle excitation commands, numbers that control the simulated muscles. The wrist, thumb and movements that spread the fingers were held by braces. The requested motion used fixed fingertip targets and a half-second press-and-release pulse. These targets were engineering choices, not measurements of what the participant's muscles did.

The body was initialized once for each whole recording. After that, positions and velocities advanced through the simulator. The controller did not overwrite the hand's pose to make a press look successful. Key contact, travel and release were checked in the physical model.

The body carried out all 54 supported commands it received. That sounds perfect until we ask a different question: did those commands match the source attempt? Only 41 of the 60 supported right-finger attempts led to the correct contact. There were 13 unintended presses. The body could follow a wrong instruction accurately. That is why 54/54 command execution and 41/60 source-intention success must stay separate.

Three controls make the distinction clearer. With every muscle command set to zero, no supported source attempt produced the right contact: 0/60. A reference control was given the true source labels and reached 60/60. That control measures what this body and controller can do when given the answer; it is not neural decoding. A third control deliberately assigned neural decisions to different trials. It reached only 4/60 source-intention contacts even though the body still carried out all 54 supported commands. The deliberate reassignment is an offline comparison, not a new recording of a nervous system.

All source trials stayed in these comparisons, including unsupported attempts and mistakes. The recorded decisions were computed offline, then released on the original source clock after their windows had completed. Watching the replay at a normal pace does not make it live brain acquisition.

23.4 Simulated Musical Phrases

The muscle policy had already been trained in a separate phrase-and-chord task before the recorded-neural connection was tested. That study asked whether a simulated hand could carry out a requested sequence of notes through muscle commands. The policy received note goals, timing and fixed smooth fingertip paths. Recorded neural clips did not drive the original phrases, and during the later held test it received no teacher actions.

The 32 episodes combine eight phrase orders, two tempos and two starting poses; they are not 32 people or animals. The generic four-key simulated hand keeps its wrist, thumb and finger spreading braced and uses scripted smooth fingertip targets.

These episodes test the goal-driven policy; the recorded-neural classifier above answers the separate attempted-finger question.

The held cases used phrase orders, irregular rhythms, chords, tempos and starting poses reserved before tuning. The selected corrected policy completed all 32 phrases. It produced 704 intended strikes and 192 chords, released the keys on time and made no extra presses. The starting policy completed no whole phrases. The first new fit completed 20. The named reference controller completed 24. Zero muscle excitation completed none. Independent numerical replay checked the saved trajectories and scores.

The original evaluator ended with exit code 143. That means it was terminated; why it stopped is unknown. It had already saved the complete closed results and final output. A separate full replay checker exited 0, meaning that checker finished successfully. These two facts must both be reported. The virtual spring-key limits are soft constraints, not rigid stops. Key travel can therefore exceed the nominal 6 millimetres. The saved poses and travel were not clamped, meaning forced into an allowed range, or invented to make the display look better. This remains a computer simulation.

Local training of that muscle-policy study took about 2 minutes 36 seconds. The later neural-candidate training and validation took about 24.7 seconds. Those are saved software runtimes. Recording acquisition, labeled calibration, physical checks and independent verification require additional time. Neither runtime says how long a living pupil would need to learn.

These are useful results in a constrained numerical body. They do not show that the participant played those phrases, that a pianist's neural skill was uploaded, or that a living hand learned music. They show that a saved learned policy can carry out specified goals through simulated muscles, and that a separate recorded-neural classifier can supply a narrower set of finger goals.

24 Human Arm Simulation

A predicted movement quantity can be statistically accurate yet lead to an unsuitable physical command. Muscle-and-skeleton simulation provides a separate check on that gap. The human-model branch uses an open MyoArm asset from the MyoSim/MyoSuite ecosystem and runs its dynamics through MuJoCo. These are existing community tools, not anatomy or physics invented by this project.[10, 11, 22]

The model has 63 numerical muscles that produce forces, with internal responses that change over time. The experiment explicitly converts two velocity components into shoulder-and-elbow angle goals, while other independent joints are braced. This reduction is a choice about a bounded engineering test. It does not reconstruct a whole posture from two numbers or identify a macaque-to-human neural correspondence. The target velocity and human body remain distinguishable parts of the chain.

The controller applies muscle excitation commands that stay within declared nonnegative limits. Excitation is the requested drive supplied to the numerical muscle. Activation is the muscle model's changing internal response to that drive; the two are not the same value, and activation does not change instantly. The controller accounts for the linked shoulder-girdle loads through a calculation that relates the modeled forces

and motions to the controlled joint angles. The simulation updates 500 times per second. It does not obtain success by overwriting joint angles with the desired pose, and it does not use recorded movement as feedback. Extra artificial joint-turning forces do not replace the muscle drive. Recorded position-derived motion is reserved for evaluating the resulting path.

The correction branch uses feedback about the simulated body's position and movement, plus speed and acceleration limits. These can change the command target itself. That creates two legitimate but different scoring questions: how closely does each branch follow its own command, and how closely does each follow a common scoring reference derived from recorded movement? Reporting only the first could exaggerate the correction's apparent value by ignoring the altered target.

In the bounded 500-bin replay on the new recording, the typical corrected tracking error relative to its own command is 0.0374 radians, compared with 1.5803 for the raw command sent without feedback correction. Against the common recorded-motion reference after conversion to this body, corrected error is 0.26302 radians and raw error is 1.49325. Here "typical error" uses a root-mean-square calculation: errors are squared, averaged and square-rooted, so larger deviations contribute more heavily. A radian is an angle unit, with a full turn equal to about 6.28 radians. The common-reference comparison makes the target difference visible.[13]

The corrected maximum anatomical-limit penetration is about 0.000406 radians, below the declared 0.001-radian numerical tolerance. The raw replay violates that tolerance in 75 of 500 frames. These are model-coordinate checks under the numerical setup. They do not prove that a real subject's tissues experience the same loads or that a decoded command is biologically correct. A simulator's constraint is only as relevant as the model and task that define it.

The improvement belongs to the bounded controller after movement has been converted between bodies under the explicit rules. It remains a genuinely muscle-driven trajectory, and the scoring reference was not secretly supplied as feedback. This separates decoding quality from physical correction: the changed stage explains the improved trajectory without claiming recovery of hidden spinal signals or learning in the nervous system.

The human branch remains a reduced adapter. Its success cannot erase the failures in the native macaque branch, and it cannot justify sewing or fingertip manipulation in a model whose tested control concerns two larger arm coordinates. Physical grounding starts with a named task and a named body, then expands only when the additional coordinates, contacts and evidence are actually present.

25 Macaque Arm Geometry and Remaining Errors

The separate macaque body comes from the model family used for the source's arm analysis. It is closer to the relevant anatomy than a human arm with two controlled angles. It has seven source coordinates and 39 muscle-tendon paths. A coordinate is an independently named angle or motion setting in the model. A muscle-tendon path is the modeled route from one attachment to another, including how the route

[13] Local evidence: `artifacts/motor_transfer_physics_metrics.json`; evidence-matrix claim `new_day_muscle_retargeting`.

passes around nearby structures. The model's hand is rigid: it has no separate finger motions.[12, 23]

The retrieved revision postdates the source paper. Source-family membership is useful, but it does not prove that this revision is the exact model used for the original subject analysis. Matching joint names and units is not enough to certify matching specimen geometry. The project preserves that uncertainty. A later improvement in numerical agreement should not retroactively be described as recovery of the original subject's true anatomy.

The retrieved original model also contains zero-valued rate properties in its older muscle formulation. With those settings, it cannot calculate the required force-driven motion while keeping its numerical states finite. A separately named numerical fork restores 117 properties to defaults provided by the modeling software. A fork is a distinct saved version, not a silent edit of the original. The original geometry and the assumed default-rate version remain separately identified.[24]

Using software defaults makes a numerical experiment possible, but does not measure the subject's physiology. The assumed rates are not recovered activation times, tendon properties or force capacity. This distinction is especially important when a controller fails. The failure may reveal a limitation of the numerical assumptions or control design, but it cannot be assigned to a particular biological mechanism without further evidence.

Three native-body controller candidates are retained as rejected experiments. The first concerns an earlier source case with a different way of combining errors across joints. The actual-tendon-force feedback candidate measures modeled tendon forces and uses them in correction, yet still fails its reserved source comparison of tracking across all seven joint angles. This case had already been inspected before the initial-speed protocol was corrected, so the corrected rerun is development evidence rather than a fresh uninspected test. On its reserved source trial, its typical error is about 0.05505 radians, compared with about 0.04512 for the tonic baseline, a simpler controller that maintains its defined steady muscle drive. This error calculation squares all angle errors, averages the squared values across coordinates and time, then takes the square root. It does not average seven separately calculated typical errors. The more elaborate feedback is worse on that comparison.[14]

The short-horizon candidate tries possible commands in a copied model state before choosing what to do. It improves a synthetic validation comparison, from about 0.01989 radians for the tonic baseline to about 0.01270. On the reserved recorded-source case, however, it produces about 0.05971 radians versus about 0.03263 for tonic. It is rejected. Better performance on the synthetic validation case does not permit substitution for the failed source case.[15]

The copied-state planner also takes about 4.52 seconds to plan each 20-millisecond source interval. That is an offline experiment. Showing the resulting cached trajectory at normal playback speed does not turn its planning into real-time control. The checks that isolate copied state and restore model-owned control functions are useful implementation evidence, but the latency and tracking failure remain part of the result.

[14] Local evidence: `artifacts/native_force_metrics.json`; evidence-matrix claim `native_tendon_feedback_rejection`.

[15] Local evidence: `artifacts/native_horizon_metrics.json`; evidence-matrix claim `native_horizon_rejection`.

These failures give the architecture a concrete next problem: establish a stable, applicable numerical muscle-driven body and controller before asking it to evaluate learning rewards. The successful human-model movement-conversion branch does not answer that problem, because it uses different anatomy and a reduced task. A source-looking body is a better starting point for a source task, but its numerical behavior still has to earn its place through measurement, calibration and appropriate controls.

26 Muscle Paths and Physiological Validation

The native geometry audit reproduced an invalid muscle detour around a wrapping surface associated with the ulna, one of the forearm bones. A wrapping surface is a modeled obstacle that keeps a muscle path from passing straight through a bone or another structure. Here, a doughnut-shaped surface, formally called a torus, produced the detour in both the original geometry and the default-rate version. Making the muscle rates finite had therefore left the route problem unresolved.

The correction uses a rule derived from attachment topology. Topology here means which attachments and path segments are connected, rather than how an anomalous frame happens to look. The rule restricts three named wraps to the unique original segment from the humerus, the upper-arm bone, to the ulna in the forearm, using the software's numbering convention that starts at one and includes both ends of the selected range. No muscle, bone, attachment point or wrap shape is deleted to make the image nicer. The saved version names the three changed ranges and preserves the original model separately.[23, 24]

Across seven inspected anomalous frames, the correction removes 14 contacts outside that wrapping surface while retaining all seven coordinates and 39 muscles. It is tested on training samples, on already inspected diagnostic frames, and on a newly reserved same-session geometry window. Those supports have different evidential status and are reported separately. The checks also inspect the saved rotations and positions of rigid body parts and changes in path length as the joint angles change. They establish specified numerical behavior, not an independent anatomical measurement.[16]

A later comparison finds a broad length mismatch between this model family and the source-model-derived reference lengths. The project fits one common length factor using 128 training poses and all 39 ordered references. A pose is a set of model coordinates at a stated instant. To choose the common factor, multiply each model length by its matching reference length and add those products, then divide by the sum of the squared model lengths. That calculation chooses the single multiplier with the smallest summed squared length error on the training poses. It does not fit a separate shape to every pose or every muscle. The factor is 1.2413815, so the numerical scaling is about a 24 percent increase. It is estimated from training poses only and then kept fixed for separate validation and test poses.

On those separate poses, the typical length discrepancy falls from about 27.75 millimeters to about 0.552 millimeters. This is substantial agreement with a specific reference. The reference is itself produced by tracking and muscle-and-skeleton analysis; it is not a collection of directly measured fiber lengths. Consequently, the fit demonstrates im-

[16] Local evidence: `artifacts/monkey_wrap_candidate_metrics.json`; evidence-matrix claim `topology_range_candidate`.

proved agreement between modeled quantities under the stated source conventions. It does not identify individual bone dimensions, tissue mass, strength or activation rates.[17]

A separate saved version applies the frozen factor through the official OpenSim scaling tools. This is stronger numerical evidence than multiplying exported lengths after the fact: the model itself is scaled and its computed lengths are compared with the prediction from the single factor. Their maximum disagreement is about 6.13 micrometers. A consistency check on the modeled moment arms, the leverage distances relating joint rotation to muscle-path length, is within about 0.181 millimeters. These remain checks of the numerical model.[24]

The scaled version retains the assumed original masses and applies the corresponding geometric updates to rotational resistance and muscle-length parameters. No mass, inertia or physiology was measured for the subject through this operation. Dynamics and control are blocked for this scaled geometry-only version. Its 400 displayed observed and decoded poses reuse diagnostic frames and are not a fresh evaluation of decoded-pose accuracy. The number counts displayed model states; it does not add independently recorded subjects or a new test.




Figure 4: One common length factor, fitted on training poses, reduces mismatch on separate validation and test poses. The reference lengths come from source tracking and body-model analysis. Agreement with those lengths does not establish physiological calibration.

The order of events also matters for explanation. The known observed wrap anomaly occurs later than the evaluated window of the failed lookahead controller. The later geometry correction therefore does not establish that wrapping caused the earlier controller rejection. A useful repair can coexist with an unresolved failure. Treating every newly found defect as the explanation for every old result would replace testing with a convenient story.

[17] Local evidence: `artifacts/source_scale_frozen.json` and `artifacts/source_scale_metrics.json`; evidence-matrix claim `source_scale_fit`.

27 Template Anatomy and Participant Anatomy

A template brain is a useful reference shape. It is not automatically the brain of the person or animal whose electrical activity was recorded. Registration means establishing the spatial relationship to that actual subject with appropriate independent evidence. A template can illustrate where hand motor cortex generally lies while leaving exact electrode and neuron positions unresolved.

The current source reconstruction reproduces 122,284 template points, 244,760 triangles and 81,924 atlas values. The points are vertices: locations joined by triangles to make a surface. An atlas supplies region labels within that template. Three source MRI planes also match the named source. Those are useful checks of source correspondence, rather than proof that every biological interpretation of the image is true.

The mesh checks ask a narrow question: are these surfaces joined in the specified way? The two mid-cortical surfaces pass the specified closed-surface connectivity checks. Their Euler characteristic is +2: count the vertices, subtract the edges and add the triangular faces. That number summarizes mesh connectivity; it does not measure how closely the shape matches the recorded subject. The optional region boundary still contains 432 open edges, 838 inconsistent triangle directions and six invalid point neighbourhoods. Those defects remain even though the other surfaces passed their own checks. A second reader using the established nibabel imaging library was unavailable.

What can this template tell us about the recorded subject? The source checks do not register that subject, identify individual neurons, establish a region's function or supply an absent peripheral nerve measurement. A colour needs a declared value, source and time; brightness cannot improve the recording's spatial evidence.

A lifelike, tangible three-dimensional model would make the anatomical comparison inspectable. To judge it, we need a series of identifiable real-world references covering the relevant structures, views, poses, conditions and scales. One convenient picture cannot cover them all. Each reference must identify its original source, organism, body part, task, measurement method, units or scale and the exact feature it supports. Derived geometry and synthetic images retain their labels; neither supplies independent ground truth.

The comparison has to follow a part into the assembly. A plausible forearm could still meet a floating muscle, an implausible interface or an impossible joint pose. Comparable pose, projection and scale let reference and model views test those relationships. Close-ups, tilted orthogonal views along perpendicular axes, biological identification colours, transparency and cutaways can reveal them; the reveal still needs measured agreement.

Function adds another comparison. A displayed signal must keep its site, source clock, measured quantity and availability, with recorded channels, predictions and simulated muscle activation separately labelled. Body claims need held-out movement, joint and force comparisons wherever those quantities are claimed. Those physical measurements, full lifelike-anatomy review and independent part-plus-assembly reference acceptance remain missing.

The four historical figures here are diagrams and numerical plots with their original evidence scopes. They explain relationships; they supply neither newly validated lifelike 3D biological models nor the missing anatomical and reference-series comparisons.

28 Application Performance

The graphical user interface, usually called a GUI, should help a reader follow the evidence chain. Choosing another source must change the source label and clock rather than leaving a convincing stale value on screen. A gap in recorded support must remain a gap. A camera reset must not change the scientific meaning of a pose. Playback should show which values were measured, predicted or simulated, and whether they are current for the selected source interval.

The bounded original-control checks contain evidence for source switching, source gaps, replay and camera/restoration behaviour. Their acceptance is scoped. It is not whole-GUI acceptance or a measurement of better performance. Full source-clock, geometry, material, renderer-lifetime, functional-map, device, anatomical-reference and offline criteria remain binding.

The separately checked hand replay is deliberately a saved-data component. It automatically loads only an explicitly identified current cached replay. The demonstrated cache has 336 frames with a 20-millisecond source interval. Play, pause, seek, single-frame stepping and restoration have component-level evidence. If no cache exists for a selection, the component does not quietly request a new run. Missing values appear as dashes. An unavailable or failed source clears the prior replay and geometry instead of presenting it under a new identity.

Its saved development example shows 22 of 22 correct strikes, 6 of 6 chords, 22 of 22 timely releases, 34-millisecond worst timing error and no extra strike. A chord means more than one requested key at a time. Those values describe one constrained simulation example. They are not a replacement for the separate 32-phrase evaluation or the recorded-intention-to-contact study. Separate human neural clips do not drive the goal-driven hand policy.

Opening the online candidate requires its whole directory. HTML is the entry file a browser reads to assemble the page. Moving opaque resources out of it reduces that file from 113,298,857 to 34,295,597 bytes, while the complete candidate directory remains 93,831,812 bytes. The resources have moved within what must be delivered; the smaller entry file does not contain the application on its own.

The separate static offline export preserves the original source and occupies 113,581,899 bytes. Its supported static content can be accessed without the running online service, but research views that require the application service interface, or API, remain unavailable. Testing that original-source export and testing the whole-directory online candidate are different tasks.

File sizes establish a static packaging result. They supply no measured change in page-loading time, interaction speed, memory, crashes or graphics-processor performance. The candidate’s browser route was unavailable, so the candidate remains unpromoted; an asset archive and a source check cannot fill that missing interaction test.

The practical consequence is also scientific. An old trace under a new source label suggests a relationship that was never observed. A zero in place of a missing measurement asserts activity the recording cannot support. A saved replay presented as a fresh model run hides its development status. Delivery and playback have to preserve those distinctions before the reader can judge the displayed result.

The human EEG/ESG/ENG/EMG preview has its own evoked-stimulation context and clock. The macaque-derived human-arm branch has its own prediction and simulation chain. The GUI must not combine their appearance into a claim of simultaneous voluntary cortical, spinal, peripheral and muscle control. A hypothetical biological tutoring view must likewise stay hypothetical. The screen can explain a missing link; it cannot measure it by drawing an arrow.

29 Earlier Viewer

The application is intended to let a reader follow the chain rather than accept a still image. Source controls select a recording or an observation view. Replay shows recorded inputs and appropriate references. Model outputs identify what was predicted. Body views distinguish reference geometry, decoded geometry and numerical muscle-driven motion. Their coexistence makes comparison easier, but their labels remain necessary.

A moving skeleton can come from several routes. It may show joints obtained from upstream tracking and analysis. It may show joints predicted by a neural model. It may show the outcome of a numerical controller that acts through muscles. In the first two routes, the displayed pose can be set directly from coordinates for inspection. In the third, the motion follows the simulated forces and dynamics. Only that third route tests whether the chosen controller can move the numerical plant under its rules.

Playback has another distinction. A cached trajectory has already been computed and can be displayed smoothly. Paced playback controls how quickly the user sees stored frames. It does not report the time originally needed to compute them. The native lookahead result is the clear example: a normal-speed replay can show an offline plan that required seconds for each short interval. A real-time claim would need actual end-to-end timing under the deployment conditions.

The natural-language interface translates supported user requests into structured task descriptions. A person can ask to practise a slow precision reach or replay a supported recorded task. The compiler identifies a task, parameters and whether the available implementation can train or only display it. The structured description is written as JSON, a common text format with named fields and explicit values. This makes the request inspectable before execution.

The language interface turns a supported request into a specification the application can execute. That is its demonstrated role. Arbitrary prose does not become a verified neural program through the same step. A sewing request still needs sewing observations; a puzzle-manipulation request still needs tested object contacts and individual fingers. A fluent response cannot supply capabilities absent from the files and body model.

Sewing, Rubik's Cube solving and breakdancing remain future composite tasks. Sewing would need tested needle, fabric and fine-finger interactions; puzzle manipulation would need object contacts and controlled fingers; breakdancing would need whole-body balance and changing contacts. Each would also need recordings and outcomes appropriate to its learning claim. A reach primitive can be a useful component without becoming evidence that the complete task has been learned.

The skill-practice branch adapts two simulated controller gains. A gain is a number that determines how strongly the controller responds under its chosen rule. The learner compares outcomes using verified tracking error, effort and joint feasibility, and records reward/error curves and body replay. Its competitor is the existing controller, which is itself a candidate. Improved gain values can demonstrate a better numerical parameter choice for this setup; they do not demonstrate biological plasticity, retained human skill or a general reinforcement-learning teacher.

An interface can name a supported practice task, show its numerical history and body model, and expose where the controller failed. Showing the assumptions alongside those outcomes helps the reader judge the software. Whether a living learner retained a skill after assistance stopped requires a different test.

The application also preserves missing observations. A source view that lacks motor spinal channels should say so. A human surface preview should remain an evoked experiment on its own clock. A hypothetical organism render should remain a concept. This is not merely cautious captioning: these labels determine whether a downstream user interprets the system as replay, prediction, control or teaching. A truthful live demonstration can be ambitious while keeping those operations visibly different.

30 Digital-Fly Validation

A detailed neural map can support a useful prediction and still leave important predictions wrong. Shiu and colleagues tested a fly connectome-derived model with real perturbations and behavioural outcomes. Their tested successes coexist with missed effects involving Phantom and Usnea and wrong predictions for G2N-1 and Usnea in water-related silencing comparisons. Those are named circuit examples, not proof that the whole fly is wrong in every setting. Missing baseline activity and chemical mechanisms are among the discussed limits, including neuropeptides: small chains of amino acids used as signals. Those possible limitations are not uniquely established causes for each error.[25]

This is the positive standard too: a useful approximation earns its credibility through a test tied to a specified prediction. It does not need a claim of complete biological identity. A model can help science by showing where a structural explanation succeeds and where an additional measurement or mechanism is required. Retaining failures makes the next question more specific.

The official Eon technical account from March 2026 describes a different engineered integration. It combines a fly-derived brain model with body controllers and hand-chosen interfaces. It acknowledges largely missing state and plasticity and internal dynamics that were not yet validated against relevant known patterns.[26] That account supplies dated developer disclosures, not an independent full-animal reproduction

test. A sparse motor interface can produce an impressive body demonstration while leaving the biological mechanism unproved.

Two other source examples show why added software must remain visible. The pinned fly-chess code includes symbolic board inputs, a reduced mathematical network, a trained readout and external legal-move logic and lookahead. The pinned DoomFly code uses a different male nervous-system map, adds enemy geometry obtained from the game engine and trains an action readout. Its authors describe the failure of the originally intended looming-vision route. These are inspected software sources and author reports, not measured evidence that a living fly learned chess or Doom. Their playing strength was not independently reproduced here.[27, 28]

There is no verified primary evidence here that a FlyWire-derived brain performed something no fly could ever do in a lifetime. The source-supported criticism concerns the engineered inputs, controllers, mappings and training that supply the software's capabilities. Their biological interpretation remains unvalidated; a more dramatic impossibility claim would add no evidence.

Body simulation has its own failure modes. NeuroMechFly v2 reports that simulated leg tips can sit slightly below the ground because of numerical errors or instabilities. Its authors use a 0.05-millimetre margin to avoid a false detection of excessive stretching.[29] That is a documented contact artifact. It is not proof of gross tunnelling, perpetual motion or a FlyWire brain's impossible ability. A small explicit error is more scientifically useful than a larger invented one.

Published first-hand accounts of other simulations describe creatures exploiting numerical integration or contact errors that supply artificial energy. A model can then appear to move well for a reason that real physics would not permit. The error needs a physical repair and a new check; an improved optimizer would otherwise learn the error more effectively.[30]

An objective can fail even when the physics is not the problem. In the reported CoastRunners example, the agent kept circling reward targets rather than finishing the race. Its score improved while the intended outcome did not.[31] This is why a reward curve needs independent task outcomes. The number optimized must be checked against what the experiment was supposed to accomplish.

The protein example has a similar lesson about scope. The original AlphaFold3 paper reports 62.9 percent success on its specified structural-interface benchmark, with a 95-percent interval of 51.4 to 73.5 percent. That result averages over 65 interface clusters from 71 complexes and uses a structural agreement threshold and confidence-ranked samples: 1,000 seeds times five generated samples per target. The model generates these candidate structures by refining noise in stages, a method called diffusion sampling. DockQ is the structural-interface agreement score, and success means it exceeds 0.23. These generated samples are not independent biological experiments. Its 37.1 percent complement is the complement for that benchmark, not the percentage of every protein that fails to function in real life. Structure and biological function are different endpoints.[32]

Crystallization is a real obstacle for some measurements, but it is not the only route to a structure. Cryo-electron microscopy uses electron images of rapidly frozen samples. Nuclear magnetic resonance measures how atomic nuclei respond under controlled magnetic conditions. These provide other methods, each with limits. We do not infer

that most unknown proteins are unknown because they fail to crystallize.[33] Missing measurements are an important problem without inventing a universal failure percentage to describe them. Training can also draw on generated examples without every example containing neural signals, muscle activity and movement measured together. A simulation can supply an example; a model can supply a predicted training target, called a pseudo-label. Those values remain generated or derived. Agreement with the model or musculoskeletal simulation that produced them is not an independent measurement of living biology. Generated test examples can check a specified calculation, but they cannot fill a missing measurement. Biological claims still need comparison with independent measurements in the stated domain.

There are stronger positive examples for brain–body interfaces. Lorach and colleagues linked measured cortical signals to spinal stimulation and evaluated actual standing and walking in one participant with chronic tetraplegia. The movement happened in the person rather than only on a display.[34] The interventional outcome supports the stated single-participant interface; it does not establish every possible decoder, biological skill transfer or complete nervous-system virtualization.

Our own claim should follow the same discipline. Ask which quantity was observed, which mechanism was assumed, which outcome was independently measured and which comparison failed. Then state the tested domain. A realistic animation, a correct guess and a validated biological model remain different things even when all three look persuasive at first glance.

31 Prediction and Reward-Based Training

For a particular neural-to-body prediction, measured paired examples tell us which observations belong together. A supervised model receives an input and its corresponding desired output during fitting, then faces examples withheld under the stated rules. This gives the signal-to-target claim a reference before a controller changes actions to earn a reward. A movement component can also learn first from qualified movement-only data. That complementary route can supply a useful starting representation without supplying neural labels that were never recorded; its transfer still has to be tested.

The information supplied at prediction time defines the claim. An EEG-only predictor may use scalp observations and declared available context; it cannot secretly receive the muscle or movement target it is supposed to predict. EMG-only, movement-only and explicitly combined predictors answer other useful questions and need their own labels and matched comparisons. Muscle or body measurements may help teach a model during an explicitly declared training procedure without remaining available to the deployed EEG-only route. Such training information is called privileged because the deployed predictor does not have it. Independent evaluation must verify that the privilege ends where the claim says it ends.

Physical correction comes next, with the decoder held fixed. The controller can ask whether the decoded quantity leads to a feasible bounded movement in the numerical body. Holding the decoder fixed makes the comparison easier to interpret. If corrected motion improves, the improvement belongs to the control stage rather than being confused with a newly trained neural representation. The current human-model branch supplies a limited example of that separation.

Only after the relevant body and controller are stable does a reward-driven correction rule become a candidate worth testing. Such a rule would add a bounded correction to the existing command. Reinforcement learning is the general approach of changing action choices according to evaluated outcomes. In this project, any future such refinement must start with outcomes that the simulator can actually verify and with a fixed comparison against the supervised decoder and baseline controller.

Possible rewards include tracking a specified target, respecting joint and contact constraints, controlling effort, limiting abrupt changes in muscle-drive commands and completing a defined task. These are numerical criteria. Their meanings depend on the body model, sensors and task. A tracking reward can verify movement toward the simulator's target; it cannot independently verify the unobserved spinal command that supposedly produced that movement.

A controller can appear excellent when its answer is hidden inside its input. Feeding the recorded reference into action calculation changes the question being tested. Keep hidden test targets out of deployment. In the present bounded muscle replay, recorded position-derived motion is reserved for scoring and is not supplied as feedback. Future training and evaluation must disclose the information the agent receives.

Robustness also needs more than one successful trajectory. Future tests should hold out recordings and relevant body/task conditions, and should compare changes in morphology, friction, delay and measurement quality where those variables apply. A learned correction that exploits one plant's convenient numerical quirk may fail under another plausible setting. The test should be selected for the claim being made rather than expanded merely to accumulate impressive-looking cases.

This development order allows physics to reject impossible or unsuitable commands without pretending that physics identifies the true neural interpretation. It also prevents a reward curve from being presented as proof of biological learning. The current two-gain practice learner is a working software lesson interface. A general adaptive controller and a biological teacher remain separate future achievements, each with its own controls and failure criteria.

32 Matching future organisms to actual tasks

The broader architecture needs body models that fit the recordings and tasks. An organism-specific adapter preserves actual anatomy rather than blending convenient features from several species. Shared functional labels such as limb role, task direction, contact, effort or sensory quantity can help organize comparisons. They do not establish identical muscles, neurons or learning mechanisms across animals.

The virtual-rodent work is a relevant precedent because it combines animal behavior, embodied modeling and analysis of recorded groups of neurons. It supports the idea that an appropriately grounded body model can help ask questions about recorded activity. It does not imply that a human arm, macaque arm, rodent body and fly body can exchange neural commands without evidence.[35]

Choosing a body begins with actual anatomy, available recordings and a task the model can represent. A hypothetical animal drawing is not a validated body model or a

recording. A transparent render cannot supply hidden nerve measurements or show that an animal can tolerate a proposed interface.

Species selection remains a future decision. Care, development, available tools, ordinary behavior and interface burden all bear on it. A specified human biological feature or a tissue connection needs a comparison with direct measurements; the current companion supplies no biological outcome or repair result for those branches. A computational bridge must begin with the anatomy and data actually available.

A future rodent branch would require a supported rodent body and a task represented in matched recordings. A fly branch would need its own appropriate movement and neural sources and a body whose force-producing components have the correct declared interpretation. A human whole-body branch would require relevant contacts, muscles and task evidence beyond the current reduced arm. The source catalog can help locate candidates, but a candidate's presence in the list is not completion of these requirements.

Shared movement can provide a useful starting point before every source has paired neural recordings. Homologous structures share an evolutionary anatomical origin. Mechanically analogous structures can perform a comparable job without that shared origin. Either can motivate transfer when the actual similarities are stated: the joints and their movement directions, limb proportions, contact, loads and time scales. Similar-looking limbs need not have the same force capacity or move on the same time scale. A source-specific adapter must preserve those differences rather than quietly treating them as equal.

A movement representation could first learn from qualified motion capture, then be adapted using actual paired neural and body observations. Motion can also be retargeted to a declared body under anatomical and physical constraints. Here retargeting means calculating a corresponding movement for the new body; the calculated movement remains derived, not a newly measured neural pairing. Scans could constrain a specific anatomical gap after the selected model's own provenance has been checked. A scan from another person remains an external reference; it does not register the recorded participant or validate simulated forces.

A separate current hand/arm proposal would test movement pretraining across two people, with separately calibrated sensor-based movement descriptions. It would compare target-only training, the proposed anatomical mapping and a deliberately wrong mapping under matched resources. Its source and target archives, sensor conventions and numerical implementation still require admission; no new fit or successful transfer is reported here. Broader motion collections would need their own rights, task coverage and original-recording overlap checks before entering that route. Repeated copies of one source in different collections cannot become independent training and evaluation data.

Comparisons across organisms should include behavior-only and within-organism controls. If a shared representation appears helpful, sessions kept outside fitting, animals and eventually species should test where its help persists. Anatomical similarity can motivate the comparison without supplying cell identity. Missing channels should remain unavailable or explicitly inferred with a stated uncertainty method, rather than being reconstructed into the observed-data column. Useful mechanical transfer would earn a claim about that tested mapping; neural equivalence, causal physiology, sensation delivery and biological teaching still need their own evidence.

The proposed middle ground is therefore functional coordination with preserved anatomy. A task may ask different bodies to move toward a target or control effort, while each body uses its own joints, muscles and sensor models. That makes the research question concrete: which representation helps under these adapters and controls? It avoids claiming a universal nervous-system language before the experiments show one.

33 Next Experiments

The next computational question comes from the failed comparison. Both recurrent candidates miss the original no-harm and positive-neural-information requirements, and all five added benefit claims fail. Lower average error admits neither predictor. NeuroTranslation remains a proposed field; NeuroTranslator remains recording-specific software.

A further proposal would have to connect supported observations to decoded estimates, pass them through a declared body adapter and identify the feedback returned. Simple baselines need the same tests. Illustrative motor replay or a deliberately goal-driven simulation can examine that bounded computation if its goals, assistance and simulator information are disclosed. A positive neural-control claim still requires a predictor that passes the unchanged criteria; the current candidates do not.

That leaves two questions for the sections that follow. *Tests of Retained Learning* asks what remains when teaching help stops. *From a reach to a testable prediction* develops the paired mechanism, and *Measure both ends. Test the translation.* specifies its observations and comparisons. Reward, simulation and independently measured task outcomes need separate checks. Physical calibration, synchronized recording chains, participant-specific registration and generalization remain unverified. Better simulated control would support that tested computation; biological teaching, retention and repair still need their own evidence. Their absence leaves room for a clearly bounded computational proposal, not a biological result.

34 Tests of Retained Learning

The biological learning ambition needs a different kind of evidence from model prediction. A tutor could provide commands, feedback or task information that improves a pupil's performance while connected. That is assistance. To claim learning, the experiment must show a change in the pupil's later independent performance under an appropriate test. To claim faster learning, it must compare the relevant practice, information and time budgets.

Biological and computer-based tutors need separate tests. A biological tutor would be an experienced partner under a specified linking condition. A computer-based tutor would supply assistance under a defined rule. Either could help a pupil while connected without producing learning that lasts. Compare their effects through the same measured task and matched conditions, rather than assuming that the identity of the tutor explains the result.

Experience itself needs a control. An experienced-to-novice pair should be compared with a novice-to-novice pair and with individual practice. A matched no-link condition keeps the relevant experience, exposure and setting while removing the proposed live signal connection. A pupil that practises alone supplies a training control; it is not the same thing as a previously tutored pupil being tested alone after training. Groups need comparable task exposure before retention is assessed. Otherwise a benefit could come from extra practice, observation or assistance time rather than the proposed transfer route.

Time-shuffled or yoked comparisons can help identify whether the proposed signal alignment contributes. A yoked condition receives a matched amount of assistance according to another trial or rule, rather than assistance appropriately contingent on its own current state. The exact design belongs to the future experiment, but the principle is to make information timing and assistance budget separable. A simple controller and a behavior-only predictor are also important competitors. More neural measurements should have to show an additional relevant benefit.

Retention should be measured after tutor commands stop and again after an appropriate later interval. Transfer should ask whether improvement helps on a task condition, maze or body condition withheld from practice. Accuracy, consistency and independent control need explicit definitions. A new-looking maze image is not automatically a new scientific test. An equal target score does not prove equal difficulty across route designs or bodies. Those difficulty comparisons need their own measurements and rules. A well-executed rehearsed route can coexist with poor adaptation to a new route, and a one-time success during guidance can coexist with no later benefit.

Replay comparisons also need to identify what is being replayed. A proposed test can compare activity from the same pupil and matched session with stale or unmatched activity and with an inactive or sham comparison. A sham is a control that resembles the relevant procedure without supplying its proposed active contribution. These are conceptual study-design distinctions, not current animal results. They help test whether the matched signal matters beyond the existence of a device, a replay label or an extra source of help.

The persistent-interruption branch requires particular care. Suppose the pupil needs a standardized compensatory interface to express any movement through the interrupted route. Switching off that entire interface prevents motor expression whether or not the pupil learned. The retention comparison should remove tutor commands while retaining the necessary bridge and measurement conditions. A comparison in an intact group, or another independently justified test, may be needed to answer different learning questions. Bridge-off failure alone cannot establish absence of learning.

The corresponding positive claim also needs discipline. Success with the bridge present could still depend on active compensatory computation. The experiment should identify what remains constant, what the tutor previously supplied and what the pupil now controls. A result can demonstrate independent control through a necessary bridge without demonstrating that the interrupted tissue regenerated. Learning, assistance and regeneration are different outcomes even when they concern the same movement.

Humanized and graft comparisons add their own mechanism questions. A changed cell population or host–graft connection would need a specific definition and a justified measurement. It cannot be described as making the animal a miniature human or

as supplying an unspecified universal repair. Disease-specific branches need disease-specific outcomes. These are proposed research comparisons, and the current application supplies none of their biological results.

The computational prototype contributes an instrument-building discipline to these future stages. It can specify tasks, record where sources and commands came from, preserve timing, compare predictors and expose physical failures. It cannot replace experimental responsibility for a living pupil or infer plasticity from a software reward. The claim worth pursuing is measurable improvement that remains when the tutor's contribution is removed under the right conditions. That is a harder and more useful claim than an impressive assisted performance.

35 Tests That Could Reject the Proposal

A proposal becomes scientifically useful when it says what would count against it. The broader NeuroTranslation idea should lose a comparison if it does not help. A simpler instrument may capture enough information. A behavior-only predictor may outperform added neural channels. A model matched to one recording may beat a shared model. Ordinary practice may produce the same retention as a proposed neural tutor under matched exposure.

Several current results already have this structure. The transferred fixed core had to beat every predefined control and did not. The shared candidate had to improve validation evidence against retained specialists and did not. Native force feedback and copied-state planning had to pass their reserved source comparisons and did not. These failures are not proof that all future variants will fail. They are evidence that these particular variants have not earned the broader claim.

For the next body experiment, a useful milestone is a stable numerical body appropriate to the source whose control comparisons survive appropriate cases kept outside fitting. If geometry, force behavior or timing cannot be calibrated sufficiently for the task, the project should report that limit rather than use a prettier animation. For the next recording experiment, a useful milestone is matched voluntary measurements with explicit time and quantity support. If the added levels do not improve a relevant comparison, their cost and burden need to be reconsidered.

For a future tutor, the decisive milestone is independent retention under matched conditions. If a pupil improves only during guidance, the result supports assistance. If retained improvement is no better than ordinary matched practice, the proposed tutoring mechanism has not shown an advantage. If improvement stays on one practiced route but does not transfer, the claim should remain task-specific. Each outcome can still be useful when it is named accurately.

There is also a practical distinction between new information and more computation. A model cannot recover a verified label for an unmeasured quantity simply by becoming larger. It can make an inference, but the inference needs its own uncertainty and evaluation. If the missing variable is contact, specimen geometry, channel correspondence or upstream timing, a targeted measurement may resolve the problem more directly than further optimization on the same incomplete data.

We want the instrument to expose these limits early. That is a design judgment, supported here by the source-processing failure found in the audit and the failed native-body comparisons, rather than a measured biological result. Preserving the failures and each quantity's origin makes the next question easier to choose. Hiding them carries the same assumptions into a larger system that is harder to check.

The proposed new approach is therefore an evidence sequence: identify observations, preserve their meaning, fit a bounded model, check its predictions, test applicable mechanics, and only then test a specified teaching claim. The sequence is not guaranteed to culminate in instant skill acquisition. It is designed to reveal where the ambition fails and where an additional measurement or simpler solution actually helps.

36 Terminology and Measurement Plan

The shared names identify what is being tested. Interoceptomics combines interoception and connectomics: how sensing conditions inside the body relates to nerve-cell connections. NeuroTranslation names the proposed mapping between defined neural situations; NeuroTranslator names the implemented software; NeuroTranslation Network names the larger proposed design. Their roles were introduced in *Neural Signals and Physical Skills* and remain distinct. These are working project names, not externally established standards or evidence of a universal decoder or biological teaching. The definition supplement retains the explanations and older technical aliases.

Four other meanings must stay separate. Physical scale concerns sizes and distances. Organizational level concerns whether we study a whole body, an organ, a circuit or cells. Computational detail concerns how much information one software calculation represents. Statistical averaging concerns how we combine scores or observations. An average across several output groups is not a measurement of a larger piece of anatomy. A small model is not evidence that it measures individual nerve cells. Calling a result macro or micro without saying which of these meanings is intended would hide the very distinction the programme needs to preserve.

Future body observation would synchronize the left and right tripod views of the hands and arms. A separate perpendicular depth-sensing view could be compared for what it reveals or misses. This software did not acquire or calibrate either arrangement. A transparent body model, cutaway or colored nerve layer explains selected relationships; it does not turn hidden structures into measured signals. Proposed tissue and interface comparisons need their own measurements over time. An unchanged replay file does not demonstrate an unchanged living connection.

37 Reproducing the Studies

Reproduction begins with source identity. A dataset name is useful for orientation, but exact files, versions and checksums identify the bytes that were processed. A checksum is a compact computed fingerprint of file contents. It helps a recipient detect a different or corrupted file. It does not certify that the experiment's labels are correct, that a source license permits every reuse, or that the model trained on those bytes is biologically valid.

The package should preserve original source links, acquisition receipts and the scope of each check. The full human recording-header files, whose filenames end in SET, were verified, but the acquired previews of the large signal files, whose filenames end in FDT, cover selected byte ranges rather than the complete large data files. Their locally hashed ranges must remain described as partial support. A whole-file claim would require a whole-file check. Derived replay arrays also need their own hashes and documented extraction rules.[14, 15]

The computational recipe includes event sorting, half-open time bins, channel masks, unit conversions, coordinate transforms, numerical scaling calculated from training samples, random starting values, exact data divisions, boundary gaps, model selection and the saved model state kept fixed for evaluation. A half-open bin includes its starting boundary and excludes its ending boundary, so events on boundaries are handled consistently rather than counted twice. These details are part of the result because changing them can change the inputs and scores.

The body recipe includes the original asset, named forks, software revision, modeled constraints, controller settings and evaluation conventions. MuJoCo and OpenSim have separate environments in this project. A portable neural decoder does not require native OpenSim execution, while reproducing the native controller experiment does. The reader must not assume that one dependency list or a working dashboard recreates every mechanical result.[11, 22–24]

The evidence matrix maps the numerical claims in this document to inspectable project artifacts. Its claim groups retain the exact metric fields and interpretation limits. The long reader version explains those values; it does not generate a second experiment or alter the frozen scientific record. The source package also includes schemas and executable translation examples so that numerical predictions and their response metadata can be checked independently of the visual interface.

Previously invalid results remain withdrawn. The unsorted-event muscle-signal results, borrowed-rotation exports, stale control-function bindings and corrected initial-velocity protocol are not positive evidence to be revived by a later summary. A reproducible release needs the current valid states and the reasons earlier states were superseded. Software tests and archive checks then establish specified numerical integrity rather than a general certificate of scientific truth.

At this snapshot, the new project is a local reviewable software and manuscript effort. A verified public repository or deposition for its own code is not claimed. Responsible authorship, affiliations, an explicit code license, upstream attribution and an honest declaration of AI assistance remain release responsibilities. No submission to arXiv or a journal is implied by the formatting of the document. Public-source availability and local-project availability are different statements.

38 From a reach to a testable prediction

Start with a movement we can measure well. For the proposed snap showcase, the arm begins extended with the palm down. The elbow and forearm swing and turn; the wrist and hand turn upward during the snap, then move down to rest. The model must account for that whole movement, including the preparation, contact and return. Finger pairing, organism-specific anatomy and timing still need a real-reference series;

a human-looking animation cannot establish that a particular monkey can perform the same gesture.

The cup reach supplies a simpler precision comparison: relate recorded signals to measured movement before attempting the coordinated snap. Each task still needs its own anatomy, contact, timing and independent comparison.

That comparison connects three interacting groups: task-linked brain observations, named-muscle observations and a musculoskeletal simulation. A learner would relate the observations to the mechanics; independent movement and contact measurements would test its predictions. EEG records scalp electrical activity and surface EMG records muscle electrical activity. A separately recorded nerve or spinal signal needs its own declared channel. The proposed apparatus uses two arm sleeves, scalp EEG and synchronized, calibrated left and right tripod views. Vendor, channel, bandwidth and clock qualification remain open.

Intent to action is the target. By understanding and measuring the intermediary, we aim to make that mapping as close to one-to-one as possible within a declared task. Specify what counts as the intended action, the participant and session, state and context, permitted history, tolerated error and independent reference. The test then asks whether observing the middle reduces ambiguity and improves prediction or qualified control. It does not assume a unique hidden intention or claim that the best possible mapping has already been achieved.

The proposed learner must explain the recorded brain and muscle activity, where the hand moved and when. These are proposed comparisons: no paired trial, trained model, data acquisition, fine-tuning, reinforcement-learning rollout or accepted checkpoint is established for this EEG/EMG/movement loop. Its sources and permissions, physical and computational behaviour, clinical interfaces, reference comparisons and held-out tests still need independent assessment.

The completed LINK comparison supplies a warning about what would count as success. Its 18 runs and 720 saved epochs tested a different question; both model-admission gates and all five benefit claims failed. Neither those runs nor a future successful prediction would show that a learner received sensation or produced an action. Recording, prediction, simulated movement, sensory delivery and physical action each need evidence of their own. EEG and EMG recorders alone cannot write sensation, and no sensory delivery or physical actuation is established for this proposal.

38.1 Form, function and action need a measured middle

A structural map constrains what a system could do. A NeuroConnectome maps specified neural connections; its organism, coverage, resolution and source would have to be declared. The signals passing through those connections still have to be observed or inferred, with the difference made explicit. To predict the next action, we need the processes that turn structural constraints into an outcome. The proposed programme follows form to function to action, while intent to action names the task-level translation we want to improve.

DNA to RNA and RNA to protein put a process between a starting constraint and its downstream product. Regulatory context, RNA processing and cell state change what

that process produces; protein structure alone does not determine the behaviour of a whole cell. The modelling jobs differ: AlphaGenome regulatory prediction [36], scGPT cell-state modelling [37] and AlphaFold 3 structure prediction [32] address different parts of that chain. AlphaTranscriptome names a desired predictive capability here. Connecting the predictors would still leave system dynamics and the environment to account for, with experimental outcomes needed to test the combined prediction. These modelling examples do not establish an integrated cell programmer. The comparison uses the reported modelling roles of AlphaGenome and scGPT; their complete methods have not been independently assessed here.

In the biological pathway, Brain2Spine and Spine2Body name proposed links to test; their composition is the Brain2Body aim. The spinal cord integrates descending and sensory signals and contributes local coordination, reflex regulation and adaptation. This is a different mechanism from RNA processing, but it serves the same explanatory purpose: account for the context-dependent process between an initial constraint and its outcome. The constrained example of Spinal sensorimotor adaptation [38] illustrates a spinal process; supported observations would have to test our proposed pathway. Where they are absent, the internal states remain inferred or simulated. Physical spinal work remains read-only. That example establishes neither unrestricted skill transfer nor validation of our proposed pathway. The comparison draws on the abstract and relevant author-manuscript passages; equivalence to the final published edition and the complete methods and statistics remain unverified here.

Thought2Action relates a declared intention to an independently measured action. Action2World follows the action to its consequence in the task environment; Thought2World names the proposed composition. Body2World drew attention to the consequence outside the body; Body2Action focuses on body mechanics and a specified task outcome, while Brain2Motion focuses on the movement pathway. These working labels identify related scopes for a test. They do not establish interchangeable or working controllers.

The engineering route connects neural activity to musculoskeletal simulation and then to a programmable model, toward NeuroTranslation. The proposed movement-focused learner is a large movement model. System 3 thinking names the proposed human–AI supervisory partnership around it. The supervisory model would compare task strategies and diagnose where neural or mechanical predictions miss independent measurements, then propose training or calibration comparisons for the signal mapping and virtual body. The task learner would perform the declared prediction or control; the supervisor would help choose what to test. Neither role replaces the biological spinal intermediary or a physical interface. Final held-out outcomes must remain outside rewards and model selection.

Shaw and Nave's SSRN preprint, *Thinking—Fast, Slow, and Artificial*, and its institutional discussion provide conceptual context for this proposed human–AI role. [39] The comparison is limited to that framing; the complete preprint and institutional article have not been reviewed here. Neither establishes a third anatomical brain system or validates this programme's proposed learner or supervisor. Expert footage may supply movement and tactical examples, with rights and camera uncertainty accounted for; it supplies no measured expert EEG, EMG, muscle force or stimulation plan.

Action changes the outcome. Its sensory consequences inform perception and the next intention. Independently measured movement would anchor the action part

of that loop; it would not by itself decode a unique sensation or perception. Known stimuli, measured feedback and appropriate recordings or reports would have to test those further mappings. The return path must therefore be measured rather than drawn into existence. The full Interoceptomics aim includes internal-body sensing and connectivity; external touch and proprioceptive tasks contribute evidence but do not by themselves solve that wider problem. A prediction, assisted execution and retained skill without assistance answer different questions. Each wider claim must earn its own independent comparison.

38.2 Context connects. Grounding checks

Within a reach, context has a concrete job: relate brain activity to muscle activity in this task and at this time. Attention offers a candidate computation for those relationships, following Vaswani et al. (2017) [40] and Tsai et al. (2019) [41]. The model compares a representation called a query with representations called keys, then uses the resulting weights to combine their values. Masks keep unavailable observations and future samples out. The calculation weights information; it does not establish that attention understands all context.

To see what those weights mean, follow one permitted observation through the calculation. An encoder turns a stated signal segment into a list of numbers, called a vector. Learned calculations produce three such descriptions: the query describes what this part of the model is looking for, a key describes an observation it can compare with that query, and a value carries information that observation can contribute. These are roles in a calculation. Their entries are learned features, not automatically electrical amplitudes, muscle forces or identified nerve cells. The original channel, time and quantity still need their own labels.

The proposed technical method writes the operation as

$$\text{Attention}(Q, K, V) = \text{softmax}\left(QK^{\top}/\sqrt{d_k} + M\right)V.$$

Read it from the inside out. Q holds the query vectors, K the key vectors and V the value vectors. A query and key have the same number of entries, their common width d_k. For one query–key comparison, multiply corresponding entries and add those products. That sum is a dot product. The representations are learned; multiplying and adding form the numerical matching score. It is not a measured biological connection strength or proof that the matched observation caused the movement.

The superscript T on K means transpose. It rearranges rows into columns so the matrix multiplication can calculate a score for each query against each key. Transposing does not reverse the recording's time order or change which electrode supplied a value. Dividing the scores by $\sqrt{d_k}$ means dividing by the square root of the common vector width. With comparably sized components, a wider dot product can have a larger scale; this division counteracts that typical growth before scores become weights. It does not calibrate the prediction's uncertainty or establish a physical unit for a learned feature.

M is the admitted mask. For each query it specifies which observations may contribute. In the additive form shown, an allowed entry can leave a score unchanged, while an excluded entry can be represented by negative infinity so that it receives zero

weight. The actual numerical implementation still needs checking. An unavailable input is not an observed zero, and a query with no admitted keys has no admitted weighted answer; the interface must preserve that unavailability rather than manufacture a normal-looking result.

Softmax converts the permitted scores into relative weights. It applies the exponential function to a score, giving a positive quantity, then divides by the sum of those quantities for that query. The permitted weights therefore sum to one when an admitted answer exists. A larger score receives more weight; softmax does not simply choose the largest score and discard every other permitted observation. The final multiplication by V multiplies each value vector by its weight and adds the results. That combined representation still needs a declared output calculation to predict a named target in its stated units. A neat set of weights is not yet a correct reach.

The mask must enforce the claim all the way through the calculation. For an EEG-only prediction, withheld muscle and movement targets cannot re-enter as queries, keys, values or features computed upstream. Future observations must also stay out of a prediction issued before they are available. A timestamp alone cannot establish this: filtering, alignment or scaling could already have used a later sample. Calling the attention mask causal cannot undo that earlier leak. Shared cues and movement artefacts still need their own controls, even when every matrix operation is correct.

No query, key, value weights, EEG encoder or gradient route have been selected or executed for this proposed loop. The calculation supplies an inspectable method. Independently measured movement must still supply its test.

A pattern can fit inside the model and still describe the wrong movement. Grounding therefore means testing the declared prediction against qualified observations under the same conditions. Independently measured movement would check the outcome, while muscle activity would add an observation that constrains the brain model. Even a matching reach cannot identify a unique private experience. The proposed paired trial would have to show which of these observations adds useful information.

38.3 Muscle activity tests the brain model

Record brain and named-muscle activity during the same reach. In the proposed paired trial, EEG would sample scalp electrical activity and surface EMG would sample activity associated with the named muscles. Paired training could use the muscle observation to constrain their relationship. Then withhold the muscle target and movement reference from the EEG-only predictor: can the permitted brain observations predict a specified muscle-activity observable or movement?

Pairing and calibration remain proposed. Shared cues and movement artefacts could give that predictor a shortcut, so the comparison needs controls for both. The muscle observations would cover only the named muscles, and EMG supplies neither afferent nerve activity nor direct force. Sensory claims still need known stimuli and measured feedback. Several neural states could remain compatible with even a well-matched pair; the pair could narrow a task-specific explanation without revealing the complete hidden brain. Checking the movement itself requires the next independent observation.

The candidate reference at https://www.nature.com/articles/sdata2018133 has not yet been checked for exact support or reuse rights.

38.4 Measured motion tests the virtual body

Measure the same hand and arm from the aligned left and right tripod views. The proposed motion-capture relay-composite would align the two point maps in a common clock and coordinate frame, then join them into one composite while retaining each point's origin. Before that joined map can check a prediction, its calibration, alignment and capture precision would have to be independently verified.

The movement map would constrain the external movement model: surface motion and pose in the task's physical frame. To explain that motion mechanically, the internal musculoskeletal model would describe specified bones, joints and soft tissues. Organism, developmental stage and task would determine the appropriate anatomical sources. X-ray projections could inform bone and joint relationships; appropriate MRI references could inform specified soft tissues. Registration, rights and source-specific limits would need independent checks. No scan set is selected for this proposed comparison. Anatomy still leaves activation, forces and neural function to test.

With a qualified composite, the musculoskeletal-simulation physics-engine's joints, muscles, contacts and physical limits would face a measured comparison. The simulation methods in Seth et al. (2018) [24] and MyoSuite documentation [42] would support this comparison: fit the model on training data, then compare its predicted reach with held-out measured movement. A force claim would require an additional force measurement. The body's form limits possible motion; measured function would test the mechanics and show where they need refinement.

A lifelike hand could expose a missed contact or a late reach. The comparison still needs independent capture alignment, precision, mechanics and biological fidelity; none has been demonstrated for this proposal. Captured geometry cannot establish hidden neural state, internal forces or unique subjective experience. It would check the declared movement prediction within those limits.

38.5 Two pairs. One conditional learner

The learner would have two connected jobs: relate EEG observations to muscle activity, and relate measured movement to predicted mechanics. Large movement model names the proposed family; deep neural network describes a possible implementation. Large refers to intended scope, not a demonstrated parameter count. Encoders would accept only observations permitted for the named test. Two branches could use the attention and multimodal computations of Vaswani et al. (2017) [40] and Tsai et al. (2019) [41] to summarize those relationships in a shared task representation, with separate output parts for each direction's targets.

Signal features belong to branches, and branches belong to the learner. That hierarchy describes the computation, not two anatomical thinking systems. A common clock, task and physical frame would connect the branches; independent measurements would check their errors. Form constrains the prediction, and checked function would guide refinement. Several hidden states could still fit the same reach, so neither

a shared representation nor conditional predictions would establish an exact inverse nervous system. The architecture has not been selected, implemented, trained or independently accepted. To choose it, we would have to compare it with simpler baselines on appropriately reserved observations.

38.6 Learn the movement, then test what transfers

A recording of a reach already contains a possible lesson for a computer: use the earlier movement to predict where the hand goes next. It need not contain EEG to pose that question. A separate proposed comparison would ask whether learning from one person's grasp-and-lift movement helps predict another person's movement. The WAY-EEG-GAL description identifies continuous recordings of lifting series as well as separate windowed trials and lift-summary tables.[43] The continuous movement could supply both the history and the later checking observation. It would not require matching AllLifts Run or trial rows, and it would create no measured neural pair between the two people. The original study of five complete weight series remains a different design.

To transfer anything useful, we must say what corresponds. Homologous structures share an evolutionary anatomical origin. Mechanically analogous structures can perform a comparable job without that shared origin: a robot gripper's opening and a human thumb–finger opening might both describe how an object is approached. That example would require a separate robotic study; the proposed two-person study would not test it. Each body keeps its own joints and possible directions of movement, positive-axis conventions, proportions, muscle–tendon roles, loads, inertia, contact and timing. Two similar-looking limbs need not generate the same forces or move at the same rate. Calculating a corresponding movement for another body is retargeting; the calculation remains derived, alongside separately identified tracking observations, estimates, predictions and simulations.

The proposed description of movement contains thirteen quantities. Three give the index sensor's position relative to the wrist, three do the same for the thumb and three for the object. One describes the distance between the two digit sensors; the final three describe wrist velocity using only information already available. Thirteen extra mask values say which features are actually available. Each person needs checked position units, sensor placement and a wrist orientation that turns positions into the intended frame without reflecting the body. After the checked conversion to metres, the middle, or median, wrist-to-index-sensor distance from that person's assigned training support supplies a positive length scale for position and velocity. This is a sensor-distance scale, not a measured bone length; development observations do not set it. Velocity is also multiplied by the same 0.1-second interval in both people. The thirteen prediction features then have no physical units. To recover velocity errors in metres per second, multiply by that person's length scale and divide by 0.1 seconds. Missing features contribute no target error; writing a masked zero does not make a missing observation measured. These features do not supply all finger joints, individual muscle forces or the person's inertia.

The model would use fifty movement frames at 100 observations per second to predict 100 milliseconds beyond the latest filtered input actually available. The source rate must first be checked as 500 observations per second. A proposed filter combining 51

present and earlier samples would precede keeping every fifth sample, producing 100 observations per second. Its linear-phase delay is 50 milliseconds. That delay stays in the account of when the information became available; moving a timestamp backward cannot make the predictor respond earlier. Filter coefficients, the frequencies it preserves, timestamp conventions, gaps and handling at recording edges still need checking. Only the named movement columns may enter. The source's kinematics matrix also contains force-plate signals, which cannot quietly become movement features.

Knowing which input was read is different from knowing whether two inputs are independent. Trustworthy published participant attribution, an unchanged exact archive entry and a checked capture can identify the participant record and recorded input without requiring one particular spelling of an ID inside the file. They do not authenticate a biological person or prove that two files came from different original acquisitions. A longer recording and its trimmed copy could have different names and file fingerprints while sharing the same movement. Shared samples, trims, derived versions and overlaps must therefore remain together as one acquisition group before filtering, cutting windows, scaling or assigning roles. The complete public non-ST roster and these relationships still need establishing. All 294 rows of the earlier AllLifts table remain unavailable for training, evaluation and assigning trials or acquisition groups. ST, competition storage and reserved LINK recordings remain closed.

Qualified P1 groups would provide the earlier movement learning. P2 groups would be divided between target training and development checking. At least two independently established P2 acquisition groups are needed. If there are $G \geq 2$, a fixed hash calculation ranks their established original-parent identifiers; the first $\lfloor 3G/5 \rfloor$ become training groups and the rest become development groups. The floor brackets mean rounding down, so the nominal 60/40 division is explicit even when the number of groups is small. The exact identifiers, how they are written as bytes and the complete roster must be settled before ranking or seeing outcomes. The order is not chronology and need not balance lifting conditions. If uncertain ancestry forces all P2 recordings into one group, the comparison stops. Cutting that group into windows cannot create independent training and checking acquisitions. No actual group or movement segment has been assigned by this proposed identity method.

The three training arms keep the target task and model the same. B0 first learns from correctly mapped P2 training movement. B1 and B2 first learn from exactly the same P1 windows in the same order. B2 uses the proposed correct correspondence. B1 deliberately uses the thumb sensor for the index role, the object sensor for the thumb role and the index sensor for the object role, leaving the wrist anchor fixed. Both use the same correct source calibration and scale before this change, then the same correct target adapter and ordered target-training batches. Sampling gives each original acquisition group balanced treatment and records repeated as well as unique windows. The learner might undo the false correspondence; changing roles can also change which features are available. Equal numbers of updates do not give the arms equal diversity of source movements. Those limits must stay in the explanation of any difference, rather than prompting a more convenient control after results are known.

The proposed network is a single gated recurrent unit, or GRU, layer: a calculation that updates a numerical memory as it reads the sequence. It has a memory width of 32, accepts the thirteen movement features and thirteen masks as 26 inputs, and predicts thirteen outputs. That software memory is not measured biological memory. Each arm

uses the same initialization for a given fixed random seed, with seeds 17, 31 and 73. Every arm/seed receives 200 earlier-learning updates and 100 target-training updates, using batches of 16 examples. Adam, the proposed weight-update rule, has learning rate 0.001, beta settings 0.9 and 0.999, epsilon 10^{-8} and zero weight decay. There is no clipping, changing learning-rate schedule or early stopping; the final update supplies the checkpoint. During training, squared prediction errors are averaged over observed target features; a batch with no observed targets must stop. Across three arms and three seeds this would be 2,700 updates. None has been performed for this comparison. No external checkpoint is selected, and the numerical updates, filter, precision and actual computing limits still need independent checks.

For each development acquisition group and seed, the proposed score adds the squared errors for the observed target features, divides by how many such targets were observed, then takes the square root. It then averages those group scores equally, so a long recording does not automatically outweigh a short one. A comparison with no observed targets has no valid denominator and must stop. The report must give feature counts, missing observations, errors converted back to physical units, uncertainty and a persistence forecast—continuing the latest available movement value—using the same information endpoint. Every worse group or feature remains visible. B2 would need lower normalized error than both B0 and B1 in each fixed seed, with no applicable original requirement failing, to justify another investigation. Two people and development checking do not establish performance across a population, untouched final confirmation or biological teaching.

Larger movement collections could supply more examples after their exact files, permissions, relevant movements and original-recording overlap are checked. AddBiomechanics distinguishes recorded markers and ground reactions from fitted joint movements and torques estimated by inverse dynamics—calculating forces or torques consistent with motion and a body model. Those estimates are not new direct force measurements. The selected AMASS asset would need its research-use, non-commercial and redistribution terms checked. The same original recording in two collections stays one source, not independent training and checking data. LaBraM's earlier training inventory flags the WAY source family, but exact checkpoint, participant and trial exposure remains unknown. A later decision to reserve a recording cannot remove its possible influence from already trained weights. No such checkpoint is selected for this comparison.

Scans have a more specific job than making the body look complete. Before adding X-ray/CT or MRI, check which anatomical sources the chosen musculoskeletal model already uses. A new scan is useful when it fills a stated gap or provides a genuinely independent check. Its person or species, scale, registration, permissions and uncertainty still need checking. Registration establishes the correspondence between that image and the body being studied. Another person's scan remains an external reference; a generic body model does not secretly measure this participant's geometry, muscle activation or forces. No scan set is selected here.

The actual eligible recordings, acquisition groups, units, frames, clocks and calibration are still unresolved for this continuous comparison. It reports no new fit or successful transfer. A movement description that proved useful could later be tested alongside genuinely paired neural and body observations, using only the inputs allowed for that prediction. The transferred or calculated target would not become a simul-

taneous measurement. The useful next answer is where the movement forecast improves, where it worsens and which measurement or assumption explains the difference. Neural equivalence, causal physiology, delivered sensation and a skill that remains after guidance ends would each need a further experiment.

38.7 Pretrain. Pair. Verify. Refine

Those comparisons start with the observations we may use. Data rights, calibration and held-out subjects, sessions and tasks determine which can enter the study; resolve them before processing data or choosing a model. Open-source code does not grant blanket permission to use datasets, checkpoints or clinical interfaces. Qualified data could first train representations for each recording type. LaBraM, described by Jiang, Zhao and Lu (2024) [44], is one EEG encoder candidate, not a complete brain-body writer. Synchronized paired observations could then train the declared mapping from permitted inputs.

That first split has to survive the model's past. Before fitting a scaler, training a tokenizer or selecting an encoder, identify the exact proposed checkpoint and its pretraining corpus: versions, original recordings, participants, sessions, tasks and every derivative used. The same recording can appear in several collections; overlapping windows can appear under different filenames. Keep those copies and derivatives with their original recording and participant when defining the applicable splits. A new archive name does not make the person or trial new.

The current overlap audit flags the WAY-EEG-GAL source family in LaBraM's pretraining inventory. The exact checkpoint, participant and trial exposure remains unknown. No LaBraM checkpoint has been selected for the separate proposed hand/arm transfer comparison, and its target development observations are development data throughout. A model tested there cannot be described as independently confirmed on untouched final recordings. The audit needs the actual source and checkpoint identities before that stronger claim can be assessed. Unknown overlap is a limit on an independence claim; it is not a blanket prohibition on useful pretraining or transfer.

For components fitted in this study, means, scales, tokenizer parameters, codebooks and encoder updates must use only their assigned training support. Development observations can make the predeclared selections; final held-out observations must not set the preprocessing, representation, mapping, stopping point or reward. A separately admitted external pretraining corpus can be useful, but its exposure remains part of the model's history. Removing a record from the later fine-tuning set cannot remove its influence from weights already trained on it. Freezing a previously exposed model does not turn that record back into independent final confirmation.

LaBraM's candidate sequence separates three learning problems. First, a neural tokenizer would learn a way to describe specified signal segments. A tokenizer is the calculation that turns those segments into model tokens. In this route, a learned set of numerical patterns, called a codebook, supplies discrete code identities for the segments. A code identifies a model pattern; it is not an EEG voltage, a neuron identity, a muscle command or a word whose meaning is already known. The codebook's learned numerical entries and the code labels that select them are different things. Their signal support and tokenizer version have to stay with the training record. The segment

definition, tokenizer objective and numerical implementation remain choices to qualify; none has been selected for our paired learner.

Second, masked neural-code prediction would train an encoder using those code targets. Hide selected signal segments from the predictor, give it the admitted remaining context, and ask it to predict the code identities assigned to the hidden segments by the specified tokenizer. Its output assigns scores or probabilities to possible codes. The training loss penalizes a poor prediction of the saved target code at the hidden positions. Computing that target from the original training segment is legitimate supervision; leaking the hidden segment, its target code or a feature calculated from it into the predictor would defeat the exercise. Predicting an easy-to-leak answer would teach us little about the representation.

Hiding a segment for learning and excluding an observation by permission serve different purposes. A learning mask makes a stated prediction exercise; an input-availability or causal mask limits what the named route may know. Pretraining must declare its permitted context. An offline masked-segment exercise does not by itself establish that an online prediction uses only available past and present inputs. That later claim needs the entire input route checked under its deadline, including the preprocessing.

Third, downstream fine-tuning would adapt the representation to the declared task. Actual paired observations would supply the named EEG, muscle or movement targets for the permitted direction. The outputs would then face their own units, uncertainty, baselines and independent measurements. A useful code prediction score cannot substitute for a movement error, a force measurement or retained biological learning. Likewise, the previously reported neural next-bin training is its own objective; it is not evidence that this staged tokenizer route has already run.

Movement-only pretraining and unpaired representation learning remain useful candidate routes. Transfer may use homologous structures with shared anatomical origin or mechanically analogous structures with comparable jobs, after their actual mechanics, scale, timing, contact and missing features are qualified. Such training could supply a movement representation before every source has simultaneous neural observations. Retargeted or learned movements must keep their derived identity; they do not become measured neural–muscle–movement pairs. The proposed transfer and the paired prediction ask complementary questions, each with its own matched controls and independent target. Neither is a new fit or a successful transfer reported here.

Paired prediction would give later refinement a baseline to beat. Before optional reinforcement learning, post-training or task-specific fine-tuning, the physical predictions and reward need checking against independent outcomes; a reward the computer can calculate supplies no biological proof by itself. The offline reinforcement-learning method of Kumar et al. (2020) [45] is a candidate only where qualified actions, transitions and rewards support it: labels alone cannot tell us what an untried action would do. Backpropagation can update differentiable neural components, but it cannot automatically pass through every physics engine. The simulation methods in Seth et al. (2018) [24] and MyoSuite documentation [42] do not establish universal differentiability for this proposed route. Simpler baselines and frozen final tests remain through every phase.

This proposed paired training sequence has not been carried out.

38.8 Respond quickly. Improve carefully

A frozen accepted model would provide the proposed response: predict from permitted past and present observations, then prepare encoded outputs for a qualified interface. Inspecting the errors would be a separate job. That path would calibrate and propose a candidate update, to be independently evaluated with a restorable checkpoint before it could replace the running model. Updating an estimate of the current state therefore differs from changing learned weights; examining an error would not silently change the predictor.

This fast-and-slow comparison is a Kahneman-like analogy for the proposed division of work. It does not identify two biological systems or assign inherent thinking speeds to EEG and spatial data. Real-time performance would have to be measured from acquisition through filtering, alignment, inference, output, feedback and rendering, including delay tails and jitter. No accepted model, real-time demonstration or running system that adapts under these rules is established here. The loop has no measured end-to-end latency or accuracy guarantee.

That timing comparison must also count missed deadlines. An observation that arrives too late cannot repair the response already due. Test the complete chain while it coexists with the declared healthy workloads, and report the conditions as well as delay tails and jitter. Timing one model calculation alone cannot establish that acquisition, prediction, output and feedback meet the task's deadline together. These remain proposed measurements, not a real-time result from this loop.

38.9 Write sensation. Enact action

What reaches the learner when the computer has made its prediction? A sensory transducer would have to deliver a sensory output; a controller and actuator would have to produce action in a virtual, robotic or later qualified biological body. Input and output describe the computer boundary. Afferent and efferent describe physiological direction relative to the central nervous system.

A display or haptic interface supplies sensory feedback, which differs from direct neural writing. Direct cortical writing could have a sensory role without being a peripheral afferent signal, just as a robot command is not an anatomical efferent nerve. EEG and EMG recorders do not write, and predicting an EEG-like pattern does not deliver sensation. Each proposed output needs an independently qualified interface, permission for its use and a measurement of what it delivers. No such physical interface, stimulation, acquisition or actuation is established by this proposal.

Comparing a recorder with a sensory or action device requires evidence about what each measures or delivers. The clinical source could not be read, so it supplies no methods evidence here. Implanted precedents cannot establish that EEG or EMG recorders are equivalent to devices that deliver sensation or produce an action. Those physical additions remain unpriced and outside the acquisition and virtual-modelling scope.

38.10 Close the loop with evidence

Return to the cup with two independent checks: withheld body observations for the brain-to-body prediction, and the recorded neural target for the conditional estimate from the body. Agreement between the models or a high reward could still accompany a wrong answer. Neither establishes a unique inverse brain or someone's private experience. A later sensory or action interface would need a further measurement of what it delivered, under which conditions, with what error and delay.

Approximation gets us towards plausibility and virtualization gets us to precision. Independent measurements, repeatability, causal checks and stated error bounds must earn that precision; the proposal supplies neither perfect biology nor an automatic result. The original held-out and real-reference controls would test where each prediction works and where it fails. The retained-learning controls ask a further question: what remains when useful guidance stops, with any necessary movement bridge kept constant?

Physical sensory writers, transducers and actuators remain unpriced additions outside the acquisition and virtual-modelling costs. Those costs cannot tell us the price of delivering sensation or action. No completed loop, training or physical-writing result is claimed here. *Follow the action, then test the prediction* develops the tasks that would challenge the mechanism; *Measure both ends. Test the translation.* gives the detailed measurement and validation protocol. Comparable observations, predictions and errors would make those tests possible.

39 Follow the action, then test the prediction

Watch a ball pass from one hand to the other. Where were the hands? When did one let go? When did the other catch it? A model might follow the movement and still get the handover wrong. That is why the next proposed study needs more than a picture that looks convincing. It needs observations that can disagree with the prediction.

We aim to connect a stated intention with an action as closely as possible in a defined task. Understanding the process between them should make that connection more specific. The test must still say whose movement it concerns, under which conditions, how much error is tolerated and which independent observation checks the result. It cannot turn success in one task into a complete map of the mind.

39.1 Three recording views of the same event

The scalp recording, arm sleeves and left/right tripod views introduced in *From a reach to a testable prediction* would have to agree on which event they observed. The two surface-EMG sleeves would record one arm each; scalp EEG would record scalp electrical activity, EMG muscle electrical activity, and calibrated cameras the hands and arms. Their sites, units, capacity, clocks and delays need checking before a handover can be called a shared observation. OpenBCI or an equivalent configurable system remains an unacquired, unqualified candidate.

For this hand task, the motion-capture relay-composite would join the left and right observations. Earlier top and bottom dot maps describe another proposed configu-

ration. Each needs its own calibration and visibility checks. An unseen finger remains unseen even if a model can draw a plausible replacement; the display must keep that prediction separate from measured points.

The virtual body would then predict a response for comparison with the measured movement. Its joints, muscles and contacts need appropriate reference evidence. EMG does not directly measure force or incoming sensory-nerve activity. If the claim concerns contact or force, the experiment needs an observation that can check that claim.

39.2 Let the task ask the next question

Start with rapid hand rubbing. Contact and movement happen together, so matched conditions are needed to find what each contributes. Record the requested knuckle movement and the stretch with interlaced fingers, palms turned outward and arms extended as distinct actions. The cold-hands example explains the rubbing; it does not establish a cold-exposure experiment or a measured sensation.

Then pass a juggling ball between the hands—the proposed hot-potato task—and progress to the preferred two-ball juggling task. One hand's release changes what the other must do. The model now has to account for both limbs, the object and the timing of a catch. Check it against simpler predictions from the cue or previous movement; those may explain an apparent success without useful brain information.

The boxing stage would distinguish stated punch types from independently observed movement. It would become NeuroBoxer, a proposed virtual game. A prime-era Mike Tyson opponent gives the game a recognizable aim; it supplies no physical opponent or guarantee about injury. Boxing also uses the hands and wrists for stabilization. Footage of an expert can show movement and tactics, subject to its rights and camera limits. It cannot supply that expert's brain signals, muscle signals or force measurements.

Toy archery adds another relationship. One hand holds while the other draws and releases; the fingers change as the arrow leaves. The proposed apparatus has arrows with small, cup-shaped suction tips and an over-arm pouch with several arrows. NeuroArcher would turn the measured coordination into action on a virtual target. A hit in the game still needs the appropriate test before it can mean anything about biological control.

The complete snap described in *From a reach to a testable prediction* tests another relationship: preparation, contact and return must all agree with the specified movement. The cup reach remains the simpler precision comparison. Both need organism-specific anatomy, contact, timing and real-reference evidence; a human-looking animation cannot establish that a monkey can perform the snap.

39.3 Hands first; a brain contribution needs its own test

The first game milestone would use measured body motion. A later milestone would ask whether permitted EEG observations can control a specified virtual action without using withheld muscle or movement targets. Eye activity, small covert muscle contractions, residual movement, cues and information from the future could all make a pre-

diction look better. Those alternatives need declared controls. Looking hands-free is not enough.

Keep the original brain-only, body-only and paired comparisons, including the simple prediction that the target stays as it was. Set the allowed history and the original success rules before fitting anything. Keep required people, sessions and tasks separate before making time windows, and learn preprocessing from training data only. A pretrained model's earlier exposure must be checked before a recording can serve as independent final confirmation.

Recorded body observations could also predict a stated recorded EEG feature. That reverse prediction is conditional: several brain states might fit the same movement. It does not deliver a sensation. Qualified data and simpler baselines come before paired fitting or fine-tuning. Reinforcement learning would need specified actions, resulting transitions and rewards, rather than merely a prediction error. A reward inside a simulation is not a biological result. Final held-out tests stay outside training and selection; a running model stays frozen until a candidate update is independently evaluated.

39.4 A recording device does not become a writer

The output boundary in *Write sensation. Enact action* applies to these tasks too. EEG and surface EMG record; neuromuscular electrical stimulation (NMES) and functional electrical stimulation (FES) can cause contractions or functional movement. A body-output experiment or sensory writer would need its own qualified interface and permission. Physical spinal work remains read-only, and these physical additions remain outside the acquisition and virtual-work budget.

A proposed blindfolded condition removes visual feedback; it does not prove neural control or learning. To ask what was retained, remove tutor information while keeping the necessary movement bridge and comparable task conditions. Check what the learner can still do against the original controls. These recordings, writer experiments and retention tests have not been performed here. The current LINK failures remain failures; the sequence gives the next paired study questions it would have to answer.

40 Measure both ends. Test the translation.

The following prospective protocol tests the paired learner described in "Two pairs. One conditional learner": can permitted observations on one side of a sensorimotor task predict withheld measurements on the other, on recordings the model has not seen? The apparatus remains non-invasive EEG, non-invasive surface EMG, a calibrated motion-capture relay-composite, an open musculoskeletal-simulation physics-engine with a lifelike explanatory view, and an open multimodal model. Its acquisition and validation are unfinished.

The earlier brain–muscle and measured-movement–virtual-body comparisons define the two pairs. Here the protocol specifies their records, targets, calibration and independent tests. Anatomical form constrains possible mechanisms; measured function must test the proposed connections. A conditional learner's combined prediction must answer to measurements outside itself.

40.1 Keep the observations distinct

Keep raw EEG, raw EMG, derived features and movement estimates in separate records. Identify the participant and session in each record, then declare the sensor sites, references, coordinate conventions, units, sampling and timestamp semantics, and clocks. Trace every processing step and preserve missing intervals and uncertainty. Retain task instructions, stimulus events, observed behaviour and any separately obtained participant report. Independent participants or recordings cannot supply a simultaneous brain–muscle–movement observation.

Surface EMG records muscle electrical activity. A sensory-loop claim also needs known stimuli and appropriate measured feedback, contact or force channels; muscle recordings do not provide incoming sensory-nerve traffic. Preserve the actual spatial resolution of EEG measurements and source estimates. Templates and explanatory cutaways do not register participants or localize individual neurons.

40.2 The spine shapes the loop

The spinal cord changes how sensory input becomes muscle output. Account for local coordination, sensory gating, reflex gain and some lasting adaptations, rather than reducing it to a transmission delay. Separate a response to the current posture or task from a change retained after training. Keep both apart from adaptation in sensory receptors, peripheral pathways, neuromuscular junctions and mechanical tissues. These processes interact; changed output alone does not locate a memory.

Human H-reflex conditioning and the constrained mouse adaptation studied by Lavaud and colleagues ask different questions.[38, 46, 47] The human experiments do not establish brain-independent skill learning. The mouse study does not establish unrestricted walking or reaching. Circuits required for acquisition or recall are not thereby exclusive memory-storage sites. Our human comparison uses the abstracts, selected results and limited methods passages. The mouse comparison also draws on relevant author-manuscript passages; equivalence to the final published edition and the complete methods and statistics have not been established here. Passive proprioceptive training motivates a peripheral observation model; its psychophysical and spindle-afferent experiments were separate.[48] Those observations do not establish complex memory stored in peripheral axons.

Define the function before choosing its computational substitute. Candidate functions include gain and inhibition, phase- and load-dependent sensory responses, coordination across supported muscles or joints, relevant rhythms, and acquisition, retention and expression of a declared adaptation. Give each function its own task, species, anatomical scope, measurement and reference. Naming a mechanism does not show that the model implements it. A hand task cannot inherit an unmeasured locomotor circuit.

Record task context and history. Distinguish the state within a trial from a learned parameter change; retain elapsed time, intervening activity, resets, drift and uncertainty. Recorded spinal or peripheral activity needs supported channels of its own. Where those observations are absent, label internal state as estimated or as a simulated controller. EEG, EMG and movement cannot be relabeled as recorded spinal activity or identified interneurons.

Declare controls and endpoints before fitting or experimentation. Test immediate context effects separately from retention after a declared interval and from peripheral or tissue changes. Preserve the original held-out subjects and tasks, eligible independent measurements, matched baselines and ablations. Check alternative explanations, time shifts, missing inputs and artifact leakage. Lower movement error alone cannot locate a biological adaptation, establish its cause or certify useful plasticity.

To externalize a specified function, propose a substitute that can be tested through declared peripheral and cerebral interfaces. Compare latency, state dependence, stability, uncertainty and measured outcomes with the specified biological function. Computational feedback, peripheral stimulation and restored biological function require different evidence. A matched virtual trajectory does not demonstrate spinal replacement, relocated learning or clinical repair. Keep the spinal-cord site, measured function and proposed computational substitute distinct. Physical spinal scope remains read-only.

40.3 Give the two directions different targets

For brain-to-limb prediction, give the model EEG and only the declared context available at inference. Test its predicted muscle and movement observables against withheld measurements. A brain-only condition receives no measured EMG or movement input. If those inputs help, evaluate them in a separately labeled hybrid condition.

For limb-to-brain prediction, give the model muscle activity, movement and declared context. Its answer must allow for different patterns in the supported recorded EEG features. A conditional distribution assigns probabilities to specified feature values or ranges, given those inputs. Compare that prediction with independently retained EEG, then report uncertainty and alternatives. Movement can narrow the possibilities without identifying a unique hidden brain state or subjective experience. Agreement between learned models is a consistency check; it cannot supply the measured target.

40.4 Reading a signal and writing an output

The protocol records EEG and EMG; its two prediction directions do not themselves deliver sensation or enact a movement. “Write sensation. Enact action” defines the computer and physiological boundaries. Testing a writer would additionally require a separately qualified sensory writer or transducer, a specified actual response and distinct device, measurement, safety and clinical evidence. Indirect sensory feedback and direct neural writing remain different interfaces; a predicted EEG feature is neither. Enaction needs an appropriate virtual, robotic or biological output interface. A robot command has an action role, not the anatomical role of an efferent nerve.

Physical sensory writers, transducers and body actuators remain excluded from the acquisition and virtual-work plan, unqualified and unpriced. This proposal authorizes no stimulation, participant acquisition, biological actuation, new equipment purchase or training.

40.5 Align before learning

Calibrate the acquisition views. Verify their clocks against recorded events, offsets and drift, while preserving occlusion and dropout. Keep a missing observation missing: a predicted finger position is not a measurement. Declare frames, scale, joint conventions and acceptable spatial, temporal and end-to-end errors before selecting equipment or models. Position, joint, contact and force claims each need an appropriate independent reference.

Specify how the virtual body represents subject scale, muscles, tendons, joint constraints and contact. Declare its integration settings and observation models. Biomechanical simulation predicts mechanics; VFX rendering makes those predictions visible. Judge individual parts and their assembly against the original anatomical, physical, functional and real-reference-series criteria.

40.6 Build an open corpus without inventing pairs

Inventory neural structure, neural activity, muscle structure and muscle activity as separate domains. Use measured movement and task context as constraints. For each source, record rights, version, access conditions, species, participants, tasks, montages, units, clocks, preprocessing and missing paired modalities. Broad open-data coverage remains a continuing objective, not an assertion that every dataset is accessible, licensed, compatible or already used. Check code, pretrained weights and training-data rights separately.

The candidate uses an encoder for each modality, explicit input-availability masks, a shared conditional representation and separate decoders for the two directions. Keep simple EEG-only, EMG-only, movement-only and hybrid baselines. Define pretraining, post-training and fine-tuning tasks before fitting. An existing encoder supplies a candidate component, not an already established brain–body model.

40.7 Make the reward answer to measurements

First test paired supervised prediction in each direction. Compare any later reinforcement-learning or other closed-loop refinement with that baseline. Evaluate independent movement measurements, task outcomes, relevant contact or force, latency and physical validity. Freeze reward units, terms, weights and decision thresholds before evaluation. The candidate cannot invent the target against which it earns a reward.

Backpropagation updates model parameters. Reverse prediction estimates another observable. Measured biological feedback comes from the body. Identify which process the study actually implements. A supervised prediction error alone does not establish reinforcement learning: a proposed control study must also declare its state, action, transition and reward.

Partition eligible participants, sessions and novel tasks before preprocessing or model selection. Preserve TRAIN-only normalization, frozen seeds and checkpoint selection, untouched held-out evaluation, uncertainty and original negative controls. Include informative missing-modality, time-shift, artifact, drift and alternative-inverse

comparisons. Keep reserved recordings closed and retain completed fits and failed benefit conjunctions. Evaluate frozen inference separately from any proposed adaptive update. This prospective protocol admits no new fitting, optimizer update or model/backend promotion.

40.8 Show what was measured and what was inferred

Show the selected source clock and the inputs available to each prediction. Place recorded EEG, muscle activity and movement beside their predictions, with uncertainty, errors, gaps and stimulus or contact context. Identify recordings, inferred features and simulation as separate layers. Preserve site/channel inspection and source-time play, pause, seek and step. Unsupported peripheral or spinal pathways remain visible gaps. An animated cord cannot substitute for a spinal recording or supported anatomical localization.

41 Demonstrated Results and Open Questions

The current LINK comparison completed and failed its original improvement requirements. Earlier results support certain recording-specific predictions and reject fixed-core transfer in favour of a locally calibrated specialist on a separate old-day recording. The muscle-driven tests distinguish successful reduced human-arm correction from rejected native macaque controllers. Source and geometry defects keep their withdrawal and repair records. These are bounded results that a reader can inspect, each with its own tested scope.

The three later hand-related results must stay separate. The neural classifier correctly identified 116 of 150 later attempted-finger labels in one locally calibrated participant. In the linked simulation, 41 of 60 supported source intentions became correct contacts while all 54 issued supported commands were executed and 13 unintended presses remained. The separate goal-driven hand policy completed 32 of 32 constrained simulated phrases. Those fractions have different denominators because they answer different questions.

A simulated hand can execute its command accurately even when the neural decision chose the wrong finger. A hand policy can learn a requested key sequence without recorded brain activity driving it. A simulation can be mechanically checked without proving that a person learned the same action. None of these results establishes biological teaching, a neural policy for the phrases, simultaneous voluntary brain–spine–nerve–muscle control, universal mastery or a unique translation of private experience.

The next comparison depends on measurements and checks still missing. The proposed neural-context branch has not run, and current fitting is not admitted; reserved recordings stay closed. Complete independent checkpoint/update, random-state, reload and trajectory evidence is absent. Real-world joint and force measurements would test the mechanics, while subject registration and resolved units and clocks would establish which body and interval the values describe. Source-aware functional maps, lifelike 3D reference series, whole-GUI acceptance and the limits of disconnected service each need their own review. Another report check cannot answer those questions.

Can measured neural and bodily relationships make physical learning more effective and leave a learner more capable after assistance stops? That remains the question to test. The present software helps formulate it and exposes where its assumptions fail; it supplies no skill file to accept on faith. Progress requires experiments specific enough to show a benefit, or show where the proposed route fails.

Evidence, scope and edition status

The computational studies in these unpublished working manuscripts lead to a separate proposed paired experiment. No new fitting, reserved-data evaluation, model promotion or biological teaching is reported here. The negative results constrain the next test; they do not finish it. The common optimizer still needs independent implementation checks, including final-checkpoint and update verification. Reserved confirmation, complete GUI and offline checks, and applicable anatomical and functional reference comparisons also remain open.

The original tolerances and reserved recordings remain unchanged. A failed comparison cannot become a successful one through revised wording. Scientific, clinical, physical, real-reference, rights and runtime claims still require their original validation. Manuscript sources, citations, figures, rendered outputs and publication have not completed their checks. Source support for a negative report establishes neither full scientific validity nor a qualified interface or release.

This edition uses the 194-entry shared glossary, revision 29, SHA-256 4189722b `c823c1634084c4a28b93dcc198e583f2b11443e315f0cb593fd9b038`. Its 178-entry definition supplement and 16-entry addendum retain their scientific meanings. Four component entries now use the October 19 names and explain the proposed roles beside their measurement limits. Lookup labels can refer to related or contrasting ideas; the entries explain how the terms are used here. Earlier definitions remain in their historical editions. Updating the vocabulary does not revalidate the earlier studies or establish a proposed capability.

A generated illustration can explain a mechanism; it cannot replace the working model or measured evidence.

The packaging comparison in *Application Performance* distinguishes whole-directory online delivery from the separate original-source static export, whose API-dependent views were unavailable. The candidate’s browser route remains unverified and unpromoted. File sizes establish no interaction, loading, memory, crash or GPU performance result, nor a newer browser qualification.

The requested public byline is `@eliminatenoise`. Author identity, applicable affiliation and repository submission requirements must be resolved before publication. No affiliation or publication acceptance is implied.

The retained metadata and bounded passages for Logothetis and colleagues, Tang and colleagues, the quantum-measurement scientific background, and the NIST measurement-uncertainty guidance support only their stated uses here. Complete manuscript citation and claim verification remains pending.

42 Exactly What the LINK Controls Change

A model can improve its average by doing better on one recording and worse on another. That is why the LINK comparison keeps four results visible: two finger groups on each of two validation dates. A better average cannot cancel a harmed group.

The study pairs recorded neural features with measured positions of the index finger and the combined middle, ring and small-finger group in one macaque. It trains on January 27 and 30 and February 4 and 5, 2020, then selects models on February 6 and 11. Those positions retain the source's normalized units. They are not forces or a reconstruction of every finger joint. There is no simultaneous muscle, peripheral-nerve or spinal recording in this comparison.

Every example contains eleven successive neural bins, ending at the position being predicted. A twelfth bin supplies the next-neural target used by the extra-task model. All twelve must be in the same trial, with adjacent recorded times between 18.5 and 21.5 milliseconds apart. Even a baseline that never uses the twelfth bin needs it to be present. Everyone is therefore compared on the same examples. The ten earlier gaps span a history before the current bin; the nominal 20-millisecond interval does not turn that history into a measured nerve-conduction delay.

The 192 neural inputs contain 96 transformed threshold-crossing counts and 96 archived power features. Both sets follow the same physical electrode contact order. A contact is not a permanently identified individual neuron. Scaling uses only the four training dates, counting each trial-owned frame once. Repeated overlapping windows do not give that frame extra influence over the scale, and validation answers do not supply scaling statistics.

The first training date fixes the contact order. The count and power columns move together when reordered, so both descriptions still refer to the same declared physical contacts. The count transformation takes the natural logarithm of one plus each nonnegative count. It keeps a zero count at zero while compressing larger counts. The archived power features keep their supplied numerical scale; the two feature types are not converted into one physical quantity merely because they enter the same model.

The scaler calculates a separate mean and population standard deviation for each transformed feature. Population standard deviation means subtracting the mean, squaring those differences, averaging over all the fitting frames and taking the square root. Those calculations use float64, the declared numerical format with more precision than float32. Each unique frame belonging to an eligible training trial contributes once across the training dates, even when many overlapping windows later reuse it. The scaler therefore describes those frames, rather than a new weighting produced by how often they appear in windows. Validation supplies neither a mean nor a spread.

Normalization subtracts the training mean and divides by the saved training spread. Exactly zero spread is replaced by a divisor of one, which avoids division by zero for a constant training feature. There is no other minimum spread: a small nonzero value is not raised to a chosen floor. There is no clipping to trim large normalized values. This is the exact retained numerical rule, not a general recommendation to change it after inspecting a result. Replacing a zero divisor does not fill a missing observation or prove that the underlying biological signal is constant.

The transform is calculated in float64, then its output is cast to float32 for the model. Casting means representing the computed values in the other numerical format; rounding can occur. It does not improve an electrode's physical accuracy or settle an uncertain unit. The position targets keep their archived float32 values. The constant reference uses the mean of unique trial-owned training positions. Nonfinite measurements, unknown contacts or incompatible data descriptions cause a failure, rather than silently dropping rows or filling them with invented values.

The source descriptions leave several conflicts visible. A threshold-crossing attribute says volts, while the quantity is interpreted as event counts; the comparison makes no voltage conversion. It also retains the archived power values without an unexplained multiplication by four in the author's loader. Neither choice establishes absolute power calibration. The documented 32-millisecond interval differs from the retained nominal 20-millisecond clock. The observed timestamps and their allowed jitter define this recipe; the conflict remains unresolved, rather than being repaired by silently changing the interval. Full author trial counts must agree with trial-stop timestamps, and time-series references that are uniformly one entry short are identified separately. Changing units or discarding an inconvenient boundary would change which experiment was being compared.

The recurrent model reads each window from its declared starting state. Its numerical memory is reset between windows; it does not carry the previous window's final state into the next one. Adjacent windows may reuse some source samples, but that overlap is not an extra memory channel. Each prediction must be accounted for by the input window and the fixed model it declares.

Within the window, each new bin updates the hidden values. The position output combines the final hidden values with another description: for every neural feature, its mean across all eleven input bins. That mean retains the feature's average level while discarding its within-window order. The final recurrent state can depend on the sequence. The output therefore has access to both descriptions; a benefit from history alone cannot be attributed uniquely to recurrent ordering. That is one reason for the separate order control.

A separate linear output predicts the next neural feature vector. It remains present in both candidate architectures, but has zero objective weight for position-only fitting. Its presence does not give that model an additional movement target. Likewise, an old software name for the position output does not turn the normalized position estimate into velocity. These statements describe the retained recipe; they do not independently verify every state reset, prediction or update in the completed execution.

The first control asks what happens when the training pairing is broken. Imagine each example's neural history and its next-neural target held together as one packet. The control moves that packet to another example within the same training date, while the position answer stays where it was. It moves whole eligible windows, not individual channels or bins, and not whole trials as blocks. Overlapping windows can move separately. The same fixed shuffle serves every epoch of that run. It is shared by the two model types starting from the same seed, but differs across seeds and recording dates.

The two validation recordings remain unchanged for this control. We therefore fit on mismatched training pairs and ask how the resulting model predicts the ordinary measured validation positions. Some windows can accidentally stay in place; common task

structure also remains. The control challenges the declared association without proving that every other association has gone.

The second control asks whether the declared order helps. Number an input's bins from zero to ten, with ten being the current bin. The control presents them as nine, eight, seven, six, five, four, three, two, one, zero, ten. The ten older bins reverse; the current bin stays last. Position answers and next-neural targets remain unchanged. This happens in both training and validation. The operation is fixed, uses no random draw and preserves all the values in each window. A model could learn the reversed arrangement, so this is a particular order comparison rather than a guarantee that timing information has vanished.

Both model types start from each of three fixed seeds: 20261007, 20261008 and 20261009. The starting tensors are checked against the saved initialization for that seed. A separate generator restarts from the same seed in each paired run and draws one training-row order per epoch. For the association shuffle, another generator starts at the seed plus one million and advances across the four dates. Matching seeds specify matching procedures; they do not themselves prove that the completed execution followed every procedure.

There are 40 epochs per run, with batches of 256 and a retained final partial batch. Every epoch remains in the record. Each seed selects its lowest average validation error across the four date/group cells, taking the earlier epoch on an exact tie. Final predictions average all three selected seed models equally. Neither control competes to become the chosen measured model. Two model types, three seeds and three conditions produce the reported 18 runs and 720 saved epochs.

The simple linear references try five fixed penalties: 0.01, 0.1, 1, 10 and 100. A tie selects the smaller penalty, then the current-bin reference ahead of the history reference if their selected errors tie. A tie between the two measured recurrent ensembles selects position-only. These rules prevent a favourable seed, epoch or tie decision being quietly substituted later.

The protocol asks five further questions: does the position-only model beat current-bin ridge; does it beat its reversed-history control; does the extra-task model beat current-bin ridge; does it beat its own reversed-history control; and does the extra-task model beat position-only? Each comparison requires all three conditions together: a strictly lower average error, no higher error in any date/group, and a negative upper end of its paired 95-percent error-difference interval. Lower error is better, so a candidate-minus-reference interval wholly below zero favours the candidate.

That interval repeatedly samples whole supported trials within each validation date, keeping every sampled trial's supported frames and using the same draws for the models and groups. It uses 1,000 draws with fixed seed 20261007 and linear percentile interpolation. It describes uncertainty within these validation-selected comparisons; it does not confirm a result in a new animal or on a reserved recording.

For model admission, the three-part comparison is made against the selected best linear reference. Every date/group must also have a defined, positive ordinary prediction score, called R^2, and exceed its matched association control. Ordinary R^2 compares error with predicting that validation group's mean; the separately named training-mean score uses a different reference. An undefined value cannot count as a pass. This model-admission rule does not replace the five separate benefit comparisons.

The retained independent postfit checker records each condition separately for all five comparisons. Every comparison has a lower average error, yet every one makes at least one date/group worse. Three intervals have an upper end below zero. None of that cancels the failed no-harm conditions: all five benefit claims fail, and both models fail their separate admission rules. These are the existing decisions, not a newly calculated result.

The remaining checks concern how the learning calculation was performed. The order-control ledgers have empty provenance fields; the source and earlier control evidence do not provide a new dynamic reversal check. The correctly negative postfit report also cannot independently verify every optimizer update, checkpoint or restored random state. A completed run and a saved file are different evidence from that verification.

The later recordings remain closed: February 22 and 24, 2020, and June 21 and 22, 2023. Here, “earlier input” means earlier in the supplied file’s source indices. It does not establish that archive filtering used no later signal, or that an online biological loop has the same delay. Predicting recorded positions is a bounded decoding test. It demonstrates neither sensory delivery nor a nervous system learning and retaining a skill.

NeuroTranslation Definitions in Simple English

Canonical registry revision 26; `fc5dbd61462ecf98ada2629e84659ab2d05c0005 8df44efa80e3b397e20ca042`.

A model, a measurement and a claim about biology need different words. These 178 entries state what each term means in this programme. Naming a capability does not establish that it has been demonstrated.

Lookup labels help find an entry. Some name related or contrasting concepts, so they are not all interchangeable. The portable JSON retains the selected fields and complete lookup index. Original definition histories remain in the canonical registry.

Organizational level describes which part or signal is considered. Physical ranges and units describe dimensions. Computational granularity describes the detail represented in a model; statistical aggregation describes how observations are grouped. A missing range or unit remains unspecified.

Some technical notes describe a named source edition or prototype. Its measurements, numerical results and implementation limits belong to that context; they are not timeless claims about every model. The entries distinguish recorded observations, calculated quantities, simulations and proposed capabilities. This supplement reports no new experimental result.

A checked message between software parts

A structured message and interface specify what the values mean and how software parts exchange them.

The checks include recording, ordered channels, quantity, timing where supplied, units and body axes. Passing a check does not prove that the caller's claimed physical source is true.

Lookup labels: Translation packet, typed port and API; packet; translation port; typed interface; API; application programming interface

A group of recorded neural features

Several recorded neural features considered together when predicting an outcome.

Their joint pattern can help predict movement. That does not establish that the same pattern has the same meaning in another animal, task or day.

Lookup labels: Neural population; population decoding; population model

A map of physical connections

A structural map records physical connections. A functional recording measures activity over time, such as which recorded features produced events during a task.

The structure can guide a model, but it cannot supply missing time-recorded activity. A drawing, connection map and synchronized functional recording have different evidential roles.

Lookup labels: Structural connectome and anatomical prior; connectome; connectomic connectivity; anatomical prior; structural connectivity; structural reference; recorded function; structural versus functional measurement

A model spanning the body

A future model connecting relevant observations and actions across the brain, spinal cord, nerves, muscles and movement.

The project does not yet have a matched voluntary recording across that whole chain. Separate datasets cannot fill the missing measurements.

Lookup labels: Body-wide functional model; body-wide neural fusion; whole-body neural translator

A specified human-related feature

Studying a defined human-related biological component or feature in a model organism.

This can overlap with adding donor cells. One selected immune or neural feature does not make an animal a miniature human or establish human-like cognition.

Lookup labels: Humanization; humanized; human-related feature

Ability that remains after guidance is removed

A learned ability that remains without the training guidance and can be tested again later.

Remove tutor commands while keeping any bridge needed to express the pupil's own control. Switching off that required route can prevent movement regardless of what the pupil learned.

Lookup labels: Retained learning; retention; independent pupil control; retained skill; pupil-alone; necessary bridge held constant; pupil-alone with necessary bridge constant

Action2World

The hand reaches; the cup moves or stays still. Contact, load and the measured outcome tell us whether the action did what we intended, and that feedback shapes the next attempt.

The relationship between an action and its consequences for the body and surrounding environment, including the sensory information those consequences produce.

A predicted consequence is not an observed outcome. Specify the object, reference frame, task, units and uncertainty. Footage supplies movement examples without supplying the performer's neural, muscle or force measurements.

Organizational level: whole system; network; signal/feature

Lookup labels: action2world; action to world; action-to-world

Activity state inside the muscle model

The model's internal state that responds to a command and affects its force.

This state can change more slowly than the command. The displayed activation comes from the computer model, not recovered physiological activation from the macaque recording.

Lookup labels: Muscle activation; activation; activation dynamics

Adjustment using evidence from the new setting

Changing or checking a model using examples from where it will be used.

Adjusting a decoder, checking probability scores and measuring a body's physical properties are different kinds of calibration. The new-day model uses labeled examples.

Lookup labels: Calibration; recalibration; calibrated transfer; uncalibrated; physiological calibration; physiological fidelity; subject calibration

Agent2Agent

One software agent passes declared information to another.

A proposed link carrying specified information between software agents.

Name the agents, message or representation, direction and tested outcome. Software communication does not by itself supply a biological recording, sensory writer, shared experience or demonstrated skill transfer.

Lookup labels: agent2agent; agent-to-agent; agent to agent

Agent2Brain

An agent would give a person feedback during a stated task. Tests would have to distinguish help during that task from learning that remains afterwards.

A proposed path from a software agent to a person through specified feedback or a separately qualified neural output interface.

Feedback would reach a person through an ordinary sensory route or a separately qualified direct neural interface. Those routes need different devices, evidence and admission: feedback on a screen is not direct neural delivery. EEG and EMG record; they do not write. The proposed agent-to-person path leaves the reverse observation and feedback direction intact. Help during a task must be tested separately from learning retained after it ends. Agent2Brain establishes no stimulation or physical-action authority. Physical spinal scope remains read-only.

Lookup labels: Agent2Brain?; agent2brain; agent2brain?; agent-to-brain; agent to brain

All outputs inside their ranges together

How often every output of interest falls within its stated range in the same case.

A 90% range for each separate output does not guarantee 90% coverage of all outputs at once or of a whole body.

Lookup labels: Simultaneous coverage; all-output coverage; whole-body coverage

An independent way the model can move

One independent model movement, such as rotation at a joint. The formal shorthand is DOF.

The native arm has seven coordinates and no separate finger movements. The human replay controls two goals while bracing other independent joints.

Lookup labels: Degree of freedom; DOF; DOFs; independent coordinate; braced joint

Analysis timing and biological travel time

An analysis offset aligns two recorded quantities. A conduction delay concerns how long a signal travels through biology.

The 40 ms sensory offset estimates an earlier limb state. The motor target's 4 ms offset comes from sampling. Neither measures neural conduction time.

Lookup labels: S1 alignment offset and conduction delay; 40 ms sensory lag; S1 lag; 4 ms sampling offset; conduction delay; physiological latency

Animal drawing and measured anatomy

An illustration explains a proposed animal or body. An empirical anatomical atlas is built from verified observations of anatomy; it cannot be established by a convincing drawing.

The antechinus illustration is a proposal, separate from acquired macaque and human sources. The implementation has no matched validated antechinus neural/body atlas and makes no living-animal learning claim from the image.

Lookup labels: Antechinus proposal; antechinus; marsupial proposal; hypothetical organism; Proposed marsupial setting; anatomy illustration; illustrative model; empirical atlas; anatomical atlas

Another brain area used in the finger study

A brain area recorded alongside the movement area in the human finger study.

The formal name is posterior parietal cortex, or PPC. The study provides attempted-finger labels, not measured trajectories of executed finger movement.

Lookup labels: Posterior parietal cortex; PPC; Parietal brain area

Assumed repair to the native muscle model

A separately named model version replaces unusable zero-rate properties with the software's default values.

The source uses a named Schutte muscle model. Restoring 117 default properties permits numerical tests but does not measure the subject's muscle response rates.

Lookup labels: Schutte muscle properties and default-rate fork; Schutte; zero-rate; assumed-rate fork; class defaults

Attachment order and the chosen route segment

The ordered connection points and the numbered segment to which a wrapping rule applies.

The rule uses the source model's attachment order. The SDK counts from one and includes both range endpoints; the correction does not fit arbitrary points to an error frame.

Lookup labels: Attachment topology and SDK range; attachment topology; one-based inclusive range; humerus-to-ulna segment

Axes, pushes and turns

A coordinate frame states the axes used for movement. A handle wrench combines forces and turning moments measured in that frame.

The handle record has three force and three moment components. An unknown mapping into the computer-body axes prevents treating those forces as verified simulator inputs.

Lookup labels: Coordinate frame and handle wrench; body frame; XY; physical frame; handle wrench; forces and moments

Biological tissue repair

Restoration or replacement of biological tissue or its function, supported by direct biological evidence.

Better simulated tracking, assisted movement and retained behavior are different outcomes. The prototype does not demonstrate neural tissue repair.

Lookup labels: Regeneration; tissue regeneration; repair

Biological virtualization

For a movement model, matching the path is one question; matching the living system's response to an intervention is another.

A claim that a digital model reproduces specified biological behaviour and causal dynamics within an independently tested domain and stated error bounds.

Independent ground truth must establish measured error and repeatability within declared conditions and tolerances. For causal dynamics, the comparison also needs independently measured responses to appropriate causal interventions; a similar-looking trajectory alone cannot establish them. Approximation can make a model

plausible and may contribute to a validated model when its assumptions, errors and domain are tested and disclosed. A musculoskeletal simulation is itself a model to test, not independent empirical ground truth. Numerical detail and repeated verifier results guarantee neither biological accuracy nor complete physiology, subjective continuity, consciousness transfer or implemented Brain2Body capability. This biological claim is distinct from operating-system virtualization.

Scope: validation: Specified observed behaviours and causal dynamical responses under declared conditions.

Organizational level: whole system; network; organ; local circuit; cell; signal/feature

Computational granularity: Declared model and brain-body interfaces

Statistical aggregation: Declared validation aggregation; separate from physical scale

Lookup labels: virtualization; virtualisation; biological virtualisation

Body dimensions and resistance to motion

Mass is the amount of matter modeled. Inertia describes resistance to changes in motion; anthropometry means body dimensions.

The scaled model keeps assumed source masses and applies geometry-related inertia updates. Its length fit does not identify the animal's actual masses, strengths or individual bone dimensions.

Lookup labels: Mass, inertia and anthropometry; inertia; mass; anthropometry; subject scaling; specimen scale

Body position stored by the simulator

The model's stored configuration, such as its joint positions.

The formal variable name is qpos. Its entries depend on the model and are not automatically measured joint angles. The matching velocity variable, qvel, is explained separately.

Lookup labels: Generalized position and velocity; qpos; joint state

Body-model software and its programming tools

OpenSim provides tools for body models, geometry, scaling and simulation. Its software development kit, or SDK, lets code work with those models.

Checks on these tools establish the stated model's numerical behavior. They do not certify the exact upstream model version or the recorded animal's anatomy.

Lookup labels: OpenSim and its SDK; OpenSim; SDK; software development kit; native SDK; OpenSim 4.5.2

Body-position feedback

Proprioception means sensing body position and movement. For example, it helps a body monitor where a limb is. Biofeedback uses bodily information to guide action or learning.

The implemented correction uses simulated body position. It does not add measured peripheral nerve signals or show that a biological feedback process taught a retained skill.

Lookup labels: Proprioception and biofeedback; proprioception; simulated proprioception; biofeedback; Body-state sensing and feedback; proprioceptive feedback

Body2Action

The proposed link from body mechanics and sensory interaction to a specified, independently measured task action or outcome.

A task outcome makes this proposed link testable: the body's forces, contacts and timing have to be measured in the relevant context. Body2Action connects body mechanics and sensory interaction to that specified action or outcome; it establishes no working controller. World labels are historical conceptual lookup references, not a strict synonym for every environmental interaction.

Organizational level: Declared system or interface

Computational granularity: Declared process/interface/model

Statistical aggregation: Validation domain stated independently of physical scale

Lookup labels: Body to action; Body2World; Body to world

Brain imaging related to blood oxygen

An imaging method, called fMRI, that measures signals associated with changes in blood oxygenation.

It does not record individual electrical spikes. The paper discusses a published model for this kind of image, not a project result showing that brain scans and spikes are interchangeable.

Lookup labels: Functional magnetic resonance imaging; fMRI

Brain stimulation

An intervention that applies a specified physical stimulus to alter brain activity.

The method must be named, such as transcranial magnetic/electrical stimulation or intracortical microstimulation. These differ in access, risks and capabilities. EEG records; a scalp EEG headset does not provide general sensory writing or safe skill upload. Broad neuromodulation is not identical to precise task-content encoding.

Organizational level: Declared game/model/interface role

Computational granularity: Declared task-specific model or interface

Statistical aggregation: Validation scope declared per experiment; no physical-scale inference

Lookup labels: Neural stimulation; Neurostimulation

Source: A brain-computer interface that evokes tactile sensations improves robotic arm control

Source identifier: flesher2021

DOI: 10.1126/science.abd0380

https://pubmed.ncbi.nlm.nih.gov/34016775/

Research precedent for motor decoding plus sensory feedback through intracortical microstimulation; invasive and not a consumer EEG capability

Brain2Agent?

A recording supplies observations that an agent may use for a stated task.

A proposed path from specified brain observations to a software agent through declared recording and interpretation interfaces.

Recorded brain observations would reach an agent through a declared recording and interpretation interface. Where applicable, feedback toward the agent remains distinct from Agent2Brain's proposed agent-to-person path. Neither direction identifies unique private intent or experience. Recording supplies observations; inference and simulation interpret or model them, while actual sensory delivery requires its own interface. Brain2Agent? remains an open proposal.

Lookup labels: Brain2Agent; brain2agent; brain2agent?; brain-to-agent; brain to agent

Brain2Body

Connecting brain and body function; the 2 means to.

The numeral 2 is the preferred spelling. The programme includes body-to-brain feedback as well as outward pathways; the name does not establish complete biological translation or novelty of body–brain research.

Organizational level: whole system; network; local circuit; signal/feature

Lookup labels: brain2body; Brain2body; brain 2 body; brain-to-body; brain to body

Brain2Brain

Information links between two brain or neural systems.

The project's label for studying specified information links between brain or neural systems, including tutor–pupil comparisons.

Brain2Brain is the numeral-style public label for the project's existing brain-to-brain research direction. Each experiment must specify its signal, task and controls; the name itself establishes no shared thoughts, general skill transfer or successful biological teaching.

Organizational level: whole system; network; local circuit; signal/feature

Lookup labels: brain2brain; brain 2 brain; brain-to-brain; brain to brain

Brain2Motion

The proposed movement pathway connecting Brain2Body with Body2Action and the resulting measured motion, including the returning sensory feedback.

The label concerns the movement part of the wider programme, not every sensory/cognitive function. Brain/spinal/peripheral observations, muscle activity, body mechanics and external outcomes stay distinct. A decoded motion signal, simulation or lifelike animation is not a complete physiological explanation or validated skill transfer.

Organizational level: Declared system or interface

Computational granularity: Declared process/interface/model

Statistical aggregation: Validation domain stated independently of physical scale

Lookup labels: Brain to motion

Brain2Spine

A movement command meets a spinal cord that already regulates reflexes, coordinates muscles and adapts through experience. Understanding that middle step helps explain how the same intention can produce different actions.

The pathway from brain activity into spinal processing: descending signals influence circuits that combine them with sensory input and the body's current state.

A scalp EEG recording does not identify every descending signal or measure the spinal circuit's hidden state. The physical spine remains read only. This label does not name an admitted stimulation interface.

Organizational level: whole system; network; signal/feature

Lookup labels: brain2spine; brain to spine; brain-to-spine

BrainNet

A network of specified links between brain or neural systems.

A working network metaphor for connected brain or neural systems within the programme.

BrainNet pictures specified links between brain or neural systems as a network. It is a programme metaphor; it establishes no validated universal neural network, uniquely coined field or available trademark.

Organizational level: whole system; network; local circuit; signal/feature

Lookup labels: brainnet; Brain Net

Choosing a model and deciding if it passes

Choosing settings and applying a stated pass rule using the validation data.

The frozen-transfer rule requires a prediction score at least 0.01 above every specified control. A failing candidate stays rejected rather than being given an easier success rule.

Lookup labels: Validation selection and admission; validation-selected; acceptance criterion; admission; failure criterion

Command sent to a modeled muscle

The input command that starts the modeled muscle's activation process.

The command is bounded and nonnegative here. It differs from the resulting activity state, recorded muscle electricity and instructions for a biological intervention.

Lookup labels: Muscle excitation; excitation; actuator command; muscle control

Communication route around an interruption

An interface carrying selected information around a modeled break or between stated recording and control channels.

A bridge can compensate without repairing tissue or supplying muscle energy. The virtual interruption does not establish a biological injury model or treatment.

Lookup labels: Digital bridge; compensatory bridge; brain–spinal bridge; BCI; brain-computer interface; virtual pathway interruption

Comparable roles in different organisms

Comparing roles such as reaching or support while keeping each organism's anatomy explicit.

Related roles do not imply identical neurons or muscles. A combined fictional body cannot replace the measured sources and checks needed for each real organism.

Lookup labels: Organism role and homology; organism adapter; limb role; functional coordinate; homology; biped/quadruped

Comparisons that test whether guidance matters

Matched replay uses the relevant recorded activity under matched task conditions. Stale or unmatched replay uses activity from a different time or condition. No-link and inactive or sham comparisons test whether the proposed information route adds benefit.

These are proposed comparison types, not new animal results. Shuffling disrupts timing; a yoked comparison gives matched help from another case. Guidance amount, timing and later pupil control need their own stated comparisons.

Lookup labels: Shuffled and yoked controls; shuffled-input control; time-shuffled; yoked signal comparison; Matched comparisons with altered information; matched replay; matched own-session activity; stale replay; unmatched replay; no-link; sham; inactive comparison

Completed time interval for counting events

A stated time interval groups events into one count. A half-open interval includes its start and excludes its end.

Inputs use completed intervals. The exact boundary rule, interval duration and timing must remain explicit rather than being guessed from the display.

Lookup labels: Completed time bin and half-open binning; bin; 20 ms bin; 50 ms bin; half-open; bin end; cadence

Computer processors, memory and file size

A CPU is a general processor, a GPU is another kind of parallel processor, and RAM is working memory. Bytes and GiB measure digital data size.

The training described in this source edition used four CPU threads; GPU acceleration was neither verified nor used. AI-assisted coding does not establish independent biological validation or an authorship credential.

Lookup labels: Computing hardware and data size; CPU; GPU; RAM; AMD; AI; Ryzen AI Max+395; GiB; byte; bytes

Correct-label rate and chance comparison

Accuracy is the proportion of labels chosen correctly. A confusion table shows which labels were mistaken for others.

A uniform guess among ten balanced classes has a 10% reference rate. Accuracy and label scores do not prove executed movement or confidence in biological truth.

Lookup labels: Classification accuracy and chance; accuracy; uniform chance; ten-class confusion; confusion matrix

Count-prediction improvement per recorded event

Bits per spike describes how much a count-prediction score improves over a defined baseline, divided by the number of recorded spikes.

The baseline uses the training mean rate. A positive result concerns estimated average counts, not newly recorded activity or verified stimulation instructions.

Lookup labels: Bits per spike; BPS; ΔBPS; bits/spike; likelihood gain

Data for learning, choosing and checking

Separate portions used to fit the model, choose its settings, and check the selected result.

The paper uses local time-ordered splits. If test results have already been inspected, later reuse cannot be described as another independent test.

Lookup labels: Training, validation and test partitions; train/validation/test; train/val/test; split; chronological 70/15/15

Data kept out of a stated step

Data reserved from training or from another specified development step.

Independence depends on what was actually excluded. A previously inspected case does not become a fresh test just because it is called held-out.

Lookup labels: Holdout; held-out; reserved window; independent evaluation

Describing motion and calculating what causes it

Describing a body’s position and movement is one task; calculating how modeled forces change that movement is another.

The paper calls these kinematics and dynamics. A replayed pose and a muscle-driven trajectory are different results; neither alone proves physiological accuracy.

Lookup labels: Kinematics and dynamics; kinematics; dynamics; forward dynamics; numerical plant

Electrical recording in outer brain tissue

Electrodes in the brain’s outer layer, called the cortex, record electrical signals outside the cells.

This differs from a scalp recording. It also does not observe every cell in a circuit; the source file defines which events and channels were recorded.

Lookup labels: Intracortical extracellular recording; intracortical; extracellular cortical events; Electrical recording inside the cortex; cortex

Error range based on validation examples

A range placed around a prediction using the errors seen on the data used for model selection.

The ranges have constant width for each output. They do not guarantee future coverage when examples overlap in time or their errors are related.

Lookup labels: Residual band; empirical residual bounds; validation residual quantile; 90% per-output residual band

Events grouped as one neural feature

The source recording process groups events into features that the model can count separately.

A group is not a verified lifelong identity for one neuron. It must stay separate from unassigned events and from the channel labels used in other recordings.

Lookup labels: Sorted neural unit; sorted unit; sorted cell; sorted feature

Expected event count and its fit score

A model estimates the average event count for given inputs, then a score checks how that estimate fits the recorded counts.

The paper uses Poisson negative log likelihood for that check. A predicted average may be fractional; a good count-fit score does not establish a complete biological spike model.

Lookup labels: Conditional count mean and Poisson likelihood; expected count mean; conditional count; Poisson; negative log likelihood; NLL

External movement model

The external part of the body model, constrained by independently measured surface movement and pose in a declared task and coordinate frame.

The motion-capture relay-composite retains the source views, clocks, calibration and coordinate frame for the declared task. The earlier upper/lower hand concept and the later synchronized left/right tripod arm proposal are different arrangements; each needs its own visibility, synchronization and error checks. The composite is derived.

Hidden internal states, forces and intent are not uniquely measured. LiDAR and optical infrared tracking require distinct hardware, calibration and uncertainty qualification.

Extra correction and its scoring rule

A model can add a correction to an existing controller. A reward scores the result; command-change rate describes how quickly the input changes.

The formal names include residual policy, reinforcement learning and actuator slew. A simulator can score tracking or task completion without proving biological learning or correct hidden neural activity.

Lookup labels: Residual policy, reward and actuator slew; residual policy; reinforcement learning; RL; verifiable reward; actuator slew; task completion

File fingerprints

A checksum or hash is calculated from file bytes to detect changes or match a stated reference.

The named methods here include MD5 and SHA-256. A match checks bytes against that reference; it does not prove scientific truth or verify an entire file when only a range was acquired.

Lookup labels: Checksums and hashes; checksum; hash; MD5; SHA-256; source checksum; archive hash

Force in the modeled muscle and tendon

The force produced by the computer model for a muscle-tendon unit, or a force measured by a stated physical method.

The native test reads forces from the running simulator rather than an old lookup table. Those values are still simulated rather than isolated forces recorded in the source animal.

Lookup labels: Tendon force; muscle force; isolated muscle force

Form → function → action

The programme narrative follows structural constraints, the context-dependent processes they support, and independently measured actions or outcomes.

The three words organize the explanation; every molecular and neural level has its own structure and dynamics. Form informs and constrains function but does not determine the full process alone. Feedback returns outcomes to the system; this is not a one-way causal chain or a guaranteed one-to-one mapping.

Organizational level: Declared system or interface

Computational granularity: Declared process/interface/model

Statistical aggregation: Validation domain stated independently of physical scale

Lookup labels: Form to function to action

Functional electrical stimulation

Electrical stimulation coordinated to produce a specified functional movement or task.

FES is the appropriate functional-actuation label for the proposed later assisted-body study. It requires separately qualified devices, control/safety limits and specialist-supervised research approval. This registry contains no stimulation settings or self-experiment instructions.

Organizational level: Declared game/model/interface role

Computational granularity: Declared task-specific model or interface

Statistical aggregation: Validation scope declared per experiment; no physical-scale inference

Lookup labels: FES

Source: Restoring cortical control of functional movement in a human with quadriplegia

Source identifier: bouton2016

DOI: 10.1038/nature17435

https://www.nature.com/articles/nature17435

Research precedent linking implanted cortical recording to a custom neuromuscular stimulation sleeve; not an EEG/OpenBCI or elite-skill result

Further training for the target task

Continuing model training so it predicts the desired target, using the relevant inputs and labels.

The paper calls this fine-tuning. Changing software weights is not evidence that an animal or person learned a biological skill.

Lookup labels: Fine-tuning; paired-output fine-tuning

Future testing and analysis of existing data

A future test checks later unseen outcomes under a fixed plan; an existing-data test analyzes outcomes already recorded.

The second source file was chosen before inspection, but its recording day is earlier than the original model's day. Choosing a file in advance does not make it future biological deployment.

Lookup labels: Prospective and retrospective evaluation; prospective; retrospective; prospective biological deployment

Gap between data portions

Leaving out an interval around a split boundary so overlapping windows do not cross into another portion.

The continuous pipeline uses a one-second gap and checks the input and target support. This protects the software split, not every assumption about the original measurement.

Lookup labels: Partition embargo; embargo; boundary embargo

Guide and learner

The tutor supplies guidance; the pupil is the learner whose later control is tested. An experienced guide helping a novice asks a different question from two novices practicing together.

The proposed comparisons include experienced-to-novice, novice-to-novice, individual practice and matched no-link conditions. Later pupil-alone testing removes tutor commands while retaining any bridge required to express movement.

Lookup labels: Tutor and pupil; biological tutor; artificial tutor; live tutoring; tutor withdrawal; experienced-to-novice tutor; novice-to-novice; individual practice

Hallucination

A model can predict a movement correctly while inventing the biological mechanism it claims produced it.

Invented or ungrounded model content presented as if it corresponded to reality. In programme claims, this includes fabricated biological structure, dynamics or ability presented as established biological fidelity.

Research on AlphaFold3 uses the term for generative-model errors; this programme also applies it to unsupported biological attributions. A disclosed approximation, hypothesis, counterfactual or unvalidated candidate is a different kind of statement, and missing evidence alone does not prove it false. Numerical error concerns the calculation; objective misspecification concerns what is being optimized; causal attribution error concerns the mechanism being credited. Those differences matter when deciding what a result supports. An ungrounded generated answer can happen to be correct without validating its claimed biological mechanism or reliability elsewhere. Informed predictions therefore still require independent performance evaluation. The rolling-dice analogy describes reliance on unverified claims, not literal randomness or equal odds. Calling every approximation a hallucination, or every connectome or simulation fictitious, would erase the distinction.

Scope: usage: Model-generated biological content and claims of biological fidelity.

Computational granularity: Model output and its interpretation

Lookup labels: hallucination; model hallucination

Help during current performance

Help from a controller, replay, tutor or interface that improves performance while it is present.

For example, a pupil can move successfully while following tutor commands. This does not show independent learning or tissue regeneration.

Lookup labels: Assistance; compensation; assisted performance

How a muscle's pull turns a joint

To relate a muscle's pulling force to joint turning, the model uses its geometry. Consistent work calculations also relate those forces to small coordinate changes.

The formal terms are moment arm and virtual work. Their numerical checks do not measure biological muscle strength; the human controller uses them to account for dependent shoulder movements.

Lookup labels: Moment arm and virtual work; moment arm; virtual-work projection; dependent shoulder-girdle load

How many labeled examples were supplied

The labeled examples given to train or choose a model, including examples from prior recordings.

The first 5% counts new training labels only. Validation labels, earlier-source labels and extra neural samples are additional information.

Lookup labels: Label budget and supervision; label budget; paired supervision; adaptation labels; validation labels; source-task supervision

How scores from several outputs are combined

Scores can be averaged across individual outputs or first combined within defined groups. In this entry, macro describes the averaging and weighting rule, not the size of a body part, the scope of a nervous system, or the level of detail in a computer model.

The sensory result gives equal weight to five physical output groups. This avoids letting a larger group dominate but does not make their different physical units interchangeable.

Lookup labels: Per-output and group-macro scoring; per-output; group-macro; macro R^2

How uncertain the result remains

The remaining doubt about a prediction, including why it could be wrong or change.

Noise in the instrument, errors in the model, changing conditions and missing observations are different causes. The current ranges do not separate all of them.

Lookup labels: Prediction uncertainty; uncertainty; model uncertainty; measurement noise; drift

Human arm model used for playback

MyoArm is the human arm model used for the displayed muscle-driven replay.

The replay uses 63 modeled muscles and two mapped joint goals. Those quantities are simulated, and the macaque velocity mapping does not prove neural or skill transfer into a human body.

Lookup labels: MyoArm; human MyoArm; MyoArm right

Internal musculoskeletal model

The internal anatomy part of the body model: specified bones, joints and soft tissues, assembled from appropriate registered anatomical measurements.

Proposed complementary X-ray/CT and MRI inform different structures. Anatomy does not directly measure activation, force, material properties or neural function. Wētā FX provides visual/simulation inspiration, not a verified identical acquisition pipeline.

Interoception

Information about the body's internal condition, such as signals related to heartbeat or breathing.

Scope: Sensing the body's internal condition differs from sensing a limb's position and movement. Internal sensing remains a research objective; this prototype does not provide a fully measured body-wide internal signal.

Lookup labels: interoception; interoceptive signal; internal sensations

Interoceptomics

How does the body sense a heartbeat or its breathing, and how are the nerve connections involved arranged? Interoceptomics brings those questions together in a proposed study, relating observations of internal-body sensing to maps of the connections carrying or processing that information.

A proposed field combining interoception and connectomics to study internal-body sensing and its relationships with neural connectivity across scales.

The programme uses Interoceptomics as an umbrella for this proposed research. Giving the work a name does not establish a validated comprehensive map or a recognized external standard.

Scope: macro: Whole-body, organ and network relationships relevant to internal-body sensing; micro: Local signals, cells, circuits and interfaces relevant to those relationships.

Organizational level: whole system; network; organ; local circuit; cell; signal/feature

Lookup labels: interoceptomics

Keeping each source separate

Keeping track of which recording, channel, time and physical setting a value belongs to.

A channel numbered 12 in one day is not automatically the same cell as channel 12 on another day. A software label also cannot prove where supplied data physically came from.

Lookup labels: Source conditioning; source-conditioned; source-specific; recording-specific

Keeping each trial together

Assigning an entire trial to one data portion instead of dividing it among portions.

This prevents pieces of the same trial from being shared between the relevant splits. It does not remove prior inspection or other source limitations.

Lookup labels: Whole-trial separation; whole-trial-separated; successful trial; trial partition

Keeping up now and computing for later

Real-time computation keeps pace with incoming data; offline computation can take longer and be played back later.

Native planning takes about 4.52 seconds for a 20 ms simulated step and is offline. Smooth cached playback does not prove live planning or biological control.

Lookup labels: Real-time and offline execution; real-time; offline; paced playback; cached reference

Kind of measurement

What a method records, such as electrical spikes, scalp voltage, muscle electrical activity or a brain-scan signal.

These signals measure different things. They cannot be treated as interchangeable numbers merely because all of them relate to the nervous system.

Lookup labels: Signal modality; modality; observation process

Large Movement Model

The shorthand “NeuroTranslate with MoCap MyoSim = Large Movement Model” names the proposed combination of NeuroTranslate, MoCap ReComp and MyoSim Replay. It brings a learned mapping, measured movement and virtual mechanics into one architecture. The equals sign is not a mathematical identity or evidence of a trained model. EEG, EMG, measured movement, virtual mechanics and the learner retain their distinct roles.

The proposed movement-focused learned model that brings neural structure and functional observations together with internal musculoskeletal anatomy and independently measured external movement in a declared task.

The programme model-family name, analogous in ambition to large language model. It does not replace accurate technical architecture descriptions or mean that every DNN is a movement model. Scans and capture alone do not train a model. Parameter count, scale, generalization and nervous-system fidelity require evidence. System 3 thinking remains the partnership framing.

Lookup labels: large movement models; LMM; Large movement model

Lasting change in the nervous system

Changes in the nervous system that can contribute to learning or adaptation.

Updating software weights or controller gains is a different event. The practice interface in the computer model does not measure synaptic change in a living organism.

Lookup labels: Biological plasticity; synaptic plasticity; biological learning

Learning before the final task

Training first on another objective, such as predicting a later neural count, before training for a paired movement target.

The paper calls this pretraining. Earlier source-task labels remain part of the information the model received, even when only new-setting labels are counted in a small budget.

Lookup labels: Pretraining; neural next-bin pretraining

Mapping movement onto another body model

Turn a specified movement quantity, such as fingertip velocity components, into movement goals for a particular computer body. The mapping depends on that body and the chosen task.

Mapping specified movement quantities into goals for a particular body model, with the source quantities, target coordinates and transformation declared. This does not by itself reconstruct full posture or demonstrate biological transfer.

The retained source-specific adapter takes two macaque fingertip velocity components as its source and produces human-model shoulder and elbow goals. Their signs carry direction; scalar speed would discard it. These are goals for that model and task, so the mapping establishes neither cross-species skill transfer nor verified biological function.

Lookup labels: Retargeting; body adapter; organism-specific body adapter; joint goal

Meme-jacking

Borrow the recognition; earn the explanation. A familiar image should help the audience see the scientific point before the script develops it.

Use a recognizable meme or cultural reference to make a scientific point immediately legible, drawing on familiarity already earned by others.

Memification hijacking is the user's expansion. References may come from any online culture, not only films. Apply one purposeful reference per teaching concept without crowding formal methods or labels. Recognition does not grant reuse rights, endorsement, proven comprehension or scientific validity. Preserve the original Meme-ification history.

Lookup labels: meme-ification; memeification; mimification; Meme-ification; meme-jacking; meme jacking; memification hijacking

Meme-ification/memeification are spelling forms; mimification is retained only as the corrected historical transcription.

Mixed-source animal and added tissue

A chimera has biological contributions from different sources. A graft is added tissue; when it crosses species, it is a xenotransplant. An organoid is an organized tissue model.

Survival, physical connection, activity and useful function are separate questions. The proposed comparisons do not establish a humanized whole brain or an implemented treatment.

Lookup labels: Chimera, graft and organoid; chimera; chimerism; graft; organoid; host–graft; xenotransplant; xenograft

Model that chooses a label

A statistical model that assigns scores to categories, such as the ten attempted-finger labels.

The selected human model uses logistic classification, but its scores do not establish validated confidence in biological truth. Its reported accuracy comes from development data that have already been seen.

Lookup labels: Logistic classifier; logistic regression; classifier; classification; logistic

Model weights kept fixed

Keeping the fitted numbers in a model unchanged during a defined comparison.

The tested transfer trains a connector while retaining the older main model. Fixed weights make the comparison clear; they do not prove biological sameness across days.

Lookup labels: Frozen parameters; frozen trunk; frozen readout; frozen checkpoint

Modeled route from one muscle attachment to another

The route and length assigned to a muscle and tendon as the model's joints move.

The native arm retains 39 named routes. Their modeled lengths differ from direct measurements of living tissue, muscle commands and force.

Lookup labels: Muscle-tendon path; musculotendon length; modeled muscle length; geometric path

Models that convert inputs or predict outputs

One model can turn an input into a representation; another can use available inputs to predict a named result.

The paper calls these encoders and decoders. Predicting counts from mechanics or mechanics from counts does not by itself show the biological cause of either.

Lookup labels: Encoder and decoder; encoding; decoding; readout; decode; encoder; decoder

MoCap ReComp

MoCap ReComp is Motion-Capture Relay-Composite: the proposed measurement component that brings views of the same movement into a common physical frame. It should preserve which view supplied each point, so the joined map can be compared with its original observations.

The proposal starts with two dot maps of the same moving body: one from above, one from below. Align their time and position in a common physical coordinate frame, then join them into one motion map while retaining the source of each point.

A proposed method that creates two dot maps (3D point clouds) of the same moving body, one captured from above and one from below, aligns them in time and a common physical coordinate frame, then stitches them into one composite motion map while retaining each point's source.

To compare the same movement from above and below, the proposal must align both streams in time and a common physical coordinate frame while retaining each observation's source. Bidirectional denotes those opposing measurements, not neural communication or causal direction. LiDAR ranging and infrared optical motion capture are proposed alternatives; marker triangulation and LiDAR point clouds are different measurements, so the actual modality and camera/ranging geometry must be qualified. The maze geometry calls for measurements perpendicular to the floor, with viewing paths from both sides through material intended to be clear. Transmission and material effects need testing; concentrated and distributed arrays remain alternatives. Hardware, coverage, timing, calibration, spatial alignment, occlusion, motion error and latency require validation against real references. The joined map is a derived record, not a direct observation of hidden joints, tissue mechanics, muscle commands or neural function. Neither successful implementation, complete body reconstruction nor material transparency has been established by the name. The single vertical camera illustration remains schematic.

Geometry: Declare the top/bottom sensor positions, measured object, coordinate frame, viewing/illumination paths and coverage. Preserve the requested perpendicular-to-maze-floor geometry; document deviations rather than inferring them from an illustration.

Modality: Declare LiDAR ranging or infrared optical motion capture, including marker-based/markerless method, camera count, triangulation geometry, material path and actual calibration. No complete reconstruction or physiological writing follows from opposing views.

Timing: Record source timestamps, clocks, acquisition cadence, synchronization error and any interpolation, offline processing or end-to-end latency. No real-time capability is assumed.

Calibration and registration: Preserve calibration data and transformations placing both streams into a common physical frame; measure registration error and keep original observations and reconstruction steps traceable.

Limits: Record overlap, occlusion, missing observations, material effects, uncertainty and failure cases. Opposing measurements alone do not prove complete 3D pose, forces or biological function.

Physical scale: Declare measured distance ranges and units for an actual acquisition; no supported numeric range or physical unit assignment is presently available for this proposal.

Statistical aggregation: Declare any chosen evaluation grouping/averaging rule separately from physical scale and computational granularity.

References and acceptance: Use the Reference Comparison Protocol and unfilled record to identify the real-reference series needed for each acquisition component and the assembled map. Its provenance, rights, organism-stage, physical-unit, modality, clock, calibration, occlusion, contact, independent held-out, error, uncertainty and acceptance fields remain unfilled and HOLD. It supplies no measured series or apparatus validation. The unchanged programme reference criteria and every stronger original requirement govern their respective claims; no acceptance threshold is introduced or relaxed.

Outputs: Retain the top dot map, bottom dot map and joined map as separate traceable outputs. Their timestamps and common-frame transformations must be explicit; do not fill unobserved regions as though they were measured.

Scope: proposed application: Complementary top/bottom motion measurements of a body moving through the maze; concentrated coordinated platforms and distributed arrays remain alternatives; measurement boundary: Observed distances or geometry remain distinct from registered/stitched composites and any model-estimated pose or musculoskeletal quantity.

Organizational level: whole system; signal/feature

Computational granularity: top dot map (3D point cloud); bottom dot map (3D point cloud); time alignment and spatial registration; joined composite motion sequence

Lookup labels: motion capture composite relay; motion-capture composite relay; motion capture composite; bidirectional composite motion capturing using LiDAR; Motion capture composite relay; motion capture relay composite; motion-capture relay composite; bidirectional LiDAR; opposed-view infrared motion capture; bidirectional infrared; motion-capture relay-composite; Motion-Capture Relay-Composite

Historical spellings name this same proposed capture method. Relay here means passing captured measurements onward; the separate agent-coordination Relay protocol does not describe motion capture.

Movement brain area

A brain area involved in movement. The paper uses the names motor cortex, MC and M1 for relevant source recordings.

The signals help predict recorded movement-related targets. Knowing the brain area does not identify matching cells across recordings or reveal a whole-body command pathway.

Lookup labels: Motor cortex; M1; MC; primary motor cortex

Muscle electrical recording

Electrical activity recorded from muscles; the method is called EMG.

Muscle electrical activity differs from force and from the computer model's command and activity states. The trained targets here are rescaled signal summaries.

Lookup labels: Electromyography; EMG

MyoSim Replay

MyoSim Replay is the proposed MusculoSkeletal Simulation Physics-Engine. Declared anatomy, mechanical parameters and control inputs would produce movement predictions to compare with independent measurements. The external MyoSim body-model collection is a separate resource. Simulation replay is not a measured biological replay.

The proposed digital model would calculate how muscles and the skeleton move and exert forces, with real measurements used to check its predictions.

The proposed physics-based simulation component that models specified muscles, bones, joints and their mechanical interactions, using declared anatomy, parameters, forces and contact rules, with predictions tested against independent movement and other applicable physical measurements.

In the proposed five-component arrangement, declared anatomy, muscle/control inputs and physical context would drive a simulation of movement and forces. The motion-capture relay-composite would provide traceable measured movement to compare with those predictions. That comparison needs matching timing, coordinates, units and calibration, and tests that preserve anatomical and physical constraints, uncertainty, held-out cases, baseline controls, a series of real references and independent acceptance. Movement geometry alone does not measure muscle activation, internal forces, hidden neural state or subjective experience; force, activation and causal claims need additional independent references. Visual effects (VFX) rendering shows the model but cannot validate its mechanics. This remains a proposed simulation component, not a newly demonstrated implementation or external scientific field. Approximate simulation and biological virtualization verified within declared error bounds remain distinct; this component establishes neither universal precision nor whole-body completeness.

Scope: programme role: Virtual-body mechanics component; initially constrained hand and foot tasks; inputs and outputs: Declared anatomical parameters, muscle/control inputs and physical context produce simulated movement and mechanical quantities. Independently acquired motion and other necessary observables remain references, not simulator ground truth.

Organizational level: whole system; organ

Computational granularity: musculoskeletal model; mechanical solver; measurement-to-prediction comparison

Lookup labels: musculoskeletal simulation physics engine; musculoskeletal-simulation physics engine; musculoskeletal simulation; musculoskeletal physics model; musculoskeletal-simulation physics-engine; MusculoSkeletal Simulation Physics-Engine

Names used for source subjects

Indy, Han and Monkey L label macaque sources; N1 labels the human finger source.

These labels keep different subjects separate. Similar brain-region or task names do not make them one synchronized recording.

Lookup labels: Source subject labels; Indy; Han; Monkey L; N1

Nerves bringing body information in

Afferent paths carry body-related information toward the brain and spinal cord, together called the central nervous system.

For example, a limb-related sensory signal can travel inward. The source-specific cortical predictions do not measure this whole path or make missing nerve activity observed.

Lookup labels: afferent; afferent pathway; body-to-CNS; CNS; central nervous system

Nerves carrying commands out

Efferent paths carry outputs from the brain and spinal cord toward the body, including muscles and organs.

A prediction of movement is not a recording of that outward pathway. The prototype does not supply a synchronized voluntary sequence through spinal cord, nerves and muscles.

Lookup labels: efferent; efferent pathway; CNS-to-body

Neural decoding

Estimating declared information such as intended action from recorded neural observations using a specified model.

Decode accuracy, channels, source identity, task and held-out domain must be demonstrated. Brain-only control requires exclusion of covert muscle, eye and motion signals; decoding does not write signals into the brain.

Organizational level: Declared game/model/interface role

Computational granularity: Declared task-specific model or interface

Statistical aggregation: Validation scope declared per experiment; no physical-scale inference

Source: Restoring cortical control of functional movement in a human with quadriplegia

Source identifier: bouton2016

DOI: 10.1038/nature17435

https://www.nature.com/articles/nature17435

Research precedent linking implanted cortical recording to a custom neuromuscular stimulation sleeve; not an EEG/OpenBCI or elite-skill result

Source: A brain-computer interface that evokes tactile sensations improves robotic arm control

Source identifier: flesher2021

DOI: 10.1126/science.abd0380

https://pubmed.ncbi.nlm.nih.gov/34016775/

Research precedent for motor decoding plus sensory feedback through intracortical microstimulation; invasive and not a consumer EEG capability

Neural encoding

Mapping declared information to a representation in neural activity; in a sensory-interface design, constructing candidate stimulation patterns for specified feedback.

A computational encoder is distinct from a qualified stimulation device and evidence that a participant receives the intended sensation. The term does not mean arbitrary thought writing or skill upload.

Organizational level: Declared game/model/interface role

Computational granularity: Declared task-specific model or interface

Statistical aggregation: Validation scope declared per experiment; no physical-scale inference

Source: A brain-computer interface that evokes tactile sensations improves robotic arm control

Source identifier: flesher2021

DOI: 10.1126/science.abd0380

https://pubmed.ncbi.nlm.nih.gov/34016775/

Research precedent for motor decoding plus sensory feedback through intracortical microstimulation; invasive and not a consumer EEG capability

Neural Replay

Revisiting a stored sequence of neural samples with its stated timing and channel order.

This playback is not a live recording or instructions for stimulating a nervous system. A displayed arm movement does not show what the source animal's muscles actually did.

Lookup labels: Neural replay; recorded replay; archived replay; cached playback; Playing back a recording

NeuroArcher

A proposed archery game that studies coordinated use of both hands and arms through physical motion control, brain-signal control of a digital body, and a separately admitted later assisted-body experiment.

The near-term prop is a toy bow with small suction-cup tips and an over-arm arrow pouch. Target/creature choice is unresolved. Simulated performance does not establish muscle stimulation or retained biological archery skill.

Organizational level: Declared game/model/interface role

Computational granularity: Declared task-specific model or interface

Statistical aggregation: Validation scope declared per experiment; no physical-scale inference

Lookup labels: Neuro Archer

NeuroBoxer

A proposed boxing game that compares arm-motion control, brain-signal control of a digital body, and a separately admitted later assisted-body experiment.

Prime-era Mike Tyson is the requested virtual opponent and meme reference. A game, recorded prediction, stimulation-assisted motion and retained biological skill learning need different evidence. No actual opponent, head contact, finished game or stimulation capability is claimed.

Organizational level: Declared game/model/interface role

Computational granularity: Declared task-specific model or interface

Statistical aggregation: Validation scope declared per experiment; no physical-scale inference

Lookup labels: Neuro Boxer

NeuroConnectome

A map of specified neural connections used to constrain a model of the nervous system.

Connectome is the established term. The user's NeuroConnectome label does not establish complete coverage or identify functional dynamics, state, plasticity, sensory context or unique thought from wiring alone. Declare species, anatomical coverage, resolution and provenance.

Lookup labels: Neuroconnectome

Neuromuscular electrical stimulation

Electrical stimulation intended to elicit muscle contraction through the relevant neuromuscular pathways.

NMES is a writing/actuation intervention, whereas EMG records muscle activity. EMG electrodes or an OpenBCI recording board do not by themselves provide qualified stimulation. Neither contraction nor imposed movement demonstrates retained skill.

Organizational level: Declared game/model/interface role

Computational granularity: Declared task-specific model or interface

Statistical aggregation: Validation scope declared per experiment; no physical-scale inference

Lookup labels: NMES; Electrical muscle stimulation; EMS

Source: Restoring cortical control of functional movement in a human with quadriplegia

Source identifier: bouton2016

DOI: 10.1038/nature17435

https://www.nature.com/articles/nature17435

Research precedent linking implanted cortical recording to a custom neuromuscular stimulation sleeve; not an EEG/OpenBCI or elite-skill result

Neuroscience recording files

NWB stores neuroscience data and descriptions. In the paired source files here, SET holds recording descriptions and FDT holds binary samples.

A stale unit in the NWB muscle source must not override verified processing. SET headers match source hashes; FDT previews have checked local byte ranges rather than full verification of each upstream file.

Lookup labels: Neuroscience recording files; Neurodata Without Borders file; NWB; Recording header and sample file; SET and FDT files; SET; FDT; EEGLAB header; byte-range preview

NeuroTransfer

Specify what would move between which systems, then test what the recipient can do with and without assistance.

The proposed transfer of specified task-relevant information or a mapping between declared systems, with assistance and retained learning evaluated separately.

The label does not establish a successful biological transfer or retained skill. A weight copy, recorded replay, guided movement and independently retained learning answer different questions. Each proposed interface needs its own source, target, task, controls, rights and qualified outcome.

Lookup labels: neurotransfer

NeuroTranslate

Brain2Body Neural Activity is the long-form component label paired with NeuroTranslate in this proposed architecture. Recorded activity is an observation. NeuroTranslate names the mapping operation that could relate specified observations to movement, or reconstruct specified recorded features in the reverse direction. The observation, learned relationship and predicted value remain different things.

State the observations, the target and the task, then test how well the mapping works.

The proposed operation of mapping specified neural and body observations between declared inputs and targets in a stated task.

A model could predict movement from specified observations, or reconstruct specified recorded features in the reverse direction. Each direction needs its own test in the stated task. Neither establishes a unique hidden state, sensory delivery or biological skill transfer. NeuroTranslate names this proposed mapping operation; NeuroTranslation names the field and NeuroTranslator the implemented software.

Lookup labels: neurotranslate; NeuroTranslate; Brain2Body Neural Activity

NeuroTranslation

How could a particular neural recording be related to a defined movement task? NeuroTranslation is the proposed study of mapping nerve signals and the patterns that describe them between clearly defined situations like these. Every mapping must state where its inputs come from, what its outputs mean, and how it is tested.

A proposed field for translating or mapping neural signals and representations between explicitly defined source and target domains, with stated context, scale, tests and limitations.

Each connection must be assessed against its named source and stated test. The project has not demonstrated a universal brain language or an uploaded skill.

Scope: macro: Relationships between neural systems, body systems and defined tasks or organisms; micro: Mappings involving identified local signals, channels, features and circuit-level representations.

Organizational level: whole system; network; organ; local circuit; signal/feature

Lookup labels: neurotranslation; neural translation; Connecting neural recordings to defined tasks; Neurotranslation

NeuroTranslation Network

A plan for connecting more neural and body components while keeping the origin and meaning of each value clear.

The proposed network would connect neural and body components while carrying the origin and meaning of each value through the mapping. Each link could then be examined in its own recording context. Body-wide translation and biological teaching remain unproved.

Lookup labels: Source-Conditioned Neurotranslation Architecture; SCNA; Neurotranslation Network

NeuroTranslator

The software that joins particular recordings, prediction models, playback and computer-body checks.

Predictions and playback can be checked against the particular recordings they use. That is the scope of the implemented NeuroTranslator; neither a universal brain language nor skill upload has been demonstrated.

Lookup labels: Neurotranslation Engine; NTE; Neurotranslator

Numerical arrays, saved arrays and prediction

NumPy provides tools for numerical arrays. NPZ saves arrays; inference means running a trained model to produce an output.

Portable execution still needs the correct processing and source identity. Matching saved-model outputs does not establish success on new organisms or biological skills.

Lookup labels: NumPy inference and NPZ archive; NumPy; NPZ; portable inference; inference

Numerical checks on allowed movement

Checks that the computer model stays defined and within its stated joint limits.

Joint-limit penetration means going past an angular bound, not entering tissue. The 0.001 rad tolerance is a numerical rule, not a certificate of correct neural commands.

Lookup labels: Mechanical feasibility and anatomical tolerance; anatomical limit; limit penetration; finite state; joint range; numerical tolerance

Numerical software and its data file

MATLAB is numerical-computing software, and MAT is a format for its structured data.

The second Indy recording uses the original MAT source. The format does not prove matching cells, past-only source processing or complete observation.

Lookup labels: MATLAB and MAT file; MATLAB; MAT

Observe it, connect it, keep it useful

Observation burden, prediction on excluded cases and lasting task benefit need separate measurements. A clear picture does not answer those experimental questions.

Lookup labels: Access it, Ground it, Keep it; access; grounding; stability; signal stability

One multiplier for modeled lengths

A single number chosen to reduce differences between the model's muscle lengths and the source-derived length references.

The number is fitted on training poses and checked on distinct observed poses. It is not complete body calibration; no movement-control experiment is run on the scaled candidate.

Lookup labels: Scalar length fit; global length factor; uniform factor; a*; scalar bridge; recording length-fit candidate; SDK-scaled candidate

One recording period

One experiment or recording period with its own subject, channels, timing and task.

Two recording days, or recordings from different animals, do not form one observed nervous system simply because the files are loaded together.

Lookup labels: Recording and session; source recording; session; recording family

Open body-model collection

MyoSim supplies computer-body models with muscles and bones, including models used in this project.

The collection is earlier work, not a new project invention. Availability of an arm model does not establish matching macaque and human muscles or neural commands.

Lookup labels: MyoSim, MyoSuite and MyoArm; MyoSim

Open muscle-control task tools

MyoSuite provides tasks and tools for experiments with muscle-driven computer-body control.

It is earlier software reused here. Success on a simulated task is not proof of biological learning or a recovered neural command.

Lookup labels: MyoSuite

Other published models of neural recordings

NDT2 learns patterns across recordings made inside the cortex, the brain's outer layer. POYO handles differing sets of recorded neural features by representing events and learning relationships between them.

The paper cites these as earlier work. It does not claim to have implemented them or use their existence as proof of universal transfer or matching cells.

Lookup labels: Other published models of neural recordings; NDT2; large-scale neural pretraining; Published model for varying recorded populations; POYO; neural-event tokenization; cross-attention bottleneck

Passing information and gaining a lasting skill

Receiving useful task information differs from acquiring a durable ability that works independently in new conditions.

A short software label budget is not measured biological practice time. Sewing, cube solving and breakdancing remain future examples without matched skill recordings here.

Lookup labels: Task information transfer and skill acquisition; task transfer; skill transfer; skill upload; compressed acquisition; learning speed; learning; physical skill learning; skill acquisition

Past-only inputs and processing that uses later data

The local model uses completed past inputs. Some earlier source processing may still have used later samples.

Past-only indexing cannot reverse earlier filtering or rescaling that used the whole recording. It does not certify the full measurement-to-output delay in a living system.

Lookup labels: Causal indexing and acausal preprocessing; causal; algorithmic support; acausal filtering; offline interpolation; upstream filtering delay

Peripheral nerve electrical recording

A method for recording electrical signals associated with peripheral nerves, called ENG.

The human preview contains aggregate electrical observations. It does not provide separately identified nerve-cell spike trains or a complete voluntary command sequence.

Lookup labels: Electroneurography; ENG; surface ENG; peripheral recording

Placing body parts from joint positions

Calculating where body parts and muscle routes lie when joint positions are given.

The formal name is forward kinematics, or FK. It places geometry; it does not calculate muscle-driven motion through time or recover muscle commands.

Lookup labels: Forward kinematics; FK; kinematic replay

Planned commands, corrections and constant input

A planned command is feedforward; adjusting it from current model information is feedback; a constant muscle input is tonic control.

The human correction can change the bounded command goal. Recorded movement stays a scoring reference, and the native correction candidates remain rejected against constant-input comparisons.

Lookup labels: Feedforward, feedback and tonic control; feedforward; feedback; corrected controller; tonic excitation; constant tonic

Prediction score compared with a mean-value guess

R^2 compares squared prediction errors with a constant mean-value reference. Higher values usually indicate better prediction on the stated data.

The score can be negative. Different recordings, target processing and ways of combining outputs prevent treating all R^2 values as directly comparable.

Lookup labels: Coefficient of determination; R^2; R2; R^2; variance explained

Processing within spinal and peripheral pathways

Body-related information can be processed locally in spinal and peripheral structures rather than passing through one simple unchanged wire.

A cortex-only prediction does not observe those local processes. The separate recordings and computer-body checks do not establish a complete measured brain-to-body causal chain.

Lookup labels: local spinal processing; local peripheral processing; spinal/peripheral processing

Programmable neurobiology

The proposed ability to specify a bounded nervous-system or sensorimotor outcome, select a qualified intervention, predict its effects, measure what happens and adapt within a validated closed loop.

Scope: Brain, spinal, peripheral, muscle, mechanical and sensory feedback roles need separate evidence. Bidirectional prediction is different from safe sensory/action writing. An intermediary may improve a mapping without making it one-to-one. Arbitrary skill upload or universal disease/disability repair is not demonstrated.

Organizational level: Declared system or interface

Computational granularity: Declared process/interface/model

Statistical aggregation: Validation domain stated independently of physical scale

Programmable synthetic biology

Engineering specified biological behaviours by combining design, context-dependent molecular prediction, experimental measurement and iterative correction.

DNA/regulation, RNA/cell state and protein/interactions are explanatory layers, not a sufficient literal three-model recipe. Metabolism, feedback, environment and measured function matter. AlphaGenome and AlphaFold do not jointly certify whole-cell programmability; AlphaTranscriptome is a desired capability placeholder here.

Organizational level: Declared system or interface

Computational granularity: Declared process/interface/model

Statistical aggregation: Validation domain stated independently of physical scale

Lookup labels: Programmable molecular biology

Public reaching recordings

Public files pairing cortical electrical events with reaching behavior. The sources use names such as RTT and MC_RTT.

The original model's release and the separately acquired Indy day have different processing. Their dates and target definitions must remain explicit.

Lookup labels: Reaching source archive; RTT; MC_RTT; MC_RTT; O'Doherty reaching archive; Sabes reaching corpus

Public source records and document links

Repositories such as DANDI and OpenNeuro identify source versions. PDF is a document format, and a URL gives a resource location.

Source licenses and credit must be retained. A local paper draft or public input dataset does not mean the project's new code is published, licensed or submitted to arXiv or a journal.

Lookup labels: Public records, document files and links; DANDI; OpenNeuro; PDF; URL; arXiv; public deposition; license; attribution

Published models for brain scans and scalp recordings

BrainLM learns from fMRI brain-scan data. Neuro-GPT combines an EEG input model with a model of changes over time and is discussed for motor imagery.

These are earlier methods for different measurements. The project does not claim to have trained them, make scans and electrical spikes interchangeable, or upload skills.

Lookup labels: Published models for brain scans and scalp recordings; BrainLM; Published model of scalp signals; Neuro-GPT; NeuroGPT

Published neural-model comparison tasks

The Neural Latents Benchmark, or NLB, provides shared tasks for comparing models of neural recordings.

It informs the choice of comparisons. The paper's own local scores are not official NLB benchmark scores.

Lookup labels: Neural Latents Benchmark; NLB

Published tests of changing recordings

FALCON is a published benchmark concerned with neural decoding when recordings change and recalibration is limited.

The paper uses related source recordings and its own data splits. Its local muscle-signal scores are not official FALCON scores.

Lookup labels: FALCON benchmark; FALCON; FALCON M1; FALCON M1-A

Ranges that need statistical assumptions

A confidence interval gives a range for a quantity being estimated. A conformal prediction range tries to contain a future actual result at a stated frequency when its required assumptions hold.

The transfer figure shows one fixed run. The paper's ranges are based on earlier prediction errors, with related errors across time; they do not guarantee how often future true values will fall inside.

Lookup labels: Ranges that need statistical assumptions; Confidence interval and conformal coverage; confidence interval; repeated-seed interval; Prediction range with tested coverage; conformal; conformal coverage; prospective-conformal; distribution-free coverage

Recent-signal model

A model component that keeps a learned memory of recent inputs as it predicts the next result.

Its formal name is gated recurrent unit, or GRU. This established method uses completed input history; its memory does not establish a universal neural language.

Lookup labels: Gated recurrent unit; GRU; compact recurrent model; recurrent network

Record of what was observed

A record showing which channels or intervals were actually measured and usable.

Missing observations stay missing; they do not become zeros. The second Indy source does not supply separate observation intervals for every recorded unit.

Lookup labels: Observation mask; observation interval; invalid support; missing observation

Recorded neural events

A spike is an electrical event identified in a recording. A spike train is the sequence of those events over time.

A recorded event count is a whole number tied to one channel and time interval. A model's average expected count can be a fraction and is a different kind of value.

Lookup labels: Spike and spike train; neural event; spike count; spike train

Records linking files, checks and claims

A manifest lists specified files and identities; a receipt records checks; an evidence matrix links a claim to its supporting record.

These records also keep failures and withdrawn results visible. A catalog listing does not show that every dataset was acquired or used to train a model.

Lookup labels: Manifest, receipt and evidence matrix; manifest; source manifest; audit receipt; processing receipt; evidence matrix; withdrawal record

Relay

Pass focused work between agents, then check their results before accepting it.

A manual coordination protocol that passes bounded work and verified evidence between specialist sessions, with one integration owner and an independent acceptance reviewer. Each session follows the currently authorized model, effort and speed routing.

A specialist can work on a bounded question while an independent reviewer checks its evidence before the integration owner accepts it. This is a project coordination workflow, distinct from an established external standard or native Ultra mode. Efficiency and quality claims apply only to tested tasks; universal performance equivalence and a 50 percent weekly saving remain undemonstrated.

Computational granularity: finite delegated tasks and evidence artifacts

Lookup labels: relay; manual Relay protocol; Relay coordination

Rescaled muscle signal

A processed summary of muscle electrical activity put onto a relative scale.

The 16 targets have no physical voltage unit. A stale millivolt label in the source does not make them measured voltage, force or muscle activation.

Lookup labels: Normalized EMG envelope; EMG envelope; quantile normalization; dimensionless EMG

Rescaling using training data only

Learning a rescaling rule from the training portion, then applying the same rule to later values.

This avoids using local test values to fit that rule. It cannot undo source processing that already used future samples or the whole recording.

Lookup labels: Training-only normalization; scaler; target statistics; normalization

Response after an electrical stimulus

An electrical recording made while observing the response to a stimulus.

The human preview is a stimulus-response experiment, not voluntary movement. The stimulus itself can also leave an unwanted signal in the recording; that is an artifact.

Lookup labels: Evoked potential and stimulus artifact; evoked stimulation; evoked recording

Results already seen during development

Results that have been inspected and can therefore influence later decisions.

The human 90% result and local motor test windows have this limitation. They can be reported, but their later reuse is not a new independent test.

Lookup labels: Development evidence; development holdout; pilot; descriptive local test; inspected test

Reusing learning in another recording

Trying to use information learned in one setting to improve performance in another.

The comparison must state the new-setting labels and the controls. The reported frozen motor transfer and unadjusted human cross-day result do not establish successful biological or cross-species transfer.

Lookup labels: Cross-recording transfer; transfer; cross-day transfer; cross-species transfer

Routing a muscle around a modeled obstacle

A rule bends a modeled muscle route around an obstacle. One obstacle shape, a torus, is shaped like a doughnut.

The correction restricts three elbow wrapping rules to a stated attachment segment. It removes reproduced route errors without deleting a muscle or claiming a new anatomical measurement.

Lookup labels: Muscle wrapping and torus; wrap; wrapping route; torus; ELBOW_ULNA; ELBOW_ULNA; off-torus contact

Saved model and matching-output check

A checkpoint saves a model's state. A parity check asks whether another execution produces the specified matching output.

Repeating a result needs the same support, ordering, conversions, data splits, settings and body-model version. Passing software checks does not certify biological validity.

Lookup labels: Checkpoint and parity; checkpoint; replay/checkpoint parity; model parity; reproduction

Scalp electrical recording

Electrodes on the scalp record electrical potential; the method is called EEG.

This is an aggregate electrical signal, not a list of individual cortical spikes. The project's paired preview follows electrical stimulation rather than voluntary motor training.

Lookup labels: Electroencephalography; EEG; scalp potentials

Settings needed to repeat a run

The numbers and choices fixing one training run's starting point and procedure.

One fixed run can be reproduced. It does not show how results vary across repeated starts, animals or future recording days.

Lookup labels: Random seed and configuration; seed; single-seed; fixed protocol

Shared internal model

A model can learn an internal pattern and reuse that pattern when making several predictions.

The paper calls the pattern a latent representation and the reusable model a backbone or trunk. The tested shared model and frozen-transfer candidates were rejected.

Lookup labels: Latent representation and backbone; latent model; shared latent; backbone; trunk; shared parameters

Simple weighted prediction model

A linear model that combines inputs using fitted weights while discouraging excessively large weights.

The formal method is ridge regression. It provides a meaningful comparison: a more complex model must add value rather than merely produce a plausible display.

Lookup labels: Ridge regression; ridge; linear control; linear model

Simplicity principle

Introduce one concept or element at a time, using separate slides or successive reveals according to what makes the relationship easiest to understand.

Introduce each new element on its own, then show how the elements connect. Use separate slides or successive reveals to make the logical relationship visible. Simplicity

cannot remove scientific qualifications, evidence, source rights or required methods. Actual comprehension and exported readability still need review.

Small connector model

A smaller fitted mapping that connects one recording to an existing model or interface.

The connector can change while the older model stays fixed. That does not establish matching neurons or useful transfer without new-setting calibration.

Lookup labels: Adapter; linear adapter; recording adapter

Software that calculates a computer body's motion

MuJoCo calculates how a modeled body moves under forces and control inputs.

It is established software reused here. Its availability does not prove that the chosen body model or mapping matches a particular animal's physiology.

Lookup labels: MuJoCo; dynamics engine

Spine2Body

A muscle signal becomes a movement through tendons, joints, contact and load. Measure those steps together, and a failed reach becomes a specific question about activation, coordination or mechanics.

The pathway through which spinal output reaches peripheral motor nerves and muscles, producing action through the body's mechanics, while sensory signals return from the body.

Surface EMG measures muscle electrical activity, not peripheral nerve firing or force. Spinal plasticity, momentary reflex modulation and peripheral adaptation remain distinct. Simulated movement is a prediction to compare with independent measurements.

Organizational level: whole system; network; signal/feature

Lookup labels: spine2body; spine to body; spine-to-body

Stopping training under a stated rule

Ending training when the chosen development rule says to stop, rather than always using every allowed round.

Compared methods have equal round limits but can perform different numbers of actual updates. This is not measured biological learning time.

Lookup labels: Early stopping; epoch cap; training update

Structured task text and supported instructions

JSON stores structured text values. The task compiler converts a supported instruction into a defined program.

The compiler chooses available recorded building blocks and limited computer-controller practice. It does not program arbitrary biological skills or supply missing task evidence.

Lookup labels: JSON and task compiler; JSON; task JSON; natural-language compiler; supported primitive

Surface electrical recording over the spine

Surface electrodes placed over spinal regions record electrical potentials; the method is called ESG.

These measurements combine electrical contributions. They are not separately identified spinal-neuron spike trains.

Lookup labels: Electrospinography; ESG; surface spinal recording; surface ESG

System 3 thinking

System 3 thinking is the partnership; a large movement model is the movement-focused model we aim to build within it.

The programme's human–AI partnership framing in which an external supervisory model helps interpret, train or calibrate task-specific neural/body mappings; the movement-focused model being built is called a large movement model.

Expert footage provides movement examples, but it does not supply the depicted experts' neural or muscle recordings. An external supervisor would help interpret, train or calibrate task-specific neural/body mappings while the large movement model remains the movement-focused model being built within that partnership. Shaw and Nave use System3 for artificial cognition outside the brain in a different research account. This programme's task-specific framing establishes no new anatomical brain layer, biological neo-neocortex, third anatomical thinking system or achieved universal nervous-system model.

Organizational level: Declared game/model/interface role

Computational granularity: Declared task-specific model or interface

Statistical aggregation: Validation scope declared per experiment; no physical-scale inference

Lookup labels: System three thinking; System3 thinking

Source: Thinking—Fast, Slow, and Artificial

Source identifier: shaw-nave2026

DOI: 10.2139/ssrn.6097646

https://papers.ssrn.com/sol3/papers.cfm?abstract_id=6097646

Prior proposed System3 usage for artificial cognition outside the brain; not an established third anatomical brain system

Source: Thinking Fast, Slow, Artificially: AI and Your Brain

Source identifier: wharton-authors2026

https://executiveeducation.wharton.upenn.edu/thought-leadership/wharton-at-work/2026/05/thinking-fast-slow-and-artificially/

Primary institutional account of Shaw and Nave System3 research

Testing on an excluded day, animal or species

Checking a model on complete identities that were kept out of the relevant development steps.

The paper uses formal names such as leave-session-out or leave-species-out. A good score within one session does not answer these broader tests.

Lookup labels: Leave-out generalization; leave-session-out; leave-animal-out; leave-species-out; unseen-organism support

Testing possible next actions in the model

Simulating near-future actions before choosing the next command.

The copied test states must not change the live model. The native result remains rejected and too slow for real-time use; cached playback is a separate function.

Lookup labels: Short-horizon planning and lookahead; horizon controller; lookahead; copied-state rollout; model predictive planning

The comparison needed to judge improvement

A defined comparison that shows whether the proposed method adds useful information or performance.

A simple predictor, random fixed model and constant muscle command answer different questions. Producing a plausible animation is not a substitute for beating the relevant comparison.

Lookup labels: Baseline and control; simple baseline; tonic baseline; random frozen control; behavior-only predictor

Thought2Action

Begin with one intention and one action: reach for the cup. Measure the neural, muscular and mechanical steps between them. The aim is to make that intent-to-action relationship as close to one-to-one as possible within the declared task, person, state, context and tolerated error.

A task-conditioned mapping from a participant's stated or inferred intent to a specified action, evaluated through independently measured outcomes.

Intent inferred from EEG is not direct access to private thought. Movement constrains competing explanations; it does not certify an achieved universal bijection or the best possible mapping.

Organizational level: whole system; network; signal/feature

Lookup labels: thought2action; thought to action; thought-to-action

Thought2World

Follow the intention all the way to its consequence, then follow sensation and perception back to the next intention. Measuring the middle makes errors easier to locate and the next experiment easier to define.

The composed pathway Thought2Action followed by Action2World: intent is translated into an action, and that action produces an outcome that can be independently checked.

This is a proposed programme pathway, not a claim of unrestricted thought control. It is not silently equivalent to the existing Body2World lookup label, Body2Action or Brain2Motion. External touch and movement tasks alone do not solve internal-body sensing or the full Interoceptomics programme.

Organizational level: whole system; network; signal/feature

Lookup labels: thought2world; thought to world; thought-to-world

Timing relationships between spikes

How closely spikes can repeat and how spikes from different recorded features occur together.

The project checks predicted average counts. It does not establish these finer timing relationships or a complete account of biological spike noise.

Lookup labels: Refractoriness and spike synchrony; refractoriness; joint spike synchrony; biological count-noise model

Touch brain area

A brain area that processes body-related sensory information. The source study records from somatosensory cortex, including Area 2.

The formal shorthand is S1. The selected model estimates an earlier limb state; it does not recover voluntary motor commands or spinal and nerve recordings.

Lookup labels: Somatosensory cortex and Area 2; S1; Area 2; Area2_Bump; somatosensory

Training a fresh model

Training a new model for the current recording without importing an older model's learned main weights.

This is the scratch specialist. It performs better than the frozen-transfer candidate in both reported label budgets.

Lookup labels: Scratch training; scratch specialist; new-recording scratch specialist

Training with neural samples without movement labels

Using neural samples for a training objective that does not require paired movement labels.

These samples still provide information and require computation. The first 5% label condition permits full training-neural support, so it is not only 28.5 seconds of total observation.

Lookup labels: Neural-only training support; neural-only pretraining; unlabeled neural support

Trying to move and actually moving

Trying or being cued to move is different from measuring the movement that occurred.

The human labels describe attempted finger movement. They do not independently separate cue from intent or provide executed finger trajectories.

Lookup labels: Attempted versus executed movement; attempted finger identity; cued attempted movement; executed kinematics

Typical error on the original scale

RMS or RMSE squares the deviations, averages them, and takes a square root so the result has the original unit.

An error per joint differs from a combined seven-joint error. An error against a changed command goal also differs from an error against the same recorded reference.

Lookup labels: Root mean square error; RMSE; RMS; root-mean-square; tracking error

Unassigned event channel

A channel collecting events not assigned to the sorted features used by the model.

These events are excluded from the 171 sorted features in the second Indy recording. They cannot silently become another identified cell.

Lookup labels: Residual or hash cell; residual/hash; hash slot; threshold crossing

Units for distance, speed and angle

Metres, centimetres, millimetres and micrometres measure distance. Metres per second measures speed; degrees and radians measure angle. Radians per second (rad/s) measures the rate of change of angle.

One metre is 100 cm or 1000 mm; one mm is 1000 µm. Right-angle and varied-angle maze layouts differ in geometry, not in a validated difficulty multiplier. Unit conversion or a small model error does not prove anatomical or decoded-pose accuracy.

Lookup labels: Length, velocity and angle units; m; metre; cm; centimetre; mm; millimetre; µm; micrometre; um; m/s; rad; radian; degrees; °; rad/s; orthogonal; nonorthogonal; varied-angle maze; maze layout

Units for pushes, turns and electrical potential

Newtons measure force; newton metres measure turning moment; millivolts measure electrical potential. A dimensionless value has no physical unit.

The handle record mixes force and moment units. The rescaled muscle targets are dimensionless despite a stale mV label and cannot be read as force or activation.

Lookup labels: Force, moment and voltage units; N; newton; N m; N·m; newton metre; mV; millivolt; dimensionless

Units for time and sample rate

Seconds measure time; milliseconds are thousandths of a second. Hertz counts repetitions or samples per second.

A 250 Hz source sample interval is 4 ms; a 500 Hz simulation interval is 2 ms. These rates differ from playback pace, biological travel time and time spent computing.

Lookup labels: Time and frequency units; s; second; seconds; ms; millisecond; milliseconds; Hz; hertz; sample rate; 250 Hz; 500 Hz

Unwanted stimulus signal in a recording

Part of a recording caused by the stimulus or measuring setup rather than the intended response alone.

Stimulus artifacts remain in the human previews. Their presence and the evoked task limit interpretation as voluntary motor evidence.

Lookup labels: stimulus artifact; artifact

Use in a new setting without labeled adjustment

Applying a learned model to a new setting without using its labels to adjust the model.

The second M1 model uses explicit new-recording labels. Its test score is a result after calibration, not zero-shot success.

Lookup labels: Zero-shot transfer; zero-shot

Velocity estimated from earlier positions

Two recorded fingertip positions can give an estimate of how fast the fingertip moved and in which direction between the samples. The signed components describe velocity; speed is its non-negative magnitude.

A position-derived velocity estimate formed from the difference between current and earlier recorded positions divided by their elapsed time; individual components retain sign. Speed is the magnitude of the velocity vector.

In the separate calibrated motor recording, each interval uses the last available fingertip sample and the actual elapsed time to form a velocity target in m/s. This makes the calculation causal with respect to available position samples, not proof that the tracker supplied them without filtering or delay. Upstream filtering and latency remain unestablished; the derived target is not an original, directly supplied velocity trace.

Lookup labels: Backward finite difference; backward difference; finite difference; causally derived velocity; 250 Hz position support; Speed estimated from earlier positions

Velocity of each model movement

The model's stored velocity for its movement degrees of freedom, including direction.

The formal variable name is qvel. Its signed generalized velocities depend on the model's degrees of freedom; speed is a magnitude. Component units and frames depend on the declared coordinate and model. In MuJoCo, quaternion orientations can make qpos and qvel different lengths, so qvel is not an entry-by-entry derivative of qpos.

Lookup labels: qvel; generalized velocity; joint speed; Speed of each model movement

What a model estimated

A model's estimate of a defined result, such as speed, from the inputs it was given.

An estimate remains an estimate even when it matches the test data well. It does not become a new measurement of the spinal cord, nerves or muscles.

Lookup labels: Decoded or inferred prediction; decoded; inferred; reconstructed; prediction

What an instrument recorded

A value produced by a stated measuring method, such as an electrode or a movement tracker.

Recorded data can contain noise, filtering or artifacts. Calculating muscle length from tracked markers does not turn that length into a direct tissue measurement.

Lookup labels: Recorded measurement; measured; observed; recorded signal

What the computer body produced

A value produced while running a computer model, such as a modeled muscle's activity.

Computer-body movement and forces can be checked for numerical errors. They remain separate from measurements of a living body and from evidence that an organism learned.

Lookup labels: Simulated quantity; simulated; numerical model state

What was calculated from tracking

A value calculated from measurements together with a body model, such as an estimated joint angle.

The study's joint angles and muscle lengths use tracked movement and a model. They are not direct recordings of muscle commands, tissue length or peripheral nerve spikes.

Lookup labels: Model-derived quantity; tracking-derived; source-derived; biomechanical covariate

Where a value came from

The record of a value's source and the steps used to produce it.

For example, a measured hand position, an angle calculated from that position and a computer-generated muscle state have different origins. The software must preserve those differences.

Lookup labels: Provenance; lineage; source integrity

Which recorded channel is which

The labels and order used to identify neural features within one recording.

The labels do not identify the same neurons across days. The project did not accept unverified matches between cells in different recordings.

Lookup labels: Source-local unit identity; ordered channel identity; cell correspondence; unit order; neuron index

Which samples a value depends on

The input history and exact time interval needed to produce a value or target.

A single timestamp does not show all of this support. Overlapping histories and invalid samples near data splits need explicit checks.

Lookup labels: Temporal support and context; support; history window; context; next-target support; overlapping histories

Composed pathways

The proposed intermediary has a positive purpose: understand and measure the processes between intent and action so the task-specific mapping can be made as close to one-to-one as possible. The task, participant, state, context, target and tolerated error must be specified and independently tested. This is an aim for identifiability and control, not an achieved universal bijection or a demonstrated optimum.

Form → function → action and intent → action describe connected questions. The following proposed pathways separate the links that would need independent tests before their combined prediction could be trusted.

Biological pathway: Brain2Spine → Spine2Body; resulting in Brain2Body

Relate brain activity to spinal processing, and spinal/peripheral processing to the body; compose the tested links into an intent-to-body-action pathway.

Functional pathway: Thought2Action → Action2World; resulting in Thought2World

Relate a declared intention to a measured action, and that action to its measured consequence in the task environment.

Molecular analogy: DNA → RNA; RNA → protein; resulting in DNA → protein

The intermediate processes explain how an initial specification reaches its downstream product. This analogy illustrates the need for a measured middle; it does not assert identical biology or a context-free one-to-one relationship.

System 3 engineering route: Neural activity → Musculoskeletal simulation → Programmable model

The proposed engineering route to NeuroTranslation, coordinated by the System3 human–AI supervisory model.

Paired source-bound brain/spinal/peripheral/muscle and sensory/outcome observations constrain mechanics and a task-specific learner. A musculoskeletal simulation represents the biomechanical middle. Model read/write capabilities must be qualified individually.

Intent → action → outcome returns through sensory feedback to perception and subsequent intent; actual observed/inferred/simulated links remain distinguishable.

Interoceptomics combines interoception and connectomics. Touch, proprioception and external sensorimotor tasks can support this programme; they do not by themselves demonstrate internal-body sensing. Combining the proposed pathways advances a research aim rather than establishing a comprehensive solution.

Brain2Body names the wider programme. Body2World remains a contextual lookup label for Body2Action; Brain2Motion and Body2Action retain their own scopes. These related names do not make their measurement targets equivalent to those of the five composed paths.

The physical spinal pathway remains read-only in this proposal. Each claimed recording or writing capability needs its own independent qualification.

Additional programme terms and proposed names

This addendum uses glossary revision 28 and programme specification 30. The preceding glossary supplement preserves its historical revision 26.

Glossary revision 28 (SHA-256):

`c253cdfa96c3ca68877ae2f5af05322d9876952bef8bed5eb646928d3ec90041`

Programme specification 30 (SHA-256):

`deacac166f7a00021e84516c640279fa59ade74a18dd6aa3daf568503716d147`

A connection map, an individual profile and a proposed feedback route answer different questions. The terms below keep those questions apart.

Body2Body

A measured movement can constrain a digital body; a digital body can suggest a movement to test. Body2Body asks which quantities can travel between those settings and whether the resulting movement matches an independent reference.

A proposed research direction relating specified physical-body measurements to digital body models and testing mappings or feedback from those models to declared target bodies.

The user's physical-to-digital and digital-to-physical wording names a proposed direction, not a proven symmetric inverse. Observation-to-model fitting, retargeting and a separately qualified physical output have different requirements. Homologous and mechanically analogous features can support unpaired pretraining or transfer when their mechanics, scale, contacts, timing and missing features are declared. That learned relationship is not an actually measured neural pairing. Keep inferred and simulated quantities distinct from measurements. Biological virtualization still requires independent biological outcomes in a stated domain; no real body actuation, retained skill or whole-organism equivalence follows here.

Lookup labels: Body to body

Brain–Body Interface

A brain recording and a measured hand movement answer different questions about the same reach. A Brain–Body Interface would connect the stated observations and any separately qualified outputs so that the proposed relationship can be tested.

A proposed interface linking specified brain observations with body observations or control outputs in a declared task, with each direction and physical route identified.

This names an interface role, rather than the Brain2Body programme or a model spanning the body. A Digital Bridge is the existing selected-information route around an interruption or between specified recording and control channels; it is related, not an automatic synonym for every Brain–Body Interface. Recording, inference, simulated control and physical output require distinct evidence. EEG and EMG record; a feedback or stimulation output needs its own qualified interface. The label establishes neither complete coverage nor a bidirectional biological loop. No new acronym is introduced.

Lookup labels: Brain-Body Interface

Ecotype

A population adapted to a coastal habitat is an example of the ecological distinction at issue. Ecotype names the adapted population or form; the surroundings themselves are its environment.

A locally adapted population or form associated with a particular ecological setting.

Ecotype is an established population/ecological concept, not an individual's surroundings or an obligatory third stage after genotype and phenotype. State the organism and evidence for the claimed local differentiation or adaptation. The retained Turesson source is a historical plant example [49], not a complete modern evolutionary theory or evidence about the proposed nervous-system experiments.

Enactome

A reach has a path, a time and a result. An Enactome would organize observations like these so that the action and what followed can be compared across stated conditions.

A proposed organization of specified action observations and the recorded relationships between actions and their outcomes in declared tasks.

Declare which actions, body parts, tasks, units, frames and times the data cover. Keep commands, measured movement, sensory consequences and simulated outcomes separate. An observed association does not establish causation, a complete repertoire or the person's unique intent. This proposed data organization differs from the tentative Enactotype individual-profile label.

EndoHumanisation

Choose a particular human-related feature, then ask what introducing or studying that feature would change in the model organism. EndoHumanisation names that proposed line of work.

A proposed research stage studying specified human-related genetic features within a model organism and testing their relevance to a declared biological question.

The roadmap places XenoTransgenesis at step 1.1. The working interpretation concerns defined genetic features; the actual manipulation and its established scientific name remain to be specified. A selected feature does not make an animal human or establish human cognition, disease fidelity or an appropriate intervention age. Biological relevance, function and animal/participant, ethical, safety and rights requirements

need their own evidence and admission. This entry supplies no experimental procedure.

ExoHumanisation

Added tissue can survive without doing the job expected of it. ExoHumanisation names a proposed study of a specified human-related graft: what survives, what connects, and what function can actually be measured?

A proposed research stage studying specified human-related donor cells or tissue in a model organism and testing their survival, integration and function.

The roadmap associates step 2.1 with XenoTransplantation. A cross-species graft retains that established meaning; cell survival, anatomical connection, activity and useful functional integration are distinct outcomes. A graft does not establish a human nervous system, a shared mind or whole-organism human equivalence. Species, tissue identity, biological purpose, ethics, safety and rights remain explicit dependencies. This label provides no transplantation procedure or intervention-age window.

Genotype

A genetic description can record which versions of a DNA sequence an organism carries. Genotype names that genetic make-up, whether the description covers a selected part of the DNA or a wider set. The scope must be stated; the genetic description alone does not tell us every observable trait.

The genetic constitution being described for an organism, with the genetic scope of the description stated.

Genotype is an established scientific term. Its description is not a complete prediction of the organism's observed traits; phenotype also depends on environment and development. The three labels in the user's organism-level example are not three obligatory sequential stages or three fixed individual types.

Interoceptome

A heartbeat signal and a breathing signal describe different parts of the body's internal condition. An Interoceptome would organize the selected observations and their relationships, retaining how, where and when each was recorded.

A proposed organization of specified observations of internal-body sensing and the relationships being studied among them.

This is a data-organization proposal within Interoceptomics. Its coverage must name the organism, body systems, measurements, timing and task. Measured signals, calculated quantities and model estimates remain distinguishable. Touch and limb-position sensing are not relabelled as interoception, and the suffix does not establish a complete internal-body map or an individual biological type.

Mind-Meld

What information could one system give another, and would it help with the task? Mind-Meld names the proposed first Brain2Brain encounter, whose signal and effects would have to be measured.

A proposed first Brain2Brain study of a specified information link between neural systems during a declared task.

The roadmap places this at step 3.1 before later NeuroTransfer studies. The name does not describe fused minds, shared private experience, arbitrary thought reading or demonstrated skill transfer. Specify the source, recipient, recording and feedback interfaces, task, controls and independent outcome. Assistance during a link and learning retained without tutor information need separate tests, with any necessary compensatory bridge held constant. A reported natural connection is a motivating case, not evidence that this engineered link exists.

Mind-Merge

An agent could guide practice by giving feedback about a stated task. Mind-Merge names the proposed study of that interaction: what help does the person receive, and what can they do later without it?

A proposed Agent2Brain study of task-specific feedback from a software agent to a person and its measurable effects.

The roadmap places this at step 4.1. Ordinary sensory feedback and direct neural delivery remain different routes with different interfaces, evidence and admission. EEG and EMG record; neither supplies a neural writer. No merged identity, shared mind, retained skill or physical intervention follows from the name. Preserve the reverse observation path, matched practice and delayed/new-task retention tests, removing tutor information while keeping a necessary bridge constant. Physical spinal work remains read-only.

NeuroHandler

How well can a hand carry out the chosen task, and what information helps it do so? NeuroHandler is the proposed manual-dexterity experiment, with the hand's measured action providing the result to explain.

A proposed manual-dexterity experiment studying specified neural/body observations, task control and independently measured outcomes.

The earlier proposed manual tasks remain: rapid hand rubbing, the requested knuckle gesture and the interlaced-hand stretch. NeuroHandler names the manual-dexterity experiment; it does not establish a finished apparatus or successful model. Define the action, available inputs, physical or simulated setting, comparison and outcome before evaluation. Keep motion control, neural prediction, assistance and retained learning separate; any physical output requires separate qualification and admission. No dexterity gain, clinical benefit or intervention procedure is established.

NeuroJuggler

Moving each limb successfully does not settle whether the limbs work together. NeuroJuggler is the proposed coordination experiment: define the joint task, then measure the relationship between the limb actions and the result.

A proposed multi-limb coordination experiment studying how specified limb actions are coordinated in a declared task.

The earlier coordination proposal remains a hot-potato transfer between the hands, followed preferably by two-ball juggling. Those are proposed tasks; the final apparatus and qualified measurement setup remain unestablished. The label supplies no successful performance or implemented neural interface. Declare the task, limbs, inputs, timing, body model or physical setting and independent outcomes. Separate coordination from isolated-limb performance, simulated success from biological function, and current assistance from retained learning. Physical output, safety, rights and held-out tests keep their own admission requirements.

NeuroReplay

What changes when a learner receives replay-based guidance? NeuroReplay names that proposed study: compare performance while guidance is available, then test what remains when the guidance ends.

A proposed Stage 0 research direction for studying replay-guided sensorimotor feedback and its effects on current performance and later learning.

Proposed replay-guided feedback and learning studies.

This is the new roadmap label for steps 0.2–0.5, with a derived working scope; it does not rename Neural Replay, the existing stored-sample playback entry playing-back-a-recording. A stored sequence can supply a comparison, but playback alone establishes neither delivery to a nervous system nor biological learning. Fix the task, signal, feedback route, timing and equal-practice comparisons; distinguish matched, stale or unmatched replay, no-link and inactive or sham controls. Test delayed retention and new tasks after removing tutor information while keeping any necessary compensatory bridge constant. The questioned antechinus age ranges are not established developmental or intervention windows. No physical writer, procedure or present result is supplied by this label.

Phenotype

The trait is what must be observed: for example, a specified body characteristic or response in the setting being studied. Phenotype names these observable traits, rather than the genetic description alone.

The observable traits of an organism arising through genotype, environment and development.

State the actual trait, measurement method, developmental and environmental context. A phenotype is not a universal function that can be read uniquely from structure or sequence. Retain the distinction between a measured trait and a model's estimate.

Whole Body Interface

The hand is one part of the question. Whole Body Interface names the wider ambition to connect declared body systems, while showing which pathways have actually been observed and which remain missing.

A proposed extension of brain–body interfacing toward specified observations and outputs across the brain, spinal, peripheral and body systems.

Whole body states an ambition, not achieved coverage. An interface exchanges specified observations or outputs; the existing model spanning the body is a related modelling ambition, not the same object. State the recorded systems, missing pathways, units, clocks, frames and output routes. Separate datasets can support qualified learning and transfer, but they do not become simultaneous measurements of one body. Physiological input/output direction, software input/output and ordinary sensory feedback remain distinct; no spinal writer or physical actuation is authorized.

XenoTransgenesis

Which genetic feature would be studied, in which organism, and what would count as the relevant change? XenoTransgenesis is the user's working label for that proposed question within EndoHumanisation.

A working roadmap name for proposed research involving specified genetic components from another species in a model organism.

XenoTransgenesis is the preferred spelling; XenoTransgenicism remains a historical lookup label. This is not an established replacement name for every form of transgenesis, genome editing or humanisation; use the established term appropriate to any actual manipulation. Neither a genetic change nor its name establishes the intended functional effect or human equivalence. No procedure, approved organism, developmental schedule or experimental permission is defined here.

Lookup labels: XenoTransgenicism

A cross-species graft

A chimera has biological contributions from different sources. A graft is added tissue; when it crosses species, it is a xenotransplant. An organoid is an organized tissue model.

Survival, physical connection, activity and useful function are separate questions. The proposed comparisons do not establish a humanized whole brain or an implemented treatment.

Cross-species-graft component only; not a strict synonym for every chimera, graft or organoid, or achieved ExoHumanisation.

Additional lookup label: XenoTransplantation

Proposed names and explanatory comparisons

Neo-neocortex

A metaphor for an external machine contribution to human cognition; no anatomical addition is claimed.

AlphaTranscriptome

AlphaTranscriptome is a proposed name for a desired RNA/cell-state prediction capability. It is not an adopted general-purpose model. AlphaGenome already predicts some expression and splicing [36]; other RNA/cell-state models have bounded domains. These precedents leave whole-cell programmability to be independently demonstrated.

AlphaCell

A label for integrating cellular layers appears in the supplied passage; no implementation, novelty or product entitlement follows.

Connetype

A connection profile would describe the selected observations for one individual. Its anatomical coverage, resolution, method and uncertainty must remain visible. The profile does not identify that person's unique function, thoughts or a fixed biological type.

An individual's specified neural-connection profile under a declared measurement and representation.

The original three-name line ends in a question mark; all three remain tentative. No formal empirical definition or repeatability threshold is fixed.

The tentative name is Connetype. Connectype remains an unapproved editorial alternative; it is neither a lookup alias nor an adopted spelling.

Interotype

A heartbeat-related observation can vary with state and measurement conditions. A proposed individual profile must state what was observed and how repeatability would be assessed; it cannot treat touch or proprioception as interchangeable with interoception.

An individual's profile of specified internal-body sensing observations under declared conditions.

The original three-name line ends in a question mark; all three remain tentative. No formal empirical definition or repeatability threshold is fixed.

Interotype is a tentative name, rather than an established scientific type.

Enactotype

A profile of selected actions is bounded by the tasks, observations and conditions used to construct it. Repeatability, state dependence and generalization remain empirical questions; a stable innate action type or inferred unique intent is not established.

An individual's profile of specified actions and action–outcome observations in declared tasks.

The original three-name line ends in a question mark; all three remain tentative. No formal empirical definition or repeatability threshold is fixed.

Enactotype is a tentative name, rather than an established scientific type.

Form, Function, Feature

Start with a structure, ask what it does in the stated setting, then name the observable feature being compared. A hand's form, its grasping function and a measured property of a particular grasp answer related but different questions.

Feature must identify the actual observed or defined trait in its context; it is not a new universal third biological layer or a substitute for function or action. The existing Form → function → action account and intent–action distinction remain unchanged. Structure constrains function; context, history, selection and co-option prevent a guaranteed one-to-one or teleological chain.

Semiosis as a sensorimotor analogy

A drawing can resemble a hand, a pointing finger can indicate an object, and an instruction can follow a learned convention. Such signs can guide action through different relations; they do not assign perception, sensation and action to three exclusive boxes.

Icon, index and symbol describe sign–object relations, while sensation, perception and action name processes. A sign can combine relations. No one-to-one biological correspondence, neural code, private-experience identity or strict isomorphism is established. Outside-in and inside-out perspectives must state whether they concern physiology, modelling or interpretation.

Agent vs Neurology

The roadmap ends by asking what an agent could contribute to a defined neurological problem. Agent vs Neurology retains that proposed destination; the specific problem, task and comparison still have to be chosen.

An unresolved Stage 5 research question, not a selected disorder, intervention, diagnostic system or clinical trial.

No specific disease, patient population, endpoint, treatment mechanism, universal cure or successful clinical benefit is inferred. Any future study must define those matters and its ordinary feedback or separately qualified physical interface under the

original scientific, participant, rights, safety and independent gates. A prior software, metadata or model result cannot supply this evidence.

Agent vs Neurology names Stage 5 of the proposed roadmap.

References

[1] Brain2Body: The Next Generation In Body-Brain Interfacing., 2026. Unpublished working companion article, R736 source edition; authorship unconfirmed; no DOI. Concepts introduced independently in each work; not external experimental support.

[2] Dorkenwald et al. Neuronal wiring diagram of an adult brain, 2024. URL https://www.nature.com/articles/s41586-024-07558-y. Primary paper; anatomical reconstruction and coverage limits.

[3] N. K. Logothetis, J. Pauls, M. Augath, T. Trinath, and A. Oeltermann. Neurophysiological investigation of the basis of the fMRI signal. *Nature*, 412(6843):150–157, 2001. doi: 10.1038/35084005. URL https://pubmed.ncbi.nlm.nih.gov/11449264/. Simultaneous macaque visual-cortex fMRI/electrophysiology constrains interpretation of BOLD; not universal decoding of experience.

[4] Emanuel Todorov and Michael I. Jordan. Optimal feedback control as a theory of motor coordination, 2002. URL https://www.nature.com/articles/nn963. Primary feedback-control theory; programme application is a rationale, not a reported biological teaching result.

[5] Jerry Tang, Amanda LeBel, Shailee Jain, and Alexander G. Huth. Semantic reconstruction of continuous language from non-invasive brain recordings. *Nature Neuroscience*, 26(5):858–866, 2023. doi: 10.1038/s41593-023-01304-9. URL https://pubmed.ncbi.nlm.nih.gov/37127759/. Task-conditioned semantic reconstruction requiring participant cooperation; not literal or universal subjective decoding.

[6] Class for Physics of the Royal Swedish Academy of Sciences. Measuring and Manipulating Individual Quantum Systems, 2012. URL https://www.nobelprize.org/uploads/2018/06/advanced-physicsprize2012.pdf. Distinguishes controlled individual quantum systems from ensemble descriptions; analogy only, not evidence of quantum neural computation.

[7] Barry N. Taylor and Chris E. Kuyatt. Guidelines for Evaluating and Expressing the Uncertainty of NIST Measurement Results. NIST Technical Note 1297, National Institute of Standards and Technology, September 1994. URL https://www.nist.gov/pml/nist-technical-note-1297/nist-guidelines-evaluating-and-expressing-uncertainty-nist-measurement. Accuracy is qualitative agreement; repeatability/reproducibility and uncertainty require declared conditions. Prediction error and biological measurement accuracy describe different comparisons.

[8] Joseph E. O'Doherty, Mariana M. B. Cardoso, Joseph G. Makin, and Philip N. Sabes. Nonhuman Primate Reaching with Multichannel Sensorimotor Cortex Electro-

physiology. Zenodo dataset, version 2, 2020. URL https://zenodo.org/records/3854034. Published 26 May 2020.

[9] Felix Pei, Joel Ye, David Zoltowski, Anqi Wu, Raeed H. Chowdhury, Hansem Sohn, Joseph E. O'Doherty, Krishna V. Shenoy, Matthew T. Kaufman, Mark Churchland, Mehrdad Jazayeri, Lee E. Miller, Jonathan Pillow, Il Memming Park, Eva L. Dyer, and Chethan Pandarinath. Neural Latents Benchmark '21: Evaluating latent variable models of neural population activity. In *Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks*, volume 1, 2021. URL https://datasets-benchmarks-proceedings.neurips.cc/paper/2021/hash/979d472a84804b9f647bc185a877a8b5-Abstract-round2.html.

[10] Vittorio Caggiano, Huawei Wang, Guillaume Durandau, Massimo Sartori, and Vikash Kumar. MyoSuite: A Contact-rich Simulation Suite for Musculoskeletal Motor Control. In *Proceedings of the 4th Annual Learning for Dynamics and Control Conference*, volume 168 of *Proceedings of Machine Learning Research*, pages 492–507. PMLR, 2022. URL https://proceedings.mlr.press/v168/caggiano22a.html.

[11] MyoHub. MyoSim. Software repository, version 0.2.3, 2026. URL https://github.com/MyoHub/myo_sim/tree/93b0ca8f4ec90c9899ee7f05fee561e9911da91b. Revision 93b0ca8f4ec90c9899ee7f05fee561e9911da91b, committed 16 September 2026.

[12] Raeed H. Chowdhury, Joshua I. Glaser, and Lee E. Miller. Area 2 of primary somatosensory cortex encodes kinematics of the whole arm. *eLife*, 9:e48198, 2020. doi: 10.7554/eLife.48198. URL https://pmc.ncbi.nlm.nih.gov/articles/PMC6977965/.

[13] Charles Guan, Tyson Aflalo, Kelly Kadlec, and Jorge Gamez. Finger_RL: human intracortical recordings during attempted finger movements of right and left hands. DANDI Archive dataset, version 0.230408.2207, 2023. URL https://dandiarchive.org/dandiset/000252/0.230408.2207.

[14] Birgit Nierula, Tilman Stephani, Merve Kaptan, André Moruaux, Burkhard Maess, Gabriel Curio, Vadim V. Nikulin, and Falk Eippert. Somatosensory evoked potentials in the human spinal cord to mixed nerve stimulation. OpenNeuro dataset ds004388, version 1.0.0, 2023. URL https://openneuro.org/datasets/ds004388/versions/1.0.0.

[15] Birgit Nierula, Tilman Stephani, Merve Kaptan, André Moruaux, Burkhard Maess, Gabriel Curio, Vadim V. Nikulin, and Falk Eippert. Somatosensory evoked potentials in the human spinal cord to mixed and sensory nerve stimulation. OpenNeuro dataset ds004389, version 1.0.0, 2023. URL https://openneuro.org/datasets/ds004389/versions/1.0.0.

[16] Brianna M. Karpowicz, Joel Ye, Chaofei Fan, Pablo Tostado-Marcos, Fabio Rizzoglio, Clay Washington, Thiago Scodeler, Diogo de Lucena, Samuel R. Nason-Tomaszewski, Matthew J. Mender, Xuan Ma, Ezequiel Matias Arneodo, Leigh R. Hochberg, Cynthia A. Chestek, Jaimie M. Henderson, Timothy Q. Gentner, Vikash Gilja, Lee E. Miller, Adam G. Rouse, Robert A. Gaunt, Jennifer L. Collinger, and Chethan Pandarinath. Few-shot Algorithms for Consistent Neural Decoding (FAL-

CON) Benchmark. In *Advances in Neural Information Processing Systems*, volume 37, pages 76578–76615, 2024. doi: 10.52202/079017-2439. URL https://proceedings.neurips.cc/paper_files/paper/2024/hash/8c2e6bb15be1894b8fb4e0f9bcad1739-Abstract-Datasets_and_Benchmarks_Track.html.

[17] DANDI Archive. LINK archive: Monkey N centre-out finger task, version 0.251023.2336. URL https://dandiarchive.org/dandiset/001201/0.251023.2336. Pinned dataset identity; manuscript uses its six development sessions only.

[18] Joel Ye, Jennifer Collinger, Leila Wehbe, and Robert Gaunt. Neural Data Transformer 2: Multi-context Pretraining for Neural Spiking Activity. In *Advances in Neural Information Processing Systems*, volume 36, pages 80352–80374, 2023. doi: 10.52202/075280-3523. URL https://proceedings.neurips.cc/paper_files/paper/2023/hash/fe51de4e7baf52e743b679e3bdba7905-Abstract-Conference.html.

[19] Mehdi Azabou, Vinam Arora, Venkataramana Ganesh, Ximeng Mao, Santosh Nachimuthu, Michael J. Mendelson, Blake Richards, Matthew G. Perich, Guillaume Lajoie, and Eva L. Dyer. A Unified, Scalable Framework for Neural Population Decoding. In *Advances in Neural Information Processing Systems*, volume 36, pages 44937–44956, 2023. doi: 10.52202/075280-1948. URL https://proceedings.neurips.cc/paper_files/paper/2023/hash/8ca113d122584f12a6727341aaf58887-Abstract-Conference.html.

[20] Josue Ortega Caro, Antonio H. de O. Fonseca, Christopher Averill, Syed A. Rizvi, Matteo Rosati, James L. Cross, Prateek Mittal, Emanuele Zappala, Daniel Levine, Rahul M. Dhodapkar, Chadi G. Abdallah, and David van Dijk. BrainLM: A foundation model for brain activity recordings. *bioRxiv*, 2023. doi: 10.1101/2023.09.12.557460. URL https://www.biorxiv.org/content/10.1101/2023.09.12.557460v1. Preprint, version 1, posted 13 September 2023.

[21] Wenhui Cui, Woojae Jeong, Philipp Thölke, Takfarinas Medani, Karim Jerbi, Anand A. Joshi, and Richard M. Leahy. Neuro-GPT: Towards A Foundation Model For EEG. In *2024 IEEE International Symposium on Biomedical Imaging (ISBI)*, pages 1–5. IEEE, 2024. doi: 10.1109/ISBI56570.2024.10635453. URL https://doi.org/10.1109/ISBI56570.2024.10635453.

[22] Emanuel Todorov, Tom Erez, and Yuval Tassa. MuJoCo: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pages 5026–5033. IEEE, 2012. doi: 10.1109/IROS.2012.6386109. URL https://doi.org/10.1109/IROS.2012.6386109.

[23] limblab. monkeyArmModel. OpenSim macaque arm model repository, 2021. URL https://github.com/limblab/monkeyArmModel/tree/4fb7dddeec06a0df9525c18f37234a824cb1b5b1. MIT-licensed source; revision 4fb7dddeec06a0df9525c18f37234a824cb1b5b1, committed 24 May 2021; accessed 3 October 2026.

[24] Ajay Seth, Jennifer L. Hicks, Thomas K. Uchida, Ayman Habib, Christopher L. Dembia, James J. Dunne, Carmichael F. Ong, Matthew S. DeMers, Apoorva Rajagopal, Matthew Millard, Samuel R. Hamner, Edith M. Arnold, Jennifer R. Yong,

Shrinidhi K. Lakshmikanth, Michael A. Sherman, Joy P. Ku, and Scott L. Delp. OpenSim: Simulating musculoskeletal dynamics and neuromuscular control to study human and animal movement. *PLOS Computational Biology*, 14(7):e1006223, 2018. doi: 10.1371/journal.pcbi.1006223. URL https://journals.plos.org/ploscompbiol/article?id=10.1371/journal.pcbi.1006223.

[25] Shiu et al. A Drosophila computational brain model reveals sensorimotor processing, 2024. URL https://www.nature.com/articles/s41586-024-07763-9. Primary paper; tested circuit predictions and disclosed mismatches; not whole-fly fidelity.

[26] Eon Systems team. How the Eon Team Produced a Virtual Embodied Fly, 2026. URL https://eon.systems/updates/embodied-brain-emulation. Official developer technical account dated 10 March 2026; not peer-reviewed biological validation.

[27] mncrftfrcnm repository. Pinned fly-chess trainer source. URL https://github.com/mncrftfrcnm/making-fly-play-chess/blob/b97dfefbf9b8850f3cdf6b412c2ed840be94e260/scripts/fly_chess_trainer.py. Source descriptor, not a published paper title. Static-code evidence; gameplay strength unreproduced.

[28] shreyash-sharma repository. Pinned DoomFly threat-input source. URL https://github.com/shreyash-sharma/doomFly/blob/5f6c2881be5f5f40b0592a75e6ee231b50333b40/src/doom/fearless/danger.py. Source descriptor, not a published paper title. Static-code and dated author-report evidence; performance unreproduced.

[29] Wang-Chen et al. NeuroMechFly v2: simulating embodied sensorimotor control in adult Drosophila, 2024. URL https://www.nature.com/articles/s41592-024-02497-y. Primary paper with a disclosed contact artifact; author-hosted final text.

[30] Lehman et al. The Surprising Creativity of Digital Evolution, 2018. URL https://arxiv.org/html/1803.03453v4. Published first-hand accounts of specified simulation exploits; no FlyWire-specific result inferred.

[31] Google DeepMind. Specification gaming: the flip side of AI ingenuity, 2020. URL https://deepmind.google/blog/specification-gaming-the-flip-side-of-ai-ingenuity/. Official reported reward-misspecification example; not an independent reproduction here.

[32] Abramson et al. Accurate structure prediction of biomolecular interactions with AlphaFold 3, 2024. URL https://www.nature.com/articles/s41586-024-07487-w. Primary structural benchmark and limitations; not a universal functional failure rate.

[33] RCSB PDB-101. Methods for Determining Atomic Structures. URL https://pdb101.rcsb.org/learn/guide-to-understanding-pdb-data/methods-for-determining-structure. Official structure-method guide; undated in this reference, with incomplete bibliographic metadata.

[34] Henri Lorach, Andrea Galvez, Valeria Spagnolo, Felix Martel, Serpil Karakas, Nadine Intering, Molywan Vat, Olivier Faivre, Cathal Harte, Salif Komi, Jimmy Ravier, Thibault Collin, Laure Coquoz, Icare Sakr, Edeny Baaklini, Sergio Daniel Hernandez-Charpak, Gregory Dumont, Rik Buschman, Nicholas Buse, Tim Denison, Ilse van Nes, Leonie Asboth, Anne Watrin, Lucas Struber, Fabien Sauter-Starace, Lilia Langar, Vincent Auboiroux, Stefano Carda, Stephan Chabardes, Tetiana Aksenova, Robin Demesmaeker, Guillaume Charvet, Jocelyne Bloch, and Grégoire Courtine. Walking naturally after spinal cord injury using a brain–spine interface. *Nature*, 618(7963):126–133, 2023. doi: 10.1038/s41586-023-06094-5. URL https://www.nature.com/articles/s41586-023-06094-5.

[35] Diego Aldarondo, Josh Merel, Jesse D. Marshall, Leonard Hasenclever, Ugne Klibaite, Amanda Gellis, Yuval Tassa, Greg Wayne, Matthew Botvinick, and Bence P. Ölveczky. A virtual rodent predicts the structure of neural activity across behaviours. *Nature*, 632:594–602, 2024. doi: 10.1038/s41586-024-07633-4. URL https://www.nature.com/articles/s41586-024-07633-4.

[36] Žiga Avsec, Natasha Latysheva, Jun Cheng, Guido Novati, Kyle R. Taylor, Tom Ward, Clare Bycroft, Lauren Nicolaisen, Eirini Arvaniti, Joshua Pan, Raina Thomas, Vincent Dutordoir, Matteo Perino, Soham De, Alexander Karollus, Adam Gayoso, Toby Sargeant, Anne Mottram, Lai Hong Wong, Pavol Drotár, Adam Kosiorek, Andrew Senior, Richard Tanburn, Taylor Applebaum, Souradeep Basu, Demis Hassabis, and Pushmeet Kohli. Advancing regulatory variant effect prediction with AlphaGenome. *Nature*, 649(8099):1206–1218, 2026. doi: 10.1038/s41586-025-10014-0. URL https://doi.org/10.1038/s41586-025-10014-0.

[37] Haotian Cui, Chloe Wang, Hassaan Maan, Kuan Pang, Fengning Luo, Nan Duan, and Bo Wang. scGPT: toward building a foundation model for single-cell multi-omics using generative AI. *Nature Methods*, 21(8):1470–1480, 2024. doi: 10.1038/s41592-024-02201-0. URL https://doi.org/10.1038/s41592-024-02201-0.

[38] Simon Lavaud, Charlotte Bichara, Mattia D'Andola, Shu-Hao Yeh, and Aya Takeoka. Two inhibitory neuronal classes govern acquisition and recall of spinal sensorimotor adaptation. *Science*, 2024. doi: 10.1126/science.adf6801. URL https://pubmed.ncbi.nlm.nih.gov/38603479/.

[39] Steven D Shaw and Gideon Nave. Thinking—Fast, Slow, and Artificial: How AI is Reshaping Human Reasoning and the Rise of Cognitive Surrender. SSRN preprint, 2026. URL https://doi.org/10.2139/ssrn.6097646.

[40] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is All you Need. In *Advances in Neural Information Processing Systems*, volume 30, 2017. URL https://papers.nips.cc/paper/2017/hash/3f5ee243547dee91fbd053c1c4a845aa-Abstract.html.

[41] Yao-Hung Hubert Tsai, Shaojie Bai, Paul Pu Liang, J. Zico Kolter, Louis-Philippe Morency, and Ruslan Salakhutdinov. Multimodal Transformer for Unaligned Multimodal Language Sequences. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 6558–6569, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1656. URL https://aclanthology.org/P19-1656/.

[42] *Welcome to MyoSuite's documentation!* URL https://myosuite.readthedocs.io/en/latest/. Undated documentation; retained page labels itself MyoSuite 3.0.0.

[43] Matthew D. Luciw, Ewa Jarocka, and Benoni B. Edin. Multi-channel EEG recordings during 3,936 grasp and lift trials with varying weight and friction. *Scientific Data*, 1, 2014. doi: 10.1038/sdata.2014.47. URL https://doi.org/10.1038/sdata.2014.47.

[44] Wei-Bang Jiang, Li-Ming Zhao, and Bao-Liang Lu. Large Brain Model for Learning Generic Representations with Tremendous EEG Data in BCI, 2024. URL https://arxiv.org/html/2405.18765v1. arXiv preprint, version 1, dated 29 May 2024.

[45] Aviral Kumar, Aurick Zhou, George Tucker, and Sergey Levine. Conservative Q-Learning for Offline Reinforcement Learning, 2020. URL https://arxiv.org/abs/2006.04779v3. arXiv preprint, version 3, revised 19 August 2020.

[46] Aiko K. Thompson, Xiang Yang Chen, and Jonathan R. Wolpaw. Acquisition of a Simple Motor Skill: Task-Dependent Adaptation Plus Long-Term Change in the Human Soleus H-Reflex. *The Journal of Neuroscience*, 29(18):5784–5792, 2009. doi: 10.1523/JNEUROSCI.4326-08.2009. URL https://pmc.ncbi.nlm.nih.gov/articles/PMC2696311/.

[47] Aiko K. Thompson, Ferne R. Pomerantz, and Jonathan R. Wolpaw. Operant Conditioning of a Spinal Reflex Can Improve Locomotion after Spinal Cord Injury in Humans. *The Journal of Neuroscience*, 33(6):2365–2375, 2013. doi: 10.1523/jneurosci.3968-12.2013. URL https://doi.org/10.1523/jneurosci.3968-12.2013.

[48] Rochelle Ackerley, Léonard Samain-Aupic, and Edith Ribot-Ciscar. Passive Proprioceptive Training Alters the Sensitivity of Muscle Spindles to Imposed Movements. *eneuro*, 9(1):ENEURO.0249–21.2021, 2022. doi: 10.1523/eneuro.0249-21.2021. URL https://doi.org/10.1523/eneuro.0249-21.2021.

[49] Göte Turesson. The Species and the Variety as Ecological Units. *Hereditas*, 3:100–113, 1922. doi: 10.1111/j.1601-5223.1922.tb02727.x. URL https://people.wku.edu/charles.smith/biogeog/TURE1922.htm.

A Reference Comparison Protocol: Unfilled Record

A moving hand gives the instruments something in common to answer to. Scalp EEG would observe electrical activity at declared scalp sites; surface EMG would observe muscle electrical activity at declared arm sites. Neither tells us, by itself, where the hand went. The proposed LEFT and RIGHT tripod views would provide complementary movement observations. Each acquisition needs its own identifiable series of real references, followed by an independent comparison of the assembly. Two streams can agree because they share the same mistaken calibration.

This is an unfilled protocol and record. No observations, admitted reference series, measured errors or acceptance decisions have been entered. The apparatus and its anatomical and functional claims remain unvalidated. The older above/below maze illustration retains its separate schematic context, perpendicular-to-floor geometry and material-path questions. Its directions are not synonyms for the current LEFT/RIGHT tripod arrangement. Actual positions, viewing paths, coverage and transmission would need evidence.

Identify the body and the observation

A photograph can constrain a visible proportion; it cannot supply an EEG channel or a calibrated trajectory. Record each reference's provider, stable identifier, version or acquisition context, checksum if materialized, license, access terms and supporting claim. Identify the organism, developmental stage, participant or specimen, session, body part, task and view or time interval. Record physical dimensions and units, posture, support and contact, so that the comparison concerns the same body and movement. Keep those dimensions separate from computational detail and from the rule used to average errors. Existing datasets, atlases and photographs retain their separate study identities; none is silently admitted for this apparatus.

EEG needs sites, reference, channel order and electrical units. Surface EMG needs named muscles, sleeve and contact identities, reference and electrical units; it supplies neither incoming sensory-nerve traffic nor direct force. Each tripod view needs its selected modality and camera or ranging geometry. Optical triangulation and LiDAR ranging measure different things. Preserve raw observations, derived features and model estimates separately. These recordings do not identify hidden spinal activity, individual neurons or a unique brain state.

Make time and position comparable

A reach can follow the measured path and still arrive late. Record source timestamps, clock identities, cadence and units, synchronization events, offsets, drift, dropped samples and interpolation. Retain calibration observations, frame transformations, their uncertainty and checks against an independent reference. Report offline processing and end-to-end latency explicitly. An alignment error must not disappear inside a movement score, and no real-time capability follows from this protocol.

Compare scalp EEG, each arm's surface EMG, each tripod acquisition, and the time/frame calibration and any actual material path against their respective series

of real references. Keep overlap, occlusion, dropout and failed views alongside anatomy, proportion, support and contact. Preserve both motion observations and the joined map. A missing finger remains missing unless its replacement is labelled as an estimate. The assembled map then needs its own independent movement comparison; agreement among its inputs cannot establish the accuracy of their common reconstruction.

Test what the assembly claims

Independently measured movement can test a virtual body's path. Contact and force claims need appropriate measurements of contact and force; a lifelike image cannot establish valid mechanics. A learner's prediction needs a withheld measured target, declared input availability, baselines, negative controls, independent held-out participants, sessions, tasks or species where applicable, and leakage checks. Keep the reserved recordings closed and the original tolerances unchanged. This record admits no new fitting, biological teaching, participant acquisition, stimulation, physical intervention or model promotion. Physical spinal scope remains read-only.

For each component and the assembled apparatus, retain matched reference views or time intervals, the target observable, result, error with units, repeatability, uncertainty and failures. Declare the applicable original acceptance rule, its source, domain, comparator and tolerances before evaluation. The programme's unchanged real-reference contract and every stronger original scientific, anatomical, functional, physical, held-out, rights, visual, runtime and export criterion still govern their respective claims. No universal numeric threshold is introduced or relaxed. Biological function and clinical readiness need evidence beyond a matched motion record.

Unfilled comparison record

Use one record per reference and comparison, retaining a series for every component and for the assembled map. All values below are `null`; reference-series lists are empty and every acceptance state is `HOLD`.

Source and rights. Record ID, component or assembly, provider, source identifier, version or acquisition context, local checksum if materialized, license, access and supporting claim.

Body and task. Organism, developmental stage, participant or specimen, session, body part, task, view or time interval, physical dimensions and units, posture, support, contact, actual sensor geometry and material path.

Acquisition. Modality, measured quantity and units, sites, montage, reference, channel and contact identities, source frame and clock, timestamps, cadence, synchronization events, offsets, drift, calibration observations and transforms, calibration uncertainty, interpolation, missingness, occlusion, offline processing and end-to-end latency.

Independent comparison. Component-series and assembly-series identifiers, independent reference and its acquisition, aligned interval, raw/derived/simulated provenance, input availability, held-out split and custodian, baseline, negative controls, leakage checks and target observable.

Result and decision. Result, error and units, repeatability, uncertainty, failure cases, applicable original acceptance rule and source, domain, comparator, tolerances, independent reviewer, evidence and verdict.

No measured series or scientific validation is supplied by this empty record. Rights, physical, clinical, runtime, native, render, export and publication acceptance remain separate and open; no hosted release is claimed.