

# 纯配客户 TMS 对接文档

Published On: Feb, 2022

## Contents

<b>1. ENCRYPTION RULES 加密规则 .....</b>	<b>3</b>
<b>1. INTERFACE INSTRUCTION AND DATA STRUCTURE .....</b>	<b>4</b>
<b>(接口指令与数据结构) .....</b>	<b>4</b>
<b>1.1. ONLINE ORDER (下单接口) .....</b>	<b>4</b>
1.1.1. INTERFACE INSTRUCTION .....	4
1.1.2. INPUT PARAMETER INSTRUCTION .....	4
1.1.3. OUTPUT PARAMETER INSTRUCTION .....	14
<b>1.2. REFUND LABEL 退款.....</b>	<b>16</b>
1.2.1. INTERFACE INSTRUCTION .....	16
1.2.2. INPUT PARAMETER INSTRUCTION .....	16
1.2.3. OUTPUT PARAMETER INSTRUCTION .....	17
<b>1.3. FETCH LABEL 抓取面单.....</b>	<b>18</b>
1.3.1. INTERFACE INSTRUCTION .....	18
1.3.2. INPUT PARAMETER INSTRUCTION .....	18
1.3.3. OUTPUT PARAMETER INSTRUCTION .....	18
<b>1.4. GET RATES 询价接口 .....</b>	<b>20</b>
1.4.1. INTERFACE INSTRUCTION .....	20
1.4.2. INPUT PARAMETER INSTRUCTION .....	20
1.4.3. OUTPUT PARAMETER INSTRUCTION .....	24
<b>1.5. TRACKING INFORMATION PUSH 轨迹推送.....</b>	<b>25</b>
1.5.1. INTERFACE INSTRUCTION .....	25
1.5.2. INPUT PARAMETER INSTRUCTION .....	25
1.5.3. OUTPUT PARAMETER INSTRUCTION .....	27

# 1. Encryption rules 加密规则

Message content (json)+timestamp+ key (provided by JDL TMS), which will be encrypted by MD5 and transferred to Base64 string and finally URL encoded. 报文内容(json) +时间戳+密钥(京东提供), 然后进行 MD5 加密, 再转换为 Base64 字符串, 最后进行 URL 编码

## Demo

Step	content	内容
1	Assumed the message content is {"customerCode": "your customer code"}, time stamp is 2020-01-01 00:00:00, and the secret key is 123456	假设报文内容为: {"customerCode": "your customer code"}, 时间戳是 2020-01-01 00:00:00, 密钥为 123456
2	URL encode the message content with charset UTF-8, the result is %7B%22customerCode%22%3A%22%20your%20customer%20code%20%22%7D	对报文进行 URL 编码, 字符集是 UTF-8, 结果为 %7B%22customerCode%22%3A%22%20your%20customer%20code%20%22%7D
3	Contact the message content, time stamp and the secret key, the result is {"customerCode": "your customer code"}2020-01-01 00:00:00123456	将报文内容、时间戳与密钥拼接为一个字符串, 结果为 {"customerCode": "your customer code"}2020-01-01 00:00:00123456
4	Encrypt the result of 3rd step by MD5 Algorithm, the result is 302244deb7b2ec32c0f97925102b406d	对步骤 3 的字符串进行 MD5 加密, 结果为 302244deb7b2ec32c0f97925102b406d
5	Encrypt the result of 4th step to Base64 characters, the result is MzAyMjQ0ZGVhN2lyZWZmMmMwZjk3OTI1MTAyYjQwNmQ=	对步骤 4 得到的字符串进行 Base64 加密, 结果为 MzAyMjQ0ZGVhN2lyZWZmMmMwZjk3OTI1MTAyYjQwNmQ=

6	URL encode the result of 5 <sup>th</sup> step, the result is MzAyMjQ0ZGVhN2IyZWZmMmMwZjk3OTI1MTAyYjQwNmQ%3D	对步骤 5 得到的字符串做 URL 编码, 结果为 MzAyMjQ0ZGVhN2IyZWZmMmMwZjk3OTI1MTAyYjQwNmQ%3D
7	The final data to be sent is logistics_info=%7B%22logisticsProviderCode%22%3A%22JD%22%7D encrypt_data= Y2VhMGM2NzA3NWQ0NjAxYzNIZDRjNWQ5YmUwZjcxZjY%3D timestamp=2020-01-01 00:00:00	那么, 最终得到的三个参数分别为 logistics_info=%7B%22customerCode%22%3A%22%20your%20customer%20code%20%22%7D encrypt_data= MzAyMjQ0ZGVhN2IyZWZmMmMwZjk3OTI1MTAyYjQwNmQ%3D timestamp=2020-01-01 00:00:00

# 1. Interface instruction and data structure

## (接口指令与数据结构)

### 1.1. Online order (下单接口)

#### 1.1.1. Interface instruction

Interface name	下单接口
Function description	客户对 JDL TMS 下单
Interface supplied by	JDL TMS
Data transfer	Https
Interaction method	Post
Encryption format	application/x-www-form-urlencoded; charset=UTF-8
Data format	Json
Interface address	由 JDL TMS 提供给客户

#### 1.1.2. Input parameter instruction

Field name	Field description	Required or not
logistics_info	URL encoded for online order message 在线下单的消息体, <b>对报文要进行 URL 编码</b>	Yes

encrypt_data	Signed string generated based on specific encryption rules 根据一定的加密规则，得到的签名字符串	Yes
timestamp	Timestamp, format: yyyy-MM-dd HH:mm:ss, e.g. 2017-07-15 17:56:42 时间戳，格式 yyyy-MM-dd HH:mm:ss 如果时间戳与当前北京时间相差 15 分钟以上，则视为恶意访问；因此，应注意时间戳的准确性。	Yes

### 1. logistics\_info message body instruction

Field name	Field description	Required or not	Type	Length
customerCode	Customer code, supplied by JD (JD 提供客户唯一编号)	Yes	String	20
waybillCode	运单号(在线下单时未必有运单号，如果为空物流公司生成运单号返回，否则原号返回)	No	String	64
orderId	Customer order number 订单号	Yes	String	64
packageInfos	Package info (For details, please refer to PackageInfo instruction) 包裹信息(详情参见 PackageInfo 说明)	No	Array	
sender	SenderInfo(For details, please refer to Sender Instruction) 发件人信息(详情参见 Sender 说明)	Yes	Sender	
receiver	ReceiverInfo (For details, please refer to Receiver Instruction) 收件人信息(详情参见 Receiver 说明)	Yes	Receiver	
orderDetail	OrderDetail , Product name (For details, please refer to OrderDetail Instruction) 订单服务详情(详情参见 OrderDetail 说明)	Yes	OrderDetail	
extendFields	ExtendedField (For details, please refer to ExtendField) 扩展字段(详情参见 ExtendField 说明)	No	Array	
remark	Remark 备注	No	String	256
createSiteName	Sorting center name 下单分拣中心名称	No	String	100
country	To distinguish the business of different countries (e.g. "th") 国别二字码	Yes	String	10
sellerName	商家名称	No	String	100
sellerCode	商家编码	No	String	10

returnAddress	Target address for returned waybill (For details, please refer to ReturnAddress) 退回地址(详情参见 ReturnAddress 说明)	No	ReturnAddress	
LabelSpecification	specs for label. however, if the label spec is fixed and acceptable for us, this attribute can be just ignored 面单格式 (详情参见 LabelSpecification 说明)	No	LabelSpecification	
packageCount	The amount of packages 包裹总数	No	Integer	
currencyCode	The code of currency. e.g. USD 币种	No	String	3
dimensionsUnits	The unit of measurement of width、length and height. the default is IN 长度单位 (默认英尺)	Yes	String	10
weightUnits	The unit of measurement of weight. The default is LB 重量单位 (默认磅)	Yes	String	10

PackageInfo field name	Field description	Required or not	Type	Length
packageId	Package number 包裹号, 京东内部操作使用	Yes	string	60
weight	Package weight, unit: LB 包裹重量 LB	Yes	Number	
volume	Package volume, unit: Cubic IN 包裹体积	No	Number	
length	Package length, unit: IN 包裹长度	Yes	Number	
width	Package width, unit: IN 包裹宽度	Yes	Number	
height	Package height, Unit: IN 包裹高度	Yes	Number	
goods	Goods list in Package items (For details, please refer to Goods in Package) 商品列表 (详情参见 Goods in Package 说明)	No (Required for International shipment)	List	
Goods in Package field name	Field description	Required or not	Type	Length
goodsCode	商品编码	Yes	String	35
goodsName	商品名称	Yes	String	50
goodsNameEn	商品英文报关名称	No	String	50
goodsCount	商品数量, 表示该包裹中该商品的数量	Yes	Integer	
goodsBrand	商品品牌	No	String	50
goodsBarcode	商品条码	No	String	50
hsCode	HS 编码	No	String	50
sourceCountry	原产国国别二字码	No	String	3
worth	商品申报单价 (单个商品的申报价值, 不含数量)	No	Number	
currency	商品申报币种, 标准币制编码, 如美元传 USD	Yes	String	3

chargedStatus	是否带电：0-否；1是。若不传则默认 0	No	Integer	
magneticStatus	是否有磁性：0-否；1是。若不传则默认 0	No	Integer	
liquidStatus	是否液体标识：0-否；1-是。若不传则默认 0	No	Integer	
cosmeticStatus	是否品化妆品标识：0 否；1-是。若不传则默认 0	No	Integer	
dangerousStatus	是否危险品：0-否；1是。若不传则默认 0	No	Integer	
powderStatus	是否粉末：0-否；1是。若不传则默认 0	No	Integer	
url	商品销售链接 URL	No	String	150
goodsWeight	商品重量	No	Number	
goodsWeightUnits	商品重量单位，默认：磅	No	String	

Sender field name 发件人	Field description	Required or not	Type	Length
name	发件人姓名	Yes	String	64
companyName	发件人公司名称	No	String	64
mobile	发件人手机号 (与发件人电话号其中之一必传)	Yes	String	32
tel	发件人电话号	No	String	32
country	发件人国别二字码	Yes	String	2
province	省	Yes	String	32
city	市	Yes	String	32
county	区县	No	String	32
town	街道	No	String	32
address	详细地址	Yes	String	50
address2	详细地址 2	No	String	50
address3	详细地址 3	No	String	50
houseNumber	寄件人门牌号	No	String	25
zipCode	邮政编码	Yes	String	32

Receiver field name 收件人信息	Field description	Required or not	Type	Length
name	收件人姓名	Yes	String	64
companyName	收件人公司名称	No	String	64
mobile	收件人手机号 (与收件人电话号其中之一必传)	Yes	String	32
tel	收件人电话号	No	String	32
Country	收件人国别二字码	Yes	String	2

province	省	Yes	String	32
city	市	Yes	String	32
county	区县	No	String	32
town	街道	No	String	32
address	详细地址	Yes	String	50
address2	详细地址 2	No	String	50
address3	详细地址 3	No	String	50
houseNumber	收货人门牌号	No	String	25
zipCode	邮政编码	Yes	String	32
email	邮箱	No	String	64
identityName	收货人身份证姓名	No	String	50
taxNo	收货人纳税号	No	String	50
identityNo	收货人身份证号	No	String	50
identityIssueDate	收货人身份证签发日期,格式 yyyy-MM-dd HH:mm:ss	No	String	50
selfPickUpCode	自提点编码	No	String	25
selfPickUpName	自提点名称	No	String	25

OrderDetail relevant field name 订单详情	Field description	Required or not	Type	Length
orderCreateTime	订单创建时间, 格式为 yyyy-MM-dd HH:mm:ss, 例如 2017-07-20 16:46:48	No	String	32
orderType	订单业务类型 (1, 正常配送订单、2, 上门取件订单、3, 商家送货到站点)	Yes	Integer	4
gotStartTime	上门揽件开始时间, 格式为 yyyy-MM-dd HH:mm:ss, 例如 2017-07-20 16:46:48 默认为订单创建时间	No	String	32
gotEndTime	上门揽件结束时间, 格式为 yyyy-MM-dd HH:mm:ss, 例如 2017-07-20 16:46:48 默认为上门揽收开始时间后一天	No	String	32
goodsValue	商品总金额, 单位: 元 (如果金额获取失败则默认是 0, 则非真实订单金额)	No	Double	
insuranceValue	保价金额, 单位: 元	No	Double	
currency	货币	No	String	
homeDeliveryService	是否宅配, 0 否, 1 是, 不传默认为 0	No	Boolean	



signatureService	是否需要收货人签名, 0 否, 1 是, 不传默认为 0	No	Boolean	
orderPerformance	订单的交付天数	No	Integer	
isDiscard	无法妥投是否销毁 0-否; 1-是. 不传默认为 0	No	Integer	
distributionMode	配送方式: 1-配送; 2-自提。不传默认为 1			
serviceCode	Integrated product code from JDL, TMS 下发的京东产品编码	Yes	String	

ExtendField relevant field name	Field description	Required or not	Type	Length
key	扩展字段名称	Yes	String	64
value	扩展字段值	Yes	String	256

#### Format of Extend Field 扩展字段格式说明

Key	Description
vendorId	vendorId, example: {"key": "vendorId", "value": "106" }

ReturnAddress field name 退货信息	Field description	Required or not	Type	Length
name	退货人姓名	Yes	String	64
mobile	退货人手机(与退货人电话其中之一必填)	Yes	String	32
province	省	Yes	String	32
city	市	Yes	String	32
county	区县	No	String	32
town	街道	No	String	32
address	详细地址	Yes	String	256
zipCode	邮政编码	Yes	String	32
email	邮箱	No	String	64
country	国别二字码	Yes	String	2

LabelSpecification field name	Field description	Required or not	Type	Length
imageType	面单格式, 如 PDF、PNG	No	String	25

imageSize	面单尺寸, 如 4×6	No	String	25
-----------	-------------	----	--------	----

## Message sample

**json:**

```
{
  "customerCode": "your customer code",
  "waybillCode": null,
  "orderId": "V000042135549",
  "packageInfos": [
    {
      "packageId": "V000042135549-1-3",
      "weight": 6.67,
      "volume": 1.0,
      "length": 1.0,
      "width": 1.0,
      "height": 1.0
    },
    {
      "packageId": "V000042135549-2-3-",
      "weight": 6.67,
      "volume": 1.0,
      "length": 1.0,
      "width": 1.0,
      "height": 1.0
    },
    {
      "packageId": "V000042135549-3-3-",
      "weight": 6.67,
      "volume": 1.0,
      "length": 1.0,
      "width": 1.0,
      "height": 1.0
    }
  ],
  "goods": [
    {
      "goodsCode": "SKU_7771661",
      "goodsName": "靴子",
    }
  ]
}
```

```

    "goodsNameEn": "grey boot",
    "goodsBrand": "",
    "goodsBarcode": "",
    "hsCode": "",
    "sourceCountry": "CN",
    "unitCode": "",
    "goodsCount": 1,
    "worth": 10.0,
    "currency": "USD",
    "chargedStatus": 0,
    "magneticStatus": null,
    "liquidStatus": 0,
    "cosmeticStatus": 0,
    "dangerousStatus": 0,
    "powderStatus": 0,
    "url": "",
    "goodsType": 1,
    "goodsWeight": 0.0,
    "goodsWeightUnits": ""
  }
]
}
],
"sender": {
  "name": "Pelamor",
  "companyName": "MyTest Corp",
  "mobile": "01756321199",
  "province": "Selangor",
  "city": "PETALING JAYA",
  "county": null,
  "town": null,
  "address": "Kompleks Penchala, Ground Floor, No 50",
  "zipCode": "46052",
  "country": "MY",
  "tel": "",
  "address2": ""

```

```
"address3": "",
"houseNumber": ""
},
"receiver": {
  "name": "SOMA PULIN",
  "companyName": null,
  "mobile": "60012345427",
  "province": "Johor",
  "city": "Kahang",
  "county": null,
  "town": null,
  "address": "KOLEJ KEDIAMAN D (MAIDAM), KAMPUS PERUBATAN UNISZA",
  "zipCode": "86733",
  "email": null,
  "country": "MY",
  "tel": "",
  "address2": "",
  "address3": "",
  "houseNumber": "",
  "identityName": null,
  "taxNo": null,
  "identityNo": null,
  "identityIssueDate": null,
  "selfPickUpCode": null,
  "selfPickUpName": null
},
"orderDetail": {
  "orderCreateTime": "2020-05-29 16:51:47",
  "orderType": 1,
  "gotStartTime": "2020-05-29 16:51:47",
  "gotEndTime": "2020-05-30 16:51:47",
  "goodsValue": 100.0,
  "totalFee": 100.0,
  "insuranceValue": 0.0,
  "totalServiceFee": 0.0,
  "codSplitFee": 0.0,
```

```
"scheduleType": 1,
"currency": "MYR",
"homeDeliveryService": false,
"signatureService": false,
"serviceType": 1,
"orderPerformance": null,
"isDiscard": null,
"distributionMode": 1,
"serviceCode": "EP"
},
"extendFields": [
  {
    "key": "vendorId ",
    "value": "233"
  },
  {
    "key": "needToSign",
    "value": "N"
  }
],
"remark": "your remark",
"createSiteName": "popseller",
"country": "MY",
"returnAddress": {
  "name": "Pelamor",
  "mobile": "01756321199",
  "province": "Selangor",
  "city": "PETALING JAYA",
  "county": null,
  "town": null,
  "address": "Kompleks Penchala, Ground Floor, No 50",
  "zipCode": "46052",
  "country": "MY"
},
"labelSpecification": {
  "imageType": "PDF",
```

```

    "labelSize": "STOCK_4X6"
  },
  "packageCount": 3,
  "currencyCode": "MYR",
  "dimensionsUnits": "IN",
  "weightUnits": "LB"
}

```

### 1.1.3. Output parameter instruction

Field name	Field description	Type	Length
customerCode	Customer code, supplied by JD (JD 提供客户唯一编号)	String	20
waybillCode	物流公司运单号	String	64
orderId	客户订单号	String	64
isSuccess	在线下单是否成功 true 或 false	Boolean	
reason	如果失败, 备注原因, 如果成功, 可为“”	String	64
labels	面单信息 (详情参见 Labels 说明)	Array	
totalAmount	面单价格	Number	

Label Field name	Field description	Type	Length
labelType	面单类型 (默认返回 OUTBOUND_LABEL)	String	20
packageID	原客户包裹号, 如 V000042135549-2-3-	String	64
trackingNumber	该包裹对应的三方物流跟踪号		
imageType	面单图片类型, PDF 或 PNG。如果返回的面单为外部链接, 本字段填为 URL.	String	64
images	一个图片的数组, 数组的元素为图片流的 Base64 编码字符串 (字符集为 UTF-8) 或外部链接, 如果面单只包含一张图片, 那么该数组中只有一个元素。生成图像字符串的方法: 1. 将图像的字节数组转换为 base64 字节数组 2. 通过使用 UTF-8 字符集解码 base64 字节数组构造一个字符串	array	

### Message sample

json:

```

{
  "reason": "",

```

```

"orderId": "V000042135549",
"isSuccess": true,
"customerCode": "your customer code",
"waybillCode": "YOURWAYBILLCODE123",
"totalAmount ": 20,
"labels": [
  {
    "images": [

"JVBERi0xLjcKJeLjz9MKNiAwIG9iago8PCAvVHlwZSAvUGFnZSAvUGFyZW50L....."
    ],
    "packageID": "V000042135549-1-3"
    "trackingNumber": "YOURWAYBILLCODE12301",
    "labelType": "OUTBOUND_LABEL",
    "imageType": "PDF"
  },
  {
    "images": [

"JVBERi0xLjcKJeLjz9MKNiAwIG9iago8PCAvVHlwZSAvUGFnZSAvUGFyZW50L....."
    ],
    "packageID": "V000042135549-2-3"
    "trackingNumber": "YOURWAYBILLCODE12302",
    "labelType": "OUTBOUND_LABEL",
    "imageType": "PDF"
  },
  {
    "images": [

"JVBERi0xLjcKJeLjz9MKNiAwIG9iago8PCAvVHlwZSAvUGFnZSAvUGFyZW50L....."
    ],
    "packageID": "V000042135549-3-3"
    "trackingNumber": "YOURWAYBILLCODE12303",
    "labelType": "OUTBOUND_LABEL",
    "imageType": "PDF"
  }
}

```

]

## 1.2. refund label 退款

### 1.1.1. Interface instruction

<b>Interface name</b>	退款接口
<b>Function description</b>	客户提出退款需求, JDL TMS 进行退款拦截
<b>Interface supplied by</b>	JDL TMS
<b>Data transfer</b>	Https
<b>Interaction method</b>	Post
<b>Encryption format</b>	application/x-www-form-urlencoded; charset=UTF-8
<b>Data format</b>	Json
<b>Interface address</b>	由 JDL TMS 提供给客户

### 1.1.2. Input parameter instruction

Field name	Field description	Required or not
logistics_info	运费信息的信息体, <b>对报文要进行 URL 编码</b>	Yes
encrypt_data	根据一定的加密规则, 得到的签名字符串	Yes
timestamp	时间戳, 格式 yyyy-MM-dd HH:mm:ss	Yes

### logistics\_info message body instruction

Field name	Field description	Required or not	Type	Length
customerCode	Customer code, supplied by JD 客户编码	Yes	String	20
trackingNumbers	Tracking numbers 追踪号	Yes	List	

### Message sample

json:

```
{
  "customerCode": "Your customer code",
  "trackingNumbers": [
    "9405511202565712314674",
    "9405511202565712711053",
    "9405511202565712421522",
    "9405511202565712653094"
  ]
}
```



}

### 1.1.3. Output parameter instruction

Field name	Field description	Type	Length
list	Refund list with refund status and error message 一个或多个轨迹的列表	List	

RefundList Field name	Field description	Type	Length
succeed	成功或者失败	Boolean	
trackingNumber	尾程跟踪号	String	
error	如果失败的报错信息	String	

### Message sample

json:

```
{
  "list": [
    {
      "succeed": true,
      "trackingNumber": "9405511202565712314674"
    },
    {
      "succeed": false,
      "trackingNumber": "9405511202565712711053",
      "error": "tracking number not found for this customer."
    },
    {
      "succeed": false,
      "trackingNumber": "9405511202565712421522",
      "error": "tracking number not found for this customer."
    },
    {
      "succeed": false,
      "trackingNumber": "9405511202565712653094",
      "error": "tracking number not found or already refunded."
    }
  ]
}
```

## 1.3. fetch label 抓取面单

### 1.1.1. Interface instruction

Interface name	抓取面单接口
Function description	客户获取真实运单
Interface supplied by	JDL TMS
Data transfer	Https
Interaction method	Post
Encryption format	application/x-www-form-urlencoded; charset=UTF-8
Data format	Json
Interface address	由 JDL TMS 提供给客户

### 1.1.2. Input parameter instruction

Field name	Field description	Required or not
logistics_info	运费信息的信息体， <b>对报文要进行 URL 编码</b>	Yes
encrypt_data	根据一定的加密规则，得到的签名字符串	Yes
timestamp	时间戳，格式 yyyy-MM-dd HH:mm:ss	Yes

### logistics\_info message body instruction

Field name	Field description	Required or not	Type	Length
customerCode	Customer code, supplied by JD 客户编码	Yes	String	20
customerOrderNumber	Customer Order Number 客户订单号	Yes	String	64

### Message sample

json:

```
{
  "customerCode": "Your customer code",
  "customerOrderNumber": "ABC20222H000009822"
}
```

### 1.1.3. Output parameter instruction

Field name	Field description	Type	Length
waybillCode	物流公司运单号	String	64
orderId	客户订单号	String	64
isSuccess	在线下单是否成功 true 或 false	Boolean	
reason	如果失败，备注原因，如果成功，可为“”	String	64
labels	面单信息（详情参见 Labels 说明）	Array	

totalAmount	面单价格	Number	
-------------	------	--------	--

Label Field name	Field description	Type	Length
labelType	面单类型 (默认返回 OUTBOUND_LABEL)	String	20
packageID	原客户包裹号, 如 V000042135549-2-3-	String	64
trackingNumber	该包裹对应的三方物流跟踪号		
imageType	面单图片类型, PDF 或 PNG。如果返回的面单为外部链接, 本字段填为 URL。	String	64
images	一个图片的数组, 数组的元素为图片流的 Base64 编码字符串 (字符集为 UTF-8) 或外部链接, 如果面单只包含一张图片, 那么该数组中只有一个元素。生成图像字符串的方法: 1. 将图像的字节数组转换为 base64 字节数组 2. 通过使用 UTF-8 字符集解码 base64 字节数组构造一个字符串	array	

### Message sample

json:

```
{
  "reason": "",
  "orderId": "V000042135549",
  "isSuccess": true,
  "customerCode": "your customer code",
  "waybillCode": "YOURWAYBILLCODE123",
  "totalAmount": 20,
  "labels": [
    {
      "images": [
        "JVBERi0xLjcKJeLjz9MKNiAwIG9iago8PCAvVHlwZSAvUGFnZSAvUGFyZW50L....."
      ],
      "packageID": "V000042135549-1-3",
      "trackingNumber": "YOURWAYBILLCODE12301",
      "labelType": "OUTBOUND_LABEL",
      "imageType": "PDF"
    },
    {
      "images": [
```

```

    "JVBeri0xLjcKJeLjz9MKNiAwIG9iago8PCAvVHlwZSAvUGFnZSAvUGFyZW50L....."
  ],
  "packageID": "V000042135549-2-3"
  "trackingNumber": "YOURWAYBILLCODE12302",
  "labelType": "OUTBOUND_LABEL",
  "imageType": "PDF"
},
{
  "images": [
    "JVBeri0xLjcKJeLjz9MKNiAwIG9iago8PCAvVHlwZSAvUGFnZSAvUGFyZW50L....."
  ],
  "packageID": "V000042135549-3-3"
  "trackingNumber": "YOURWAYBILLCODE12303",
  "labelType": "OUTBOUND_LABEL",
  "imageType": "PDF"
}
]
}

```

## 1.4. get rates 询价接口

### 1.4.1. Interface instruction

<b>Interface name</b>	询价接口
<b>Function description</b>	客户对相应尾程产品询价
<b>Interface supplied by</b>	JDL TMS
<b>Data transfer</b>	Https
<b>Interaction method</b>	Post
<b>Encryption format</b>	application/x-www-form-urlencoded; charset=UTF-8
<b>Data format</b>	Json
<b>Interface address</b>	由 JDL TMS 提供给客户

### 1.4.2. Input parameter instruction

Field name	Field description	Required or not
logistics_info	<b>URL encoded for online order message</b> 在线下单的消息体， <b>对报文要进行 URL 编码</b>	Yes
encrypt_data	Signed string generated based on specific encryption rules 根据一定的加密规则，得到的签名字符串	Yes

timestamp	Timestamp, format: yyyy-MM-dd HH:mm:ss, e.g. 2017-07-15 17:56:42 时间戳, 格式 yyyy-MM-dd HH:mm:ss 如果时间戳与当前北京时间相差 15 分钟以上, 则视为恶意访问; 因此, 应注意时间戳的准确性。	Yes
-----------	--	-----

### 1. logistics\_info message body instruction

Field name	Field description	Required or not	Type	Length
customerCode	Customer code, supplied by JD (JD 提供客户唯一编号)	Yes	String	20
serviceCode	Integrated product code from JDL , TMS 下发的京东产品编码	Yes	String	
packageInfos	Package info (For details, please refer to PackageInfo instruction) 包裹信息(详情参见 PackageInfo 说明)	No	Array	
sender	SenderInfo(For details, please refer to Sender Instruction) 发件人信息(详情参见 Sender 说明)	Yes	Sender	
receiver	ReceiverInfo (For details, please refer to Receiver Instruction) 收件人信息(详情参见 Receiver 说明)	Yes	Receiver	
dimensionsUnits	The unit of measurement of width、length and height. the default is IN 长度单位 (默认英尺)	Yes	String	10
weightUnits	The unit of measurement of weight. The default is LB 重量单位 (默认磅)	Yes	String	10

PackageInfo field name	Field description	Required or not	Type	Length
weight	Package weight, unit: LB 包裹重量 LB	Yes	Number	
volume	Package volume, unit: Cubic IN 包裹体积	No	Number	
length	Package length, unit: IN 包裹长度	Yes	Number	
width	Package width, unit: IN 包裹宽度	Yes	Number	
height	Package height, Unit: IN 包裹高度	Yes	Number	

Sender field name 发件人	Field description	Required or not	Type	Length
name	发件人姓名	Yes	String	64
companyName	发件人公司名称	No	String	64

mobile	发件人手机号 (与发件人电话号其中之一必传)	Yes	String	32
tel	发件人电话号	No	String	32
country	发件人国别二字码	Yes	String	2
province	省	Yes	String	32
city	市	Yes	String	32
county	区县	No	String	32
town	街道	No	String	32
address	详细地址	Yes	String	50
address2	详细地址 2	No	String	50
address3	详细地址 3	No	String	50
houseNumber	寄件人门牌号	No	String	25
zipCode	邮政编码	Yes	String	32

Receiver field name 收件人信息	Field description	Required or not	Type	Length
name	收件人姓名	Yes	String	64
companyName	收件人公司名称	No	String	64
mobile	收件人手机号 (与收件人电话号其中之一必传)	Yes	String	32
tel	收件人电话号	No	String	32
Country	收件人国别二字码	Yes	String	2
province	省	Yes	String	32
city	市	Yes	String	32
county	区县	No	String	32
town	街道	No	String	32
address	详细地址	Yes	String	50
address2	详细地址 2	No	String	50
address3	详细地址 3	No	String	50
houseNumber	收货人门牌号	No	String	25
zipCode	邮政编码	Yes	String	32
email	邮箱	No	String	64

## Message sample

**json:**

```
{
  "customerCode": "your customer code",
  "serviceCode": "PF",
```

```
"packageInfos": [  
  {  
    "weight": 6.67,  
    "volume": 1.0,  
    "length": 1.0,  
    "width": 1.0,  
    "height": 1.0  
  }  
],  
"sender": {  
  "name": "Pelamor",  
  "companyName": "MyTest Corp",  
  "mobile": "01756321199",  
  "province": "Selangor",  
  "city": "PETALING JAYA",  
  "county": null,  
  "town": null,  
  "address": "Kompleks Penchala, Ground Floor, No 50",  
  "zipCode": "46052",  
  "country": "MY",  
  "tel": "",  
  "address2": "",  
  "address3": "",  
  "houseNumber": ""  
},  
"receiver": {  
  "name": "SOMA PULIN",  
  "companyName": null,  
  "mobile": "60012345427",  
  "province": "Johor",  
  "city": "Kahang",  
  "county": null,  
  "town": null,  
  "address": "KOLEJ KEDIAMAN D (MAIDAM), KAMPUS PERUBATAN UNISZA",  
  "zipCode": "86733",  
  "email": null,
```

```

    "country": "MY",
    "tel": "",
    "address2": "",
    "address3": "",
    "houseNumber": ""
  },
  "dimensionsUnits": "IN",
  "weightUnits": "LB"
}

```

### 1.1.3. Output parameter instruction

Field name	Field description	Type	Length
list	Rate list 询价返回列表	List	

RefundList Field name	Field description	Type	Length
isSuccess	成功或者失败	Boolean	
errMsg	失败的报错信息	String	
estimatedDays	预计运输时间	String	
totalWeight	重量	String	
weightUnit	重量单位	String	
yourRate	预估运费价格	Number	
currency	币种	String	
serviceCode	Integrated product code from JDL , TMS 下发的京东产品编码	String	

### Message sample

json:

```

{
  "list": [
    {
      "isSuccess": true,
      "errMsg": null,
      "estimatedDays": "3-10",
      "totalWeight": "0.125",
      "weightUnit": "lb",
      "yourRate": 3.5,
    }
  ]
}

```



```

    "currency": "USD",
    "serviceCode": "PF"
  }
]
}

```

## 1.5. Tracking Information Push 轨迹推送

### 1.5.1. Interface instruction

Interface name	轨迹推送
Function description	回推轨迹给客户
Interface supplied by	客户提供
Data transfer	Https
Interaction method	Post
Encoding format	application/x-www-form-urlencoded; charset=UTF-8
Data format	Xml or Json
Interface address	客户提供

### 1.5.2. Input parameter instruction

Field name	Field description(EN)	Field description(CN)	Required or not	Type	Length
list	A list of one or several tracking records	一个或多个轨迹的列表	Yes	Array	

Field name	Field description(EN)	Field description(CN)	Required or not	Type	Length
logistics_info	<b>URL encoded for tracking information</b>	路由信息的信息体， <b>对报文要进行 URL 编码</b>	Yes	Object	
encrypt_data	Signed string generated by specific encryption rules	根据一定的加密规则，得到的签名字符串	Yes	String	
timestamp	Timestamp, format is yyyy-MM-dd HH:mm:ss, e.g. 2016-06-24 11:51:45.	时间戳，格式 yyyy-MM-dd HH:mm:ss	Yes	String	

### logistics\_info/轨迹消息体结构说明

Field name	Field description(EN)	Field description(CN)	Required or not	Type	Length
waybillCode	Logistics waybill number	物流公司运单号	Yes	String	64
traces	Tracking information list	轨迹列表（详情参见 Trace 说明）	Yes	List	

### Trace/轨迹列表

Trace field name	Field description(EN)	Field description(CN)	Required or not	Type	Length
operateTime	Operate time, format is yyyy-MM-dd HH:mm:ss	操作时间, 格式为 yyyy-MM-dd HH:mm:ss	Yes	String	64
desc	Tracking information description	轨迹信息描述	Yes	String	256
scanType	Event/operation, for details, please refer to below SCANTYPE table encryption specifications, Mandatory for THA and IND, Optional for other countries	事件/操作, 详情参见 SCANTYPE 编码规范。无对应事件可置为 OTHER, 每一单均需以 SIGNED 或 FAILED 作结束状态。THA 和 IND 强制, 其他国家可选	Based on certain conditions	String	64
originalScanType	Origin 3p event codes	服务商原始状态码	Yes	25	
city	Current city	当前城市	Yes	String	64

### Message sample

json:

```
{
  "list": [
    {
      "waybillCode": "YOURWAYBILLCODE12301",
      "traces": {
        "operateTime": "2020-05-27 17:03:57",
        "desc": "Pickup Complete",
        "scanType": "GOT",
        "originalScanType": "COLLECTED",
        "city": "Kuala Lumpur"
      }
    },
    {
      "waybillCode": "YOURWAYBILLCODE12302",
      "traces": {
        "operateTime": "2020-05-27 17:03:57",
        "desc": "Arrived to customer",
```

```

    "scanType": "SIGNED",
    "city": "Kuala Lumpur"
  }
}
]
}

```

### 1.5.3. Output parameter instruction

Field name	Field description(EN)	Field description(CN)	Required or not	Type	Length
customerCode	Customer code, supplied by JD	JD 提供客户唯一编号	Yes	String	20
responseItems	Pushed orders execution responses	推送订单的执行结果 (详情参见 Response 说明)	Yes	List	
responseState	Response of interface calling, 0 represents full success, 1 represents partial success, 2 represents failure of parameter verification and 3 represents abnormal responses	调用接口的执行结果, 0 为全部成功 1 为部分成功 2 为参数校验失败 3 为执行时出现异常	Yes	Integer	
errorDesc	Error descriptions, when responseState is 0 or 1, the value is "", when responseState is 2 or 3, relevant error descriptions will be given	错误描述信息, responseState 为 0 或者 1 时, 值为 "", responseState 为 2 或者 3 时, 有对应的错误描述	No	String	64

### Response/订单的执行结果

Response field name	Field description(EN)	Field description(CN)	Required or not	Type	Length
waybillCode	logistics waybill number	物流公司运单号	Yes	String	64
isSuccess	Success or not; true or false	是否成功 true 或者 false	Yes	Boolean	
reason	Failed reason	失败原因	No	String	64

### Message sample

json:

```

{
  "customerCode": "your customer code",

```

```
"responseState": 0,
"errorDesc": "",
"responseItems": [
  {
    "waybillCode": "YOURWAYBILLCODE12302",
    "isSuccess": true,
    "reason": ""
  },
  {
    "waybillCode": "YOURWAYBILLCODE12301",
    "isSuccess": true,
    "reason": ""
  }
]
}
```