


MESA

Week 3: Binary evolution

MESA Binary - simplified

MESA binary combines the single star evolution code found in `mesa/star` for two stars, and adds a binary module on top of this:



The binary part of MESA can be found in: `mesa/binary`, and has the same structure as the single star part.


A standard working directory: `mesa/binary/work`

List of examples (test suite): `mesa/binary/test_suite`

MESA Binary - reality

MESA binary combines the single star evolution code found in `mesa/star` for two stars, and adds a binary module on top of this:

There is a lot of switching between modules to set variables.



- In theory donor and accretor can switch roles, but in practice it is easier to assign each star a fixed role.
- In theory Mesa can evolve 3 or more stars, but in practice this is not implemented.

Binary: file structure

Evolve 2 stars at the same time → double the amount of input files + binary controls

```
inlist                # base inlist for mesa
inlist_project        # inlist with binary parameters

binary_history_columns.list # binary parameters to save

history_columns.list   # star parameters to save for history
profile_columns.list   # star parameters to save for profiles

binary_history.data    # mesa output for binary
```

Star 1 files - donor

```
LOGS1
photos1
inlist1
```

star 2 files - accretor

```
LOGS2
photos2
inlist2
```

Binary: file structure

Evolve 2 stars at the same time → double the amount of input files + binary controls

```
inlist                # base inlist for mesa
inlist_project        # inlist with binary parameters

binary_history_columns.list # binary parameters to save

history_columns.list   # star parameters to save for history
profile_columns.list   # star parameters to save for profiles

binary_history.data    # mesa output for binary
```

Not in the LOG directory!

Star 1 files - donor

LOGS1
photos1
inlist1

star 2 files - accretor

LOGS2
photos2
inlist2

These are the same structure and format
as for single star evolution

Binary: input

In the `inlist_project` file: define the binary parameters and the links to the stellar input parameters

`&binary_job`

Different names than single star environments!

```
inlist_names(1) = 'inlist1' ! input file for star 1
```

```
inlist_names(2) = 'inlist2' ! input file for star 2
```

```
evolve_both_stars = .true. ! you can evolve star 1, or both stars
```

```
/ ! end of binary_job namelist
```

`&binary_controls`

```
m1 = 1.0d0 ! donor mass in Msun
```

```
m2 = 0.8d0 ! companion mass in Msun
```

```
initial_period_in_days = 2d0
```

```
/ ! end of binary_controls namelist
```

`&binary_pgstar`

Does not exists yet!

Binary: input

`&binary_job`: Only define inlists for stars, and whether to evolve both stars or not. There are no other settings here.

`&binary_job`

```
inlist_names(1) = 'inlist1' ! input file for star 1
inlist_names(2) = 'inlist2' ! input file for star 2

evolve_both_stars = .true. ! you can evolve star 1, or both stars
```

`/ ! end of binary_job namelist`

`&binary_controls`

```
m1 = 1.0d0 ! donor mass in Msun
m2 = 0.8d0 ! companion mass in Msun
initial_period_in_days = 2d0
```

`/ ! end of binary_controls namelist`

MESA can treat the companion (accretor) as a point mass.

Binary: input

`&binary_controls`: Initial setup, output parameters, mass loss settings, ...

`&binary_job`

```
inlist_names(1) = 'inlist1'  ! input file for star 1  
inlist_names(2) = 'inlist2'  ! input file for star 2
```

```
evolve_both_stars = .true.    ! you can evolve star 1, or both stars
```

```
/ ! end of binary_job namelist
```

`&binary_controls`

```
m1 = 1.0d0  ! donor mass in Msun  
m2 = 0.8d0  ! companion mass in Msun  
initial_period_in_days = 2d0
```

```
/ ! end of binary_controls namelist
```

Remember: [mesa/binary/defaults](http://mesa.sourceforge.net/) and <http://mesa.sourceforge.net/>

Binary: Output

Binary parameters are only history parameters (There is nothing to make a profile of)

Indicate in `binary_history_columns.list` which parameters to save

Binary parameters are saved in `binary_history.data`

```
model_number ! model number of donor star
```

```
age          ! age of donor star
```

```
period_days  ! orbital period in days
```

```
binary_separation ! orbital separation in rsun
```

```
eccentricity  ! orbital eccentricity
```

```
J_orb        ! orbital angular momentum
```

```
rl_1          ! roche lobe radius of first star in rsun
```

```
lg_mstar_dot_1 ! log10 of first star abs(mdot) in Msun/secyer
```

```
lg_wind_mdot_1 ! log10 of first star abs(mdot) due to winds in Msun/secyer
```

```
...
```

Binary: pgplot

Plotting parameters are defined in the pgstar section of the first star: **inlist1**

Binary parameters are history parameters → use history plot

&pgstar

```
History_Panels1_win_flag = .true.
```

```
History_Panels1_win_width = 5
```

```
History_Panels1_title = 'Orbital evolution'
```

```
History_Panels1_num_panels = 2
```

```
History_Panels1_yaxis_name(1) = 'period_days'
```

```
History_Panels1_other_yaxis_name(1) = 'lg_mstar_dot_1'
```

```
History_Panels1_yaxis_name(2) = 'Jdot'
```

```
History_Panels1_other_yaxis_name(2) = 'binary_separation'
```

```
/ ! end of pgstar namelist
```

Binary: pgplot

Plotting parameters are defined in the pgstar section of the first star: **inlist1**


Binary parameters are history parameters → use history plot

For pgstar to access the history output, you need to also write the history output of the binary module to the stellar history files:

```
append_to_star_history = .true.
```

This is turned on by default.

Binary: mass-loss fractions



$$1 - \alpha - \beta - \delta = \epsilon$$

- Alpha : Mass lost in fast wind around donor
- Beta : Mass transferred to companion, and then lost in a fast wind
- Delta : Mass lost through the outer lagrange point L2
- Epsilon : Accreted mass

Exercise 3: Roche lobe overflow

Roche lobe overflow (RLOF) during the RGB is an important process that creates many 'special' types of systems. In this exercise you will start from a system containing a main sequence star and a red giant on a wide orbit ($P \sim 600$ days), and study the effect of the mass loss fractions on the orbital parameters.

Pick a set of α , β and γ so that their sum is 1 (no accretion). Evolve the system till after RLOF starts, and check what happened with the orbital period and the mass loss rate.

Hints:

We will only evolve the donor star (to speed up)

You need to setup the initial parameter so that the RGB model is loaded for the donor star, and the companion is a regular main sequence star.

Also set:

```
terminate_if_initial_overflow = .false.  
mdot_scheme = 'Kolb'  
max_explicit_abs_mdot = 1d-2  
mass_transfer_gamma = 1.2
```