

class 13

Eli Sobel A69027989

```
library(DESeq2)
```

Loading required package: S4Vectors

Loading required package: stats4

Loading required package: BiocGenerics

Attaching package: 'BiocGenerics'

The following objects are masked from 'package:stats':

IQR, mad, sd, var, xtabs

The following objects are masked from 'package:base':

anyDuplicated, aperm, append, as.data.frame, basename, cbind,
colnames, dirname, do.call, duplicated, eval, evalq, Filter, Find,
get, grep, grepl, intersect, is.unsorted, lapply, Map, mapply,
match, mget, order, paste, pmax, pmax.int, pmin, pmin.int,
Position, rank, rbind, Reduce, rownames, sapply, saveRDS, setdiff,
table, tapply, union, unique, unsplit, which.max, which.min

Attaching package: 'S4Vectors'

The following object is masked from 'package:utils':

findMatches

The following objects are masked from 'package:base':

expand.grid, I, unname

Loading required package: IRanges

Attaching package: 'IRanges'

The following object is masked from 'package:grDevices':

windows

Loading required package: GenomicRanges

Loading required package: GenomeInfoDb

Loading required package: SummarizedExperiment

Loading required package: MatrixGenerics

Loading required package: matrixStats

Warning: package 'matrixStats' was built under R version 4.4.2

Attaching package: 'MatrixGenerics'

The following objects are masked from 'package:matrixStats':

colAlls, colAnyNAs, colAnys, colAvgsPerRowSet, colCollapse,
colCounts, colCummaxs, colCummins, colCumprods, colCumsums,
colDiffs, colIQRDiffs, colIQRs, colLogSumExps, colMadDiffs,
colMads, colMaxs, colMeans2, colMedians, colMins, colOrderStats,
colProds, colQuantiles, colRanges, colRanks, colSdDiffs, colSds,
colSums2, colTabulates, colVarDiffs, colVars, colWeightedMads,
colWeightedMeans, colWeightedMedians, colWeightedSds,
colWeightedVars, rowAlls, rowAnyNAs, rowAnys, rowAvgsPerColSet,
rowCollapse, rowCounts, rowCummaxs, rowCummins, rowCumprods,

```
rowCumsums, rowDiffs, rowIQRDiffs, rowIQRs, rowLogSumExps,
rowMadDiffs, rowMads, rowMaxs, rowMeans2, rowMedians, rowMins,
rowOrderStats, rowProds, rowQuantiles, rowRanges, rowRanks,
rowSdDiffs, rowSds, rowSums2, rowTabulates, rowVarDiffs, rowVars,
rowWeightedMads, rowWeightedMeans, rowWeightedMedians,
rowWeightedSds, rowWeightedVars
```

Loading required package: Biobase

Welcome to Bioconductor

```
Vignettes contain introductory material; view with
'browseVignettes()'. To cite Bioconductor, see
'citation("Biobase")', and for packages 'citation("pkgname")'.
```

Attaching package: 'Biobase'

The following object is masked from 'package:MatrixGenerics':

```
rowMedians
```

The following objects are masked from 'package:matrixStats':

```
anyMissing, rowMedians
```

Today we're going to work with bulk RNASeq data from Himes et al. where airway smooth muscle cells were treated with dexamethasone (dex), a synthetic glucocorticoid steroid with anti-inflammatory effects.

```
counts <- read.csv("airway_scaledcounts.csv", row.names=1)
metadata <- read.csv("airway_metadata.csv")
head(counts)
```

	SRR1039508	SRR1039509	SRR1039512	SRR1039513	SRR1039516
ENSG000000000003	723	486	904	445	1170
ENSG000000000005	0	0	0	0	0
ENSG000000000419	467	523	616	371	582
ENSG000000000457	347	258	364	237	318
ENSG000000000460	96	81	73	66	118

ENSG00000000938	0	0	1	0	2
	SRR1039517	SRR1039520	SRR1039521		
ENSG00000000003	1097	806	604		
ENSG00000000005	0	0	0		
ENSG00000000419	781	417	509		
ENSG00000000457	447	330	324		
ENSG00000000460	94	102	74		
ENSG00000000938	0	0	0		

```
head(metadata)
```

	id	dex	celltype	geo_id
1	SRR1039508	control	N61311	GSM1275862
2	SRR1039509	treated	N61311	GSM1275863
3	SRR1039512	control	N052611	GSM1275866
4	SRR1039513	treated	N052611	GSM1275867
5	SRR1039516	control	N080611	GSM1275870
6	SRR1039517	treated	N080611	GSM1275871

```
nrow(counts)
```

```
[1] 38694
```

Q1 How many transcripts/genes are in the `counts` object?

There are 38694 genes in this dataset

Q2 How many “control” samples are there?

There are 4 control samples.

```
sum(metadata$dex == "control")
```

```
[1] 4
```

```
table(metadata$dex)
```

control	treated
4	4

I want to compare “control” vs “treated”.

1. Let’s split the “counts” into `control.counts` and `treated.counts`.

```
metadata$id == colnames(counts)
```

```
[1] TRUE TRUE TRUE TRUE TRUE TRUE TRUE TRUE
```

```
control.inds <- metadata$dex == "control"  
control.treated <- metadata$dex == "treated"
```

```
control.counts <- counts[ , control.inds]  
head(control.counts)
```

	SRR1039508	SRR1039512	SRR1039516	SRR1039520
ENSG000000000003	723	904	1170	806
ENSG000000000005	0	0	0	0
ENSG000000000419	467	616	582	417
ENSG000000000457	347	364	318	330
ENSG000000000460	96	73	118	102
ENSG000000000938	0	1	2	0

```
treated.counts <- counts[ , control.treated]
```

Other ways to do this:

```
control.inds
```

```
[1] TRUE FALSE TRUE FALSE TRUE FALSE TRUE FALSE
```

```
!control.inds
```

```
[1] FALSE TRUE FALSE TRUE FALSE TRUE FALSE TRUE
```

```
metadata$dex != "control"
```

```
[1] FALSE TRUE FALSE TRUE FALSE TRUE FALSE TRUE
```

```
metadata$dex == "treated"
```

```
[1] FALSE TRUE FALSE TRUE FALSE TRUE FALSE TRUE
```

2. Let's calculate the mean counts per gene for "control" and "treated" - then we can compare these. Let's call it `control.mean` and `treated.mean`.

I can use the `apply()` function to apply `mean()` over the rows or columns in our data.frame.

```
head(control.counts)
```

	SRR1039508	SRR1039512	SRR1039516	SRR1039520
ENSG000000000003	723	904	1170	806
ENSG000000000005	0	0	0	0
ENSG000000000419	467	616	582	417
ENSG000000000457	347	364	318	330
ENSG000000000460	96	73	118	102
ENSG000000000938	0	1	2	0


```
control.mean <- apply(control.counts, 1, mean)
treated.mean <- apply(treated.counts, 1, mean)
```

Put together for ease of book-keeping

```
meancounts <- data.frame(control.mean, treated.mean)
plot(meancounts, log="xy")
```

Warning in `xy.coords(x, y, xlabel, ylabel, log)`: 15032 x values ≤ 0 omitted from logarithmic plot

Warning in `xy.coords(x, y, xlabel, ylabel, log)`: 15281 y values ≤ 0 omitted from logarithmic plot



We most often use log2 transforms here because it makes the math easier.

```
log2(10/10)
```

```
[1] 0
```

```
log2(20/10)
```

```
[1] 1
```

```
log2(40/10)
```

```
[1] 2
```

Let's calculate the log2 fold change and add it to our table `meancounts`.

```
meancounts$log2fc <- log2(meancounts$treated.mean/meancounts$control.mean)
head(meancounts)
```

	control.mean	treated.mean	log2fc
ENSG000000000003	900.75	658.00	-0.45303916
ENSG000000000005	0.00	0.00	NaN
ENSG000000000419	520.50	546.00	0.06900279
ENSG000000000457	339.75	316.50	-0.10226805
ENSG000000000460	97.25	78.75	-0.30441833
ENSG000000000938	0.75	0.00	-Inf

Filter out all genes with zero counts in either control or treated:

```
to.rm <- rowSums(meancounts[,1:2] == 0) > 0
mycounts <- meancounts[!to.rm, ]
head(mycounts)
```

	control.mean	treated.mean	log2fc
ENSG000000000003	900.75	658.00	-0.45303916
ENSG000000000419	520.50	546.00	0.06900279
ENSG000000000457	339.75	316.50	-0.10226805
ENSG000000000460	97.25	78.75	-0.30441833
ENSG000000000971	5219.00	6687.50	0.35769358
ENSG00000001036	2327.00	1785.75	-0.38194109

```
nrow(mycounts)
```

```
[1] 21817
```

Q. How many “down” regulated genes do we have at the common log2 fold change value of < -2 ?

```
367
```

```
count(mycounts[,3] < -2 )
```

```
[1] 367
```

Q. How many “up” at log2FC > 2 ?

```
250
```



```
count(mycounts[,3] > 2 )
```

```
[1] 250
```

Do we trust this? Is there anything missing?

We are missing the stats!

DESeq analysis

```
library(DESeq2)
```

DESeq, like many BioConductor packages, wants our input data in a very specific format.

```
dds <- DESeqDataSetFromMatrix(countData = counts, colData = metadata, design = ~dex)
```

converting counts to integer mode

Warning in DESeqDataSet(se, design = design, ignoreRank): some variables in design formula are characters, converting to factors

```
head(dds)
```

```
class: DESeqDataSet
dim: 6 8
metadata(1): version
assays(1): counts
rownames(6): ENSG000000000003 ENSG000000000005 ... ENSG000000000460
           ENSG000000000938
rowData names(0):
colnames(8): SRR1039508 SRR1039509 ... SRR1039520 SRR1039521
colData names(4): id dex celltype geo_id
```

The main function of DESeq2 is called DESeq().

```
dds <- DESeq(dds)
```

estimating size factors

estimating dispersions

gene-wise dispersion estimates

mean-dispersion relationship

final dispersion estimates

fitting model and testing

```
res <- results(dds)
```

```
head(res)
```

log2 fold change (MLE): dex treated vs control

Wald test p-value: dex treated vs control


DataFrame with 6 rows and 6 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG000000000003	747.194195	-0.3507030	0.168246	-2.084470	0.0371175
ENSG000000000005	0.000000	NA	NA	NA	NA
ENSG000000000419	520.134160	0.2061078	0.101059	2.039475	0.0414026
ENSG000000000457	322.664844	0.0245269	0.145145	0.168982	0.8658106
ENSG000000000460	87.682625	-0.1471420	0.257007	-0.572521	0.5669691
ENSG000000000938	0.319167	-1.7322890	3.493601	-0.495846	0.6200029
	padj				
	<numeric>				
ENSG000000000003	0.163035				
ENSG000000000005	NA				
ENSG000000000419	0.176032				
ENSG000000000457	0.961694				
ENSG000000000460	0.815849				
ENSG000000000938	NA				

A common overview figure plots the logFC vs the P-value.

```
mycols <- rep("gray", nrow(res))
mycols[res$log2FoldChange > 2] <- "red"
mycols[res$log2FoldChange < -2] <- "blue"
mycols[res$padj > 0.005] <- "gray"

plot(res$log2FoldChange, -log(res$padj), col=mycols)
abline(v=c(2,-2), col="gray")
abline(h=-log(0.005), col="gray")
```



```
write.csv(res, file="myresults.csv")
```

Gene annotation

```
head(res)
```

log2 fold change (MLE): dex treated vs control

Wald test p-value: dex treated vs control

DataFrame with 6 rows and 6 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>

ENSG000000000003	747.194195	-0.3507030	0.168246	-2.084470	0.0371175
ENSG000000000005	0.000000	NA	NA	NA	NA
ENSG0000000000419	520.134160	0.2061078	0.101059	2.039475	0.0414026
ENSG0000000000457	322.664844	0.0245269	0.145145	0.168982	0.8658106
ENSG0000000000460	87.682625	-0.1471420	0.257007	-0.572521	0.5669691
ENSG0000000000938	0.319167	-1.7322890	3.493601	-0.495846	0.6200029

padj
<numeric>

ENSG000000000003	0.163035
ENSG000000000005	NA
ENSG0000000000419	0.176032
ENSG0000000000457	0.961694
ENSG0000000000460	0.815849
ENSG0000000000938	NA

```
library("AnnotationDbi")
library("org.Hs.eg.db")
```

```
columns(org.Hs.eg.db)
```

[1]	"ACCNUM"	"ALIAS"	"ENSEMBL"	"ENSEMBLPROT"	"ENSEMBLTRANS"
[6]	"ENTREZID"	"ENZYME"	"EVIDENCE"	"EVIDENCEALL"	"GENENAME"
[11]	"GENETYPE"	"GO"	"GOALL"	"IPI"	"MAP"
[16]	"OMIM"	"ONTOLOGY"	"ONTOLOGYALL"	"PATH"	"PFAM"
[21]	"PMID"	"PROSITE"	"REFSEQ"	"SYMBOL"	"UCSCKG"
[26]	"UNIPROT"				

```
res$symbol <- mapIds(org.Hs.eg.db,
                      keys=row.names(res), # Our genenames
                      keytype="ENSEMBL",   # The format of our genenames
                      column="SYMBOL",     # The new format we want to add
                      multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

Pathway analysis

```
library(pathview)
```

```
#####  
Pathview is an open source software package distributed under GNU General  
Public License version 3 (GPLv3). Details of GPLv3 is available at  
http://www.gnu.org/licenses/gpl-3.0.html. Particullary, users are required to  
formally cite the original Pathview paper (not just mention it) in publications  
or products. For details, do citation("pathview") within R.
```

The pathview downloads and uses KEGG data. Non-academic uses may require a KEGG license agreement (details at <http://www.kegg.jp/kegg/legal.html>).

```
#####
```

```
library(gage)
```

```
library(gageData)
```

I need to speak ENTREZID so I can check KEGG pathway overlap as KEGG uses ENTREZ format IDs

```
res$entrez <- mapIds(org.Hs.eg.db, keys=row.names(res), keytype="ENSEMBL", column="ENTREZID"
```

'select()' returned 1:many mapping between keys and columns

I can now use the **gage** function to check for overlap with known KEGG pathways.

```
foldchanges <- res$log2FoldChange  
names(foldchanges) <- res$entrez  
head(foldchanges)
```

7105	64102	8813	57147	55732	2268
-0.35070302	NA	0.20610777	0.02452695	-0.14714205	-1.73228897

```
data(kegg.sets.hs)
```

```
# Get the results
keggres = gage(foldchanges, gsets=kegg.sets.hs)
```

```
attributes(keggres)
```

```
$names
[1] "greater" "less"      "stats"
```

```
head(keggres$less, 3)
```

		p.geomean	stat.mean	p.val
hsa05332	Graft-versus-host disease	0.0004250461	-3.473346	0.0004250461
hsa04940	Type I diabetes mellitus	0.0017820293	-3.002352	0.0017820293
hsa05310	Asthma	0.0020045888	-3.009050	0.0020045888

		q.val	set.size	exp1
hsa05332	Graft-versus-host disease	0.09053483	40	0.0004250461
hsa04940	Type I diabetes mellitus	0.14232581	42	0.0017820293
hsa05310	Asthma	0.14232581	29	0.0020045888

```
hsa05310
```

```
pathview(gene.data=foldchanges, pathway.id="hsa05310")
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory C:/Users/eliso/Desktop/Bioinformatics/class13

Info: Writing image file hsa05310.pathview.png




Figure 1: A pathway figure