

class11

Eli Sobel A69027989

Today, before delving into structure prediction with AlphaFold we will finish off our previous lab10 “comparative structure analysis” section.

```
library(bio3d)

id <- "1ake_A"

aa <- get.seq(id)
```

Warning in get.seq(id): Removing existing file: seqs.fasta

Fetching... Please wait. Done.

aa

```

      1      .      .      .      .      .      .      60
pdb|1AKE|A  MRIILLGAPGAGKGTQAQFIMEKYGIPQISTGDMMLRAAVKSGSELGKQAKDIMDAGKLVT
      1      .      .      .      .      .      .      60

      61      .      .      .      .      .      .      120
pdb|1AKE|A  DELVIALVKERIAQEDCRNGFLLDGFPRTPQADAMKEAGINVDYVLEFDVPDELIVDRI
      61      .      .      .      .      .      .      120

      121      .      .      .      .      .      .      180
pdb|1AKE|A  VGRRVHAPSGRVYHVKNPPKVEGKDDVTGEELTTRKDDQEETVRKRLVEYHQMTAPLIG
      121      .      .      .      .      .      .      180

      181      .      .      .      214
pdb|1AKE|A  YYSKEAEAGNTKYAKVDGTPVAEVRADLEKILG
      181      .      .      .      214
```

```
Call:
  read.fasta(file = outfile)
```

```
Class:
  fasta
```

```
Alignment dimensions:
  1 sequence rows; 214 position columns (214 non-gap, 0 gap)
```

```
+ attr: id, ali, call
```

```
b <- blast.pdb(aa)
```

```
Searching ... please wait (updates every 5 seconds) RID = JS1FFSC6016
...
Reporting 85 hits
```

```
attributes(b)
```

```
$names
[1] "hit.tbl" "raw"      "url"
```

```
$class
[1] "blast"
```


```
head(b$hit.tbl)
```

	queryid	subjectids	identity	alignmentlength	mismatches	gapopens	q.start		
1	Query_1967435	1AKE_A	100.000	214	0	0	1		
2	Query_1967435	8BQF_A	99.533	214	1	0	1		
3	Query_1967435	4X8M_A	99.533	214	1	0	1		
4	Query_1967435	6S36_A	99.533	214	1	0	1		
5	Query_1967435	8Q2B_A	99.533	214	1	0	1		
6	Query_1967435	8RJ9_A	99.533	214	1	0	1		
	q.end	s.start	s.end	evaluate	bitscore	positives	mlog.evaluate	pdb.id	acc
1	214	1	214	1.58e-156	432	100.00	358.7458	1AKE_A	1AKE_A
2	214	21	234	2.58e-156	433	100.00	358.2555	8BQF_A	8BQF_A
3	214	1	214	2.82e-156	432	100.00	358.1665	4X8M_A	4X8M_A
4	214	1	214	4.14e-156	432	100.00	357.7826	6S36_A	6S36_A
5	214	1	214	1.10e-155	431	99.53	356.8054	8Q2B_A	8Q2B_A
6	214	1	214	1.10e-155	431	99.53	356.8054	8RJ9_A	8RJ9_A

```
hits <- plot(b)
```

```
* Possible cutoff values: 197 11
    Yielding Nhits:      19 85
```

```
* Chosen cutoff value of: 197
    Yielding Nhits:      19
```



```
attributes(hits)
```

```
$names
```

```
[1] "hits" "pdb.id" "acc" "inds"
```

```
$class
```

```
[1] "blast"
```

Top hits that we like from our blast results:

```
hits$pdb.id
```

```
[1] "1AKE_A" "8BQF_A" "4X8M_A" "6S36_A" "8Q2B_A" "8RJ9_A" "6RZE_A" "4X8H_A"  
[9] "3HPR_A" "1E4V_A" "5EJE_A" "1E4Y_A" "3X2S_A" "6HAP_A" "6HAM_A" "4K46_A"  
[17] "4NP6_A" "3GMT_A" "4PZL_A"
```

find and download all related structures

```
# download related PDB files  
files <- get.pdb(hits$pdb.id, path="pdbs", split=TRUE, gzip=TRUE)
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/1AKE.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/8BQF.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/4X8M.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/6S36.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/8Q2B.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/8RJ9.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/6RZE.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/4X8H.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/3HPR.pdb exists. Skipping download
```

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1E4V.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/5EJE.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1E4Y.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3X2S.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6HAP.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6HAM.pdb exists. Skipping download


Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4K46.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4NP6.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3GMT.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4PZL.pdb exists. Skipping download

	0%
====	5%
=====	11%
=====	16%



I have now found and downloaded all ADK structures in the PDB database but viewing them is difficult as they need to be aligned and superposed.

I am going to install BiocManager package from CRAN. Then I can use “BiocManager::install(“msa”)“.

```
# Align related PDBs
pdbbs <- pdbaln(files, fit = TRUE, exefile="msa")
```

Reading PDB files:

```

pdbs/split_chain/1AKE_A.pdb
pdbs/split_chain/8BQF_A.pdb
pdbs/split_chain/4X8M_A.pdb
pdbs/split_chain/6S36_A.pdb
pdbs/split_chain/8Q2B_A.pdb
pdbs/split_chain/8RJ9_A.pdb
pdbs/split_chain/6RZE_A.pdb
pdbs/split_chain/4X8H_A.pdb
pdbs/split_chain/3HPR_A.pdb
pdbs/split_chain/1E4V_A.pdb
pdbs/split_chain/5EJE_A.pdb
pdbs/split_chain/1E4Y_A.pdb
pdbs/split_chain/3X2S_A.pdb
pdbs/split_chain/6HAP_A.pdb
pdbs/split_chain/6HAM_A.pdb
pdbs/split_chain/4K46_A.pdb
pdbs/split_chain/4NP6_A.pdb
pdbs/split_chain/3GMT_A.pdb
pdbs/split_chain/4PZL_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
.    PDB has ALT records, taking A only, rm.alt=TRUE
..   PDB has ALT records, taking A only, rm.alt=TRUE
.    PDB has ALT records, taking A only, rm.alt=TRUE
.    PDB has ALT records, taking A only, rm.alt=TRUE
.    PDB has ALT records, taking A only, rm.alt=TRUE
..   PDB has ALT records, taking A only, rm.alt=TRUE
..   PDB has ALT records, taking A only, rm.alt=TRUE
....  PDB has ALT records, taking A only, rm.alt=TRUE
.    PDB has ALT records, taking A only, rm.alt=TRUE
....

```

Extracting sequences

```


pdb/seq: 1    name: pdbs/split_chain/1AKE_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 2    name: pdbs/split_chain/8BQF_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 3    name: pdbs/split_chain/4X8M_A.pdb
pdb/seq: 4    name: pdbs/split_chain/6S36_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 5    name: pdbs/split_chain/8Q2B_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 6    name: pdbs/split_chain/8RJ9_A.pdb

```


```
PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 7   name: pdbc/split_chain/6RZE_A.pdb
PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 8   name: pdbc/split_chain/4X8H_A.pdb
pdb/seq: 9   name: pdbc/split_chain/3HPR_A.pdb
PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 10  name: pdbc/split_chain/1E4V_A.pdb
pdb/seq: 11  name: pdbc/split_chain/5EJE_A.pdb
PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 12  name: pdbc/split_chain/1E4Y_A.pdb
pdb/seq: 13  name: pdbc/split_chain/3X2S_A.pdb
pdb/seq: 14  name: pdbc/split_chain/6HAP_A.pdb
pdb/seq: 15  name: pdbc/split_chain/6HAM_A.pdb
PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 16  name: pdbc/split_chain/4K46_A.pdb
PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 17  name: pdbc/split_chain/4NP6_A.pdb
pdb/seq: 18  name: pdbc/split_chain/3GMT_A.pdb
pdb/seq: 19  name: pdbc/split_chain/4PZL_A.pdb
```

Principal Component analysis

```
pc <- pca(pdbc)
plot(pc)
```

```
plot(pc, pc.axes = c(1:2))
```



To examine in more detail what PC1 (or any PC) is capturing here we can plot the loadings or make a movie (trajectory) of moving along PC1

```
mktrj(pc, pc=1, file="pc1.pdb")
```