

A: Datasheet

Algorithm: aadi_000

Developer: [**Developer name**]

Submission Date: 2023_06_27

Template size: 512 bytes

Template time (2.5 percentile): 339 msec

Template time (median): 346 msec

Template time (97.5 percentile): 353 msec

Investigation:

Frontal mugshot ranking 427 (out of 428) -- FNIR(1600000, 0, 1) = 0.9991 vs. lowest 0.0008 from intema_001

Mugshot webcam ranking 388 (out of 390) -- FNIR(1600000, 0, 1) = 1.0000 vs. lowest 0.0054 from sensetime_009

Mugshot profile ranking 358 (out of 359) -- FNIR(1600000, 0, 1) = 1.0000 vs. lowest 0.0517 from sensetime_009

Immigration visa-border ranking 314 (out of 317) -- FNIR(1600000, 0, 1) = 1.0000 vs. lowest 0.0006 from cloudwalk_mt_002

Identification:


Frontal mugshot ranking 425 (out of 428) -- FNIR(1600000, T, L+1) = 0.9998, FPIR=0.001000 vs. lowest 0.0011 from idemia_010

Mugshot webcam ranking 385 (out of 388) -- FNIR(1600000, T, L+1) = 1.0000, FPIR=0.001000 vs. lowest 0.0072 from sensetime_009


Mugshot profile ranking 353 (out of 358) -- FNIR(1600000, T, L+1) = 1.0000, FPIR=0.001000 vs. lowest 0.0634 from cloudwalk_mt_002

Immigration visa-border ranking 309 (out of 315) -- FNIR(1600000, T, L+1) = 1.0000, FPIR=0.001000 vs. lowest 0.0010 from cloudwalk_mt_002


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (verigram_000)




C: Evolution of accuracy for AADI algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images




F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate



G: FPIR dependence on T by probe type for N = 1600000 subjects




H: Reduced length candidate lists for human review
Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image




I: FNIR and FPIR dependence on threshold

Dataset is border-border with time-lapse [10,15] YRS with N = 1600000. Probes are 10-15 years later than enrollment image


False {Negative | Positive} Identification Rate




J: DET for Mugshot natural images and various N. Links connect points of equal threshold.




K: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime_009)




L: Investigational mode: FNIR(1600000, R, 0) by probe type



M: Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements. The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations




O: FNIR(T, N = 1.6 million) by sex, age and time-lapse. The top row gives investigational rank-1 miss rates. The bottom panels give high threshold for more lights-out identification with low FPIR.



P: FPIR(N = 1.6 million) by sex and age. It is typical for false positive identification rates to be higher in women except in their teens.

Algorithm: aadi_000, Dataset: Border-Crossing Ageing
Threshold: 87.482700 set to achive FPIR(30-45, Male) = 0.001



Q: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801

