

Index

Editor's Note: Except for commonly used phrases and abbreviations, topics are indexed by their noun names. Many topics are also cross-indexed. The names of software programs are italicized.

The letters "ff" after a page number indicate coverage of the indexed topic on succeeding pages.

A separate Project Index and Author Index follow the main index.

1-Wire:	14.4
<i>4nec2</i> by Arie Voors:	21.21
555 timer IC:	3.55
8-level vestigial sideband (8-VSB):	8.11
802.11 network:	4.29

A

A index:	19.12	Alternating current (AC):	2.15
<i>AADE Filter Design and Analysis</i> :	11.26	Average values:	2.20
Abbreviations list:	22.57	Frequency:	2.16
Absorption:	19.2	Fundamental:	2.16
Atmospheric:	19.23	Harmonic:	2.16
D-layer:	19.13	Instantaneous values:	2.19
MF:	19.32	Non-sinusoidal measurements:	2.21
Absorption Glass Mat, battery (AGM):	7.44	Peak and peak-to-peak values:	2.19
Absorption wavemeter:	25.10	Peak envelope power (PEP):	2.21
AC circuit models:	5.14ff	Peak power:	2.19
AC component:	25.1, 25.8	Period:	2.16
AC coupling:	3.28	Periodic waveform:	2.16
Oscilloscope:	25.11	Phase:	2.17
AC ground:	3.29	Root-mean-square (RMS):	2.20
AC measurements:	25.8	Waveform measurements:	2.21
Average:	25.8	Waveforms:	2.15
Frequency response:	25.9	Alternator:	2.16
Oscilloscope:	25.9	Alternator whine:	27.37
Peak, peak-to-peak:	25.8	Aluminum	
RMS:	25.8	Alloy types and specifications:	22.41
RMS, true-RMS:	25.8ff	Tubing sizes:	21.34
AC power:	7.2ff	AM (<i>see</i> Amplitude modulation)	
AC-DC power conversion:	7.4	Amateur Radio	
Comparison of rectifier circuits:	7.7	American Radio Relay League (ARRL):	1.1
Filter, capacitive and inductive:	7.5	Call sign:	1.6
Full-wave bridge and center-tap rectifier:	7.6	Contesting:	1.12
Half-wave rectifier:	7.5	Direction finding:	1.17
Ripple:	7.4	DXing:	1.13
AC-line filter:	27.23	Getting on the air:	1.10
Accuracy:	25.2	In the classroom:	1.19
Active filter:	3.46, 11.18ff	License:	1.5
Design tools:	11.22	Log (on-air activity):	1.9
Adaptive compression:	16.4	Mobile operating:	1.16
Adaptive filter (DSP):	15.17	Modes:	1.10
Adcock antenna:	21.68	Operating awards:	1.14
Adjacent channel rejection:	25.32	Public service:	1.18
Adjacent-channel power:	8.21	QRP (Low power operating):	1.15
Admittance (Y):	2.46	QSLs:	1.14
Advanced Circuits (PCB vendor):	6.16	Resources:	1.20
<i>Advanced Design System (ADS)</i> :	6.10	Rules and regulations:	1.2
AF (<i>see</i> Audio Frequency)		Satellites:	1.15
AGC (<i>see</i> Automatic gain control)		Study guides:	1.4
<i>Airmail</i> :	16.26	VHF, UHF, microwave:	1.16
Alias:	15.7	Amateur Radio Emergency Service (ARES):	1.18
Aliasing		Amateur television (ATV):	8.18
Digital oscilloscope:	25.13	8-VSB:	8.19
		Digital:	8.19
		DVB-S:	8.19
		NTSC channel:	8.18
		Remote sensing:	14.11
		American Radio Relay League (ARRL):	1.1, 1.6
		Ammeter:	25.2
		Ammeter, RF:	25.19, 25.45
		Ampere (A):	2.2

Ampere-hours (Ah):	2.11	Tank circuit:	17.9ff
Amplification:	3.1	Tank circuit design methods:	17.10ff
Linear:	17.2	Transmission line transformer:	17.29
Amplifier:	3.1	Troubleshooting:	26.28ff
Bode plot:	3.3	Tuning procedure:	17.14
Buffer:	3.40	VHF/UHF tank circuit:	17.13
Class:	3.29, 5.16, 17.2, 17.7ff, 17.31	Amplitude modulation (AM):	3.5, 8.3, 10.5ff
Classes of operation:	13.26	Demodulation:	10.8
Common-emitter/base/collector:	3.31, 3.32	Full-carrier, double-sideband:	13.5
Configuration:	3.29	Modulator:	13.4
Cutoff (corner) frequency:	3.5	Transmitter:	13.4
Dynamic range:	3.2	Amplitude-shift keying (ASK):	8.8
Emitter-follower (EF):	3.31	Analog (signal):	4.1
Feedback:	5.17	Analog Filter Wizard by Analog Devices:	11.22
Field-effect transistor:	3.36	Analog switches and multiplexers:	3.56
Frequency response:	3.2, 3.28	Crossover switch:	3.56
Gain:	3.2	Crosstalk:	3.56
Half-power frequency:	3.5	Analog systems:	3.27
High-frequency model:	3.29	Analog signal:	3.1
Hybrid:	13.27	Black box:	3.27
Input impedance:	3.33	Buffering:	3.29
Large-signal model:	3.29	Cascading stages:	3.28
Limiter:	3.5	Interstage loading:	3.28
Linear:	13.26ff, 17.2	Network:	3.27
Load line:	3.32	Port:	3.27
Log:	3.5	Signal processing:	3.1
Low-frequency model:	3.29	Terminology:	3.6
Microphone:	13.10	Transfer function:	3.27
Nonlinear:	13.26	Analog-digital conversion:	3.48
Operating point:	3.32	Accuracy:	3.48
Output impedance:	3.35	ADC, DAC:	3.48
QSK Controller:	24.43	Aliasing:	3.49, 15.7
Quiescent (Q) point:	3.32	Anti-aliasing filter:	15.7
Slew rate:	3.2	Band-limiting:	3.49
Small-signal model:	3.29	Bandwidth:	3.49
Stability:	3.4	Binary coded decimal (BCD):	3.48
Summing:	3.4	Bipolar and Unipolar:	3.48
TR switching:	13.32	Choosing a converter:	3.54
Transconductance:	3.6	Code:	3.48
Transmitter:	13.26ff	Conversion rate:	3.49
Vertical:	25.11	Decimation:	15.8
Wideband	25.28	Differential nonlinearity:	3.49
Amplifier, RF power:	17.1ff	Digitization:	3.48
Automatic level control (ALC):	17.25	Effective number of bits (ENOB):	3.49
Broadband transformer:	17.30	Full-scale (FS) value:	3.48
Cold tuning:	17.13	Full-scale error:	3.49
Combiners and splitters:	17.33	Hexadecimal:	3.48
Common cathode:	17.6	Integral nonlinearity (INL):	3.49
Comparison of solid state vs vacuum tube:	17.3	Interpolation:	15.9
Component ratings:	17.13ff	Jitter:	3.49
Cooling methods:	17.19ff	Least significant bit (LSB):	3.48
DC blocking capacitor:	17.17	Linearity error:	3.49
Filament voltage:	17.17	Nyquist frequency:	3.49
Grid bias:	17.18	Nyquist rate:	3.49
Grounded grid:	17.6	Nyquist Sampling Theorem:	3.49
Harmonic rejection:	17.10ff	Offset:	3.49
Impedance matching:	17.31ff	Over- and undersampling:	3.49
Mobile operation:	29.12	Percentage resolution:	3.48
MOSFET design:	17.26ff	Quantization:	15.9ff
Neutralization:	17.21	Quantization code:	3.48
Parasitic oscillation:	17.23	Quantization error:	3.49, 15.2, 15.10
Parasitic suppressor:	17.24	Range:	3.48
Pi network:	17.10	Reconstruction filter:	15.8
Pi-L network:	17.11	Resolution:	3.48, 15.2
Plate voltage:	17.17	Sample:	3.49
Protection and control circuits:	17.37	Sample rate:	15.2, 15.6ff
References:	17.50	Sampling:	15.6ff
RF choke:	17.16	Signal-to-noise and distortion ratio (SINAD):	3.49
Screen voltage:	17.18	Sinc function:	15.8
Solid state:	17.31ff	Spurious-free dynamic range (SFDR):	3.49, 15.2
Solid state HF amplifier design:	17.36ff	Step size:	3.48
Solid state, advantages:	17.31	Total harmonic distortion+noise (THD+N):	3.49
Stabilization:	17.21ff, 17.34ff	Zero-stuffing:	15.9
Surplus parts:	17.42	Analog-digital interfacing:	4.20

Analog-to-digital converter (ADC):	4.21, 15.2	Portable operation:	29.17ff
Analog and digital ground:	3.52	Quad:	21.39
Delta-encoded converters:	3.51	Radiation pattern:	21.4, 21.56
Dual-slope integrating converter:	3.51	Radiation resistance:	21.2
Flash (direct-conversion) converter:	3.50	Radio direction finding (RDF):	21.66
Input buffering and filtering:	3.52	References:	21.73
Parallel I/O interfaces:	4.20	Remotely-tuned antennas:	21.49, 21.51
Sample-and-hold (S/H):	3.51	Repeater operation (home station):	18.7
Serial I/O interfaces:	4.20	Safety:	28.13ff
Sigma-delta converter:	3.51	Safety references:	28.21
Single-ended and differential inputs:	3.52	Sense:	21.67
Successive-approximation converter (SAC):	3.50	Skeleton slot:	21.43
AND gate:	4.5	Stacking:	21.60
Anderson PowerPole:	29.6	T:	21.28
Angle modulation:	10.9ff	Temperature:	5.31
Analog signals:	8.6	Through-the-glass (mobile):	18.7
Demodulation:	10.12	Trap dipole:	21.14, 21.17
Digital signals:	8.10	Trap vertical:	21.27
Equations:	10.9	Vertical:	21.22
Quadrature detection:	10.12	VHF/UHF:	21.55ff
Transmitter:	13.6	VHF/UHF mobile:	18.7
Angle, radians and degree-radian conversion:	2.17	Whip:	21.45ff
<i>Ansoft Designer SV2</i> :	6.2	Wire strength:	22.40
Antenna		Yagi, optimized designs:	21.36
Azimuth(al) pattern:	21.4	Yagi, Yagi-Uda:	21.32ff, 21.60
Balun:	21.8, 21.38, 21.57	Zoning:	28.13
Bandwidth:	21.3	Antenna analyzer:	25.24
Coaxial dipole:	21.58	Broadcast interference:	26.33
Conductor diameter:	21.3	Antenna coupler:	20.14
Construction:	21.8	Antenna switch	
Construction, Yagi:	21.35ff	Automatic:	24.14
Current and voltage distribution:	21.2	Remote:	24.18, 24.50
Delta loop:	21.41	Antenna systems	
Dipole:	21.6ff	Troubleshooting:	26.32ff
Dipole, multiband:	20.6	Antenna tuner (ATU):	20.14
Dipole, sloping and vertical:	21.28ff	Adjusting:	20.16
Directivity:	21.1	Antenna tuner (ATU, Antenna coupler, Matchbox, Transmatch):	20.14
E- and H-field:	21.2	Balanced and unbalanced load:	20.14
Effects of ground:	21.5	Location in the antenna system:	20.15
Elevation angle:	21.5	T configuration:	20.10, 20.15
Elevation pattern:	21.4	Unbalanced-to-balanced:	20.14
Far (near) field:	21.22	Z-Match:	24.1
Feed point impedance:	21.2	Anti-VOX:	13.29
Feeding, ground-plane:	21.25	Anticyclone:	19.24
Folded dipole:	21.12, 21.57	APCO-25:	16.27
Gain:	21.1, 21.4, 21.55	Apparent power:	2.48
Glossary:	21.72	Application-specific integrated circuit (ASIC):	3.27, 15.3
Ground losses:	21.22, 21.50	APRS:	16.23
Ground systems:	21.23	Automatic Identification System (AIS):	16.24
Ground-plane:	21.22ff	Beacon:	16.23
Height above ground:	21.3	D-STAR and DPRS:	16.25
HF mobile:	21.45	Email:	16.25
Impedance matching:	21.38, 21.51	GPS:	16.23
Impedance matching at VHF/UHF:	21.56	Igate:	16.23
Installation:	28.17	Relay:	16.23
Insulators:	21.9	Secondary Station ID (SSID):	16.23
Inverted-L:	21.28	Software:	16.23
Inverted-V:	21.11	Tactical call:	16.23
Isotropic:	21.1	Tracker:	16.23
Length-to-diameter (l/d) ratio:	21.3	Winlink:	16.25
Lightning arrestor:	28.9	Arbitrary waveform generator (AWG):	25.17
Loading:	21.25, 21.47ff	Arcing:	5.10
Lobes and nulls:	21.4	Arduino:	4.23
Loop:	21.39	Arithmetic logic unit (ALU):	15.4
Loop and halyard:	28.13	Armstrong, Maj. Edwin:	12.7
Magnet (mag) mount:	18.7	ARRL:	1.1
Mast material:	28.17	RF Safety Committee:	28.22
Mobile mounting:	21.50, 21.54	Section Manager (SM):	27.2
Modeling:	21.21, 29.19	Technical Coordinator (TC):	27.2
Multiband:	21.44	Technical Information Service (TIS):	22.2
Multiband dipole:	21.13	ARRL Lab	
National Electrical Code (NEC):	28.8	Receiver test procedure:	25.29ff
Pattern ratios (F/B, F/S, F/R):	21.5	Test procedures, transmitter:	25.21
Polarization:	21.2, 21.55	Transmitter test procedure:	25.33ff

ARRL Radio Designer:	6.5
ASAPS:	19.22
ASK (<i>see</i> Amplitude-shift keying)	
Astrotex (shock mounts):	29.9
Atmosphere:	19.6
Attenuation:	3.1, 11.2
Conversion between reflection coefficient, SWR, and return loss:	22.56
Free space:	19.2
Of transmission lines:	20.4
Attenuation constant (α):	20.7
Attenuator:	3.3, 25.27
Pi- and T-network values:	22.44
ATV (<i>see</i> Amateur television)	
Audio	
Intelligibility enhancement:	24.36
Radio interface:	24.40
Audio amplifier IC:	3.56
Audio equalizer, intelligibility enhancement:	24.35
Audio equipment RFI:	27.33
Audio frequency (AF):	2.18
Audio frequency shift keying (AFSK):	8.14
Aurora:	19.14
Auroral E:	19.14
Authority having jurisdiction (AHJ):	28.2
AutoCAD:	6.3
Automatic frequency control (AFC):	9.30
Automatic gain control (AGC):	12.23ff
Circuits:	12.26
DSP-based:	15.28
Automatic level control (ALC):	13.11, 13.17, 17.2
Automatic link establishment (ALE):	16.16
FSK:	16.16
Link quality analysis (LQA):	16.16
Scanning:	16.16
Automatic noise limiter (ANL):	12.26
Automatic Packet Reporting System (APRS)	
Position data:	14.8
Remote sensing:	14.7
Telemetry:	14.7
Automatic repeat request (ARQ):	16.17
Automotive RFI:	27.36, 29.13
Alternator whine:	27.37
Electric vehicle (EV):	27.39
Hybrid-electric vehicle (HEV):	27.39
Ignition noise:	27.38
Autoranging:	25.5
Autotransformer:	2.62, 2.66
Avalanche breakdown:	3.15
Aviation headsets:	24.34

B

B2 Spice:	6.3
Back-EMF:	2.35
Background noise:	5.33
Backscatter:	19.18
Balanced modulator:	8.5, 10.30ff, 13.11
MC1496P:	10.33ff
Balun:	20.16, 21.8, 21.38, 21.57
Bazooka:	20.17
Bead:	20.24
Broadband:	20.22
Choke:	20.17ff
Coiled coaxial:	20.22
Combination ferrite and coiled coax:	20.25
Current:	5.23, 20.19ff
Current (ferrite bead) balun:	20.19
Quarter-Three-Quarter Wave (Q3Q):	20.19
Quarter-wave:	20.18
Transmitting, ferrite:	20.23
Voltage:	20.19
Wound-coax ferrite choke:	20.23
Band-stop (band-reject) filter:	11.2
Bandpass filter:	3.5, 11.2
Transmitter:	13.23

Bandwidth	
Antenna:	21.3
Communication modes:	12.9
Digital signals:	8.17
Filter:	11.3ff
Occupied:	8.21
Barkhausen criteria:	9.3
BASIC Stamp:	4.23
Battery:	7.32
Absorption Glass Mat (AGM):	7.35, 7.45
Alkaline:	7.34ff
Cold-cranking amps (CCA):	7.44
Deep-cycle:	7.35, 7.44
Discharging methods:	7.41
Handling guidelines:	7.43ff
Lead acid:	7.34ff
Lithium chemistries:	7.34ff
Marine:	7.44
NiCd:	7.34ff
NiMH:	7.34ff
Recycling:	7.44
Remote sensing:	14.9
Reserve capacity (RC):	7.44
Safety:	7.32
Starter-lights-ignition (SLI):	7.35, 7.44
Test and monitoring:	7.43
Battery charging:	7.37ff
Chargers:	7.37
From USB:	7.38
Full charge detection:	7.39
Lead acid:	7.38
Lithium chemistries:	7.40
NiCd:	7.39
NiMH:	7.40
Battery Council Institute (BCI):	7.44
Baud rate:	8.9
Bazooka (balun):	20.18
Beacon (radio propagation):	19.22
Beam antenna:	21.33
Beat frequency:	2.17
Beat frequency oscillator (BFO):	8.5, 12.2
Bermuda high:	19.26
Bessel (constant delay) filter:	11.5
Beta (current gain):	3.17, 3.31
Bias (amplifier):	3.7, 17.2
Bias point:	3.7
Quiescent (Q) point:	3.7
Bias (device), forward and reverse:	3.9
Bias Tee:	24.49
Bilateral diode switch (<i>see</i> Diac)	
Bilateral networks:	5.26
Bill of Materials (BOM):	6.17
Binary	
Number:	4.2
State:	4.3
Binary coded decimal (BCD):	3.48, 4.3
Binary phase-shift keying (BPSK):	8.11, 10.24
Bipolar junction transistor (BJT):	3.10, 3.18
Active (linear) region:	3.18
Breakdown region:	3.19
Common-emitter/base/collector:	3.19, 3.29
Current gain (β):	3.18
Cutoff region:	3.18
Dynamic emitter resistance, r_e :	3.31
Early effect:	3.19
Ebers-Moll model:	3.31
Emitter, collector, and base:	3.18
High-frequency models:	5.15
Hybrid-pi model:	3.32, 5.16
Operating parameters:	3.19
Phototransistor:	3.21
Saturation region:	3.18
Small-signal characteristics:	3.19
Specifications:	22.25
Birdies:	25.33
Bit error ratio (BER):	25.37

Bit rates	
Audio and video:	16.6
BJT (<i>see</i> Bipolar junction transistor)	
Bleeder resistor:	2.26, 7.13
High-voltage supplies:	7.29, 7.30
Blocking dynamic range (BDR):	25.30
Blocking gain compression:	12.20
Bluetooth:	4.26
BNC connector:	29.7
Boat Anchor Manual Archive:	26.14
Bode plot:	3.3
Bolometer:	25.19
Boolean	
Algebra:	4.4
Theorems:	4.6
Boost converter:	7.23
BPL (broadband over power lines):	27.5
BPSK (<i>see</i> Binary phase-shift keying)	
Branch (circuit):	2.7
Break-in (CW):	13.29
Breakdown, dielectric:	5.10
Brick wall response (filter):	11.3
Bridge	
LCR:	25.17
Wien:	25.16
Wheatstone:	25.3
Broadband noise:	27.14
Buck converter:	7.21
Critical inductance:	7.22
Buck-boost converter:	7.23
Buffer (digital), inverting and non-inverting:	4.6
Buffer amplifier	
Cascode buffer:	3.40
Darlington pair:	3.40
Emitter-follower (EF):	3.40
Source-follower:	3.40
Burden voltage:	25.6
Butterworth (maximally flat) filter response:	11.3
Bypass capacitor (RFI):	27.23
Bypassing:	5.10
Paralleling capacitors:	5.11

C

C-rate:	7.33
Cable TV, frequencies and leakage:	27.30ff
CadWeld:	28.8
Calibration (sensors):	14.4
Call sign:	1.6
Capacitance (C):	2.22
Capacitor:	2.22
AC current and voltage:	2.26
AC-rated:	27.24
Axial and radial leads:	2.30, 5.5, 22.6
Ceramic, disc and monolithic:	22.6
Charging and discharging:	2.25
Color codes, obsolete:	22.9
DC blocking:	17.17
Dielectric constant:	2.24
Dissipation factor (DF):	2.28
Effective series resistance (ESR):	2.28
EIA identification and marking:	22.10
Electrolytic, aluminum and tantalum:	22.7
Electrolytic, reforming:	26.36
Equivalent (effective) series inductance (ESL):	5.5
Film:	22.6
High-voltage:	7.29
Labeling:	22.8
Loss angle or tangent (θ):	2.28
Oil-filled:	7.29
Parasitic inductance:	5.5
Parasitic inductance model:	5.5
Poly-chlorinated biphenyls (PCB):	7.30
Ratings:	2.28
Ratings, RF power amplifier:	17.15

RC time constant (τ):	2.25
Series and parallel capacitors:	2.24
Standard values:	22.6
Temperature characteristics:	22.7
Temperature coefficient (tempco):	2.28
Types:	2.29
Voltage ratings:	22.9
Capacity (battery):	7.33
Capture effect:	8.7, 10.13
Capture range:	9.32
Carabiner:	28.15
Carrier squelch:	18.8
Carrier-current device:	27.5
Carson's rule:	8.7
Cascode buffer:	3.40
Cathode-ray tubes (CRT):	3.27
Cauer (elliptic function) filter:	11.4
Cavity resonator oscillator:	9.27
CDMA (<i>see</i> Code-division multiple access spread spectrum)	
Ceramic microphone:	13.10
Channel capacity:	8.17
Characteristic (surge) impedance (Z_0):	20.3
Characteristic curve:	3.6, 17.4ff
Charge-coupled device (CCD):	3.27
Chatter (comparator):	3.45
Chebyshev (equiripple) filter response:	11.3
Chinook wind:	19.26
Chip rate:	8.15
Chip64 and Chip128	
Spread spectrum:	16.12
Choke	
Common-mode:	27.25ff
Choke balun:	20.17ff
Chordal hop:	19.16
Circuit:	2.2
Branches and nodes:	2.7
Equivalent circuit:	2.9
Open (short) circuit:	2.2
Parallel (series) circuit:	2.2
Circuit breaker:	2.13, 7.2
Ground fault circuit interrupter (GFCI or GFI):	7.2, 28.5
Ratings:	2.13
Circuit simulation	
Component models and sources:	6.4
DC operating or bias point:	6.7
Electromagnetic:	6.13
Harmonic balance:	6.10, 6.13
Limitations at RF:	6.12
Scale factors:	6.3
Sources, voltage and current:	6.4
Switchmode power conversion:	7.28
Time and frequency domain:	6.8
Time step:	6.6
Transient:	6.8
Circular mil:	22.39
Clamping (<i>see</i> Clipping)	
Class (amplifier):	13.26, 17.2, 17.7ff, 17.31
A,B,AB,C,D,E,F:	3.29, 5.16
Efficiency:	5.17
Clipping:	3.5
Audio, speech:	13.10
Clock	
Frequency and period:	4.8
CLOVER:	16.20
Coder efficiency:	16.20
Modulation:	16.20
Phase-shift modulation (PSM):	16.20
CMOS:	3.13
Families:	4.17
Integrated circuit (IC):	4.17
Interface to TTL:	4.19
Coaxial cable (coax):	20.1
Center insulator:	20.1
Dielectric:	20.2
Hardline:	20.1

Jacket:	20.1, 20.6	Conducted emissions:	27.6
Shield:	20.1	Conduction current:	5.5
Types of:	20.6	Conductor:	2.1
Coaxial detector:	25.28	Connector:	29.6ff
Code-division multiple access spread spectrum (CDMA):	8.16	Audio:	29.6
Codec:	16.4	BNC:	22.47, 22.49
Codec2 by VK5DGR:	16.16	Coaxial, types:	22.50
Coded orthogonal frequency-division multiplexing (COFDM): ...	8.12	Computer, pinouts:	22.44
Coded squelch (repeater):	18.8	Crimp:	29.6
COFDM (<i>see</i> Coded orthogonal frequency-division multiplexing)		Data:	29.8
Cohn ladder crystal filter:	11.25	F:	22.52
Coil (<i>see</i> Inductor)		N:	22.51
Cold Cranking Amps:	7.33	PowerPole, Anderson:	29.6
Color code		RF:	29.7
AC wiring:	28.4	RJ:	29.8
Capacitor, obsolete:	22.9	Troubleshooting:	26.7
Diode:	22.16	UHF:	22.46
Inductor:	22.11	Weatherproofing:	28.18
Resistor:	22.3	Constellation diagram:	8.11, 15.24
Transformer:	22.15	Construction techniques	
Colpitts oscillator:	9.9	Circuit layout:	23.21ff
Combinational logic:	4.4ff	Common standard parts	23.15
Combiner, power:	20.21	Component mounting:	23.16
Common reference potential:	28.7	Crimping tools:	23.6
Common-base (CB) amplifier:	3.31, 3.35	Drill sizes:	23.5
Current gain:	3.35	Drilling:	23.29
Input impedance:	3.36	Electrostatic discharge (ESD):	23.14
Output impedance:	3.36	Enclosure fabrication:	23.29
Common-collector (CC) amplifier:	3.31	Ground-plane (dead-bug, ugly):	23.16
Input impedance:	3.35	High-voltage:	23.24
Output impedance:	3.35	Manhattan style:	23.18
Power gain:	3.35	Mechanical fabricatin:	23.28
Common-drain (CD) amplifier:	3.38	Metalworking:	23.28
Output impedance:	3.38	Microwave:	23.26
Common-emitter (CE) amplifier:	3.31	Nibbling tool:	23.6
AC performance:	3.35	Painting:	23.29
Fixed-bias:	3.33	Panel layout:	23.32
Frequency response:	3.35	PCB fabrication services:	23.20
Input impedance:	3.34, 3.35	Perforated board:	23.18
Output impedance:	3.34	Point-to-point:	23.16
Power gain:	3.35	Printed-circuit board (PCB):	23.20ff
Self-bias:	3.33	Recommended tools:	23.4
Voltage gain:	3.35	Socket or chassis punch:	23.6
Common-gate (CG) amplifier:	3.39	Soldering:	23.7ff
Input impedance:	3.40	Solderless breadboard or prototype board:	23.18
Output impedance:	3.40	Surface-mount technology (SMT):	23.10
Voltage gain:	3.39	Terminal and wire:	23.18
Common-mode:	27.9, 27.22	Tools:	23.3ff
Current:	20.17	Winding coils:	23.24
Common-mode rejection ratio (CMRR):	3.42	Wire-wrap:	23.18
Common-source (CS) amplifier:	3.37	Wired traces (lazy PC board):	23.18
AC performance:	3.39	Wiring:	23.24
Input impedance:	3.37	Consumer Electronics Association (CEA):	27.17
Output impedance:	3.37	Contesting (radiosport):	1.12
Self-bias:	3.39	Continuous conduction mode (CCM):	7.22
Source bypass:	3.39	Continuous tone-coded squelch system (CTCSS):	18.6ff
Source degeneration:	3.38	Tone frequencies:	18.8
Voltage gain:	3.37	Continuous wave:	9.2
Comparator		Control interface	
Hysteresis:	3.45	Audio:	24.40
Voltage:	3.44	Serial, RS-232:	24.25
Compensation		Transceiver:	24.22
Oscilloscope probe:	25.14	USB:	24.26
Compensation (frequency):	3.42	Control wiring, low-voltage:	28.6
Complex frequency:	3.3	Conventional current:	2.2
Complex loss coefficient (η):	20.7	Conversion	
Compression		Attenuation, SWR, return loss:	22.56
Audio, speech:	13.11	Degrees and radians:	2.17
Receiver dynamic range:	12.20	Power and voltage:	22.55
Compression (data):	16.4, 16.4ff	Conversion loss:	10.21
Compression (signal):	3.5	Convolution:	15.12
Computer-aided circuit design (CAD) (<i>see</i> Circuit simulation)		Cooperative agreement, utilities:	27.22
Conductance (G):	2.3	Coordination (repeater):	18.8
Leakage:	5.3	Corona discharge:	19.31, 27.21
Series and parallel:	2.8	Coronal hole:	19.12
Siemens (S):	2.3		

Coronal mass ejection (CME):	19.12	Repeater hardware:	18.13
Coulomb (C):	2.2	Station ID:	18.12
Counter		Station routing:	18.12
Flip-flops:	4.11	Texas Interconnect Team:	16.28
Coupling (inductive):	2.36	Trust server:	16.27
Courtesy tone:	18.4	D-type flip-flop:	4.10
Crimp connector:	29.6	Damping:	9.2
Critical frequency:	19.8	Darlington pair:	3.40, 7.16
Cross-reference, semiconductor:	3.8, 26.10	Pass transistor:	7.16
Crossband repeater:	14.10	Data converter:	15.2
Crosspoint switch:	3.56	Data logger:	25.5
Crosstalk:	3.56	Data sheet:	3.7
Crowbar overvoltage protection (OVP):	7.20	dBd:	21.1
CRT (oscilloscope):	25.11	dB _i :	21.1
Crystal (lattice) filter		dBm:	25.19
Superheterodyne receiver:	12.11	DC channel resistance, r_{DS} :	3.19
Equivalent circuit:	9.21	DC component:	25.1, 25.8
Crystal ladder filters		DC coupling:	3.28
Transmitter:	13.13	Oscilloscope:	25.11
Crystal, quartz		DCS (<i>see</i> Digital coded squelch)	
AT-cut:	11.23	Dead reckoning:	14.7
Characterization:	11.26	Decimation:	15.8
Equivalent (effective) series resistance (ESR):	11.23	Decoupling:	5.11
Equivalent circuit:	9.21, 11.23	Deep-cycle battery:	7.44
Fundamental:	11.23	Delta loop antenna:	21.41
Holders:	22.38	Delta match:	21.56
Oscillator:	9.19ff	Demodulator:	10.1ff
CTCSS (<i>see</i> Continuous tone-coded squelch system)		IQ:	8.12, 15.22ff
CubeSats:	14.1	DeMorgan's Theorem:	4.7
Current		Depletion region:	3.9
Conventional:	25.2	Design cycle:	6.2
Electronic:	25.2	Detection:	10.8
Current (I):	2.1	Detector	
Ampere (A):	2.2	Amplitude modulation (AM), DSP-based:	15.29
Conventional current:	2.2	Diode:	25.19
Current source:	2.9	Quadrature:	10.12
Electronic current:	2.2	Thermocouple:	25.19
Current balun:	5.23	Deviation (frequency):	8.6, 10.9
Current divider:	2.7	Measurement:	25.36
Current gain (β):	3.18	Deviation ratio:	8.6
Current inrush:	7.11	Diac:	3.10
Current shunt:	25.7	Diamagnetic:	2.31
Current transfer ratio (CTR):	3.23	Dielectric breakdown and arcing (strength):	5.10
Cutoff (corner) frequency:	3.5	Dielectric constant:	2.24
Cutoff (semiconductor):	3.11	Transmission line:	20.2, 20.8
Cutoff frequency:	11.2	Dielectric resonator oscillator:	9.28
CW		Difference amplifier:	3.44
Keying waveform:	13.2, 13.15	Differential amplifier:	3.44
Modulation:	10.6	Differential phase-shift keying (DPSK):	8.10
Transmitter:	13.15	Differential quadrature phase-shift keying (DQPSK):	8.12
Waveshaping:	8.8	Differential-mode (signal, current):	20.19, 27.9, 27.22
		Digipeater:	16.24
D		Digital (signal):	3.1, 4.1, 15.6
D layer propagation:	19.12	Digital audio	
D'Arsonval meter movement:	25.2	Audio formats:	16.3
d^* Chat:	16.29	Bit depth:	16.3
D-RATS:	16.29	Bit rate:	16.4
D-STAR:	16.27, 16.29, 18.12ff	Codec:	16.4
Backbone:	16.28	MIDI:	16.3
Call sign routing:	16.27	MP3:	16.4
d^* Chat:	16.29	Digital coded squelch (DCS):	18.8
D-RATS:	16.29	Digital data (mode):	16.1
D-STAR TV:	16.29	Automatic repeat request (ARQ):	16.2
Digital data (DD):	16.28	Baud:	16.1
Digital voice (DV):	16.28	Baudot code:	16.2
Dplus:	16.29, 18.13	Bit, bit rate (bps):	16.1
DPRS:	16.29	Bridge:	16.23
DV Dongle:	16.29	Checksum:	16.2
Ethernet bridge:	16.28	Code pages:	16.3
Gateway:	16.28	Control characters:	16.3
Hidden transmitter:	16.28	Cyclical redundancy check (CRC):	16.2
JARL:	16.27	Data rate:	16.1
Network overview:	18.11	Dibit:	16.9
References:	18.14	Emission designator:	16.1
		Encryption:	16.6

Error detection and correction:	16.2	Digital-to-analog converter (DAC):	15.2
Error-correcting code (ECC):	16.2	Binary weighting:	3.53
Forward error correction (FEC):	16.2	Current output DAC:	3.53
FSK:	16.6	Monotonicity:	3.53
Gray code:	16.10	Parallel I/O interfaces:	4.20
Gross and net bit rate:	16.1	R-2R ladder DAC:	3.53
Hybrid ARQ:	16.2	Serial I/O interfaces:	4.20
Networking modes:	16.17	Settling time:	3.53
Parity:	16.2	Summing:	3.53
Sound card:	16.5	Diode:	3.14, 22.15
Symbol, symbol rate:	16.1	AC circuit model:	5.14
Table of modes:	16.30	Anode:	3.14
Throughput (bps):	16.2	At high frequencies:	5.14
Unicode:	16.3	Cathode:	3.14
Varicode:	16.2, 16.9	Color code:	22.16
Viterbi algorithm, coding:	16.9	Dynamic resistance:	5.14
Digital downconverter (IC):	15.27	Fast-recovery:	3.15, 7.10
Digital image		Forward voltage:	3.14, 3.15
Color depth:	16.3	Free-wheeling:	7.5, 7.22
High, true color:	16.3	Package dimensions:	22.17
JPEG:	16.4	Peak Inverse Voltage (PIV, PRV):	3.15
Palette:	16.3	Photodiode:	3.21
Pixel:	16.3	PIN:	3.15
Raster:	16.3	Point-contact:	3.15
Vector:	16.3	Ratings:	3.14
Digital logic		Schottky:	3.15, 7.10
3.3 V - 5 V interface:	4.19	Specifications:	22.16
Bipolar families:	4.14	Switching time:	5.14
Combinational:	4.4ff	Transient voltage suppressor (TVS):	3.16
Comparing families of:	4.13	Vacuum tube:	17.4
Families:	22.31	Varactor:	3.16
Gates:	4.5	Zener:	3.16
Positive and negative:	4.7	Diode detector:	25.19
Programmable devices:	4.22	Diode mixer:	10.18ff
Sequential:	4.8ff	Dip (grid dip) meter:	25.10, 26.3
Transistor-transistor logic (TTL):	4.14	Diplexer:	10.22ff
Digital modulation:	8.8	<i>Diplexer Designer</i> by W4ENE:	11.41
Bit error ratio (BER):	25.37	Dipole:	21.6ff
Channel capacity:	8.17	Coaxial:	21.58
Constellation diagram:	8.11	Fan:	21.13
Packet error ratio (PER):	25.37	Folded:	21.12, 21.57
Test procedures:	25.37	Inverted-V:	21.11
Digital Radio Mondiale (DRM):	16.15	Multiband:	21.13
Slow-scan television (SSTV):	8.20	Near Vertical Incidence Skywave (NVIS):	21.14
Digital sensor interfaces:	14.4	Sloping:	21.11, 21.28ff
Digital signal processing (DSP):	15.1ff	Trap:	21.14, 21.17
Adaptive filter:	15.17	Vertical:	21.28ff
Analytic signals:	15.21ff	Direct conversion receiver:	12.12
Automatic gain control (AGC):	15.28	Direct current (dc):	2.15
Embedded systems:	15.6	Direct digital synthesis (DDS):	9.30, 15.17, 15.28
Filters:	12.12, 15.11ff	Sine-wave generator:	25.17
Finite impulse response (FIR) filter:	15.11ff	Direct FM:	10.11
Glossary:	15.32	Direct sampling:	12.2
Hilbert transformer:	15.23	Direct sequence spread spectrum (DSSS):	8.16
I/Q demodulator:	15.22ff	Direction finding:	1.17
I/Q modulator:	15.22ff	Directional coupler:	25.28
Infinite impulse response (IIR):	15.16ff	Directional wattmeter:	25.19
Microprocessors:	15.4	Directional wattmeter (<i>see also</i> Reflected power meter)	
Modulation:	15.21ff	Discharge (battery):	7.41
Modulator and demodulator:	10.14, 15.29	Discontinuous conduction mode (DCM):	7.22
References:	15.31	Displacement current:	5.5
Sine wave generation:	15.17ff	Dissipation (power):	2.11
Speech processing:	15.30	Distributed elements:	5.1
SSB modulator and demodulator:	15.22ff	Dithering:	15.10
Tone decoder:	15.19	DMM (digital multimeter):	25.4
Digital TV modulation:	8.11	Autoranging:	25.5
Digital video:	16.3	DominoEX:	16.10
Bit rate:	16.4	Doppler shift:	21.71, 25.11
Codec:	16.6	Mobile communication:	19.27
Digital voice, HF:	16.15	Double sideband (DSB):	8.4, 10.7
AOR:	16.15	Double-balanced mixer:	10.20ff
<i>Dream</i> :	16.15	Doubler (frequency):	13.7
<i>FreeDV</i> by KDØEAG and VK5DGR:	16.15	<i>Dplus</i> :	16.29
<i>WinDRM</i> by HB9TLK:	16.15	DPRS:	16.29
Digital-analog converter:	4.21	DPSK (<i>see</i> Differential phase-shift keying)	

DQPSK (<i>see</i> Differential quadrature phase-shift keying)	
<i>Dream</i> :	16.15
Drift velocity:	3.12
Driver array IC:	3.54
DSP (<i>see</i> Digital signal processing)	
DSP filter:	11.18
DTMF (<i>see</i> Dual-tone multi-frequency)	
DTV, HDTV (<i>see</i> Digital television)	
Dual-tone multi-frequency (DTMF)	
Tone frequencies:	18.8
Ducting:	19.25ff
Dummy load:	25.27, 26.3
Duplexer:	18.4
Adjustment using spectrum analyzer:	25.23
DVB-S:	8.19
DVD (Digital Video Disk) player RFI:	27.32
DXing:	1.13
Dynamic microphone:	13.10
Dynamic range:	3.2, 12.1
Blocking (BDR):	12.20
Compression (CFDR):	12.20
Intermodulation distortion (IMD):	10.14, 10.16, 25.31
Receiver:	12.19
Spectrum analyzer:	25.21
Spurious-free (SFDR):	12.21
Test procedures, receiver:	10.16
Dynamic resistance:	2.58, 5.14
E	
E layer propagation (E skip):	19.13ff
E-field:	21.2
<i>EAGLE</i> (CAD software):	6.2
Earth-Moon-Earth (EME) communication	
Propagation:	19.30
Ebers-Moll transistor model:	5.15
EchoLink:	18.10
Eddy current:	2.38, 2.65
Education	
Amateur Radio in the classroom:	1.19
Effective sunspot number (SSNe):	19.21
Efficiency (Eff, η):	2.11
EHF (frequency range classification):	2.19
EIA-RS-232:	4.28
Electret microphone:	13.10
Electric charge:	2.1
Coulombs (C):	2.2
Electric fence RFI:	27.15
Electric field	
Electromagnetic wave:	19.1
Electrostatic field:	2.22
RF exposure:	28.25
Electric vehicle (EV) RFI:	27.39
Electrical length (L_e , transmission line):	20.7
Electroluminescence:	3.23
Electromagnetic	
Radiation:	19.1
Spectrum:	19.1
Wave:	19.1
Electromagnetic compatibility (EMC):	27.1
Electromagnetic interference (EMI):	27.1
Electromotive force (EMF):	2.1
Voltage (V, E):	2.1
Electron:	2.1
Free electron:	2.1, 3.8
Mobility:	3.12
Electronic current:	2.2
Electronic design automation (EDA) (<i>see</i> Circuit simulation)	
Electrostatic discharge (ESD):	3.20
Prevention:	23.14
Elliptic-function filter:	11.4
Elmer:	1.6
<i>Elsie</i> by W4ENE:	11.9
Embedded system (DSP):	15.6
EME (Earth-Moon-Earth) communication:	1.16
Emergency communication:	1.18
Using repeaters:	18.3
Emission designators:	8.1
Table, ITU Radio Regulations:	8.2
Emitter-follower (<i>see</i> Common-collector amplifier)	
Encryption:	16.6
Energy and work:	2.2, 2.11
Ampere-hours (Ah):	2.11
Energy density:	2.11
Horsepower (hp):	2.11
Joule (J):	2.2
Potential energy:	2.22
Watt (W):	2.11
Watt-hour (Wh):	2.11
Envelope detection:	10.8
Equator, geomagnetic:	19.19
Equipment	
Arranging a station:	29.3
Interconnection:	29.5
Mobile mount:	29.9
Equivalent (effective) series inductance (ESL):	5.5
Equivalent (effective) series resistance (ESR)	
Capacitor:	2.28
Quartz crystal:	11.23
Error vector magnitude:	8.22
Error, measurement:	25.2
Ethernet:	4.25, 4.29
Bridge:	29.23
RFI:	27.14
Excess noise ratio (ENR):	25.26
Excess temperature:	5.30
<i>ExpressPCB</i> (PCB vendor):	6.16, 17.36, 17.49
Eye diagram:	8.22
<i>EZNEC</i> by W7EL:	21.21
F	
F layer propagation:	19.16ff
Facsimile (Fax):	8.19, 16.13
Formats:	16.13
Index of cooperation:	16.13
Fading	
Digital signals:	19.28
Ionospheric:	19.9
Tropospheric:	19.27
FAI:	19.14
Fair-Rite Products Corp:	5.19
Fan-out:	4.14
Farad (F):	2.23
Faraday rotation:	19.30
Fast Fourier transform (FFT):	8.14, 15.18, 16.10, 25.24
Fast-scan television (FSTV) (<i>see</i> Amateur television)	
FCC	
Basis and Purpose:	1.2
Citation:	27.22
Field Inspector:	27.22
Interference Handbook:	27.32
Notice of Apparent Liability (NAL):	27.22
RF Interference, cooperation with ARRL:	27.10
RFI:	27.2ff
FCC Part 15:	27.4
Absolute emission limits:	27.7
Certification:	27.9
Declaration of conformity:	27.9
Notification:	27.9
Operator requirements:	27.11
RFI rules and definitions:	27.8
FCC Part 18:	27.4
FCC Part 2 definitions:	27.6
FCC Part 97:	1.2, 27.2ff
Spurious emission limits:	27.4
Feed line (<i>see</i> Transmission line)	
Feed line radiation:	27.24
Feed point impedance:	20.7, 21.1
Feed-through termination:	25.28
Feedback:	3.4
Oscillator:	9.3

Field-Hell:	16.13	Digital signals:	8.17
Ferri- and ferromagnetic:	2.31	Effect of component Q:	11.9
Ferrite:	5.19	Effect of ripple:	11.10
Bead:	5.20	Family comparison:	11.5
Chokes:	5.23	Family selection:	11.15
Equivalent circuits:	5.19, 5.22	Finite impulse response (FIR):	15.11ff
Permeability:	5.19	Group delay:	11.4
Permeability vs frequency:	5.21	Helical resonator:	11.32ff
Resonances of cores:	5.20	High, Low, Band-pass:	11.2
Toroid cores:	22.14	High-pass:	3.5
Type 31 material:	5.23	Infinite impulse response (IIR):	15.16ff
Type or mix:	5.19, 22.11	Insertion loss:	11.9
Use for EMI suppression:	5.23	Intermediate frequency (IF):	12.2
Ferrite bead		Ladder:	11.6
Current balun:	20.24	Linear phase response:	11.25
FET (<i>see</i> Field-effect transistor)		Low-pass:	3.5
FFT (<i>see</i> Fast Fourier transform)		Lumped-element (LC):	11.5
Fiber optics:	3.23	Magnitude response:	11.2
Field		Mesh capacitor-coupled:	11.9
Electric (electrostatic):	2.22, 19.1	Mid-band response:	3.5
Magnetic:	2.31, 19.1	Multiple-feedback:	11.20
Field Day stub filters:	20.9	Nodal-capacitor- and -inductor-coupled:	11.8
Field programmable gate array (FPGA):	4.20, 4.22, 15.3	Normalized design values:	11.11
Field-aligned irregularities (FAD):	19.14	Normalized value tables:	11.12
Field-effect transistor (FET):	3.12, 3.18	Notch:	11.2
Breakdown region:	3.20	Order:	11.3
Channel:	3.12	Overshoot:	11.5
CMOS, NMOS, PMOS:	3.13	Passband:	3.5, 11.2
Common-source/gate/drain:	3.20, 3.37	Phase response:	11.2
Cutoff region:	3.20	Reconstruction:	15.8
DC channel resistance, r_{DS} :	3.19	Return loss:	11.11
Depletion mode:	3.13	RFI:	27.22
Enhancement mode:	3.13	Ringing:	11.5
Forward transconductance, g_m :	3.19	Ripple:	11.3
Gate leakage current, I_G :	3.19	Ripple bandwidth:	11.3
High-frequency circuit model:	5.16	Ripple-VSWR-Return Loss table:	11.10
Junction breakpoint voltage:	3.19	Rolloff:	3.5, 11.3
Junction FET (JFET):	3.12	Sallen-Key:	11.20
Mixer:	10.17ff	Scaling, frequency and impedance:	11.15
MOSFET:	3.12	Stop band:	3.5, 11.2
N-channel, P-channel:	3.12	Stop band depth and frequency:	11.4
Ohmic region:	3.20	Switched-capacitor (SCAF):	11.18ff
On resistance, $r_{DS(ON)}$:	3.12	Topology:	11.7
Operating parameters:	3.20	Transformation, high-pass to band-stop:	11.7
Phototransistor:	3.21	Transformation, low-pass to band-pass:	11.6
Pinch-off:	3.12	Transition region:	11.2
Saturation region:	3.20	Ultimate attenuation:	11.2
Small-signal model:	5.17	Use at VHF and UHF:	11.35
Source, drain, and gate:	3.12	Filter, crystal:	11.23ff
Specifications:	22.24, 22.28	Cohn minimum-loss (min-loss):	11.25
Field-strength meter (FSM):	25.37	Dishal crystal-ladder filter:	11.25
Filter:	3.4	Evaluation:	11.28
Active:	3.46	Group delay:	11.25
Active filter design tools:	11.22	Half-lattice:	11.24
Active RC:	11.18, 11.20	Insertion loss:	11.24
Adaptive (DSP):	15.17	Monolithic:	11.24
All-pass:	3.5	Motional parameters:	11.23
Anti-aliasing:	15.7	Overtone:	11.23
Band-pass:	3.5	Parallel-resonator-end-section (PRES):	11.25
Band-stop (band-reject):	11.2	Parameters:	11.24
Bandpass, transmitting:	13.23	Pole-zero separation (PZ):	11.23
Bandwidth:	11.3ff	Shape factor:	11.24
Basic types and definitions:	11.2ff	Transmitting:	13.13
Bessel (constant delay):	11.5	Unloaded Q:	11.23
Brick wall response:	11.3	Filter, surface acoustic wave (SAW):	11.28
Butterworth (maximally flat):	11.3	Filter, transmission line:	11.28
Capacitor- and inductor-input:	11.6	Band-pass:	11.30
Cauer (elliptic function):	11.4	Emulating LC filters:	11.31
Center frequency:	11.6	Hairpin resonator:	11.30
Chebyshev (equiripple):	11.3, 11.24	Interdigital:	11.30
Cutoff frequency:	11.2	Microstrip:	11.29
Denormalizing (scaling):	11.15	Quarter-wave:	11.30
Design examples:	11.11ff	Stripline:	11.29
Digital:	15.11ff	FilterPro by Texas Instruments:	11.22
Digital commutating:	10.28		

Finite impulse response (FIR) filter:	15.11ff	Fundamental overload:	27.12ff
Coefficient:	15.14	Fuse:	2.13, 7.2
Tap:	15.12	Fuse holders:	2.14
Window function:	15.13	High-voltage:	7.31
Window function equations:	15.15	Ratings:	2.13
Fire extinguisher:	29.5	G	
FireWire (IEEE-1394):	4.29	G-TOR:	16.20
Flat topping:	17.2	Golay FEC:	16.20
<i>FLDIGI</i> by W1HKJ:	16.5	Huffman A and B coding:	16.20
Flip-flop (digital):	4.9ff	GaAs FET:	3.21
Flyback converter:	7.23	Gain	
Flywheel effect:	17.9	Amplifier:	3.2, 3.6
Foldback current limiting:	7.18	Antenna:	21.1, 21.55
Forecast (propagation)	19.20ff	Noise:	5.31
Tropospheric ducting:	19.27	Voltage, current, and power:	3.2
Forward bias:	3.9	Gain-bandwidth product (F_T , GBW):	3.28, 3.42, 5.15
Forward converter:	7.25	Gallium Arsenide (GaAs):	3.12
Forward resistance:	3.9	Gamma match:	21.38, 21.57
Fourier transform:	15.18	Gap noise circuit:	27.15
Free space attenuation:	19.2	Gate (digital):	4.5
<i>FreeDV</i> by KD0EAG and VK5DGR:	16.15	Gate leakage current, I_G :	3.19
Frequencies		Gateway (D-STAR):	18.12
Beacons:	19.22	Gauss (G):	2.32
Frequency:	2.16	Gaussian filter:	8.10
Calibration:	25.11	Gaussian minimum-shift keying (GMSK):	8.10
Complex:	3.3	<i>GC Prewue</i> (CAD software):	6.24
Counters:	25.9ff	<i>gEDA</i> (CAD software):	6.2
Deviation:	8.6, 10.9	Generator, function:	25.16
Discrimination:	10.11	Generator, power:	28.5, 29.14ff
Marker generators:	25.10	Generator, signal:	25.26
Measurement:	25.10, 25.14	Generator, tracking:	25.23
Multiplier:	10.10	Generic Array Logic (GAL):	4.20, 4.22, 15.3
Frequency accuracy		Geomagnetic equator:	19.19
Receiver:	25.33	Geomagnetic storm:	19.12
Frequency coordination		<i>Gerbv</i> :	6.24
Repeater:	18.9	Germanium (device):	3.9
Frequency counter		Gilbert (Gb):	2.32
Use for troubleshooting:	26.6	Gilbert cell mixer:	10.5, 10.30ff, 10.33ff
Frequency domain:	25.20	Gin-pole:	28.15
Frequency hopping spread spectrum (FHSS):	8.15	Global Positioning System (GPS):	25.11
Frequency modulation (FM):	8.6, 10.9	Glossary	
Equipment, FM voice:	18.6	AC theory and reactance:	2.21
Receiver:	12.28ff	Amateur Radio, general terms:	1.21
Transmitter:	13.7	Analog electronic terms:	3.57
Frequency multiplier:	13.7, 13.22	Antenna:	21.72
Frequency response:	3.2, 3.28	DC and basic electricity:	2.2
AC measurement:	25.9	Digital electronics:	4.30
Measurement with noise source:	25.27	Digital modes:	16.31
Frequency shift keying (FSK):	8.10, 16.6	Digital signal processing (DSP):	15.32
Frequency stability		Filters:	11.44
Receiver:	25.33	FM and Repeater:	18.15
Frequency standard stations:	25.11	Modulation:	8.23
Frequency synthesizer		Oscillators and Synthesizers:	9.46
Automatic frequency control (AFC):	9.30	Power source:	7.45
Direct analog (DAS) and digital synthesis (DDS):	9.30	Propagation:	19.31
Fractional-N:	9.41	Radio frequency interference (RFI):	27.42
Phase noise:	9.41	Remote stations:	29.26
Phase-locked loops (PLL):	9.30ff	RF techniques:	5.36
Voltage-controlled oscillator (VCO):	9.42	Software defined radio (SDR):	15.32
Friis formula:	5.31	Test equipment and measurements:	25.55
FSK441:	16.14	Transmission lines:	20.28
Bit sequences and messages:	16.14	GMSK (<i>see</i> Gaussian minimum-shift keying)	
Meteor scatter:	16.14	GPIB:	25.6, 25.16, 25.26
Ping Jockey:	16.14	GPS:	14.7ff
Synchronization to WWV:	16.14	Sentences (data):	14.7
FSTV (<i>see</i> Amateur television)		Gray (grey) line propagation:	19.17
FTP:	16.23	Gray code:	16.10, 16.11
Full-bridge converter:	7.25	Grid (vacuum tube):	17.5
Quasi-square wave:	7.25	Bias:	17.18
Full-wave bridge, center-tap rectifier:	7.6	Control:	17.5
Output voltage:	7.6	Screen:	17.5
Voltage ratings:	7.6	Suppressor:	17.5
Function generator:	25.16ff		
Fundamental (signal):	2.16		
Fundamental diode equation:	3.9		

Grid-dip meter (GDO):	25.10
Measuring L and C:	25.17
Ground:	29.2
AC (signal) ground:	3.29
Bonding:	28.6, 28.10
Coax shields:	28.9
Cold water pipe:	28.7
Common reference potential:	28.7
Concrete encased grounding electrode (CEGR):	28.7
Conductors:	28.8, 28.10
Dissimilar metals:	28.10
Earth:	28.7
Exothermic welding (CadWeld):	28.8
Galvanizing:	28.10
Lightning dissipation:	28.7
Methods of grounding:	28.7
Radio frequency interference (RFI):	27.13
RF ground:	28.6
Safety ground:	27.13, 28.6
Single-point:	28.10
Soldering and brazing:	28.7
Star:	27.13
Ground fault circuit interrupter (GFCI or GFI):	7.2, 28.5
RFI:	27.35
Ground loop:	27.13
Ground rod:	28.7
Ground wave:	19.6
Ground-plane antenna:	21.22ff
Feeding:	21.25
Grounded grid:	17.6
Group delay (filter):	11.4
Guanella transformer:	20.20
Gummel-Poon transistor model:	5.16
Guy wire, lengths to avoid:	22.40

H

H (hybrid) parameters:	5.15, 5.35
H-field:	21.2
Half-bridge converter:	7.25
Half-power frequency:	3.5
Half-wave rectifier:	7.5
Output voltage:	7.5
Voltage ratings:	7.6
Half-wave vertical dipole (HVD):	21.11
<i>Ham Radio Deluxe</i> digital communications software:	16.13
Hamfests:	1.8
Hardware description language (HDL):	15.3
Harmful interference:	27.4, 27.6
Harmonics:	2.16
Measurement with spectrum analyzer:	25.21
RFI:	27.4, 27.12
Hartley oscillator:	9.10
Harvard architecture:	15.4
Headsets, aviation:	24.34
Heat management:	2.66
Forced-air and water cooling:	2.70
Heat pipe cooling:	2.70
Rectifiers:	2.69
RF heating:	2.69
RF power amplifier:	17.19ff
Thermoelectric cooling:	2.70
Transistor derating:	2.69
Heat sink:	2.67, 7.11
Selection:	2.67
<i>Helical</i> by W4ENE:	11.33
Helical resonator:	11.32ff
Coupling:	11.35
Design nomograph:	11.33
Insertion loss:	11.35
Tuning:	11.34
Hellschreiber:	16.12
Henry (H):	2.34
Hertz (Hz):	2.16
Heterodyne:	12.2

Hexadecimal:	3.48, 4.3
HF (frequency range classification):	2.19
h_{FE} , h_{fe} :	3.18
<i>HFTA</i> (HF Terrain Analysis):	29.20
High-pass filter:	3.5, 11.2
RFI:	27.3, 27.23
High-voltage power supply:	7.29
Bleeder resistor:	7.29, 7.30
Capacitors:	7.29
Construction techniques:	7.30, 23.24
Equalizing resistors:	7.29
Fuses:	7.31
Grounding stick (hook):	7.31, 28.12
Inductors:	7.30
Metering:	7.30
Transformers:	7.30
Hilbert transformer:	15.23
Hipot test:	7.30
Hop rate:	8.15
Horizon (radio):	19.23
Horsepower (hp):	2.11
Hot stick:	27.21
Hot, neutral, ground wiring:	7.2, 28.4
Hot-carrier diode (<i>see</i> Schottky diode)	
HP8640B generator:	25.26
HPIB:	25.6, 25.16
Huffman coding:	16.4
Hybrid combiner:	25.24
Wilkinson:	25.29
Hybrid-electric vehicle (HEV)	
Automotive RFI:	27.39
Hybrid- π transistor model:	3.31, 5.15
Hysteresis (comparator):	3.45
Hysteresis (magnetic):	2.34

I

I-V curves:	3.6
I/Q	
Demodulator:	8.12, 15.22ff
Modulator:	8.12, 15.22ff
I ² C:	14.5
IC (<i>see</i> Integrated circuit)	
ICAP4:	6.15
IEC (International Electrotechnical Commission):	27.24
IEEE-1394 (FireWire):	4.29
IEEE-488:	25.6, 25.16
IF (<i>see</i> Intermediate frequency)	
IF rejection:	25.32
Ignition noise:	27.38
Image	
Frequency:	12.4, 12.9
GIF:	16.3
Image modulation:	8.18
Image rejection:	25.32
Image response:	5.32
IMD (<i>see</i> Intermodulation distortion)	
Immunity, RF:	27.4, 27.9
Impedance (Z):	2.44
Antenna:	21.2
Calculating from R and X:	2.46
Equivalent series and parallel circuits:	2.47
Graphical representation:	2.44
Mobile antenna:	21.50
Ohm's law for impedances:	2.47
Phase angle:	2.44
Polar form:	2.45
Polar-rectangular conversion:	2.45
Power factor:	2.48
Reactive power (VA):	2.48
Rectangular form:	2.44
Impedance inversion, π networks:	5.26
Impedance matching:	5.24ff
Antenna to transmission line:	20.11
Antennas:	21.56

Conjugate matching:	20.10	NMOS:	4.16
L network:	5.24, 20.10ff	Parasitic SCR:	3.27
Network:	20.10	PMOS:	4.16
Pi network:	5.26, 17.10, 20.10	Programmable-gate arrays (PGA):	3.27
Pi-L network:	17.11	Transistor-transistor logic (TTL):	4.14
Quarter-wave (Q) section:	20.12	Integrated circuits (linear):	3.24
Resonating the antenna:	20.12	Hybrid circuits:	3.24
Series- and shunt-input circuits:	20.10	Monolithic:	3.26
Solid state amplifier:	17.31ff	Silicon-on-sapphire (SOS):	3.26
Switching:	24.11	Substrate:	3.26
T network:	5.26, 20.10ff, 20.15	Intentional emitters:	27.5
Transformer:	20.12, 21.57	Inter-IC Communication (I2C) bus:	4.20
Transmission line:	20.10, 20.13	Inter-symbol interference:	8.10, 8.17, 19.29
Twelfth-wave transformer:	20.13	Intercept point (IP):	10.15, 10.16, 25.31
Vertical antenna:	24.9	Receiver:	12.21
Impedance matching unit (<i>see</i> Antenna Tuner)		Interface	
Impedance transformer		Analog-digital:	4.20
Transmission line:	20.19ff	Between logic families:	4.18
Incidental emitters:	27.5	Bluetooth:	4.26
Independent sideband (ISB):	10.7	Digital to analog I/O:	4.19
Indirect FM:	10.11	Ethernet:	4.25
Inductance (L):	2.34	High voltage equipment:	29.8
Air core formula:	2.51	Microcontroller:	4.22
Henry (H):	2.34	Microcontroller I/O:	4.21
Induced voltage (back-voltage):	2.34	PC parallel (LPT) port:	4.24
Mutual inductance (M):	2.36	PC serial (COM) port:	4.24
Straight wires:	2.52	Personal computer:	4.27ff
Inductance index (A_L):	2.53	RS-232:	4.25
Inductor:	2.31	USB:	4.25
AC current and voltage:	2.38	WiFi:	4.26
Air core:	2.50	Zigbee:	4.26
Air gap:	2.35	Interference (<i>see</i> Electromagnetic interference)	
At radio frequencies:	5.6	Intermediate frequency (IF):	12.2
Color code:	22.11	Speech clipping:	13.13
Coupling:	2.36	Intermodulation distortion (IMD):	8.20, 10.4, 12.20
Eddy current:	2.38	Dynamic range:	10.14, 10.16, 12.20
Effects of coupling:	5.7	Dynamic range test procedures:	10.16
Effects of shielded enclosures:	5.7	Identifying:	27.16
Encapsulated:	2.49	Measurement:	25.31ff
Energizing and de-energizing:	2.38	Products:	12.20
Ferrite toroid cores:	22.14	RFI:	27.4, 27.12ff
Ferrite toroidal:	2.54	Spectrum analyzer:	25.21
High-voltage:	7.30	Internal impedance	
Inductance index (A_L):	2.53	Voltage and current sources:	2.9
Iron core:	2.53	International power standards:	28.4
Kick-back:	2.37	Internet Radio Linking Project (IRLP):	18.10
Laminations:	2.38	Interpolation:	15.9
Machine-wound coil specifications:	22.42	Inverse FFT:	8.14
Parasitic capacitance:	5.6	Inversion:	19.24
Powdered-iron toroid cores:	2.53, 22.12	Inverted-L antenna:	21.28
Ratings, RF power amplifier:	17.15	Inverted-V antenna:	21.11
RL time constant (τ):	2.36	Inverter (digital):	4.6
Saturation:	2.35	Inverters, dc-ac:	7.44
Series and parallel:	2.36	Sine-wave output:	7.44
Series resistance:	5.6	Square-wave output:	7.44
Slug-tuned:	2.53	Volt-ampere (VA) product, rating:	7.44
Standard values:	22.11	Inverting amplifier:	3.43
Swinging choke:	7.14	Ion:	2.1
Infinite impulse response (IIR) filter:	15.16ff, 15.17	IONCAP:	19.22
Insertion loss (filter):	11.9	Ionogram:	19.8
Insertion loss (IL):	5.13	Ionosonde:	19.8
Instrumentation amplifier:	3.44	Ionosphere:	19.7ff
Insulated-gate FET (<i>see</i> MOSFET)		Ionospheric	
Insulator:	2.1	Fading:	19.9
Antenna:	21.9	Forward scatter:	19.2
Integrated circuit (IC):	22.18	Refraction:	19.7
Application-specific IC (ASIC):	3.27	IR drop (<i>see</i> Voltage, Voltage drop)	
Bipolar families:	4.14	ISM (Industrial, Scientific, Medical):	27.4
CMOS:	4.16	Isolation	
Comparing logic families:	4.13	Summing amplifier:	3.4
Digital:	4.13ff	Isotropic:	21.1
Latch-up:	3.27	Isotropic path loss:	5.33
Metal-oxide semiconductor (MOS):	4.16	ITU emission designators:	8.2
Mixer:	10.30ff		

J

J-K flip-flop:	4.10
Johnson, Johnson-Nyquist noise:	5.30
Joules (J):	2.2
JPEG compression:	16.4
JT65:	16.14
Data compression:	16.14
Earth-moon-earth (EME):	16.14
Reed-Solomon code:	16.15
Synchronization:	16.15
JT6M:	16.14
FSK, 44-tone:	16.14
Ping Jockey:	16.14
WSJT:	16.14
Junction FET (JFET):	3.12

K

K index:	19.12
Kelvin, Lord (<i>see</i> Thompson, Sir William)	
Key click:	8.7, 10.7, 13.2, 26.18
Keyer, miniature, TiCK-4:	24.31
Keying interface, universal:	24.29
Keying, CW waveform:	10.7, 13.2
Kicad (CAD software):	6.2
Kirchoff's Current Law (KCL):	2.7
Kirchoff's Voltage Law (KVL):	2.7
Kit, transceiver:	13.32
Klystron:	9.29
Knife-edge diffraction:	19.2

L

L network:	5.24, 20.10ff
Ladder (filter):	11.6
Lagging (leading)	
Power factor:	2.49
Large-signal model:	3.29
Laser diode:	3.23
Lasing current:	3.23
Monochromatic light:	3.23
Latch-up:	3.27
Lead acid battery	7.32ff
Charging:	7.38
Leakage current:	7.29
Leakage flux:	2.64
Leakage path:	5.10
Leakage reactance:	2.65
Least significant bit (LSB):	3.48
Level converter:	29.9
LF (frequency range classification):	2.19
Licensing:	1.5
Light-emitting diode (LED):	3.23
Circuit design:	3.23
Electroluminescence:	3.23
Lightning (source of noise):	19.31
Lightning protection	
Cable entrance panel:	28.10
Lightning arrester:	28.9
Suppliers:	28.10
Limiter (amplifier):	3.5, 8.7
Limiting:	3.5
Line loss:	20.4
Line of sight propagation:	19.22
Linear (system):	3.1
Linear amplifier:	13.26ff, 17.2
Liquid-crystal displays (LCD):	3.27
Lithium-ion battery	
Charging:	7.40
Litz wire:	2.50, 5.6
Loading (antenna):	21.25
Lock range:	9.32
Log (logarithmic) amplifier:	3.47
Log (on-air activity):	1.9

Logbook of The World (LoTW):	1.14
Logic analyzer:	25.36
Logic probe:	25.36
Logic-gate oscillator:	9.26
Logical operations:	4.5ff
Long-path propagation:	19.17
Loop antenna:	21.39
Loss	
Filter insertion loss:	5.13
Loss angle or tangent (θ):	2.28
Losses (radiative):	5.10
Lossless and lossy compression:	16.4
Low-pass filter:	3.5, 11.2
DC motors:	27.37
RFI:	27.3, 27.23
Telephone RFI:	27.33
Lowest usable frequency (LUF):	19.9
LTSpice by Linear Technologies:	6.2, 17.11
LUF:	19.9
Lumped elements:	5.1
Lumped-element (LC) filter:	11.5
LZW compression:	16.4

M

M-factor:	19.9
Macros:	16.5
Magnetic circuit analogies:	2.32
Magnetic field:	2.31
Electromagnetic wave:	19.1
Gauss (G):	2.32
Hysteresis:	2.34
Magnetic field strength (H):	2.32
Magnetic flux:	2.32
Magnetic flux density (ϕ):	2.32
Magnetic flux linkage:	2.34
Magnetomotive force (MMF, \Im):	2.32
Mean magnetic path length:	2.32
Oersted (Oe):	2.32
Permeability (μ):	2.32
RF exposure:	28.25
Right-hand rule:	2.32
Saturation:	2.33
Tesla (T):	2.32
Magnetic flux	
Maxwell (Mx):	2.32
Weber (Wb):	2.32
Magnetism:	2.31
Magnetometer:	19.12
Magnetomotive force (MMF, \Im):	2.32
Reluctance (\Re):	2.33
Magnetosphere:	19.6
Magnetron:	9.29
Magnitude response (filter):	11.2
Manuals, equipment:	26.14
Marine battery:	7.44
Marine layer:	19.26
Marker generator:	25.10
Master-slave flip-flop:	4.10
MATCH by WØIYH:	20.11
Matchbox (<i>see</i> Antenna Tuner)	
Maunder minimum:	19.10
Maxim, Hiram Percy:	1.1
Maximum usable frequency (MUF):	19.8
Prediction:	19.20ff
Maxwell (Mx):	2.32
Megger:	7.30
MESFET:	3.21
Metal-oxide semiconductor (MOS)	
Integrated circuit (IC):	4.16
Metal-oxide varistor (MOV)	
Specifications:	22.37
Meteor	
Scatter:	19.15
Shower:	19.16

Meter	
Digital panel (DPM):	25.7
Internal resistance	25.3
Panel:	25.6
Protection diodes:	25.7
Resistance:	25.6
Scales:	25.7
Shunt	25.5
<i>MeterBasic</i> by W4ENE:	17.49, 25.7
Method of moments:	21.21
Metric units:	22.54
MF propagation:	19.32
MF (frequency range classification):	2.19
MFSK (<i>see</i> Multi-level FSK)	
<i>MICROCAP9</i> :	6.15
Microcontroller:	4.23ff
CPU size:	4.24
Development tools:	4.25
FLASH memory:	4.26
I/O:	4.21
I/O requirements:	4.24
Interfacing:	4.22
Memory:	4.24
Peripherals:	4.24
Programming:	4.25
Resources:	4.26
Selecting:	4.24
Microphone	
Amplifier:	13.10
Types of:	13.10
Microprocessor:	15.4
Microstrip:	11.29
Microwave	
Construction techniques:	23.26
Microwave band designations:	25.28
Microwire:	4.20, 4.21, 14.5
Military Auxiliary Radio Service (MARS):	1.19
Minimum discernable signal (MDS):	25.21, 25.29
Minimum-shift keying (MSK):	8.10
Mirror scale, meter:	25.6
Mix (ferrite):	2.53, 5.19
Mix, Tom ITS:	14.1
Mixer:	10.1ff
Diode:	10.18ff
Diplexer:	10.22
Double-balanced:	10.20ff
Dynamic range:	10.14ff
Equations:	10.3
FET:	10.17ff
Gain controlled amplifier:	10.16ff
Gilbert cell:	10.26ff
Image:	12.4
Image-rejecting:	12.12
MOSFET:	19.29
NE602/SA602/SA612:	10.30ff
Nonlinear signal combinations:	12.3
References:	10.35
Switching:	10.18ff
Tayloe:	10.28ff
Transistor:	10.24ff
Mixing products:	10.4
<i>MixW</i> digital communications software:	16.12
Mobile	
Antenna impedance matching:	21.50
Antenna routing:	21.50, 21.54
Antennas (HF):	21.45
Antennas (VHF/UHF):	21.54
Ground losses:	21.50
Impedance matching:	21.51
Remotely-tuned antennas:	21.49, 21.51
SSB and CW antennas at VHF/UHF:	21.54
Mobile operation:	29.9ff
Air bags:	29.11
Amplifiers:	29.12
Automotive interference:	29.13
Cables and wiring:	29.10ff
Mounts, control head:	29.10
Operating techniques:	29.14
RFI:	27.36
Shock mounts:	29.9
VHF/UHF propagation:	19.27ff
Mode (digital):	16.1ff
Modem:	16.17
Modes:	8.1ff
Typical bandwidths:	12.9
Modulation:	8.1ff
Accuracy:	8.21
Amplitude (AM):	3.5, 8.3, 10.5ff
Amplitude-shift keying (ASK):	8.8
Analog:	8.3ff
Angle:	8.6ff, 10.9ff
Continuous wave (CW):	8.8, 10.6
Digital:	8.7
Digital signal processing (DSP):	15.21ff
Double sideband (DSB):	8.4
Frequency (FM):	8.6
Image:	8.18
Impairments:	8.20ff
Linearity:	10.6
Multi-carrier:	8.13
On-off keying (OOK):	8.8
Phase (PM):	8.6
Products:	3.5
Pulse:	8.9
Quadrature:	8.11ff
Single sideband (SSB):	8.5
Transmitter:	13.24
Modulation index	
AM:	8.3
FM:	8.6
Modulation percentage	
Measurement:	25.36
Modulator:	10.1ff, 10.35
Balanced:	8.5, 13.11
Balanced, MC1496:	10.33ff
IQ:	8.12, 15.22ff
Molex connector:	29.6
Monolithic microwave IC (MMIC)	
Specifications:	22.22
Monopole:	21.22
Monte Carlo analysis:	6.1
Moonbounce (<i>see</i> Earth-Moon-Earth (EME) communication)	
Morse code:	8.8
MOSFET:	3.12, 3.20
Depletion mode:	3.21
Electrostatic discharge (ESD):	3.21
Enhancement mode:	3.21
Pass transistor:	7.17
Power:	3.21
MOSFET, RF Power	
Data sheet parameters and ratings:	17.28
Gate structures:	17.26
LDMOS vs VDMOS:	17.27
RF power amplifier design:	17.26ff
Thermal design:	17.28
Transfer characteristics:	17.30
Voltage ratings:	17.27
MP3 compression:	16.4
MSFK16:	16.9
Convolution code:	16.10
Fast Fourier Transform (FFT):	16.11
Gray code:	16.10
Hamming distance:	16.11
Interleaver:	16.10
Modulation:	16.11
Quadbit, nibble:	16.10
MSK (<i>see</i> Minimum-shift keying)	
MT63:	16.12
Error-correction:	16.12
Latency:	16.12

Navy MARS:	16.12
Noise immunity:	16.12
Tuning error:	16.12
Walsh function:	16.12
MUF (<i>see</i> Maximum usable frequency)	
Multi-level FSK (MFSK):	8.10
Multi-protocol controller (MPC):	16.17
Multimeter:	25.3
Input impedance:	25.6
Specifications:	25.5
Use of:	25.5
Used and surplus:	25.6
Multimode communications processor (MCP):	16.17
Multipath propagation:	19.28
Multiplexer, frequency:	13.7, 13.22
MultiPSK:	16.13
Multivibrator:	4.12
Astable (free-running):	4.13
Bistable:	4.12
Monostable (one-shot):	4.12
Mutual inductance (M):	2.36, 2.62

N

N connector:	29.7
NAND gate:	4.5
Narrowband and wideband FM:	8.6
Narrowband noise:	27.14
National Bureau of Standards (NBS):	25.1
National Electrical Code (NEC):	28.2
Antennas:	28.8
National Institute of Standards and Testing (NIST):	25.1
National Recognized Testing Laboratories (NRTL):	28.2
National Traffic System (NTS):	1.19
Navigation data:	14.7
NE602/SA602/SA612 mixer:	10.30ff
Near field:	25.37
Near-vertical incidence skywave (NVIS):	19.9, 21.14
NEC modeling engine:	21.21
Negative resistance:	9.4
Neper:	20.7
Netlist:	6.6, 6.17
Network	
Wireless:	4.29
Network analyzer:	25.25ff
Neutralization:	17.21
NiCd battery	
Charging:	7.39
NiMH battery	
Charging:	7.40
NIST:	25.1
NIST traceable standard:	25.1
Node (circuit):	2.7
Noise:	5.30ff
Atmospheric:	12.17
Background:	5.33
Bandwidth:	12.17
Broadband:	27.14
Cosmic:	19.31
Effects on receivers:	12.17
Factor (F) or Figure (NF):	3.28
Friis formula:	5.31
From losses:	5.31
Gain:	5.31
Galactic:	12.17
Gap noise:	27.15
Generator, use in transmission line measurements:	20.9
Ignition:	27.38
Image response:	5.32
Immunity (digital IC):	4.14
Johnson noise:	3.28
Johnson, Johnson-Nyquist:	5.30
Man-made:	12.17, 19.30
Narrowband:	27.14
Noise blanker (NB):	12.27

Noise limiter (ANL, NL):	12.26
Of cascaded amplifiers:	5.31
Of preamplifiers:	5.32
Phase noise:	12.17
Power:	5.30, 12.18
Pulse noise:	12.26
Signal-to-noise ratio (SNR):	3.28
Simulation:	5.17
Sun:	5.32
Temperature:	5.30
Thermal:	12.17
Thermal noise:	3.28
White:	5.30
Wideband, transmitting:	13.16
Noise bandwidth:	25.30
Noise factor (F):	3.28, 5.31
Noise figure (NF):	3.28, 5.31, 12.18, 25.30
Measuring:	25.26
Relationship to noise temperature:	22.43
Noise floor:	12.1
Noise reduction	
Noise reduction (NR)	
DSP:	12.28
Pulse noise:	12.26
Noise source:	25.26
Noise temperature	
Relationship to noise figure:	22.43
Nominal value:	2.4, 22.2
Non-inverting amplifier:	3.43
Non-linear junction:	27.16
NOR gate:	4.5
Northern California DX Foundation (NCDXF):	19.21
Norton equivalent circuit:	2.10
Norton's Theorem:	2.10
Notch filter:	11.2
NTSC (analog TV):	8.18
Number systems:	4.2ff
Binary:	4.2
Binary coded decimal (BCD):	4.3
Conversion techniques:	4.3
Hexadecimal:	4.3
Numerically controlled oscillator (NCO):	15.17
NVIS (<i>see</i> Near-vertical incidence skywave)	
Nyquist	
Criterion:	8.10, 15.6ff
Frequency:	3.49, 8.10, 15.6ff
Rate:	3.49, 15.6ff
Nyquist filter:	8.17
Nyquist sampling theorem:	3.49

O

O wave:	19.9
Occupied bandwidth:	8.21
Oersted (Oe):	2.32
OFDM (<i>see</i> Orthogonal frequency-division multiplexing)	
Off-center fed dipole:	21.7
Offset quadrature phase-shift keying (OQPSK):	8.12
Ohm (Ω):	2.3
Ohm's law:	2.3
Power formulas:	2.12
Ohmmeter:	25.3
Oil-filled capacitor:	7.29
Olivia:	16.12
MFSK:	16.12
Orthogonal tones:	16.12
On-off keying (OOK):	8.8, 13.2
Open-collector output:	3.45
Open-wire line:	21.7
Operational amplifier (op-amp):	3.42
Active filter:	3.46
Common-mode rejection ratio (CMRR):	3.42
Comparator:	3.44
Compensation (frequency):	3.42
Difference amplifier:	3.44

Differential amplifier:	3.44	OSI networking model:	16.17
Gain:	3.42	Layers:	16.17
Gain-bandwidth product (F_T , GBW):	3.42	Protocol stack:	16.17
Input and output impedance:	3.42	Out-of-band emissions:	27.4
Input bias current:	3.42	Overmodulation:	10.5
Input offset voltage:	3.42	Overshoot:	11.5
Instrumentation amplifier:	3.44	Ozonosphere:	19.6
Inverting and non-inverting amplifier:	3.43		
Log amplifier:	3.47	P	
Open-loop gain:	3.42	P25:	16.29
Peak detector:	3.47	APCO-25:	16.29
Power-supply rejection ratio (PSRR):	3.42	Continuous 4-level FM (C4FM):	16.29
Rail-to-rail:	3.42	Improved MultiBand Excitation (IMBE):	16.29
Rectifier circuit:	3.46	Tetra:	16.29
Specifications:	22.32	Packet error ratio (PER):	25.37
Summing amplifier:	3.44	Packet radio (AX.25):	16.23
Summing junction:	3.43	APRS:	16.24
Transimpedance:	14.3	Cluster:	16.23
Unity-gain buffer:	3.44	Digipeater:	16.24
Use of feedback:	3.43	FTP:	16.24
Virtual ground:	3.43	KISS:	16.24
Voltage-current converter:	3.47	Packet bulletin-board systems (PBBS):	16.23
Voltage-follower circuit:	3.43, 3.44	TCP/IP:	16.24
Optoisolator:	3.23, 4.20	TNC interface:	16.23
Circuit design:	3.23	PACTOR:	16.18
Current transfer ratio (CTR):	3.23	Contact flow:	16.18
OR gate:	4.5	Link establishment:	16.18
Order (filter):	11.3	PACTOR-I, -II, -III:	16.18
Orthogonal frequency-division multiplexing (OFDM):	8.13	PACTOR-III link establishment:	16.19
Oscillation:	3.4	Speed comparison:	16.18
Oscillator		Panadapter:	25.24
Active device selection:	9.17	Parallel I/O interface:	4.20, 4.27ff
Audio frequency:	25.16ff	Parallel-bridge converter:	7.25
Capacitor selection:	9.15	Paramagnetic:	2.31
Cavity resonator oscillator:	9.28	Parasitic:	5.1
Crystal:	9.19ff	Capacitance (stray):	5.3, 5.5
Crystal circuits:	9.22ff	Capacitance of inductors:	5.6
Crystal test:	11.27	Effect on filter performance:	5.13
Dielectric resonator oscillator:	9.28	Effect on Q:	5.8
Disciplined:	25.11	Effects of parasitic characteristics:	5.3
Feedback loop:	9.3	General component model:	5.3
Inductor selection:	9.17	Inductance:	5.3, 5.17
LC circuits:	9.9ff	Inductance of capacitors:	5.5
Logic-gate oscillator:	9.26	Inductance of resistors:	5.4
Negative resistance:	9.4	Inductance per inch of wire:	5.3
Numerically controlled (NCO):	15.17	Inter-electrode capacitance:	5.6
Phase noise:	9.5ff, 12.17	Leakage conductance:	5.3
RC circuits:	9.11	Oscillation:	17.23, 17.34
Resonator:	9.3	Package capacitance:	5.6
Shielding:	9.19	Parasitic SCR:	3.27
Start-up:	9.4	Radiative losses:	5.10
Temperature compensation:	9.18	Resistance:	5.3
Transmitter:	13.22	Self-resonance:	5.9
Troubleshooting:	26.24	Parasitic suppressor:	17.24, 17.32
Twin-T, audio:	25.16	Parasitics (oscillation):	27.4, 27.12
UHF and above:	9.26	Part 15 devices:	27.4
Variable crystal oscillator (VXO):	9.25	Part 18 devices:	27.4
VFO construction:	9.15ff	Passband (filter):	11.2
Wien bridge:	25.16	PC board material, FR-4:	6.17
YIG-tuned oscillator:	9.28	PC board construction:	23.20ff
Oscillators and Synthesizers		PC board layout:	6.15ff
Glossary:	9.46	Annotation, forward and backward:	6.17
References:	9.47	Annular ring:	6.18
Oscilloscope:	25.11ff	Auto-placement:	6.20
AC measurement:	25.9	Auto-router (autorouting):	6.22
Analog:	25.11	Bill of Materials (BOM):	6.17
Buying used:	25.16	Board house:	6.17
Digital:	25.13	Component and solder sides:	6.17
Dual-trace:	25.12	Component footprint:	6.16
Features and specifications:	25.15ff	Copper fill:	6.23
Probes:	25.14	Design Rule Check (DRC):	6.23
Rise time and bandwidth:	25.13	Double- and multi-layer:	6.17
Use for troubleshooting:	26.4	Drill file:	6.24
Use of:	25.14ff	Excellon file:	6.24
X-Y mode:	25.13		

Gerber file (RS-274X):	6.23	Photovoltaic cell:	3.22
Net:	6.16	Conversion efficiency:	3.23
Netlist:	6.17	Open-circuit, V_{OC} , or terminal, V_T , voltage:	3.22
Panelizing:	6.18	Photovoltaic potential:	3.22
Photoplotter:	6.24	Short-circuit current, I_{SC} :	3.23
Plated-through hole:	6.17	Solar panel:	3.23
RF interference:	6.22	Pi network:	5.26, 20.10
Routing (traces):	6.20	Impedance inversion:	5.26
Silkscreen:	6.18	RF power amplifier:	17.10
Software:	6.15ff	<i>PI-EL Design</i> by W4ENE:	17.10
Solder mask:	6.18	Pi-L network	
Surface-mount component:	6.17	Component selection:	17.11
Symbol library:	6.16	RF power amplifier:	17.10
Through-hole component:	6.17	Table of values:	17.12
Tin plating:	6.18	PICAXE:	4.23
Trace current limits:	6.23	Picket fencing:	19.28
PCB fabrication services:	6.17ff	Piezoelectric effect:	9.19
Peak and peak-to-peak values:	2.19	Pilot carrier:	13.8
Peak detection:	3.5	PIN diode:	3.15
Peak detector:	3.47	Pinch-off:	3.12
Peak envelope power (PEP):	2.21, 25.19	Pinouts:	3.7
Peak inverse voltage (PIV, PRV):	3.15, 7.11	PL-259 connector:	29.7
Peak power:	2.19	Plasma frequency:	19.8
Peak surge current, I_{SURGE} :	7.11	Plastic	
Pedersen ray:	19.16	Repair and restoration:	26.38
Peltier effect:	2.70	PN junction:	3.8
Pentode:	17.5	Anode:	3.9
Performance requirements:	3.31, 6.2, 11.11	Barrier (threshold) voltage:	3.9
Period:	2.16	Cathode:	3.9
Permeability (μ):	2.32	Depletion region:	3.9
Ferrite:	5.19	Forward resistance:	3.9
Of magnetic materials:	2.33	Forward voltage drop:	3.10
Phase:	2.17	Fundamental diode equation:	3.9
Lag and lead:	2.17	Junction capacitance:	3.15
Phase shift:	3.3	Recombination:	3.8
Phase angle (impedance):	2.44	Response speed, recovery time:	3.15
Phase constant (β):	20.7	Reverse breakdown voltage:	3.15
Phase detector:	9.31, 9.35	Reverse leakage current:	3.9, 3.15
Phase modulation (PM):	8.6, 10.9	Reverse-bias saturation current, I_S :	3.10, 3.15
Transmitter:	13.8	PNPN Diode:	3.10
Phase noise:	9.5ff, 12.17	Point-contact diode:	3.15
Frequency synthesizer:	9.41	Polar cap absorption (PCA):	19.12
Measurement:	9.6	Polarity (phase):	2.17
Reciprocal mixing:	9.7	Polarity (voltage):	2.1
Transmitted:	9.8	Polarization	
Phase response (filter):	11.2	Antenna:	21.2, 21.55
Phase-locked loops (PLL):	9.30ff	Circular:	21.56
Capture range:	9.32	Radio wave:	19.9
Charge pump:	9.36	Pole (transfer function):	3.4, 11.20, 11.23
Demodulator:	10.13	Port, electronic:	25.24
Dynamic stability:	9.33	Portable operation:	29.14ff
Frequency resolution (step size):	9.33	Antennas:	29.17ff
Lock range:	9.32	Power sources:	29.14ff
Loop bandwidth:	9.31, 9.33	Potentiometer:	2.6
Loop filter:	9.32, 9.39ff	Taper (log, audio):	2.6
Measurement and troubleshooting:	9.44	Powdered-iron core:	22.12
Modulator:	10.11	Power:	2.11
Noise:	9.33	Horsepower (hp):	2.11
Phase (frequency) detector:	9.35	Joule (J):	2.2
Phase detector:	9.31	Station:	29.2
Prescaling:	9.38	Watt (W):	2.11
Reference oscillator:	9.32, 9.39ff	Watt-hour (Wh):	2.11
Voltage-controlled oscillator (VCO):	9.32	Power density	
Phased array:	21.68	Spectral:	5.30
Phasing line:	20.12	Power divider:	25.29
Phasing method (SSB generation):	8.5, 12.12, 13.6	Power factor:	2.48
Phasor diagram:	15.22	AC measurement:	25.8
Photoconductivity:	3.21	Power filtering	
Photoconductor:	3.8, 3.21	Bleeder resistor:	7.12
Photodiode:	3.21	Capacitor-input:	7.13
Photoelectricity:	3.22	Choke inductor constant (A):	7.14
Photoisolator (<i>see</i> Optoisolator)		Choke-input:	7.14
Photoresistor:	3.22	Swinging choke:	7.14
Phototransistor:	3.22	Power strip load rating:	28.2
Optoisolator:	3.23		

Power supply.....	7.1ff	Multicast:	16.17
Fault symptoms:	26.22	P25:	16.29
Use for troubleshooting:	26.5	Packet radio (AX.25):	16.23
Power supply regulation:	7.12	PACTOR:	16.18ff
Crowbar OVP circuit:	7.20	RMS:	16.26
Foldback current limiting:	7.18	SMTP:	16.24
Linear regulator:	7.16	Stack:	16.17
Load resistance:	7.12	TCP/IP:	16.17, 16.24
MOSFET:	7.17	TELNET:	16.24, 16.26
Over-voltage protection (OVP):	7.20	Terminal node controller (TNC):	16.17
Overcurrent protection:	7.17	UDP:	16.17
Pass transistor:	7.16	Unicast (point to point):	16.17
Pass transistor power dissipation:	7.16	WINMOR:	16.22
Remote sensing:	7.16	PSK31:	16.8
Series and shunt regulator:	7.15	BPSK, QPSK:	16.9
Three-terminal voltage regulator:	7.18	Convolution code:	16.9
Voltage regulation:	7.12	Dibit:	16.9
Zener diode regulator:	7.15	Envelope modulation:	16.9
Power-line noise:	27.15, 27.18ff	Phase-shift modulation:	16.9
Cooperative agreement:	27.22	PSK63, PSK125:	16.9
Corona discharge:	27.21	Varicode:	16.9
Noise-locating equipment:	27.19	Viterbi algorithm:	16.9
Signature or fingerprint:	27.20	PSPICE:	6.14
Ultrasonic location:	27.19	Public service:	1.18
Utility complaint:	27.18	Public-address equipment RFI:	27.34
PowerPole, Anderson:	29.6	Pull-up resistor:	3.45
Powerstat (transformer):	2.66	Pulse modulation:	8.9
Preamplifier:	12.18	Pulse noise reduction:	12.26
Noise:	5.32	Pulse-amplitude modulation (PAM):	8.10
Precipitation static:	19.31	Pulse-position modulation (PPM):	8.10
Precision (value):	2.4	Pulse-width modulation (PWM):	8.10
Precision rectifier circuit:	3.46	Switchmode power conversion:	7.22, 7.26
Precision resistor:	2.4, 22.2	Push-to-talk (PTT):	13.29
Prescaler:	9.38, 25.9		
Preselector:	11.1		
Primary battery:	7.32		
Probe		Q	
Logic:	25.36	Q section:	20.12
Oscilloscope:	25.14	QAM (<i>see</i> Quadrature amplitude modulation)	
RF:	25.18	QRP (Low power operating):	1.15
Sniffer:	25.22	QSL card:	1.14
Voltage:	25.22	Quad antenna:	21.39
Processing gain:	8.14	QuadNet by W4ENE:	11.21
Product detector:	8.5	Quadrature amplitude modulation (QAM):	8.11ff
Programmable Array Logic (PAL):	4.20	Quadrature detector:	10.12
Programmable gate array (PGA):	3.27, 4.22	Quadrature phase shift keying (QPSK):	8.12, 10.24
Programmable logic device (PLD):	4.19, 4.22, 15.3	Quality factor (Q):	2.49
PropLab Pro propagation software	19.22	Amplifier tank circuit:	17.9
Propagation:	19.1ff	Loaded:	2.60
Back- and sidescatter:	19.18	Loaded and unloaded:	5.13
Below AM broadcast:	19.32	Of components:	2.49
Chart:	19.19	Unloaded:	2.55
D layer:	19.13	Quantization:	15.6ff, 15.9ff
Delay (digital circuit):	4.4	Quantization error:	3.50, 15.2, 15.10
E layer:	19.13ff		
Emerging theories:	19.19		
F layer:	19.16ff	R	
Forecast:	19.20ff	Radians:	2.17, 11.4
Glossary:	19.31	Radiated emissions:	27.6
References:	19.33	Radiation	
Sky wave:	19.6ff	Ionizing and non-ionizing:	28.20
Software:	19.21, 19.22	Radiation inversion:	19.24
Space communication:	19.30ff	Radiation pattern:	21.4, 21.56
Summary by band:	19.4ff	Radiation resistance:	21.2
Tropospheric:	19.22ff	Radio Amateur Civil Emergency Service (RACES):	1.18
VHF/UHF mobile:	19.27ff	Radio direction finding (RDF):	1.17, 21.66ff
Protocol, digital		Doppler shift:	21.71
APRS:	16.24	Electronic antenna rotation:	21.69
Automatic repeat request (ARQ):	16.2, 16.17	Methods at VHF/UHF:	21.69
B2F:	16.26	RFI:	27.18
Broadcast:	16.17	Switched antennas:	21.70
CLOVER:	16.20	Time of arrival:	21.70
Connected and connectionless:	16.17	Radio frequency (RF):	2.18
D-STAR:	16.27	Radio frequency interference (RFI):	27.1ff
G-TOR:	16.20	AC line (brute-force) filter:	27.24
		Alternator whine:	27.37

Audio equipment:	27.33	Rate of change (Δ):	2.34
Audio filter:	27.34	Rayleigh fading:	19.27
Automotive:	27.36	RC time constant (τ):	2.25
Bypass capacitors:	27.23	Reactance (X):	2.27
Choke placement:	27.29, 27.35	Capacitive (X_C):	2.27
Common-mode:	27.9, 27.22	Chart versus frequency:	2.40
Common-mode choke:	27.25ff	Complex waveforms:	2.43
Computers and accessories:	27.34	Inductive (X_L):	2.39
Consumer Electronics Association (CEA):	27.17	Like, in series and parallel:	2.40
Cooperative agreement:	27.22	Ohm's law for reactance:	2.39
Corona discharge:	27.21	Unlike, in parallel:	2.42
Differential mode:	27.9	Unlike, in series:	2.41
Differential-mode:	27.22	Reactance modulator:	10.10
Electric fence:	27.15	Reactive power (VA):	2.48
Electric vehicle (EV):	27.39	Reber, Grote W9GFZ:	14.1
Electrical noise:	27.15	Receive converters	
Fundamental overload:	27.12ff	VHF and UHF:	12.29
Glossary:	27.42	Receiver	
Ground:	27.13	Automatic gain control (AGC):	12.23ff
Ground loop:	27.13	Bandwidth, various modes:	12.7ff
Ground-fault circuit interruptors (GFCI):	27.35	Beat frequency oscillator (BFO):	12.2
Harmful interference:	27.4	Direct conversion:	12.3ff
High-pass filter:	27.3, 27.23	Dynamic range:	12.1, 12.19
Hybrid-electric vehicle (HEV):	27.39	FM:	12.28ff
Identifying:	27.13	Frequency accuracy:	25.33
Ignition noise:	27.38	Frequency stability:	25.33
Immunity:	27.4, 27.9	Front end:	12.2
Intermodulation distortion (IMD):	27.4, 27.12ff	Image:	12.4, 12.9
Keeping a log:	27.14	Image rejection:	12.9, 12.12, 12.19
Locating source of:	27.16	Intercept point (IP):	10.16
Low-pass filter:	27.3, 27.23	Intermediate frequency (IF):	12.2
Non-linear junction:	27.16	Intermediate frequency (IF) selection:	12.9
Notch filter:	27.28	Limiting, FM:	12.29
Path:	27.9	Noise and sensitivity:	12.17
Power-line noise:	27.15, 27.18ff	Noise figure:	12.18
Product review testing:	27.4	Noise floor:	12.1
Public-address equipment:	27.34	Preamplifier:	12.18
References:	27.43	Selectivity:	12.1
Source:	27.9	Sensitivity:	12.1, 12.17, 25.29
Speakers:	27.34	Software defined radio (SDR):	15.25ff
Survival kit:	27.27	Superheterodyne (superhet):	12.2, 12.7ff
Susceptibility:	27.3ff	Third-order intercept point (IP3):	10.16
Switching supplies:	27.35	Troubleshooting:	26.25
Telephone:	27.32	Two-tone IMD test:	10.16
Transmitters:	27.27	UHF and microwave:	12.30ff
Troubleshooting:	27.26ff	Up- and down-converting:	12.19
Ultrasonic location:	27.19	VHF and UHF:	12.28ff
Utility complaint:	27.18	Reciprocal mixing:	9.7, 25.31
Victim:	27.9	Recombination:	3.8
Radio horizon:	19.23	Reconstruction filter:	15.8
Radio propagation:	19.1ff	Rectification:	3.5, 7.4
Radio spectrum:	2.18	Rectifier:	7.10
Classifications:	2.19	Average dc current rating, I_O :	7.11
Radiosport (contesting):	1.12	Circuits:	3.17
Radioteletype (RTTY):	16.6	Current inrush:	7.11
AFSK, FSK:	16.6	Equalizing resistors:	7.11
Baudot code:	16.6	Fast-recovery:	7.10
Diddle character:	16.6	Heat sinking:	7.12
F1B versus F2B:	16.6	Inrush current limiting:	7.11
Fading:	16.8	Parallel diodes:	7.11
Inverted or reverse shift:	16.6	Peak inverse voltage (PIV, PRV):	7.11
Keyed AFSK:	16.6	Peak repetitive forward current, I_{REP} :	7.11
Mark:	16.6	Peak surge current, I_{SURGE} :	7.11
Minimal shift keyed (MSK):	16.8	Power dissipation:	7.11
Shift, LTRS and FIGS:	16.6	Ratings and protection:	7.11
Shifts:	16.8	Reverse recovery time:	7.11
Space:	16.6	Schottky diode:	7.10
Spotting an RTTY signal:	16.6	Semiconductor:	7.10
Start and stop bit:	16.6	Series diode strings:	7.11
Terminal Unit (TU):	16.6	Switching speed:	7.11
Tone pair:	16.6	Thermal resistance (θ):	7.11
Unshift-on-space (USOS):	16.8	Reed-Solomon code:	16.15
USB and LSB:	16.6	References	
Rain scatter:	19.24	Analog basics:	3.59
Ramp wave:	2.16	Antenna:	21.73

Antenna safety:	28.21	Duplexer:	18.4
Computer-Aided Circuit Design:	6.24	FM voice:	18.2, 18.4ff
D-STAR:	18.16	Glossary:	18.12
Digital electronics:	4.27, 4.31	History:	18.1
Digital modes:	16.33	Internet linking:	18.10
Digital signal processing (DSP):	15.31	Linking:	18.4, 18.9
Electrical safety:	28.12	Narrowbanding:	18.9
Filters:	11.44	Offsets, standard:	18.9
Mixers, Modulators and Demodulators:	10.29ff	Operation (FM voice):	18.4
Modulation:	8.25	P25:	18.14
Oscillators and Synthesizers:	9.47	Remote receiver:	18.5
PC-board layout:	6.24	Rules and regulations:	18.3
Power sources:	7.47	Timer:	18.4
Propagation:	19.33	Tone access:	18.6
Radio frequency interference (RFI):	27.43	Reserve capacity, battery (RC):	7.44
Receivers:	12.36	Resistance (R):	2.3
Remote stations:	29.27	Bridge circuits:	25.3
RF power amplifier:	17.50	Effect of temperature:	2.4
RF techniques:	5.37	Equivalent resistance:	2.7
Software defined radio (SDR):	15.31	Four-wire resistance measurement:	25.5
Telemetry and Navigation Data:	14.11	Ohmmeter:	25.3
Test equipment and measurements:	25.54	Resistivity (ρ):	2.3
Transmission lines:	20.29	Resistor:	2.2, 2.5
Transmitters and Transceivers:	13.39	Bleeder:	7.13
Troubleshooting:	26.39	Carbon composition (carbon comp):	22.2
Reflection:	19.2	Carbon film:	22.2
Reflection coefficient (Γ , ρ):	5.36, 20.4	Color code:	22.3
Conversion between attenuation, SWR, return loss:	22.56	EIA identification and marking:	22.4
Refraction:	19.2	Equalizing:	7.29
Ionospheric:	19.7	Metalized film:	22.2
Tropospheric:	19.24	Non-inductive:	5.4
Refractive index:	19.2	Package dimensions:	22.3
Regeneration:	3.4	Parallel resistors:	2.7
Register		Parasitic inductance:	5.4
Formed by flip-flops:	4.11	Parasitic inductance model:	5.4
Shift:	4.11	Power:	22.4
Storage:	4.11	Precision:	2.4, 22.2, 25.3
Relay:	2.14	Pull-up:	3.45
Configurations:	2.14	Resistor pack:	3.44
Construction:	2.14	Series resistors:	2.8
Ratings:	2.14	Standard values:	22.5
Types of relays:	2.14	Temperature coefficient (tempco):	2.5
Reluctance (\mathfrak{R}):	2.33	Thick-film power:	22.3
Remote sensing:	14.1	Thin-film resistor:	3.26
Batteries:	14.9	Types of resistors:	2.5
HF payloads:	14.11	Wire-wound:	22.3
High-altitude:	14.9	Resolution:	25.2
Payloads:	14.10	Resolution bandwidth (RBW):	25.21
Platform design:	14.9	Resonance:	2.42, 9.1
Remote stations:	29.19ff	Of ferrite cores:	5.20
Basic HF station:	29.24	Resonant circuits:	2.55
Connecting and controlling:	29.21ff	Antiresonance:	2.57
Electrical power:	29.20	Circulating current:	2.60
Ethernet bridge:	29.23	Parallel:	2.57
Insurance and security:	29.21	Parallel, above and below resonance:	2.59
Internet and telephone access:	29.20	Parallel, loaded Q:	2.60
Internet bandwidth:	29.23	Parallel, use for impedance matching:	2.62
Latency:	29.19, 29.23	Resonant frequency:	2.55
Licensing:	29.21	Selectivity:	2.56
Property and access:	29.20	Series:	2.55
Requirements:	29.19	Series and parallel:	2.42
Resources:	29.25	Series, unloaded Q and bandwidth:	2.56
Safety:	29.21	Resonant frequency:	2.55
Site preparation:	29.20	Return loss (RL):	5.36, 11.11, 20.4
Repeater:	18.1ff	Converting between attenuation, reflection coefficient, and SWR:	22.56
AM and SSB:	18.2	Return loss bridge (RLB):	25.24
Amateur television (ATV):	18.2	Reverse Beacon Network:	19.21
Closed:	18.6	Reverse bias:	3.9
Controller:	18.4	Reverse breakdown voltage:	3.15
Coordination:	18.2, 18.9	Reverse leakage current:	3.9
D-STAR:	18.12ff	RF ammeter:	25.19, 25.45
D-STAR hardware:	18.13	RF amplifier	
Digital:	18.2, 18.3	Feedback:	5.17
Digital voice:	18.14	Power amplifiers:	17.1ff
DMR:	18.14		

RF choke:	2.54, 17.16, 22.10
RF connectors:	22.46ff, 29.7
RF exposure and safety:	28.21ff
Cardiac pacemakers:	28.26
Environments, controlled and uncontrolled:	28.24
FCC exposure regulations:	28.25
Low-frequency fields:	28.27
Maximum permissible exposure (MPE):	28.22
MPE limits table:	28.25
Power density:	28.28
Power threshold table:	28.26
RF awareness guidelines:	28.29
<i>RF Exposure and You:</i>	28.29
RF safety standards:	28.24
Specific absorption rate (SAR):	28.22
Station evaluation:	28.26
Thermal and athermal effects:	28.22
RF heating:	2.69, 5.8
RF impedance	
Measuring:	25.24
RF interference (RFI)	27.1ff
Automotive:	29.13
RF measurements:	25.18ff
RF power measurements:	25.19
RF power amplifier:	17.1ff
RF power modules	
Specifications:	22.31
RF power transistors (MOSFET)	
Specifications:	22.28ff
RF probe:	25.18
RF sniffer:	27.41
RF transformers:	5.27
Air-core resonant:	5.27
Binocular core:	5.29
Broadband ferrite:	5.28
Right-hand rule:	2.32
Ringing (filter):	11.5
Ripple:	7.4
Bandwidth (filter):	11.3
Filter:	11.3
Frequency:	7.13
Voltage:	7.13
Rise and fall time	
Keying:	25.35
RJ connector:	29.8
RL time constant (τ):	2.37
Rolloff (filter):	3.5, 11.3
Root-mean-square (RMS):	2.20, 25.8
Non-sinusoidal waveforms:	25.8
Rope:	28.15
RS-232:	4.25, 4.28
RS-274X:	6.24
RS-422:	4.29
Run length encoding (RLE):	16.4
Ruthroff transformer:	20.21
S	
S (scattering) parameters:	5.35
S-R flip-flop:	4.9
Safe operating area (SOA):	3.14, 7.17
Safety	
Antenna:	28.13ff
Bleeder resistor:	7.30
Chemical properties and hazards:	23.2
Electrical:	28.1ff
Electrical safety rules and guidelines:	26.1ff
Generator:	29.15
Remote stations:	29.21
RF exposure:	28.21ff
Soldering:	23.9
Workbench and shop:	23.1ff
Safety ground:	7.2
Safety, electrical:	28.1ff
Back-feeding ac line:	28.5
Class 1, 2, 3 wiring:	28.5
Distribution box:	28.3
Energized circuits:	28.11
Lockout:	28.2
National Electrical Code (NEC):	28.2
References:	28.12
Solar panel:	28.11
Uninterruptible power supply (UPS):	28.11
Safety, RF exposure:	28.21ff
Sample rate:	15.2
Sampling, analog-digital conversion:	15.6ff
Satellite	
Propagation:	19.30
Space weather:	19.21
Satellites (amateur):	1.15
Saturation (magnetic):	2.33
Saturation (semiconductor):	3.11
Sawtooth wave:	2.16
Scalar network analyzer:	25.25
Scale, meter:	25.7
Scaling:	3.1
Scatter	
Forward:	19.12
Rain:	19.23
Tropospheric:	19.23
Scattering:	19.2
Scattering (S) parameters:	25.25
Schematic capture	
Subcircuits:	6.6
Schematic capture software	
<i>Eagle:</i>	6.16
<i>Kicad:</i>	6.16
Schematic diagram:	2.2
Schottky barrier:	3.15
Schottky diode:	3.15
Scintillation:	19.26, 19.30
SCR (<i>see</i> Silicon controlled rectifier)	
Screen grid:	17.5
SDR (<i>see</i> Software defined radio)	
Secondary (battery):	7.32
Secondary emission:	17.5
Section Manager (SM):	27.2
Selective fading:	8.4, 8.10
Selectivity:	12.1
Self-discharge:	7.32
Self-resonance:	5.9
Semiconductor	
Acceptor and donor impurities:	3.8
Compound:	3.8
Cross-reference:	26.10
Cutoff (semiconductor):	3.11
Depletion region:	3.9
Doping:	3.8
Extrinsic:	3.8
Free electron:	3.8
Hole:	3.8
Intrinsic:	3.8
Junction semiconductor:	3.9
Majority and minority carriers:	3.8
Monocrystalline:	3.8
N-type, P-type:	3.8
Photoconductor:	3.8
PN junction:	3.8
Polycrystalline:	3.8
Recombination:	3.8
Safe Operating Area (SOA):	3.14
Saturation:	3.11
Substitution:	26.11
Substrate:	3.12
Temperature effects:	3.14
Thermal runaway:	3.14
Sensitivity:	12.1, 12.17
Sensors:	14.1ff
Calibration:	14.4
Capacitance-based:	14.3

Current-based:	14.2	Small-signal transistor model:	3.29, 5.16
Digital interfaces:	14.4	BJT:	3.29
Powering:	14.6	FET:	3.36
Remote sensing:	14.1	Smith chart:	20.4
Resistance-based:	14.2	Sniffer probe:	25.22
Voltage-based:	14.3	Snubber network:	2.38
Sequential logic:	4.8ff	Software	
<i>Serenade</i> :	6.10	<i>4nec2</i> by Arie Voors	21.21
Serial I/O interface:	4.20ff, 4.27ff	<i>AADE Filter Design and Analysis</i> :	11.26
IEEE-1394 (FireWire):	4.29	<i>Airmail</i> :	16.26
RS-232:	4.28	<i>Analog Filter Wizard</i> by Analog Devices:	11.22
RS-422:	4.29	ASAPS:	19.22
Universal serial bus (USB):	4.29	<i>Codec2</i> by VK5DGR:	16.16
Serial Peripheral Interface (SPI):	4.20, 4.21, 14.5	<i>d*Chat</i> :	16.29
Service monitor:	25.36	<i>D-RATS</i> :	16.29
Shack notebook:	26.6	<i>Diplexer Designer</i> by W4ENE:	11.41
Shannon-Hartley theorem:	8.17	<i>Dplus</i> :	16.29, 18.13
SHF (frequency range classification):	2.19	<i>DPRS</i> :	16.29
Shield, RFI:	27.22	<i>Dream</i> :	16.15
Shielding, oscillator:	9.19	<i>Elsie</i> by W4ENE:	11.9
Shift register:	4.11	<i>ExpressPCB</i> :	17.36, 17.49
Shock hazards and effects:	26.1, 28.12	<i>EZNEC</i> by W7EL:	21.21
Shock mounts:	29.9	<i>FilterPro</i> by Texas Instruments:	11.22
Short skip:	19.13	<i>FLDIGI</i> by W1HKJ:	16.5
Shortwave broadcast bands:	19.22	<i>FreeDV</i> by KD0EAG and VK5DGR:	16.15
Shunt feed:	21.25	<i>GC Prevue</i> :	6.24
Sidescatter:	19.18	<i>Gerbv</i> :	6.24
Siemens (S):	2.3, 2.28, 2.39	<i>Helical</i> by W4ENE:	11.33
Signal generator:	25.26	<i>HFTA</i> (HF Terrain Analysis):	29.20
Use for troubleshooting:	26.5	<i>IONCAP</i> :	19.22
Signal injector		<i>LTSpice</i> :	17.11
Use for troubleshooting:	26.5	<i>MATCH</i> by W0IYH:	20.11
Signal source		<i>MeterBasic</i> by W4ENE:	17.49
Use for troubleshooting:	26.5	Modulators and demodulators:	15.29
Signal to noise ratio (SNR):	5.30	MUF prediction:	19.22
Signal tracing:	26.6	MultiPSK:	16.13
Signal tracing and injection:	26.15ff	PC-board layout:	6.15ff
Signal-to-noise and distortion ratio (<i>see</i> SINAD)		<i>PI-EL Design</i> by W4ENE:	17.10
Signal-to-noise ratio (SNR):	3.28, 12.1	<i>PropLab Pro</i> :	19.22
Silicon (device):	3.9	<i>QuadNet</i> by W4ENE:	11.21
Silicon controlled rectifier (SCR):	3.11	<i>SVC Filter Designer</i> by W4ENE:	11.11, 17.31
Anode gate:	3.11	<i>TLW</i> by N6BV:	20.4
Cathode gate:	3.11	<i>TubeCalculator</i> :	17.7ff
Use in a crowbar circuit:	3.11	VOACAP:	19.22
Use in ac power control:	3.11	<i>W6ELProp</i> :	19.22
Simplex:	18.2	<i>Webench</i> by National Semiconductor:	11.22
Simplex repeater:	14.10	<i>WinDRM</i> by HB9TLK:	16.15
SINAD:	3.49, 25.30	<i>WSJT</i> by K1JT:	16.14
Sinc function:	8.17, 15.8	Software (CAD)	
Sine wave:	2.15, 2.16	<i>Advanced Design System (ADS)</i> :	6.10
Sine wave generation (DSP):	15.17ff	<i>Ansoft Designer SV2</i> :	6.2
Single sideband (SSB):	8.5, 10.7	<i>ARRL Radio Designer</i> :	6.5
DSP modulator and demodulator:	15.22ff	<i>AutoCAD</i> :	6.3
Filter method:	8.5, 13.5	<i>B2 Spice</i> :	6.3
Lower and upper sideband (LSB and USB):	8.5	<i>EAGLE</i> :	6.2
Phasing method:	8.5, 13.6	<i>gEDA</i> :	6.2
Single-sideband, suppressed-carrier:	13.5	<i>ICAP4</i> :	6.15
Weaver method:	8.5, 13.6, 15.24	<i>Kicad</i> :	6.2
Skeleton slot antenna:	21.43	<i>LTSpice</i> :	6.2
Skew path:	19.19	<i>MICROCAP9</i> :	6.15
Skin effect:	5.6, 5.8, 20.1	<i>OrCAD</i> :	6.2
Skin depth (δ):	5.8	<i>PSPICE</i> :	6.14
Skip zone:	19.8	RF-fluent:	6.9
Sky wave propagation:	19.6ff	<i>Serenade</i> :	6.10
Slew rate:	3.2	Software defined radio (SDR):	15.1, 15.25ff
Slow-scan television (SSTV):	8.19, 16.13	Dynamic range:	15.26
Analog modes:	8.19	Glossary:	15.32
Digital modes:	8.20	Hardware:	15.25ff
Frame sequential:	8.19	Local oscillator (LO):	15.28
Line sequential:	8.19	Modulators and demodulators:	15.29
Redundant digital file transfer (RDFT):	8.20	References:	15.31
Remote sensing:	14.10	Sampling at RF:	15.27
Vertical interval signaling (VIS):	8.19	Software architecture:	15.28ff
		Speech processing:	15.30

Solar 27-day rotation:	19.11	Standards	
Solar battery or cell (<i>see</i> Photovoltaic cell)		Measurements:	25.1
Solar cycle:	19.10	Traceability and transfer:	25.1
Solar flare:	19.12	Standing-wave ratio (SWR, VSWR, ISWR):	20.4
Solar flux:	19.10	Bridge:	20.24
Solar panel:	3.23	Bridge, audible:	24.20
Solar power		Conversion of attenuation, reflection coefficient, and return loss:	22.56
Remote stations:	29.20	Converting to return loss:	5.36
Solar wind:	19.6	Flat line:	20.4
Soldering:	23.7ff	Myths about:	20.16
Desoldering:	23.9	Star ground:	27.13
Irons and guns:	23.7	Static (precipitation):	19.31
Lead-free:	23.8	Station	
Printed-circuit board (PCB):	23.21	Accessory projects:	24.1ff
Reduction of Hazardous Substances (RoHS):	23.8	Assembly:	29.1ff
Safety:	23.9	Documentation:	29.8
Solder types:	23.7	Layout:	29.2ff
Surface-mount technology (SMT):	23.11	Location:	29.1
Solenoid:	2.14	Power:	29.2
Solenoidal coil:	2.31	Stefan-Boltzmann's constant (k):	5.30, 5.33
Solid-state relay:	4.20	Step recovery diode (SRD):	13.7
Sound card:	16.5	Stethoscope	
Test equipment:	25.38	Use for troubleshooting:	26.6
Source, RFI:	27.11	Stop band (filter):	11.2
Source-follower (<i>see</i> Common-drain amplifier)		Stop band depth and frequency:	11.4
Space weather satellite:	19.22	Storage register:	4.11
Span, frequency:	25.21	Stratosphere:	19.6
Speakers		Stripline:	11.29
RFI:	27.34	Stub (transmission line):	20.7
Twisted-pair cable:	27.34	As filters:	20.7
Specific energy (battery):	7.33	Combinations:	20.8
Specific power (battery):	7.33	Connecting:	20.8
Spectral power and voltage density:	5.30	Field Day stub filters:	20.9
Spectral purity		Measuring:	20.8
Transmitter:	25.33	Quarter- and half-wave:	20.7
Spectrum analyzer:	25.19ff	Universal:	20.24
Features and specifications:	25.23ff	Subaudible tone:	18.8
Tracking generator:	25.23	Subaudible tone (<i>see also</i> CTCSS):	18.6
Use of:	25.21ff	Substitution guide (semiconductor):	3.8
Spectrum, frequency range classifications:	2.19	Sudden ionospheric disturbance (SID):	19.12
Speech		Summing amplifier:	3.44
Clipping, AF:	13.11	Sunspot:	19.10
Clipping, IF:	13.13	Sunstone Circuits (PCB vendor):	6.16
Compression:	13.11	Superheterodyne (superhet) receiver:	12.2, 12.7ff
Processing:	13.10	Bandwidth, various modes:	12.7
Processing, with digital signal processing (DSP):	15.30	Collins system:	12.11
Spike (<i>see</i> Transient)		Crystal lattice filters:	12.10
Splatter:	8.21	IF selection:	12.9
Split operation:	18.2	Multiple conversion:	12.11
Repeater offsets:	18.9	Sensitivity:	12.17
Splitter, power:	20.21	Superheterodyne (transmitter):	13.9
Sporadic E propagation:	19.13	Superposition:	3.1
Spread spectrum (SS):	8.14ff, 16.12	Suppression, sideband	
Chip rate:	8.15	Measurement:	25.34
Code-division multiple access (CDMA):	8.16	Surface acoustic wave (SAW):	11.28
Direct sequence (DSSS):	8.16, 16.12	Surface-mount technology (SMT):	22.2, 23.10
Frequency hopping (FHSS):	8.15	Package types:	23.10
Processing gain:	8.14	Soldering:	23.11
Spreading:	16.12	Susceptance (B):	2.28
Spurious emissions:	27.4ff, 27.12	Capacitive (B_C):	2.28
Spurious response		Inductive (B_L):	2.39
Spectrum analyzer:	25.21	Susceptibility, RF:	27.3ff
Spurious signals		SVC Filter Designer by W4ENE:	11.11, 17.31
Transmitter:	13.16	Sweep, oscilloscope:	25.12
Spurious-free dynamic range (SFDR):	3.49, 15.2	Swinging choke:	7.14
Square wave:	2.16	Switch:	2.12
Square-law device:	3.37	Make and break:	2.13
Squegging (squeeging):	9.11	Poles and positions:	2.13
Squelch:	18.8	Ratings:	2.12
Sensitivity test:	25.32	Types of switches:	2.13
SSNe:	19.21	Switched-capacitor filter (SCAF):	11.19
SSTV (<i>see</i> Slow-scan television)		Switching circuit:	3.41
Standard cell (battery) sizes:	7.32	Circuit design:	3.41
Standard frequency stations:	25.11	High-side and low-side switching:	3.41

Power dissipation:	3.41
Reactive loads:	3.41
Transistor selection:	3.41
Switching mixer:	10.18ff
Switching supplies (<i>see also</i> Switchmode power conversion)	
RFI:	27.35
Switching time:	5.14
Switchmode power conversion:	7.21
Boost converter:	7.23
Bridge converter:	7.25
Buck converter:	7.21
Buck-boost converter:	7.23
Continuous conduction mode (CCM):	7.22
Design aids and tools:	7.28
Discontinuous conduction mode (DCM):	7.22
Flyback converter:	7.23
Forward converter:	7.25
Pulse-width modulation:	7.22, 7.26
RFI:	7.21, 27.13
Switching loss:	7.21
SWR meter:	25.37, 26.4
SWR monitor:	24.4
Symbol library (PCB layout):	6.16
Symbol rate:	8.8
Synchronicity (logic):	4.8
Synchronous detector:	8.4
Synchronous transformer:	20.12
Synthesizer, frequency	
Direct digital synthesis (DDS):	15.17

T

T antenna:	21.28
T match:	21.38
T network:	5.26, 20.10
Design:	20.15
Tank circuit:	9.1, 17.9ff
Component ratings:	17.15ff
Efficiency:	17.10
Flywheel effect:	17.9
Manual design methods:	17.12
Taylor mixer:	10.28ff
TCP/IP:	16.23
Technical Coordinator (TC), ARRL:	26.2
Technical Specialist (TS), ARRL:	26.2
Telemetry:	14.7
Digital modes:	14.8
Non-licensed:	14.8
Telephone	
RFI:	27.32
RFI filter:	27.33
Television interference (TVI):	27.1, 27.27ff
Analog TV:	27.29
Cable TV:	27.30ff
Channel guide:	27.30
Digital TV:	27.29
DVD and VCRs:	27.32
Electrical noise:	27.30
Fundamental overload:	27.27
High-pass filter:	27.28
Preamplifiers:	27.28
Spurious emissions:	27.29
Temperature	
Antenna:	5.31
Excess:	5.30
Noise:	5.30
Temperature coefficient (tempco):	2.5, 22.2
Capacitor:	2.28
Temperature compensated oscillator:	9.21
Temperature compensation:	2.70
Oscillator:	9.18
Temperature inversion:	19.24
Temperature sensor:	3.59
Terminal node controller (TNC):	16.17
Modem:	16.17

Multi-protocol controller (MPC):	16.17
Multimode communications processor (MCP):	16.17
Terminations:	25.15, 25.27
Tesla (T):	2.32
Test equipment	
Troubleshooting:	26.3ff
Test probes:	26.4
Inductive pickup:	26.4
Use for troubleshooting:	26.4
Tetrode:	17.5
Thermal conductivity (k):	2.67
Thermal resistance (θ):	2.67
Rectifier:	7.11
Thermal runaway:	3.14
Thermionic emission:	17.4
Thermistors:	2.70
Thermocouple detector:	25.19
Thevenin equivalent circuit:	2.9
Thevenin's Theorem:	2.9
Thin-film resistor:	3.26
Third-order intercept point (IP3):	10.16, 25.31
Thompson, Sir William (Lord Kelvin):	25.1
Three-terminal voltage regulator:	7.18
Adjustable regulator:	7.19
Current source:	7.20
Increasing output current:	7.20
Low dropout regulator:	7.19
Throb:	16.12
Thyristor:	3.10
Time base	
Frequency counter:	25.9ff
Time constant (τ)	
RC:	2.25
RL:	2.37
Time domain:	2.17, 25.19
Time standard stations:	25.11
Time-invariant:	3.1
Timer (multivibrator) IC:	3.55
Astable (free-running):	3.55
Monostable (one-shot):	3.55
TLW by N6BV:	20.4
Tolerance:	2.4, 22.2
Tone	
Decoder, DSP:	15.19
Repeater access:	18.6
Tools	
Care of:	23.3
Recommended for electronics:	23.4
Toroid winding:	5.29
Total harmonic distortion+noise (THD+N):	3.49
Tower	
Base, concrete:	28.15
Carabiner:	28.15
Climbing harnesses and belts:	28.19
Climbing safety:	28.19
Crank-up:	28.9
Erection and maintenance:	28.15
Gin-pole:	28.15
Ground crew:	28.19
Guy wires, lengths to avoid:	22.40
Guyed:	28.14
Guying and guy wires:	28.16
Legal considerations:	28.13
Roof-mounted:	28.15
Ropes:	28.15
Safety references:	28.21
Safety tips:	28.21
Self-supporting:	28.14
TIA-222:	28.13
Wind load:	28.13
TR switching:	13.30
Amplifier interfacing:	13.32
Tracking generator:	25.23

Transceiver	
Architecture:	13.28ff
Break-in (CW):	13.29
Handheld:	18.7
Home station (FM voice):	18.7
Mobile (FM voice):	18.7
Push-to-talk (PTT):	13.29
Software defined radio (SDR):	15.25ff
TR switching:	13.30
Troubleshooting:	26.28
Upconverting:	13.28
Voice-operated-transmit (VOX):	13.29ff
Transconductance:	3.6
Forward transconductance, g_m :	3.19
Transducer:	2.16
Transverse propagation (TE):	19.19
Transfer characteristics:	3.3
Transfer function:	3.3, 3.27
Transfer switch:	28.5
Transformer:	2.62
50 Hz considerations:	7.3
Broadband (RF):	17.31
Color code:	22.15
Evaluating:	7.3
High-voltage:	7.30
Impedance matching:	20.12, 21.57
Impedance ratio:	2.64
Interwinding capacitance:	2.65
Isolation:	7.3
Laminations:	2.63
Leakage flux:	2.64
Leakage reactance:	2.65
Losses:	2.64
Magnetizing inductance:	7.3
Power:	7.3
Power ratio:	2.64
Primary and secondary:	2.62
RF:	5.27
Shielding:	2.65
Step-up and step-down:	2.63
Turns ratio:	2.63
Volt-ampere rating:	7.3
Voltage and current ratio:	2.63
Transient:	7.12
Transient protection	
Gas tube:	7.12
Varistor:	7.12
Zener diode:	7.12
Transient suppressor diode (TVS):	3.17
Transimpedance amplifier:	14.3
Transistor	
Gain versus frequency:	5.16
Switching circuits:	3.41
Transistor array IC:	3.54
Transistor tester	
Use for troubleshooting:	26.6
Transistor-transistor logic (TTL):	4.14
Circuits:	4.15
Driving CMOS:	4.18
Three-state outputs:	4.16
Unused inputs:	4.16
Transition region (filter):	11.2
Transition time (digital circuit):	4.4
Transmatch (<i>see</i> Antenna Tuner)	
Transmission line	
Attenuation (loss):	20.4
Attenuation of two-conductor twisted pair:	22.41
Balanced and unbalanced load:	20.17
Balancing devices:	20.17
Coaxial cable:	20.1
Digital circuits:	20.27
Effects of loss:	20.5
Impedance of two-conductor twisted pair:	22.41
Impedance transformation:	20.7
Impedance transformer:	20.19ff
Incident, forward, and reflected waves:	20.4
Ladder line:	20.6
Length per dB of loss:	20.6
Load:	20.3
Lumped-constant:	20.3
Matched and mismatched:	20.3
Matched- (ML) and mismatched-line loss:	20.5
Mechanical considerations:	20.6
Microstrip:	11.29
Open-wire:	20.1
Parallel-conductor (twin-lead):	20.1
Phasing antennas:	20.12
Quarter-wave (Q) section:	20.12
Radiation cancellation in:	20.1
Radiation from:	20.17
Selecting type of line:	20.5
Specifications:	22.48
Stripline:	11.29
Stubs:	20.7
Synchronous transformer:	20.12
Termination:	20.3
Transformer:	17.29
Twin-lead:	20.1
Velocity factor (VF):	20.1, 20.8
VHF/UHF:	21.56
Waveguide:	20.28
Weatherproofing:	28.18
Window line:	20.1
Transmitter	
Amplitude modulation (AM):	13.4
Angle modulation (FM, PM):	13.6
Automatic level control (ALC):	13.17
Bandpass filter:	13.23
Carrier and unwanted sideband suppression:	25.34
CW keying waveform:	13.2
CW mode:	13.15
Data, Morse, Pulse:	13.1ff
Frequency modulation (FM):	13.7
Intermodulation distortion:	25.34
Modulation:	13.24
Oscillator:	13.22
Phase modulation (PM):	13.8
Speech processing:	13.10
Spurious signal:	13.16
Superheterodyne, SSB/CW:	13.9
Troubleshooting:	26.26
Two-tone test:	13.14, 25.34
VHF signal sources:	13.19
Wideband noise:	13.16
Transverse electromagnetic mode (TEM):	11.29
Trap (antenna):	21.14, 21.17, 21.27
Traveling wave tube:	9.29
Tri-state gate:	4.6
Triac:	3.11
Triangle wave:	2.16
Triggering	
Oscilloscope:	25.12, 25.16
Triggering, flip-flop:	4.9
Triode:	17.5
Tripler (frequency):	13.7
Triplexer:	20.8
Troposphere:	19.6
Tropospheric	
Bending:	19.27
Ducting:	19.25ff
Fading:	19.27
Propagation:	19.22ff
Refraction:	19.24
Scatter:	19.23
Troubleshooting	
Amplifier circuits:	26.23
Amplifiers, power:	26.28ff
Antenna systems:	26.32ff
Assessing symptoms:	26.13
Battery hazards:	26.8

Circuit-level, analog:	26.18ff	Cooling methods:	17.6
Circuit-level, digital:	26.20ff	Grid (control, screen, suppressor):	17.5
Completing repair:	26.21	Grid dissipation:	17.14
Component level:	26.7ff	Nomenclature:	17.5
Connectors:	26.7	Operating parameters:	17.8ff
General symptoms:	26.26	Pentode:	17.5
Inspections:	26.14	Plate (anode):	17.4
Microprocessor equipment:	26.17	Plate dissipation:	17.14
Newly constructed equipment:	26.14	Ratings:	17.14
Oscillators:	26.24	Screen dissipation:	17.13
Power supplies:	26.22	Secondary emission:	17.5
Professional repair:	26.22	Specifications:	22.34
Radio frequency interference (RFI):	27.26ff	Tetrode:	17.5
Receivers:	26.25	Thermionic emission:	17.4
Recommended equipment:	26.3ff	Triode:	17.5
References:	26.39	Vacuum tubes	
Search engines:	26.2	Troubleshooting:	26.12
Semiconductors:	26.9ff	Varactor diode:	3.16, 13.7
Shack notebook:	26.6	Specifications:	22.19
Signal tracing and injection:	26.15ff	Variable crystal oscillator (VXO):	9.25
Systematic vs instinctive:	26.12	Variac (transformer):	2.66
Television interference (TVI):	27.27	Varicode:	8.8, 16.3, 16.8ff
Transceivers:	26.28	Varistor:	7.12
Transmit amplifier modules:	26.25	VCR (Videotape Cassette Recorder) RFI:	27.32
Transmitters:	26.26	Vector:	2.44
Tube tester:	26.36	Vector network analyzer (VNA):	20.9, 25.25
Vacuum tubes:	26.12	Velocity (radio wave):	19.1
TTL (<i>see</i> transistor-transistor logic)		Velocity factor (VF):	20.1, 20.8
Tube (<i>see</i> Vacuum tube)		Vertical	
Tube tester:	26.36	Amplifier:	25.11
<i>TubeCalculator</i> software:	17.7ff	Vertical antenna:	21.22ff
Tubing, aluminum:	21.34	Trap:	21.27
Tuned circuit		Vertical interval signaling (VIS):	8.19
Single-tuned circuit:	5.13	Vestigial sideband (VSB):	8.18
Tuned radio frequency (TRF) receiver:	12.3	Digital television:	8.11
Tuning procedure		VFO (<i>see</i> Oscillator)	
Amplifier, RF power:	17.14	VHF (frequency range classification):	2.19
Turn-around time		VHF/UHF	
Transmitter:	25.35	FM voice equipment:	18.7
Tuska, Clarence:	1.1	Home station antenna (for repeaters):	18.7
Twelfth-wave transformer:	20.13	Mobile antennas:	18.7
Twisted-pair speaker cable:	27.34	Propagation (mobile):	19.27ff
Two-port network:	3.27	Victim, RFI:	27.11
Two-port network parameters:	5.34	Video bandwidth:	25.21
Two-port parameters:	5.34	Vintage equipment:	1.17
Two-tone IMD:	8.21, 10.16	Repair and restoration:	26.35ff
Two-tone test:	25.34	Virtual height:	19.7
Transmitter:	13.14	VLF (frequency range classification):	2.19
		VOACAP:	19.22
		Voice-operated transmit (VOX):	13.29ff
		Volt-amp reactive (VAR):	2.48
		Volt-ampere rating (transformer):	7.3
		Voltage	
		Potential difference:	25.2
		Voltage (V, E):	2.1
		Potential:	2.1
		Voltage drop:	2.9
		Voltage source:	2.9
		Volts (V):	2.1
		Voltage divider:	2.8
		Voltage multiplier:	7.7, 7.10
		Full-wave voltage doubler:	7.7, 7.8
		Half-wave voltage doubler:	7.7
		Voltage tripler and quadrupler:	7.8
		Voltage probe:	25.22
		Voltage reference IC:	3.54
		Voltage regulation:	7.13
		Adjustable regulator:	7.19
		Dynamic and static regulation:	7.13
		Three-terminal voltage regulator:	7.18
		Voltage regulator IC:	3.54, 22.17
		Specifications:	22.20
		Voltage-controlled oscillator (VCO):	9.32, 9.37
		Noise:	9.42
		Phase-locked loops (PLL):	9.37
U			
Ufer ground:	28.7		
UHF (frequency range classification):	2.19		
UHF connector:	29.7		
Ultimate attenuation (filter):	11.2		
Ultraviolet radiation:	19.6		
Underwriter Labs (UL):	28.1		
Unintentional emitters:	27.5		
Uninterruptible power supply (UPS):	28.11		
Unipolar transistor (<i>see</i> Field-effect transistor)			
Units			
Systems of measurement:	25.1		
Units and conversion factors:	22.53		
Unity-gain buffer:	3.44		
Universal serial bus (USB):	4.29		
Universal stub:	20.24		
USB:	4.25		
Battery charging:	7.38		
V			
Vackar oscillator:	9.12		
Vacuum tube:	17.4ff		
Cathode:	17.4		
Construction:	17.6		

Voltage-current converter:	3.47
Voltage-follower circuit:	3.44
Voltage-power conversion:	22.55
Voltmeter	
Digital multimeter (DMM):	25.4
Multiplier resistor:	25.7
Sensitivity, ohms-per-volt:	25.3
Vacuum-tube, VTVM:	25.3
Volunteer Consulting Engineer (VCE), ARRL:	28.1
Volunteer Examiner (VE):	1.5
VOM (volt-ohm-meter):	25.3
Von Neumann architecture:	15.4
VOX (<i>see</i> Voice-operated transmit)	
VSB, 8-VSB (<i>see</i> Vestigial sideband)	

W

W1AW:	1.7
W6ELProp:	19.22
Waterfall display:	16.5
Watt (W):	2.11
Watt-hour (Wh):	2.11
Wattmeter:	26.4
Directional:	20.4, 25.19
Reflectometer:	20.4
Wave cyclone:	19.26
Waveguide:	20.26
Coax-to-waveguide adapters:	25.28
Coupling to:	20.27
Cutoff frequency:	20.26
Dimensions:	20.27
Dominant mode:	20.27
Modes (TM, TE):	20.27
Wavelength (λ):	2.18, 19.1
Wavemeter:	25.10
Waveshaping, CW:	8.8, 10.7
Weaver method (SSB generation):	8.5, 13.6, 15.24
Webench by National Semiconductor:	11.22
Weber (Wb):	2.32
Weston, Edward:	25.3
Wheatstone bridge:	25.3
Whip antenna:	21.45ff
Loading:	21.47
White noise:	5.30
Wien bridge:	25.16
Oscillator:	25.43
WiFi:	4.26
Wilkinson hybrid combiner:	25.28
WinCAP Wizard:	19.22
WinDRM by HB9TLK:	16.15

Winlink 2000 (WL2K):	16.25ff
Airmail:	16.26
B2F:	16.26
Common Message Servers (CMS):	16.26
Paclink:	16.24
PACTOR:	16.24
PMBO:	16.26
Radio Message Server (RMS):	16.26
TELNET:	16.26
WINMOR:	16.22
Comparison to PACTOR:	16.22
SCAMP:	16.22
Sound card:	16.22
TNC interface:	16.22
Wire size	
Mobile installations:	29.12
Wire, specifications:	22.39
Wireless network:	4.29
WSJT by K1JT:	16.14
Meteor scatter:	19.15
WSPR:	16.15
WWV, WWVH:	19.21, 25.11
Propagation forecast:	19.10, 19.12

X

X wave:	19.9
XOR gate:	4.5

Y

Y (admittance) parameters:	5.35
Yagi antenna:	21.32ff
Stacking:	21.60
VHF/UHF:	21.60
YIG-tuned oscillator:	9.28

Z

Z (impedance) parameters:	5.35
Zener diode:	3.16
Noise generation:	3.18
Specifications:	22.18
Voltage regulator:	7.15
Zepp (antenna):	21.7
Extended, double:	21.22
Zero (transfer function):	3.4, 11.20, 11.23
Zero bias:	17.2
Zero-stuffing:	15.9
Zigbee:	4.26

Project Index

A

Amplifier, RF Power	
10 GHz 2 W Amplifier:	17.40
250-W Broadband Linear Amplifier:	17.36
3CX1500D7 RF Linear Amplifier:	17.45
6-Meter Kilowatt Amplifier:	17.49
All-Mode, 2 Meter, 80 W Linear Amp:	17.38
Everyham's Amplifier:	17.42
QSK Controllers for Amplifiers:	24.43
Antenna tuner	
160 and 80 Meter Matching Network for Your	
43-Foot Vertical:	24.9
Switching the Matching Network for Your 43-Foot Vertical: ..	24.11
Z-match:	24.1
Antenna, accessory	
Audible Antenna Bridge:	24.20
Eight-Channel Remote-Control Antenna Switch	24.50
External Automatic Antenna Switch for Use with Yaesu	
or ICOM Radios:	24.14
Legal-Limit Bias-Tee:	24.49
Low-cost Remote Antenna Switch:	24.18
Microprocessor-controlled SWR Monitor:	24.4
Mounts for Remotely-Tuned Antennas:	21.52
Transmitting Choke Baluns:	20.22
Antenna, HF	
40-15 Meter Dual-Band Dipole:	21.16
All-Wire 30 Meter CVD:	21.32
Compact Vertical Dipole (CVD):	21.30
Extended Double-Zepp For 17 Meters:	21.22
Family of Computer-Optimized HF Yagis:	21.37
Five-Band, Two-Element HF Quad:	21.40
Half-Wave Vertical Dipole (HVD):	21.29
Low-band Quad and Delta Loops:	21.41
Multiband Center-Fed Dipole:	21.14
Multiband Horizontal Loop Antenna:	21.44
Retuning a CB Whip Antenna:	21.53
Skeleton Slot for 14-30 MHz:	21.43
Top-Loaded Low-Band Antenna:	21.26
Tri-band Moxon Yagi Antenna	21.38
Two W8NX Multiband, Coax-Trap Dipoles:	21.21
Two-Band Loop for 30 and 40 Meters:	21.43
W4RNL Inverted-U Antenna:	21.17
Antenna, VHF/UHF	
A Medium-Gain 2 Meter Yagi:	21.61
Cheap Yagis by WA5VJB:	21.62
Homebrew Coaxial Dipole for VHF or UHF:	21.58
Simple, Portable Ground-Plane Antenna:	21.58
Three and Five-Element Yagis for 6 Meters:	21.60

C

Computer interface	
Simple Serial Interface:	24.25
Trio of Transceiver/Computer Interfaces:	24.22
USB Interfaces for Your Ham Gear:	24.26
CW Keyer	
TiCK-4 -- A Tiny CMOS Keyer:	24.31
Universal Keying Adapter:	24.29

F

Filter, audio	
Audio Intelligibility Enhancer:	24.35
Filter, RF	
Band-pass filter for 145 MHz:	11.42
Broadcast-Band Reject Filter:	11.37
Crystal Ladder Filter for SSB:	11.35
Diplexer Filters:	11.39
Field Day Stub Assembly:	20.9
High-Performance, Low-Cost 1.8 to 54 MHz Low-Pass Filter: ..	11.41
Optimized Harmonic Transmitting Filters:	11.39
Wave Trap for Broadcast Stations:	11.38

O

Oscillator	
JFET Hartley VFO:	9.15
Low-noise Differential Oscillator:	9.12
Modified Vackar VFO:	9.12

P

Power source	
12-V, 15-A Power Supply:	7.50
13.8-V, 5-A Regulated Power Supply:	7.53
Adjustable Resistive Load:	7.54
Adjustable Tracking Power Supply	7.61
Automatic Sealed-Lead-Acid Battery Charger:	7.58
Four-Output Switching Bench Supply:	7.48
High-Voltage Power Supply:	7.56
Inverting DC-DC Converter:	7.54
Overvoltage Crowbar Circuit:	7.63
Overvoltage Protection for AC Generators:	7.62
Reverse-Polarity Protection Circuits:	7.57

R

Receiver	
10 GHz Preamplifier:	12.33
430 MHz Preamplifier:	12.31
Micro R2 SSB or CW Receiver:	12.13
Rock-Bending Receiver for 7 MHz:	12.3
RF Interference	
RF Sniffer:	27.41

S

Station accessory	
Adapting Aviation Headsets to Ham Radios:	24.34
Audio Interface Unit for Field Day and Contesting:	24.40

T

Test equipment	
Bipolar Transistor Tester:	25.38
Fixed-Frequency Audio Oscillator:	25.42
Gate-Dip Oscillator:	25.49
High-Power RF Samplers:	25.47
Hybrid Combiners for Signal Generators:	25.49
Inductance Tester:	25.41
Logic Probe:	25.40
RF Current Meter:	25.44
RF Oscillators for Circuit Alignment:	25.48
RF Power Meter:	25.53
RF Step Attenuator:	25.46
Two-Tone Audio Generator:	25.43
Wide-Range Audio Oscillator:	25.42
Transceiver	
HBR-2000 High Performance Transceiver:	13.35
TAK-40 SSB/CW Transceiver:	13.33
Transmitter	
MicroT2 Single-Band SSB Transmitter:	13.18
MkII Universal QRP Transmitter:	13.19, 13.30
Pebble Crusher 7 MHz QRP CW Transmitter:	13.3
VHF Signal Sources (50 and 144 MHz):	13.20

Author Index

Author	Call	Topic	Section Ref	Page Ref
Adams, Chuck	K7QO	Making PC Boards With Printed Artwork	Chapter 25	CD-ROM
Applegate, Alan	KØBG	Mobile antennas	21.8	21.45ff
		Mobile battery selection	7.13.8	7.37
		Mobile stations	29.2	29.9ff
Bartholomew, Wayde	K3MF	Dual-band antenna for 146/446 MHz	Chapter 21	CD-ROM
Belrose, John	VE2CV	Mobile antenna efficiency	21.8	21.49
		Mobile ground losses	21.8	21.50
		Sloping antennas	21.5	21.28
Blackburn, Wally	AA8DX	Station Construction	Chapter 29	29.1ff
		Transceiver/Computer Interfaces	24.8	24.22
Blevins, Ken	K5ALQ	Adapting Aviation Headsets to Amateur Radio	Chapter 24	24.34
Bloom, Alan	N1AL	Digital Signal Processing (DSP)	Chapter 15	15.1ff
		Modulation	Chapter 8	8.1ff
		Test Equipment and Measurements	Chapter 25	25.1ff
		Digital Mode Table	16.5	16.30
		Test Instrument Bibliography	Chapter 25	CD-ROM
Botkin, Dale	NØXAS	Digital Basics	Chapter 4	4.1ff
		Simple Serial Interface	24.9	24.25
		USB Interfaces for Your Ham Gear	24.10	24.26
		Universal Keying Adapter	24.11	24.29
Bramwell, Denton	K7OWJ	RF Step Attenuator	25.8	25.46
Brenner, James	NT4B	Two-band Loop for 30 and 40 Meters	21.49	21.43
Britain, Kent	WA5VJB	Cheap Yagi antennas	21.11	21.62
Brown, Bill	WB8ELK	Remote Sensing Payloads	Chapter 14	14.8
Brown, Jim	K9YC	Ferrite materials	5.4	5.14ff
		Ferrite transmitting chokes	20.5	20.21ff
		Measuring chokes	Chapter 20	CD-ROM
Buchmann, Isidor		Batteries and Charging	7.13	7.32
Bunsold, Pat	WA6MHZ	Refurbishing Vintage Equipment	26.11	26.35
Buxton, Al	W8NX	Multiband, coax-trap dipoles	21.1	21.17
Campbell, Jeremy	KC8FEI	Automotive RF interference	27.9	27.36ff
Campbell, Rick	KK7B	Binaural I-Q receiver	Chapter 12	CD-ROM
		Micro R2 Receiver	12.3	12.16
		RF semiconductor design	Chapter 5	5.1ff
		VHF Signal Sources	13.2	13.19
Carcia, Joe	NJ1Q	External Automatic Antenna Switch (Icom or Yaesu radios)	24.5	24.14
Cebik, L.B.	W4RNL (SK)	Inverted-U antenna	21.1	21.16
		Medium-gain 2 meter Yagi	21.11	21.61
Chen, Kok	W7AY	Unstructured Digital Modes	16.2	16.5ff
Christensen, Paul	W9AC	QSK Controller	24.16	24.43
Cooknell, D.A.	G3DPM	Oscillator construction	9.3	9.16
Colville, Jim	W7RY	QSK Controller	24.16	24.43
Coval, Jeff	ACØSC	FLDIGI	16.1	16.5
Coyle, Larry	K1QW	Microprocessor Controlled SWR Monitor	24.2	24.4
Cutsogeorge, George	W2VJN	Transmission Lines	Chapter 20	20.1ff
Danzer, Paul	N1II	Digital Basics	Chapter 4	4.1ff
		FM voice repeaters	Chapter 18	18.1ff
		Parallel-port interface	Chapter 4	CD-ROM
Daughters, George	K6GT	6 Meter Kilowatt Amplifier	17.12	17.49
Dehaven, Jerry	WAØACF	Phase-locked loops	9.7	9.34ff
Demaw, Doug	W1FB (SK)	Tuna Tin 2 transmitter	13.3	CD-ROM
Devoldere, John	ON4UN	Low band quad and delta loop antennas	21.7	21.41
Diana, Gary	N2JGU	TICK-4 — A Tiny CMOS Keyer	24.12	24.31
Dobbs, George	G3RJV	QRP CW Transmitter for 7 MHz	13.3	13.5
Dodd, Peter	G3LDO	Skeleton Slot Antenna for 14-28 MHz	21.7	21.43
Doig, Al	W6NBH	Multiband quad antenna	21.7	21.40
Duffey, Jim	KK6MC	Circuit Construction	Chapter 23	23.1ff
Dzado, Michael	ACØHB	Eight-Channel Remote-Control Antenna Switch	24.18	24.50
Eenhoorn, Anjo	PAØZR	Active attenuator	Chapter 27	CD-ROM
Eisenberg, Joe	KØNEB	Construction Techniques	Chapter 23	23.1ff
Fitzsimmons, John	W3JN	Restoring vintage equipment	26.9	26.32
Fletcher, Terry	WAØITP	Reverse-Polarity Protection Circuits	7.16	7.51
Ford, Jim	N6JF	Return Loss Bridge	25.8	CD-ROM
Ford, Steve	WB8IMY	Digital Communications	Digital Comms	CD-ROM
		Space Communications	Space Comms	CD-ROM
Frey, Dick	K4XU	250 W Broadband Linear Amplifier	17.11	17.36
		Solid-state amplifiers	17.26-17.30	17.29ff
		RF Transistor tables	Chapter 22	22.28-31

Author	Call	Topic	Section Ref	Page Ref
Geiser, Dave	W5IXM	Simple seeker RFI receiver	Chapter 27	CD-ROM
Gordon-Smith, Dave	G3UUR	Crystal filters	11.6	11.30ff
Grebenkemper, John	KI6WX	Tandem match	25.8	CD-ROM
Grover, Dale	KD8KYZ	PC-board CAD	6.3	6.31ff
Gruber, Mike	W1MG	RF Interference	Chapter 27	27.1ff
Grumm, Linley	K7HFD	Low-noise oscillator	9.3	9.15
Hallas, Joel	W1ZR	Receivers	Chapter 12	12.1ff
		Transmitters and Transceivers	Chapter 13	13.1ff
		Handbook History	Special section	
		Annual Transceiver Survey	CD-ROM	CD-ROM
		Receiver and Transmitter Architectural History	CD-ROM	CD-ROM
Halstead, Roger	K8RI	Amplifier tuning	17.9	17.26
		Surplus amplifier parts	17.11	17.44
Hansen, Markus	VE7CA	High-Performance HF Transceiver — HBR-2000	14.7	14.23
Harden, Paul	NA5N	Component Data and References	Chapter 22	22.1ff
Hare, Ed	W1RFI	Circuit Construction	Chapter 23	23.1ff
		RF Interference	Chapter 27	27.1ff
		Troubleshooting and Maintenance	Chapter 26	26.1ff
Hartnagel, Hans		The Dangers of Simple Usage of Microwave Software	Chapter 6	CD-ROM
Hayward, Roger	KA7EXM	JFET Hartley VFO	9.3	9.17
Hayward, Wes	W7ZOI	JFET Hartley VFO	9.3	9.17
		Oscillator temperature compensation	9.3	9.19
		RF semiconductor design	Chapter 5	5.1ff
		Segment-tuned VCO	9.7	9.50
Henderson, Dan	N1ND	RFI Management	27.2	27.4
Henderson, Randy	W15W	Rock-bending Receiver for 7 MHz	12.2	12.5
Hilding, Rick	K6VVA	Remote Stations	29.4	29.18ff
Hollingsworth, Riley	K4ZDH	RF Interference and the FCC	27.2	27.10
Honnaker, Scott	N7SS	Digital Modes	Chapter 16	16.1ff
Hood, Mike	KD8JB	All-copper, 2 meter J-pole antenna	Chapter 21	CD-ROM
Hranac, Ron	NØIVN	Cable and digital television	27.8	27.29ff
		HDTV modulation	8.3	8.11
Humbertson, Ken	WØKAH	FLDIGI	16.1	16.5
Hutchinson, Chuck	K8CH	Antennas	Chapter 21	21.1ff
Hutchinson, Sylvia	K8SYL	75 and 10 meter dipole	Chapter 21	CD-ROM
Jones, Dave	KB4YZ	Slow-scan television	Image Comms	CD-ROM
Jones, Bill	K8CU	1.8 to 54 MHz Low-Pass Filter	11.11	11.49
Karlquist, Rick	N6RK	Audio latency measurement system	29.4	29.21
		Mixers, Modulators, and Demodulators	Chapter 10	10.1ff
Kay, Leonard	K1NU	Analog Basics	Chapter 3	3.1ff
		RF Techniques	Chapter 5	5.1ff
Kennedy, Hal	N4GG	Audio Intelligibility Enhancer	24.14	24.35
Keuken, Jack	KE2QJ	Base-loading system for whip antennas	21.8	21.48
Kleinschmidt, Kirk	NTØZ	Generators	29.3	29.13
Klitzing, James	W6PQL	All-Mode, 2 Meter, 80 W Linear Amp	17.11	17.38
Kreuter, Rod	WA3ENK	Audible Antenna Bridge	24.7	24.20
Lakhe, Rucha		Mathematical stability problems in non-linear simulation programs	Chapter 6	CD-ROM
Lampereur, Steve	KB9MWR	10 GHz 2 W Amplifier	17.11	17.40
Lapin, Greg	N9GL	Analog Basics	Chapter 3	3.1ff
Larkin, Bob	W7PUA	RF semiconductor design	Chapter 5	5.1ff
Lau, Zack	W1VT	ARRL phase noise measurement	9.2.5	9.10
Lewellan, Roy	W7EL	JFET Hartley VFO	9.3.2	9.17
Lindquist, Rick	WW1ME	What Is Amateur Radio?	Chapter 1	1.1ff
Loveall, Pete	AE5PL	D-STAR repeaters	18.4	18.11
Luetzelschwab, Carl	K9LA	Propagation	Chapter 19	19.1ff
Lux, Jim	W6RMK	Electrical Safety	28.1	28.1ff
Machesney, Brian	K1LI	Tri-band Moxon Yagi Antenna	21.6	21.38
Martin, Mike	K3RFI	Power-line RF Noise	27.6	27.17ff
McClellan, Jim	N5MIJ	D-STAR repeaters	18.4	18.11
McCune, Earl	WA6SUH	Oscillators	Chapter 9	9.1ff
Miller, Russ	N7ART	2 meter RF power amplifier	Chapter 17	CD-ROM
Mitchell, Bradley	WB8YGG	TICK-4 — A Tiny CMOS Keyer	24.12	24.31
Moell, Joe	KØOV	Radio Direction-finding antennas	21.12	21.72ff
		Radio Direction-finding techniques	Chapter 27	CD-ROM
Montgomery, Christine	KGØGN	Digital Basics	Chapter 4	4.1ff
Morris, Steve	K7LXC	Tower and antenna safety	28.2	28.12ff
Mullett, Chuck	KR6R	CAD for power supplies	17.11	17.28
Newkirk, David	W9VES	Computer-Aided Circuit Design	Chapter 6	6.1ff
		Mixers, Modulators, and Demodulators	Chapter 10	10.1ff
O'Hara, Tom	W6ORG	Amateur television	Image Comms	CD-ROM

Author	Call	Topic	Section Ref	Page Ref
Ott, Henry	WA2IRQ	Electromagnetic Compatibility	Chapter 27	27.1ff
Pearce, Gary	KN4AQ	FM voice repeaters	Chapter 18	18.1ff
Pittenger, Jerry	K8RA (SK)	3XC1500D7 RF Linear Amplifier	17.12	17.45
Pocock, Emil	W3EP	Propagation	Chapter 19	19.1ff
Portune, John	W6NBC	Coaxial Dipole for VHF or UHF	21.10	21.58
Raydo, John	KØIZ	Adapting Aviation Headsets to Amateur Radio	24.13	24.34
		Audio Interface Unit for Field Day and Contesting	24.15	24.40
Rauch, Tom	W8JI	RF Current Meter	25.8	25.44
Rogers, Robert	WA1PIO	Inductance Tester	25.8	25.41
Rohde, Ulrich	N1UL	2 meter down-converter	12.7	12.34
		Butler oscillator	9.5.4	9.27
		Mathematical stability problems in non-linear simulation programs	Chapter 6	CD-ROM
		Measuring intermodulation performance	10.4	10.16
		Mixer performance capability	Chapter 10	CD-ROM
		Modified Vackar oscillator	9.3	9.15
		Oscillator design	Chapter 9	CD-ROM
		Phase noise	Chapter 9	CD-ROM
		Simulation at RF	6.3	6.28ff
		Testing mixer performance	10.5	10.21
		The Dangers of Simple Usage of Microwave Software	Chapter 6	CD-ROM
		Using Simulation at RF	Chapter 6	CD-ROM
		VHF/UHF Grounded-base Oscillator	Chapter 9	CD-ROM
Rowe, David	VK5DGR	Digital Voice - CODEC2	16.4	16.15
Sabin, Bill	WØIYH	Conversion Loss in Mixers	10.5	10.19ff
		CW Key Waveform	13.3	13.17
		Diplexer Filter	11.11	11.46
		Half-Lattice Single-Crystal Filter	11.6	11.31
		IF Speech Clipper	13.3	13.16
		<i>MATCH</i> by WØIYH	20.4	CD-ROM
		<i>MATCH</i> by WØIYH	5.6	CD-ROM
		Superhet Receiver	12.3	12.15
		Thermistor Uses	2.15	2.70
		Transmission-line transformers	20.5	20.19ff
Salas, Phil	AD5X	100-W Compact Z-Match Antenna Tuner	24.1	24.1
		160- and 80-Meter Matching Network for Your 43-Foot Vertical	24.3	24.9
		Switching the Matching Network for Your 43-Foot Vertical	24.4	24.11
		Legal-Limit Bias-Tee	24.17	24.49
Severns, Rudy	N6LF	Power Sources	Chapter 7	7.1ff
Silver, Ward	NØAX	Amplifier maintenance	26.5	26.21
		Analog Basics	Chapter 3	3.1ff
		Antennas	Chapter 21	21.1ff
		Electrical Fundamentals	Chapter 2	2.1ff
		Filters	11.1-11.4	11.1ff
Siwiak, Kai	KE4PT	Discussion of Q	2.11, 2.16	2.49, 2.56
Smith, Bill	KO4NR	Low Cost Remote Antenna Switch	24.6	24.18
Stanley, John	K4ERO	Amplifiers, Vacuum-Tube	17.1-17.9	17.1ff
		Everyham's Amp	17.11	17.42
		Optimum Ground Systems	21.3	21.23
Steffka, Mike	WW8MS	Automotive RF Interference	27.9	27.36ff
Stein, William	KC6T	Multiband quad antenna	21.7	21.40
Stewart, Jim		Inverting DC-DC Converter	7.16	7.54
Stockton, David	GM4ZNX	Oscillators	9.1-9.6	9.1ff
		Poles and zeros	3.1.2	3.3
Stroud, Dick	W9SR	Top-loaded, low-band antenna	21.3	21.26
Straw, Dean	N6BV	Antenna modeling and design	Chapter 21	21.1ff
		HFTA antenna modeling software	29.4	29.18
		Transmission Lines	Chapter 20	20.1ff
Stuart, Ken	W3VVN	Power Sources	Chapter 7	7.1ff
Tayloe, Dan	N7VE	Active Filters	11.5	CD-ROM
		Tayloe mixer	10.5	10.28
Taylor, Joe	K1JT	Background noise	5.8	5.33ff
		Earth-Moon-Earth (EME) Communications	Space Comms	CD-ROM
Taylor, Roger	K9ALD	DC circuits and resistance	Chapter 2	2.1ff
Telewski, Fred	WA7TZY	Poles and zeros	3.1	3.3
		Synthesizers	9.7	9.33ff
Thompson, Tom	WØIVJ	High-Power RF Samplers	25.8	25.47
Tonne, Jim	W4ENE	Filters	11.1-11.4	11.1
		Optimized Harmonic Transmitting Filters	11.11	11.46

Author	Call	Topic	Section Ref	Page Ref
Tracy, Mike	KC1SX	ARRL phase noise measurement	9.2	9.10
Ulbing, Sam	N4UAU	Surface-mount technology	Chapter 23	CD-ROM
Veatch, Jim	WA2EUJ	TAK-40 SSB/CW Transceiver	14.7	14.19
Verhage, Paul	KD4STH	Remote Sensing and Navigation Data	Chapter 14	14.1-8
Wade, Paul	W1GHZ	Noise theory		5.8 5.30ff
		Noise Instrumentation and Measurement	Chapter 5	CD-ROM
		Microwave Construction Techniques	23.6	23.26-28
Wetherhold, Ed	W3NQN	Broadcast-band Reject Filter	11.11	11.45
Whitten, Mel	KØPFX	Digital Voice - CODEC2	16.4	16.15
Yoshida, Wayne	KH6WZ	Surface-mount device desoldering	Chapter 23	CD-ROM
Youngblood, Gerald	K5SDR	Taylor mixer	10.5	10.28

