

State Is All You Need: Toward World-State Processing Units

WPU Research Prototype

May 10, 2026

Abstract

Token sequences are a powerful substrate for language, but they are not the natural computational primitive for persistent world processing. A world is not only observed; it is maintained, updated, branched, corrected, and queried as state. This paper proposes the World-State Processing Unit (WPU), a state-native model and execution abstraction in which objects, relations, time, uncertainty, events, and branch deltas are first-class components. The central operation is not token attention but state propagation: events produce sparse deltas, deltas traverse causal relations, affected regions are updated locally, and dense recomputation is invoked only when locality breaks. We define the token-state distinction, introduce propagation as a simplified local-physics prior, derive a sparse-dense crossover metric, and present a small PyTorch reference implementation, `WorldStateProcessor`. On a synthetic robot-cup object physics task, the prototype reduces next-state prediction MSE from 0.8111 to 0.0005 after 200 training steps and improves branch classification accuracy from 0.1289 to 0.7188, exceeding a 0.6680 majority baseline. These results do not establish broad world understanding. They establish a falsifiable research program: if world processing is dominated by persistent identity, local causal change, uncertainty, and branching, then state should be treated as a primary computational substrate rather than as a serialization target for tokens.

1 Introduction

The dominant abstraction in modern deep learning is the token sequence. A token sequence is a list of symbols or embeddings processed through position-indexed operations, most notably attention. This abstraction has been remarkably successful for language and for many domains that can be serialized into a sequence. However, world processing has a different structure. Physical and simulated worlds contain persistent objects, typed relations, heterogeneous attributes, temporal continuity, uncertainty, local causal effects, and multiple possible futures.

This paper asks a narrow question: if the target workload is world processing, should the fundamental unit be the token or the state? We argue that tokens can *describe* state, but they do not preserve state as a computational invariant. A cup can be serialized into text, but the resulting sequence does not make object identity, relation locality, delta updates, uncertainty, or branch sharing first-class operations. A state-native model should not merely retrieve relevant positions; it should update persistent entities and propagate the consequences through a structured world memory.

We introduce the World-State Processing Unit (WPU) as both a model family and an execution abstraction. It is not proposed as a replacement for GPUs, TPUs, or NPUs as general numerical accelerators. Instead, it is a workload definition for world-state processing: a WPU maintains explicit state memory, performs sparse event-driven propagation when changes are local, falls back to dense recompute when affected regions become large, and represents alternative futures as deltas over a shared base state.




Figure 1: Token processing operates over ordered evidence. State processing operates over persistent entities and relations. The distinction is not what can be represented, but which operations are first-class.

Central thesis. The central thesis is that world processing is not primarily a problem of continuing a sequence; it is a problem of maintaining a changing state under partial observation. Tokens are excellent carriers of evidence, but state is the substrate on which consequences accumulate. A state-native model should therefore make identity, locality, delta update, uncertainty, and branching operationally explicit.

Contributions. This paper makes four contributions. First, it formulates a token-state non-equivalence claim in operational rather than representational terms: tokens can serialize state, but serialization does not preserve state operations as invariants. Second, it defines propagation as the central operation of world-state processing and relates it to simplified local physical causality. Third, it proposes a WPU architecture with sparse, hybrid, and dense execution paths selected by an affected-state crossover metric. Fourth, it provides a minimal reference implementation and small-scale validation task, intended as a starting point for stronger benchmarks rather than as final evidence.

2 Relation to Existing Work

WPU is deliberately positioned near several mature research lines rather than outside them. Object-centric representation learning studies how objects can be discovered from perceptual input, including iterative variational inference and slot-based attention mechanisms [6, 7]. Graph networks and interaction networks show that object- and relation-centric message passing is a powerful inductive bias for physical reasoning [2, 3, 9]. Set Transformers and Graph Transformers show how attention can be adapted to sets and graphs [8]. Latent world-model agents such as PlaNet, Dreamer, DreamerV3, and IRIS learn compact dynamics models for planning or imagination [10, 11, 12, 13]. Recent object-centric and graph world models further emphasize structured entities, causal interactions, sparse attention, and planning over object representations [15, 16, 14, 17].

The WPU claim is therefore not that message passing, object-centric modeling, or world models are new. The distinction is operational and systems-oriented. WPU treats persistent state, event frontiers, sparse-dense routing, delta overlays, branch sharing, and update work as the primary interface. In contrast, most prior world models define a learned dynamics model and then

optimize control or prediction quality; most object-centric perception models focus on extracting objects; most graph simulators focus on accurate dynamics under a chosen graph; and most sparse Transformer models keep attention as the central operation. WPU asks a different question: what execution abstraction is appropriate when the workload is maintaining and branching a large world state under local events?

This also clarifies an important limitation. The current prototype assumes that the object-relation state is already available. A complete WPU system would need a perception front-end, such as slot/object discovery or supervised segmentation, to construct and repair the state graph from pixels, point clouds, or multimodal observations. This front-end is outside v1 and is treated as a required next step, not as a solved problem.

3 Token and State Primitives

3.1 Token

A token model receives a sequence

$$X = (x_1, x_2, \dots, x_T), \quad x_t \in \mathbb{R}^d.$$

Its memory is usually position-indexed: sequence context, hidden activations, or KV cache. The central operation in a Transformer is attention:

$$\text{Attn}(Q, K, V) = \text{softmax} \left(\frac{QK^\top}{\sqrt{d}} \right) V.$$

This operation answers: which positions should a position retrieve from?

3.2 State

A world state is a persistent structured object:

$$\mathcal{S}_t = \{\mathcal{O}_t, \mathcal{R}_t, \mathcal{T}_t, \mathcal{P}_t\}.$$

Here $\mathcal{O}_t$ is a set of object records, $\mathcal{R}_t$ is a typed relation graph, $\mathcal{T}_t$ is temporal memory, and $\mathcal{P}_t$ represents uncertainty. An event e_t produces a delta:

$$\mathcal{S}_{t+1} = \mathcal{S}_t \oplus \Delta \mathcal{S}_t.$$

The central operation is propagation:

$$\delta o_i^{(\ell+1)} = f_\theta \left(o_i, e_t, \sum_{j \in \mathcal{N}(i)} g_\theta(o_i, r_{ij}, o_j, \delta o_j^{(\ell)}) \right).$$

This operation answers: what changed, which objects are causally affected, and how far should the consequences propagate?

Propagation is also a deliberately simplified physical prior. Many useful physical approximations are local: contact forces, support constraints, occlusion, collision risk, and signal flow usually begin at a small set of entities and spread through nearby relations. The WPU does not claim that this local propagation is exact physics. It claims that, for many world-processing regimes, local causal propagation can play the role that simplified Newtonian mechanics plays below relativistic scales: an approximate but operationally useful computation before a more global correction is needed.

Property	Token sequence	World state
Basic unit	position embedding	object / relation / belief
Identity	implicit in context	explicit object identity
Memory update	append or rewrite	patch existing state
Relation	inferred by attention	stored as typed edge
Future	continuation	branch overlay
Typical target	next token	next state / delta / branch

Table 1: Token and state differ at the level of computational primitive, not merely at the level of data format.

3.3 Non-equivalence Claim

The claim is not that tokens cannot encode state. Any finite state can be serialized. The claim is that serialization does not preserve the operational invariants needed for efficient world processing: persistent identity, local delta update, relation-addressed propagation, branch sharing, and uncertainty updates. In short:

Token = representation of evidence, State = substrate of update.

This distinction is important because representational universality can obscure computational mismatch. A text string can describe a database, a graph, or a physical scene, but the string does not by itself provide indexed update, referential integrity, graph traversal, or copy-on-write branching. The WPU proposal is analogous: it does not deny that token models can learn world regularities; it claims that world-state operations should not have to be reconstructed from sequence position at every step.

4 Why a WPU?

GPUs, TPUs, and NPUs are excellent dense numerical engines. LPUs and similar sequence-oriented systems emphasize token streams. A WPU is defined by a different workload: world-state maintenance and update.

This workload has four recurring properties. First, most state persists across time. Second, most events affect only a small subset of the state. Third, effects propagate through a structured neighborhood rather than uniformly across all entities. Fourth, future uncertainty is often branching: multiple hypotheses share the same past and differ only in local deltas. A processor that treats all state as a fresh dense input at every step ignores these properties.

The term “processing unit” is used here as a workload and execution-abstraction claim, not as a completed chip design. Recent accelerator proposals for language or reasoning inference emphasize memory bandwidth and token-generation bottlenecks [18], while neuromorphic and sparse-computation surveys emphasize event-like sparsity and recurrent state dynamics [19]. WPU is complementary: it identifies the memory objects and update operations that a future world-state accelerator would need, but the present implementation remains a PyTorch reference model.

The performance claim is conditional. If the world has N objects, an event initially changes ΔN objects, relation fanout is k , propagation depth is h , and there are B branches, then the affected fraction is

$$\rho = \frac{\Delta N k^h B}{N}.$$

Unit	Main workload	Strength	WPU contrast
GPU	dense tensor kernels	throughput	graph-local state updates
TPU	matrix/tensor programs	systolic dense compute	sparse-dense routing
NPU	neural layer inference	efficient feedforward models	persistent state memory
LPU	token sequence inference	low-latency token generation	object/relation deltas
WPU	world-state processing	local update + branching	state-native primitive

Table 2: The WPU is best understood as a workload and architecture proposal, not as a claim that current dense accelerators are obsolete.

Dense recomputation is roughly $O(N)$ for set-level processing or $O(N^2)$ for full attention. Sparse WPU propagation is approximately

$$O(\Delta N k^h B).$$

Therefore, when $\rho \ll 1$, sparse state propagation can be more efficient than full dense recomputation. When ρ is large, the WPU should route to hybrid or dense computation. The WPU advantage is not universal; it is workload-dependent and measurable.

This complexity model is intentionally incomplete as a hardware model. It does not include graph construction, dynamic edge repair, irregular memory access, frontier queue overhead, scatter/gather efficiency, kernel launch overhead, or state-corruption recovery. Those terms determine whether a WPU-style design actually outperforms dense accelerators on real hardware. The v1 experiments therefore report CPU latency and work proxies, but they should not be read as final hardware evidence.

Conditional performance proposition. For workloads in which $\Delta N k^h B \ll N$, a WPU-style update has lower asymptotic state-update work than dense recomputation while preserving access to dense correction when locality fails. For workloads in which the affected region is global, the WPU should reduce to dense computation and offers no sparse advantage. This conditional nature is a feature of the proposal: it makes the claim measurable and falsifiable.

5 WPU Architecture

A WPU has five components:

1. **State memory:** object store, relation graph, temporal buffer, belief store, and branch delta store.
2. **Frontier generator:** maps observations and actions to initially changed objects.
3. **Propagation core:** performs event-conditioned sparse message passing through typed relations.
4. **Dense fallback:** performs global or regional recomputation when the affected fraction is high.
5. **Branch manager:** maintains multiple futures as deltas rather than full state copies.




Figure 2: WPU schematic. Events generate frontiers, the scheduler chooses a sparse, hybrid, or dense execution path, and branches are maintained as deltas over shared state.

Memory model. The memory hierarchy is not an implementation detail; it is part of the computational claim. Token systems primarily cache sequence positions. A WPU caches persistent objects, typed relations, recent deltas, uncertainty, and branch overlays. The intended memory operations are lookup-by-identity, neighbor-fetch, delta-append, branch-overlay, and region materialization.

6 Propagation Rather Than Attention

Attention remains useful inside a WPU, especially for dense fallback and global consistency. The claim is not that attention is obsolete. The claim is that attention is not the defining operation for world-state processing. For token models, attention retrieves information across positions. For WPU models, propagation computes consequences across causal relations.

This gives propagation a physical interpretation. In the same way that a mechanical disturbance first affects objects in contact or support relation, a state delta should first update the frontier of causally adjacent entities. The dense path is then analogous to a global correction step: it is invoked when the local approximation is no longer sufficient because the affected region has become too large.

The analogy is not that WPU propagation is a complete physical law. The analogy is methodological. Newtonian mechanics remains useful in regimes where relativistic corrections are negligible because it captures a stable low-order structure of the world. Similarly, local propagation is proposed as a low-order computational prior for many world-processing regimes: useful where causal effects are local, insufficient where long-range coupling dominates, and therefore paired with a dense correction path.




Figure 3: Branch memory. A WPU shares the base state and stores branch-specific deltas, reducing memory from $O(BN)$ to $O(N + B\Delta)$ when branches are local.

7 Reference Implementation

We implemented a small PyTorch reference model named `WorldStateProcessor`. It receives a `StateGraphBatch` containing object features, relation indices, relation features, event features, masks, and scheduler metrics. It predicts object deltas, relation logits, uncertainty, and branch probabilities.

The prototype has three paths:

- **Sparse:** learned relation-conditioned message passing from the event target.
- **Hybrid:** sparse update plus regional dense correction.
- **Dense:** global attention over the object set.

The scheduler uses fixed thresholds:

$$\rho < 0.05 \rightarrow \text{sparse}, \quad \rho < 0.25 \rightarrow \text{hybrid}, \quad \rho \geq 0.25 \rightarrow \text{dense}.$$


These thresholds are engineering defaults for making the v1 route behavior inspectable. They are not claimed to be optimal constants. The B -sweep and training-step sweep below show that fixed thresholds can hurt accuracy, which is why learned routing is a primary follow-up requirement.

The reference implementation is intentionally small. It should be read as an executable specification of the architecture, not as an optimized model. The important interface is that the same module consumes structured state graphs, routes computation by affected-state metrics, predicts deltas instead of only labels, and emits branch probabilities that can be stored as overlays.

8 Small-Scale Validation

The validation task is a synthetic robot-cup object physics problem. The scene contains a cup, table, robot hand, table edge, and configurable background objects. The event is a hand touching the cup with variable force. The model predicts the next object delta and one of three branch labels: stable, falls, or caught.

This task is deliberately not a benchmark of general physical reasoning. It is a unit test for the WPU hypothesis: can an explicit state graph, a local event, a sparse-dense route decision, and branch probabilities be trained and inspected in a single neural model? The experiment is therefore closer to a controlled physics-inspired assay than to a claim of broad physical competence.



frontier expands only through affected relations

Figure 4: State propagation. An event produces a delta at a target object, and the delta propagates through typed relations until the scheduler stops or escalates the update.




Figure 5: Validation task. The model observes an object-relation state graph and an event, then predicts next-state deltas and future branch probabilities.

Model	Next-state MSE	Branch NLL	Branch accuracy
Untrained WSP	0.8111	1.2070	0.1289
Majority baseline	–	–	0.6680
Trained WSP	0.0005	0.8074	0.7188

Table 3: Small-scale validation on 256 synthetic evaluation samples. The model was trained for 200 steps with batch size 16.

Background objects	Sparse ratio	Hybrid ratio	Dense ratio
0	0.0000	0.0000	1.0000
20	0.0000	1.0000	0.0000
80	1.0000	0.0000	0.0000

Table 4: Routing sweep. The same local event routes differently depending on the fraction of world state affected by the event.

Model	Acc. at $N = 4$	Acc. at $N = 24$	Acc. at $N = 84$
WPU routed	0.6719	0.7969	0.6719
WPU sparse	0.7812	0.8047	0.6719
WPU hybrid	0.7812	0.7969	0.7969
WPU dense	0.6719	0.6719	0.6719
Dense graph	0.4219	0.5000	0.5938
Serialized token	0.5625	0.6641	0.7891

Table 5: Baseline and ablation branch accuracy after 100 training steps. The results are mixed: WPU variants are strong in small/intermediate regimes, while the serialized-token baseline is competitive and strongest at $N = 84$. This supports a regime hypothesis rather than universal WPU dominance.

Regime	Best WPU	Accuracy	Best non-WPU	Accuracy
$N = 4$	WPU hybrid	0.7242 ± 0.0260	Dense graph	0.6398 ± 0.1257
$N = 24$	WPU hybrid	0.7320 ± 0.0280	Graph Transformer	0.6609 ± 0.0680
$N = 84$	WPU hybrid	0.7508 ± 0.0244	Graph Transformer	0.6953 ± 0.0388
$N = 204$	WPU sparse/routed	0.4516 ± 0.1957	Graph Transformer	0.7172 ± 0.0615


Table 6: Robust baseline comparison over five seeds, 150 training steps, and 256 evaluation samples per condition. The result supports a medium-local regime advantage but refutes universal WPU quality dominance.

Change type	Measured bracket	Estimated N	Interpretation
Route: dense to hybrid	$12 \rightarrow 16$	16 measured	hard scheduler crosses $\rho < 0.25$
Route: hybrid to sparse	$52 \rightarrow 68$	68 measured	hard scheduler crosses $\rho < 0.05$
Accuracy: WPU vs non-WPU	$108 \rightarrow 132$	≈ 120	WPU-family advantage disappears
Runtime: routed WPU vs token	$108 \rightarrow 132$	≈ 124	routed sparse becomes faster than token
Runtime: routed WPU vs dense graph	$164 \rightarrow 204$	≈ 178	routed sparse becomes faster than dense graph


Table 7: Dense N -sweep change points over $N = 4, 8, 12, 16, 24, 36, 52, 68, 84, 108, 132, 164, 204, 260$. The v1 gap is now precise: accuracy advantage ends around $N \approx 120$, while runtime advantage begins around $N \approx 124$ versus token baselines and $N \approx 178$ versus dense graph.

N	Best B	Best routed acc.	Best runtime ms/sample	Route changes
24	1	0.7258	0.6452	$B = 1$ sparse, $B = 2$ hybrid, $B = 6$ dense
84	1	0.7531	0.7204	$B = 1$ sparse, $B = 5$ hybrid
132	1	0.6305	0.6050	$B = 1$ sparse, $B = 7$ hybrid
204	1	0.4594	0.6483	$B = 1$ sparse, $B = 11$ hybrid

Table 8: Dense B -sweep over $B = 1, \dots, 16$. Increasing branch pressure moves routed WPU toward hybrid or dense execution, but accuracy is not monotonic in B . This is evidence that the fixed threshold scheduler should be replaced by an accuracy-latency-aware learned router.



(a) Routed WPU execution-path ratios as world size and branch pressure vary.




(b) Accuracy and routed work versus world size at $B = 3$, aggregated over seeds.


Figure 6: Regime evidence. The route diagram supports the WPU scheduler hypothesis, while the accuracy/work plot shows that lower routed work and higher accuracy do not automatically occur in the same N regime.

Model	Best step	Best acc.	Acc. at 150	Acc. at 300
WPU routed	300	0.7477	0.6836	0.7477
WPU sparse	300	0.7477	0.6836	0.7477
WPU hybrid	100	0.7719	0.7281	0.7070
Dense graph	75	0.7617	0.6125	0.6961
Graph Transformer	75	0.7906	0.6555	0.7555
Serialized token	75	0.7875	0.6422	0.7063

Table 9: Dense training-step sweep at $N = 84, B = 3$ over steps 0, 5, 10, 15, 20, 30, 40, 50, 75, 100, 125, 150, 200, 250, 300. Many baselines peak before 150 steps, so a single fixed training budget is not sufficient evidence of model-family dominance.




(a) Accuracy with 95% confidence intervals over five seeds.




(b) Accuracy-runtime surface at branch pressure $B = 3$.

Figure 7: Robust evidence package. WPU variants are strongest in the medium local synthetic regimes, but graph/token baselines dominate accuracy at $N = 204$. Runtime advantage appears only at large N , where the current WPU accuracy fails.



(a) Accuracy crossover curve. Positive values mean the best WPU variant exceeds the best non-WPU baseline.



(b) Routed WPU path transition at branch pressure $B = 3$.


Figure 8: Dense N -sweep evidence. The scheduler transitions occur near the theoretical ρ thresholds, but the accuracy crossover and runtime crossover do not yet align.

Model	Acc. at 0	Acc. at 128	Acc. drop	MSE multiplier	Cup-MSE multiplier
WPU routed	0.7289	0.6961	0.0328	30.03	1.40
WPU sparse	0.7289	0.6961	0.0328	30.03	1.40
WPU hybrid	0.7508	0.7258	0.0250	6.60	1.36
Graph Transformer	0.6859	0.3422	0.3438	10.17	5.58
Serialized token	0.6742	0.6328	0.0414	8.52	11.64


Table 10: Controlled relation-noise stress test over irrelevant extra relation edges 0, 4, 8, 16, 32, 64, 128. WPU-hybrid preserves branch accuracy best, while the relation-aware Graph Transformer collapses under heavy irrelevant edge noise. This supports frontier/routing control in noisy state graphs, not universal WPU dominance.

Model	Best affected-bg MSE	Affected-bg MSE at 64	Acc. at 64	Cup MSE at 64
WPU routed	0.000269	0.000568	0.7508	0.0182
WPU sparse	0.000269	0.000568	0.7508	0.0182
WPU hybrid	0.002344	0.002344	0.7094	0.0186
Graph Transformer	0.000839	0.001014	0.7000	0.0032
Serialized token	0.000514	0.000514	0.7172	0.0021

Table 11: Controlled affected-count stress test with strong background deltas. The branch label remains cup-centric, so affected-background MSE is the relevant failure-mode metric. Serialized token is best at the largest affected count, while routed/sparse WPU remains competitive.



(a) Branch accuracy under irrelevant relation noise.



(b) Affected-background MSE under increasing affected-region size.

Figure 9: Controlled stress tests. Relation noise tests robustness to irrelevant edges; affected count tests whether local-update models remain valid when the changed region becomes less local.

9 Discussion

The next-state result shows that the prototype learns the local synthetic delta rule. The branch result is more important: the trained model exceeds the majority baseline despite class imbalance, indicating that event force and object geometry are used for future prediction. The routing sweep is the clearest architectural signal. It demonstrates that WPU compute is a function of affected-state fraction: the same event can be dense in a tiny world, hybrid in a medium world, and sparse in a large world.

The current evidence is intentionally modest. It does not show general world understanding, nor does it validate the propagation rule on real sensorimotor data. It shows that a state-native model can be implemented, trained, and evaluated with explicit state, propagation, branch deltas, and sparse-dense routing. The physical claim should therefore be read as an architectural prior: propagation is a simplified local-causality operator that must be tested against richer physics and real-world dynamics.

The robust baseline results are deliberately included because they constrain the claim. Over five seeds, WPU-hybrid is strongest at $N = 4, 24, 84$ in this synthetic local task, but graph-transformer and serialized-token baselines dominate at $N = 204$. Runtime profiling tells a complementary story: routed WPU becomes faster than dense graph, graph-transformer, and serialized-token baselines at $N = 204$, but this is precisely where its accuracy collapses. The central unsolved problem is therefore not whether sparse state propagation can reduce work; it can. The unsolved problem is how to make the efficiency regime and the accuracy regime overlap.

A denser N -sweep sharpens this statement. With $B = 3$, routed execution changes from dense to hybrid at the measured point $N = 16$, and from hybrid to sparse at $N = 68$, consistent with the hard ρ thresholds. However, the best-WPU accuracy advantage crosses below the best non-WPU baseline at roughly $N \approx 120$, while routed WPU becomes faster than serialized-token around $N \approx 124$ and faster than dense graph around $N \approx 178$. The next model target is therefore concrete: push the accuracy crossover beyond the runtime crossover while preserving the sparse execution curve.

Dense sweeps over branch pressure and training steps further constrain the claim. Increasing B is not uniformly beneficial: it can trigger a route transition that increases work and reduces accuracy. Likewise, several baselines reach their best validation accuracy before the nominal final training step. These results make the v1 conclusion stricter: future claims must report not just isolated points, but surfaces over N , B , route, training budget, accuracy, calibration, and latency.

The controlled stress tests sharpen the failure-mode picture. Under irrelevant relation noise, WPU-hybrid loses only 0.025 branch-accuracy points from 0 to 128 extra relations, while the Graph Transformer loses 0.3438 points. This is a positive result for explicit frontier/routing control: not every relation in a state graph should receive equal effective update pressure. However, the affected-count stress test is more mixed. When many background objects receive synthetic deltas, serialized-token has the best affected-background MSE at the largest affected count, and routed/sparse WPU is competitive but not dominant. This result is important because it prevents an overclaim: state-native propagation is promising for noisy local updates, but v1 does not prove broad superiority for all state-delta regimes.

This does not invalidate the WPU hypothesis; it narrows it. The present evidence supports the routing and state-interface claims more strongly than it supports a quality dominance claim. A stronger paper must therefore compare matched models on the full accuracy-compute-memory surface, not only on accuracy.

10 Limitations

The two external reviews of this manuscript correctly identify several limitations that are not solved by the current prototype. First, v1 assumes a structured object-relation state and does not solve perception-to-state construction. Second, the experiments are synthetic and small compared with standard physical-simulation, model-based reinforcement-learning, or robotics benchmarks. Third, WPU propagation overlaps mathematically with message passing in GNNs and Graph Network-based Simulators; the novelty is the execution model and state-memory abstraction, not a new message-passing equation. Fourth, the hard ρ scheduler is not derived from optimal control or hardware cost models. Fifth, the current memory analysis does not yet measure real branch overlay memory, irregular sparse-kernel cost, or GPU/accelerator efficiency. Sixth, persistent state introduces a safety problem: wrong deltas can corrupt future state, so checkpointing, rollback, uncertainty gates, and consistency checks are required before deployment.

These limitations change the paper’s scientific posture. The current claim is not that WPU already surpasses Transformers, GNN simulators, Dreamer-style agents, or object-centric world models. The claim is that world-state processing defines a testable regime: when persistent identity, local causal change, branching, and sparse affected regions dominate, explicit state propagation and delta overlays should be a better execution primitive than repeatedly serializing the whole world into tokens. The experiments in this paper are a first assay of that regime, not a final proof.

11 Falsifiable Predictions

For the WPU proposal to be scientifically useful, it must make predictions that can fail. We identify four.

1. **Locality scaling:** for fixed prediction quality, routed WPU models should require less update work than dense baselines when $\rho \ll 1$.
2. **Crossover behavior:** as ρ increases, the optimal execution path should move from sparse to hybrid to dense rather than remaining sparse.
3. **Branch memory:** for multi-hypothesis rollout with local divergence, delta branches should use less memory than full state copies without losing branch identity.
4. **State advantage:** on tasks where object identity persists across many events, state-native models should need fewer examples or less compute than serialized-token baselines at matched accuracy.

Any of these predictions could fail. If serialized token models match state models at equal compute across controlled identity, locality, and branching benchmarks, then WPU is not a necessary primitive. If sparse routing harms accuracy before it yields meaningful efficiency, then propagation is not the right central operation. These are empirical questions, not matters of terminology.

12 Roadmap

The next stage requires stronger validation:

1. balanced synthetic benchmarks with controllable $N, \Delta N, k, h, B$;

2. ablations against sparse-only, dense-only, Graph Transformer, Set Transformer, and serialized-token baselines;
3. controlled stress tests for irrelevant relations, global affected regions, identity swaps, distractor objects, and long-horizon branch divergence;
4. learned routing compared with the hard ρ scheduler;
5. perception-to-state front-ends using slot/object discovery or supervised segmentation;
6. checkpoint, rollback, and state-integrity mechanisms for persistent delta updates;
7. calibration metrics for branch probabilities;
8. long-horizon rollout error and branch collapse analysis;
9. runtime and memory profiling on CPU/GPU;
10. real or simulator-backed object dynamics datasets such as learned-physics, MuJoCo, Isaac Gym, or robotics manipulation benchmarks.

A high-impact validation should not only report accuracy. It should report the accuracy-compute-memory surface as the world size, affected fraction, causal depth, and number of branches vary. The most important experiment is not whether WPU wins on one small task; it is whether the predicted regime diagram appears: state-native propagation should dominate in local-change regimes, dense models should dominate in global-change regimes, and hybrid routing should occupy the crossover.

13 Conclusion

World processing requires more than describing the world in tokens. It requires persistent, updateable state. The WPU proposal makes state the primary computational object and propagation the central operation. Tokens remain useful as observations and descriptions, and attention remains useful inside dense state modules, but neither is sufficient as the defining primitive for state-native world models. The current prototype is a small first step: it implements explicit world state, event-conditioned propagation, sparse-dense routing, and branch deltas in a reproducible neural model.

References

- [1] Ashish Vaswani et al. Attention Is All You Need. Advances in Neural Information Processing Systems, 2017.
- [2] Peter W. Battaglia, Razvan Pascanu, Matthew Lai, Danilo J. Rezende, and Koray Kavukcuoglu. Interaction Networks for Learning about Objects, Relations and Physics. Advances in Neural Information Processing Systems, 2016.
- [3] Peter W. Battaglia et al. Relational inductive biases, deep learning, and graph networks. arXiv:1806.01261, 2018.
- [4] Thomas N. Kipf and Max Welling. Semi-Supervised Classification with Graph Convolutional Networks. ICLR, 2017.

- [5] David Ha and Jürgen Schmidhuber. World Models. arXiv:1803.10122, 2018.
- [6] Klaus Greff, Raphaël Lopez Kaufman, Rishabh Kabra, Nick Watters, Christopher P. Burgess, Daniel Zoran, Loic Matthey, Matthew Botvinick, and Alexander Lerchner. Multi-Object Representation Learning with Iterative Variational Inference. Proceedings of the 36th International Conference on Machine Learning, 2019.
- [7] Francesco Locatello, Dirk Weissenborn, Thomas Unterthiner, Aravindh Mahendran, Georg Heigold, Jakob Uszkoreit, Alexey Dosovitskiy, and Thomas Kipf. Object-Centric Learning with Slot Attention. Advances in Neural Information Processing Systems, 2020.
- [8] Juho Lee, Yoonho Lee, Jungtaek Kim, Adam R. Kosiorek, Seungjin Choi, and Yee Whye Teh. Set Transformer: A Framework for Attention-based Permutation-Invariant Neural Networks. Proceedings of the 36th International Conference on Machine Learning, 2019.
- [9] Alvaro Sanchez-Gonzalez, Jonathan Godwin, Tobias Pfaff, Rex Ying, Jure Leskovec, and Peter W. Battaglia. Learning to Simulate Complex Physics with Graph Networks. Proceedings of the 37th International Conference on Machine Learning, 2020.
- [10] Danijar Hafner, Timothy Lillicrap, Ian Fischer, Ruben Villegas, David Ha, Honglak Lee, and James Davidson. Learning Latent Dynamics for Planning from Pixels. Proceedings of the 36th International Conference on Machine Learning, 2019.
- [11] Danijar Hafner, Timothy Lillicrap, Jimmy Ba, and Mohammad Norouzi. Dream to Control: Learning Behaviors by Latent Imagination. International Conference on Learning Representations, 2020.
- [12] Danijar Hafner, Jurgis Pasukonis, Jimmy Ba, and Timothy Lillicrap. Mastering Diverse Domains through World Models. arXiv:2301.04104, 2023.
- [13] Vincent Micheli, Eloi Alonso, and François Fleuret. Transformers are Sample Efficient World Models. arXiv:2209.00588, 2022.
- [14] Anson Lei, Bernhard Schölkopf, and Ingmar Posner. SPARTAN: A Sparse Transformer World Model Attending to What Matters. Advances in Neural Information Processing Systems, 2025.
- [15] Yosuke Nishimoto and Takashi Matsubara. Object-Centric World Models for Causality-Aware Reinforcement Learning. Proceedings of the AAAI Conference on Artificial Intelligence, 40(29):24585–24593, 2026.
- [16] Rodion Vakhitov, Leonid Ugadiarov, and Aleksandr Panov. Object-Centric World Models Meet Monte Carlo Tree Search. arXiv:2601.06604, 2026.
- [17] Jiawei Liu, Senqiao Yang, Mingjun Wang, Yu Wang, and Bei Yu. Graph World Models: Concepts, Taxonomy, and Future Directions. arXiv:2604.27895, 2026.
- [18] Matthew Adiletta, Gu-Yeon Wei, and David Brooks. RPU: A Reasoning Processing Unit. arXiv:2602.18568, 2026.
- [19] Osvaldo Simeone. Modern Neuromorphic AI: From Intra-Token to Inter-Token Processing. arXiv:2601.00245, 2026.