

Sequencing Legal DNA

NLP for Law and Political Economy

4. Supervised Learning with Text

Weekly Q&A Page

`bit.ly/NLP-QA04`

ML Essentials

Overview

Regression / Regularization


Binary Classification

Multi-Class Models

Osnabruegge, Ash, and Morelli 2020

Ensemble Learning with XGBoost

What is machine learning?



- ▶ In classical computer programming, humans input the rules and the data, and the computer provides answers.
- ▶ In machine learning, humans input the data and the answers, and the computer learns the rules.

Machine Learning with Text Data

- ▶ We have a corpus (or dataset) D of $n_D \geq 1$ documents (or data points), whose features can be represented as a matrix of vectors \mathbf{x} with $n_x \geq 1$ features.

Machine Learning with Text Data

- ▶ We have a corpus (or dataset) D of $n_D \geq 1$ documents (or data points), whose features can be represented as a matrix of vectors \mathbf{x} with $n_x \geq 1$ features.
- ▶ Each document has an associated outcome or label \mathbf{y} with dimensions $n_y \geq 1$

Machine Learning with Text Data

- ▶ We have a corpus (or dataset) D of $n_D \geq 1$ documents (or data points), whose features can be represented as a matrix of vectors \mathbf{x} with $n_x \geq 1$ features.
- ▶ Each document has an associated outcome or label \mathbf{y} with dimensions $n_y \geq 1$
- ▶ Some documents are unlabeled \rightarrow we would like to train a model to machine-classify them.

Objectives of Machine Learning Project

1. **What is the question or problem?**

Objectives of Machine Learning Project

1. **What is the question or problem?**
2. Corpus and Data:
 - ▶ obtain, clean, preprocess, and link.
 - ▶ Produce descriptive visuals and statistics on the text and metadata

Objectives of Machine Learning Project

1. **What is the question or problem?**
2. Corpus and Data:
 - ▶ obtain, clean, preprocess, and link.
 - ▶ Produce descriptive visuals and statistics on the text and metadata
3. Machine learning:
 - ▶ Select a model and train it.
 - ▶ Fine-tune hyperparameters for out-of-sample fit.
 - ▶ Interpret predictions using model explanation methods.

Objectives of Machine Learning Project

1. **What is the question or problem?**
2. Corpus and Data:
 - ▶ obtain, clean, preprocess, and link.
 - ▶ Produce descriptive visuals and statistics on the text and metadata
3. Machine learning:
 - ▶ Select a model and train it.
 - ▶ Fine-tune hyperparameters for out-of-sample fit.
 - ▶ Interpret predictions using model explanation methods.
4. Empirical analysis
 - ▶ Produce statistics or predictions with the trained model.
 - ▶ **Answer the question / solve the problem.**

ML Essentials

Overview

Regression / Regularization

Binary Classification

Multi-Class Models

Osnabruegge, Ash, and Morelli 2020

Ensemble Learning with XGBoost

Three Types of (Standard) Machine Learning Problems

Determined by the data type of the outcome variable (or label):

- ▶ **Binary classification**: two choices, normalized to zero and one.
 - ▶ e.g., guilty or innocent

Three Types of (Standard) Machine Learning Problems

Determined by the data type of the outcome variable (or label):

- ▶ **Binary classification**: two choices, normalized to zero and one.
 - ▶ e.g., guilty or innocent
- ▶ **Regression**: a one-dimensional, continuous, real-valued outcome.
 - ▶ e.g., number of days of prison assigned

Three Types of (Standard) Machine Learning Problems

Determined by the data type of the outcome variable (or label):

- ▶ **Binary classification:** two choices, normalized to zero and one.
 - ▶ e.g., guilty or innocent
- ▶ **Regression:** a one-dimensional, continuous, real-valued outcome.
 - ▶ e.g., number of days of prison assigned
- ▶ **Multinomial Classification:** Three or more discrete, un-ordered outcomes.
 - ▶ e.g., predict what judge is assigned to a case: Alito, Breyer, or Cardozo

What do ML Algorithms do? Minimize a cost function

- ▶ A typical cost function (or loss function) for regression problems is Mean Squared Error (MSE):

$$\text{MSE}(\theta) = \frac{1}{n_D} \sum_{i=1}^{n_D} (h(x_i; \theta) - y_i)^2$$

- ▶ n_D , the number of rows/observations
- ▶ x , the matrix of predictors, with row x_i
- ▶ y , the vector of outcomes, with item y_i
- ▶ $h(x_i; \theta) = \hat{y}$ the model prediction (hypothesis)

Loss functions, more generally

- ▶ The loss function $L(\hat{\mathbf{y}}, \mathbf{y})$ assigns a score based on prediction and truth:
 - ▶ Should be bounded from below, with the minimum attained only for cases where the prediction is correct.
- ▶ The average loss for the test set is

$$\mathcal{L}(\theta) = \frac{1}{n_D} \sum_{i=1}^{n_D} L(h(\mathbf{x}_i; \theta), \mathbf{y}_i)$$

- ▶ The estimated parameter matrix θ solves

$$\hat{\theta} = \arg \min_{\theta} \mathcal{L}(\theta)$$

↪ optimizes over parameter space; treats the data as constants.

OLS Regression is Machine Learning

- ▶ Ordinary Least Squares Regression (OLS) assumes the functional form $f(x; \theta) = x'_i \theta$ and minimizes the mean squared error (MSE)

$$\min_{\hat{\theta}} \frac{1}{n_D} \sum_{i=1}^{n_D} (x'_i \hat{\theta} - y_i)^2$$

OLS Regression is Machine Learning

- ▶ Ordinary Least Squares Regression (OLS) assumes the functional form $f(x; \theta) = x'_i \theta$ and minimizes the mean squared error (MSE)

$$\min_{\hat{\theta}} \frac{1}{n_D} \sum_{i=1}^{n_D} (x'_i \hat{\theta} - y_i)^2$$

- ▶ This minimand has a closed form solution

$$\hat{\theta} = (\mathbf{x}'\mathbf{x})^{-1} \mathbf{x}'\mathbf{y}$$

- ▶ most machine learning models do **not** have a closed form solution → use numerical optimization (gradient descent).

$$\text{MSE}(\theta) = \frac{1}{n_D} \sum_{i=1}^{n_D} (h(\theta; \mathbf{x}_i) - y_i)^2$$

- The partial derivative for feature j is

$$\frac{\partial \text{MSE}}{\partial \theta_j} = \frac{2}{n_D} \sum_{i=1}^{n_D} \underbrace{(h(\theta; \mathbf{x}_i) - y_i)}_{\text{error for this obs}} \underbrace{\frac{\partial h(\theta; \mathbf{x}_i)}{\partial \theta_j}}_{\text{how } \theta_j \text{ shifts } h(\cdot)}$$

- → estimates how changing θ_j would reduce the error across the whole dataset.

$$\text{MSE}(\theta) = \frac{1}{n_D} \sum_{i=1}^{n_D} (h(\theta; \mathbf{x}_i) - y_i)^2$$

- ▶ The partial derivative for feature j is

$$\frac{\partial \text{MSE}}{\partial \theta_j} = \frac{2}{n_D} \sum_{i=1}^{n_D} \underbrace{(h(\theta; \mathbf{x}_i) - y_i)}_{\text{error for this obs}} \underbrace{\frac{\partial h(\theta; \mathbf{x}_i)}{\partial \theta_j}}_{\text{how } \theta_j \text{ shifts } h(\cdot)}$$

- ▶ → estimates how changing θ_j would reduce the error across the whole dataset.

- ▶ The **gradient** ∇ gives the vector of these partial derivatives for all features:

$$\nabla_{\theta} \text{MSE} = \begin{bmatrix} \frac{\partial \text{MSE}}{\partial \theta_1} \\ \frac{\partial \text{MSE}}{\partial \theta_2} \\ \vdots \\ \frac{\partial \text{MSE}}{\partial \theta_j} \end{bmatrix}$$

- ▶ **Gradient descent** nudges θ against the gradient (the direction that reduces MSE):

$$\theta_{t+1} = \theta_t - \eta \nabla_{\theta} \text{MSE}$$

- ▶ η = learning rate

$$\text{MSE}(\theta) = \frac{1}{n_D} \sum_{i=1}^{n_D} (h(\theta; \mathbf{x}_i) - y_i)^2$$

- ▶ The partial derivative for feature j is

$$\frac{\partial \text{MSE}}{\partial \theta_j} = \frac{2}{n_D} \sum_{i=1}^{n_D} \underbrace{(h(\theta; \mathbf{x}_i) - y_i)}_{\text{error for this obs}} \underbrace{\frac{\partial h(\theta; \mathbf{x}_i)}{\partial \theta_j}}_{\text{how } \theta_j \text{ shifts } h(\cdot)}$$

- ▶ → estimates how changing θ_j would reduce the error across the whole dataset.

- ▶ The **gradient** ∇ gives the vector of these partial derivatives for all features:

$$\nabla_{\theta} \text{MSE} = \begin{bmatrix} \frac{\partial \text{MSE}}{\partial \theta_1} \\ \frac{\partial \text{MSE}}{\partial \theta_2} \\ \vdots \\ \frac{\partial \text{MSE}}{\partial \theta_j} \end{bmatrix}$$

- ▶ **Gradient descent** nudges θ against the gradient (the direction that reduces MSE):

$$\theta_{t+1} = \theta_t - \eta \nabla_{\theta} \text{MSE}$$

- ▶ η = learning rate

- ▶ **Stochastic gradient descent (SGD)** computes the gradient for a single randomly sampled instance (at each iteration). Much faster, still works well.

Data Prep for Machine Learning

- ▶ Data Pre-Processing: See Geron Chapter 2 for pandas and sklearn syntax:
 - ▶ imputing missing values.
 - ▶ feature scaling (often helpful/necessary for ML models to work well)
 - ▶ if predictors are sparse (e.g. bag-of-words), use `StandardScaler(with_mean=False)`.
 - ▶ encoding categorical variables.
 - ▶ **Best practice: reproducible data pipeline.**

Data Prep for Machine Learning

- ▶ Data Pre-Processing: See Geron Chapter 2 for pandas and sklearn syntax:
 - ▶ imputing missing values.
 - ▶ feature scaling (often helpful/necessary for ML models to work well)
 - ▶ if predictors are sparse (e.g. bag-of-words), use `StandardScaler(with_mean=False)`.
 - ▶ encoding categorical variables.
 - ▶ **Best practice: reproducible data pipeline.**
- ▶ Train/Test Split:
 - ▶ ML models can achieve arbitrarily high accuracy in-sample, so performance should be evaluated out-of-sample.

Data Prep for Machine Learning

- ▶ Data Pre-Processing: See Geron Chapter 2 for pandas and sklearn syntax:
 - ▶ imputing missing values.
 - ▶ feature scaling (often helpful/necessary for ML models to work well)
 - ▶ if predictors are sparse (e.g. bag-of-words), use `StandardScaler(with_mean=False)`.
 - ▶ encoding categorical variables.
 - ▶ **Best practice: reproducible data pipeline.**
- ▶ Train/Test Split:
 - ▶ ML models can achieve arbitrarily high accuracy in-sample, so performance should be evaluated out-of-sample.
 - ▶ standard approach: randomly sample 80% training dataset to learn parameters, form predictions in 20% testing dataset for evaluating performance.

Use Cross-Validation During Model Training

- ▶ Within the training set:
 - ▶ Use cross-validation with grid search to get model performance metrics across subsets of data using different hyperparameter specs.
 - ▶ Find the best hyperparameters for out-of-fold prediction in the training set.
- ▶ Then evaluate model performance in the test set using these hyperparameters.

Use Cross-Validation During Model Training

- ▶ Within the training set:
 - ▶ Use cross-validation with grid search to get model performance metrics across subsets of data using different hyperparameter specs.
 - ▶ Find the best hyperparameters for out-of-fold prediction in the training set.
- ▶ Then evaluate model performance in the test set using these hyperparameters.
- ▶ Cross-validation is less common in deep learning, where training multiple models is too computationally expensive.
 - ▶ instead, use dropout and early stopping (next week).

Model Evaluation in Test Set

Evaluating a “good” model is context-dependent. Here are some basics.

Regression:

- ▶ mean squared error (MSE)
- ▶ R-squared (same ranking as MSE, but units are more interpretable)
- ▶ mean absolute error (MAE, $\sum |\hat{y}(\theta) - y|$) is less sensitive to outliers.

Model Evaluation in Test Set

Evaluating a “good” model is context-dependent. Here are some basics.

Regression:

- ▶ mean squared error (MSE)
- ▶ R-squared (same ranking as MSE, but units are more interpretable)
- ▶ mean absolute error (MAE, $\sum |\hat{y}(\theta) - y|$) is less sensitive to outliers.

Classification:

- ▶ more complicated, but accuracy is a good baseline:
accuracy = ($\#$ correct test-set predictions) / ($\#$ of test-set observations)

Model Evaluation in Test Set

Evaluating a “good” model is context-dependent. Here are some basics.

Regression:

- ▶ mean squared error (MSE)
- ▶ R-squared (same ranking as MSE, but units are more interpretable)
- ▶ mean absolute error (MAE, $\sum |\hat{y}(\theta) - y|$) is less sensitive to outliers.

Classification:

- ▶ more complicated, but accuracy is a good baseline:
accuracy = ($\#$ correct test-set predictions) / ($\#$ of test-set observations)
- ▶ What if one of the outcomes is over-represented – e.g., 19 out of 20? Then I can guess the modal class and get 95% accuracy.
 - ▶ Some alternative classifier metrics designed to address class imbalance (more below).

ML Essentials

Overview

Regression / Regularization

Binary Classification

Multi-Class Models

Osnabruegge, Ash, and Morelli 2020

Ensemble Learning with XGBoost

Regression models \leftrightarrow Continuous outcome

- ▶ If the outcome is continuous (e.g., Y = tax revenues collected, or criminal sentence imposed in months of prison):
 - ▶ Need a regression model.
- ▶ Problems with OLS:
 - ▶ tends to over-fit training data.
 - ▶ cannot handle multicollinearity.




Figure 4-14. High-degree Polynomial Regression

Regression models \leftrightarrow Continuous outcome

- ▶ If the outcome is continuous (e.g., Y = tax revenues collected, or criminal sentence imposed in months of prison):
 - ▶ Need a regression model.
- ▶ Problems with OLS:
 - ▶ tends to over-fit training data.
 - ▶ cannot handle multicollinearity.




Figure 4-14. High-degree Polynomial Regression

- ▶ **Regularization**: model training methods designed to reduce/prevent over-fitting.

Regularized Loss Function

$$\hat{\theta} = \arg \min_{\theta} \frac{1}{n_D} \sum_{i=1}^{n_D} L(h(\mathbf{x}_i; \theta), \mathbf{y}_i) + \lambda R(\theta)$$

- ▶ $R(\theta)$ is a “regularization function” or “regularizer”, designed to reduce over-fitting.
- ▶ λ is a hyperparameter where higher values increase regularization.

Regularized Loss Function

$$\hat{\theta} = \arg \min_{\theta} \frac{1}{n_D} \sum_{i=1}^{n_D} L(h(\mathbf{x}_i; \theta), \mathbf{y}_i) + \lambda R(\theta)$$

- ▶ $R(\theta)$ is a “regularization function” or “regularizer”, designed to reduce over-fitting.
- ▶ λ is a hyperparameter where higher values increase regularization.

In particular:

- ▶ “Lasso” (or L1) penalty:

$$R_1 = \|\theta\|_1 = \sum_{j=1}^{n_x} |\theta_j|$$

- ▶ shrinks coefficients toward zero. automatically performs feature selection and outputs a sparse model.

Regularized Loss Function

$$\hat{\theta} = \arg \min_{\theta} \frac{1}{n_D} \sum_{i=1}^{n_D} L(h(\mathbf{x}_i; \theta), \mathbf{y}_i) + \lambda R(\theta)$$

- ▶ $R(\theta)$ is a “regularization function” or “regularizer”, designed to reduce over-fitting.
- ▶ λ is a hyperparameter where higher values increase regularization.

In particular:

- ▶ “Lasso” (or L1) penalty:

$$R_1 = \|\theta\|_1 = \sum_{j=1}^{n_x} |\theta_j|$$

- ▶ shrinks coefficients toward zero. automatically performs feature selection and outputs a sparse model.
- ▶ “Ridge” (or L2) penalty:

$$R_2 = \|\theta\|_2^2 = \sum_{j=1}^{n_x} (\theta_j)^2$$

- ▶ shrinks coefficients toward zero and helps select between collinear predictors.

Regularized Loss Function

$$\hat{\theta} = \arg \min_{\theta} \frac{1}{n_D} \sum_{i=1}^{n_D} L(h(\mathbf{x}_i; \theta), \mathbf{y}_i) + \lambda R(\theta)$$

- ▶ $R(\theta)$ is a “regularization function” or “regularizer”, designed to reduce over-fitting.
- ▶ λ is a hyperparameter where higher values increase regularization.

In particular:

- ▶ “Lasso” (or L1) penalty:

$$R_1 = \|\theta\|_1 = \sum_{j=1}^{n_x} |\theta_j|$$

- ▶ shrinks coefficients toward zero. automatically performs feature selection and outputs a sparse model.
- ▶ “Ridge” (or L2) penalty:

$$R_2 = \|\theta\|_2^2 = \sum_{j=1}^{n_x} (\theta_j)^2$$

- ▶ shrinks coefficients toward zero and helps select between collinear predictors.
- ▶ Elastic Net: $R_{\text{enet}} = \lambda_1 R_1 + \lambda_2 R_2$

Causal Graphs Activity

<https://padlet.com/eash44/c0j5x4dwfc1evhgi>

ML Essentials

Overview

Regression / Regularization

Binary Classification

Multi-Class Models

Osnabruegge, Ash, and Morelli 2020

Ensemble Learning with XGBoost

Binary Outcome \leftrightarrow Binary Classification

- ▶ Binary classifiers try to match a boolean outcome $y \in \{0, 1\}$.
 - ▶ The standard approach is to apply a transformation (e.g. sigmoid/logit) to normalize $\hat{y} \in [0, 1]$.
 - ▶ Prediction rule is 0 for $\hat{y} < .5$ and 1 otherwise.


Binary Outcome \leftrightarrow Binary Classification

- ▶ Binary classifiers try to match a boolean outcome $y \in \{0, 1\}$.
 - ▶ The standard approach is to apply a transformation (e.g. sigmoid/logit) to normalize $\hat{y} \in [0, 1]$.
 - ▶ Prediction rule is 0 for $\hat{y} < .5$ and 1 otherwise.
- ▶ The binary cross-entropy (or log loss) is:

$$L(\theta) = \underbrace{-\frac{1}{n_D}}_{\text{negative}} \sum_{i=1}^{n_D} \left[\underbrace{y_i}_{y_i=1} \underbrace{\log(\hat{y}_i)}_{\log \text{ prob}_{y_i=1}} + \underbrace{(1-y_i)}_{y_i=0} \underbrace{\log(1-\hat{y}_i)}_{\log \text{ prob}_{y_i=0}} \right]$$


- In **logistic regression** we use a sigmoid transformation:

$$\hat{y} = \text{sigmoid}(\mathbf{x} \cdot \theta) = \frac{1}{1 + \exp(-\mathbf{x} \cdot \theta)}$$



- In **logistic regression** we use a sigmoid transformation:

$$\hat{y} = \text{sigmoid}(\mathbf{x} \cdot \theta) = \frac{1}{1 + \exp(-\mathbf{x} \cdot \theta)}$$




- Plugging into the binary-cross entropy loss gives the logistic regression cost objective:

$$\min_{\theta} \sum_{i=1}^{n_D} -y_i \log(\text{sigmoid}(\mathbf{x}_i \cdot \theta)) - [1 - y_i] \log(1 - \text{sigmoid}(\mathbf{x}_i \cdot \theta))$$

- does not have a closed form solution, but it is convex (guaranteeing that gradient descent will find the global minimum).

- In **logistic regression** we use a sigmoid transformation:

$$\hat{y} = \text{sigmoid}(\mathbf{x} \cdot \theta) = \frac{1}{1 + \exp(-\mathbf{x} \cdot \theta)}$$



- Plugging into the binary-cross entropy loss gives the logistic regression cost objective:


$$\min_{\theta} \sum_{i=1}^{n_D} -y_i \log(\text{sigmoid}(\mathbf{x}_i \cdot \theta)) - [1 - y_i] \log(1 - \text{sigmoid}(\mathbf{x}_i \cdot \theta))$$

- does not have a closed form solution, but it is convex (guaranteeing that gradient descent will find the global minimum).
- The gradient for one data point is

$$\frac{\partial L(\theta)}{\partial \theta_j} = \underbrace{(\text{sigmoid}(\mathbf{x}_i \cdot \theta) - y_i)}_{\text{error for obs } i} \underbrace{x_i^j}_{\text{input } j}$$

- In **logistic regression** we use a sigmoid transformation:

$$\hat{y} = \text{sigmoid}(\mathbf{x} \cdot \theta) = \frac{1}{1 + \exp(-\mathbf{x} \cdot \theta)}$$



- Plugging into the binary-cross entropy loss gives the logistic regression cost objective:

$$\min_{\theta} \sum_{i=1}^{n_D} -y_i \log(\text{sigmoid}(\mathbf{x}_i \cdot \theta)) - [1 - y_i] \log(1 - \text{sigmoid}(\mathbf{x}_i \cdot \theta))$$

- does not have a closed form solution, but it is convex (guaranteeing that gradient descent will find the global minimum).
- The gradient for one data point is

$$\frac{\partial L(\theta)}{\partial \theta_j} = \underbrace{(\text{sigmoid}(\mathbf{x}_i \cdot \theta) - y_i)}_{\text{error for obs } i} \underbrace{x_i^j}_{\text{input } j}$$

- Like linear regression, logistic regression can be regularized with L1 or L2 penalties.

A **Confusion Matrix** is a nice way to visualize classifier performance:

		Predicted Class	
		Negative	Positive
True Class	Negative	# True Negatives	# False Positives
	Positive	# False Negatives	# True Positives

- ▶ Cell values give counts in the test set.

A **Confusion Matrix** is a nice way to visualize classifier performance:

		Predicted Class	
		Negative	Positive
True Class	Negative	# True Negatives	# False Positives
	Positive	# False Negatives	# True Positives

- ▶ Cell values give counts in the test set.

$$\text{Accuracy} = \frac{\text{True Positives} + \text{True Negatives}}{\text{True Positives} + \text{False Positives} + \text{False Negatives} + \text{True Negatives}}$$

A **Confusion Matrix** is a nice way to visualize classifier performance:

		Predicted Class	
		Negative	Positive
True Class	Negative	# True Negatives	# False Positives
	Positive	# False Negatives	# True Positives

- ▶ Cell values give counts in the test set.

$$\text{Accuracy} = \frac{\text{True Positives} + \text{True Negatives}}{\text{True Positives} + \text{False Positives} + \text{False Negatives} + \text{True Negatives}}$$

$$\text{Precision (for positive class)} = \frac{\text{True Positives}}{\text{True Positives} + \text{False Positives}}$$

- ▶ Precision decreases with false positives. “When I guess this outcome, I tend to guesses correctly.”

A **Confusion Matrix** is a nice way to visualize classifier performance:

		Predicted Class	
		Negative	Positive
True Class	Negative	# True Negatives	# False Positives
	Positive	# False Negatives	# True Positives

- ▶ Cell values give counts in the test set.

$$\text{Accuracy} = \frac{\text{True Positives} + \text{True Negatives}}{\text{True Positives} + \text{False Positives} + \text{False Negatives} + \text{True Negatives}}$$

$$\text{Precision (for positive class)} = \frac{\text{True Positives}}{\text{True Positives} + \text{False Positives}}$$

- ▶ Precision decreases with false positives. “When I guess this outcome, I tend to guesses correctly.”

$$\text{Recall (for positive class)} = \frac{\text{True Positives}}{\text{True Positives} + \text{False Negatives}}$$

- ▶ Recall decreases with false negatives. “When this outcome occurs, I don’t miss it.”

If labels are (almost) balanced, then accuracy is a decent metric.

- ▶ If not (say 90% in one category), accuracy will be uninformative/misleading.

If labels are (almost) balanced, then accuracy is a decent metric.

- ▶ If not (say 90% in one category), accuracy will be uninformative/misleading.

Balanced accuracy = the average recall in both classes:

$$\text{Balanced Accuracy} = \frac{1}{2} \left(\frac{\text{TP}}{\text{TP} + \text{FN}} + \frac{\text{TN}}{\text{TN} + \text{FP}} \right)$$

- ▶ → equal to accuracy when classes are balanced, or when performance is the same across classes.

If labels are (almost) balanced, then accuracy is a decent metric.

- ▶ If not (say 90% in one category), accuracy will be uninformative/misleading.

Balanced accuracy = the average recall in both classes:

$$\text{Balanced Accuracy} = \frac{1}{2} \left(\frac{\text{TP}}{\text{TP} + \text{FN}} + \frac{\text{TN}}{\text{TN} + \text{FP}} \right)$$

- ▶ → equal to accuracy when classes are balanced, or when performance is the same across classes.

F_1 score = the harmonic mean of precision and recall:

$$F_1 = \frac{2}{\frac{1}{\text{precision}} + \frac{1}{\text{recall}}} = 2 \times \frac{\text{precision} \times \text{recall}}{\text{precision} + \text{recall}}$$

- ▶ penalizes both false positives and false negatives; still ignores true negatives.

If labels are (almost) balanced, then accuracy is a decent metric.

- ▶ If not (say 90% in one category), accuracy will be uninformative/misleading.

Balanced accuracy = the average recall in both classes:

$$\text{Balanced Accuracy} = \frac{1}{2} \left(\frac{\text{TP}}{\text{TP} + \text{FN}} + \frac{\text{TN}}{\text{TN} + \text{FP}} \right)$$

- ▶ → equal to accuracy when classes are balanced, or when performance is the same across classes.

F_1 score = the harmonic mean of precision and recall:


$$F_1 = \frac{2}{\frac{1}{\text{precision}} + \frac{1}{\text{recall}}} = 2 \times \frac{\text{precision} \times \text{recall}}{\text{precision} + \text{recall}}$$

- ▶ penalizes both false positives and false negatives; still ignores true negatives.

AUC-ROC = Area Under the Receiver Operating Characteristic Curve

- ▶ provides an aggregate measure of performance across all possible classification thresholds.
- ▶ Interpretation: randomly sample one positive and one negative example. AUC = probability that the model correctly guesses which is which.

Evaluating Classification Models: Calibration Curves



- ▶ Plotting the binned fraction in a category (Y axis) against the predicted probability in a category (X axis):
- ▶ Provides evidence of whether the classifier is replicating the conditional distribution of the outcome.

```
from seaborn import regplot  
regplot(y_test, y_pred, x_bins=20)
```

Application: Predicting Political Party from Text

Andrew Peterson and Arthur Spirling, “Classification accuracy as a substantive quantity of interest: Measuring polarization in Westminster systems,” *Political Analysis* (2018).

Application: Predicting Political Party from Text

Andrew Peterson and Arthur Spirling, “Classification accuracy as a substantive quantity of interest: Measuring polarization in Westminster systems,” *Political Analysis* (2018).

- ▶ Machine Learning Problem:
 - ▶ Corpus $D = 3.5\text{M}$ U.K. parliament speeches, 1935-2013.

Application: Predicting Political Party from Text

Andrew Peterson and Arthur Spirling, “Classification accuracy as a substantive quantity of interest: Measuring polarization in Westminster systems,” *Political Analysis* (2018).


- ▶ Machine Learning Problem:
 - ▶ Corpus $D = 3.5\text{M}$ U.K. parliament speeches, 1935-2013.
 - ▶ Label $Y =$ party of speaker (Conservative or Labour)

Application: Predicting Political Party from Text

Andrew Peterson and Arthur Spirling, “Classification accuracy as a substantive quantity of interest: Measuring polarization in Westminster systems,” *Political Analysis* (2018).

- ▶ Machine Learning Problem:
 - ▶ Corpus $D = 3.5\text{M}$ U.K. parliament speeches, 1935-2013.
 - ▶ Label $Y =$ party of speaker (Conservative or Labour)

In years that classifier is more accurate, speech is more polarized:



ML Essentials

Overview

Regression / Regularization

Binary Classification

Multi-Class Models

Osnabruegge, Ash, and Morelli 2020

Ensemble Learning with XGBoost

Multiple Classes: Setup

- ▶ The outcome is $y_i \in \{1, \dots, k, \dots, n_y\}$ output classes, which can also be represented as a one-hot vector

$$\mathbf{y}_i = \{\mathbf{1}[y_i = 1], \dots, \mathbf{1}[y_i = n_y]\}$$

Multiple Classes: Setup

- ▶ The outcome is $y_i \in \{1, \dots, k, \dots, n_y\}$ output classes, which can also be represented as a one-hot vector

$$\mathbf{y}_i = \{\mathbf{1}[y_i = 1], \dots, \mathbf{1}[y_i = n_y]\}$$

- ▶ We want to learn a vector function

$$\mathbf{y} = \mathbf{h}(\mathbf{x}, \theta)$$

taking text features \mathbf{x} as inputs and outputting a vector of probabilities across outcome classes:

$$\hat{\mathbf{y}} = \{\hat{y}^1, \dots, \hat{y}^{n_y}\}, \sum_{k=1}^{n_y} \hat{y}^k = 1, \hat{y}^k \geq 0 \quad \forall k$$

- ▶ for prediction step, can select the highest-probability class:

$$\tilde{y} = \arg \max_k \hat{y}_{[k]}$$

Categorical Cross Entropy

- ▶ The standard loss function in multinomial classification is **categorical cross entropy**:

$$L(\theta) = - \sum_{k=1}^{n_y} \mathbf{y}^k \log(\hat{y}^k(\mathbf{x}, \theta))$$

- ▶ measures dissimilarity between the true label distribution \mathbf{y} and the predicted label distribution $\hat{\mathbf{y}}$.

Categorical Cross Entropy

- ▶ The standard loss function in multinomial classification is **categorical cross entropy**:

$$L(\theta) = - \sum_{k=1}^{n_y} \mathbf{y}^k \log(\hat{y}^k(\mathbf{x}, \theta))$$

- ▶ measures dissimilarity between the true label distribution \mathbf{y} and the predicted label distribution $\hat{\mathbf{y}}$.
- ▶ Since there is just one true class ($y = 1$ for one class k^* , and zero for others), simplifies to

$$L(\theta) = -\log(\hat{y}^{k^*}(\mathbf{x}, \theta))$$

- ▶ Rewards putting higher probability on the true class, ignores distribution of probabilities on other classes.
- ▶ function is convex \rightarrow gradient descent will find the optimum.

Multinomial Logistic Regression

Multinomial logistic regression computes probabilities for each class k using the softmax transformation

$$\hat{y}_k(\mathbf{x}_i) = \Pr(y_i = k) = \frac{\exp(\theta'_k \mathbf{x}_i)}{\sum_{l=1}^{n_y} \exp(\theta'_l \mathbf{x}_i)}$$

- ▶ softmax is the multiclass generalization of sigmoid \rightarrow can then interpret \hat{y} as probabilities.
- ▶ n_x features and n_y output classes \rightarrow there is a $n_y \times n_x$ parameter matrix Θ , where the parameters for each class θ_k are stored as rows.

Multinomial Logistic Regression

Multinomial logistic regression computes probabilities for each class k using the softmax transformation

$$\hat{y}_k(\mathbf{x}_i) = \Pr(y_i = k) = \frac{\exp(\theta'_k \mathbf{x}_i)}{\sum_{l=1}^{n_y} \exp(\theta'_l \mathbf{x}_i)}$$

- ▶ softmax is the multiclass generalization of sigmoid \rightarrow can then interpret \hat{y} as probabilities.
- ▶ n_x features and n_y output classes \rightarrow there is a $n_y \times n_x$ parameter matrix Θ , where the parameters for each class θ_k are stored as rows.

The **L2-penalized logistic regression** has loss function

$$\mathcal{L}(\theta) = -\frac{1}{n_D} \sum_{i=1}^{n_D} \log \frac{\exp(\theta'_{k^*} \mathbf{x}_i)}{\sum_{l=1}^{n_y} \exp(\theta'_l \mathbf{x}_i)} + \lambda \sum_{j=1}^{n_x} \sum_{k=1}^{n_y} (\theta_{[j,k]})^2$$

- ▶ λ = strength of L2 penalty (could also add lasso penalty)
 - ▶ as before, predictors should be scaled to the same variance.

		Predicted Class		
		Class A	Class B	Class C
True Class	Class A	Correct A	A, classed as B	A, classed as C
	Class B	B, classed as A	Correct B	B, classed as C
	Class C	C, classed as A	C, classed as B	Correct C

More generally, with **multi-class confusion matrix** M with items M_{ij} (row i , column j):

$$\text{Precision for } k = \frac{\text{True Positives for } k}{\text{True Positives for } k + \text{False Positives for } k} = \frac{M_{kk}}{\sum_l M_{lk}}$$

$$\text{Recall for } k = \frac{\text{True Positives for } k}{\text{True Positives for } k + \text{False Negatives for } k} = \frac{M_{kk}}{\sum_l M_{kl}}$$

$$F_1(k) = 2 \times \frac{\text{precision}(k) \times \text{recall}(k)}{\text{precision}(k) + \text{recall}(k)}$$

		Predicted Class		
		Class A	Class B	Class C
True Class	Class A	Correct A	A, classed as B	A, classed as C
	Class B	B, classed as A	Correct B	B, classed as C
	Class C	C, classed as A	C, classed as B	Correct C

More generally, with **multi-class confusion matrix** M with items M_{ij} (row i , column j):

$$\text{Precision for } k = \frac{\text{True Positives for } k}{\text{True Positives for } k + \text{False Positives for } k} = \frac{M_{kk}}{\sum_l M_{lk}}$$

$$\text{Recall for } k = \frac{\text{True Positives for } k}{\text{True Positives for } k + \text{False Negatives for } k} = \frac{M_{kk}}{\sum_l M_{kl}}$$

$$F_1(k) = 2 \times \frac{\text{precision}(k) \times \text{recall}(k)}{\text{precision}(k) + \text{recall}(k)}$$

Can average these metrics across classes to get aggregate metrics.

- ▶ e.g., balanced accuracy = unweighted average of recalls across classes.
- ▶ can weight classes by their frequency in dataset

ML Essentials

Overview

Regression / Regularization

Binary Classification

Multi-Class Models

Osnabruegge, Ash, and Morelli 2020

Ensemble Learning with XGBoost

Cross-Domain (Transfer) Learning

- ▶ A recent but now widespread approach to machine learning is **transfer learning**:
 - ▶ train a model in a big labeled dataset
 - ▶ apply in a smaller (mostly) unlabeled dataset

Cross-Domain (Transfer) Learning

- ▶ A recent but now widespread approach to machine learning is **transfer learning**:
 - ▶ train a model in a big labeled dataset
 - ▶ apply in a smaller (mostly) unlabeled dataset
- ▶ In NLP:
 - ▶ transfer learning is intuitive because NLP tasks share common knowledge about language.
 - ▶ labeled data is scarce/expensive, so learn tasks on tons of unlabeled data.
 - ▶ reflected in success of pre-trained models, e.g. BERT and GPT.

This paper takes the idea of transfer learning to the political science context.

- ▶ Learn to predict political topics from text in a labeled corpus (party manifestos from Comparative Manifesto Project)

This paper takes the idea of transfer learning to the political science context.

- ▶ Learn to predict political topics from text in a labeled corpus (party manifestos from Comparative Manifesto Project)
- ▶ Apply model to classify topics in unlabeled corpus (parliamentary speeches).

This paper takes the idea of transfer learning to the political science context.

- ▶ Learn to predict political topics from text in a labeled corpus (party manifestos from Comparative Manifesto Project)
- ▶ Apply model to classify topics in unlabeled corpus (parliamentary speeches).
- ▶ Use for empirical analysis of electoral institutions and speech content.

Overview of Text Analysis Methods

	Dictionaries (Custom)	Dictionaries (Generic)	Topic Modeling	Within-Domain Supervised Learning	Cross-Domain Supervised Learning
Design/Annotation Costs	High	Low	Low	High	Moderate
Specificity	High	Moderate	Low	High	Moderate
Interpretability	High	High	Moderate	High	High
Validatability	Low	Low	Low	High	High

Breakout Groups: Section Responses

- ▶ See links in the chat.

ML Essentials

Overview

Regression / Regularization


Binary Classification

Multi-Class Models


Osnabruegge, Ash, and Morelli 2020

Ensemble Learning with XGBoost

XGBoost: Overview




XGBoost Ingredients: Decision Trees




Decision Trees

Classification Tree




- ▶ Decision trees learn a series of binary splits in the data based on hard thresholds.
 - ▶ if yes, go right; if no, go left.
- ▶ Can have additional splits as you move through the tree.
- ▶ fast and interpretable, but performance is often poor.

Voting Classifiers




- ▶ voting classifiers (ensembles of different models that vote on the prediction) generally out-perform the best classifier in the ensemble.
 - ▶ more diverse algorithms will make different types of errors, and improve your ensemble's robustness.

XGBoost Ingredients: Bootstrapping





Bootstrapping

- ▶ Rather than use the same data on different classifiers, one can use different subsets of the data on the same classifier:




- ▶ can also use different subsets of features across subclassifiers.

Bootstrapping Benefits



- ▶ A bootstrapped ensemble generally has a similar bias but lower variance than a single predictor trained on all the data.
- ▶ Predictors can be trained in parallel using separate CPU cores.

XGBoost Ingredients: Random Forests



Random Forests

Random Forests are optimized ensembles of bootstrapped decision trees:

```
from sklearn.ensemble import RandomForestClassifier  
rfc = RandomForestClassifier()  
rfc.fit(X,y)
```

Random Forests

Random Forests are optimized ensembles of bootstrapped decision trees:

```
from sklearn.ensemble import RandomForestClassifier  
rfc = RandomForestClassifier()  
rfc.fit(X,y)
```

1. Each voting tree gets its own sample of data.

Random Forests

Random Forests are optimized ensembles of bootstrapped decision trees:

```
from sklearn.ensemble import RandomForestClassifier  
rfc = RandomForestClassifier()  
rfc.fit(X,y)
```

1. Each voting tree gets its own sample of data.
2. At each tree split, a random sample of features is drawn, only those features are considered for splitting.

Random Forests

Random Forests are optimized ensembles of bootstrapped decision trees:

```
from sklearn.ensemble import RandomForestClassifier  
rfc = RandomForestClassifier()  
rfc.fit(X,y)
```


1. Each voting tree gets its own sample of data.
2. At each tree split, a random sample of features is drawn, only those features are considered for splitting.
3. For each tree, error rate is computed using data outside its bootstrap sample.

XGBoost Ingredients: Gradient Boosting

Bootstrap aggregating or Bagging is an ensemble meta-algorithm combining predictions from multiple decision trees through a majority voting mechanism


Models are built sequentially by minimizing the errors from previous models while increasing (or boosting) influence of high-performing models

Optimized Gradient Boosting algorithm through parallel processing, tree-pruning, handling missing values and regularization to avoid overfitting/bias



Gradient Boosting Machines

- ▶ Gradient boosting refers to an additive ensemble of trees:




- ▶ Adds additional layers of trees to fit the residuals of the first layers

XGBoost Ingredients

Bootstrap aggregating or Bagging is an ensemble meta-algorithm combining predictions from multiple decision trees through a majority voting mechanism

Models are built sequentially by minimizing the errors from previous models while increasing (or boosting) influence of high-performing models

Optimized Gradient Boosting algorithm through parallel processing, tree-pruning, handling missing values and regularization to avoid overfitting/bias



XGBoost

- ▶ Feurer et al (2018) find that XGBoost beats a sophisticated AutoML procedure with grid search over 15 classifiers and 18 data preprocessors.
- ▶ A good starting point for any machine learning task.

- ▶ easy to use
- ▶ actively developed
- ▶ efficient / parallelizable
- ▶ provides model explanations
- ▶ takes sparse matrices as input


```
from xgboost import XGBClassifier
model = XGBClassifier()

model.fit(X_train, y_train,
          early_stopping_rounds=10,
          eval_metric="logloss",
          eval_set=[(X_eval, y_eval)]
          )

y_pred = model.predict(X_test)
accuracy = accuracy_score(y_test, y_pred)
```



Tree Ensembles are Black Boxes

- Small decision trees have the advantage of being highly interpretable.



Tree Ensembles are Black Boxes

- ▶ Small decision trees have the advantage of being highly interpretable.



- ▶ Larger trees and ensembles (e.g. XGBoost) lose this nice feature.
- ▶ Best-performing ML models are hard to interpret because they use lots of features and exploit non-linearities and interactions.

Interpreting Tree Ensembles

XGBoost's Feature Importance Metric:

- ▶ At each decision node, compute **information gain** for feature j (**change in predicted probability**).
- ▶ Average across all nodes for each j .


Ranks predictors by their relative contributions.

```
from xgboost import plot_importance
plot_importance(xgb_reg, max_num_features=10)
```

Feature Importance

```
from xgboost import plot_importance  
plot_importance(xgb_reg, max_num_features=20)
```

<IPython.core.display.Javascript object>



1

- ▶ XGBoost provides a metric of feature importance that summarizes how well each feature contributes to predictive accuracy.

A baseline for machine learning using text

1. Take POS-filtered bigrams as inputs X .

A baseline for machine learning using text

1. Take POS-filtered bigrams as inputs X .
2. Select a machine learning model for predicting outcome y :
 - ▶ For regression (y is one-dimensional and continuous), elastic net or gradient boosted regressor.
 - ▶ For classification (y is discrete), L2-penalized logistic regression or gradient boosted classifier.

A baseline for machine learning using text

1. Take POS-filtered bigrams as inputs X .
2. Select a machine learning model for predicting outcome y :
 - ▶ For regression (y is one-dimensional and continuous), elastic net or gradient boosted regressor.
 - ▶ For classification (y is discrete), L2-penalized logistic regression or gradient boosted classifier.
 - ▶ *(If y is more complicated, e.g. a sequence of words, we use deep learning.)*

A baseline for machine learning using text

1. Take POS-filtered bigrams as inputs X .
2. Select a machine learning model for predicting outcome y :
 - ▶ For regression (y is one-dimensional and continuous), elastic net or gradient boosted regressor.
 - ▶ For classification (y is discrete), L2-penalized logistic regression or gradient boosted classifier.
 - ▶ *(If y is more complicated, e.g. a sequence of words, we use deep learning.)*
3. Use cross-validation grid search in training set to select model hyperparameters.
 - ▶ For classification, use cross entropy; for regression, use mean squared error.

A baseline for machine learning using text

1. Take POS-filtered bigrams as inputs X .
2. Select a machine learning model for predicting outcome y :
 - ▶ For regression (y is one-dimensional and continuous), elastic net or gradient boosted regressor.
 - ▶ For classification (y is discrete), L2-penalized logistic regression or gradient boosted classifier.
 - ▶ *(If y is more complicated, e.g. a sequence of words, we use deep learning.)*
3. Use cross-validation grid search in training set to select model hyperparameters.
 - ▶ For classification, use cross entropy; for regression, use mean squared error.
4. Evaluate model in held-out test set:
 - ▶ For classification, use balanced accuracy, confusion matrix, and calibration plot.
 - ▶ For regression, use R squared and binscatter plot.

A baseline for machine learning using text

1. Take POS-filtered bigrams as inputs X .
2. Select a machine learning model for predicting outcome y :
 - ▶ For regression (y is one-dimensional and continuous), elastic net or gradient boosted regressor.
 - ▶ For classification (y is discrete), L2-penalized logistic regression or gradient boosted classifier.
 - ▶ *(If y is more complicated, e.g. a sequence of words, we use deep learning.)*
3. Use cross-validation grid search in training set to select model hyperparameters.
 - ▶ For classification, use cross entropy; for regression, use mean squared error.
4. Evaluate model in held-out test set:
 - ▶ For classification, use balanced accuracy, confusion matrix, and calibration plot.
 - ▶ For regression, use R squared and binscatter plot.
5. Interpret the model predictions:
 - ▶ for gradient boosting, use feature importance ranking.
 - ▶ for linear models, examine coefficients
 - ▶ look at highest and lowest ranked documents for \hat{y}

A baseline for machine learning using text

1. Take POS-filtered bigrams as inputs X .
2. Select a machine learning model for predicting outcome y :
 - ▶ For regression (y is one-dimensional and continuous), elastic net or gradient boosted regressor.
 - ▶ For classification (y is discrete), L2-penalized logistic regression or gradient boosted classifier.
 - ▶ *(If y is more complicated, e.g. a sequence of words, we use deep learning.)*
3. Use cross-validation grid search in training set to select model hyperparameters.
 - ▶ For classification, use cross entropy; for regression, use mean squared error.
4. Evaluate model in held-out test set:
 - ▶ For classification, use balanced accuracy, confusion matrix, and calibration plot.
 - ▶ For regression, use R squared and binscatter plot.
5. Interpret the model predictions:
 - ▶ for gradient boosting, use feature importance ranking.
 - ▶ for linear models, examine coefficients
 - ▶ look at highest and lowest ranked documents for \hat{y}
6. Answer the research question!