

Multilingual Radiology Report Classification



Desmond Elliott

Language and Multimodal Processing Group

Department of Computer Science

University of Copenhagen

Medical

This talk


Everyone else here today

How Do Multilingual Language Models Remember Facts?

Constanza Fierro¹ Negar Foroutan¹ Desmond Elliott¹ Anders Søgaard¹

¹ Department of Computer Science, University of Copenhagen

² EPFL



Multilingual

FoodieQA: A Multimodal Dataset for Fine-Grained Understanding of Chinese Food Culture

Wenyan Li,¹ Xinyu Zhang,² Jiaang Li,¹ Qiwei Peng,¹ Raphael Tang,^{2,3} Li Zhou,^{4,5} Weijia Zhang,⁶ Guimin Hu,¹ Yifei Yuan,¹ Anders Søgaard,¹ Daniel Herschovich,¹ Desmond Elliott¹

¹University of Copenhagen ²University of Waterloo ³Comcast AI Technologies

⁴The Chinese University of Hong Kong, Shenzhen ⁵Shenzhen Research Institute of Big Data

⁶University of Amsterdam

Multi-Image VQA

哪一道菜属于川菜中的凉菜? Which is a cold dish in Sichuan cuisine?



Single-Image VQA

以下菜品是哪个地区的特色菜? Which region is this food a specialty?



Text QA

白切鸡的口味特色是? What is the flavor of 白切鸡?


- (A) 麻辣 (spicy) (B) 松软 (soft)
(C) 外焦里嫩 (crispy-tender) (D) 咸 (salty)

Multimodal

EFFICIENT TEST-TIME SCALING FOR SMALL VISION-LANGUAGE MODELS



Mehmet Onurcan Kaya^{1,2} Desmond Elliott^{3,2} Dim P. Papadopoulos^{1,2}

¹ Technical University of Denmark ² Pioneer Center for AI ³ University of Copenhagen



Radiology Report Classification

- Backbone of training imaging classification systems
 - regex is everywhere
 - SSL emerging as an alternative
 - This is compute-intensive compared to LLM knowledge
- Not much publicly shared data
 - MIMIC-CXR, CheXpert, etc.
- Disjoint findings labels
 - MIMIC-CXR: 15 findings
 - PadChest: 49 findings



How can we combine
publicly available radiology
report resources into a
single classification model?



Alice

MOSAIC: A Multilingual, Taxonomy-Agnostic, and Computationally Efficient Approach for Radiological Report Classification

**Alice Schiavone^{1,2}, Marco Fraccaro³, Lea Marie Pehrson^{1,4,5}, Silvia Ingala^{4,6}, Rasmus Bonnevie³
Michael Bachmann Nielsen⁵, Vincent Beliveau⁷, Melanie Ganz^{1,2}, Desmond Elliott¹**

¹Department of Computer Science, University of Copenhagen

²Neurobiology Research Unit, Copenhagen University Hospital

³Unumed Aps, ⁴Department of Diagnostic Radiology, Copenhagen University Hospital

⁵Department of Clinical Medicine, University of Copenhagen

⁶Cerebriu A/S, ⁷Institute for Human Genetics, Medical University of Innsbruck

Desiderata

- **Fully open source:** keep your medical data on-site
- **Accessible:** run and train on inexpensive general-purpose GPUs
 - training and inference on an 24GB RTX 3090
- **Multilingual:** works for any EU26 major language
 - only evaluated in 4 languages due to data availability
- **Flexible:** adapts to different findings labels with minimal intervention

The LLM money pit

The rich man experience:

- LLM can solve 6 additional **high-school** competition math problems (AIME) for 4.2M USD
 - Reaching 65% on the test (below the acceptance cutoff) using only 16 tries...






Figure 1 Predictably Scaling RL compute to 100,000 GPU Hours (a) We ran ScaleRL for 100k GPU hours on an 8B dense

Alexia Jolicoeur-Martineau, Mila,
October 2025



MOSAIC-4B and 12B

- Finetuned on 10K reports in English, Spanish, and French
 - QLoRA optimization on the Q,K,V, FF, and Output layers
 - Need maximum of 16.2G VRAM and 33 minutes for SFT
- Prompt-based inference that can predict up to 68 findings



1. CheX-GPT, 2. CASIA-CLS, 3. DanskBERT

Lucas Dixon, Google DeepMind

How [↑] I think
about LLMs...

An interpreter (that can translate
between languages, concepts, and styles)



**An improv
comedian**

**A fuzzy
database of
the web**

Prompt-based Inference Example

Require JSON-structured responses

You are a helpful radiology assistant. Given a radiology report, classify each abnormality into a class. Output a valid JSON with each abnormality as key, and the class as value. The keys must be {findings}. The values can be one of {classes}. The values have the following interpretation:

Define style of positive/uncertain findings

(1) the abnormality was mentioned, even with uncertainty, in the report, e.g. 'A large pleural effusion', 'The cardiac contours are stable.', 'The cardiac size cannot be evaluated.';

Negative mentions

(2) the abnormality was negatively mentioned in the report; e.g. 'No pneumothorax.'


Datasets

Dataset	Language	Modality	Number of Findings	Avg. Chars	Mention Classes	Train	Dev	Test
MIMIC-CXR	en	Chest X-Ray	14	760	+, -, ~	535	50	100
PadChest-GR	es, en	Chest X-Ray	49	115	+	1951	100	879
CASIA-CXR	fr	Chest X-Ray	5	400	+	7677	100	3334
DanskCXR	da	Chest X-Ray	48	312	+, -	1600	125	750
DanskMRI	da	Brain MRI	3	1941	+, -, ~	194	50	345

- Focus on publicly available datasets
 - 194-7600 training examples
 - 115–1941 characters
 - 3–49 findings across variable number of mention classes
- DanskMRI evaluates performance on different imaging modality

Which Backbone LLM?


- Setups:
 - Zero-shot prompting
 - Few-shot prompting
 - Dataset-specific fine-tuning
- Gemma and LLaMA LLMs
 - 3B–27B variants
 - General and **medical domain**



Finding 1: No substantial difference between
general / medical domain models


Finetuning on Public Datasets

- How does performance improve as we train on different label sets?




Finding 2: Improvements are additive and do not seem to interfere

New Dataset Adaptation



Finding 3: MOSAIC is a better starting point for new data



How Much Data Do You Need?



Finding 4: You don't need much data if you start from MOSAIC

Different Imaging Modality

- Adapt MOSAIC to predicting three findings in Epilepsy MRI reports



Finding 5: MOSAIC can be repurposed to a new modality

Open Directions

- **Multimodal inputs** could improve performance but how to handle reports from different imaging modalities
- **Simple text-only augmentation** could substantially improve performance [Aepli and Sennrich, 2022; Kaya et al. 2025]
- **Multi-agent LLMs** could better handle different mention classes
- **Broken tokenizers** could be fixed to further improve performance
 - See, e.g. TokenDist [Dobler et al. 2025]
- **Synthetic data generation** using self-consistency [Wang et al. 2023]

Conclusions

- Multilingual LLMs are radiology report classifiers
 - Handle different label sets
 - Handle reports from different imaging modalities
- Multilingual multi dataset SFT can reduce the total amount of data that needs expert annotation
 - Focus the time of our clinical colleagues on labelling lower-frequency findings or difficult examples
- MOSAIC is open source
 - Please tell us if it works for your data and language

References

- A. Schiavone M. Fraccaro, L. M. Pehrson, S. Ingala, R. Bonnevie, M. B. Nielsen, V. Beliveau, M. Ganz, and D. Elliott. 2025. MOSAIC: A Multilingual, Taxonomy-Agnostic, and Computationally Efficient Approach for Radiological Report Classification
- K. Dobler, D. Elliott, and G. de Melo. 2025. Token Distillation: Attention-aware Input Embeddings For New Tokens.
- M. O. Kaya, D. Elliott, and D. P. Papadopoulos. 2025. Efficient Test-Time Scaling for Small Vision-Language Models.
- Aepli and Sennrich. ACL 2022. Improving Zero-Shot Cross-lingual Transfer Between Closely Related Languages by Injecting Character-Level Noise.
- Wang et al. ICLR 2023. Self-Consistency Improves Chain of Thought Reasoning in Language Models.