Chapter 1 · Semester 1

PHYSICAL QUANTITIES AND MEASUREMENTS

Notes by Cikgu Suhaili

29 worked examples 1 simulation Exercises with answers

1.1 Dimensions of physical quantities

Physical quantity

is a quantity that can be **observed and measured**.

Basic (base) quantity

is a quantity that **cannot be derived from any other quantity**.

Derived quantity

is a quantity that is **derived from a combination of base quantities** by mathematical operations (multiplication and division).

SI units

- In 1960 the General Conference of Weights and Measures recommended one metric system of measurement for everyone: the International System of Units, abbreviated **SI** in all languages.
- SI comes from its French name, **Système International**.
- **Prefixes** represent larger or smaller values.

Table 1.1 SI base units

Base quantity	Unit	Symbol
length	metre	m
mass	kilogram	kg
time	second	s
electric current	ampere	A
temperature	kelvin	K
amount of substance	mole	mol
luminous intensity	candela	cd

Table 1.2 Prefixes for powers of ten

Power	Prefix	Symbol
10^{-12}	pico	p
10^{-9}	nano	n
10^{-6}	micro	μ
10^{-3}	milli	m
10^{-2}	centi	c
10^{-1}	deci	d
10^{3}	kilo	k
10^{6}	mega	M
10^{9}	giga	G

Table 1.3 Derived units

Quantity	Unit	In terms of base units
Velocity, v	m s^{-1}	m s^{-1}
Acceleration, a	m s^{-2}	m s^{-2}
Frequency, f	hertz, Hz	s^{-1}
Force, F	newton, N	kg m s^{-2}
Energy and work, W	joule, J	kg m^2 s^{-2}
Power, P	watt, W	kg m^2 s^{-3}
Pressure, p	pascal, Pa	kg m^{-1} s^{-2}

Unit conversion

Unit conversion

is a **procedure** of changing a physical quantity from one system of units to another. It is sometimes necessary, or more useful, to change from one set of units to another.

Conversions in the metric (mks) system you must be able to do:

$\text{km h}^{-1} \rightarrow \text{m s}^{-1}$ | $\text{mm}^3 \rightarrow \text{m}^3$ | $\text{g cm}^{-3} \rightarrow \text{kg m}^{-3}$ | $\text{K} \leftrightarrow \text{°C}$

Example 1.1

The speed of a car is **72 km/h**. What is the speed in $\textbf{m s}^{-1}$?

Solution

$$72\ \text{km h}^{-1} = \frac{72\ \text{km}}{1\ \text{hour}} = \frac{72\ (1000\ \text{m})}{3600\ \text{s}} = \mathbf{20\ m\,s^{-1}}$$

Example 1.2

The density of lead is 11.3 g cm^{-3}. What is the value in kilograms per cubic metre?

Solution

$$11.3\ \frac{\text{g}}{\text{cm}^3} = \frac{11.3 \times 10^{-3}\ \text{kg}}{(10^{-2}\ \text{m})^3} = \mathbf{1.13 \times 10^4\ kg\,m^{-3}}$$

Example 1.3

How many nanoseconds does it take for light to travel 1.00 km in vacuum?

Solution

$$\text{time} = \frac{\text{distance}}{\text{speed}} = \frac{10^3\ \text{m}}{3.00 \times 10^8\ \text{m s}^{-1}} = 3.33 \times 10^{-6}\ \text{s} = \mathbf{3.33 \times 10^3\ ns}$$

Exercises: unit conversion

1. A rectangular metal plate of thickness 2.5 mm is 50 mm long and 65 mm wide. Its mass is 60 g. Calculate (a) the distance round its edge, in metres, (b) the area of one of its flat faces, in m^2, (c) its

volume, in m^3, (d) its density, in kg m^{-3}.

Answer

(a) 0.230 m (b) 3.25×10^{-3} m^2 (c) 8.13×10^{-6} m^3 (d) 7380 kg m^{-3}

FULL SOLUTION

Convert to metres first: thickness = 2.5×10^{-3} m, length = 0.050 m, width = 0.065 m, mass = 0.060 kg.

(a) Distance round the edge = 2(l + w) = 2(0.050 + 0.065)

= **0.230 m**

(b) A = l × w = 0.050 × 0.065

= **3.25×10^{-3} m^2**

(c) V = A × t = $(3.25 \times 10^{-3})(2.5 \times 10^{-3})$

= 8.125×10^{-6} = **8.13×10^{-6} m^3**

(d) ρ = m / V = 0.060 / (8.125×10^{-6})

= **7.38×10^{3} kg m^{-3}** (7380 kg m^{-3})

2. A solid aluminium rod of length 0.2 m has a uniform diameter of 52 mm. The density of aluminium is 2700 kg m^{-3}. Calculate (a) its volume, in m^3, (b) its mass, in kg.

Answer

(a) 4.25×10^{-4} m^3 (b) 1.15 kg

FULL SOLUTION

r = d/2 = 52/2 = 26 mm = 0.026 m, L = 0.2 m

(a) $V = \pi r^2 L = \pi(0.026)^2(0.2)$

= **4.25×10^{-4} m^3**

(b) m = ρV = 2700 × 4.247×10^{-4}

= **1.15 kg**

3. (a) Calculate the volume of a steel sphere of diameter 12 mm. (b) Calculate the diameter of a steel sphere of volume 4.80 cm^3.

Answer

(a) 9.0×10^{-7} m^3 (b) 2.09×10^{-2} m

FULL SOLUTION

(a) r = 12/2 = 6 mm = 6.0×10^{-3} m

$V = (4/3)\pi r^3 = (4/3)\pi(6.0 \times 10^{-3})^3$

= 9.05×10^{-7} = **9.0×10^{-7} m^3**

(b) V = 4.80 cm^3 = 4.80×10^{-6} m^3

$r^3 = 3V/(4\pi) = 3(4.80 \times 10^{-6})/(4\pi) = 1.146 \times 10^{-6}$ m^3

r = 1.046×10^{-2} m

d = 2r = **2.09×10^{-2} m** (20.9 mm)

Dimensions

> **Dimension**
> of a physical quantity shows **how that quantity is related to the base quantities**.

- Symbol: [quantity] or [symbol of quantity].
- Example: [mass] = M or [m] = M. We say "the dimension of mass is M".

Base quantity	Dimension
[length] or [l]	L
[mass] or [m]	M
[time] or [t]	T
[current] or [I]	I
[temperature] or [T]	θ
[luminous intensity]	J
[amount of substance]	N

> **Dimensionless quantities**
> are quantities that have **no dimension and no unit**. All numerical values (numbers) and coefficients have no dimensions.

$$[2] = [\pi] = [\mu] = 1$$

Example 1.4

What are the dimensions of volume and velocity?

Solution

[volume] = [length] × [width] × [height] = L × L × L = $\mathbf{L^3}$

[velocity] = [displacement] ÷ [time] = $\mathbf{L\,T^{-1}}$

Exercise: dimensions

1. Find the dimensions of (a) density, (b) pressure, (c) work, (d) power.

Answer

(a) $\mathbf{M\,L^{-3}}$ **(b)** $\mathbf{M\,L^{-1}\,T^{-2}}$ **(c)** $\mathbf{M\,L^{2}\,T^{-2}}$ **(d)** $\mathbf{M\,L^{2}\,T^{-3}}$

FULL SOLUTION

(a) Density = mass / volume

[ρ] = M / L^3 = $\mathbf{M\,L^{-3}}$

(b) Pressure = force / area, and force = mass × acceleration, so [F] = M L T^{-2}

[p] = M L T^{-2} / L^2 = $\mathbf{M\,L^{-1}\,T^{-2}}$

(c) Work = force × displacement

[W] = (M L T^{-2})(L) = $\mathbf{M\,L^{2}\,T^{-2}}$

(d) Power = work / time

[P] = M L^2 T^{-2} / T = $\mathbf{M\,L^{2}\,T^{-3}}$

Applications of dimensions

Dimensional analysis can be used to

- **(a) verify (check) the homogeneity of an equation**. However, an equation that is dimensionally correct is not necessarily correct.
- **(b) construct an equation** from the given quantities.
- **(c) determine the dimension and unit** of a physical quantity in an equation.

Teacher's note

Dimension on the left-hand side = dimension on the right-hand side, and **each term in the equation has the same dimension**.

Rules for adding, multiplying and dividing

Addition or subtraction: A + B = C − D

$$[A] = [B] = [C] = [D]$$

Multiplication: A = B × C

$$[A] = [B] \times [C]$$

[B] and [C] may be equal or different. Distance $x = vt$: $[x] = [v][t]$ although $[v] \neq [t]$.

Division: $A = \frac{B}{C} \Rightarrow [A] = \frac{[B]}{[C]}$, and in general [B] ≠ [C] ≠ [A].

Example 1.5

Which is correct: (a) 2 m + 3 m = 8 m − 3 m or (b) 2 s + 3 kg = 8 m − 3 cm?

Solution

> **(a)** is correct: every term is a length, so every term has the same dimension, L. In (b) a time is added to a mass, which is meaningless.

Example 1.6

Multiplication: $1\ \text{m}^2 = 1\ \text{m} \times 1\ \text{m}$, and distance $x = vt$.

Solution

> $[x] = [v][t] = (\text{L}\,\text{T}^{-1})(\text{T}) = \text{L}$, even though $[v] \neq [t]$.

Example 1.7

Division: (i) $1\ \text{m}^2 = \frac{1\ \text{m}^3}{1\ \text{m}}$ (ii) $1\ \text{m s}^{-1} = \frac{1\ \text{m}}{1\ \text{s}}$

Solution

> The dimension of a quotient is the quotient of the dimensions: $\frac{\text{L}^3}{\text{L}} = \text{L}^2$ and $\frac{\text{L}}{\text{T}} = \text{L}\,\text{T}^{-1}$.

(a) To verify (check) the homogeneity of an equation

Step 1. Identify all the physical quantities in the equation.

Step 2. Write the dimension of each known physical quantity.

Step 3. Equate the dimensions of the quantities on both sides of the equation.

Step 4. The equation is **homogeneous** if the dimensions on both sides are **equal**.

Example 1.8

Show that the equation $v^2 = u^2 + 2as$ is homogeneous.

Solution

$[v]^2 = [\text{velocity}]^2 = \dfrac{[\text{displacement}]^2}{[\text{time}]^2} = \dfrac{\mathrm{L}^2}{\mathrm{T}^2} = \mathrm{L}^2\,\mathrm{T}^{-2}$

$[u]^2 = [\text{velocity}]^2 = \mathrm{L}^2\,\mathrm{T}^{-2}$

$[2][a][s] = (1)[\text{acceleration}][\text{displacement}] = \dfrac{[\text{velocity}]}{[\text{time}]}[\text{displacement}] = \dfrac{\mathrm{L}\,\mathrm{T}^{-1}}{\mathrm{T}}\,\mathrm{L} = \mathrm{L}^2\,\mathrm{T}^{-2}$

$[v]^2 = [u]^2 = [2][a][s]$: each term on both sides has the same dimension, so the equation is **dimensionally correct (homogeneous)**.

(b) To construct an equation from given quantities

Step 1. Write a general equation that relates all the quantities.

Step 2. Identify the dimensionless quantities.

Step 3. Write the dimension of every quantity on both sides.

Step 4. Equate the indices of each dimension on both sides.

Step 5. Determine the values of the indices.

Step 6. Rewrite the equation with the indices.

Example 1.10

Construct an expression for the period t of a simple pendulum which shows how t is related to the mass m of the bob, the length l of the string and the acceleration due to gravity g.

Solution

Step 1: let $t \propto m^x l^y g^z$, so $t = k\, m^x l^y g^z$

Step 2: k is a dimensionless constant; x, y, z are unknowns.

Step 3: $[t] = [k][m]^x[l]^y[g]^z \Rightarrow \mathrm{T} = \mathrm{M}^x \mathrm{L}^y (\mathrm{L\ T^{-2}})^z = \mathrm{M}^x \mathrm{L}^{y+z} \mathrm{T}^{-2z}$

Step 4: M: $0 = x$; L: $0 = y + z$; T: $1 = -2z$

Step 5: $z = -\frac{1}{2}$, $y = \frac{1}{2}$, $x = 0$

Step 6: $t = k\, m^0 l^{\frac{1}{2}} g^{-\frac{1}{2}}$, so $\boldsymbol{t = k\sqrt{\frac{l}{g}}}$

Example 1.11

The frequency of a simple pendulum depends only on its **length** and the **gravitational field strength**. Use dimensions to derive a possible form of the equation for the frequency.

Solution

Let $f \propto l^x g^y$, so $f = k\, l^x g^y$ (k dimensionless; x, y unknown)

$[f] = [k][l]^x[g]^y \Rightarrow \mathrm{T}^{-1} = (1)(\mathrm{L})^x(\mathrm{L\ T^{-2}})^y = \mathrm{L}^{x+y} \mathrm{T}^{-2y}$

T: $-1 = -2y$; L: $0 = x + y \Rightarrow y = \frac{1}{2}$, $x = -\frac{1}{2}$

$f = k\, l^{-\frac{1}{2}} g^{\frac{1}{2}}$, so $\boldsymbol{f = k\sqrt{\frac{g}{l}}}$

Exercises: homogeneity and constructing equations

1. The speed of a wave on a rope is $C = \sqrt{\frac{F}{m}}$. Check its homogeneity using dimensional analysis.

Answer

It is homogeneous when m is the mass per unit length (kg m^{-1}): $[F/m] = \frac{M\,L\,T^{-2}}{M\,L^{-1}} = L^2\,T^{-2}$, so $[\sqrt{(F/m)}] = L\,T^{-1} = [C]$.

FULL SOLUTION

Left side: $[C] = L\,T^{-1}$ (speed).

Right side: F is a force, $[F] = M\,L\,T^{-2}$; for the equation to work m must be the mass per unit length, $[m] = M\,L^{-1}$.

$[F/m] = M\,L\,T^{-2} / M\,L^{-1} = L^2\,T^{-2}$

$[\sqrt{(F/m)}] = (L^2\,T^{-2})^{1/2} = L\,T^{-1}$

Both sides have dimensions $L\,T^{-1}$, so **the equation is homogeneous** (with m as mass per unit length, kg m^{-1}).

2. Show whether each equation is homogeneous: $v = u + at^2$ and $s = ut + \frac{1}{2}at^2$.

Answer

$v = u + at^2$ is not homogeneous ($[at^2] = L$, but $[v] = L\,T^{-1}$). $s = ut + \frac{1}{2}at^2$ is homogeneous (every term L).

FULL SOLUTION

$v = u + at^2$:

$[v] = L\,T^{-1}$, $[u] = L\,T^{-1}$, $[at^2] = (L\,T^{-2})(T^2) = L$

The last term has different dimensions, so **$v = u + at^2$ is not homogeneous**.

$s = ut + \frac{1}{2}at^2$:

$[s] = L$, $[ut] = (L\,T^{-1})(T) = L$, $[\frac{1}{2}at^2] = (L\,T^{-2})(T^2) = L$ (½ is dimensionless)

Every term has dimension L, so **$s = ut + \frac{1}{2}at^2$ is homogeneous**.

3. A student suggests that the force F on a vertical wall due to a horizontal jet of liquid striking it is $F = k\rho Av$, where k is a dimensionless constant and ρ, A and v are the density of the liquid, the cross-sectional area of the jet and the speed of the jet. Is the expression dimensionally correct?

Answer

No. $[\rho Av] = (M\,L^{-3})(L^2)(L\,T^{-1}) = M\,T^{-1}$, but $[F] = M\,L\,T^{-2}$. ($F = k\rho Av^2$ would be homogeneous.)

FULL SOLUTION

$[F] = M\,L\,T^{-2}$

$[k\rho Av] = (1)(M\,L^{-3})(L^2)(L\,T^{-1}) = M\,T^{-1}$

$M\,T^{-1} \neq M\,L\,T^{-2}$, so **the expression is not dimensionally correct**.

Check of the suggested form: $[\rho A v^2] = (M\,L^{-3})(L^2)(L^2\,T^{-2}) = M\,L\,T^{-2} = [F]$, so $F = k\rho A v^2$ is homogeneous.

4. The time t taken by a body to fall freely from rest through a height h depends only on h and the acceleration due to gravity g. Using dimensions, find the equation relating t with h and g.

Answer

$$t = k\sqrt{\frac{h}{g}}$$

FULL SOLUTION

Let $t = k\,h^x\,g^y$, where k is a dimensionless constant.

Dimensions: $T = L^x\,(L\,T^{-2})^y = L^{x+y}\,T^{-2y}$

Compare powers of T: $-2y = 1 \Rightarrow y = -\frac{1}{2}$

Compare powers of L: $x + y = 0 \Rightarrow x = \frac{1}{2}$

$t = k\,h^{\frac{1}{2}}\,g^{-\frac{1}{2}}$, so **$t = k\sqrt{h/g}$**

(c) To determine the dimension and unit of a quantity in an equation

Step 1. Identify all the physical quantities in the equation.

Step 2. Write the dimension of each **known** physical quantity.

Step 3. Solve the equation to get the dimension of the **unknown** physical quantity.

Example 1.9

Find the dimension and unit of acceleration in the equation $v = u + at$.

Solution

$[v] = [u] = L\,T^{-1}$ and $[t] = T$

$v = u + at \therefore a = \frac{v-u}{t}$, so $[a] = \frac{[v-u]}{[t]} = \frac{L\,T^{-1}}{T}$

$[a] = L\,T^{-2}$; unit of a = **$m\,s^{-2}$**

Limitations of dimensional analysis

- It cannot determine numerical constants such as 2, π, ½ or e. For $T = 2\pi\sqrt{\frac{l}{g}}$ it gives only $T \propto \sqrt{\frac{l}{g}}$.
- It cannot tell whether terms are added or subtracted. In $s = ut + \frac{1}{2}at^2$, the factor ½ cannot be obtained.
- It cannot distinguish scalar quantities from vector quantities.
- It cannot handle trigonometric functions (sin θ, cos θ, tan θ).
- A dimensionally correct equation may still be physically incorrect.

Exam note: dimensional analysis only tests the homogeneity of an equation; it cannot prove that the equation is physically correct.

STPM Practice 1.1 · Question 1

A sphere moving through a fluid experiences a viscous drag force $F = 6\pi\eta r v$, where r is the radius, v the speed and η the coefficient of viscosity. Determine the dimensions and the SI base unit of η. [4 marks]

Solution

$[F] = \mathrm{M\,L\,T^{-2}}$, $[r] = \mathrm{L}$, $[v] = \mathrm{L\,T^{-1}}$ (6π is dimensionless)

$$[\eta] = \frac{[F]}{[r][v]} = \frac{\mathrm{M\,L\,T^{-2}}}{\mathrm{L \cdot L\,T^{-1}}} = \mathrm{M\,L^{-1}\,T^{-1}}$$

Dimension of η = $\mathrm{M\,L^{-1}\,T^{-1}}$; SI unit = **kg m^{-1} s^{-1}**

STPM Practice 1.1 · Question 2

Using dimensional analysis, show that $p = \rho g h + \tfrac{1}{2}\rho v^2$ is homogeneous, where p is pressure, ρ density, g the acceleration of free fall, h height and v speed. [4 marks]

Solution

$[p]$ = force/area = $\dfrac{\mathrm{M\,L\,T^{-2}}}{\mathrm{L^2}} = \mathrm{M\,L^{-1}\,T^{-2}}$

$[\rho g h] = (\mathrm{M\,L^{-3}})(\mathrm{L\,T^{-2}})(\mathrm{L}) = \mathrm{M\,L^{-1}\,T^{-2}}$

$[\tfrac{1}{2}\rho v^2] = (\mathrm{M\,L^{-3}})(\mathrm{L\,T^{-1}})^2 = \mathrm{M\,L^{-1}\,T^{-2}}$

All three terms have the same dimension, $\mathrm{M\,L^{-1}\,T^{-2}}$, so the equation is **homogeneous**.

STPM Practice 1.1 · Question 3

The period T of a small liquid drop oscillating under surface tension may depend on its density ρ, radius r and surface tension σ (SI unit N m^{-1}). Use dimensional analysis to derive an expression for T. [6 marks]

Solution

Let $T = k\rho^a r^b \sigma^c$ (k dimensionless)

$[\sigma] = \mathrm{N\,m^{-1}} = \dfrac{\mathrm{M\,L\,T^{-2}}}{\mathrm{L}} = \mathrm{M\,T^{-2}}$

$\mathrm{T} = (\mathrm{M\,L^{-3}})^a(\mathrm{L})^b(\mathrm{M\,T^{-2}})^c = \mathrm{M}^{a+c}\,\mathrm{L}^{b-3a}\,\mathrm{T}^{-2c}$

M: $a + c = 0$; T: $-2c = 1$; L: $b - 3a = 0 \Rightarrow c = -\tfrac{1}{2}$, $a = \tfrac{1}{2}$, $b = 3/2$

$$T = k\rho^{1/2} r^{3/2} \sigma^{-1/2} = k\sqrt{\frac{\rho r^3}{\sigma}}$$

1.2 Scalars and vectors

Scalar quantity


is a quantity which has **magnitude only**. Examples: mass, temperature, kinetic energy, time and density.

Vector quantity

is a quantity which has **both magnitude and direction**. Examples: displacement, velocity, acceleration, force and momentum.


Properties of two vectors

(a) Equality of two vectors: two vectors are equal only when they have the **same magnitude** and the **same direction**.



$A = B$
(parallel)

(b) Negative of a vector: it has the **same magnitude** as the original vector but the **opposite direction**.



−A: same size, opposite direction
(antiparallel)


Vector addition

Two methods of finding the resultant vector:


- **(a) Graphical method**: (i) tail to tip (triangle and polygon methods); (ii) parallelogram.
- **(b) Component method**: by calculation.
- The graphical (tail-to-tip) method obeys the **commutative**, **associative** and **distributive** laws.

Commutative law: $A + B = B + A$

The arrow drawn from the **tail** of the first vector to the **tip** of the second represents the sum (resultant). This is the **triangle method**.




Associative law (more than two vectors): $(\boldsymbol{v}_1 + \boldsymbol{v}_2) + \boldsymbol{v}_3 = \boldsymbol{v}_1 + (\boldsymbol{v}_2 + \boldsymbol{v}_3)$. This is the **polygon method**.




Either grouping gives the same resultant (red).

Distributive law: $m(A + B) = mA + mB$




Parallelogram method (for two vectors): V_R is the **diagonal** of the parallelogram and represents the sum, or resultant, of the two vectors.



Simulation

Vector addition: tail to tip, parallelogram and components

Drag the sliders to change the two vectors. Switch between the triangle and parallelogram methods, and watch the component table add up to the same resultant.



$\lvert R\rvert = \sqrt{(R_x^2 + R_y^2)}$	direction from +x axis	angle between A and B	$A \cdot B = AB\cos\theta$
9.96	**74.0°**	**105°**	**−12.94**

$\lvert A \times B\rvert = AB\sin\theta$
48.30

This is a still picture. Open PhysiQ › Notes › Semester 1 › Chapter 1 to use the simulation.

Scalar (dot) product and vector (cross) product

Scalar (dot) product
of two vectors $\boldsymbol{A}$ and $\boldsymbol{B}$ is a **scalar**.

$$\boldsymbol{A} \cdot \boldsymbol{B} = AB\cos\theta$$

θ is the angle between $\boldsymbol{A}$ and $\boldsymbol{B}$ (0° ≤ θ ≤ 180°). Component form: $\boldsymbol{A} \cdot \boldsymbol{B} = A_x B_x + A_y B_y$.

- $\boldsymbol{A} \cdot \boldsymbol{B} = \boldsymbol{B} \cdot \boldsymbol{A}$ (commutative)
- $\boldsymbol{A} \cdot \boldsymbol{B} = 0$ when $\boldsymbol{A} \perp \boldsymbol{B}$ (θ = 90°)
- Maximum when θ = 0° (parallel); $\boldsymbol{A} \cdot \boldsymbol{A} = A^2$

Vector (cross) product
of two vectors $\boldsymbol{A}$ and $\boldsymbol{B}$ is a **vector**.

$$|\boldsymbol{A} \times \boldsymbol{B}| = AB\sin\theta$$

Its direction is perpendicular to the plane of $\boldsymbol{A}$ and $\boldsymbol{B}$, given by the right-hand rule. In the x-y plane: $\boldsymbol{A} \times \boldsymbol{B} = (A_x B_y - A_y B_x)\,\boldsymbol{k}$.

- $\boldsymbol{A} \times \boldsymbol{B} = -(\boldsymbol{B} \times \boldsymbol{A})$ (anti-commutative)
- $\boldsymbol{A} \times \boldsymbol{B} = 0$ when $\boldsymbol{A} \parallel \boldsymbol{B}$ (θ = 0° or 180°)
- Maximum when θ = 90°; $|\boldsymbol{A} \times \boldsymbol{B}|$ = area of the parallelogram

Worked example · scalar product

Two coplanar vectors $\boldsymbol{A}$ and $\boldsymbol{B}$ have magnitudes A = 5.0 N and B = 4.0 N. The angle between them is 60°. Find $\boldsymbol{A} \cdot \boldsymbol{B}$.

Solution

$\boldsymbol{A} \cdot \boldsymbol{B} = AB\cos\theta = (5.0)(4.0)\cos 60° = 20 \times 0.5 =$ **10** (a scalar)

Worked example · vector product

For the same two vectors (5.0 N and 4.0 N at 60°), find the magnitude of $\boldsymbol{A} \times \boldsymbol{B}$.

Solution

$|\boldsymbol{A} \times \boldsymbol{B}| = AB\sin\theta = (5.0)(4.0)\sin 60° = 20 \times 0.866 =$ **17.3** (a vector)

Direction: perpendicular to the plane of $\boldsymbol{A}$ and $\boldsymbol{B}$ (right-hand rule).


Scalar product	Vector product
$A \cdot B = AB \cos \theta$	$\lvert A \times B \rvert = AB \sin \theta$
Result is a scalar	Result is a vector
Used in work done	Used in torque
$A \cdot B = B \cdot A$	$A \times B \neq B \times A$
Zero when $\theta = 90°$	Zero when $\theta = 0°$
Maximum at $\theta = 0°$	Maximum at $\theta = 90°$

Component method

A vector V is resolved into x and y components, V_x and V_y. From simple trigonometry:

$$V_x = V \cos \theta$$

$$V_y = V \sin \theta$$



The **magnitude** of the resultant:

$$V = \sqrt{V_x^2 + V_y^2}$$

The **direction** of the resultant is the angle θ between V and the positive x-axis:

$$\tan \theta = \frac{V_y}{V_x}$$

Example 1.12


Calculate the horizontal and vertical components of a force of 50 N acting at 40° to the horizontal.

Solution

Step 1: sketch the force on the Cartesian axes. **Step 2**: find the x and y components.


Horizontal component = 50 cos 40° = **38 N**

Vertical component = 50 sin 40° = **32 N**



Example 1.13

Find the resultant of the forces shown.



Solution


Step 1: find the x and y components of each force.

Force	x-component	y-component
10 N	10 cos 45° = +7.07 N	10 sin 45° = +7.07 N
5 N	−5 cos 30° = −4.33 N	5 sin 30° = +2.50 N

Step 2: $\Sigma F_x = +7.07 - 4.33 = 2.74$ N; $\Sigma F_y = +7.07 + 2.50 = 9.57$ N

Step 3: $F = \sqrt{(\Sigma F_x)^2 + (\Sigma F_y)^2} = \sqrt{(2.74)^2 + (9.57)^2}$ = **9.95 N**

Step 4: $\theta = \tan^{-1}\dfrac{9.57}{2.74} = 74°$. **The resultant is 9.95 N at 74° to the positive x-axis.**



STPM Practice 1.2 · Question 1

Two forces of 8.0 N and 6.0 N act at a point. The angle between them is 60°. Determine the magnitude and direction of the resultant force. [5 marks]

Solution

Resolve along the 8.0 N force (x-axis): $F_x = 8.0 + 6.0 \cos 60° = 11.0$ N; $F_y = 6.0 \sin 60° = 5.20$ N

$R = \sqrt{11.0^2 + 5.20^2} = \sqrt{148} = \mathbf{12.2\ N}$

$\theta = \tan^{-1}\dfrac{5.20}{11.0} = \mathbf{25.3°}$ from the 8.0 N force

STPM Practice 1.2 · Question 2

Two vectors are $\boldsymbol{A} = 3\boldsymbol{i} + 4\boldsymbol{j}$ and $\boldsymbol{B} = 5\boldsymbol{i} - 12\boldsymbol{j}$. Find (a) the scalar product $\boldsymbol{A} \cdot \boldsymbol{B}$, (b) the angle between $\boldsymbol{A}$ and $\boldsymbol{B}$. [5 marks]

Solution

(a) $\boldsymbol{A} \cdot \boldsymbol{B} = A_xB_x + A_yB_y = (3)(5) + (4)(-12) = 15 - 48 = \mathbf{-33}$

(b) $|\boldsymbol{A}| = \sqrt{3^2 + 4^2} = 5$; $|\boldsymbol{B}| = \sqrt{5^2 + 12^2} = 13$

$\cos\theta = \dfrac{-33}{(5)(13)} = -0.508 \Rightarrow \theta = \mathbf{120.5°}$

STPM Practice 1.2 · Question 3

A force $\boldsymbol{F} = (3\boldsymbol{i} + 4\boldsymbol{j})$ N acts at a point with position vector $\boldsymbol{r} = (2\boldsymbol{i} - \boldsymbol{j})$ m from a fixed axis. Using the vector product, calculate the torque of the force about the axis. [4 marks]

Solution

$\tau = \boldsymbol{r} \times \boldsymbol{F} = (r_x F_y - r_y F_x)\,\boldsymbol{k}$

$= [(2)(4) - (-1)(3)]\,\boldsymbol{k} = (8 + 3)\,\boldsymbol{k} =$ **11 $\boldsymbol{k}$ N m**

Magnitude 11 N m, directed out of the plane (anticlockwise rotation).

1.3 Uncertainties in measurements

Learning outcome (a): explain systematic errors and random errors in measurements.

The error in a measurement is decided by the instruments used and the physical constraints of the observer. The two main types are **systematic error** and **random error**.

Random error

(chance error) is a deviation between an observed value and the true value due to **unpredictable and fluctuating factors** during measurement.

- It makes readings **scatter** about the true value.
- Individual readings may be higher or lower than the true value.
- **Reduced** by taking repeated measurements and using the mean, and by increasing the sample size.

Common sources: parallax errors, the sensitivity of an instrument, the physical constraints of the observer, poorly controlled procedures.

Systematic error

is an error that **occurs consistently**, or changes in a predictable way, every time a measurement is made.

- All readings are shifted from the true value by the same amount in the same direction.
- **Eliminated** by improving the measurement method, e.g. using a different instrument.

Common sources: zero errors, instrumental error, incorrect assumptions.

Every measurement has an uncertainty, limited by the instrument and the observer. For example, the length of A4 paper measured with a metre ruler (error 0.1 cm) is written **29.7 ± 0.1 cm**.

(b) Uncertainty from repeated measurements: standard deviation

Standard deviation

expresses **by how much the members of a group differ from the mean value** of the group.

$$\sigma = \sqrt{\frac{\Sigma(x - \bar{x})^2}{N - 1}}$$

Standard deviation · Example

The diameter of a boiling tube is measured five times: 31.33, 31.15, 31.26, 31.02 and 31.20 mm. Find the mean, the average deviation and the standard deviation.

Solution

$$\text{Mean} = \frac{\text{sum of readings}}{\text{number of readings}} = \frac{155.96 \text{ mm}}{5} = \mathbf{31.19 \text{ mm}}$$

Reading	Diameter / mm	Deviation / mm
1	31.33	+0.14
2	31.15	−0.04
3	31.26	+0.07
4	31.02	−0.17
5	31.20	+0.01

Average deviation, d = **0.086 mm**

$$\sigma = \sqrt{\frac{(0.14)^2 + (-0.04)^2 + (0.07)^2 + (-0.17)^2 + (0.01)^2}{5 - 1}} = \mathbf{0.12 \text{ mm}}$$

(c) Uncertainty in a derived quantity

Trigonometric functions are not required. (d) Give a derived quantity to an appropriate number of significant figures.

$$Z = A \pm B \Rightarrow \Delta Z = \Delta A + \Delta B$$

$$Z = AB \text{ or } \frac{A}{B} \Rightarrow \frac{\Delta Z}{Z} = \frac{\Delta A}{A} + \frac{\Delta B}{B}$$

$$Z = A^n \Rightarrow \frac{\Delta Z}{Z} = n\frac{\Delta A}{A}$$

Adding or subtracting: add the absolute uncertainties. Multiplying or dividing: add the fractional uncertainties.

Addition and subtraction · Example 1

Mass of beaker with liquid, m_1 = (32.0 ± 0.1) g; mass of beaker, m_2 = (3.0 ± 0.1) g. Calculate the mass of the liquid.

Solution


Mass of liquid = $m_1 - m_2$ = 32.0 − 3.0 = 29.0 g

Absolute uncertainty = 0.1 + 0.1 = 0.2 g

Mass of liquid = (29.0 ± 0.2) g

Addition and subtraction · Example 2

External diameter of a test tube, D = (1.23 ± 0.01) cm; internal diameter, d = (1.13 ± 0.01) cm. Calculate the thickness of the wall.



Solution

Thickness, $t = \dfrac{D - d}{2} = \dfrac{1.23 - 1.13}{2} = 0.05$ cm

$\Delta t = ½\Delta D + ½\Delta d = ½(0.01) + ½(0.01) = 0.01$ cm

Thickness = (0.05 ± 0.01) cm

Multiplication and division · Example

The dimensions of a piece of A4 paper are x = (297 ± 1) mm and y = (209 ± 1) mm. Calculate the area.

Solution

Area $A = xy = 297 \times 209 = 62\,073$ mm^2

$\dfrac{\Delta A}{A} = \dfrac{\Delta x}{x} + \dfrac{\Delta y}{y} \Rightarrow \Delta A = (\dfrac{1}{297} + \dfrac{1}{209})(62\,073) = 506$ mm^2 $= 5 \times 10^2$ mm^2 (1 s.f.)

Area, A = (6.21 ± 0.05) × 10^4 mm^2

STPM Practice 1.3 · Question 1

A student records five readings of the diameter of a wire (in mm): 0.52, 0.54, 0.53, 0.55, 0.51. Determine (a) the mean diameter, (b) the standard deviation, (c) the diameter with its uncertainty. [6 marks]

Solution

(a) $\bar{x} = \dfrac{0.52 + 0.54 + 0.53 + 0.55 + 0.51}{5} = \mathbf{0.530\ mm}$

(b) Deviations: −0.01, +0.01, 0.00, +0.02, −0.02; $\Sigma(x - \bar{x})^2 = 0.0010\ \text{mm}^2$

$\sigma = \sqrt{\dfrac{0.0010}{4}} = \mathbf{0.016\ mm}$

(c) **Diameter = (0.530 ± 0.016) mm**

STPM Practice 1.3 · Question 2

A small cube has mass m = (24.0 ± 0.1) g and side L = (2.00 ± 0.01) cm. Calculate its density $\rho = m/L^3$ and the uncertainty in the density. [6 marks]

Solution

$V = L^3 = 8.00\ \text{cm}^3$; $\rho = \dfrac{24.0}{8.00} = 3.00\ \text{g cm}^{-3}$

$\dfrac{\Delta\rho}{\rho} = \dfrac{\Delta m}{m} + 3\dfrac{\Delta L}{L} = \dfrac{0.1}{24.0} + 3\left(\dfrac{0.01}{2.00}\right) = 0.00417 + 0.0150 = 0.0192$

$\Delta\rho = 0.0192 \times 3.00 = 0.06\ \text{g cm}^{-3}$; **$\rho = (3.00 \pm 0.06)\ \text{g cm}^{-3}$**

STPM Practice 1.3 · Question 3

In a cooling experiment the initial temperature is $\theta_1 = (75.5 \pm 0.5)$ °C and the final temperature is $\theta_2 = (28.0 \pm 0.5)$ °C. Calculate the temperature change and its uncertainty, to an appropriate number of significant figures. [4 marks]

Solution

$\Delta\theta = \theta_1 - \theta_2 = 75.5 - 28.0 = 47.5$ °C

For subtraction the absolute uncertainties add: $0.5 + 0.5 = 1.0$ °C

$\Delta\theta = (47.5 \pm 1.0)$ °C

STPM specimen question

In determining the density of a solid sphere, a student measures its diameter and its mass. The percentage errors in the diameter and the mass are 2.0% and 3.0% respectively. What is the percentage error in the density of the sphere?

A. 5.0%

B. 8.0%

C. 9.0%

D. 11%

Answer

Answer: C

$\rho = \frac{m}{V}$ and $V = \frac{4}{3}\pi r^3$. Since $r = d/2$, $V \propto d^3$, so $\rho \propto \frac{m}{d^3}$

$\frac{\Delta\rho}{\rho} = \frac{\Delta m}{m} + 3\frac{\Delta d}{d} = 3.0\% + 3(2.0\%) =$ **9.0%**

STPM examination tips


- ✔ **Dimensions**: express dimensions using base quantities (M, L, T) only.
- ✔ **Homogeneity**: every term in an equation must have the same dimensions.
- ✔ **Constructing equations**: equate the indices of M, L and T separately.
- ✔ **Uncertainties**: for × and ÷, add the percentage uncertainties.
- ✔ **Significant figures**: the answer is no more accurate than the least accurate measurement.

Common mistakes

- ✖ mixing dimensions with units
- ✖ using T for the temperature dimension (it is θ)
- ✖ forgetting powers in uncertainty calculations
- ✖ assuming a homogeneous equation is automatically correct

Physics in Real Life

Real-world videos for this chapter. Tap a picture to play it here.



REAL EVENT

When NASA Lost a Spacecraft Because It Didn't Use Metric · It Happened in Space

Open in YouTube ↗

A spacecraft lost to a unit mistake

One team worked in pound-force seconds and the other in newton seconds; the mismatch sent the Mars Climate Orbiter too close to Mars. Units and dimensions must be checked in every calculation.