User Guide

How to run TIVIDY on Windows:

1. Check you have g++ (one-time setup)

Open PowerShell and run:

g++ --version

If it says "not recognized":

- Install MSYS2 from msys2.org

- Open the "MSYS2 UCRT64" terminal and run: pacman -S mingw-w64-ucrt-x86_64-gcc

- Add C:\msys64\ucrt64\bin to your Windows PATH, then open a NEW PowerShell window

2. Get the latest main

cd <your repo folder>

git checkout main

git pull

3. Build and run (in PowerShell, NOT Git Bash, where linking can fail)

Set-ExecutionPolicy -Scope Process Bypass

.\web\build.ps1 -Clean

.\web\run.ps1

Then open http://localhost:8080 (it may open by itself).

4. Stop it with Ctrl+C in that PowerShell window.

Using TIVIDY:

- "+ New workflow" opens the 6-step wizard. Pick a template (University admission or Patient booking) or start from scratch, then click "Create workflow" and it gets its own tab.

- Start a case, then assign/start/complete steps and watch the "Patterns in action" panel.

- "Reset demo" clears everything. Nothing is saved.

- The full 10-minute demo script is in web/README.md. Please run through it once before the demo so we all know it.

Optional: to run the 71 API checks, start the server, then open a SECOND PowerShell window in the repo folder and run:

Set-ExecutionPolicy -Scope Process Bypass

.\web\tests\api-smoke.ps1

If something goes wrong:

- "not recognized" for .\web\...: you're not in the repo folder. cd into it first.

- "running scripts is disabled": run the Set-ExecutionPolicy line again (it only lasts for that window).

- "Access denied" / "Permission denied" when building: the server is still running. Stop it with:

Get-Process tividy-web -ErrorAction SilentlyContinue | Stop-Process -Force

If your repo is in OneDrive, pausing OneDrive sync can also help.

- After pulling new engine changes, always rebuild with .\web\build.ps1 -Clean before running.

- Mac users: the scripts are Windows-only for now.