STM32
CubeMX

1. Description

1.1. Project

Project Name	stm32-freertos
Board Name	STM32L476G-DISCO
Generated with:	STM32CubeMX 6.11.0
Date	04/05/2024

1.2. MCU

MCU Series	STM32L4
MCU Line	STM32L4x6
MCU name	STM32L476VGTx
MCU Package	LQFP100
MCU Pin number	100

1.3. Core(s) information

Core(s)	Arm Cortex-M4

2. Pinout Configuration



3. Pins Configuration

Pin Number LQFP100	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
1	PE2	I/O	SAI1_MCLK_A	SAI1_MCK [CS43L22_MCLK]
2	PE3 *	I/O	GPIO_Output	AUDIO_RST [CS43L22_RESET]
3	PE4	I/O	SAI1_FS_A	SAI1_FS [CS43L22_LRCK]
4	PE5	I/O	SAI1_SCK_A	SAI1_SCK [CS43L22_SCLK]
5	PE6	I/O	SAI1_SD_A	SAI1_SD [CS43L22_SDIN]
6	VBAT	Power		
7	PC13	I/O	GPIO_EXTI13	MFX_IRQ_OUT [MFX_V2_IRQOUT]
8	PC14-OSC32_IN (PC14)	I/O	RCC_OSC32_IN	
9	PC15-OSC32_OUT (PC15)	I/O	RCC_OSC32_OUT	
10	VSS	Power		
11	VDD	Power		
12	PH0-OSC_IN (PH0)	I/O	RCC_OSC_IN	
13	PH1-OSC_OUT (PH1)	I/O	RCC_OSC_OUT	
14	NRST	Reset		
15	PC0 *	I/O	GPIO_Input	
16	PC1 *	I/O	GPIO_Input	MAG_INT [LSM303CTR_MAG_INT]
17	PC2 *	I/O	GPIO_Input	MAG_DRDY [LSM303CTR_DRDY_MAG]
18	PC3	I/O	LCD_VLCD	VLCD
19	VSSA	Power		
20	VREF-	Power		
22	VDDA	Power		
23	PA0 *	I/O	GPIO_Input	JOY_CENTER [MT-008A_CENTER]
24	PA1 *	I/O	GPIO_Input	JOY_LEFT [MT-008A_LEFT]
25	PA2 *	I/O	GPIO_Input	JOY_RIGHT [MT-008A_RIGHT]
26	PA3 *	I/O	GPIO_Input	JOY_UP [MT-008A_UP]
27	VSS	Power		
28	VDD	Power		
29	PA4	I/O	GPIO_EXTI4	MFX_WAKEUP [MFX_V2_WAKEUP]

Pin Number LQFP100	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
30	PA5 *	I/O	GPIO_Input	JOY_DOWN [MT-008A_DOWN]
31	PA6	I/O	LCD_SEG3	SEG23 [GH08172T_SEG23]
32	PA7	I/O	LCD_SEG4	SEG0 [GH08172T_SEG0]
33	PC4	I/O	LCD_SEG22	SEG22 [GH08172T_SEG22]
34	PC5	I/O	LCD_SEG23	SEG1 [GH08172T_SEG1]
35	PB0	I/O	LCD_SEG5	SEG21 [GH08172T_SEG21]
36	PB1	I/O	LCD_SEG6	SEG2 [GH08172T_SEG2]
37	PB2 *	I/O	GPIO_Output	LD_R [LED red]
38	PE7	I/O	SAI1_SD_B	AUDIO_DIN [MP34DT01_DOUT]
39	PE8 *	I/O	GPIO_Output	LD_G [LED_Green]
40	PE9 **	I/O	SAI1_FS_B	AUDIO_CLK [MP34DT01_CLK]
41	PE10	I/O	QUADSPI_CLK	QSPI_CLK [N25Q128A13EF840E_C]
42	PE11	I/O	QUADSPI_NCS	QSPI_CS [N25Q128A13EF840E_S#]
43	PE12	I/O	QUADSPI_BK1_IO0	QSPI_D0 [N25Q128A13EF840E_DQ0]
44	PE13	I/O	QUADSPI_BK1_IO1	QSPI_D1 [N25Q128A13EF840E_DQ1]
45	PE14	I/O	QUADSPI_BK1_IO2	QSPI_D2 [N25Q128A13EF840E_DQ2]
46	PE15	I/O	QUADSPI_BK1_IO3	QSPI_D3 [N25Q128A13EF840E_DQ3]
47	PB10	I/O	I2C2_SCL	MFX_I2C_SLC [MFX_V2_I2C_SCL]
48	PB11	I/O	I2C2_SDA	MFX_I2C_SDA [MFX_V2_I2C_SDA]
49	VSS	Power		
50	VDD	Power		
51	PB12	I/O	LCD_SEG12	SEG20 [GH08172T_SEG20]
52	PB13	I/O	LCD_SEG13	SEG3 [GH08172T_SEG3]
53	PB14	I/O	LCD_SEG14	SEG19 [GH08172T_SEG19]
54	PB15	I/O	LCD_SEG15	SEG4 [GH08172T_SEG4]
55	PD8	I/O	LCD_SEG28	SEG18 [GH08172T_SEG18]
56	PD9	I/O	LCD_SEG29	SEG5 [GH08172T_SEG5]

Pin Number LQFP100	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
57	PD10	I/O	LCD_SEG30	SEG17 [GH08172T_SEG17]
58	PD11	I/O	LCD_SEG31	SEG6 [GH08172T_SEG6]
59	PD12	I/O	LCD_SEG32	SEG16 [GH08172T_SEG16]
60	PD13	I/O	LCD_SEG33	SEG7 [GH08172T_SEG7]
61	PD14	I/O	LCD_SEG34	SEG15 [GH08172T_SEG15]
62	PD15	I/O	LCD_SEG35	SEG8 [GH08172T_SEG8]
63	PC6	I/O	LCD_SEG24	SEG14 [GH08172T_SEG14]
64	PC7	I/O	LCD_SEG25	SEG9 [GH08172T_SEG9]
65	PC8	I/O	LCD_SEG26	SEG13 [GH08172T_SEG13]
66	PC9 *	I/O	GPIO_Output	OTG_FS_PowerSwitchOn [STMPS2141STR_EN]
67	PA8	I/O	LCD_COM0	COM0 [GH08172T_COM0]
68	PA9	I/O	LCD_COM1	COM1 [GH08172T_COM1]
69	PA10	I/O	LCD_COM2	COM2 [GH08172T_COM2]
72	PA13 (JTMS-SWDIO)	I/O	SYS_JTMS-SWDIO	SWDIO
73	VDDUSB	Power		
74	VSS	Power		
75	VDD	Power		
76	PA14 (JTCK-SWCLK)	I/O	SYS_JTCK-SWCLK	SWCLK
77	PA15 (JTDI)	I/O	LCD_SEG17	SEG10 [GH08172T_SEG10]
78	PC10	I/O	GPIO_EXTI10	OTG_FS_OverCurrent [STMPS2141STR_FAULT]
79	PC11 *	I/O	GPIO_Output	OTG_FS_VBUS [EMIF02-USB03F2_Vbus]
81	PD0	I/O	GPIO_EXTI0	EXT_RST [SSM-104-L-DH_EXT_RST]
82	PD1	I/O	SPI2_SCK	MEMS_SCK [L3GD20_SCL/SPC]
83	PD2	I/O	GPIO_EXTI2	GYRO_INT1 [L3GD20_INT1]
84	PD3	I/O	SPI2_MISO	MEMS_MISO [L3GD20_SA0/SDO]
85	PD4	I/O	SPI2_MOSI	MEMS_MOSI [L3GD20_SDA/SDI/SDO]
86	PD5	I/O	USART2_TX	USART_TX
87	PD6	I/O	USART2_RX	USART_RX
88	PD7 *	I/O	GPIO_Output	GYRO_CS [L3GD20_CS_I2C/SPI]
89	PB3 (JTDO-TRACESWO) *	I/O	GPIO_Output	M3V3_REG-ON
90	PB4 (NJTRST)	I/O	LCD_SEG8	SEG11 [GH08172T_SEG11]
91	PB5	I/O	LCD_SEG9	SEG12 [GH08172T_SEG12]

Pin Number LQFP100	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
92	PB6	I/O	I2C1_SCL	I2C1_SCL [SSM-104-L-DH_SCL]
93	PB7	I/O	I2C1_SDA	I2C1_SDA [SSM-104-L-DH_SDA]
94	BOOT0	Boot		
95	PB8	I/O	GPIO_EXTI8	GYRO_INT2 [L3D20_DRDY/INT2]
96	PB9	I/O	LCD_COM3	COM3 [GH08172T_COM3]
97	PE0 *	I/O	GPIO_Output	XL_CS [LSM303CTR_CS_XL]
98	PE1	I/O	GPIO_EXTI1	XL_INT [LSM303CTR_INT_XL]
99	VSS	Power		
100	VDD	Power		

* The pin is affected with an I/O function

** The pin is affected with a peripheral function but no peripheral mode is activated

4. Clock Tree Configuration



5. Software Project

5.1. Project Settings

Name	Value
Project Name	stm32-freertos
Project Folder	D:\ew2024\stm32-freertos
Toolchain / IDE	STM32CubeIDE
Firmware Package Name and Version	STM32Cube FW_L4 V1.18.0
Application Structure	Advanced
Generate Under Root	Yes
Do not generate the main()	No
Minimum Heap Size	0x200
Minimum Stack Size	0x400

5.2. Code Generation Settings

Name	Value
STM32Cube MCU packages and embedded software	Copy only the necessary library files
Generate peripheral initialization as a pair of '.c/.h' files	No
Backup previously generated files when re-generating	No
Keep User Code when re-generating	Yes
Delete previously generated files when not re-generated	Yes
Set all free pins as analog (to optimize the power consumption)	No
Enable Full Assert	No

5.3. Advanced Settings - Generated Function Calls

Rank	Function Name	Peripheral Instance Name
1	SystemClock_Config	RCC
2	MX_GPIO_Init	GPIO
3	MX_I2C1_Init	I2C1
4	MX_I2C2_Init	I2C2
5	MX_LCD_Init	LCD
6	MX_QUADSPI_Init	QUADSPI
7	MX_SAI1_Init	SAI1
8	MX_SPI2_Init	SPI2
9	MX_USART2_UART_Init	USART2

1. Power Consumption Calculator report

1.1. Microcontroller Selection

Series	STM32L4
Line	STM32L4x6
MCU	STM32L476VGTx
Datasheet	DS10198_Rev4

1.2. Parameter Selection

Temperature	25
Vdd	3.0

1.3. Battery Selection

Battery	Li-SOCL2(A3400)
Capacity	3400.0 mAh
Self Discharge	0.08 %/month
Nominal Voltage	3.6 V
Max Cont Current	100.0 mA
Max Pulse Current	200.0 mA
Cells in series	1
Cells in parallel	1

1.4. Sequence

Step	Step1	Step2
Mode	RUN	STOP2
Vdd	3.0	3.0
Voltage Source	Battery	Battery
Range	Range1-High	NoRange
Fetch Type	SRAM2	n/a
CPU Frequency	80 MHz	0 Hz
Clock Configuration	HSE PLL	ALL CLOCKS OFF
Clock Source Frequency	4 MHz	0 Hz
Peripherals		
Additional Cons.	0 mA	0 mA
Average Current	10.7 mA	1.18 µA
Duration	0.1 ms	0.9 ms
DMIPS	100.0	0.0
Ta Max	103.65	105
Category	In DS Table	In DS Table

1.5. Results

Sequence Time	1 ms	Average Current	1.07 mA
Battery Life	4 months, 10 days, 3 hours	Average DMIPS	100.0 DMIPS

1.6. Chart


Consumption Profile by Step
Consumption (mA)
10.0
7.5
5.0
2.5
0.0
1:RUN
2:STOP2
0.0
0.1
0.2
0.3
0.4
0.5
0.6
0.7
0.8
0.9
1.0
Time (ms)
Idd by Step
Average Current

2. Peripherals and Middlewares Configuration

2.1. I2C1

I2C: I2C

2.1.1. Parameter Settings:

Timing configuration:

Custom Timing	Disabled
I2C Speed Mode	Standard Mode
I2C Speed Frequency (KHz)	100
Rise Time (ns)	0
Fall Time (ns)	0
Coefficient of Digital Filter	0
Analog Filter	Enabled
Timing	**0x20303E5D ***

Slave Features:

Clock No Stretch Mode	Disabled
General Call Address Detection	Disabled
Primary Address Length selection	7-bit
Dual Address Acknowledged	Disabled
Primary slave address	0

2.2. I2C2

I2C: I2C

2.2.1. Parameter Settings:

Timing configuration:

Custom Timing	Disabled
I2C Speed Mode	Standard Mode
I2C Speed Frequency (KHz)	100
Rise Time (ns)	0
Fall Time (ns)	0
Coefficient of Digital Filter	0
Analog Filter	Enabled
Timing	**0x20303E5D ***

Slave Features:

Clock No Stretch Mode	Disabled
General Call Address Detection	Disabled
Primary Address Length selection	7-bit

Dual Address Acknowledged	Disabled
Primary slave address	0

2.3. LCD

Mode: 1/4 Duty Cycle

mode: SEG3

mode: SEG4

mode: SEG5

mode: SEG6

mode: SEG8

mode: SEG9

mode: SEG12

mode: SEG13

mode: SEG14

mode: SEG15

mode: SEG17

mode: SEG22

mode: SEG23

mode: SEG24

mode: SEG25

mode: SEG26

mode: SEG28

mode: SEG29

mode: SEG30

mode: SEG31

mode: SEG32

mode: SEG33

mode: SEG34

mode: SEG35

2.3.1. Parameter Settings:

Clock Parameters:

Clock Prescaler	1
Clock Divider	16

Basic Parameters:

Duty Selection	1/4

Bias Selector	1/4
Multiplex mode	Disable

Advanced Parameters:

Voltage Source Selection	Internal
Contrast Control	2.60V
Dead Time Duration	No dead Time
High Drive	Disable
Pulse ON Duration	0 pulse
Blink Mode	Disabled
Blink Frequency	fLCD/8

2.4. QUADSPI

Single Bank: Quad SPI Line

2.4.1. Parameter Settings:

General Parameters:

Clock Prescaler	**1 ***
Fifo Threshold	**4 ***
Sample Shifting	**Sample Shifting Half Cycle ***
Flash Size	**24 ***
Chip Select High Time	1 Cycle
Clock Mode	Low

2.5. RCC

High Speed Clock (HSE): Crystal/Ceramic Resonator

Low Speed Clock (LSE) : Crystal/Ceramic Resonator

2.5.1. Parameter Settings:

System Parameters:

VDD voltage (V)	3.3
Instruction Cache	Enabled
Prefetch Buffer	Disabled
Data Cache	Enabled
Flash Latency(WS)	2 WS (3 CPU cycle)

RCC Parameters:

HSI Calibration Value	16
MSI Calibration Value	0

MSI Auto Calibration	Enabled
HSE Startup Timout Value (ms)	100
LSE Startup Timout Value (ms)	5000
LSE Drive Capability	LSE oscillator low drive capability

Power Parameters:

Power Regulator Voltage Scale	Power Regulator Voltage Scale 1

2.6. SAI1

Mode: Master with Master Clock Out

Mode: Synchronous Slave

2.6.1. Parameter Settings:

SAI A:

Synchronization Inputs	Asynchronous
Basic Parameters	
Protocol	Free
Audio Mode	Master Transmit
Frame Length	8 bits
Data Size	8 Bits
Slot Size	DataSize
Output Mode	Stereo
Companding Mode	No companding mode
SAI SD Line Output Mode	Driven
Frame Parameters	
First Bit	MSB First
Frame Synchro Active Level Length	1
Frame Synchro Definition	Start Frame
Frame Synchro Polarity	Active Low
Frame Synchro Offset	First Bit
Slot Parameters	
First Bit Offset	0
Number of Slots	1
Slot Active Final Value	0x00000000
Slot Active	Neither
Clock Parameters	
Master Clock Divider	Enabled
Audio Frequency	192 KHz
Real Audio Frequency	**66.964 KHz ***
Error between Selected	**-65.12 % ***
Clock Strobing	Falling Edge

Advanced Parameters	
Fifo Threshold	Empty
Output Drive	Disabled

SAI B:

Synchronization Inputs	Synchronous with other block of same SAI
Basic Parameters	
Protocol	Free
Audio Mode	Slave Receive
Frame Length (only Even Values)	8
Data Size	8 Bits
Slot Size	DataSize
Output Mode	Stereo
Companding Mode	No companding mode
SAI SD Line Output Mode	Driven
Frame Parameters	
First Bit	MSB First
Frame Synchro Active Level Length	1
Frame Synchro Definition	Start Frame
Frame Synchro Polarity	Active Low
Frame Synchro Offset	First Bit
Slot Parameters	
First Bit Offset	0
Number of Slots	1
Slot Active Final Value	0x00000000
Slot Active	Neither
Clock Parameters	
Real Audio Frequency	0
Error between Selected	0
Clock Strobing	Falling Edge
Advanced Parameters	
Fifo Threshold	Empty
Output Drive	Disabled

2.7. SPI2

Mode: Full-Duplex Master

2.7.1. Parameter Settings:

Basic Parameters:

Frame Format	Motorola
Data Size	4 Bits

First Bit	MSB First

Clock Parameters:

Prescaler (for Baud Rate)	2
Baud Rate	**24.0 MBits/s ***
Clock Polarity (CPOL)	Low
Clock Phase (CPHA)	1 Edge

Advanced Parameters:

CRC Calculation	Disabled
NSSP Mode	Enabled
NSS Signal Type	Software

2.8. SYS

Debug: Serial Wire

Timebase Source: TIM7

2.9. USART2

Mode: Asynchronous

2.9.1. Parameter Settings:

Basic Parameters:

Baud Rate	115200
Word Length	8 Bits (including Parity)
Parity	None
Stop Bits	1

Advanced Parameters:

Data Direction	Receive and Transmit
Over Sampling	16 Samples
Single Sample	Disable

Advanced Features:

Auto Baudrate	Disable
TX Pin Active Level Inversion	Disable
RX Pin Active Level Inversion	Disable
Data Inversion	Disable
TX and RX Pins Swapping	Disable
Overrun	Enable
DMA on RX Error	Enable
MSB First	Disable

2.10. FREERTOS

Interface: CMSIS_V2

2.10.1. Config parameters:

API:

FreeRTOS API	CMSIS v2

Versions:

FreeRTOS version	10.3.1
CMSIS-RTOS version	2.00

MPU/FPU:

ENABLE_MPU	Disabled
ENABLE_FPU	Disabled

Kernel settings:

USE_PREEMPTION	Enabled
CPU_CLOCK_HZ	SystemCoreClock
TICK_RATE_HZ	1000
MAX_PRIORITIES	56
MINIMAL_STACK_SIZE	128
MAX_TASK_NAME_LEN	16
USE_16_BIT_TICKS	Disabled
IDLE_SHOULD_YIELD	Enabled
USE_MUTEXES	Enabled
USE_RECURSIVE_MUTEXES	Enabled
USE_COUNTING_SEMAPHORES	Enabled
QUEUE_REGISTRY_SIZE	8
USE_APPLICATION_TASK_TAG	Disabled
ENABLE_BACKWARD_COMPATIBILITY	Enabled
USE_PORT_OPTIMISED_TASK_SELECTION	Disabled
USE_TICKLESS_IDLE	Disabled
USE_TASK_NOTIFICATIONS	Enabled
RECORD_STACK_HIGH_ADDRESS	Disabled

Memory management settings:

Memory Allocation	Dynamic / Static
TOTAL_HEAP_SIZE	3000
Memory Management scheme	heap_4

Hook function related definitions:

USE_IDLE_HOOK	Disabled
USE_TICK_HOOK	Disabled
USE_MALLOC_FAILED_HOOK	Disabled

USE_DAEMON_TASK_STARTUP_HOOK	Disabled
CHECK_FOR_STACK_OVERFLOW	Disabled

Run time and task stats gathering related definitions:

GENERATE_RUN_TIME_STATS	Disabled
USE_TRACE_FACILITY	Enabled
USE_STATS_FORMATTING_FUNCTIONS	Disabled

Co-routine related definitions:

USE_CO_ROUTINES	Disabled
MAX_CO_ROUTINE_PRIORITIES	2

Software timer definitions:

USE_TIMERS	Enabled
TIMER_TASK_PRIORITY	2
TIMER_QUEUE_LENGTH	10
TIMER_TASK_STACK_DEPTH	256

Interrupt nesting behaviour configuration:

LIBRARY_LOWEST_INTERRUPT_PRIORITY	15
LIBRARY_MAX_SYSCALL_INTERRUPT_PRIORITY	5

Added with 10.2.1 support:

MESSAGE_BUFFER_LENGTH_TYPE	size_t
USE_POSIX_ERRNO	Disabled

CMSIS-RTOS V2 flags:

USE_OS2_THREAD_SUSPEND_RESUME	Enabled
USE_OS2_THREAD_ENUMERATE	Enabled
USE_OS2_EVENTFLAGS_FROM_ISR	Enabled
USE_OS2_THREAD_FLAGS	Enabled
USE_OS2_TIMER	Enabled
USE_OS2_MUTEX	Enabled

2.10.2. Include parameters:

Include definitions:

vTaskPrioritySet	Enabled
uxTaskPriorityGet	Enabled
vTaskDelete	Enabled
vTaskCleanUpResources	Disabled
vTaskSuspend	Enabled
vTaskDelayUntil	Enabled
vTaskDelay	Enabled
xTaskGetSchedulerState	Enabled
xTaskResumeFromISR	Enabled
xQueueGetMutexHolder	Enabled

xSemaphoreGetMutexHolder	Disabled
pcTaskGetTaskName	Disabled
uxTaskGetStackHighWaterMark	Enabled
xTaskGetCurrentTaskHandle	Enabled
eTaskGetState	Enabled
xEventGroupSetBitFromISR	Disabled
xTimerPendFunctionCall	Enabled
xTaskAbortDelay	Disabled
xTaskGetHandle	Disabled
uxTaskGetStackHighWaterMark2	Disabled

2.10.3. Advanced settings:

Newlib settings (see parameter description first):

USE_NEWLIB_REENTRANT	**Enabled ***

Project settings (see parameter description first):

Use FW pack heap file	Enabled

*** User modified value**

3. System Configuration

3.1. GPIO configuration

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
I2C1	PB6	I2C1_SCL	Alternate Function Open Drain	**Pull-up ***	**Very High ***	I2C1_SCL [SSM-104-L-DH_SCL]
	PB7	I2C1_SDA	Alternate Function Open Drain	**Pull-up ***	**Very High ***	I2C1_SDA [SSM-104-L-DH_SDA]
I2C2	PB10	I2C2_SCL	Alternate Function Open Drain	**Pull-up ***	**Very High ***	MFX_I2C_SLC [MFX_V2_I2C_SCL]
	PB11	I2C2_SDA	Alternate Function Open Drain	**Pull-up ***	**Very High ***	MFX_I2C_SDA [MFX_V2_I2C_SDA]
LCD	PC3	LCD_VLCD	Alternate Function Push Pull	No pull-up and no pull-down	Low	VLCD
	PA6	LCD_SEG3	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG23 [GH08172T_SEG23]
	PA7	LCD_SEG4	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG0 [GH08172T_SEG0]
	PC4	LCD_SEG22	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG22 [GH08172T_SEG22]
	PC5	LCD_SEG23	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG1 [GH08172T_SEG1]
	PB0	LCD_SEG5	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG21 [GH08172T_SEG21]
	PB1	LCD_SEG6	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG2 [GH08172T_SEG2]
	PB12	LCD_SEG12	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG20 [GH08172T_SEG20]
	PB13	LCD_SEG13	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG3 [GH08172T_SEG3]
	PB14	LCD_SEG14	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG19 [GH08172T_SEG19]
	PB15	LCD_SEG15	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG4 [GH08172T_SEG4]
	PD8	LCD_SEG28	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG18 [GH08172T_SEG18]
	PD9	LCD_SEG29	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG5 [GH08172T_SEG5]
	PD10	LCD_SEG30	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG17 [GH08172T_SEG17]
	PD11	LCD_SEG31	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG6 [GH08172T_SEG6]
	PD12	LCD_SEG32	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG16 [GH08172T_SEG16]
	PD13	LCD_SEG33	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG7 [GH08172T_SEG7]
	PD14	LCD_SEG34	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG15 [GH08172T_SEG15]
	PD15	LCD_SEG35	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG8 [GH08172T_SEG8]
	PC6	LCD_SEG24	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG14

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
						[GH08172T_SEG14]
	PC7	LCD_SEG25	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG9 [GH08172T_SEG9]
	PC8	LCD_SEG26	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG13 [GH08172T_SEG13]
	PA8	LCD_COM0	Alternate Function Push Pull	No pull-up and no pull-down	Low	COM0 [GH08172T_COM0]
	PA9	LCD_COM1	Alternate Function Push Pull	No pull-up and no pull-down	Low	COM1 [GH08172T_COM1]
	PA10	LCD_COM2	Alternate Function Push Pull	No pull-up and no pull-down	Low	COM2 [GH08172T_COM2]
	PA15 (JTDI)	LCD_SEG17	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG10 [GH08172T_SEG10]
	PB4 (NJTRST)	LCD_SEG8	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG11 [GH08172T_SEG11]
	PB5	LCD_SEG9	Alternate Function Push Pull	No pull-up and no pull-down	Low	SEG12 [GH08172T_SEG12]
	PB9	LCD_COM3	Alternate Function Push Pull	No pull-up and no pull-down	Low	COM3 [GH08172T_COM3]
QUADSPI	PE10	QUADSPI_CLK	Alternate Function Push Pull	No pull-up and no pull-down	**Very High ***	QSPI_CLK [N25Q128A13EF840E_C]
	PE11	QUADSPI_NCS	Alternate Function Push Pull	No pull-up and no pull-down	**Very High ***	QSPI_CS [N25Q128A13EF840E_S#]
	PE12	QUADSPI_BK1_IO0	Alternate Function Push Pull	No pull-up and no pull-down	**Very High ***	QSPI_D0 [N25Q128A13EF840E_DQ0]
	PE13	QUADSPI_BK1_IO1	Alternate Function Push Pull	No pull-up and no pull-down	**Very High ***	QSPI_D1 [N25Q128A13EF840E_DQ1]
	PE14	QUADSPI_BK1_IO2	Alternate Function Push Pull	No pull-up and no pull-down	**Very High ***	QSPI_D2 [N25Q128A13EF840E_DQ2]
	PE15	QUADSPI_BK1_IO3	Alternate Function Push Pull	No pull-up and no pull-down	**Very High ***	QSPI_D3 [N25Q128A13EF840E_DQ3]
RCC	PC14-OSC32_IN (PC14)	RCC_OSC32_IN	n/a	n/a	n/a	
	PC15-OSC32_OUT (PC15)	RCC_OSC32_OUT	n/a	n/a	n/a	
	PH0-OSC_IN (PH0)	RCC_OSC_IN	n/a	n/a	n/a	
	PH1-OSC_OUT (PH1)	RCC_OSC_OUT	n/a	n/a	n/a	
SAI1	PE2	SAI1_MCLK_A	Alternate Function Push Pull	No pull-up and no pull-down	**Very High ***	SAI1_MCK [CS43L22_MCLK]

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
	PE4	SAI1_FS_A	Alternate Function Push Pull	No pull-up and no pull-down	**Very High ***	SAI1_FS [CS43L22_LRCK]
	PE5	SAI1_SCK_A	Alternate Function Push Pull	No pull-up and no pull-down	**Very High ***	SAI1_SCK [CS43L22_SCLK]
	PE6	SAI1_SD_A	Alternate Function Push Pull	No pull-up and no pull-down	**Very High ***	SAI1_SD [CS43L22_SDIN]
	PE7	SAI1_SD_B	Alternate Function Push Pull	No pull-up and no pull-down	**Very High ***	AUDIO_DIN [MP34DT01_DOUT]
SPI2	PD1	SPI2_SCK	Alternate Function Push Pull	No pull-up and no pull-down	**Very High ***	MEMS_SCK [L3GD20_SCL/SPC]
	PD3	SPI2_MISO	Alternate Function Push Pull	No pull-up and no pull-down	**Very High ***	MEMS_MISO [L3GD20_SA0/SDO]
	PD4	SPI2_MOSI	Alternate Function Push Pull	No pull-up and no pull-down	**Very High ***	MEMS_MOSI [L3GD20_SDA/SDI/SDO]
SYS	PA13 (JTMS-SWDIO)	SYS_JTMS-SWDIO	n/a	n/a	n/a	SWDIO
	PA14 (JTCK-SWCLK)	SYS_JTCK-SWCLK	n/a	n/a	n/a	SWCLK
USART2	PD5	USART2_TX	Alternate Function Push Pull	**Pull-up ***	**Very High ***	USART_TX
	PD6	USART2_RX	Alternate Function Push Pull	**Pull-up ***	**Very High ***	USART_RX
Single Mapped Signals	PE9	SAI1_FS_B	Alternate Function Push Pull	No pull-up and no pull-down	Low	AUDIO_CLK [MP34DT01_CLK]
GPIO	PE3	GPIO_Output	Output Push Pull	No pull-up and no pull-down	**High ***	AUDIO_RST [CS43L22_RESET]
	PC13	GPIO_EXTI13	**External Event Mode with Rising edge trigger detection ***	No pull-up and no pull-down	**n/a**	MFX_IRQ_OUT [MFX_V2_IRQOUT]
	PC0	GPIO_Input	Input mode	No pull-up and no pull-down	**n/a**	
	PC1	GPIO_Input	Input mode	No pull-up and no pull-down	**n/a**	MAG_INT [LSM303CTR_MAG_INT]
	PC2	GPIO_Input	Input mode	No pull-up and no pull-down	**n/a**	MAG_DRDY [LSM303CTR_DRDY_MAG]
	PA0	GPIO_Input	Input mode	**Pull-down ***	**n/a**	JOY_CENTER [MT-008A_CENTER]
	PA1	GPIO_Input	Input mode	**Pull-down ***	**n/a**	JOY_LEFT [MT-

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
						008A_LEFT]
	PA2	GPIO_Input	Input mode	**Pull-down ***	**n/a**	JOY_RIGHT [MT-008A_RIGHT]
	PA3	GPIO_Input	Input mode	**Pull-down ***	**n/a**	JOY_UP [MT-008A_UP]
	PA4	GPIO_EXTI4	**External Event Mode with Rising edge trigger detection ***	No pull-up and no pull-down	**n/a**	MFX_WAKEUP [MFX_V2_WAKEUP]
	PA5	GPIO_Input	Input mode	**Pull-down ***	**n/a**	JOY_DOWN [MT-008A_DOWN]
	PB2	GPIO_Output	Output Push Pull	**Pull-up ***	**Very High ***	LD_R [LED red]
	PE8	GPIO_Output	Output Push Pull	**Pull-up ***	**Very High ***	LD_G [LED_Green]
	PC9	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	OTG_FS_PowerSwitchOn [STMPS2141STR_EN]
	PC10	GPIO_EXTI10	**External Event Mode with Rising edge trigger detection ***	No pull-up and no pull-down	n/a	OTG_FS_OverCurrent [STMPS2141STR_FAULT]
	PC11	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	OTG_FS_VBUS [EMIF02-USB03F2_Vbus]
	PD0	GPIO_EXTI0	**External Event Mode with Rising edge trigger detection ***	No pull-up and no pull-down	n/a	EXT_RST [SSM-104-L-DH_EXT_RST]
	PD2	GPIO_EXTI2	**External Event Mode with Rising edge trigger detection ***	No pull-up and no pull-down	n/a	GYRO_INT1 [L3GD20_INT1]
	PD7	GPIO_Output	Output Push Pull	No pull-up and no pull-down	**Very High ***	GYRO_CS [L3GD20_CS_I2C/SPI]
	PB3 (JTDO-TRACESWO)	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	M3V3_REG-ON
	PB8	GPIO_EXTI8	**External Event Mode with Rising edge trigger detection ***	No pull-up and no pull-down	n/a	GYRO_INT2 [L3D20_DRDY/INT2]
	PE0	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	XL_CS [LSM303CTR_CS_XL]
	PE1	GPIO_EXTI1	**External Event Mode with Rising edge trigger detection ***	No pull-up and no pull-down	n/a	XL_INT [LSM303CTR_INT_XL]

3.2. DMA configuration

nothing configured in DMA service

3.3. NVIC configuration

3.3.1. NVIC

Interrupt Table	Enable	Preenmption Priority	SubPriority
Non maskable interrupt	true	0	0
Hard fault interrupt	true	0	0
Memory management fault	true	0	0
Prefetch fault, memory access fault	true	0	0
Undefined instruction or illegal state	true	0	0
System service call via SWI instruction	true	0	0
Debug monitor	true	0	0
Pendable request for system service	true	15	0
System tick timer	true	15	0
TIM7 global interrupt	true	15	0
PVD/PVM1/PVM2/PVM3/PVM4 interrupts through EXTI lines 16/35/36/37/38	unused		
Flash global interrupt	unused		
RCC global interrupt	unused		
I2C1 event interrupt	unused		
I2C1 error interrupt	unused		
I2C2 event interrupt	unused		
I2C2 error interrupt	unused		
SPI2 global interrupt	unused		
USART2 global interrupt	unused		
QUADSPI global interrupt	unused		
SAI1 global interrupt	unused		
LCD global interrupt	unused		
FPU global interrupt	unused		

3.3.2. NVIC Code generation

Enabled interrupt Table	Select for init sequence ordering	Generate IRQ handler	Call HAL handler
Non maskable interrupt	false	true	false
Hard fault interrupt	false	true	false
Memory management fault	false	true	false
Prefetch fault, memory access fault	false	true	false
Undefined instruction or illegal state	false	true	false
System service call via SWI instruction	false	false	false
Debug monitor	false	true	false
Pendable request for system service	false	false	false
System tick timer	false	false	true

Enabled interrupt Table	Select for init sequence ordering	Generate IRQ handler	Call HAL handler
TIM7 global interrupt	false	true	true

*** User modified value**

4. System Views

4.1. Category view

4.1.1. Current



5. Docs & Resources

Type	Link