

go-zkfp Development Guide

Go Binding for ZKFinger Reader SDK (libzkfp.dll)

github.com/elmyrockers/go-zkfp

Based on ZKTeco ZKFinger Reader SDK C API Version 2.0

Contents

1	Overview	3
2	Disclaimer	3
3	System Requirements	3
4	Installation and Deployment	3
5	Description of Go Interfaces	3
5.1	Design Conventions	3
5.2	Function Mapping	4
5.3	Type Definitions and Constants	4
6	Global Library Functions	4
6.1	Init	4
6.2	Terminate	5
6.3	GetDeviceCount	5
6.4	OpenDevice	5
6.5	DBInit	5
7	Device Methods	6
7.1	Device.Close	6
7.2	Device.ImageSize	6
7.3	Device.AcquireFingerprint	6
7.4	Device.AcquireFingerprintImage	6
7.5	Device.GetParameter	7
7.6	Device.SetParameter	7
8	Database/Algorithm Methods	7
8.1	DB.Free	7
8.2	DB.Merge	7
8.3	DB.Add	8
8.4	DB.Del	8
8.5	DB.Clear	8
8.6	DB.Count	8
8.7	DB.Identify	9
8.8	DB.Match	9
8.9	DB.ExtractFromImage	9
9	Usage Example	9

10	Appendixes	11
10.1	Appendix 1: List of Common Parameter Codes	11
10.2	Appendix 2: Descriptions of Returned Error Values	11

1 Overview

`go-zkfp` (github.com/elmyrockers/go-zkfp) is a Go binding for `libzkfp.dll`, the ZKFinger Reader SDK from ZKTeco. It allows Go programs to enumerate ZKTeco fingerprint readers, capture images and templates, and register, identify, and match fingerprints. This document describes the Go API, mapping one-to-one to the C functions of the ZKFinger Reader SDK (C API Version 2.0).

2 Disclaimer

`go-zkfp` is an independent open-source wrapper and does not include the ZKTeco SDK binaries. `libzkfp.dll` must be obtained by installing the official ZKFinger SDK from ZKTeco. Use of the SDK is subject to ZKTeco's licensing terms.

3 System Requirements

1. Operating system: Windows XP or a later version
2. Go 1.27.1 or later
3. ZKFinger SDK 5.x / ZKOnline SDK 5.x installed (providing `libzkfp.dll` and reader drivers)
4. The architecture of the Go program (`GOARCH=386` or `amd64`) must match the architecture of `libzkfp.dll`
5. `cgo` and a C compiler are **not** required: the library is loaded at runtime via `golang.org/x/sys/windows` (`windows.NewLazyDLL`) utilizing standard calling conventions required by the SDK.

4 Installation and Deployment

1. Install ZKFinger SDK 5.x / ZKOnline SDK 5.x.
2. Add the package to your module:

```
go get github.com/elmyrockers/go-zkfp
```
3. Make `libzkfp.dll` loadable by placing it next to your executable or in a directory on your system `PATH`.
4. Import the package in your code:

```
import "github.com/elmyrockers/go-zkfp"
```

5 Description of Go Interfaces

5.1 Design Conventions

- **Errors.** Functions return a standard Go `error` instead of raw integer return codes. Non-zero SDK results return values of type `zkfp.Error` (see Appendix 2), allowing direct comparison with `errors.Is` or `errors.As`.
- **Handles.** C `HANDLE` types are encapsulated into clean Go types: `*Device` (for reader instances) and `*DB` (for algorithm caches/databases).

- **Buffers.** C pointer-and-size parameter pairs are represented as native Go slices (`[]byte`). Output buffers are automatically allocated and trimmed to the actual data size returned by the SDK.
- **Cleanup.** `Close()` and `Free()` methods are implemented safely and idempotently.

5.2 Function Mapping

C function	Go function / method
ZKFPM_Init	zkfp.Init
ZKFPM_Terminate	zkfp.Terminate
ZKFPM_GetDeviceCount	zkfp.GetDeviceCount
ZKFPM_OpenDevice	zkfp.OpenDevice
ZKFPM_CloseDevice	(*Device).Close
ZKFPM_SetParameters	(*Device).SetParameter
ZKFPM_GetParameters	(*Device).GetParameter
ZKFPM_AcquireFingerprint	(*Device).AcquireFingerprint
ZKFPM_AcquireFingerprintImage	(*Device).AcquireFingerprintImage
ZKFPM_DBInit	zkfp.DBInit
ZKFPM_DBFree	(*DB).Free
ZKFPM_DBMerge	(*DB).Merge
ZKFPM_DBAdd	(*DB).Add
ZKFPM_DBDel	(*DB).Del
ZKFPM_DBClear	(*DB).Clear
ZKFPM_DBCount	(*DB).Count
ZKFPM_DBIdentify	(*DB).Identify
ZKFPM_DBMatch	(*DB).Match
ZKFPM_ExtractFromImage	(*DB).ExtractFromImage

5.3 Type Definitions and Constants

```
package zkfp

type Device struct { /* unexported */ }
type DB struct { /* unexported */ }
type Error int32

const (
    maxTemplateSize = 2048
    paramImageSize  = 106
)
```

6 Global Library Functions

6.1 Init

[Function] `func Init() error`

[Purpose] Initializes the ZKFinger SDK resources. Must be called once before invoking other methods.

[Parameter Description] None

[Return Value]

- `nil`: Succeeded (including code 1 indicating already initialized)
- `error`: Failed (See Appendix 2)

6.2 Terminate

[Function] `func Terminate() error`

[Purpose] Releases ZKFinger SDK resources.

[Parameter Description] None

[Return Value]

- `nil`: Succeeded
- `error`: Failed (See Appendix 2)

6.3 GetDeviceCount

[Function] `func GetDeviceCount() (int, error)`

[Purpose] Returns the number of connected fingerprint devices.

[Parameter Description] None

[Return Value]

- `int, nil`: Connected device count (≥ 0)
- `0, error`: Failed to query device count (See Appendix 2)

6.4 OpenDevice

[Function] `func OpenDevice(index int) (*Device, error)`

[Purpose] Opens a fingerprint device by its zero-based index.

[Parameter Description]

- `index`: Zero-based device index integer

[Return Value]

- `*Device, nil`: Opened device handle instance
- `nil, error`: Failed to open device (returns `ErrOpenDevice`)

6.5 DBInit

[Function] `func DBInit() (*DB, error)`

[Purpose] Creates an algorithm cache/database instance.

[Parameter Description] None

[Return Value]

- `*DB, nil`: Initialized algorithm database handle instance
- `nil, error`: Initialization failed

7 Device Methods

7.1 Device.Close

[Method] func (d *Device) Close() error

[Purpose] Closes the fingerprint device handle.

[Parameter Description] None

[Return Value]

- nil: Succeeded
- error: Failed to close device handle (See Appendix 2)

7.2 Device.ImageSize

[Method] func (d *Device) ImageSize() (int, error)

[Purpose] Queries the required fingerprint image buffer size from the device.

[Parameter Description] None

[Return Value]

- int, nil: Required image buffer size in bytes
- 0, error: Failed to retrieve size parameter (See Appendix 2)

7.3 Device.AcquireFingerprint

[Method] func (d *Device) AcquireFingerprint(image []byte) ([]byte, error)

[Purpose] Captures a fingerprint image and extracts its template.

[Parameter Description]

- image: Pre-allocated byte slice buffer to store the scanned fingerprint image (sized using ImageSize)

[Return Value]

- []byte, nil: Extracted fingerprint template slice trimmed to actual size
- nil, error: Capture or extraction failed (e.g., ErrCaptureFailed)

7.4 Device.AcquireFingerprintImage

[Method] func (d *Device) AcquireFingerprintImage(image []byte) error

[Purpose] Captures a raw fingerprint image without template extraction.

[Parameter Description]

- image: Pre-allocated byte slice buffer to receive the raw image data

[Return Value]

- nil: Succeeded
- error: Image capture failed (See Appendix 2)

7.5 Device.GetParameter

[Method] `func (d *Device) GetParameter(code int, size int) ([]byte, error)`

[Purpose] Reads a device parameter code value.

[Parameter Description]

- `code`: Integer parameter code (See Appendix 1)
- `size`: Allocation buffer size based on parameter type (e.g., 4 for integer, larger for strings)

[Return Value]

- `[]byte, nil`: Raw parameter bytes trimmed to size reported by SDK
- `nil, error`: Parameter query failed (See Appendix 2)

7.6 Device.SetParameter

[Method] `func (d *Device) SetParameter(code int, value []byte) error`

[Purpose] Writes or configures a device parameter code value.

[Parameter Description]

- `code`: Integer parameter code (See Appendix 1)
- `value`: Raw parameter data bytes (e.g., 4-byte little-endian integer)

[Return Value]

- `nil`: Succeeded
- `error`: Parameter update failed (See Appendix 2)

8 Database/Algorithm Methods

8.1 DB.Free

[Method] `func (db *DB) Free() error`

[Purpose] Releases the algorithm cache resources.

[Parameter Description] None

[Return Value]

- `nil`: Succeeded
- `error`: Failed to release cache (See Appendix 2)

8.2 DB.Merge

[Method] `func (db *DB) Merge(template1 []byte, template2 []byte, template3 []byte) ([]byte, error)`

[Purpose] Combines three fingerprint templates into a single registered template.

[Parameter Description]

- `template1`: First capture template byte slice
- `template2`: Second capture template byte slice
- `template3`: Third capture template byte slice

[Return Value]

- `[]byte, nil`: Merged template slice trimmed to final size
- `nil, error`: Merge operation failed (e.g., `ErrMergeFailed`)

8.3 DB.Add

[Method] func (db *DB) Add(fid uint, template []byte) error

[Purpose] Adds a registered fingerprint template to the algorithm cache with an associated ID.

[Parameter Description]

- **fid:** Unsigned integer fingerprint ID (> 0)
- **template:** Registered template byte slice

[Return Value]

- **nil:** Succeeded
- **error:** Failed to add template (See Appendix 2)

8.4 DB.Del

[Method] func (db *DB) Del(fid uint) error

[Purpose] Deletes a fingerprint template from the algorithm cache by its ID.

[Parameter Description]

- **fid:** Unsigned integer fingerprint ID to delete

[Return Value]

- **nil:** Succeeded
- **error:** Failed to delete template (See Appendix 2)

8.5 DB.Clear

[Method] func (db *DB) Clear() error

[Purpose] Removes all fingerprint templates from the algorithm cache.

[Parameter Description] None

[Return Value]

- **nil:** Succeeded
- **error:** Failed to clear cache (See Appendix 2)

8.6 DB.Count

[Method] func (db *DB) Count() (int, error)

[Purpose] Returns the total number of fingerprint templates stored in the algorithm cache.

[Parameter Description] None

[Return Value]

- **int, nil:** Template count integer
- **0, error:** Failed to fetch count (See Appendix 2)

8.7 DB.Identify

[Method] `func (db *DB) Identify(template []byte) (uint, uint, error)`

[Purpose] Performs a 1:N fingerprint comparison against all templates in the cache.

[Parameter Description]

- `template`: Query fingerprint template byte slice

[Return Value]

- `fid, score, nil`: Matched fingerprint ID and comparison score uint values
- `0, 0, error`: Identification failed or no match found (See Appendix 2)

8.8 DB.Match

[Method] `func (db *DB) Match(template1, template2 []byte) (int, error)`

[Purpose] Compares two fingerprint templates directly (1:1 matching).

[Parameter Description]

- `template1`: First fingerprint template byte slice
- `template2`: Second fingerprint template byte slice

[Return Value]

- `int, nil`: Comparison match score integer (≥ 0)
- `0, error`: Comparison calculation failed (See Appendix 2)

8.9 DB.ExtractFromImage

[Method] `func (db *DB) ExtractFromImage(path string, dpi uint) ([]byte, error)`

[Purpose] Extracts a fingerprint template from an image file (BMP or JPG format).

[Parameter Description]

- `path`: Full file system path string to the image file
- `dpi`: Image resolution DPI unsigned integer

[Return Value]

- `[]byte, nil`: Extracted template byte slice trimmed to actual size
- `nil, error`: Extraction failed or unsupported version (See Appendix 2)

9 Usage Example

```
package main

import (
    "fmt"
    "log"

    "github.com/elmyrockers/go-zkfp"
)

func main() {
```

```

// 1. Initialize the SDK
if err := zkfp.Init(); err != nil {
    log.Fatalf("Init failed: %v", err)
}
defer zkfp.Terminate()

// 2. Initialize the algorithm database/cache for matching & storage
db, err := zkfp.DBInit()
if err != nil {
    log.Fatalf("DBInit failed: %v", err)
}
defer db.Free()

// 3. Check for connected devices
count, err := zkfp.GetDeviceCount()
if err != nil || count == 0 {
    log.Fatalf("No device found: %v", err)
}

// 4. Open the first device
dev, err := zkfp.OpenDevice(0)
if err != nil {
    log.Fatalf("OpenDevice failed: %v", err)
}
defer dev.Close()

fmt.Println("Device opened and Algorithm DB initialized successfully
!")

// 5. Query required image buffer size and capture fingerprint
imgSizeBytes, err := dev.ImageSize()
if err != nil {
    log.Fatalf("Failed to get image size: %v", err)
}

imgBuf := make([]byte, imgSizeBytes)
fmt.Println("Please place your finger on the scanner...")

template, err := dev.AcquireFingerprint(imgBuf)
if err != nil {
    log.Fatalf("Fingerprint capture failed: %v", err)
}

// 6. Add the captured template to the algorithm database with ID 1
var fingerprintID uint = 1
if err := db.Add(fingerprintID, template); err != nil {
    log.Fatalf("Failed to add template to DB: %v", err)
}

totalCount, _ := db.Count()
fmt.Printf("Fingerprint successfully registered! Total records in DB
: %d\n", totalCount)
}

```

10 Appendixes

10.1 Appendix 1: List of Common Parameter Codes

Parameter Code	Property	Data Type	Description
1	Read-only	Int	Image width
2	Read-only	Int	Image height
3	Read-write (LIVEID20R only)	Int	Image DPI (750/1000 recommended for children)
106	Read-only	Int	Image data size (paramImageSize)
1015	Read-only	4-byte array	VID & PID bytes (former two indicate VID, latter two PID)
2002	Read-write (LIVEID20R only)	Int	Anti-fake function (1: enable; 0: disable)
2004	Read-only	Int	True if lower five bits are all 1's (value&31==31)
1101	Read-only	String	Vendor information
1102	Read-only	String	Product name
1103	Read-only	String	Device SN
101	Write-only	Int	1 indicates white light blinks; 0 indicates disabled
102	Write-only	Int	1 indicates green light blinks; 0 indicates disabled
103	Write-only	Int	1 indicates red light blinks; 0 indicates disabled
104	Write-only	Int	1 indicates buzzing started; 0 indicates disabled
10001	Write-only (ISO/ANSI only)	Int	0: ANSI378; 1: ISO 19794-2

10.2 Appendix 2: Descriptions of Returned Error Values

Code	Go Error Value	Description
-1	ErrInitLib	Failed to initialize the algorithm library
-2	ErrInitCapture	Failed to initialize the capture library
-3	ErrNoDevice	No device connected
-4	ErrNotSupported	Not supported by the interface
-5	ErrInvalidParam	Invalid parameter
-6	ErrOpenDevice	Failed to start the device
-7	ErrInvalidHandle	Invalid handle
-8	ErrCaptureFailed	Failed to capture the image
-9	ErrExtractFailed	Failed to extract the fingerprint template
-10	ErrAbort	Suspension operation
-11	ErrNoMemory	Insufficient memory
-12	ErrBusy	Device is busy capturing
-13	ErrAddFailed	Failed to add template to memory
-14	ErrDeleteFailed	Failed to delete template
-17	ErrOperationFailed	Operation failed (other error)
-18	ErrCaptureCancelled	Capture cancelled
-20	ErrMatchFailed	Fingerprint comparison failed
-22	ErrMergeFailed	Failed to combine registered templates
-23	ErrOpenFile	Opening the file failed
-24	ErrImageProcess	Image processing failed