Safebase - User stories

Name	Description	User flow	Acceptance criteria
US00 - Authentication and account management	As a user, I want to create an account and log in securely so that only authorized administrators can access SAFEBASE.	1. The user opens the login page. 2. They enter their email and password (or create an account). 3. SAFEBASE verifies the credentials. 4. On success, they are redirected to the homepage. 5. On failure, an error message is shown.	• A user can create an account with an email and a password. • The password is salted and hashed (bcrypt), never stored in clear text. • A registered user can log in and log out. • Protected pages are inaccessible without a valid session. • An error message is displayed if the credentials are incorrect.
US01 - Adding a database	As a user, I want to add a database connection so that SAFEBASE can access and back up my database.	1. They click Add a database. 2. They choose the database type: MySQL, PostgreSQL or MongoDB. 3. They enter the required information: database name, host, port, username, password. 4. They save the connection. 5. SAFEBASE tests the connection. 6. The database is added only if the connection is valid. 7. The database appears in the database list.	• The user opens the Homepage. • The user can choose between MySQL, PostgreSQL and MongoDB. • All required connection information must be entered. • SAFEBASE checks the database connection before saving it. • An error message is displayed if the connection fails. • The database is displayed in the list after a successful connection test. • The database password is not displayed to the user.
US02 - Schedule automatic backups	As a user, I want to schedule backups for a database so that it is backed up automatically without manual action.	1. They select the database where they want to schedule an automatic backup. 2. They fill in the information (time and date) for the automatic database backup. 3. SAFEBASE creates the corresponding cron schedule. 4. At the scheduled time, SAFEBASE starts the backup. 5. The backup is saved as a file, with the information of this backup.	• The user opens the Homepage. • The user can select one or more databases. • The user can define a backup frequency. • A cron schedule is created from the selected frequency. • A backup is automatically started at the scheduled time. • A backup record is created after the operation. • The backup record contains at least the date, database, file location and size. • A failed backup is reported to the user.

Name	Description	User flow	Acceptance criteria
US03 - View and manage backup versions	As a user, I want to view the different backup versions of a database so that I can choose the correct version when I need to restore it.	1. They select the database. 2. SAFEBASE displays all available backup versions; they can identify the date, size, status and other useful information. 3. They click on the clock icon to restore a specific backup version.	• The user opens the Homepage. • Backups are grouped or linked to their database. • Each backup has a unique record. • The user can see the backup date, size and status. • Different backup versions can be distinguished easily. • Failed backups are clearly identified.
US04 - Restore a database backup	As a user, I want to restore a specific backup version so that I can recover my data after a loss or error.	1. The user selects a database and one of its backup versions. 2. They click restore. 3. A confirmation dialog warns that current data will be replaced. 4. The user confirms. 5. SAFEBASE runs the restore and reports the result.	• The user can select a specific backup version to restore. • A confirmation is required before starting the restore (destructive action). • The restore uses the correct tool depending on the database type. • The user is informed of the outcome (success or failure). • A failed restore triggers an alert.
US05 - Remove a database connection	As a user, I want to remove a database connection so that I can clean up databases I no longer manage.	1. The user selects a database from the list. 2. They click delete. 3. A confirmation is requested. 4. The database is removed from the list.	• The user can delete a database from the list. • A confirmation is required before deletion. • The database no longer appears in the list after deletion. • The behaviour regarding its existing backups is defined (kept or deleted — to be decided).
US06 - View and manage alerts	As a user, I want to be alerted when a backup or restore fails so that I can react quickly to problems.	1. A backup or restore fails. 2. SAFEBASE creates an alert. 3. The user sees the alert in the interface. 4. They open it to see the details.	• A failed backup or restore automatically generates an alert. • Alerts are visible in the interface, with the concerned database and date. • The user can distinguish read from unread alerts. • Alert details help with troubleshooting.

Name	Description	User flow	Acceptance criteria
US07 - Alert on restore failure	As a user, I want to be alerted when the restoration of one of my databases fails so that I can react quickly and avoid discovering too late that my backups are unusable.	1. They select the database. 2. They click on the clock icon to restore a specific backup version. 3. The restoration fails. 4. SAFEBASE creates an alert linked to the backup concerned. 5. The alert appears in the interface with an "unread" indicator. 6. They open the alert, read its details and mark it as read.	• When a restoration fails, an alert of type restore_failed is created and linked to the backup concerned. • The alert shows the database name, the backup file name, the date and time of the failure, and the cause of the error when known (database unreachable, file not found, invalid credentials, etc.). • The alert appears in the interface at the user's next action, with an "unread" indicator. • The user can mark an alert as read, and the indicator disappears. • A user only sees alerts linked to their own databases. • Read alerts remain available in the history. • No e-mail or external notification in this version: alerts are only visible in the application.