

- (b) What is our prediction with $K = 1$? Why?
- (c) What is our prediction with $K = 3$? Why?
- (d) If the Bayes decision boundary in this problem is highly non-linear, then would we expect the *best* value for K to be large or small? Why?

Applied

8. This exercise relates to the **College** data set, which can be found in the file **College.csv**. It contains a number of variables for 777 different universities and colleges in the US. The variables are

- **Private** : Public/private indicator
- **Apps** : Number of applications received
- **Accept** : Number of applicants accepted
- **Enroll** : Number of new students enrolled
- **Top10perc** : New students from top 10 % of high school class
- **Top25perc** : New students from top 25 % of high school class
- **F.Undergrad** : Number of full-time undergraduates
- **P.Undergrad** : Number of part-time undergraduates
- **Outstate** : Out-of-state tuition
- **Room.Board** : Room and board costs
- **Books** : Estimated book costs
- **Personal** : Estimated personal spending
- **PhD** : Percent of faculty with Ph.D.'s
- **Terminal** : Percent of faculty with terminal degree
- **S.F.Ratio** : Student/faculty ratio
- **perc.alumni** : Percent of alumni who donate
- **Expend** : Instructional expenditure per student
- **Grad.Rate** : Graduation rate

Before reading the data into **R**, it can be viewed in Excel or a text editor.

- (a) Use the **read.csv()** function to read the data into **R**. Call the loaded data **college**. Make sure that you have the directory set to the correct location for the data.
- (b) Look at the data using the **fix()** function. You should notice that the first column is just the name of each university. We don't really want **R** to treat this as data. However, it may be handy to have these names for later. Try the following commands:

```
> rownames(college)=college[,1]
> fix(college)
```

You should see that there is now a `row.names` column with the name of each university recorded. This means that `R` has given each row a name corresponding to the appropriate university. `R` will not try to perform calculations on the row names. However, we still need to eliminate the first column in the data where the names are stored. Try

```
> college=college[,-1]
> fix(college)
```

Now you should see that the first data column is `Private`. Note that another column labeled `row.names` now appears before the `Private` column. However, this is not a data column but rather the name that `R` is giving to each row.

- (c)
 - i. Use the `summary()` function to produce a numerical summary of the variables in the data set.
 - ii. Use the `pairs()` function to produce a scatterplot matrix of the first ten columns or variables of the data. Recall that you can reference the first ten columns of a matrix `A` using `A[,1:10]`.
 - iii. Use the `plot()` function to produce side-by-side boxplots of `Outstate` versus `Private`.
 - iv. Create a new qualitative variable, called `Elite`, by *binning* the `Top10perc` variable. We are going to divide universities into two groups based on whether or not the proportion of students coming from the top 10% of their high school classes exceeds 50%.

```
> Elite=rep("No",nrow(college))
> Elite[college$Top10perc >50]="Yes"
> Elite=as.factor(Elite)
> college=data.frame(college,Elite)
```

Use the `summary()` function to see how many elite universities there are. Now use the `plot()` function to produce side-by-side boxplots of `Outstate` versus `Elite`.

- v. Use the `hist()` function to produce some histograms with differing numbers of bins for a few of the quantitative variables. You may find the command `par(mfrow=c(2,2))` useful: it will divide the print window into four regions so that four plots can be made simultaneously. Modifying the arguments to this function will divide the screen in other ways.
- vi. Continue exploring the data, and provide a brief summary of what you discover.