

1. Retrieve all customer\_id, first\_name, and last\_name columns from customer
  - a. `SELECT customer_id, first_name, last_name FROM customer;`
2. Retrieve first\_name, last\_name, and email from customer.
  - a. `SELECT first_name, last_name, email FROM customer;`
3. Retrieve all customers that last\_name starts with 'D';
  - a. `SELECT * FROM customers WHERE last_name LIKE 'D%';`
4. Retrieve customers sorted by create\_date descending.
  - a. `SELECT * FROM customer ORDER BY create_date DESC;`
5. Retrieve first 10 customers
  - a. `SELECT * FROM customer LIMIT 10;`
6. Retrieve the second 10 customers
  - a. `SELECT * FROM customer LIMIT 10 OFFSET 10;`
7. Retrieve customers whose email contains 'sakila'.
  - a. `SELECT * FROM customer WHERE email LIKE '%sakila%';`
8. Retrieve all films with rental\_rate that above 3.
  - a. `SELECT * FROM film WHERE rental_rate > 3;`
9. Retrieve films with rental\_duration between 3 AND 7.
  - a. `SELECT * FROM film WHERE rental_duration BETWEEN 3 AND 7;`
10. Retrieve films with rating 'PG' or 'G'.
  - a. `SELECT * FROM film WHERE rating IN ('PG','G');`
11. Retrieve films sorted by length descending.
  - a. `SELECT * FROM film ORDER BY length DESC;`
12. Retrieve first 20 film titles and rental rates.
  - a. `SELECT title, rental_rate FROM film LIMIT 20;`
13. Count total number of customers name it as 'customer\_no'.

- a. `SELECT COUNT(*) as customer_no FROM customer;`
- 14. Insert a new actor with first\_name = 'Kennedy' last\_name = 'Slick'.
  - a. `INSERT INTO actor (first_name,last_name) VALUES ('Kennedy', 'Slick');`
- 15. Update customer email of customer\_id = 4 to 'ezeey@email.com'.
  - a. `UPDATE customer SET email = 'ezeey@email.com' WHERE customer_id = 4;`
- 16. Increase rental rate of all films by 5%.
  - a. `UPDATE film SET rental_rate = rental_rate * 1.05;`
- 17. Retrieve films where length is less than 60 or rental\_rate > 4.
  - a. `SELECT * FROM film WHERE length < 60 OR rental_rate > 4;`
- 18. Retrieve customers where last\_name ends with 'son'.
  - a. `SELECT * FROM customer WHERE last_name LIKE '%son';`
- 19. Retrieve first 30 payments where amount > 5
  - a. `SELECT * FROM payment WHERE amount > 5 LIMIT 30;`
- 20. Retrieve payments made by customer\_id = 1.
  - a. `SELECT * FROM payment WHERE customer_id = 1;`
- 21. Retrieve payments handled by staff\_id = 2.
  - a. `SELECT * FROM payment WHERE staff_id = 2;`
- 22. Retrieve first 40 payments ordered by amount descending.
  - a. `SELECT * FROM payment ORDER BY amount DESC LIMIT 40;`
- 23. Retrieve payments ordered by payment\_date ascending.
  - a. `SELECT * FROM payment ORDER BY payment_date ASC;`
  - b. `SELECT * FROM payment ORDER BY payment_date; (DEFAULT ASC)`
- 24. Retrieve unique customer\_ids from payment.
  - a. `SELECT DISTINCT customer_id FROM payment;`

25. Count payments as 'pay\_count' per customer.
- SELECT customer\_id, COUNT(\*) AS pay\_count FROM payment GROUP BY customer\_id;
26. Display customer\_id, and full name in customer table. Sample display:  
"Customer # 1: John Doe"
- SELECT CONCAT('Customer # ', customer\_id, ': ', first\_name, ' ', last\_name)  
FROM customer;
27. Display: Last Name, First Name (Email) from customer table.
- SELECT CONCAT(last\_name, ' ', first\_name, ' (', email, ')') FROM customer;
28. Display lowercase full names.
- SELECT UPPER(CONCAT(first\_name, ' ', last\_name)) FROM customer;
29. Display 'Customer ID -> Store store\_id' as 'customer\_store'
- SELECT CONCAT(customer\_id, ' -> Store ', store\_id) AS customer\_store  
FROM customer;
30. Display: [payment\_id] -> amount pesos FROM payment table.
- SELECT CONCAT('[', payment\_id, '] -> ', amount, ' pesos') FROM payment;