

# Item: 85322-SU

# LFX/STL/75W/MV/50K LED STREET LIGHT SUNLITE

## General Characteristics

**Fixture Life Hours** 50000 Hours Bulb Integrated LED

Lumens Per Watt (LPW) 126.87 Life (based on 3hr/day) 45.7

Estimated Energy Cost \$9.03 per Year

Safety Rating ETL Listed - Wet Location

DLC

#### Fixture Characteristics

Collection High Output Street Light

Strip Shape **Number of Lights** 1 - Light Pole Mounting Use Location Outdoor

#### **Electrical Characteristics**

Watts 75 Volts 120-277 **Equivalent Watts** 250-400 LED Chip Manufacturer Philips 3030

Number of LEDs 96 0.92 **Power Factor** 

**Operating Temperature** -40° to 40° C

## **Light Characteristics**

**Brightness** 9515 Lumens

70 Color Accuracy (CRI)

Light Appearance Super White **Color Temperature** 5000K Beam Angle 100°-60°

#### **Product Dimensions**

Item Dimensions (in) (W) 11.71 (H) 3.29 (D) 16.59 Package Dimensions (in) (W) 17.00 (H) 5.50 (D) 13.40

#### **Product Data**

Item Number 85322-SU

Case Quantity

Barcode on SKU 653703853222 Brand SUNLITE

Description LFX/STL/75W/MV/50K

**DLC File Number** P0KB6CK9



# Sunlite LFX/STL/75W/MV/50K 75 Watt Integrated LED Lamp Super White

The Sunlite high output street lights are ideal for lighting large areas. They are typically found on walkways, ramps, roadways and bike paths. Their high luminous efficiency provides high visibility while using significantly less energy. These fixtures can be mounted onto a pole, junction box or trunnion mounting (sold separately). The photo cell sensor option (sold separately) can save money and energy by automatically turning off the light when daylight is detected.



