lob Name/Title:	Catalog Number
Contractor:	Notes:

# LED Outdoor Lighting

### 150W Parking Lot / Area Light

#### **Features**

- One piece die-cast aluminum housing with UV resistant polycarbonate optical lens, outstanding corrosion protection.
- Bronze powder coat finish (other colors MTO)
- Suitable for mounting heights up to 25' in area lighting applications
- 150W replacement for 400W HID fixtures\*
- Lumen output up to 21K lumens with efficacy up to 140lm/W
- 4 or 5 Inch round or square pole mounting, or direct wall mounting
- Options to mount motion sensor or photocell
- Includes both shorting cap and twist lock photocell

#### **Specs**

- Universal Input voltage 120VAC-277VAC +/- 10%, 60 Hz
- Amperage 1.25 @ 120V; 0.54 @ 277V
- Power factor >0.95; THD <15%
- -40°F to 113°F operating ambient temperature
- Life rating (L70) 50K hours
- CRI >70
- 5 year warranty

### **Applications**

 Square or round pole area or parking lot lights or direct wall mounting
















Mounting arm with hardware included, along with round pole adapter



Catalog Number	Product Code	UPC Code	Color Temp	Watts	Lumens	IES Type Distribution	DLC ID
F-ARL/150W/50K/P3-80 F-ARL/150W/50K/P5-80	74476 74477	751338019911 751338019928	5000K 5000K	150 150	20,000 21,000	III V	PC4GY36C Pending
Accessories WD-OSF	70590	Motion sensor					

Specifications are subject to change without prior notice.

<sup>\*</sup>Direct replacement for HID, dependent of fixture design, mounting height and illumination requirements.




lob Name/Title:	Catalog Number
Contractor	Notes:


# **LED Outdoor Lighting**


## 150W Parking Lot / Area Light


#### **EPA OF AREA LIGHT**





#### **Mounting Dimensions**













Weight 150W:16.47lb 200W:17.38lb





Contact Topaz Lighting about our lighting layout service Specifications are subject to change without prior notice.

