10/100/1000M Media Converters

Enhanced Function with Dip switch

LT-MC80G Series

Overview:

LT-MC80G enhanced function series, featuring with 1*Gigabit SFP port + 1* 10/100/1000M RJ45 port, are the 10/100/1000Mbps adaptive Gigabit Ethernet media converter which adopt switching technology to fulfill media conversion. They complies with IEEE802.3, IEEE802.3u, IEEE802.3z and IEEE802.3ab standards and provide media conversion between 10/100/1000Base-T and 1000Base-SX/LX interface. The key function of enhanced series are supporting LFP, network storm suppression, forcing the electrical port and fiber port on 100M， which can meet with the different application requirement.

Picture






Features

- 10/100/1000M media converter with SFP slot
- Complies with IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T, IEEE 802.3z 1000Base-SX
- Media conversion between 10/100/1000Base-T and 1000Base-SX
- Supporting auto-sensing full-duplex and half-duplex operation
- Supporting auto-sensation of MDI/MDI-X, facilitating system commissioning and installation
- Supporting watchdog function, which can restart the equipments automatically when it is Frozen
- Dip switch function: supporting LFP, network storm suppression, forcing the electrical port and fiber port on 100M
- Supporting 1M Large buffer
- Supporting Jumbo frame 10Kbytes
- Supporting Quality of Service (QoS) and ensuring the transmission of VoIP packets;
- Store-and-Forward mechanism
- Flexible transmission distance based on different SFP module.
- 4KV surge protection, ESD: Air-15kV, Contact-8kV protection

Technical specification

Port interface	
Fixed port	1*1000 Base-X SFP port + 1*10/100/1000 Base - T RJ45
Power interface	DC jack
Ethernet standard	IEEE802.3 10Base-T Ethernet, IEEE802.3u 100Base-TX Fast Ethernet, IEEE802.3ab 1000Base-T , IEEE802.3z 1000Base-SX Gigabit Ethernet

LED indicators	
PWR	Power supply indicator
FDX	Electrical port operation mode indicator
Link/Act	Link state indicator
Copper 100M Link	Electrical port speed rate indicator
Copper 1000M Link	Electrical port speed rate indicator
Fiber Link/Act	Fiber port link state indicator



Dip switch function	
1. LFP	2. Network storm suppression
3.Forcing fiber port on 100M	4. Forcing electrical port on 100M
Cable type & transmission distance	
Twisted-pair	0-100m（CAT5e,CAT6）
Fiber port	Depending on the SFP module
Electrical Specifications	

Input voltage	DC 5 V
Total Power consumption	full load≤1.6W
Layer 2 Switching	
Switching capacity	14G
Packet forwarding rate	10.416Mpps
MAC address table	8K
Buffer	1M
Forwarding delay	<5us
MDX/MIDX	Support
Jumbo Frame	Support 10Kbytes
Watchdog	Support
LFP	Support
Environment	
Operating temperature	-20℃~70℃
Storage temperature	-40℃~85℃
Relative humidity	5%~95%（non-condensing）
Thermal methods	Fan-less, natural heat dissipation
MTBF	100,000 hours
Protection & Certification	
Power surge protection	IEC 61000-4-5 Level 4（4KV）(8/20us)
Ethernet port surge protection	IEC 61000-4-5 Level 3（2KV）(10/700us)
ESD	IEC 61000-4-2 Level 4 (8K/15K)
Free fall	0.5m
Certification	CE, FCC, RoHs
Structure	
Dimension	93*71*27mm
Installation method	Desktop, wall-mount
Weight	Net weight 0.2KG

Order information

Model	Description
LT-MC80G	10/100/1000Base-T to 1000Base-F,1*Gigabit SFP port + 1*10/100/1000M RJ45 port, without SFP module, external power adaptor, enhanced function with Dip switch