16*10/100Base-TX Industrial Ethernet Switch

LT-IS6016F-16TX-AD



Features:

- 16*10/100Base-TX RJ45 ports(No.16 is the uplink port when the port isolation enabled)
- DC 9-58V, AC 15~40V input, redundant power supply with polarity reverse protection
- Dip switch function:

  1.Port isolation; 2. Flow control; 3. QoS; 4. Broadcast storm restrain
- Support 10K Bytes Jumbo frame
- Support 4KV surge protection and ESD: Air-15kV, Contact-8kV Protection
- IP40 fan-less and Din-rail hardware design
- Operation temperature: -40 ℃ ~+75℃

Overview

The SmartByte LT-IS6016F-16TX-AD is the unmanaged industrial grade Ethernet switch with 16-port 10/100Base-TX RJ45. It is featuring with port isolation, flow control, QoS (1-2 ports) and broadcast storm restrain function, which all can be configured by the Dip switch on the top panel.

LT-IS6016F-16TX-AD is also a high cost-effective easy-to-use device, which provides essential industrial Ethernet networking function, such as wide range power input DC 9-58V, AC 15~40V, redundant power design with polarity reverse protection, robust IP40 fan-less housing with Din-rail installation, wide operation temperature from -40° C to 75° C as well as high-level EMI/EMC capability and so on. It is the best choice for heavy industrial factory, transportation, oil & gas, chemical, IP Surveillance and processing automation area where environmental conditions exceed commercial product specifications


Technical specification

<table>
<tr><td>Model No.</td><td colspan="3">LT-IS6016F-16TX-AD</td></tr>
<tr><td rowspan="2">Interface</td><td>Fiber port</td><td colspan="2">Copper RJ45 ports</td></tr>
<tr><td>0</td><td colspan="2">16</td></tr>
<tr><td>Ethernet</td><td colspan="3">16*10/100Base-TX RJ45</td></tr>
<tr><td>Standard</td><td colspan="3">IEEE 802.3 10Base-T Ethernet
IEEE 802.3u Fast Ethernet
IEEE 802.3x Full-Duplex Flow Control
IEEE 802.3az Energy Efficient Ethernet</td></tr>
<tr><td>Dip Switch</td><td colspan="3">1. Port Isolation
2. Flow control
3. QoS(1-2 ports)
4. Broadcast storm restrain</td></tr>
<tr><td rowspan="8">LED Indicators</td><td rowspan="2">P(Power indicator) Green</td><td colspan="2">Off: the device is power off or failed</td></tr>
<tr><td colspan="2">On: the device power on is normal</td></tr>
<tr><td rowspan="2">S(System indicator) Red</td><td colspan="2">Off: the chip is normal</td></tr>
<tr><td colspan="2">On: the chip read/write is unnormal</td></tr>
<tr><td rowspan="4">1-16(Copper ports)</td><td>Green indicators</td><td>Yellow indicators</td></tr>
<tr><td>Off: ports link down</td><td>Off: port speed is 10M</td></tr>
<tr><td>On: ports link up</td><td rowspan="2">On: port speed is 100M</td></tr>
<tr><td>Blinking: data on TX/RX</td></tr>
<tr><td colspan="4">Power parameters</td></tr>
<tr><td>Input voltage</td><td colspan="3">DC 9-58V, AC 15~40V, redundant power input</td></tr>
</table>

Input current	0.5A Max
Total power consumption	Full loading ≤5W
Connector	Removable 6-pin terminal block
Reverse polarity protection	Support
Switching features	
Switching capacity	3.2G
Packet forwarding rate	4.76 Mpps
MAC address table	8K
VLAN	Support the transmission of the packets with VLAN tags ranging from 1 to 4096
Buffer	2Kbits
Forwarding delay	<100us
Jumbo Frame	Support 10Kbytes
MDI/MDIX	Support
Watchdog	Support
Network Topology	
Star topology	Support
Bus topology	Support
Tree Topology	Support
Mechanical structure	
Case protection	IP40
Installation method	Din-rail
Dimension(W*D*H) mm	54x158x115mm
Weight	1.3 kg
Operating environment	
Operating temperature	-40℃~+75℃
Storage/transportation temperature	-40℃~+85℃
Relative humidity	5%~95% （non-condensing）
Industrial Standard	Surge protection of power: IEC 61000-4-5 Level 3 (4KV/2KV） （8/20us）
	Surge protection of Ethernet ports: IEC 61000-4-5 Level 3 (4KV/2KV ） （10/700us）

	DIP: IEC 61000-4-11　Level 3（10V）
	ESD: IEC 61000-4-2　Level 4（8K/15K）
	Shock：IEC 60068-2-27
	Free fall：IEC 60068-2-32
	Vibration：IEC 60068-2-6
Certification	CCC/CE/FCC/RoHS/UKCA/Reach
MTBF	> 200,000 hours
Warranty	5 years

Structure diagram



Order information

Model	Description
LT-IS6016F-16TX-AD	16-port 10/100Base-TX RJ45 industrial Ethernet switch, DC 9-58V, AC 15~40V input, redundant dual power supply; Din-rail installation. Operation temperature: -40℃～+75℃