8*10/100/1000Base-T + 4*1G/2.5GBase-X SFP

L2+ Managed Industrial Boost PoE Switch

LT-IS6312GP-4GX8GT-D-BST



Features:

- 8*10/100/1000Base-T RJ45 PoE, 4*1G/2.5GBase-X SFP
- Redundant power 12-57V input with polarity reverse/over-current protection
- Complies with IEEE802.3af PoE and IEEE802.3at PoE+ standard.
- Automatically allocate PoE power according to the input voltage
- Support DI/DO/RS485 and USB one key configuration & upgrading
- Layer 3 features: Support IPv4/IPv6 static routing, DHCP server, DHCP relay
- Layer 2 features: VLAN/GVRP/QinQ/SPAN/RSPAN/STP, RSTP, MSTP/DHCP/Multicast/ACL

  QoS/LLDP/802.1X/AAA/Loop Detect/SFP DDM/IPV6 management/Dual Stack/ PoE management/sFlow/Web/SNMP/MQTT/Telnet/TFTP/Web upgrading
- Support G.8032 ERPS protocol, recovery time ≤20ms
- Support 6KV surge protection and ESD: Air-15kV, Contact-8kV Protection
- IP40 fan-less and Din-rail hardware design
- Operation temperature: -40 ℃ ~+75℃

Overview

The SmartByte LT-IS6312GP-4GX8GT-D-BST is the highly reliable managed industrial boost PoE switch with 8-port 10/100/1000-T PoE and 4-port 1000/2500Base-X fiber optical interfaces. It adopts DC 12-57V power boost technology to solve power source only 12-24V but require to support PoE, and no special power supplies needed. It transforms a limited 12-24V power source into a robust, standards-compliant PoE network, which can support IEEE802.3af, IEEE802.3at standard PoE protocol, the Max power consumption can reach 30W (PoE+) per port. It also supports ERPS redundant network and the self-recovery mechanism is less than 20ms on full load which allows you to scheme a reliable Ethernet network by building a redundant ring topology as your back-up solution. LT-IS6312GP-4GX8GT-D-BST supports DI/DO/RS485 and robust layer 2 management function.

LT-IS6312GP-4GX8GT-D-BST is the high cost-effective easy-to-use device, which provides essential industrial Ethernet networking function, including wide range power input 12-57VDC, redundant power design with polarity reverse protection, robust IP40 fan-less housing with Din-rail installation, wide operation temperature from -40°C to 75°C as well as high-level EMI/EMC capability. It is the best choice for mobile transportation & vehicle mounted systems, solar-powered & off-deployments and industrial environments with DC backplanes application scenarios

Technical specification

Model No.	LT-IS6312GP-4GX8GT-D-BST	
Interface	Fiber ports	Copper RJ45 ports
	4	8
Ethernet	8*10/100/1000Base-T RJ45 PoE 4*1000/2500Base-X SFP	
CPU	Marvell AC5 series 1.2GHz	
Size of RAM	512MB	
Size of Flash	512MB	
Switch chip model	Marvell AC5 series	
Management port	1*RJ45 Console port (115200,8,N,1)，1*USB 2.0	
Data & Alarm channel（Removable 8-pin terminal block)	Vout: VO + , VO -	5V output（0.2A MAX）
	1 channel RS485: A, B	**Serial server:** Supports Modbus protocol transparent transmission **Network Side:** Supports TCP protocol, supports client and server mode

		Serial Port Side: Supports RTU communication mode and serial port transmission parameter settings
	1 channel digital input: DI+， DI-	Status “1”: 12V-30V Status”0”: -30V~3V Max input current: 8 mA
	1 channel digital output	Normally open， Normally closed，Pulse 2A@30V DC，0.3A@125V AC
Standard	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Ethernet IEEE 802.3ab 1000Base-T Ethernet IEEE 802.3z 1000Base-X Ethernet IEEE802.3x Flow Control and Back Pressure IEEE 802.1D Spanning Tree Protocol IEEE 802.1w Rapid Spanning Tree Protocol IEEE 802.1Q VLAN ITU-T G.8032 ERPS IEEE 802.1X Port Authentication Network Control IEEE 802.1ab LLDP IEEE 802.3ad LACP IEEE802.3af PoE IEEE802.3at PoE+	
LED Indicators		
P1/P2 (Power indicator)	Off: the device is power off or failed	On: the device power on is normal
SYS (System status indicator)	Blinking: device initialization	On: device on normal operation
USB (USB status indicator) Green	Off: USB flash drive not insert or not detected by device	
	On: USB flash drive is detected by device	
	Blinking: the device is reading and writing the data from USB flash drive	
PB1/PB2 (PoE Max budget indicators)	**PB1 & PB2 Off:** No PoE budget output	**PB1 on:** PoE output budget 60W **PB2 on:** PoE output budget 120W **PB1 & PB2 on:** PoE output budget 240W
1-8 (Copper ports indicators) Green	Off: ports link down	
	On: ports link up	
	Blinking: data on TX/RX	
1-8 (PoE status indicators) Yellow	Off: PoE not working	
	On: PoE working	
9-12 (Fiber ports indicators)	Off: ports link down	

Green	On: ports link up
	Blinking: data on TX/RX
Power parameter	
Input voltage	12-57VDC redundant power input
Input current	5.8A Max
Power consumption	Full loading without PoE ≤13W PoE power budget: ≤240W@53-57VDC Power input ≤120W@24-52VDC Power input ≤60W@12-23VDC Power input ※ Automatically allocate PoE power according to the input voltage
Connector	Removable 2*2 pin terminal block
Reverse polarity protection	Support
Over-current protection	Support
Layer 2 switching	
Port aggregation	Support GE port aggregation
	Support 2.5GE aggregation
	Support static aggregation
	Support LACP dynamic aggregation
	Up to 64 aggregation groups and up to 8 ports per group
Port features	Support IEEE802.3x flow control
	Support interface counters
	Support port isolation
	Port mirroring (One-to-One, Many-to-One)
	Support loop detection (Port-based; VLAN-based)
	Support broadcast storm suppression (broadcast; unknown multicast; unknown unicast)
VLAN	IEEE802.1Q tagged VLAN
	Mac based VLAN
	IP based VLAN
	Protocol based VLAN
	Voice VLAN, specially divide VLAN for user voice data flow
	Private VLAN, divide a VLAN broadcast domain into multiple subdomains to

	form a double-layer VLAN structure
	VLAN range: 1-4094
	Support access mode/trunk mode/hybrid mode
Mac-address table management	Support static Mac-address management
	Support dynamic Mac-address Management
	Support filtering Mac-address
	Support MAC limit based on port and VLAN
	Support MAC flapping based on port and VLAN
	16K Mac-address table size
GVRP	Normal mode
	Fixed mode
	Forbidden mode
QinQ	Port-based QinQ
	VLAN-based QinQ
	VLAN mapping
	Flow-based QinQ
LLDP	Link Layer Discovery Protocol
	Med
SPAN	Number of Sessions: 7
	Many-to-one
RSPAN	Remote Switch Port Analyzer
MSTP	802.1D STP
	802.1W RSTP
	802.1S MSTP
	BPDU Guard
	Number of Single Ring Device Connections: 20
ERPS G.8032	Major ring
	Sub ring
	Recovery time ≤20ms
	Number of Single Ring Device Connections: No limit

QoS	QoS Class, Remarking
	Support SP, WRR Queue Scheduling
	Ingress Port-based Rate-limit
	Egress Port-based Rate-limit
	Egress port-queue shaper
	Policy-based QoS
	Port Queue Numbers: 8
DHCPv4 Snooping	DHCP snooping trust port
	DHCP snooping option-82
	DHCP snooping circuit-id and remote-id customized
L2 Multicast	
IGMP	IGMP v1, v2, v3
IGMP Snooping	Internet Group Management Protocol Snooping
	Fast Leave
	Multicast Table Size: 1K
PIM-SM	Protocol Independent Multicast-Sparse Mode
Security features	
ACL	IP Standard ACL IP Extended ACL MAC extend ACL IPv6 ACL Time Range ACL apply on VLAN ACL Entrys, include input and output
802.1x	Port access control Mac-address access control RADIUS server
Port-security	Port-security
IP source guard	IP Source Guard, Port-based IP/Mac Binding Access
ARP-check	Support ARP-check and ARP packet filtering for illegal users
DAI	Dynamic ARP Inspection
Anti-gateway ARP Spoofing	Prevent Gateway ARP Spoofing
Ddos	Ddos attack protection


Access control	Support Telnet/SSH/HTTP/HTTPS user access control
AAA	RADIUS authentication access switch
	TACACS authentication access switch
	Authorization
Reliability	
Loop Detect	Loop detect, based on port or VLAN
EFM	The Ethernet in the first mile, 802.3ah
Management & Maintenance functions	
Dual Stack	IPv4 and IPv6 Dual Stack Management
System Log Management	Syslog Level 7 to 0 Corresponding Debug/Info/Notice/Warning/ Err/ Critical/ Alert
	Support connecting up to 3 Servers
	For IPv4 and IPv6
User Management	Support password protection, support MD5/SHA256/SHA512 algorithm
	Local Management of User Privilege
	Remote authorization by RADIUS or TARCAS
	Enable privilege protection
	User password complexity requirements
	User login fail protection
	User Privilege Level 0 to 15
Login Service Management	Up to 8 users online simultaneously
	Access control based on IPv4 or IPv6 ACL
Firmware Management	Firmware upgraded by WEB
	Firmware upgraded by CLI
	Dual partition
Web Management	Web Management
	Support HTTP V1.1
	Support HTTPS
	For IPv4 and IPv6
CLI management	Console/Telnet command line management

Fault Detection	Ping/Traceroute, For IPv4 and IPv6
	Optical transceiver DDM
	One click fault information collection
	Cable detection
DNS	Domain Name System
NTP	Network Time Protocol, For IPv4 and IPv6
	Support domain name configuration
Configuration Import /Export	FTP/TFTP based remote configuration import and export
	USB flash drives based local configuration import and export
sFlow	Sampled flow
SNMP	Version SNMPV2C/V3
MQTT	Message Queuing Telemetry Transport
RMON	Support RMON (Remote Monitoring) alarm
PoE management	Support 802.3af/802.3at
	Support PD watchdog
	Support PoE priority management
	Support Max PoE power configuration for each port
	Support alarm threshold configuration
	Support reserved power configuration
	Support PoE schedule
	Support POE legacy mode
Dual partition management	Support dual partition switching
Application Protocol Functions	
Telnet server	Support telnet server for IPv4 and IPv6
Telnet client	Support telnet client for IPv4 and IPv6
SCP (Secure Copy Protocol)	SCP client/server for IPv4 and IPv6
SFTP	sftp client/server for IPv4 and IPv6
SSH server	Support login based on user password-SSH2, support IPv4, IPv6
	Support public key-based login
TACACS	Support TACACS (the terminal access controller accesses the control system)

TFTP	Support TFTP Client
Layer 3 features	
Static Route	Support VLAN interface and route port
	IPv4 static routing table entry configuration
	ARP dynamic learning and static configuration
	IPv6 static routing table entry configuration
	Neighbor discovery and static configuration
	Routing prefix table size 4k for IPv4, for IPv6 divide by 4
DHCPv4 Client	Dynamic host configuration protocol for IPv4
DHCPv6 Client	Dynamic host configuration protocol for IPv6
DHCPv4 Relay	DHCP Relay for IPv4
DHCPv4 Server	DHCP Server for IPv4
Switching features	
Switching capacity	36Gbps
Packet forwarding rate	53.5Mpps
MAC address table	16K
VLAN	4K
Buffer	12Mbit
Forwarding delay	<5us
Jumbo Frame	Support 10Kbytes
MDI/MDIX	Support
Watchdog	Support
Mechanical structure	
Case protection	IP40
Installation method	Din-rail
Dimension(W*D*H)mm	96*115*158mm
Weight	2.1 kg
Operating environment	
Operating temperature	-40℃~+75℃
Storage/transportation	-40℃~+85℃

temperature	
Relative humidity	Operation humidity: 10%-90%RH Storage humidity: 5%-95%RH
Industrial Standard	
EMS	Surge protection of power: IEC 61000-4-5　6KV/4KV（8/20us）
	Surge protection of Ethernet ports: IEC 61000-4-5　6KV/2KV（10/700us）
	RS：IEC 61000-4-3 80 MHz-1 GHz：10 V/m
	EFT：IEC 61000-4-4 4K/2K
	CS：IEC 61000-4-6 10V
	ESD：IEC 61000-4-2　Contact: 8K；Air: 15K
EMI	FCC Part 15B Class A
Shock	IEC 60068-2-27
Free fall	IEC 60068-2-32
Vibration	IEC 60068-2-6
Certification	CCC/CE/UKCA/RoHS/REACH/FCC
MTBF	> 200,000 hours
Warranty	5 years

Structure diagram



Order information

Model	Description
LT-IS6312GP-4GX8GT-D-BST	L2+ Managed industrial boost PoE switch with 8*10/100/1000Base-T RJ45 ports and 4*1G/2.5GBase-X SFP slots, supports DI/DO/RS485, complies with IEEE802.3af, IEEE802.3at standard, DC12-57V input, redundant dual power supply, Din-rail installation; Operation temperature: -40℃～+75℃