



Demystifying Time in Node.js


A Developer's Guide to the Unix Epoch and ISO 8601



Everything Starts with the `Date` Object

In JavaScript and Node.js, the `Date` object is the primary interface for working with dates and times. It provides a rich API for manipulation, but its internal representation is the key to mastering it.

This constructor creates an object representing the current date and time.




```
let now = new Date();
```

- getTime()
- getFullYear()
- toISOString()
- getDate()
- getHours()
- getMilliseconds()

Under the Hood, Every Date is Just a Number

The `Date` object masks a simple reality: computers represent a specific moment in time as a single, large integer. This number is known as a timestamp.

```
new Date('2024-02-20T17:03:42Z')
```



1708448622000

The Machine's Heartbeat: The Unix Epoch

This timestamp represents the number of milliseconds that have elapsed since midnight (00:00:00 UTC) on Thursday, January 1, 1970. This starting point is called the "Unix Epoch."

Date and Time (UTC)	Unix Epoch Milliseconds
1970-01-01 00:00:00	0
1970-01-01 00:00:01	1000
1983-04-30 11:00:00	420548400000
2020-11-21 03:05:00	1605927900000

Calculating the Epoch Value

The standard Unix Epoch counts seconds. JavaScript, however, uses milliseconds for higher precision. This is why its timestamp values are often larger.

A single day = **24** hours × **60** minutes × **60** seconds × **1000** milliseconds = **86,400,000**


```
// Get the timestamp for the second day of the epoch
let start_date = new Date("1970-01-02");

// In JavaScript, Date objects can be coerced to their
// millisecond value in arithmetic operations.
console.log(start_date * 1);
```

Output: 864000000

A Global Standard Requires a Global Anchor: UTC


The Unix Epoch is always calculated relative to Coordinated Universal Time (UTC). This ensures that the timestamp ``1605927900`` represents the exact same moment in time, whether you are in Tokyo, London, or New York. Local times are calculated by applying an offset to UTC.



The Challenge of Communicating Time

A timestamp is great for computers, but humans need to read dates. This creates ambiguity. Does "04/05/06" mean April 5th, May 4th, or something else entirely? Different regions have different conventions.

Region	Common Format
United States	Month / Day / Year
Most of Europe	Day / Month / Year
Some Asian Countries	Year / Month / Day



A Universal Language for Dates and Times: ISO 8601

ISO 8601 is an international standard created to provide an unambiguous and well-defined method of representing dates and times. It is designed to be easily readable by both humans and machines.

Key Principles

- Uses the Gregorian calendar system.
- Time is always presented in a 24-hour format (no AM/PM).
- Sorts chronologically when ordered alphabetically, from the most to the least significant unit (Year, then Month, then Day).



The Anatomy of an ISO 8601 String

The standard uses a consistent `YYYY-MM-DD` format for dates, which prevents ambiguity and allows for simple string-based sorting.

Example Date: `20 February 2024, 17:03:42`

2024 - 02 - 20 — 17:03:42

YYYY - MM - DD

hh : mm : ss

Key

Y = year

M = month

D = day

h = hour

m = minute

s = second

ISO 8601 Designators: Connecting Time and Zone

Special characters are used to combine date and time, and to specify the time zone context.

1. Combining Date and Time

2024-02-20T17:03:42

└ The `T` is a literal designator that separates the date portion from the time portion.

2. Specifying UTC (Zulu Time)

2024-02-20T17:03:42Z

└ A `Z` at the end signifies that the time is in UTC (zero offset).


3. Specifying a Time Zone Offset

2024-02-20T17:03:42+02:00

└ `+hh:mm` or `-hh:mm` specifies the offset from UTC.
This example is 2 hours ahead of UTC.

Two Representations, One Moment in Time

The Unix Epoch and the ISO 8601 string are simply two different ways to represent the exact same moment. The JavaScript `Date` object is the engine that allows you to seamlessly convert between the machine-friendly number and the human-readable string.



Practical Application in Node.js

Use the built-in methods of the `Date` object to effortlessly move between representations.

From Date to Timestamp/ISO String

```
const now = new Date();

// Get the Unix Epoch timestamp (milliseconds)
console.log(now.getTime());
// Output: 1708448622000 (example)

// Get the ISO 8601 string (in UTC)
console.log(now.toISOString());
// Output: "2024-02-20T17:03:42.000Z"
```

From Timestamp/ISO String to Date

```
const timestamp = 1708448622000;
const isoString = "2024-02-20T17:03:42.000Z";

// Create Date object from timestamp
const dateFromTs = new Date(timestamp);

// Create Date object from ISO string
const dateFromIso = new Date(isoString);
```


A Clear Model for Handling Time



The Machine's View: The Unix Epoch.

At its core, a computer sees time as a single number—the milliseconds since January 1, 1970 UTC.



The Universal Language: ISO 8601.

For communication between systems or with people, use the ``YYYY-MM-DDTHH:mm:ss.sssZ`` format to eliminate all ambiguity.



The Developer's Tool: The ``Date`` Object.

Use the ``Date`` object as your robust and reliable interface to convert between these two essential formats.